Runaway edges: a smoothness-penalty blind spot makes Kolmogorov–Arnold networks non-identifiable on correlated inputs

Anonymous authors
Paper under double-blind review

Abstract

Kolmogorov–Arnold networks (KANs) are promoted as interpretable because each edge carries a learned univariate function. We show that a widely used family of smoothness penalties leaves a blind spot that undermines this promise: second-difference and curvature penalties do not charge for affine components of an edge, and SiLU base weights are often unpenalised. When the inputs to a layer are correlated, affine components on different edges can cancel inside a unit, so training inflates the parameters along directions that neither the penalty nor the data can see; the loss has no reachable finite minimum and independent runs never agree. In a pre-registered synthetic study with a known teacher, correlated inputs gave 0 of 16 converged models (median squared-norm growth 32–66×), including under a recently proposed curvature penalty that also penalises the SiLU weight, while a small penalty on the affine null space gave 16 of 16 certified minima and exact recovery of the teacher's internals. On real electrolyte-conductivity data the same mechanism explains why no model converged, and polishing beyond early stopping under a weak null-space penalty degraded held-out accuracy (RMSE 0.142 → 1.03). Closing the blind spot restores certified minima but leaves several distinct minima, so convergence and identifiability are separate problems. We give practical recommendations for penalised KANs.

1 Introduction

KANs replace a network's fixed activations with learned univariate functions on every edge. Their appeal for science rests on reading those functions: an edge that looks like an exponential decay suggests a physical law. That reading presumes the edges are determined by the data. If different training runs produce different edges with equally good predictions, the edges describe the optimiser, not the system.

This paper identifies a concrete, common mechanism that breaks that presumption. It arises from the interaction of three ingredients that are each standard in practice:

1. **A smoothness penalty with an affine null space.** Second-difference (P-spline) penalties and curvature penalties ignore straight-line components of an edge; SiLU base terms are frequently unpenalised.
2. **Correlated inputs to a layer.** Physical descriptors often move together. Hidden units can also become correlated during training, exposing the next layer.
3. **Training toward convergence.** Early stopping hides the problem; longer optimisation exposes it.

Together they create directions along which edges grow into large, mutually cancelling affine shapes. The penalty does not see them, and on the training data their contributions cancel. The loss keeps decreasing slightly along these directions, so it has no reachable finite minimum. Seeds wander apart, no model certifies as converged, and on inputs off the training correlation pattern the cancellation fails.

Contributions.

- We describe the mechanism and show that it applies to any layer whose inputs are correlated, including the output layer (Section 3).
- In a pre-registered synthetic study, we show causally that a recently proposed curvature penalty does not prevent the runaway on correlated inputs, while a small additional penalty on the affine null space prevents it and restores exact recovery of a known solution (Section 4).
- On real electrolyte-conductivity data, we trace a complete failure to converge to this mechanism and document its effect on extrapolation (Section 5).
- We show that closing the blind spot yields certified, isolated minima but not uniqueness, and that structured alternatives trade accuracy for stability (Section 6).
- We give recommendations for penalised KANs (Section 7).

All experiments were pre-registered: predictions, thresholds and interpretation rules were committed before the code that tested them. Of 65 predictions in the real-data case study, 11 held, 22 failed and 32 were inconclusive; we report them as recorded.

2 Background and related work

KAN edges. A KAN layer maps inputs to outputs by summing learned univariate functions, one per edge. In the original formulation (Liu et al., 2025) each edge is a SiLU base term plus a B-spline expansion. FastKAN (Li, 2024) approximates the B-splines with Gaussian radial basis functions on fixed centres, which is the edge type used in our experiments:

$$\varphi(x) = \alpha\,\mathrm{SiLU}(x) + \sum_{k=1}^{K} c_k \exp\left(-\left(\frac{x-\mu_k}{h}\right)^2\right) \tag{1}$$

Smoothness penalties and their null spaces. P-spline penalties charge squared second differences of the coefficients (Eilers & Marx, 1996). Constant and linear coefficient patterns cost nothing: the penalty's null space is affine. In generalised additive models this is well understood, and Marra & Wood (2011) proposed an additional penalty on the null space (the "double penalty") for variable selection. Our fix is the same construction; what is new is its consequence inside a KAN, where edges are summed within units and passed through further layers.

Curvature penalties for KANs. Bagrow (2026) proposed per-edge curvature penalties for compositional smoothness, combining the second-difference penalty with a term $K_{\mathrm{silu}}\,\alpha^2$ on the SiLU weight, and noted that the penalty has affine functions as its null space by design. That work evaluated on independent, uniformly sampled inputs. Second-derivative penalties on spline coefficients also appear in other KAN variants, typically on the spline part only, leaving the SiLU base term free (Cang et al., 2024; see also the free-knots KAN of Zheng et al., 2025). We show that the affine null space becomes a runaway direction when inputs are correlated, and that penalising the SiLU weight alone does not close it.

Concurvity. In additive models, including neural additive models (Agarwal et al., 2021), correlated inputs let one input's shape function absorb another's, making shape functions non-identifiable; this is known as concurvity. Siems et al. (2023) proposed a regulariser penalising correlations between transformed features. The cross-edge cancellation we describe is concurvity inside a KAN unit. In an additive model with a penalised null space it shifts shape between functions; combined with an unpenalised affine null space in a KAN, it becomes unbounded growth.

Losses without a finite minimum. When a loss attains its infimum only at infinity, gradient descent drives the parameter norm to diverge, slowly, and optimisation can continue while held-out performance




Figure 1: Mechanism (computed illustration) for the edge type of Section 2 (8 Gaussian RBFs on $[-1, 1]$). **(a)** Edge function produced by a unit linear coefficient pattern and its best straight line; the shaded band is the central 80% of the range, where the maximum deviation is 2.0% of the function's range (12.9% over the full range). **(b)** Penalty as a function of a tilt t applied as $+t$ to edge 1 and $-t$ to edge 2: the second-difference penalty (P0) and P1 are exactly zero for every t; only P2's term μQ grows ($\lambda = 10^{-3}$, $\mu = 10^{-5}$). **(c)** RMS change in the unit's pre-activation per unit tilt: 0.0996 on correlated inputs ($\rho = 0.95$) against 0.4403 on independent inputs (4.42×).

worsens (Soudry et al., 2018). Our runaway is an instance of this behaviour created by a penalty's null space.

Parameter-space symmetries. Exact symmetries (unit permutations, sign flips) make parameters non-identifiable in tanh and RBF networks, and completeness results characterise them (Sussmann, 1992; Kůrková & Neruda, 1994). KANs add continuous symmetries such as affine reparametrisations of hidden units. The runaway is not an exact symmetry: it is an approximate one, a nearly flat but tilted direction, which is what prevents convergence.

3 Mechanism

Consider a unit that sums edges from two inputs, $s = \varphi_1(x_1) + \varphi_2(x_2)$, each edge as in Section 2, trained with a second-difference penalty on its RBF coefficients.

Step 1: a direction the penalty cannot see. Add a linear pattern $t\,\ell$ to the RBF coefficients of edge 1 and subtract it from edge 2, with ℓ_k proportional to the centre index. Linear coefficient patterns have zero second difference, so the penalty is unchanged for every t (Figure 1b). With Gaussian bumps on a regular grid, the pattern produces a nearly affine function: over the central 80% of the input range it deviates from a straight line by at most 2% of its range (Figure 1a), and by up to 13% near the grid edges. Edge 1 thus gains approximately $t\,a\,x_1$ and edge 2 loses $t\,a\,x_2$.

Step 2: a direction the data cannot see. The unit's pre-activation changes by approximately $t\,a\,(x_1 - x_2)$. If x_1 and x_2 are strongly correlated, $x_1 - x_2$ is small wherever the data lie, so predictions change little even for large t (Figure 1c). The direction is nearly free in both the penalty and the data.

Step 3: no finite minimum. "Nearly free" is not "free". Moving along it lets the model shed curvature into the free affine and SiLU components, so the loss decreases monotonically along the direction. Both terms contribute (post-hoc decomposition). In the synthetic runaway models the smoothness penalty fell to about a quarter of its early value and supplied a median 61% of the decrease, while training error fell only 5%. On real data, from early stopping to the capped state, the penalty fell 8–88× but supplied 17–36% of the decrease, the data term the rest. In both, the growth went into whatever the penalty left free: the linear part of the RBF coefficients grew 34–40× in the synthetic runaway cells, and the SiLU weights 85× where they were unpenalised. In 12 of 20 synthetic runaway models, training error fell while test error rose. The infimum lies at infinity: gradients stay small but non-zero, the parameter norm grows without bound, and no minimum can be certified. Different seeds drift along different such directions.

Step 4: any layer can be affected. The argument needs only correlated inputs to a layer. Hidden units can become correlated during training, and then the output layer can host the same runaway even when the raw inputs are independent. Correlated hidden units appear necessary for this but not sufficient: they also occur in models that converge once the null space is penalised. Section 4 shows both forms.

Consequences.

- **Non-identifiability:** edges differ across seeds by large affine components that leave predictions almost unchanged.
- **Non-convergence:** second-order optimisers stall; certification criteria fail.
- **Extrapolation risk:** off the training correlation pattern, $x_1 - x_2$ is no longer small, and the inflated components stop cancelling.

The fix. Penalise the null space directly. For each edge, let P_{null} project its RBF coefficients onto constant-plus-linear patterns in the centre index, and add

$$Q = \sum_e \|P_{\text{null}}\, c_e\|^2 \tag{2}$$

with a small weight μ, in addition to a penalty on the SiLU weight. This makes every affine component cost something, which turns the infinite descent into a finite minimum.

4 Controlled study

Design. A teacher KAN [4, 3, 1] with smooth, hand-specified edges (fitted by smoothness-penalised least squares) generates targets with Gaussian noise of 5% of the output spread; n = 2000 training rows. Inputs are $\mathcal{N}(0,1)/3$, clipped to the grid, either independent or correlated in pairs ($\rho = 0.95$ for x_1/x_2 and x_3/x_4). Students share the teacher's architecture and are trained under three penalty levels:

- **P0:** second-difference penalty on RBF coefficients ($\lambda = 10^{-3}$).
- **P1:** P0 plus $K_{\text{silu}}\,\alpha^2$ on each SiLU weight (Bagrow-style curvature penalty, $K_{\text{silu}} = 0.443$).
- **P2:** P1 plus μQ, the affine null-space penalty.

Each of the 6 cells has 8 seeds. Each student is trained with AdamW and early stopping, then polished with an exact-Hessian trust-region method and certified by a second-order criterion (gradient, curvature and Newton decrement). μ was calibrated before the experiment by a pre-registered rule: 10^{-6} failed the pilot (5.0× growth) and 10^{-5} passed (1.32×) and was frozen.

The teacher itself runs away. Polished under P0 and P1 on correlated inputs, the teacher's parameters grew 85× and 1069× without certifying, while its predictions stayed within half a noise standard deviation of the original. The runaway changes the parameters, not the function.

Medians over 8 seeds; growth is the squared parameter norm, polished over early-stopped.

Results.

- **The published-style penalty does not prevent the runaway.** Penalising the SiLU weight (P1) halved the growth on correlated inputs but left 0 of 8 models certified (Figure 2).
- **Closing the null space prevents it everywhere.** P2 gave 16 of 16 certified models with no growth, in both input conditions.

Table 1: Synthetic 2 × 3 study, per cell.

Cell	Norm growth	Certified	Unit match to reference
Independent, P0	12.5×	6/8	1.000
Independent, P1	7.9×	6/8	1.000
Independent, P2	1.09×	8/8	1.000
Correlated, P0	65.7×	0/8	0.774
Correlated, P1	32.1×	0/8	0.883
Correlated, P2	1.00×	8/8	1.000




Figure 2: Synthetic 2 × 3 study: $\|\theta\|^2$ over exact-Hessian trust-region polishing iterations (log scale), one line per seed, coloured certified (blue) or not certified (vermillion). Rows: independent and correlated inputs; columns: P0, P1, P2. Per panel, certified seeds and median growth (polished over early-stopped): independent P0: 6/8 certified, ×12.5; independent P1: 6/8 certified, ×7.9; independent P2: 8/8 certified, ×1.1; correlated P0: 0/8 certified, ×65.7; correlated P1: 0/8 certified, ×32.1; correlated P2: 8/8 certified, ×1.0.

- **Without the runaway, the internals are recoverable.** Every cell without a runaway matched the reference's units and edges exactly (1.000), with seed-to-seed differences around 10^{-4}.
- **Independent inputs are not fully safe.** Under P0 and P1, most independent seeds grew substantially (8–12×) but settled at certified minima; 4 of 16 (seeds 0 and 4 in each cell) never certified.

Where the runaway lives. A post-hoc anatomy of the parameter change shows that in the correlated cells almost all growth sits in the output layer: the layer-1 share of the change was 0.110 (P0) and 0.024 (P1) (Figure 3a). It went into the affine part of the output edges' RBF coefficients and, under P0, into their SiLU weights. Cancellation across the edges entering the output rose from about 1.9 to 3.1–3.2, and no hidden unit saturated. The two uncertified independent-P0 seeds put 99.4% of their change into the output layer. This is Step 4 of Section 3. Among independent-input models, those that ran away were exactly those whose hidden units had become correlated (largest pairwise correlation 0.70, against 0.05 for certified models; Figure 3b), while certified P2 models kept correlations up to 0.88 without running away (post-hoc).




Figure 3: Where the runaway lives. **(a)** Mean share of $\|\Delta\theta\|^2$ by parameter block. Real data, 107 epochs→capped: layer-1 affine RBF 0.30, layer-2 affine RBF 0.31, SiLU weights 0.37; capped→further trust-region polishing: 0.40, 0.19, 0.38; synthetic correlated P0: layer-2 affine RBF 0.39, SiLU weights 0.47; correlated P1: layer-2 affine RBF 0.89. The real-data split was evaluated post hoc from archived weights (Appendix C). **(b)** Largest absolute correlation between hidden-unit activations on the training rows, median: synthetic, certified 0.054 ($n = 28$); synthetic, not certified 0.935 ($n = 20$); real, capped 0.968 ($n = 6$); real, further polishing 0.983 ($n = 6$); SC-KAN-δ polished 0.818 ($n = 10$); KAN-δ polished 0.946 ($n = 10$). Blue: certified; vermillion: not certified or runaway.

Verdicts. Of six pre-registered predictions, one held (the certification pattern, X2) and five failed. The failures refine rather than contradict the mechanism. Independent cells exceeded the growth threshold, mostly through finite growth. Cancellation and extrapolation effects were weaker than predicted. Recoverability failed only because the runaway cells were more recoverable than predicted, not less. In this synthetic setting, polishing did not degrade extrapolation: most of the off-pattern error in correlated cells was present at early stopping.

5 Real-data case study: electrolyte conductivity

Task and model. The CALiSol-23 challenge (de Blasio et al., 2024) asks for the log conductivity of lithium-ion electrolytes; every test sample contains diethyl carbonate (DEC), which never appears in training. KAN-δ anchors each prediction on the measured conductivity of pure propylene carbonate (PC) and learns only the correction, $\log k = \log k_{\mathrm{PC}} + x_{\mathrm{co}}\, h(z)$, where h is a FastKAN-style network of shape [10, 6, 1]. Its inputs are physical descriptors of the solvents (dielectric constant, log viscosity, molar mass), temperature, molality and a salt embedding. A second-difference penalty acts on the RBF coefficients, and the SiLU weights are unpenalised. Early-stopped after 107 AdamW epochs, it reached RMSE 0.142 on a held-out co-solvent.

The inputs are correlated and few-valued. The three co-solvent descriptors take only 30 distinct combinations in training, and dielectric constant and log viscosity correlate at r = 0.966.

Nothing ever converged.

- Of 190 pairs of polished independent seeds, none computed the same function.
- After 20,000 float64 L-BFGS iterations (the "capped" state used below), 0 of 26 models converged; exact-Hessian trust-region methods also failed on every seed.
- Students trained on a frozen teacher matched its predictions (correlation 0.9988) but not its hidden units (0.66).

Table 2: Dose-response in μ on real data (seeds).

μ	Seeds at a numerical minimum	Negative curvature (seeds)	Norm growth (seeds)	Training fit vs runaway
10^{-6}	0 of 6	up to 9 eigenvalues	21–31×	-3% to +13%
10^{-5}	4 of 6	up to 4 eigenvalues	9–43×	12–22% worse
10^{-4}	6 of 6	none	1.6–16×	15–39% worse

The anatomy matches Section 3.

- From early stopping to the capped state, the squared parameter norm grew 150–1550× while the smoothness penalty fell 8–88×.
- At least 99.9% of the coefficient change during exact-Newton polishing lay in the penalty's affine null space, in 9 of 9 models.
- Cancellation within an edge (SiLU against RBF) stayed small, 1.13–1.33. Cancellation across the edges entering a unit rose from 1.7–2.9 to 4–10, consistent with the correlated descriptors.
- The runaway spread across both layers: 30–40% of the parameter change went into layer-1 affine RBF coefficients, 37–38% into SiLU weights and 19–31% into layer-2 affine coefficients (post-hoc), and 12–39% of hidden units saturated. In the synthetic runaway the output layer dominated.

Extrapolation suffered. Polishing beyond early stopping, under a weak null-space penalty, raised the held-out RMSE from 0.142 to 1.03. The cancelling components appear to stop cancelling on the unseen co-solvent, whose descriptors sit off the training correlation pattern. This degradation was much stronger than in the synthetic study, where correlation itself caused most of the off-pattern error; the real model was larger, its norms grew further, and the test solvent lay at the edge of the descriptor range.

6 Closing the blind spot, and what remains

Dose-response on real data. Adding μQ (with the SiLU weights included in Q) and polishing from the early-stopped weights:

Under a second-order certificate, all six seeds at $\mu = 10^{-4}$ were certified (Figure 4). (The originally preregistered criterion, which required 10 stationary iterations, proved unreachable because the optimiser stops a few iterations after reaching a minimum; the certificate was defined afterwards and is reported alongside the original verdict.) Saturation fell to at most 0.5% and cross-edge cancellation to 2.2–2.9.

A known solution becomes recoverable. Under the regularised loss, the original teacher is no longer a minimum. Optimising it under the same loss gives a "regularised teacher" computing nearly the same function (correlation 0.9992). Students match its units at 0.87–0.90 and its edges at 0.97–0.98, against 0.68–0.72 and 0.84–0.91 for the original teacher. This comparison was defined after the results and is exploratory.

The penalty acts partly as gauge fixing. At the certified minima, the layer-2 constant shift, an essentially exact symmetry, owes 96% of its curvature to μQ: the regulariser selects one representative. The layer-1 constant shift (46%) and unit rescaling (24%) are only approximate symmetries in this architecture, because Gaussian bumps cannot represent constants exactly and tanh breaks rescaling.

Convergence is not uniqueness. Independent seeds at certified minima still disagreed: their median prediction difference fell by only 26% (Figure 5b). With the runaway removed, the loss has several distinct isolated minima.

Extrapolation. On the held-out co-solvent, RMSE was 0.142 for the early-stopped model, 1.026 after polishing at $\mu = 10^{-6}$ and 0.33 at $\mu = 10^{-4}$. Bounding the runaway recovers most of the damage, but early stopping remains the most accurate choice.




Figure 4: Real-data dose-response in the null-space weight μ (6 KAN-δ seeds; $\mu = 0$: polished without a null-space penalty). **(a)** Seeds at a numerical minimum (all of them certified): $\mu = 0$, 0 of 6; 10^{-6}, 0 of 6; 10^{-5}, 4 of 6; 10^{-4}, 6 of 6. **(b)** $\|\theta\|^2$ relative to the 107-epoch state, median (range): $\mu = 0$, 690 (170–4146); 10^{-6}, 29 (21–31); 10^{-5}, 14 (9–43); 10^{-4}, 7 (2–16). **(c)** Training data term relative to the runaway, median: 10^{-6}, 1.092; 10^{-5}, 1.146; 10^{-4}, 1.269. **(d)** Fold A RMSE: early-stopped 0.142 (dashed line); polished 5-seed ensemble 1.026 at $\mu = 10^{-6}$ and 0.334 at $\mu = 10^{-4}$; grey points are single seeds.

Table 3: Structured alternatives against the early-stopped baseline.

Model	Idea	LOCO RMSE	Converged	Seed agreement
Baseline KAN-δ	As above	0.255	0/10	0.112
Shared-curve KAN	One curve per input, mixed by penalised weights	0.292	10/10	0.187 early; 0.085 polished
Two-anchor excess model	Pure-solvent offset plus $x(1-x)$ mixing term	0.283	not tested	not tested

Structured alternatives. We tested two architectures designed to remove runaway routes by construction, against the early-stopped baseline, with leave-one-co-solvent-out (LOCO) validation:

Seed agreement is the median prediction difference between seeds (lower is better). The shared-curve model converged every time, ending with no near-flat directions where the baseline had a median of 106 (range 86–116, at non-stationary points; Figure 5a), and it was less accurate. At the early-stopped state its seeds agreed less than the baseline's (the pre-registered comparison); after polishing to certified minima their median disagreement fell to 0.085, with some seed pairs reaching the same minimum (post-hoc). The excess model's "pure co-solvent offset" tracked viscosity rather than dielectric constant (rank correlation −0.85, post hoc), reflecting that no training row contains a pure co-solvent.

7 Recommendations for practitioners

1. **Penalise the affine null space and the SiLU weights.** If a KAN uses a second-difference or curvature penalty, add a small penalty on the constant-plus-linear component of each edge's




Figure 5: Convergence is not uniqueness. **(a)** Near-null Hessian eigenvalues ($|\lambda| < 10^{-8}\lambda_{\max}$) at the end of polishing: KAN-δ baseline on fold A, median 106 (range 86–116); null-space penalty $\mu = 10^{-4}$ on all rows, median 1 (range 0–3); SC-KAN-δ on fold A, 0 in all 10 models. **The baseline counts are taken at non-stationary points**: none of the 10 baseline models was certified, and all stopped at the 500-iteration cap. **(b)** Seed disagreement d_{AB} (median, interquartile range): KAN-δ fold A early 0.112; KAN-δ fold A polished* 0.077; KAN-δ all rows capped 0.104; $\mu = 10^{-4}$ all rows certified 0.077; SC-KAN-δ fold A early 0.187; SC-KAN-δ fold A polished* 0.085. Groups are evaluated on different row sets (fold A training rows or all rows), so values are not strictly comparable across row sets. Groups marked * (polished fold A) are not in any committed result: they were evaluated post hoc from the archived polished weights (SHA-verified; predictions on the 1434 fold A training rows), without any re-optimisation.

coefficients and on each SiLU weight, in every layer. Calibrate its weight so it barely moves a known smooth solution.

2. **Check input correlations, including between hidden units.** Strongly correlated or few-valued inputs make the first layer vulnerable; any hidden layer can expose the next one.
3. **Monitor parameter norms, not only the loss.** Steady norm growth with a slowly falling loss and stubborn gradients is the signature of the runaway. Certify convergence with a second-order criterion rather than assuming it.
4. **Do not read edges from unconverged models.** Compare edges across seeds only after removing exact gauge freedoms, and only for models that reached certified minima.
5. **Treat seed disagreement as information.** Even at certified minima, distinct solutions can remain. Disagreement then signals that the data do not determine the function, not merely that training was unfinished.
6. **Validate on genuinely new conditions.** A held-out fold from the training distribution can understate extrapolation error severalfold; leave-one-group-out validation is closer to the use case.
7. **Keep early stopping as a baseline.** In our real-data case it gave the best held-out accuracy of every variant tested.

8 Limitations and research process

Scope.

- One real dataset and one synthetic teacher; small networks ([4, 3, 1] and [10, 6, 1]).
- One edge type: Gaussian RBFs on fixed centres with a SiLU base. The argument applies to B-spline KANs with second-difference or curvature penalties, but we did not test them directly.

- Our P1 keeps the second-difference penalty on RBF coefficients and adds Bagrow's SiLU term; it is Bagrow-style, not a replication of his RBF curvature form.
- The null-space weight used in the shared-curve model was carried over from the synthetic calibration, not re-calibrated.

Post-hoc elements. The second-order certificate, the regularised-teacher comparison, the gauge-curvature analysis and both anatomy studies were defined after seeing results. We report them as exploratory and never in place of pre-registered verdicts.

Extrapolation. The strong degradation from polishing appeared on real data but not in the synthetic study, so we do not claim it as a general law.

Process. Each study committed its predictions, thresholds and interpretation rules before its code existed; any later change was dated and recorded as an amendment, and every verdict is linked to the commit that produced it. Several predictions failed or proved untestable as specified; following them up, rather than reinterpreting them, is what led to the mechanism reported here. Experiments were run with an AI coding agent working under this protocol, with a rule that committed files take precedence over any number stated in a prompt.

References

Rishabh Agarwal, Levi Melnick, Nicholas Frosst, Xuezhou Zhang, Ben Lengerich, Rich Caruana, and Geoffrey E. Hinton. Neural additive models: Interpretable machine learning with neural nets. In *Advances in Neural Information Processing Systems 34 (NeurIPS 2021)*, 2021. URL `https://proceedings.neurips.cc/paper/2021/hash/251bd0442dfcc53b5a761e050f8022b8-Abstract.html`.

James Bagrow. KANs need curvature: penalties for compositional smoothness. arXiv:2605.02190, 2026.

Yueyang Cang, Yu hang Liu, and Li Shi. Can KAN work? Exploring the potential of Kolmogorov–Arnold networks in computer vision. arXiv:2411.06727, 2024.

Paolo de Blasio, Jonas Elsborg, Tejs Vegge, Eibar Flores, and Arghya Bhowmik. CALiSol-23: Experimental electrolyte conductivity data for various Li-salts and solvent combinations. *Scientific Data*, 11:750, 2024. doi: 10.1038/s41597-024-03575-8.

Paul H. C. Eilers and Brian D. Marx. Flexible smoothing with B-splines and penalties. *Statistical Science*, 11(2):89–121, 1996. doi: 10.1214/ss/1038425655.

Věra Kůrková and Roman Neruda. Uniqueness of functional representations by Gaussian basis function networks. In *ICANN '94: Proceedings of the International Conference on Artificial Neural Networks*, pp. 471–474. Springer London, 1994. doi: 10.1007/978-1-4471-2097-1_111.

Ziyao Li. Kolmogorov–Arnold networks are radial basis function networks. arXiv:2405.06721, 2024.

Ziming Liu, Yixuan Wang, Sachin Vaidya, Fabian Ruehle, James Halverson, Marin Soljačić, Thomas Y. Hou, and Max Tegmark. KAN: Kolmogorov–Arnold networks. In *International Conference on Learning Representations (ICLR)*, 2025. URL `https://openreview.net/forum?id=Ozo7qJ5vZi`.

Giampiero Marra and Simon N. Wood. Practical variable selection for generalized additive models. *Computational Statistics & Data Analysis*, 55(7):2372–2387, 2011. doi: 10.1016/j.csda.2011.02.004.

Julien Siems, Konstantin Ditschuneit, Winfried Ripken, Alma Lindborg, Maximilian Schambach, Johannes Otterbach, and Martin Genzel. Curve your enthusiasm: Concurvity regularization in differentiable generalized additive models. In *Advances in Neural Information Processing Systems 36 (NeurIPS 2023)*, 2023.

Daniel Soudry, Elad Hoffer, Mor Shpigel Nacson, Suriya Gunasekar, and Nathan Srebro. The implicit bias of gradient descent on separable data. *Journal of Machine Learning Research*, 19(70):1–57, 2018. URL `https://jmlr.org/papers/v19/18-188.html`.

Héctor J. Sussmann. Uniqueness of the weights for minimal feedforward nets with a given input-output map. *Neural Networks*, 5(4):589–593, 1992. doi: 10.1016/S0893-6080(05)80037-1.

Liangwewi Nathan Zheng, Wei Emma Zhang, Lin Yue, Miao Xu, Olaf Maennel, and Weitong Chen. Free-knots Kolmogorov–Arnold network: On the analysis of spline knots and advancing stability. arXiv:2501.09283, 2025.

A All pre-registered predictions

Generated by `F-01` from the committed verdict sections; the cell text is the committed wording. Commits are given as pre-registration → results (in the anonymous version, as neutral labels S-NN). Thresholds are part of each prediction's wording.

A.1 Synthetic study (`F-02`)

ID	Prediction (threshold)	Result	Verdict	Commits
X1	runaway (≥ 10) in correlated P0 and P1; ≤ 3 in the three independent cells and correlated P2	Correlated P0 ×65.7 and P1 ×32.1, and P2 ×1.00, as predicted. **But independent P0 ×12.5 and P1 ×7.9 exceed 3** (independent P2 ×1.09)	**failed**	S-35→S-36
X2	certified $\leq 2/8$ in correlated P0 and P1; $\geq 6/8$ elsewhere	correlated P0 0/8, P1 0/8; independent 6/8, 6/8, 8/8; correlated P2 8/8	**held**	S-35→S-36
X3	cancellation in correlated P0 and P1 each $\geq 2 \times$ correlated P2	P0 3.29 and P1 2.32, against $2 \times 1.99 = 3.98$	**failed**	S-35→S-36
X4	off-manifold ratio ≥ 3 in correlated P0 and P1, ≤ 1.5 in P2	P0 1.22, P1 **0.77**; P2 0.78 (the P2 part held)	**failed**	S-35→S-36
X5	Spearman(cancellation, off-manifold RMSE) ≥ 0.6 over the 24 correlated models	$\rho = +0.177$, p = 0.407	**failed**	S-35→S-36
X6	unit match ≥ 0.85 in the independent cells and correlated P2; < 0.7 in correlated P0 and P1	The first part held: 1.000 in all four no-runaway-predicted cells. **The second part failed: correlated P0 0.774 and P1 0.883 are not < 0.7**	**failed**	S-35→S-36

A.2 Real-data case study (`F-03`)

Rows are as committed in the case-study summary (one row may cover several predictions, e.g. F2–F5). The rank intervention's verdicts are given per arm in the result column.

Study	Prediction (threshold)	Result	Verdict	Commits
Gauge study (`gauge_F-04`)	**Control 1**: teacher edges recovered, median dense corr ≥ 0.8	0.301 (sanity: h corr 0.913 < 0.95)	**failed**	S-02→S-03
Gauge study (`gauge_F-04`)	P1: gauge fixing removes $\geq 50\%$ of edge variance	not run	inconclusive (gated by Control 1)	S-02→S-03
Gauge study (`gauge_F-04`)	P2: sparse $\geq 2\times$ dense, DEC region highest	not run	inconclusive (gated)	S-02→S-03
Gauge study (`gauge_F-04`)	P3: (e) < (d) < (c) < (a)	not run	inconclusive (gated)	S-02→S-03
Gauge study (`gauge_F-04`)	P4: every seed has a unit with $\lvert\text{corr}\rvert < 0.8$	not run	inconclusive (gated)	S-02→S-03
Gauge study (`gauge_F-04`)	P5: KAN-full edge variance > KAN-δ	not run	inconclusive (gated)	S-02→S-03
Gauge study (`gauge_F-04`)	P6: seed spread flags errors	Spearman +0.169 (A) / +0.213 (B); fold B RMSE at 80% coverage 0.153 vs random 0.137	**failed**	S-02→S-04
Control 2 (`control2_F-04`)	C1: (I,C) edges ≥ 0.9 and units ≥ 0.9	prediction corr 0.947 < 0.99	inconclusive (gate failed)	S-05→S-06

Study	Prediction (threshold)	Result	Verdict	Commits
Control 2 (`control2_F-04`)	C2: (R,C) invT, molal ≥ 0.9; co-solvent < 0.7	prediction corr $0.969 < 0.99$	inconclusive (gate failed)	S-05→S-06
Control 2 (`control2_F-04`)	C3: 107 epochs gives prediction corr < 0.95	0.858 (I,S), 0.919 (R,S)	**held**	S-05→S-06
Control 3 (`control3_F-04`)	C1': (I) passes the gate, edges ≥ 0.9, units ≥ 0.9	(I) RMSE/std $0.128 > 0.05$; unit match 0.648	**failed**	S-07→S-08
Control 3 (`control3_F-04`)	C2': (R) edges $\leq$ (I) edges $- 0.10$	(R) edges 0.852, units 0.659	inconclusive ((I) failed the gate)	S-07→S-08
Control 3 (`control3_F-04`)	C4: every continuous input ≥ 0.9 in (I)	–	inconclusive ((I) failed the gate)	S-07→S-08
Fiber (`fiber_F-04`)	F1: $\geq 50\%$ of seed pairs on-fiber	0/190 (closest d = 0.146)	**failed**	S-09→S-10
Fiber (`fiber_F-04`)	F2–F5	not run	inconclusive (no on-fiber pairs)	S-09→S-10
Fiber 2 (`fiber2_F-04`)	G1: $\geq 4/6$ seeds and $\geq 10/20$ students certify convergence	0/6, 0/20 (all at the 20,000-iteration cap)	**failed**	S-11→S-12
Fiber 2 (`fiber2_F-04`)	G2–G5	not run	inconclusive (no converged model)	S-11→S-12
Support (`support_F-04`)	H1: dim(N) ≥ 5	dim(N) = 36 of 72	**held**	S-13→S-14
Support (`support_F-04`)	H2: $\geq 50\%$ of N is REDISTRIBUTION within the correlated group	18/36	**held, exactly at threshold**	S-13→S-14
Support (`support_F-04`)	H3: set A fraction in N ≥ 0.5 and $\geq 3\times$ random	median 0.942 (random 0.5)	inconclusive (untestable: $3 \times 0.5 > 1$)	S-13→S-14
Support (`support_F-04`)	H4: set B (capped), same criterion	median 0.949	inconclusive (untestable)	S-13→S-14
Support (`support_F-04`)	H5: flattest Hessian directions overlap N ≥ 0.5	median 0.885; median layer-1 block share only 0.08	**held**, with caveat (see `support_F-04`)	S-13→S-14
Support (`support_F-04`)	H6: fraction in N rises from control-3 to capped state, $\geq$ 15/20	20/20 ($0.713 \rightarrow 0.949$)	**held**	S-13→S-14
Rule (`rule_F-04`)	I1–I5 (gate)	0 columns removed; gate stopped	inconclusive	S-16→S-17
Rank (`rank_F-04`)	I1: median max|grad| $\leq 0.1 \times$ baseline	arm G: **failed** (4.00×); arm F: **failed** (29.1×)	see result	S-18→S-19
Rank (`rank_F-04`)	I2: median d_AB $\leq 0.5 \times$ baseline	arm G: **failed** (0.945×); arm F: **failed** (0.808×)	see result	S-18→S-19
Rank (`rank_F-04`)	I3 (sanity): median loss $\leq 1.10 \times$ baseline	arm G: passed (1.004×); arm F: passed, narrowly (1.099×)	see result	S-18→S-19
Rank (`rank_F-04`)	I4: fold A RMSE ≤ 0.150 (KAN-δ 0.1420)	arm G: **held**, narrowly (0.1499); arm F: **failed** (0.1587)	see result	S-18→S-19
Rank (`rank_F-04`)	I5: edge corr on 1000/T and molality $\geq$ baseline + 0.1 (baseline 0.102)	arm G: **held** (0.927); arm F: **held** (0.338)	see result	S-18→S-19
Rank (`rank_F-04`)	I6: arm F's improvement $\geq$ arm G's in both I1 and I2	arm G: **failed** (max|grad| 29.1× vs 4.00×; d_AB does favour F, 0.808 vs 0.945)	see result	S-18→S-19
`trust_F-04`	T1 / T2: trust-krylov certifies $\geq 4/6$ seeds / $\geq 2/3$ students	0/6, 0/3. All 9 stopped on scipy's "bad approximation" after 1–62 iterations; the Hessian was accurate to $\leq 2 \times 10^{-7}$	**failed**	S-20→S-21
`trust_F-04`	T3–T5	nothing converged	inconclusive	S-20→S-21
`stage2_F-04`	U1: trust-exact (exact Hessian, 500 iterations) certifies $\geq 4/6$ seeds	0/6. All 9 hit the iteration cap	**failed**	S-22→S-26
`stage2_F-04`	U2: with L2 $\lambda = 10^{-5}$, $\geq 4/6$ seeds and $\geq 2/3$ students	1/6 seeds, 0/3 students	**failed**	S-22→S-26
`stage2_F-04`	U3: more converge at 10^{-5} than at 10^{-6}	1 vs 0	**held**	S-22→S-26

Study	Prediction (threshold)	Result	Verdict	Commits
`stage2_F-04`	U4: converged L2 models' loss without L2 $\leq 1.05 \times$ capped	1.2545	**failed**	S-22→S-26
`stage2_F-04`	U5: converged seeds' disagreement $\leq 0.5 \times$ capped	only 1 converged	inconclusive	S-22→S-26
`close_F-04`	V1: at some μ, $\geq 4/6$ seeds and $\geq 2/3$ students converge (stage2 criterion)	0 certified at every μ	**failed**	S-29→S-30
`close_F-04`	V2: converged seeds' data term $\leq 1.05 \times$ stage2 A	nothing certified at the selected $\mu = 10^{-6}$	inconclusive	S-29→S-30
`close_F-04`	V3: $\|\theta\|^2 \leq 10 \times$ start	same	inconclusive	S-29→S-30
`close_F-04`	V4: seed disagreement halved	same	inconclusive	S-29→S-30
`close_F-04`	V5: students' unit match ≥ 0.8	same	inconclusive	S-29→S-30
`close_F-04`	V6: fold A RMSE ≤ 0.150	1.0262, bias +0.9028	**failed**	S-29→S-30
`certify_F-04`	W1: at $\mu = 10^{-4}$, $\geq 5/6$ seeds certified (second-order criterion, F-a)	6/6; all 17 candidates certified	**held**	S-31→S-32
`certify_F-04`	W2: certified seeds' median d_AB $\leq 0.5 \times$ capped	0.0771 vs capped 0.1041 (−26%)	**failed**	S-31→S-32
`certify_F-04`	W3: certified students' unit match ≥ 0.8 (vs the original teacher)	0.624	**failed**	S-31→S-32
`certify_F-04`	W4: $\mu = 10^{-4}$ fold A RMSE ≤ 0.150	0.3345	**failed**	S-31→S-32
`certify_F-04`	W5: $\mu = 10^{-4}$ fold A RMSE ≤ 0.5131	0.3345	**held**	S-31→S-32
`certify_F-04`	W6: Spearman(cross-edge ratio, held-out RMSE) ≥ 0.6	$\rho = +0.345$, p = 0.328 (weak test)	**failed**	S-31→S-32

Committed tally of the case study:

Study	Held	Failed	Inconclusive
First table (Control 1, P1–P6, C1–C3, C1'/C2'/C4, F1–F5, G1–G5, H1–H6)	5	5	19
Rule (I1–I5)	0	0	5
Rank (I1, I2, I4, I5 per arm, I6)	3	6	0
Trust (T1–T5)	0	2	3
Stage 2 (U1–U5)	1	3	1
Close (V1–V6)	0	2	4
Certify (W1–W6)	2	4	0
Total	**11**	**22**	**32**

A.3 Shared-curve KAN (`F-05`)

Run after the case-study close-out; not part of the 65 predictions above.

ID	Prediction (threshold)	Result	Verdict	Commits
S1	SC LOCO RMSE $\leq 1.05 \times$ baseline	unweighted mean SC 0.2923 vs base 0.2554 (ratio 1.145; threshold 0.2681). Also reported: row-weighted 0.2478 / 0.2297 (1.079); folds ≥ 20 rows 0.3138 / 0.2093 (1.499)	failed	S-38→S-40
S2	SC fold A RMSE ≤ 0.160	SC 0.1757 (base 0.1420)	failed	S-38→S-40
S3	SC median d_AB $\leq 0.5 \times$ baseline	SC 0.1865 vs base 0.1120 (threshold 0.0560): SC seeds agree *less* than baseline seeds	failed	S-38→S-40
S4	curve corr ≥ 0.90 for ≥ 6 of 8 inputs	3 of 8 (M_co 0.959, mix_lneta 0.970, invT 0.986); lowest x_co 0.596; others 0.871–0.891	failed	S-38→S-40
S5	$\geq 8/10$ SC fold A models certified	SC 10/10 (max|grad| $\leq 7 \times 10^{-10}$, 0 near-null eigenvalues); baseline 0/10 (all hit the 500-iteration cap)	held	S-38→S-40
S6	median β-norm polished/early ≤ 3 (calibrated)	median 1.337 (range 0.652–2.356); $\|\theta\|^2$ ×4.59 (base ×67.9, range 30.6–281)	held	S-38→S-40

ID	Prediction (threshold)	Result	Verdict	Commits
S7	SC polished/early fold A RMSE ≤ 1.5	SC 1.920 (0.1757 → 0.3373); baseline 5.736 (0.1420 → 0.8147)	failed	S-38→S-40
S8	d log k/d(1000/T) < 0 on $\geq$ 95% rows in $\geq 8/10$ seeds	10/10 (median share 1.000; 1424 rows, 10 excluded per D4)	held	S-38→S-40
S9	Spearman(1000/T, |slope|) > 0 in $\geq 8/10$ seeds	10/10 (median +0.661, range +0.406 to +0.885)	held	S-38→S-40
S10	d log k/d(ln η_mix) < 0 on $\geq$ 90% rows in $\geq 8/10$ seeds	7/10 (median share 0.967; s0 0.892, s2 0.892, s8 0.826)	failed	S-38→S-40

A.4 Two-anchor excess model (`F-06`)

Run after the case-study close-out; not part of the 65 predictions above.

ID	Prediction (threshold)	Result	Verdict	Commits
E1	EX LOCO $\leq 0.95 \times$ KAN-δ	unweighted mean EX 0.2834 vs threshold 0.2426 (base 0.2554; ratio 1.110). Row-weighted 0.2363 / 0.2297 (1.029); folds ≥ 20 rows 0.2662 / 0.2093 (1.272). EX is better on EC (0.237 vs 0.256), Sulfolane, 3-Glyme, 2-Glyme and Toluene, and worse on 2-MeTHF, THF, Methylene chloride, DME and EA	failed	S-41→S-43
E2	EX fold A ≤ 0.142	EX 0.1502 (base this run 0.1420)	failed	S-41→S-43
E3	s agrees across seeds (separable co-solvents, Amendment 1)	median pairwise corr +0.987 over EA, EC, Methylene chloride: a weak test with 3 values per seed, and Methylene chloride is marginal. Seed SD of s: EA 0.063 (0.39 × the spread across co-solvents, 0.159), EC 0.091 (0.57 ×), Methylene chloride 0.067 (0.42 ×). Secondary ($\leq$ 2 rule, 7 co-solvents): +0.869	held	S-41→S-43
E4	mean s(low ε) $<$ mean s(EC, Sulfolane) in $\geq 8/10$ seeds	0/10: the ordering is reversed in every seed. Per high-ε co-solvent: vs EC alone 0/10 (EC median s +0.104), vs Sulfolane alone 0/10 (median −0.124). The low-ε mean is +0.19 to +0.49 per seed. Sulfolane does not drive the failure on its own: EC alone fails in every seed too	failed	S-41→S-43
E5	median seed-SD flagged $\geq 2 \times$ separable (Amendment 1)	0.091 vs 0.067, ratio 1.37. Secondary ($\leq$ 2 rule): 0.222 vs 0.069, ratio 3.22, no verdict; the secondary is driven by 3-Glyme (SD 0.478, M_co extrapolated) and 2-Glyme (0.222)	failed	S-41→S-43

B Post-hoc analyses

Every analysis below was defined after seeing results. Each is labelled **post hoc** in its own files, changes no pre-registered verdict, and is reported as exploratory. The description is the subject line of the commit that added the analysis.

Analysis	Commit subject (as committed)	Commit
Post hoc. Anatomy of the real-data runaway `F-07, F-08, F-09`	Plan for descriptive runaway anatomy (before F-08 exists)	S-27
	Anatomy (descriptive): Q1, Q2 not as expected, Q3 as expected; RBF growth is in the penalty null space	S-28
Post hoc. Gauge check and regularised teacher (exploratory) `F-10, F-11, F-12`	gaugecheck (POST-HOC, exploratory): penalty fixes gauge position by slope balance; students match the regularised teacher	S-33
Post hoc. Anatomy of the synthetic runaway `F-13, F-14`	paper2 anatomy_synth (POST-HOC, descriptive): synthetic runaway lives mainly in layer-2 output-edge cancellation, unsaturated; no verdicts change	S-37

Analysis	Commit subject (as committed)	Commit
Post hoc. Loss decomposition along the runaway `F-15, F-16`	paper2 lossdecomp (POST-HOC, descriptive): synthetic runaway loss decrease shared, D2 penalty median 0.61 vs data 0.37; 12/20 runaway models overfit; real-data reference recomputed	S-44
Post hoc. Descriptive checks (hidden-unit correlation, tilt affinity, references) `F-17, F-18, F-19`	paper2/checks: plan for descriptive checks (F4 hidden-unit correlation, F2 tilt affinity, A1 commit and data citation) before F-20 exists	S-46
	paper2/checks (POST-HOC, descriptive): hidden-unit correlation marks the runaway (independent cells 0.70 vs 0.05) but is not sufficient; RBF tilt affine to 2% centrally, 13% at the ends; A1 commit S-01; CALiSol-23 citation not in competition material	S-47
Post hoc. Regularised teacher (weights pinned)	Pin gaugecheck regularised-teacher weights in a seventh archive; append to weights manifest	S-34

C Reproducibility map

Generated from `F-21`. Every figure is rebuilt by its script from committed results; each figure's sidecar JSON lists the data files (path, commit, SHA-256), any archived weights (SHA-256, archive) and every plotted number. Code will be released upon publication.

Figure	Script	Data files (commit)	Archived weights
Figure 1	`make_F-22`	none (computed from committed code: F-23, F-24)	—
Figure 2	`make_F-25`	`paper2/synth_F-26` (S-36)	—
Figure 4	`make_F-27`	`stage2_F-26` (S-26); `close_F-26` (S-30); `certify_F-26` (S-32)	—
Figure 3	`make_F-28`	`weights_F-29` (S-45); `paper2/anatomy_synth_F-26` (S-37); `paper2/checks/checks_F-26` (S-47)	18 files, archives W-01, W-02, W-03
Figure 5	`make_F-30`	`arch/sc_F-26` (S-40); `certify_F-26` (S-32); `weights_F-29` (S-45)	40 files, archives W-04
Figure 6	`make_F-31`	`paper2/lossdecomp_F-26` (S-44)	—
Figure 7	`make_F-31`	`gaugecheck_F-26` (S-33)	—
Figure 8	`make_F-31`	`arch/sc_F-26` (S-40); `arch/ex_F-26` (S-43)	—

Tables in the main text (no script; values typed in the draft):

Table	Source	Data files	Commits
Table 1	typed in the draft from	`F-32`, `F-33`	S-36
Table 2	typed in the draft from	`F-34`, `F-35`, `F-36`	S-30, S-32, S-26
Table 3	typed in the draft from	`F-37`, `F-38`, `F-39`	S-40, S-43, S-48

Panels evaluated post hoc from archived weights (from `F-40`):

- **fig4a, real data:** the split of the parameter change into affine and curved RBF parts per layer, for 107 epochs → fiber2 capped → stage2 Part A.
- `stage2_F-26` stores only per-block norms, without an affine/curved split and without the 107 → capped change.
- **fig5b, polished fold A d_AB** for SC-KAN-δ and the baseline (marked *).
- arch/sc committed d_AB only at the early state.

D Research process

Pre-registration. Every study committed a pre-registration file (predictions, thresholds, interpretation rules) before the script that tested it existed. Verdicts were appended below the committed text; the pre-registered text was never edited, and corrections to reported numbers were made in separate, labelled commits.

Amendments. A change to a design after its pre-registration was committed as a dated amendment section before any affected model was trained, with its reason; the original text was kept. Choices forced by the code or data at run time were logged as numbered discrepancies at the top of each output log.

Files win. Instructions to the agent stated that committed files take precedence over any number or description in a prompt; discrepancies between a brief and the files were flagged rather than resolved silently.

Data and weights. Model weights were never committed: they were archived outside the repository with a manifest of SHA-256 hashes and producing commits, and every later analysis verified the hashes and held its inputs in memory. Post-hoc analyses were labelled as such in their files and changed no verdict.

AI assistance. Code, runs and logs were produced by an AI coding agent working under this protocol. Study designs, briefs and the manuscript were developed with an AI assistant. The author set the research questions, reviewed and approved every brief and amendment, decided each next stage, and takes responsibility for all content. Crashes were recorded in the logs and fixed in separate commits labelled as implementation-only.

Pre-registrations, amendments and crash records (from the commit history):

Commit	Date	Kind	Commit subject
S-02	2026-09-23	pre-registration	Pre-register KAN identifiability study (before any experiment)
S-05	2026-09-23	pre-registration	Pre-register corrected 2x2 control (before writing or running it)
S-07	2026-09-23	pre-registration	Pre-register control 3: reachable teacher (before writing code)
S-09	2026-09-29	pre-registration	Pre-register fiber completeness test (before writing or running F-41)
S-11	2026-09-29	pre-registration	Pre-register fiber2: certified convergence + teacher-known fiber analysis (before writing code)
S-13	2026-09-29	pre-registration	Pre-register support study: near-null space, where models differ, Hessian (before F-42 exists)
S-15	2026-09-29	pre-registration	Close-out: electrolyte case study summary (all pre-registered predictions)
S-16	2026-09-29	pre-registration	Pre-register basis-size rule intervention (before F-43 exists)
S-18	2026-09-29	pre-registration	Pre-register rank-constrained layer-1 intervention (before F-44 exists)
S-20	2026-09-30	pre-registration	Pre-register trust-region Newton polishing, stage 1 (before F-45 exists)
S-22	2026-09-30	pre-registration	Pre-register stage 2: trust-exact check, runaway diagnostic, coercivity (before F-46 exists)
S-23	2026-09-30	crash record / fix	F-46 as first run (crashed with AttributeError in callback)
S-24	2026-09-30	crash record / fix	stage2: fix AttributeError (implementation only, post-prereg)
S-25	2026-10-02	crash record / fix	stage2: hold verified inputs in memory (implementation only, post-prereg)
S-29	2026-10-02	pre-registration	Pre-register targeted null-space penalty intervention (before F-47 exists)
S-31	2026-10-03	pre-registration	Pre-register second-order certification and regularised fold A accuracy (before F-48 exists)
S-35	2026-10-03	pre-registration	paper2: pre-register synthetic 2x3 runaway test (before F-49 exists)
S-38	2026-10-03	pre-registration	arch: pre-register SC-KAN-δ (shared-curve KAN-δ) before any script exists; decisions C (centring), mu null-space term, tanh salt embedding, full beta term
S-39	2026-10-03	crash record / fix	arch sc_run: fix log() call (crash record 1, after the first fold A polish); resume from cache
S-41	2026-10-04	pre-registration	arch: pre-register EX-KAN (two-anchor excess model) before any script exists; decision B (x_co-independent g, [7,6,1]), full set for E3-E5, E4 mean rule
S-42	2026-10-04	amendment	arch ex_prereg: Amendment 1 (after Step 0, before training): primary separability rule by fixed-composition groups (EA, EC, Methylene chloride separable); committed rule reported as secondary

E Supplementary figures




Figure 6: Post hoc loss decomposition (synthetic, early→polished): share of the total-loss decrease from each term, pooled over the 8 seeds of each cell. independent P0: data 0.57, D2 0.43 (median total change -7.9%); independent P1: data 0.49, D2 0.44 (median total change -11.3%); independent P2: data 0.68, D2 0.20 (median total change -3.9%); correlated P0: data 0.35, D2 0.65 (median total change -11.7%); correlated P1: data 0.37, D2 0.55 (median total change -15.5%); correlated P2: data 0.50, D2 0.40 (median total change -5.3%).




Figure 7: Post hoc gauge check at the $\mu = 10^{-4}$ certified minima: share of the curvature along each least-squares gauge direction contributed by μQ. Medians: constant shift in layer 1, real-data seeds 0.46 ($n = 288$); constant shift in layer 1, students (trained on a frozen teacher) 0.48 ($n = 144$); constant shift in layer 2, real-data seeds 0.94 ($n = 36$); constant shift in layer 2, students 0.97 ($n = 18$); unit rescaling, real-data seeds 0.21 ($n = 36$); unit rescaling, students 0.52 ($n = 18$).




Figure 8: Leave-one-co-solvent-out RMSE per fold (5-seed ensembles, early state) for the KAN-δ baseline, SC-KAN-δ and EX-KAN. Unweighted means: KAN-δ baseline 0.2554; SC-KAN-δ 0.2923; EX-KAN 0.2834. The EA fold uses the fold A rows.