

AUTONOMOUS STRUCTURAL SCREENING

TwinVerse Inspect AI

Inspect the unreachable.

Engineers climb bridges, rappel down dams and walk pipelines with clipboards. This does that first pass from a photograph — and tells you exactly how much to trust the answer.

Ayaan Aatif · Muhammad Muneed · Inshrah Mehmood

[Event / Track] · [Date] · Bano Qabil · Alkhidmat Foundation Pakistan

THE PROBLEM

Someone has to go and look at it.

Every bridge, dam, tunnel and building has to be inspected. Today that means a person physically getting close enough to see the concrete — climbing, rappelling, or walking the length of it with a clipboard.

It is dangerous work. It is slow enough that backlogs build and structures go years between inspections. And it is inconsistent: two inspectors looking at the same crack will often write down two different things.

The result is that most maintenance is **reactive**. Problems are found after they matter rather than before.

Dangerous People work at height and over water to look at concrete with their own eyes.	Slow A single span can take days. Backlogs mean long gaps between inspections.	Inconsistent Two inspectors, two clipboards, two different answers.
---	--	---

WHAT WE BUILT

A first pass that never has to climb anything.

TwinVerse Inspect AI takes ordinary imagery — from a drone, a fixed camera, or a phone — and does the first pass automatically. It finds cracks, ranks how serious each one is, shows them on the photograph and on a 3D view of the structure, and produces a report anyone can forward.

The engineer still makes every decision. What changes is that they start from a sorted list of findings instead of from a memory card full of photographs.

HOW IT WORKS

Four steps, no black box.

1 • Capture Upload images or video. Drone, CCTV, robot or phone — it does not care which.	2 • Detect A trained model finds each crack and draws a box around it.	3 • Score Each finding gets a severity score from a formula shown on screen.	4 • Report Annotated images, a 3D view, and a PDF for whoever needs it.
---	--	--	---

WHY IT IS DIFFERENT

You can check its work.

Most systems of this kind give you a number and ask you to trust it. This one shows the arithmetic. Every severity score on screen is three values multiplied together, and all three are stored with the finding:

severity
0.0288

=

area
0.558

×

confidence
1.0

×

class weight
0.01606

=

A reader can recompute any figure by hand from the record it came from. That is a deliberate design choice, not a feature — it is the difference between a tool an engineer can sign off on and one they cannot.

WHERE IT STANDS

A running system, not a mockup.

104 automated tests	6.1s to analyse 8 images	7ms per image on a GPU	63% of cracks found on unseen data
---	--	--	--

That last figure is deliberately the conservative one. On imagery resembling its training data the detector finds about 81% of cracks; on a public dataset from an unrelated source that it had never seen, 63%. We quote the number measured where it is hardest, because a figure that only holds on familiar photographs is not a figure anyone can plan around.

WHAT COMES NEXT

The honest roadmap.

Next More defect types. Tracking cracks across video frames so counts are real.	Later A true photogrammetric twin built from the imagery itself.	Someday Predictive maintenance — which needs years of data that does not exist yet.
---	--	---

BEING HONEST ABOUT IT

We measured the weaknesses too.

Anything that inspects infrastructure has to be trustworthy before it is impressive. Every limitation below is stated inside the product itself and printed on the last page of every report it generates.

It finds cracks, and only cracks.

The model has never been shown corrosion, spalling or missing components. It will not report them even if they are in the picture.

Roughly one clean surface in five gets flagged.

Measured against 94 photographs of undamaged concrete. It is a screening tool and it errs toward flagging — a human reviews everything it raises.

It is weaker on imagery unlike its training data.

On a third-party dataset it had never seen, the detection rate falls from about 81% to 63% — roughly three cracks in five rather than four. The false-alarm rate does not change; only recall does. More varied training data is the fix, and no confidence threshold substitutes for it.

Severity is a ranking, not a measurement.

It tells you which crack to look at first. It does not tell you how wide the crack is in millimetres — that needs camera calibration or a physical scale in the frame.

The 3D view is illustrative.

The structure shown is a generic model, and marker positions come from the order the photographs were taken, not from surveyed coordinates.

Video counts are inflated.

Frames are analysed independently, so a single crack visible across ten frames is counted ten times.

“Naming a weakness costs far less than being caught by it.”

This does not replace an engineer.

It does the first pass, so the engineer spends their time on judgement instead of data collection.



Ayaan Aatif

Team Lead



Muhammad Muneed

Team Member



Inshrah Mehmood

Team Member

TwinVerse Inspect AI

[Add contact email · repository link]