Code Documentation

Classes, functions and the BCE model

Every class and every function in the back end, and every component in the front end.

Each entry names the file and the line range, so a class diagram box or a sequence-diagram lifeline can point at the exact code.

101 classes and 130 module functions in the back end; 23 components and 53 exported functions in the front end.

Repository CSIT314-InteriorDesignWebsite · commit 0fe34ce · 12 November 2026

Contents

1 How to read this document 8

1.1 The five roles 8

1.2 Where each layer lives 8

1.3 The routers, and the paths they serve 8

2 Entity layer: backend/app/domain 10

2.1 SearchCriteria 10

2.2 Project 10

2.3 Quote 13

2.4 Counter 14

2.5 QuoteRequest 15

2.6 Company 17

2.7 Account 18

2.8 Category 21

2.9 Shortlist 22

2.10 Role 23

2.11 AccountStatus 24

2.12 ProjectStatus 24

2.13 QuoteRequestState 25

2.14 QuoteState 25

2.15 AppointmentState 26

2.16 ConsultationMode 26

2.17 ReportStatus 26

2.18 DomainError 26

2.19 EmailAlreadyRegistered 27

2.20 InvalidCredentials 27

2.21 AccountNotActive 28

2.22 InvalidRoleForSelfRegistration 28

2.23 WeakPassword 28

2.24 NotPermitted 29

2.25 AccountNotFound 29

2.26 CompanyAlreadyExists 29

2.27 CompanyNotFound 29

2.28 ProjectNotFound 30

2.29 QuoteRequestNotFound 30

2.30 QuoteNotFound 30

2.31 AppointmentNotFound 31

2.32 ReportNotFound 31

2.33 InvalidState 31

2.34 ProjectReport 32
2.35 ConsultationAppointment 33
3 Entity access: backend/app/repositories 35
3.1 AccountRepository 35
3.2 AppointmentRepository 35
3.3 CategoryRepository 36
3.4 CompanyRepository 37
3.5 ProjectRepository 38
3.6 QuoteRequestRepository 39
3.7 QuoteRepository 40
3.8 ReportRepository 41
3.9 ShortlistRepository 43
4 Control: backend/app/services 44
4.1 AccountService 44
4.2 AppointmentService 45
4.3 CategoryNotFound 46
4.4 CategoryExists 46
4.5 CategoryService 46
4.6 CompanyService 47
4.7 ImageUnavailable 47
4.8 load_image_bytes() 48
4.9 _read_local() 48
4.10 _read_remote() 48
4.11 _resolve() 49
4.12 _is_public() 49
4.13 is_animal() 50
4.14 _session() 50
4.15 available() 51
4.16 Reading 51
4.17 read() 52
4.18 object_tags() 52
4.19 engine_name() 53
4.20 ProjectReportService 53
4.21 SearchResult 54
4.22 ProjectSearchService 54
4.23 ProjectService 55
4.24 QuoteService 56
4.25 Bucket 57
4.26 Report 58

4.27 ReportService 58
4.28 ShortlistService 59
4.29 PaletteEntry 59
4.30 TagSuggestion 60
4.31 suggest_tags() 60
4.32 _merge() 61
4.33 _palette() 61
4.34 _stats() 62
4.35 _tags() 62
5 Control boundary: backend/app/api 64
5.1 _to_http() 64
5.2 list_accounts() 64
5.3 approve_account() 64
5.4 suspend_account() 65
5.5 _fail() 65
5.6 _public() 66
5.7 read_slots() 66
5.8 book() 67
5.9 list_appointments() 67
5.10 accept_appointment() 68
5.11 cancel_appointment() 68
5.12 register() 69
5.13 login() 69
5.14 read_current_account() 70
5.15 BudgetRange 70
5.16 CatalogueResponse 71
5.17 read_catalogue() 71
5.18 CategoryPublic 71
5.19 CategoryInput 72
5.20 CategoryPatch 72
5.21 _to_public() 72
5.22 _fail() 73
5.23 list_categories() 73
5.24 list_all_categories() 73
5.25 create_category() 74
5.26 update_category() 74
5.27 _public() 75
5.28 _to_http() 75
5.29 create_company() 76

5.30 read_my_company() 76
5.31 update_my_company() 77
5.32 list_companies() 77
5.33 read_company() 78
5.34 get_account_repository() 78
5.35 get_account_service() 78
5.36 get_company_repository() 79
5.37 get_company_service() 79
5.38 get_project_repository() 79
5.39 get_project_service() 79
5.40 get_project_search_service() 80
5.41 get_shortlist_repository() 80
5.42 get_shortlist_service() 80
5.43 get_quote_request_repository() 80
5.44 get_quote_repository() 81
5.45 get_quote_service() 81
5.46 get_appointment_repository() 81
5.47 get_appointment_service() 82
5.48 get_report_repository() 82
5.49 get_project_report_service() 82
5.50 get_category_repository() 82
5.51 get_category_service() 83
5.52 get_report_service() 83
5.53 get_current_account() 83
5.54 HealthResponse 84
5.55 read_health() 84
5.56 _read_photo() 85
5.57 store_upload() 85
5.58 tags_for_upload() 86
5.59 _fail() 87
5.60 _public() 87
5.61 list_reasons() 88
5.62 report_project() 88
5.63 list_reports() 89
5.64 resolve_report() 89
5.65 _to_http() 90
5.66 create_project() 90
5.67 list_my_projects() 91
5.68 list_company_projects() 91

5.69 search_projects() ... 92
5.70 read_project() ... 92
5.71 update_project() ... 93
5.72 delete_project() ... 93
5.73 record_project_view() ... 94
5.74 suggest_project_tags() ... 94
5.75 _fail() ... 95
5.76 _detail() ... 95
5.77 submit_request() ... 96
5.78 list_requests() ... 96
5.79 read_request() ... 97
5.80 counter_request() ... 97
5.81 cancel_request() ... 98
5.82 refuse_request() ... 98
5.83 answer_request() ... 99
5.84 list_quotes() ... 99
5.85 revise_quote() ... 100
5.86 accept_quote() ... 100
5.87 decline_quote() ... 101
5.88 BucketPublic ... 101
5.89 ReportPublic ... 102
5.90 read_report() ... 102
5.91 _forbidden() ... 103
5.92 read_shortlist() ... 103
5.93 save_project() ... 104
5.94 unsave_project() ... 104
6 Data transfer shapes: backend/app/schemas ... 106
7 Boundary layer: the browser ... 108
7.1 App ... 109
7.2 AuthProvider ... 110
7.3 ProtectedRoute ... 111
7.4 Home ... 112
7.5 Login ... 113
7.6 Register ... 114
7.7 Dashboard ... 115
7.8 Search ... 116
7.9 ProjectDetail ... 117
7.10 Saved ... 118
7.11 Designers ... 119

7.12 DesignerDetail 120
7.13 RequestQuote 121
7.14 Quotes 122
7.15 QuoteDetail 123
7.16 MyProjects 124
7.17 ProjectEditor 125
7.18 Profile 126
7.19 Admin 127
7.20 Platform 128
7.21 BudgetSlider 129
7.22 Appointments 130
7.23 BookConsultation 131
7.99 The API client 131
8 Sequence walks 133
8.1 A customer searches by photo 133
8.2 A customer requests a quote 133
8.3 A designer answers a request 133
8.4 An administrator approves an account 133
8.5 An administrator reads a report 134
9 Appendix: every file and what it holds 134

1 How to read this document

The platform is described in the Boundary-Control-Entity form. A class diagram draws every class below as a box. A sequence diagram draws the functions below as messages between lifelines. This document is the link between the two.

Each entry has the same parts: the name, the file and line range, the role, the purpose taken from the docstring, a table of attributes and methods, and a code excerpt. A long class shows its signatures; a short one shows the whole class.

1.1 The five roles

Role	Folder	What it does	Diagram form
`Boundary`	frontend/src/pages, components	Draws a screen, collects input, calls the API client	Lifeline on the left
`Boundary (API client)`	frontend/src/api.ts	One typed function per endpoint	Message to the server
`Control`	backend/app/api, backend/app/services	Checks permission, runs the use case, returns a shape	Lifeline in the middle
`Entity`	backend/app/domain	Holds the data and the rules that protect it	Class box
`Entity (access)`	backend/app/repositories	Finds and stores entity objects	Lifeline beside the entity
`Data transfer`	backend/app/schemas, frontend/src/types.ts	Shapes that cross the HTTP edge	Not drawn; shown as parameters

1.2 Where each layer lives

Role	Folder	Files	Classes	Functions
`Entity`	backend/app/domain	13	35	14
`Entity (access)`	backend/app/repositories	8	9	0
`Control`	backend/app/services	13	19	16
`Control (boundary)`	backend/app/api	14	8	86
`Data transfer`	backend/app/schemas	7	29	0

1.3 The routers, and the paths they serve

The back end exposes 52 HTTP operations. Each one is a control function; the table gives the verb, the path and the code position.

Verb	Path	Function	Where
GET		list_accounts()	admin.py:34
POST		approve_account()	admin.py:52
POST		suspend_account()	admin.py:68
GET		read_slots()	appointments.py:69
POST		book()	appointments.py:89
GET		list_appointments()	appointments.py:114
POST		accept_appointment()	appointments.py:133
POST		cancel_appointment()	appointments.py:149
POST		register()	auth.py:40
POST	/login	login()	auth.py:59
GET	/me	read_current_account()	auth.py:80
GET		read_catalogue()	catalogue.py:38
GET		list_categories()	categories.py:73
GET		list_all_categories()	categories.py:83
POST		create_category()	categories.py:100
PATCH		update_category()	categories.py:116

POST		create_company()	companies.py:56
GET		read_my_company()	companies.py:75
PATCH		update_my_company()	companies.py:91
GET		list_companies()	companies.py:111
GET		read_company()	companies.py:126
GET	/health	read_health()	health.py:25
POST		store_upload()	images.py:86
POST		tags_for_upload()	images.py:122
GET		list_reasons()	project_reports.py:66
POST		report_project()	project_reports.py:77
GET		list_reports()	project_reports.py:95
POST		resolve_report()	project_reports.py:111
POST		create_project()	projects.py:60
GET		list_my_projects()	projects.py:76
GET		list_company_projects()	projects.py:102
GET		search_projects()	projects.py:115
GET		read_project()	projects.py:161
PATCH		update_project()	projects.py:177
DELETE		delete_project()	projects.py:197
POST		record_project_view()	projects.py:213
POST		suggest_project_tags()	projects.py:230
POST		submit_request()	quotes.py:63
GET		list_requests()	quotes.py:79
GET		read_request()	quotes.py:100
POST		counter_request()	quotes.py:115
POST		cancel_request()	quotes.py:134
POST		refuse_request()	quotes.py:153
POST		answer_request()	quotes.py:173
GET		list_quotes()	quotes.py:192
POST		revise_quote()	quotes.py:209
POST		accept_quote()	quotes.py:228
POST		decline_quote()	quotes.py:244
GET		read_report()	reports.py:46
GET		read_shortlist()	shortlist.py:31
POST		save_project()	shortlist.py:50
DELETE		unsave_project()	shortlist.py:75

2 Entity layer: backend/app/domain

These classes own the data. Each one guards its own rules in the constructor or in its methods, so a caller cannot create an object in a state the business forbids. This is the set of boxes for the class diagram.

2.1 SearchCriteria

backend/app/domain/project.py · lines 44–69

The filter a customer submits to the catalogue.

Attribute	Type	Default
keyword	str	''
category	str	''
style	str	''
budget_min	int | None	None
budget_max	int | None	None
tags	list[str]	field(default_factory=list)

Method	Purpose	Lines
def __post_init__() -> None	Refuse a budget range that cannot be answered.	58–69

project.py — backend/app/domain/project.py — CSIT314

backend › app › domain › project.py › SearchCriteria

```python
class SearchCriteria:
    """The filter a customer submits to the catalogue.

    An empty field does not filter. Each budget is optional, so the screen can
    send one end of the slider only.
    """

    keyword: str = ""
    category: str = ""
    style: str = ""
    budget_min: int | None = None
    budget_max: int | None = None
    tags: list[str] = field(default_factory=list)

    def __post_init__(self) -> None:
        """Refuse a budget range that cannot be answered."""
        if self.budget_min is not None and self.budget_min < 0:
            raise ValueError("Minimum budget must not be negative")
        if self.budget_max is not None and self.budget_max < 0:
            raise ValueError("Maximum budget must not be negative")
        if (
            self.budget_min is not None
            and self.budget_max is not None
            and self.budget_min > self.budget_max
        ):
            raise ValueError("Minimum budget must not exceed the maximum")
```

main — Python · UTF-8 · LF · lines 44–69

2.2 Project

backend/app/domain/project.py · lines 73–318

One entry in a designer's portfolio.

Attribute	Type	Default
`owner_id`	str	—
`company_id`	str	—
`title`	str	—
`description`	str	''
`style`	str	''
`category`	str	''
`budget_min`	int	0
`budget_max`	int	0
`status`	ProjectStatus	ProjectStatus.CURRENT
`images`	list[str]	field(default_factory=list)
`tags`	list[str]	field(default_factory=list)
`view_count`	int	0
`shortlist_count`	int	0
`id`	str	field(default_factory=lambda: str(uuid4()))
`created_at`	datetime	field(default_factory=lambda: datetime.now(timezone.utc))
`updated_at`	datetime | None	None

Method	Purpose	Lines
`def __post_init__() -> None`	Check the values a project cannot be created without.	93–107
`def rename(title: str) -> None`	Replace the project title.	109–117
`def update_details() -> None`	Replace the searchable details after checking them.	119–141
`def mark_past() -> None`	Mark the job as finished.	143–146
`def mark_current() -> None`	Mark the job as still running.	148–151
`def mark_taken_down() -> None`	Hide the project from customers after a report is upheld.	153–156
`def add_image(url: str) -> None`	Attach a photo address. A repeated address changes nothing.	158–168
`def remove_image(url: str) -> None`	Detach a photo address when it is present.	170–175
`def replace_images(urls: list[str]) -> None`	Replace the whole photo list, dropping blank and repeated entries.	177–183
`def _clean_tags(tags: list[str]) -> list[str]`	Strip, deduplicate and bound a tag list.	185–204
`def replace_tags(tags: list[str]) -> None`	Replace the whole tag list after checking it.	206–209
`def add_tag(tag: str) -> None`	Attach one tag. A repeated tag changes nothing.	211–214
`def remove_tag(tag: str) -> None`	Detach one tag when it is present.	216–222
`def record_view() -> None`	Count one look at the detail page.	224–226
`def record_shortlist() -> None`	Count one customer saving this project.	228–230
`def withdraw_shortlist() -> None`	Count one customer removing it. The count never falls below zero.	232–234
`def is_owned_by(account_id: str) -> bool`	Return ``True`` when ``account_id`` is the designer behind this project.	236–238
`def matches(criteria: SearchCriteria) -> bool`	Return ``True`` when this project answers ``criteria``.	240–274
`def tag_overlap(wanted: list[str]) -> int`	Return how many of ``wanted`` this project carries, ignoring case.	276–283
`def specific_overlap(wanted: list[str]) -> int`	Return how many of ``wanted`` are object tags this project carries.	285–297
`def tag_score(wanted: list[str]) -> int`	Return the ranking weight: objects count double, mood counts once.	299–308
`def _require_valid_budget(minimum: int, maximum: int) -> None`		311–315
`def _touch() -> None`		317–318

project.py — backend/app/domain/project.py — CSIT314

backend › app › domain › project.py › Project · part 1 of 2

```python
# backend/app/domain/project.py — lines 73–318, signatures only
@dataclass
class Project:
    """One entry in a designer's portfolio."""
    owner_id: str
    company_id: str
    title: str
    description: str = ''
    style: str = ''
    category: str = ''
    budget_min: int = 0
    budget_max: int = 0
    status: ProjectStatus = ProjectStatus.CURRENT
    images: list[str] = field(default_factory=list)
    tags: list[str] = field(default_factory=list)
    view_count: int = 0
    shortlist_count: int = 0
    id: str = field(default_factory=lambda: str(uuid4()))
    created_at: datetime = field(default_factory=lambda: datetime.now(timezone.utc))
    updated_at: datetime | None = None

    def __post_init__() -> None
        """Check the values a project cannot be created without."""
    def rename(title: str) -> None
        """Replace the project title."""
    def update_details() -> None
        """Replace the searchable details after checking them."""
    def mark_past() -> None
        """Mark the job as finished."""
    def mark_current() -> None
        """Mark the job as still running."""
    def mark_taken_down() -> None
        """Hide the project from customers after a report is upheld."""
    def add_image(url: str) -> None
        """Attach a photo address. A repeated address changes nothing."""
    def remove_image(url: str) -> None
        """Detach a photo address when it is present."""
    def replace_images(urls: list[str]) -> None
        """Replace the whole photo list, dropping blank and repeated entries."""
    def _clean_tags(tags: list[str]) -> list[str]
        """Strip, deduplicate and bound a tag list."""
    def replace_tags(tags: list[str]) -> None
```

main

Python · UTF-8 · LF · lines 73–318 · part 1 of 2

project.py — backend/app/domain/project.py — CSIT314

backend › app › domain › project.py › Project · part 2 of 2

```
        """Replace the whole tag list after checking it."""
    def add_tag(tag: str) -> None
        """Attach one tag. A repeated tag changes nothing."""
    def remove_tag(tag: str) -> None
        """Detach one tag when it is present."""
    def record_view() -> None
        """Count one look at the detail page."""
    def record_shortlist() -> None
        """Count one customer saving this project."""
    def withdraw_shortlist() -> None
        """Count one customer removing it. The count never falls below zero."""
    def is_owned_by(account_id: str) -> bool
        """Return ``True`` when ``account_id`` is the designer behind this project."""
    def matches(criteria: SearchCriteria) -> bool
        """Return ``True`` when this project answers ``criteria``."""
    def tag_overlap(wanted: list[str]) -> int
        """Return how many of ``wanted`` this project carries, ignoring case."""
    def specific_overlap(wanted: list[str]) -> int
        """Return how many of ``wanted`` are object tags this project carries."""
    def tag_score(wanted: list[str]) -> int
        """Return the ranking weight: objects count double, mood counts once."""
    @staticmethod
    def _require_valid_budget(minimum: int, maximum: int) -> None
    def _touch() -> None
```

main — Python · UTF-8 · LF · lines 73–318 · part 2 of 2

2.3 Quote

backend/app/domain/quote.py · lines 38–131

One total, one validity date, one state.

Attribute	Type	Default
request_id	str	—
total_cents	int	—
valid_until	date	—
gst_included	bool	False
gst_rate_bp	int	GST_RATE_BP
note	str	''
version	int	1
state	QuoteState	QuoteState.OFFERED
created_at	datetime	field(default_factory=_now)
updated_at	datetime | None	None
id	str	field(default_factory=lambda: str(uuid4()))

Method	Purpose	Lines
def __post_init__() -> None	Check the amount, the note and the validity window.	53–74
def gst_cents() -> int	Return the tax inside or on top of the total.	77–79
def grand_total_cents() -> int	Return what the customer pays.	82–84
def is_expired(today: date | None = None) -> bool	Return whether the validity date passed.	86–88
def supersede() -> None	Retire this version because a newer one exists.	90–95
def accept() -> None	The customer takes this quote.	97–104

`def decline(reason: str = '') -> None`	The customer turns this quote down.	106–113
`def expire() -> None`	Close a quote whose validity date passed.	115–119
`def validity_date(days: int, today: date | None = None) -> date`	Return the date ``days`` from now, after checking the window.	122–128
`def _touch() -> None`		130–131

quote.py — backend/app/domain/quote.py — CSIT314

backend › app › domain › quote.py › Quote

```python
# backend/app/domain/quote.py — lines 38–131, signatures only
@dataclass
class Quote:
    """One total, one validity date, one state."""
    request_id: str
    total_cents: int
    valid_until: date
    gst_included: bool = False
    gst_rate_bp: int = GST_RATE_BP
    note: str = ''
    version: int = 1
    state: QuoteState = QuoteState.OFFERED
    created_at: datetime = field(default_factory=_now)
    updated_at: datetime | None = None
    id: str = field(default_factory=lambda: str(uuid4()))

    def __post_init__() -> None
        """Check the amount, the note and the validity window."""
    @property
    def gst_cents() -> int
        """Return the tax inside or on top of the total."""
    @property
    def grand_total_cents() -> int
        """Return what the customer pays."""
    def is_expired(today: date | None = None) -> bool
        """Return whether the validity date passed."""
    def supersede() -> None
        """Retire this version because a newer one exists."""
    def accept() -> None
        """The customer takes this quote."""
    def decline(reason: str = '') -> None
        """The customer turns this quote down."""
    def expire() -> None
        """Close a quote whose validity date passed."""
    @classmethod
    def validity_date(days: int, today: date | None = None) -> date
        """Return the date ``days`` from now, after checking the window."""
    def _touch() -> None
```

main — Python · UTF-8 · LF · lines 38–131

2.4 Counter

backend/app/domain/quote_request.py · lines 28–40

One target price the customer named, with a note.

Attribute	Type	Default
`target_cents`	int	—
`note`	str	—

created_at	datetime	—
id	str	field(default_factory=lambda: str(uuid4()))

Method	Purpose	Lines
def __post_init__() -> None		36–40

quote_request.py — backend/app/domain/quote_request.py — CSIT314

backend › app › domain › quote_request.py › Counter

```python
class Counter:
    """One target price the customer named, with a note."""

    target_cents: int
    note: str
    created_at: datetime
    id: str = field(default_factory=lambda: str(uuid4()))

    def __post_init__(self) -> None:
        if self.target_cents <= 0:
            raise ValueError("A target price must be above zero")
        if len(self.note) > MAX_NOTE:
            raise ValueError(f"A note must be {MAX_NOTE} characters or fewer")
```

main — Python · UTF-8 · LF · lines 28–40

2.5 QuoteRequest

backend/app/domain/quote_request.py · lines 44–163

One customer's request to one company.

Attribute	Type	Default
customer_id	str	—
company_id	str	—
title	str	—
scope	str	—
budget_min_cents	int	0
budget_max_cents	int	0
target_cents	int | None	None
project_id	str | None	None
state	QuoteRequestState	QuoteRequestState.PENDING
counters	list[Counter]	field(default_factory=list)
closed_reason	str	''
consent_at	datetime | None	None
created_at	datetime	field(default_factory=_now)
updated_at	datetime | None	None
id	str	field(default_factory=lambda: str(uuid4()))

Method	Purpose	Lines
def __post_init__() -> None	Check what a request cannot be created without.	63–90
def is_open() -> bool	Return whether the request still accepts an answer.	93–95
def counter(target_cents: int, note: str) -> Counter	Record one target price from the customer.	97–108

`def mark_answered() -> None`	Move to answered after the designer sends a quote.	110–115
`def refuse(reason: str) -> None`	The designer declines to quote.	117–123
`def cancel(reason: str) -> None`	The customer stops the request.	125–131
`def accept() -> None`	The customer accepts the answer.	133–138
`def decline(reason: str) -> None`	The customer turns the answer down.	140–146
`def expire() -> None`	Close a request that ran out of time.	148–153
`def is_overdue(now: datetime | None = None) -> bool`	Return whether a pending request passed its open window.	155–160
`def _touch() -> None`		162–163

quote_request.py — backend/app/domain/quote_request.py — CSIT314

backend › app › domain › quote_request.py › QuoteRequest

```python
# backend/app/domain/quote_request.py — lines 44–163, signatures only
@dataclass
class QuoteRequest:
    """One customer's request to one company."""
    customer_id: str
    company_id: str
    title: str
    scope: str
    budget_min_cents: int = 0
    budget_max_cents: int = 0
    target_cents: int | None = None
    project_id: str | None = None
    state: QuoteRequestState = QuoteRequestState.PENDING
    counters: list[Counter] = field(default_factory=list)
    closed_reason: str = ''
    consent_at: datetime | None = None
    created_at: datetime = field(default_factory=_now)
    updated_at: datetime | None = None
    id: str = field(default_factory=lambda: str(uuid4()))

    def __post_init__() -> None
        """Check what a request cannot be created without."""
    @property
    def is_open() -> bool
        """Return whether the request still accepts an answer."""
    def counter(target_cents: int, note: str) -> Counter
        """Record one target price from the customer."""
    def mark_answered() -> None
        """Move to answered after the designer sends a quote."""
    def refuse(reason: str) -> None
        """The designer declines to quote."""
    def cancel(reason: str) -> None
        """The customer stops the request."""
    def accept() -> None
        """The customer accepts the answer."""
    def decline(reason: str) -> None
        """The customer turns the answer down."""
    def expire() -> None
        """Close a request that ran out of time."""
    def is_overdue(now: datetime | None = None) -> bool
        """Return whether a pending request passed its open window."""
    def _touch() -> None
```

main — Python · UTF-8 · LF · lines 44–163

2.6 Company

backend/app/domain/company.py · lines 20–129

A designer's company profile.

Attribute	Type	Default
owner_id	str	—
name	str	—
description	str	''
contact_email	str	''
contact_phone	str	''
location	str	''
meeting_address	str	''
call_link	str	''
logo_url	str	''
id	str	field(default_factory=lambda: str(uuid4()))
created_at	datetime	field(default_factory=lambda: datetime.now(timezone.utc))
updated_at	datetime | None	None

Method	Purpose	Lines
def __post_init__() -> None	Normalise the values customers will read.	36–47
def rename(name: str) -> None	Replace the company name.	49–59
def update_description(text: str) -> None	Replace the description customers read.	61–64
def update_contact(email: str, phone: str) -> None	Replace the contact pair after checking the address has a domain.	66–74
def set_location(location: str) -> None	Replace the service area.	76–79
def attach_logo(url: str) -> None	Point the profile at a logo image.	81–87
def set_meeting_address(text: str) -> None	Set where an in person consultation takes place.	89–97
def set_call_link(url: str) -> None	Set the video call room, or clear it with a blank value.	99–109
def meeting_place(online: bool) -> str	Return the address a consultation uses, or the call link.	111–113
def offers_online() -> bool	Return ``True`` when this company can take video calls.	116–122
def is_owned_by(account_id: str) -> bool	Return ``True`` when ``account_id`` is the designer behind this company.	124–126
def _touch() -> None		128–129

company.py — backend/app/domain/company.py — CSIT314

backend › app › domain › company.py › Company

```python
# backend/app/domain/company.py — lines 20–129, signatures only
@dataclass
class Company:
    """A designer's company profile."""
    owner_id: str
    name: str
    description: str = ''
    contact_email: str = ''
    contact_phone: str = ''
    location: str = ''
    meeting_address: str = ''
    call_link: str = ''
    logo_url: str = ''
    id: str = field(default_factory=lambda: str(uuid4()))
    created_at: datetime = field(default_factory=lambda: datetime.now(timezone.utc))
    updated_at: datetime | None = None

    def __post_init__() -> None
        """Normalise the values customers will read."""
    def rename(name: str) -> None
        """Replace the company name."""
    def update_description(text: str) -> None
        """Replace the description customers read."""
    def update_contact(email: str, phone: str) -> None
        """Replace the contact pair after checking the address has a domain."""
    def set_location(location: str) -> None
        """Replace the service area."""
    def attach_logo(url: str) -> None
        """Point the profile at a logo image."""
    def set_meeting_address(text: str) -> None
        """Set where an in person consultation takes place."""
    def set_call_link(url: str) -> None
        """Set the video call room, or clear it with a blank value."""
    def meeting_place(online: bool) -> str
        """Return the address a consultation uses, or the call link."""
    @property
    def offers_online() -> bool
        """Return ``True`` when this company can take video calls."""
    def is_owned_by(account_id: str) -> bool
        """Return ``True`` when ``account_id`` is the designer behind this company."""
    def _touch() -> None
```

main — Python · UTF-8 · LF · lines 20–129

2.7 Account

backend/app/domain/account.py · lines 19–64

A single platform account.

Attribute	Type	Default
email	str	—
display_name	str	—
password_hash	str	—
role	Role	—
status	AccountStatus	AccountStatus.PENDING

`id`	str	field(default_factory=lambda: str(uuid4()))
`created_at`	datetime	field(default_factory=lambda: datetime.now(timezone.utc))

Method	Purpose	Lines
`def __post_init__() -> None`	Normalise the values identity depends on.	30–33
`def check_password(raw: str) -> bool`	Return ``True`` when ``raw`` is this account's password.	35–37
`def activate() -> None`	Move the account into the ACTIVE status.	39–41
`def suspend() -> None`	Move the account into the SUSPENDED status.	43–45
`def can_login() -> bool`	Return ``True`` only while the account is ACTIVE.	47–49
`def change_display_name(name: str) -> None`	Replace the display name with ``name``.	51–60
`def is_privileged() -> bool`	Return ``True`` for administrators and platform managers.	62–64

account.py — backend/app/domain/account.py — CSIT314

backend › app › domain › account.py › Account · part 1 of 2

```python
class Account:
    """A single platform account."""

    email: str
    display_name: str
    password_hash: str
    role: Role
    status: AccountStatus = AccountStatus.PENDING
    id: str = field(default_factory=lambda: str(uuid4()))
    created_at: datetime = field(default_factory=lambda: datetime.now(timezone.utc))

    def __post_init__(self) -> None:
        """Normalise the values identity depends on."""
        self.email = self.email.strip().lower()
        self.display_name = self.display_name.strip()

    def check_password(self, raw: str) -> bool:
        """Return ``True`` when ``raw`` is this account's password."""
        return verify_password(raw, self.password_hash)

    def activate(self) -> None:
        """Move the account into the ACTIVE status."""
        self.status = AccountStatus.ACTIVE

    def suspend(self) -> None:
        """Move the account into the SUSPENDED status."""
        self.status = AccountStatus.SUSPENDED

    def can_login(self) -> bool:
        """Return ``True`` only while the account is ACTIVE."""
        return self.status is AccountStatus.ACTIVE

    def change_display_name(self, name: str) -> None:
        """Replace the display name with ``name``.

        Raises ``ValueError`` when the new name is blank; that guard is a
        programming error rather than a flow the API is expected to surface.
        """
        candidate = name.strip()
        if not candidate:
            raise ValueError("Display name must not be empty")
        self.display_name = candidate
```

main — Python · UTF-8 · LF · lines 19–64 · part 1 of 2

account.py — backend/app/domain/account.py — CSIT314

backend › app › domain › account.py › Account · part 2 of 2

```python

    def is_privileged(self) -> bool:
        """Return ``True`` for administrators and platform managers."""
        return self.role.is_privileged
```

main — Python · UTF-8 · LF · lines 19–64 · part 2 of 2

2.8 Category

backend/app/domain/category.py · lines 22–58

One room category, active or archived.

Attribute	Type	Default
`name`	str	—
`active`	bool	True
`id`	str	field(default_factory=lambda: str(uuid4()))
`created_at`	datetime	field(default_factory=_now)
`updated_at`	datetime | None	None

Method	Purpose	Lines
`def __post_init__() -> None`		31–34
`def rename(name: str) -> None`	Replace the label.	36–39
`def archive() -> None`	Hide the category from the dropdowns.	41–44
`def restore() -> None`	Show the category again.	46–49
`def _clean(name: str) -> str`		52–58

category.py — backend/app/domain/category.py — CSIT314

backend › app › domain › category.py › Category

```python
class Category:
    """One room category, active or archived."""

    name: str
    active: bool = True
    id: str = field(default_factory=lambda: str(uuid4()))
    created_at: datetime = field(default_factory=_now)
    updated_at: datetime | None = None

    def __post_init__(self) -> None:
        self.name = self._clean(self.name)
        if self.updated_at is None:
            self.updated_at = self.created_at

    def rename(self, name: str) -> None:
        """Replace the label."""
        self.name = self._clean(name)
        self.updated_at = _now()

    def archive(self) -> None:
        """Hide the category from the dropdowns."""
        self.active = False
        self.updated_at = _now()

    def restore(self) -> None:
        """Show the category again."""
        self.active = True
        self.updated_at = _now()

    @staticmethod
    def _clean(name: str) -> str:
        candidate = name.strip()
        if not candidate:
            raise ValueError("A category name must not be empty")
        if len(candidate) > MAX_NAME:
            raise ValueError(f"A category name must be {MAX_NAME} characters or fewer")
        return candidate
```

main — Python · UTF-8 · LF · lines 22–58

2.9 Shortlist

backend/app/domain/shortlist.py · lines 17–68

The saved projects of one customer, oldest first.

Attribute	Type	Default
customer_id	str	—
project_ids	list[str]	field(default_factory=list)
id	str	field(default_factory=lambda: str(uuid4()))
created_at	datetime	field(default_factory=lambda: datetime.now(timezone.utc))
updated_at	datetime | None	None

Method	Purpose	Lines

`def __post_init__() -> None`	Drop blank and repeated entries, and refuse an oversized list.	26–36
`def add(project_id: str) -> bool`	Save a project. Returns ``False`` when it was already saved.	38–49
`def remove(project_id: str) -> bool`	Drop a project. Returns ``False`` when it was not saved.	51–58
`def contains(project_id: str) -> bool`	Return whether the project is saved.	60–62
`def __len__() -> int`		64–65
`def _touch() -> None`		67–68

shortlist.py — backend/app/domain/shortlist.py — CSIT314

backend › app › domain › shortlist.py › Shortlist

```python
# backend/app/domain/shortlist.py — lines 17–68, signatures only
@dataclass
class Shortlist:
    """The saved projects of one customer, oldest first."""
    customer_id: str
    project_ids: list[str] = field(default_factory=list)
    id: str = field(default_factory=lambda: str(uuid4()))
    created_at: datetime = field(default_factory=lambda: datetime.now(timezone.utc))
    updated_at: datetime | None = None

    def __post_init__() -> None
        """Drop blank and repeated entries, and refuse an oversized list."""
    def add(project_id: str) -> bool
        """Save a project. Returns ``False`` when it was already saved."""
    def remove(project_id: str) -> bool
        """Drop a project. Returns ``False`` when it was not saved."""
    def contains(project_id: str) -> bool
        """Return whether the project is saved."""
    def __len__() -> int
    def _touch() -> None
```

main — Python · UTF-8 · LF · lines 17–68

2.10 Role

backend/app/domain/enums.py · lines 8–24

Extends str, Enum.

The kind of actor an account represents.

Method	Purpose	Lines
`def is_privileged() -> bool`	Return ``True`` for the platform oversight roles.	17–19
`def can_self_register() -> bool`	Return ``True`` when a visitor may pick this role at sign up.	22–24

enums.py — backend/app/domain/enums.py — CSIT314

backend › app › domain › enums.py › Role

```python
class Role(str, Enum):
    """The kind of actor an account represents."""

    CUSTOMER = "CUSTOMER"
    DESIGNER = "DESIGNER"
    ADMIN = "ADMIN"
    PLATFORM_MANAGER = "PLATFORM_MANAGER"

    @property
    def is_privileged(self) -> bool:
        """Return ``True`` for the platform oversight roles."""
        return self in PRIVILEGED_ROLES

    @property
    def can_self_register(self) -> bool:
        """Return ``True`` when a visitor may pick this role at sign up."""
        return self in SELF_REGISTRATION_ROLES
```

main — Python · UTF-8 · LF · lines 8–24

2.11 AccountStatus

backend/app/domain/enums.py · lines 27–32

Extends str, Enum.

Where an account sits in its approval lifecycle.

enums.py — backend/app/domain/enums.py — CSIT314

backend › app › domain › enums.py › AccountStatus

```python
class AccountStatus(str, Enum):
    """Where an account sits in its approval lifecycle."""

    PENDING = "PENDING"
    ACTIVE = "ACTIVE"
    SUSPENDED = "SUSPENDED"
```

main — Python · UTF-8 · LF · lines 27–32

2.12 ProjectStatus

backend/app/domain/enums.py · lines 35–40

Extends str, Enum.

Where a project sits in its life.

enums.py — backend/app/domain/enums.py — CSIT314

backend › app › domain › enums.py › ProjectStatus

```python
class ProjectStatus(str, Enum):
    """Where a project sits in its life."""

    CURRENT = "CURRENT"
    PAST = "PAST"
    TAKEN_DOWN = "TAKEN_DOWN"
```

main — Python · UTF-8 · LF · lines 35–40

2.13 QuoteRequestState

backend/app/domain/enums.py · lines 43–52

Extends str, Enum.

Where a customer's quote request sits.

enums.py — backend/app/domain/enums.py — CSIT314

backend › app › domain › enums.py › QuoteRequestState

```python
class QuoteRequestState(str, Enum):
    """Where a customer's quote request sits."""

    PENDING = "PENDING"
    ANSWERED = "ANSWERED"
    ACCEPTED = "ACCEPTED"
    DECLINED = "DECLINED"
    CANCELLED = "CANCELLED"
    REFUSED = "REFUSED"
    EXPIRED = "EXPIRED"
```

main — Python · UTF-8 · LF · lines 43–52

2.14 QuoteState

backend/app/domain/enums.py · lines 55–62

Extends str, Enum.

Where one priced answer sits.

enums.py — backend/app/domain/enums.py — CSIT314

backend › app › domain › enums.py › QuoteState

```python
class QuoteState(str, Enum):
    """Where one priced answer sits."""

    OFFERED = "OFFERED"
    ACCEPTED = "ACCEPTED"
    DECLINED = "DECLINED"
    SUPERSEDED = "SUPERSEDED"
    EXPIRED = "EXPIRED"
```


main — Python · UTF-8 · LF · lines 55–62

2.15 AppointmentState

backend/app/domain/enums.py · lines 65–70

Extends str, Enum.

Where one consultation booking sits.




2.16 ConsultationMode

backend/app/domain/enums.py · lines 73–77

Extends str, Enum.

How the consultation happens.




2.17 ReportStatus

backend/app/domain/enums.py · lines 80–85

Extends str, Enum.

Where one project report sits.



2.18 DomainError

backend/app/domain/errors.py · lines 12–19

Extends Exception.

Base class for every recoverable business rule failure.

Attribute	Type	Default
default_message	str	'The request breaks a business rule.'

Method	Purpose	Lines
def __init__(message: str | None = None) -> None		17–19

errors.py — backend/app/domain/errors.py — CSIT314

backend › app › domain › errors.py › DomainError

```python
class DomainError(Exception):
    """Base class for every recoverable business rule failure."""

    default_message: str = "The request breaks a business rule."

    def __init__(self, message: str | None = None) -> None:
        self.message: str = message or self.default_message
        super().__init__(self.message)
```

main — Python · UTF-8 · LF · lines 12–19

2.19 EmailAlreadyRegistered

backend/app/domain/errors.py · lines 22–25

Extends DomainError.

An account with the same email address already exists.

errors.py — backend/app/domain/errors.py — CSIT314

backend › app › domain › errors.py › EmailAlreadyRegistered

```python
class EmailAlreadyRegistered(DomainError):
    """An account with the same email address already exists."""

    default_message = "Email is already registered"
```

main — Python · UTF-8 · LF · lines 22–25

2.20 InvalidCredentials

backend/app/domain/errors.py · lines 28–31

Extends DomainError.

The supplied email and password do not identify an account.

errors.py — backend/app/domain/errors.py — CSIT314

backend › app › domain › errors.py › InvalidCredentials

```python
class InvalidCredentials(DomainError):
    """The supplied email and password do not identify an account."""

    default_message = "Invalid email or password"
```

main — Python · UTF-8 · LF · lines 28–31

2.21 AccountNotActive

backend/app/domain/errors.py · lines 34–41

Extends DomainError.

The account exists but its status forbids signing in.

Method	Purpose	Lines
`def __init__(status: AccountStatus) -> None`		39–41

errors.py — backend/app/domain/errors.py — CSIT314

backend › app › domain › errors.py › AccountNotActive

```
34 class AccountNotActive(DomainError):
35     """The account exists but its status forbids signing in."""
36
37     default_message = "Account cannot sign in"
38
39     def __init__(self, status: AccountStatus) -> None:
40         self.status: AccountStatus = status
41         super().__init__(inactive_message(status))
```

main — Python · UTF-8 · LF · lines 34–41

2.22 InvalidRoleForSelfRegistration

backend/app/domain/errors.py · lines 53–56

Extends DomainError.

A visitor tried to register with a staff only role.

errors.py — backend/app/domain/errors.py — CSIT314

backend › app › domain › errors.py › InvalidRoleForSelfRegistration

```
53 class InvalidRoleForSelfRegistration(DomainError):
54     """A visitor tried to register with a staff only role."""
55
56     default_message = "This role cannot be chosen at registration"
```

main — Python · UTF-8 · LF · lines 53–56

2.23 WeakPassword

backend/app/domain/errors.py · lines 59–62

Extends DomainError.

The chosen password does not meet the minimum length.

errors.py — backend/app/domain/errors.py — CSIT314

backend › app › domain › errors.py › WeakPassword

```
59 class WeakPassword(DomainError):
60     """The chosen password does not meet the minimum length."""
61
62     default_message = "Password must be at least 8 characters"
```

main — Python · UTF-8 · LF · lines 59–62

2.24 NotPermitted

backend/app/domain/errors.py · lines 65–68

Extends DomainError.

The caller may not perform this operation.

errors.py — backend/app/domain/errors.py — CSIT314

backend › app › domain › errors.py › NotPermitted

```python
class NotPermitted(DomainError):
    """The caller may not perform this operation."""

    default_message = "You are not allowed to do that"
```

main — Python · UTF-8 · LF · lines 65–68

2.25 AccountNotFound

backend/app/domain/errors.py · lines 71–74

Extends DomainError.

No account matches the supplied identifier.

errors.py — backend/app/domain/errors.py — CSIT314

backend › app › domain › errors.py › AccountNotFound

```python
class AccountNotFound(DomainError):
    """No account matches the supplied identifier."""

    default_message = "Account not found"
```

main — Python · UTF-8 · LF · lines 71–74

2.26 CompanyAlreadyExists

backend/app/domain/errors.py · lines 77–80

Extends DomainError.

The designer already holds a company profile.

errors.py — backend/app/domain/errors.py — CSIT314

backend › app › domain › errors.py › CompanyAlreadyExists

```python
class CompanyAlreadyExists(DomainError):
    """The designer already holds a company profile."""

    default_message = "This designer already has a company profile"
```

main — Python · UTF-8 · LF · lines 77–80

2.27 CompanyNotFound

backend/app/domain/errors.py · lines 83–86

Extends DomainError.

No company profile matches the request.

errors.py — backend/app/domain/errors.py — CSIT314

backend › app › domain › errors.py › CompanyNotFound

```python
class CompanyNotFound(DomainError):
    """No company profile matches the request."""

    default_message = "Company profile not found"
```

main — Python · UTF-8 · LF · lines 83–86

2.28 ProjectNotFound

backend/app/domain/errors.py · lines 89–92

Extends DomainError.

No project matches the request.

errors.py — backend/app/domain/errors.py — CSIT314

backend › app › domain › errors.py › ProjectNotFound

```python
class ProjectNotFound(DomainError):
    """No project matches the request."""

    default_message = "Project not found"
```

main — Python · UTF-8 · LF · lines 89–92

2.29 QuoteRequestNotFound

backend/app/domain/errors.py · lines 95–98

Extends DomainError.

No quote request matches the request.

errors.py — backend/app/domain/errors.py — CSIT314

backend › app › domain › errors.py › QuoteRequestNotFound

```python
class QuoteRequestNotFound(DomainError):
    """No quote request matches the request."""

    default_message = "Quote request not found"
```

main — Python · UTF-8 · LF · lines 95–98

2.30 QuoteNotFound

backend/app/domain/errors.py · lines 101–104

Extends DomainError.

No quote matches the request.

errors.py — backend/app/domain/errors.py — CSIT314

backend › app › domain › errors.py › QuoteNotFound

```python
class QuoteNotFound(DomainError):
    """No quote matches the request."""

    default_message = "Quote not found"
```

main — Python · UTF-8 · LF · lines 101–104

2.31 AppointmentNotFound

backend/app/domain/errors.py · lines 107–110

Extends DomainError.

No consultation appointment matches the request.

errors.py — backend/app/domain/errors.py — CSIT314

backend › app › domain › errors.py › AppointmentNotFound

```python
class AppointmentNotFound(DomainError):
    """No consultation appointment matches the request."""

    default_message = "Appointment not found"
```

main — Python · UTF-8 · LF · lines 107–110

2.32 ReportNotFound

backend/app/domain/errors.py · lines 113–116

Extends DomainError.

No project report matches the request.

errors.py — backend/app/domain/errors.py — CSIT314

backend › app › domain › errors.py › ReportNotFound

```python
class ReportNotFound(DomainError):
    """No project report matches the request."""

    default_message = "Report not found"
```

main — Python · UTF-8 · LF · lines 113–116

2.33 InvalidState

backend/app/domain/errors.py · lines 119–122

Extends DomainError.

The record is in a state that does not allow this action.

errors.py backend/app/domain/errors.py — CSIT314

backend › app › domain › errors.py › InvalidState

```
119  class InvalidState(DomainError):
120      """The record is in a state that does not allow this action."""
121
122      default_message = "The record is not in a state that allows this action"
```

main Python · UTF-8 · LF · lines 119–122

2.34 ProjectReport

backend/app/domain/report.py · lines 32–69

One complaint, from the customer who raised it.

Attribute	Type	Default
customer_id	str	—
project_id	str	—
reason	str	—
comments	str	''
status	ReportStatus	ReportStatus.OPEN
created_at	datetime	field(default_factory=_now)
resolved_at	datetime | None	None
id	str	field(default_factory=lambda: str(uuid4()))

Method	Purpose	Lines
def __post_init__() -> None	Check the identifiers, the reason and the comments.	44–57
def is_open() -> bool	Return ``True`` until staff close the report.	60–62
def close(actioned: bool) -> None	Close the report, with a note of whether anything was done.	64–69

report.py — backend/app/domain/report.py — CSIT314

backend › app › domain › report.py › ProjectReport

```python
class ProjectReport:
    """One complaint, from the customer who raised it."""

    customer_id: str
    project_id: str
    reason: str
    comments: str = ""
    status: ReportStatus = ReportStatus.OPEN
    created_at: datetime = field(default_factory=_now)
    resolved_at: datetime | None = None
    id: str = field(default_factory=lambda: str(uuid4()))

    def __post_init__(self) -> None:
        """Check the identifiers, the reason and the comments."""
        if not self.customer_id.strip():
            raise ValueError("A report needs a customer")
        if not self.project_id.strip():
            raise ValueError("A report needs a project")
        self.reason = self.reason.strip()
        if self.reason not in REPORT_REASONS:
            raise ValueError("Choose one of the listed reasons")
        self.comments = self.comments.strip()
        if len(self.comments) > MAX_COMMENTS:
            raise ValueError(
                f"Comments must be {MAX_COMMENTS} characters or fewer"
            )

    @property
    def is_open(self) -> bool:
        """Return ``True`` until staff close the report."""
        return self.status is ReportStatus.OPEN

    def close(self, actioned: bool) -> None:
        """Close the report, with a note of whether anything was done."""
        if self.status is not ReportStatus.OPEN:
            raise ValueError("This report is already closed")
        self.status = ReportStatus.ACTIONED if actioned else ReportStatus.DISMISSED
        self.resolved_at = _now()
```

main — Python · UTF-8 · LF · lines 32–69

2.35 ConsultationAppointment

backend/app/domain/appointment.py · lines 55–122

One slot a customer asked a designer to keep.

Attribute	Type	Default
customer_id	str	—
company_id	str	—
appointment_date	date	—
appointment_time	str	—
location	str	''
mode	ConsultationMode	ConsultationMode.IN_PERSON
requirements	str	''
state	AppointmentState	AppointmentState.PENDING

notified_at	datetime | None	None
created_at	datetime	field(default_factory=_now)
updated_at	datetime | None	None
id	str	field(default_factory=lambda: str(uuid4()))

Method	Purpose	Lines
def __post_init__() -> None	Check the identifiers, the slot and the day.	71–92
def is_open() -> bool	Return ``True`` while the slot still blocks the diary.	95–97
def is_pending() -> bool	Return ``True`` until the designer answers.	99–101
def accept() -> None	The designer confirms the slot.	103–108
def cancel() -> None	Either party gives the slot back.	110–115
def mark_notified() -> None	Record that the designer was told about the new booking.	117–119
def _touch() -> None		121–122

appointment.py — backend/app/domain/appointment.py — CSIT314

backend › app › domain › appointment.py › ConsultationAppointment

```python
# backend/app/domain/appointment.py — lines 55–122, signatures only
@dataclass
class ConsultationAppointment:
    """One slot a customer asked a designer to keep."""
    customer_id: str
    company_id: str
    appointment_date: date
    appointment_time: str
    location: str = ''
    mode: ConsultationMode = ConsultationMode.IN_PERSON
    requirements: str = ''
    state: AppointmentState = AppointmentState.PENDING
    notified_at: datetime | None = None
    created_at: datetime = field(default_factory=_now)
    updated_at: datetime | None = None
    id: str = field(default_factory=lambda: str(uuid4()))

    def __post_init__() -> None
        """Check the identifiers, the slot and the day."""
    @property
    def is_open() -> bool
        """Return ``True`` while the slot still blocks the diary."""
    def is_pending() -> bool
        """Return ``True`` until the designer answers."""
    def accept() -> None
        """The designer confirms the slot."""
    def cancel() -> None
        """Either party gives the slot back."""
    def mark_notified() -> None
        """Record that the designer was told about the new booking."""
    def _touch() -> None
```

main — Python · UTF-8 · LF · lines 55–122

3 Entity access: backend/app/repositories

A repository hides the store. A use case asks for 'the project with this id' and the repository answers with an entity, or with NotFound. Swapping the in-memory store for a database would change only these classes.

3.1 AccountRepository

backend/app/repositories/account_repository.py · lines 10–59

Keeps every account in process memory.

Method	Purpose	Lines
`def __init__() -> None`		18–21
`def add(account: Account) -> bool`	Store ``account`` unless its email is already taken.	23–35
`def get(account_id: str) -> Account | None`	Return the account with ``account_id``, or ``None``.	37–39
`def get_by_email(email: str) -> Account | None`	Return the account registered under ``email``, or ``None``.	41–46
`def list_all() -> list[Account]`	Return every stored account.	48–50
`def count() -> int`	Return how many accounts are stored.	52–54
`def clear() -> None`	Remove every stored account.	56–59

account_repository.py — backend/app/repositories/account_repository.py — CSIT314

backend › app › repositories › account_repository.py › AccountRepository

```python
# backend/app/repositories/account_repository.py — lines 10-59, signatures only
class AccountRepository:
    """Keeps every account in process memory."""
    def __init__() -> None
    def add(account: Account) -> bool
        """Store ``account`` unless its email is already taken."""
    def get(account_id: str) -> Account | None
        """Return the account with ``account_id``, or ``None``."""
    def get_by_email(email: str) -> Account | None
        """Return the account registered under ``email``, or ``None``."""
    def list_all() -> list[Account]
        """Return every stored account."""
    def count() -> int
        """Return how many accounts are stored."""
    def clear() -> None
        """Remove every stored account."""
```

main — Python · UTF-8 · LF · lines 10–59

3.2 AppointmentRepository

backend/app/repositories/appointment_repository.py · lines 12–86

Keeps every appointment in process memory, keyed by id.

Method	Purpose	Lines
`def __init__() -> None`		15–17
`def add(appointment: ConsultationAppointment) -> bool`	Store ``appointment`` unless its id is already present.	19–25
`def add_if_free(appointment: ConsultationAppointment) -> bool`	Store ``appointment`` only when the slot is still free.	27–45
`def get(appointment_id: str) -> ConsultationAppointment | None`	Return the appointment with ``appointment_id``, or ``None``.	47–49
`def list_by_customer(customer_id: str) -> list[ConsultationAppointment]`	Return the appointments one customer booked.	51–57
`def list_by_company(company_id: str) ->`	Return the appointments one company	59–63

`list[ConsultationAppointment]`	received.	
`def taken_times(company_id: str, day: date) -> set[str]`	Return the times already held on one company's day.	65–74
`def list_all() -> list[ConsultationAppointment]`	Return every stored appointment.	76–78
`def count() -> int`	Return how many appointments are stored.	80–82
`def clear() -> None`	Remove every stored appointment.	84–86

appointment_repository.py — backend/app/repositories/appointment_repository.py — CSIT314

backend › app › repositories › appointment_repository.py › AppointmentRepository

```python
# backend/app/repositories/appointment_repository.py — lines 12-86, signatures only
class AppointmentRepository:
    """Keeps every appointment in process memory, keyed by id."""
    def __init__() -> None
    def add(appointment: ConsultationAppointment) -> bool
        """Store ``appointment`` unless its id is already present."""
    def add_if_free(appointment: ConsultationAppointment) -> bool
        """Store ``appointment`` only when the slot is still free."""
    def get(appointment_id: str) -> ConsultationAppointment | None
        """Return the appointment with ``appointment_id``, or ``None``."""
    def list_by_customer(customer_id: str) -> list[ConsultationAppointment]
        """Return the appointments one customer booked."""
    def list_by_company(company_id: str) -> list[ConsultationAppointment]
        """Return the appointments one company received."""
    def taken_times(company_id: str, day: date) -> set[str]
        """Return the times already held on one company's day."""
    def list_all() -> list[ConsultationAppointment]
        """Return every stored appointment."""
    def count() -> int
        """Return how many appointments are stored."""
    def clear() -> None
        """Remove every stored appointment."""
```


main — Python · UTF-8 · LF · lines 12–86

3.3 CategoryRepository

backend/app/repositories/category_repository.py · lines 11–62

Keeps every category, active or archived.

Method	Purpose	Lines
`def __init__() -> None`		14–17
`def reset_defaults() -> None`	Replace the store with the ten default categories.	19–25
`def list_all() -> list[Category]`	Return every category, sorted by name.	27–29
`def list_active() -> list[Category]`	Return the categories a dropdown should show.	31–33
`def get(category_id: str) -> Category | None`	Return the category with ``category_id``, or ``None``.	35–37
`def find_by_name(name: str) -> Category | None`	Return the category whose label matches, ignoring case.	39–45
`def add(category: Category) -> bool`	Store a category unless its id or its name is already present.	47–58
`def count() -> int`	Return how many categories exist.	60–62



3.4 CompanyRepository

backend/app/repositories/company_repository.py · lines 10–57

Keeps every company in process memory.

Method	Purpose	Lines
`def __init__() -> None`		18–21
`def add(company: Company) -> bool`	Store ``company`` unless its designer already has one.	23–33
`def get(company_id: str) -> Company | None`	Return the company with ``company_id``, or ``None``.	35–37
`def get_by_owner(owner_id: str) -> Company | None`	Return the company owned by ``owner_id``, or ``None``.	39–44
`def list_all() -> list[Company]`	Return every stored company.	46–48
`def count() -> int`	Return how many companies are stored.	50–52
`def clear() -> None`	Remove every stored company.	54–57

company_repository.py — backend/app/repositories/company_repository.py — CSIT314

backend › app › repositories › company_repository.py › CompanyRepository

```python
# backend/app/repositories/company_repository.py — lines 10-57, signatures only
class CompanyRepository:
    """Keeps every company in process memory."""
    def __init__() -> None
    def add(company: Company) -> bool
        """Store ``company`` unless its designer already has one."""
    def get(company_id: str) -> Company | None
        """Return the company with ``company_id``, or ``None``."""
    def get_by_owner(owner_id: str) -> Company | None
        """Return the company owned by ``owner_id``, or ``None``."""
    def list_all() -> list[Company]
        """Return every stored company."""
    def count() -> int
        """Return how many companies are stored."""
    def clear() -> None
        """Remove every stored company."""
```

main — Python · UTF-8 · LF · lines 10–57

3.5 ProjectRepository

backend/app/repositories/project_repository.py · lines 10–57

Keeps every project in process memory, keyed by id.

Method	Purpose	Lines
`def __init__() -> None`		16–18
`def add(project: Project) -> bool`	Store ``project`` unless its id is already present.	20–26
`def get(project_id: str) -> Project | None`	Return the project with ``project_id``, or ``None``.	28–30
`def list_by_owner(owner_id: str) -> list[Project]`	Return the projects owned by ``owner_id``.	32–34
`def list_by_company(company_id: str) -> list[Project]`	Return the projects published under ``company_id``.	36–40
`def list_all() -> list[Project]`	Return every stored project.	42–44
`def count() -> int`	Return how many projects are stored.	46–48
`def remove(project_id: str) -> bool`	Drop the project with ``project_id``. Returns whether it was present.	50–53
`def clear() -> None`	Remove every stored project.	55–57

project_repository.py — backend/app/repositories/project_repository.py — CSIT314

backend › app › repositories › project_repository.py › ProjectRepository

```python
# backend/app/repositories/project_repository.py — lines 10–57, signatures only
class ProjectRepository:
    """Keeps every project in process memory, keyed by id."""
    def __init__() -> None
    def add(project: Project) -> bool
        """Store ``project`` unless its id is already present."""
    def get(project_id: str) -> Project | None
        """Return the project with ``project_id``, or ``None``."""
    def list_by_owner(owner_id: str) -> list[Project]
        """Return the projects owned by ``owner_id``."""
    def list_by_company(company_id: str) -> list[Project]
        """Return the projects published under ``company_id``."""
    def list_all() -> list[Project]
        """Return every stored project."""
    def count() -> int
        """Return how many projects are stored."""
    def remove(project_id: str) -> bool
        """Drop the project with ``project_id``. Returns whether it was present."""
    def clear() -> None
        """Remove every stored project."""
```

main — Python · UTF-8 · LF · lines 10–57

3.6 QuoteRequestRepository

backend/app/repositories/quote_repository.py · lines 11–48

Keeps every request in process memory, keyed by id.

Method	Purpose	Lines
`def __init__() -> None`		14–16
`def add(request: QuoteRequest) -> bool`	Store ``request`` unless its id is already present.	18–24
`def get(request_id: str) -> QuoteRequest | None`	Return the request with ``request_id``, or ``None``.	26–28
`def list_by_customer(customer_id: str) -> list[QuoteRequest]`	Return the requests a customer sent.	30–32
`def list_by_company(company_id: str) -> list[QuoteRequest]`	Return the requests a company received.	34–36
`def list_all() -> list[QuoteRequest]`	Return every stored request.	38–40
`def count() -> int`	Return how many requests are stored.	42–44
`def clear() -> None`	Remove every stored request.	46–48

quote_repository.py — backend/app/repositories/quote_repository.py — CSIT314

backend › app › repositories › quote_repository.py › QuoteRequestRepository

```python
class QuoteRequestRepository:
    """Keeps every request in process memory, keyed by id."""

    def __init__(self) -> None:
        self._by_id: dict[str, QuoteRequest] = {}
        self._lock = threading.Lock()

    def add(self, request: QuoteRequest) -> bool:
        """Store ``request`` unless its id is already present."""
        with self._lock:
            if request.id in self._by_id:
                return False
            self._by_id[request.id] = request
            return True

    def get(self, request_id: str) -> QuoteRequest | None:
        """Return the request with ``request_id``, or ``None``."""
        return self._by_id.get(request_id)

    def list_by_customer(self, customer_id: str) -> list[QuoteRequest]:
        """Return the requests a customer sent."""
        return [entry for entry in self._by_id.values() if entry.customer_id == customer_id]

    def list_by_company(self, company_id: str) -> list[QuoteRequest]:
        """Return the requests a company received."""
        return [entry for entry in self._by_id.values() if entry.company_id == company_id]

    def list_all(self) -> list[QuoteRequest]:
        """Return every stored request."""
        return list(self._by_id.values())

    def count(self) -> int:
        """Return how many requests are stored."""
        return len(self._by_id)

    def clear(self) -> None:
        """Remove every stored request."""
        self._by_id.clear()
```

main — Python · UTF-8 · LF · lines 11–48

3.7 QuoteRepository

backend/app/repositories/quote_repository.py · lines 51–92

Keeps every quote version, keyed by id.

Method	Purpose	Lines
`def __init__() -> None`		54–56
`def add(quote: Quote) -> bool`	Store ``quote`` unless its id is already present.	58–64
`def get(quote_id: str) -> Quote | None`	Return the quote with ``quote_id``, or ``None``.	66–68
`def list_by_request(request_id: str) -> list[Quote]`	Return every version of a request's quote, oldest first.	70–75
`def latest_for_request(request_id: str) -> Quote | None`	Return the newest version of a request's quote.	77–80
`def list_all() -> list[Quote]`	Return every stored quote.	82–84
`def count() -> int`	Return how many quotes are stored.	86–88

`def clear() -> None`	Remove every stored quote.	90–92

quote_repository.py — backend/app/repositories/quote_repository.py — CSIT314

backend › app › repositories › quote_repository.py › QuoteRepository

```python
class QuoteRepository:
    """Keeps every quote version, keyed by id."""

    def __init__(self) -> None:
        self._by_id: dict[str, Quote] = {}
        self._lock = threading.Lock()

    def add(self, quote: Quote) -> bool:
        """Store ``quote`` unless its id is already present."""
        with self._lock:
            if quote.id in self._by_id:
                return False
            self._by_id[quote.id] = quote
            return True

    def get(self, quote_id: str) -> Quote | None:
        """Return the quote with ``quote_id``, or ``None``."""
        return self._by_id.get(quote_id)

    def list_by_request(self, request_id: str) -> list[Quote]:
        """Return every version of a request's quote, oldest first."""
        versions = [
            entry for entry in self._by_id.values() if entry.request_id == request_id
        ]
        return sorted(versions, key=lambda entry: entry.version)

    def latest_for_request(self, request_id: str) -> Quote | None:
        """Return the newest version of a request's quote."""
        versions = self.list_by_request(request_id)
        return versions[-1] if versions else None

    def list_all(self) -> list[Quote]:
        """Return every stored quote."""
        return list(self._by_id.values())

    def count(self) -> int:
        """Return how many quotes are stored."""
        return len(self._by_id)

    def clear(self) -> None:
        """Remove every stored quote."""
        self._by_id.clear()
```

main — Python · UTF-8 · LF · lines 51–92

3.8 ReportRepository

backend/app/repositories/report_repository.py · lines 10–53

Keeps every project report in process memory, keyed by id.

Method	Purpose	Lines
`def __init__() -> None`		13–15
`def add(report: ProjectReport) -> bool`	Store ``report`` unless its id is already present.	17–23
`def get(report_id: str) -> ProjectReport | None`	Return the report with ``report_id``, or ``None``.	25–27

`def list_by_customer(customer_id: str) -> list[ProjectReport]`	Return the reports one customer raised.	29–35
`def list_by_project(project_id: str) -> list[ProjectReport]`	Return the reports raised about one project.	37–41
`def list_all() -> list[ProjectReport]`	Return every stored report.	43–45
`def count() -> int`	Return how many reports are stored.	47–49
`def clear() -> None`	Remove every stored report.	51–53

report_repository.py — backend/app/repositories/report_repository.py — CSIT314

backend › app › repositories › report_repository.py › ReportRepository · part 1 of 2

```python
class ReportRepository:
    """Keeps every project report in process memory, keyed by id."""

    def __init__(self) -> None:
        self._by_id: dict[str, ProjectReport] = {}
        self._lock = threading.Lock()

    def add(self, report: ProjectReport) -> bool:
        """Store ``report`` unless its id is already present."""
        with self._lock:
            if report.id in self._by_id:
                return False
            self._by_id[report.id] = report
            return True

    def get(self, report_id: str) -> ProjectReport | None:
        """Return the report with ``report_id``, or ``None``."""
        return self._by_id.get(report_id)

    def list_by_customer(self, customer_id: str) -> list[ProjectReport]:
        """Return the reports one customer raised."""
        return [
            entry
            for entry in self._by_id.values()
            if entry.customer_id == customer_id
        ]

    def list_by_project(self, project_id: str) -> list[ProjectReport]:
        """Return the reports raised about one project."""
        return [
            entry for entry in self._by_id.values() if entry.project_id == project_id
        ]

    def list_all(self) -> list[ProjectReport]:
        """Return every stored report."""
        return list(self._by_id.values())

    def count(self) -> int:
        """Return how many reports are stored."""
        return len(self._by_id)

    def clear(self) -> None:
```

main — Python · UTF-8 · LF · lines 10–53 · part 1 of 2

report_repository.py — backend/app/repositories/report_repository.py — CSIT314

backend › app › repositories › report_repository.py › ReportRepository · part 2 of 2

```
        """Remove every stored report."""
        self._by_id.clear()
```

main — Python · UTF-8 · LF · lines 10–53 · part 2 of 2

3.9 ShortlistRepository

backend/app/repositories/shortlist_repository.py · lines 10–35

Keeps one shortlist per customer id.

Method	Purpose	Lines
`def __init__() -> None`		13–15
`def add(shortlist: Shortlist) -> bool`	Store ``shortlist`` unless that customer already has one.	17–23
`def get_by_customer(customer_id: str) -> Shortlist | None`	Return the shortlist of ``customer_id``, or ``None``.	25–27
`def count() -> int`	Return how many shortlists exist.	29–31
`def clear() -> None`	Remove every shortlist.	33–35

shortlist_repository.py — backend/app/repositories/shortlist_repository.py — CSIT314

backend › app › repositories › shortlist_repository.py › ShortlistRepository

```
class ShortlistRepository:
    """Keeps one shortlist per customer id."""

    def __init__(self) -> None:
        self._by_customer: dict[str, Shortlist] = {}
        self._lock = threading.Lock()

    def add(self, shortlist: Shortlist) -> bool:
        """Store ``shortlist`` unless that customer already has one."""
        with self._lock:
            if shortlist.customer_id in self._by_customer:
                return False
            self._by_customer[shortlist.customer_id] = shortlist
            return True

    def get_by_customer(self, customer_id: str) -> Shortlist | None:
        """Return the shortlist of ``customer_id``, or ``None``."""
        return self._by_customer.get(customer_id)

    def count(self) -> int:
        """Return how many shortlists exist."""
        return len(self._by_customer)

    def clear(self) -> None:
        """Remove every shortlist."""
        self._by_customer.clear()
```

main — Python · UTF-8 · LF · lines 10–35

4 Control: backend/app/services

A service is one use case. It checks permission, loads entities through the repositories, calls entity methods, and returns a result the API layer can send.

4.1 AccountService

backend/app/services/account_service.py · lines 31–141

Applies account business rules on top of the repository.

Method	Purpose	Lines
`def __init__(repository: AccountRepository) -> None`		34–35
`def register(email: str, password: str, display_name: str, role: Role) -> Account`	Create an account and store it.	37–54
`def authenticate(email: str, password: str) -> Account`	Return the account matching ``email`` and ``password``.	56–70
`def get(account_id: str) -> Account | None`	Return the account with ``account_id``, or ``None``.	72–74
`def list_accounts(actor: Account, status: AccountStatus | None = None) -> list[Account]`	Return accounts for an administrator, newest first.	76–84
`def approve(actor: Account, account_id: str) -> Account`	Activate an account so it may sign in.	86–90
`def suspend(actor: Account, account_id: str) -> Account`	Suspend an account so it cannot sign in again.	92–96
`def ensure_staff_account(email: str, password: str, display_name: str, role: Role) -> Account | None`	Create a staff account when the address is free.	98–117
`def _require_admin(actor: Account) -> None`		120–122
`def _require_target(actor: Account, account_id: str) -> Account`		124–131
`def _require_self_registration_role(role: Role) -> None`		134–136
`def _require_strong_password(password: str) -> None`		139–141

account_service.py — backend/app/services/account_service.py — CSIT314

backend › app › services › account_service.py › AccountService

```python
# backend/app/services/account_service.py — lines 31–141, signatures only
class AccountService:
    """Applies account business rules on top of the repository."""
    def __init__(repository: AccountRepository) -> None
    def register(email: str, password: str, display_name: str, role: Role) -> Account
        """Create an account and store it."""
    def authenticate(email: str, password: str) -> Account
        """Return the account matching ``email`` and ``password``."""
    def get(account_id: str) -> Account | None
        """Return the account with ``account_id``, or ``None``."""
    def list_accounts(actor: Account, status: AccountStatus | None = None) -> list[Account]
        """Return accounts for an administrator, newest first."""
    def approve(actor: Account, account_id: str) -> Account
        """Activate an account so it may sign in."""
    def suspend(actor: Account, account_id: str) -> Account
        """Suspend an account so it cannot sign in again."""
    def ensure_staff_account(email: str, password: str, display_name: str, role: Role) -> Account | None
        """Create a staff account when the address is free."""
    @staticmethod
    def _require_admin(actor: Account) -> None
    def _require_target(actor: Account, account_id: str) -> Account
    @staticmethod
    def _require_self_registration_role(role: Role) -> None
    @staticmethod
    def _require_strong_password(password: str) -> None
```


main — Python · UTF-8 · LF · lines 31–141

4.2 AppointmentService

backend/app/services/appointment_service.py · lines 40–220

Applies the booking rules on top of the three stores.

Method	Purpose	Lines
`def __init__(appointments: AppointmentRepository, companies: CompanyRepository, accounts: AccountRepository) -> None`		43–51
`def available_slots(actor: Account, company_id: str, day: date) -> list[str]`	Return the hours still free on one company's day.	55–64
`def book(actor: Account, company_id: str, day: date, time: str, mode: ConsultationMode = ConsultationMode.IN_PERSON, requirements: str = '') -> ConsultationAppointment`	Keep one slot for one customer, in person or on a call.	66–104
`def list_for_customer(actor: Account) -> list[ConsultationAppointment]`	Return the caller's appointments, soonest first.	106–110
`def cancel(actor: Account, appointment_id: str) -> ConsultationAppointment`	Return a slot to the diary. Either party may cancel.	112–121
`def list_for_designer(actor: Account) -> list[ConsultationAppointment]`	Return the appointments sent to the caller's company, soonest first.	125–128
`def accept(actor: Account, appointment_id: str) -> ConsultationAppointment`	Confirm a pending appointment.	130–140
`def may_read_call_link(actor: Account, company_id: str) -> bool`	Return ``True`` when the caller may see the video room address.	144–162
`def customer_name(appointment: ConsultationAppointment) -> str`	Return the customer's display name for the designer's list.	164–167
`def _cutoff(day: date) -> str`	Return the clock time before which today's slots are gone.	172–175
`def _sorted(appointments: list[ConsultationAppointment]) -> list[ConsultationAppointment]`		178–184
`def _get(appointment_id: str) -> ConsultationAppointment`		186–190
`def _may_cancel(actor: Account, appointment: ConsultationAppointment) -> bool`		192–198
`def _company_of(actor: Account)`		200–206
`def _notify_designer(appointment: ConsultationAppointment) -> None`	Tell the designer.	208–215
`def _require_customer(actor: Account) -> None`		218–220




4.3 CategoryNotFound

backend/app/services/category_service.py · lines 12–16

No category matches the supplied id.

Method	Purpose	Lines
`def __init__() -> None`		15–16




4.4 CategoryExists

backend/app/services/category_service.py · lines 19–23

A category with that label already exists.

Method	Purpose	Lines
`def __init__() -> None`		22–23



4.5 CategoryService

backend/app/services/category_service.py · lines 26–87

Applies the staff rules on top of the category store.

Method	Purpose	Lines
`def __init__(categories: CategoryRepository) -> None`		29–30
`def list_active() -> list[Category]`	Return the labels a dropdown should show.	32–34
`def list_all(actor: Account) -> list[Category]`	Return every category, archived ones included.	36–39
`def add(actor: Account, name: str) -> Category`	Create a category.	41–50
`def rename(actor: Account, category_id: str, name: str) -> Category`	Change a category label.	52–62
`def get(actor: Account, category_id: str) -> Category`	Return one category for staff.	64–70
`def set_active(actor: Account, category_id: str, active: bool) -> Category`	Archive or restore a category.	72–82
`def _require_staff(actor: Account) -> None`		85–87

category_service.py — backend/app/services/category_service.py — CSIT314

backend › app › services › category_service.py › CategoryService

```python
# backend/app/services/category_service.py — lines 26–87, signatures only
class CategoryService:
    """Applies the staff rules on top of the category store."""
    def __init__(categories: CategoryRepository) -> None
    def list_active() -> list[Category]
        """Return the labels a dropdown should show."""
    def list_all(actor: Account) -> list[Category]
        """Return every category, archived ones included."""
    def add(actor: Account, name: str) -> Category
        """Create a category."""
    def rename(actor: Account, category_id: str, name: str) -> Category
        """Change a category label."""
    def get(actor: Account, category_id: str) -> Category
        """Return one category for staff."""
    def set_active(actor: Account, category_id: str, active: bool) -> Category
        """Archive or restore a category."""
    @staticmethod
    def _require_staff(actor: Account) -> None
```


main — Python · UTF-8 · LF · lines 26–87

4.6 CompanyService

backend/app/services/company_service.py · lines 12–112

Applies the company profile rules on top of the repository.

Method	Purpose	Lines
`def __init__(companies: CompanyRepository) -> None`		15–16
`def create(actor: Account, name: str, description: str, contact_email: str, contact_phone: str, location: str, meeting_address: str = '', call_link: str = '', logo_url: str = '') -> Company`	Create the company profile for ``actor``.	18–50
`def get_for_owner(actor: Account) -> Company`	Return the profile owned by ``actor``.	52–58
`def update(actor: Account) -> Company`	Change only the fields that were supplied.	60–96
`def get(company_id: str) -> Company`	Return a company by id. Any signed in account may read it.	98–103
`def list_companies() -> list[Company]`	Return every company, sorted by name for a stable listing.	105–107
`def _require_designer(actor: Account) -> None`		110–112



4.7 ImageUnavailable

backend/app/services/image_source.py · lines 28–29

The photo cannot be read, or it must not be read.

image_source.py — backend/app/services/image_source.py — CSIT314

backend › app › services › image_source.py › ImageUnavailable

```
28  class ImageUnavailable(Exception):
29      """The photo cannot be read, or it must not be read."""
```

main — Python · UTF-8 · LF · lines 28–29

4.8 load_image_bytes()

backend/app/services/image_source.py · lines 32–39

Return the bytes of the photo that ``reference`` points at.

image_source.py — backend/app/services/image_source.py — CSIT314

backend › app › services › image_source.py › load_image_bytes

```
32  def load_image_bytes(reference: str, public_dir: Path) -> bytes:
33      """Return the bytes of the photo that ``reference`` points at."""
34      candidate = reference.strip()
35      if not candidate:
36          raise ImageUnavailable("The project has no photo to read")
37      if candidate.startswith("/"):
38          return _read_local(candidate, public_dir)
39      return _read_remote(candidate)
```

main — Python · UTF-8 · LF · lines 32–39

4.9 _read_local()

backend/app/services/image_source.py · lines 42–51

image_source.py — backend/app/services/image_source.py — CSIT314

backend › app › services › image_source.py › _read_local

```
42  def _read_local(reference: str, public_dir: Path) -> bytes:
43      root = public_dir.resolve()
44      target = (root / reference.lstrip("/")).resolve()
45      if target != root and root not in target.parents:
46          raise ImageUnavailable("The photo path leaves the public folder")
47      if not target.is_file():
48          raise ImageUnavailable("The photo is not in the public folder")
49      if target.stat().st_size > MAX_BYTES:
50          raise ImageUnavailable("The photo is larger than 5 MB")
51      return target.read_bytes()
```

main — Python · UTF-8 · LF · lines 42–51

4.10 _read_remote()

backend/app/services/image_source.py · lines 54–82

image_source.py — backend/app/services/image_source.py — CSIT314

backend › app › services › image_source.py › _read_remote

```python
def _read_remote(reference: str) -> bytes:
    parsed = urlparse(reference)
    if parsed.scheme not in ("http", "https") or not parsed.hostname:
        raise ImageUnavailable("Only http and https photo addresses are accepted")
    for address in _resolve(parsed.hostname):
        if not _is_public(address):
            raise ImageUnavailable("The photo host is not a public address")

    chunks: list[bytes] = []
    size = 0
    try:
        with httpx.stream(
            "GET", reference, timeout=TIMEOUT_SECONDS, follow_redirects=False
        ) as response:
            if response.status_code != 200:
                raise ImageUnavailable("The photo could not be downloaded")
            content_type = (
                response.headers.get("content-type", "").split(";")[0].strip().lower()
            )
            if content_type not in ALLOWED_TYPES:
                raise ImageUnavailable("The address does not hold an image")
            for chunk in response.iter_bytes():
                size += len(chunk)
                if size > MAX_BYTES:
                    raise ImageUnavailable("The photo is larger than 5 MB")
                chunks.append(chunk)
    except httpx.HTTPError as exc:
        raise ImageUnavailable("The photo could not be downloaded") from exc
    return b"".join(chunks)
```

main — Python · UTF-8 · LF · lines 54–82

4.11 _resolve()

backend/app/services/image_source.py · lines 85–90

image_source.py — backend/app/services/image_source.py — CSIT314

backend › app › services › image_source.py › _resolve

```python
def _resolve(host: str) -> list[str]:
    try:
        infos = socket.getaddrinfo(host, None)
    except socket.gaierror as exc:
        raise ImageUnavailable("The photo host does not resolve") from exc
    return sorted({info[4][0] for info in infos})
```

main — Python · UTF-8 · LF · lines 85–90

4.12 _is_public()

backend/app/services/image_source.py · lines 93–105

image_source.py — backend/app/services/image_source.py — CSIT314

backend › app › services › image_source.py › _is_public

```python
def _is_public(address: str) -> bool:
    try:
        parsed = ipaddress.ip_address(address)
    except ValueError:
        return False
    return not (
        parsed.is_private
        or parsed.is_loopback
        or parsed.is_link_local
        or parsed.is_reserved
        or parsed.is_multicast
        or parsed.is_unspecified
    )
```

main — Python · UTF-8 · LF · lines 93–105

4.13 is_animal()

backend/app/services/object_labels.py · lines 122–129

Return True when the label names an animal.

object_labels.py — backend/app/services/object_labels.py — CSIT314

backend › app › services › object_labels.py › is_animal

```python
def is_animal(label: str) -> bool:
    """Return True when the label names an animal.

    Only the first synonym is matched, so "potted plant" cannot trip on "ant",
    and the word boundaries keep "car" away from "cardoon".
    """
    primary = label.split(",")[0].strip()
    return bool(ANIMAL_PATTERN.search(primary))
```

main — Python · UTF-8 · LF · lines 122–129

4.14 _session()

backend/app/services/object_labels.py · lines 133–153

@lru_cache(maxsize=1)

Load the model once. Return None when the model or runtime is absent.

object_labels.py — backend/app/services/object_labels.py — CSIT314

backend › app › services › object_labels.py › _session

```python
def _session():
    """Load the model once. Return None when the model or runtime is absent."""
    if not MODEL_PATH.is_file():
        return None
    labels_file = MODEL_PATH.with_name("synset.txt")
    if not labels_file.is_file():
        return None
    try:
        import onnxruntime as ort
        from PIL import Image  # noqa: F401  - proves Pillow is present
    except ImportError:
        return None
    session = ort.InferenceSession(
        str(MODEL_PATH), providers=["CPUExecutionProvider"]
    )
    labels = [
        line.split(" ", 1)[1] if " " in line else line
        for line in labels_file.read_text(encoding="utf-8").splitlines()
        if line.strip()
    ]
    return session, labels
```

main — Python · UTF-8 · LF · lines 133–153

4.15 available()

backend/app/services/object_labels.py · lines 156–158

Return True when a model can answer.

object_labels.py — backend/app/services/object_labels.py — CSIT314

backend › app › services › object_labels.py › available

```python
def available() -> bool:
    """Return True when a model can answer."""
    return _session() is not None
```

main — Python · UTF-8 · LF · lines 156–158

4.16 Reading

backend/app/services/object_labels.py · lines 162–169

What one inference pass saw. The diagnostics drive the interior gate.

object_labels.py — backend/app/services/object_labels.py — CSIT314

backend › app › services › object_labels.py › Reading

```python
class Reading:
    """What one inference pass saw. The diagnostics drive the interior gate."""

    tags: list[str]
    top_label: str
    top_probability: float
    interior_probability: float
    subject: str
```

main — Python · UTF-8 · LF · lines 162–169

4.17 read()

backend/app/services/object_labels.py · lines 172–231

Run one inference pass and return the tags plus the diagnostics.

object_labels.py — backend/app/services/object_labels.py — CSIT314

backend › app › services › object_labels.py › read

```python
# backend/app/services/object_labels.py — lines 172-231, first 20 lines of 60
def read(data: bytes) -> Reading | None:
    """Run one inference pass and return the tags plus the diagnostics.

    ``None`` means the model is absent or the bytes are not readable. Callers
    must fall back to the colour stage, not fail.
    ``interior_probability`` is the best probability among the classes that map
    to a catalogue tag. A photo of a monkey scores near zero there even when the
    model is confident about the monkey.
    """
    loaded = _session()
    if loaded is None:
        return None
    session, labels = loaded
    try:
        import numpy as np
        from PIL import Image

        with Image.open(BytesIO(data)) as image:
            image.load()
            small = image.convert("RGB").resize(SIZE)
    ...
```

main — Python · UTF-8 · LF · lines 172–231

4.18 object_tags()

backend/app/services/object_labels.py · lines 234–241

Return up to ``LIMIT`` catalogue tags for ``data``, most confident first.

object_labels.py — backend/app/services/object_labels.py — CSIT314

backend › app › services › object_labels.py › object_tags

```python
def object_tags(data: bytes) -> list[str]:
    """Return up to ``LIMIT`` catalogue tags for ``data``, most confident first.

    An empty list means the model is absent, refused the bytes, or saw nothing
    it can name. The caller must treat that as "colour tags only".
    """
    reading = read(data)
    return [] if reading is None else reading.tags
```

main — Python · UTF-8 · LF · lines 234–241

4.19 engine_name()

backend/app/services/object_labels.py · lines 244–246

Name the analyser for the response, so the screen can be honest.

object_labels.py — backend/app/services/object_labels.py — CSIT314

backend › app › services › object_labels.py › engine_name

```python
def engine_name() -> str:
    """Name the analyser for the response, so the screen can be honest."""
    return "objects and colour" if available() else "colour only"
```

main — Python · UTF-8 · LF · lines 244–246

4.20 ProjectReportService

backend/app/services/project_report_service.py · lines 28–124

Applies the reporting rules on top of the three stores.

Method	Purpose	Lines
`def __init__(reports: ReportRepository, projects: ProjectRepository, accounts: AccountRepository) -> None`		31–39
`def submit(actor: Account, project_id: str, reason: str, comments: str = '') -> ProjectReport`	Record one customer complaint about one project.	41–62
`def list_reports(actor: Account) -> list[ProjectReport]`	Return every report, newest first, for platform staff.	64–69
`def resolve(actor: Account, report_id: str) -> ProjectReport`	Close one report, after the chosen actions.	71–101
`def project_title(report: ProjectReport) -> str`	Return the project title the administrator reads.	105–108
`def designer_of(report: ProjectReport) -> Account | None`	Return the account that published the reported project.	110–115
`def customer_of(report: ProjectReport) -> Account | None`	Return the account that raised the report.	117–119
`def _require_staff(actor: Account) -> None`		122–124

project_report_service.py — backend/app/services/project_report_service.py — CSIT314

backend › app › services › project_report_service.py › ProjectReportService

```python
# backend/app/services/project_report_service.py — lines 28–124, signatures only
class ProjectReportService:
    """Applies the reporting rules on top of the three stores."""
    def __init__(reports: ReportRepository, projects: ProjectRepository, accounts: AccountRepository) -> None
    def submit(actor: Account, project_id: str, reason: str, comments: str = '') -> ProjectReport
        """Record one customer complaint about one project."""
    def list_reports(actor: Account) -> list[ProjectReport]
        """Return every report, newest first, for platform staff."""
    def resolve(actor: Account, report_id: str) -> ProjectReport
        """Close one report, after the chosen actions."""
    def project_title(report: ProjectReport) -> str
        """Return the project title the administrator reads."""
    def designer_of(report: ProjectReport) -> Account | None
        """Return the account that published the reported project."""
    def customer_of(report: ProjectReport) -> Account | None
        """Return the account that raised the report."""
    @staticmethod
    def _require_staff(actor: Account) -> None
```

main — Python · UTF-8 · LF · lines 28–124

4.21 SearchResult

backend/app/services/project_search_service.py · lines 21–34

One page of matches plus the numbers the screen needs.

Method	Purpose	Lines
`def pages() -> int`	Return how many pages the total fills, at least one.	30–34

project_search_service.py — backend/app/services/project_search_service.py — CSIT314

backend › app › services › project_search_service.py › SearchResult

```python
class SearchResult:
    """One page of matches plus the numbers the screen needs."""

    items: list[Project]
    total: int
    page: int
    page_size: int

    @property
    def pages(self) -> int:
        """Return how many pages the total fills, at least one."""
        if self.page_size <= 0:
            return 1
        return max(1, -(-self.total // self.page_size))
```

main — Python · UTF-8 · LF · lines 21–34

4.22 ProjectSearchService

backend/app/services/project_search_service.py · lines 37–98

Filters the catalogue. Holds no state of its own.

Method	Purpose	Lines
`def __init__(projects: ProjectRepository) -> None`		40–41

`def search() -> SearchResult`	Return the matches for one page of results.	43–98

project_search_service.py — backend/app/services/project_search_service.py — CSIT314

backend › app › services › project_search_service.py › ProjectSearchService

```python
# backend/app/services/project_search_service.py — lines 37–98, signatures only
class ProjectSearchService:
    """Filters the catalogue. Holds no state of its own."""
    def __init__(projects: ProjectRepository) -> None
    def search() -> SearchResult
        """Return the matches for one page of results."""
```


main — Python · UTF-8 · LF · lines 37–98

4.23 ProjectService

backend/app/services/project_service.py · lines 13–201

Applies the portfolio rules on top of the two stores.

Method	Purpose	Lines
`def __init__(projects: ProjectRepository, companies: CompanyRepository) -> None`		16–22
`def create(actor: Account) -> Project`	Publish a project under the caller's company.	24–61
`def get(project_id: str, viewer: Account | None = None) -> Project`	Return a project by id.	63–76
`def update(actor: Account, project_id: str) -> Project`	Change only the fields that were supplied. Owner only.	78–122
`def require_owned(actor: Account, project_id: str) -> Project`	Return the project only when the caller owns it.	124–126
`def delete(actor: Account, project_id: str) -> None`	Remove a project. Owner only.	128–131
`def list_for_owner(actor: Account, status: ProjectStatus | None = None, name: str = '') -> list[Project]`	List the owner's projects, optionally filtered by status and title.	133–170
`def list_for_company(company_id: str) -> list[Project]`	Return the projects published under one company, newest first.	172–178
`def _may_read_hidden(project: Project, viewer: Account | None) -> bool`	Return ``True`` when ``viewer`` may still read a taken down project.	181–187
`def _require_designer(actor: Account) -> None`		190–192
`def _require_owned(actor: Account, project_id: str) -> Project`		194–201



4.24 QuoteService

backend/app/services/quote_service.py · lines 32–312

Applies the quoting rules on top of the four stores.

Method	Purpose	Lines
`def __init__(requests: QuoteRequestRepository, quotes: QuoteRepository, companies: CompanyRepository, projects: ProjectRepository) -> None`		35–45
`def submit(actor: Account) -> QuoteRequest`	Send one request to one company.	49–88
`def counter(actor: Account, request_id: str, target_cents: int, note: str) -> QuoteRequest`	Record the price the customer wants and why.	90–99
`def cancel(actor: Account, request_id: str, reason: str = '') -> QuoteRequest`	Stop an open request.	101–110
`def accept(actor: Account, quote_id: str) -> Quote`	Accept one quote. Other requests of this customer stay open.	112–124
`def decline(actor: Account, quote_id: str, reason: str = '') -> Quote`	Turn one quote down.	126–134
`def answer(actor: Account, request_id: str) -> Quote`	Send version one of the quote.	138–165
`def revise(actor: Account, quote_id: str) -> Quote`	Send the next version of the quote.	167–202
`def refuse(actor: Account, request_id: str, reason: str = '') -> QuoteRequest`	Decline to quote.	204–211
`def list_for_customer(actor: Account, state: QuoteRequestState | None = None) -> list[QuoteRequest]`	Return the caller's requests, newest first.	215–220
`def list_for_designer(actor: Account, state: QuoteRequestState | None = None) -> list[QuoteRequest]`	Return the requests sent to the caller's company, newest first.	222–227
`def get_request(actor: Account, request_id: str) -> QuoteRequest`	Return one request to a party that may see it.	229–237
`def quotes_for(actor: Account, request_id: str) -> list[Quote]`	Return every version of a request's quote.	239–242
`def _sorted(requests: list[QuoteRequest], state: QuoteRequestState | None) -> list[QuoteRequest]`		246–253
`def _refresh(request: QuoteRequest) -> None`	Close what time has closed. Called on every read.	255–264

def _may_read(actor: Account, request: QuoteRequest) -> bool		266–272
def _owned_request(actor: Account, request_id: str) -> QuoteRequest		274–281
def _owned_quote(actor: Account, quote_id: str) -> tuple[Quote, QuoteRequest]		283–288
def _request_for_designer(actor: Account, request_id: str) -> QuoteRequest		290–299
def _company_of(actor: Account)		301–307
def _require_customer(actor: Account) -> None		310–312

quote_service.py — backend/app/services/quote_service.py — CSIT314

backend › app › services › quote_service.py › QuoteService

```python
# backend/app/services/quote_service.py — lines 32–312, signatures only
class QuoteService:
    """Applies the quoting rules on top of the four stores."""
    def __init__(requests: QuoteRequestRepository, quotes: QuoteRepository, companies: CompanyRepository, projects: ProjectRepository) -> None
    def submit(actor: Account) -> QuoteRequest
        """Send one request to one company."""
    def counter(actor: Account, request_id: str, target_cents: int, note: str) -> QuoteRequest
        """Record the price the customer wants and why."""
    def cancel(actor: Account, request_id: str, reason: str = '') -> QuoteRequest
        """Stop an open request."""
    def accept(actor: Account, quote_id: str) -> Quote
        """Accept one quote. Other requests of this customer stay open."""
    def decline(actor: Account, quote_id: str, reason: str = '') -> Quote
        """Turn one quote down."""
    def answer(actor: Account, request_id: str) -> Quote
        """Send version one of the quote."""
    def revise(actor: Account, quote_id: str) -> Quote
        """Send the next version of the quote."""
    def refuse(actor: Account, request_id: str, reason: str = '') -> QuoteRequest
        """Decline to quote."""
    def list_for_customer(actor: Account, state: QuoteRequestState | None = None) -> list[QuoteRequest]
        """Return the caller's requests, newest first."""
    def list_for_designer(actor: Account, state: QuoteRequestState | None = None) -> list[QuoteRequest]
        """Return the requests sent to the caller's company, newest first."""
    def get_request(actor: Account, request_id: str) -> QuoteRequest
        """Return one request to a party that may see it."""
    def quotes_for(actor: Account, request_id: str) -> list[Quote]
        """Return every version of a request's quote."""
    def _sorted(requests: list[QuoteRequest], state: QuoteRequestState | None) -> list[QuoteRequest]
    def _refresh(request: QuoteRequest) -> None
        """Close what time has closed. Called on every read."""
    def _may_read(actor: Account, request: QuoteRequest) -> bool
    def _owned_request(actor: Account, request_id: str) -> QuoteRequest
    def _owned_quote(actor: Account, quote_id: str) -> tuple[Quote, QuoteRequest]
    def _request_for_designer(actor: Account, request_id: str) -> QuoteRequest
    def _company_of(actor: Account)
    @staticmethod
    def _require_customer(actor: Account) -> None
```

main — Python · UTF-8 · LF · lines 32–312

4.25 Bucket

backend/app/services/report_service.py · lines 22–31

One period of activity.

report_service.py — backend/app/services/report_service.py — CSIT314

backend › app › services › report_service.py › Bucket

```python
class Bucket:
    """One period of activity."""

    label: str
    start: datetime
    end: datetime
    accounts: int
    projects: int
    quote_requests: int
    quotes: int
```

main — Python · UTF-8 · LF · lines 22–31

4.26 Report

backend/app/services/report_service.py · lines 35–39

A period choice and the buckets it produced.

report_service.py — backend/app/services/report_service.py — CSIT314

backend › app › services › report_service.py › Report

```python
class Report:
    """A period choice and the buckets it produced."""

    period: str
    buckets: list[Bucket]
```


main — Python · UTF-8 · LF · lines 35–39

4.27 ReportService

backend/app/services/report_service.py · lines 42–133

Builds reports from the four stores that hold timestamps.

Method	Purpose	Lines
`def __init__(accounts: AccountRepository, projects: ProjectRepository, requests: QuoteRequestRepository, quotes: QuoteRepository) -> None`		45–55
`def build(period: str = 'daily', buckets: int = DEFAULT_BUCKETS, now: datetime | None = None) -> Report`	Return the last ``buckets`` periods, oldest first.	57–85
`def _count(records: list, start: datetime, end: datetime) -> int`		88–89
`def _windows(period: str, buckets: int, now: datetime) -> list[tuple[datetime, datetime]]`	Return ``buckets`` windows, oldest first, ending at ``now``.	92–102
`def _floor(period: str, moment: datetime) -> datetime`		105–113
`def _shift(period: str, moment: datetime, count: int) -> datetime`		116–124
`def _label(period: str, start: datetime) -> str`		127–133




4.28 ShortlistService

backend/app/services/shortlist_service.py · lines 14–76

Keeps the saved list and the project counters in step.

Method	Purpose	Lines
`def __init__(shortlists: ShortlistRepository, projects: ProjectRepository) -> None`		17–23
`def add(actor: Account, project_id: str) -> Project`	Save a project for the caller. Saving twice changes nothing.	25–34
`def remove(actor: Account, project_id: str) -> None`	Drop a project from the caller's list.	36–45
`def list_for(actor: Account) -> list[Project]`	Return the saved projects, oldest save first, skipping deleted ones.	47–58
`def ids_for(actor: Account) -> list[str]`	Return the saved project ids.	60–64
`def _own_list(actor: Account) -> Shortlist`		66–71
`def _require_customer(actor: Account) -> None`		74–76



4.29 PaletteEntry

backend/app/services/tag_suggestion_service.py · lines 36–40

One colour of the photo and how much of it the photo holds.

tag_suggestion_service.py — backend/app/services/tag_suggestion_service.py — CSIT314

backend › app › services › tag_suggestion_service.py › PaletteEntry

```python
class PaletteEntry:
    """One colour of the photo and how much of it the photo holds."""

    hex: str
    percent: float
```

main — Python · UTF-8 · LF · lines 36–40

4.30 TagSuggestion

backend/app/services/tag_suggestion_service.py · lines 44–52

What the analyser found. The designer accepts or ignores it.

tag_suggestion_service.py — backend/app/services/tag_suggestion_service.py — CSIT314

backend › app › services › tag_suggestion_service.py › TagSuggestion

```python
class TagSuggestion:
    """What the analyser found. The designer accepts or ignores it."""

    palette: list[PaletteEntry]
    tags: list[str]
    width: int
    height: int
    subject: str = "room"
    objects: list[str] = field(default_factory=list)
```

main — Python · UTF-8 · LF · lines 44–52

4.31 suggest_tags()

backend/app/services/tag_suggestion_service.py · lines 55–82

Read ``data`` as an image and describe it.

tag_suggestion_service.py — backend/app/services/tag_suggestion_service.py — CSIT314

backend › app › services › tag_suggestion_service.py › suggest_tags

```python
def suggest_tags(data: bytes) -> TagSuggestion:
    """Read ``data`` as an image and describe it.

    Raises ``ValueError`` when the bytes are not an image Pillow can read.
    A photo the model reads as an animal, a person, a vehicle or a landscape is
    returned with ``subject="other"`` and no tags at all: half a tag list is
    worse than a clear refusal, because the tags would drive a search.
    """
    try:
        with Image.open(BytesIO(data)) as image:
            image.load()
            width, height = image.size
            small = image.convert("RGB").resize(ANALYSIS_SIZE)
            palette = _palette(small)
            stats = _stats(small)
    except (OSError, ValueError) as exc:
        raise ValueError("The photo could not be read as an image") from exc
    reading = read_objects(data)
    subject = reading.subject if reading is not None else "room"
    objects = reading.tags if reading is not None else []
    return TagSuggestion(
        palette=palette,
        tags=[] if subject == "other" else _merge(objects, _tags(stats)),
        width=width,
        height=height,
        subject=subject,
        objects=[] if subject == "other" else objects,
    )
```

main — Python · UTF-8 · LF · lines 55–82

4.32 _merge()

backend/app/services/tag_suggestion_service.py · lines 85–91

Object tags first, then mood tags, without repeats, capped.

tag_suggestion_service.py — backend/app/services/tag_suggestion_service.py — CSIT314

backend › app › services › tag_suggestion_service.py › _merge

```python
def _merge(objects: list[str], moods: list[str]) -> list[str]:
    """Object tags first, then mood tags, without repeats, capped."""
    merged: list[str] = []
    for tag in (*objects, *moods):
        if tag not in merged:
            merged.append(tag)
    return merged[:TAG_LIMIT]
```

main — Python · UTF-8 · LF · lines 85–91

4.33 _palette()

backend/app/services/tag_suggestion_service.py · lines 94–109

tag_suggestion_service.py — backend/app/services/tag_suggestion_service.py — CSIT314

backend › app › services › tag_suggestion_service.py › _palette

```python
def _palette(image: Image.Image) -> list[PaletteEntry]:
    quantized = image.quantize(colors=PALETTE_SIZE, method=Image.Quantize.MEDIANCUT)
    table = quantized.getpalette() or []
    counts = quantized.getcolors() or []
    total = sum(count for count, _ in counts) or 1
    entries: list[PaletteEntry] = []
    for count, index in sorted(counts, reverse=True):
        base = index * 3
        colour = tuple(table[base : base + 3])
        entries.append(
            PaletteEntry(
                hex="#%02x%02x%02x" % colour,
                percent=round(100 * count / total, 1),
            )
        )
    return entries
```

main — Python · UTF-8 · LF · lines 94–109

4.34 _stats()

backend/app/services/tag_suggestion_service.py · lines 112–124

tag_suggestion_service.py — backend/app/services/tag_suggestion_service.py — CSIT314

backend › app › services › tag_suggestion_service.py › _stats

```python
def _stats(image: Image.Image) -> dict[str, float]:
    mean = ImageStat.Stat(image)
    brightness = sum(mean.mean) / 3
    contrast = sum(mean.stddev) / 3
    saturation = ImageStat.Stat(image.convert("HSV")).mean[1]
    grey = image.convert("L")
    edge = ImageStat.Stat(grey.filter(ImageFilter.FIND_EDGES)).mean[0]
    return {
        "brightness": brightness,
        "contrast": contrast,
        "saturation": saturation,
        "edge": edge,
    }
```

main — Python · UTF-8 · LF · lines 112–124

4.35 _tags()

backend/app/services/tag_suggestion_service.py · lines 127–150

tag_suggestion_service.py — backend/app/services/tag_suggestion_service.py — CSIT314

backend › app › services › tag_suggestion_service.py › _tags

```python
def _tags(stats: dict[str, float]) -> list[str]:
    tags: list[str] = []

    if stats["brightness"] >= BRIGHT_MEAN:
        tags.append("bright")
    elif stats["brightness"] <= MOODY_MEAN:
        tags.append("moody")
    else:
        tags.append("balanced light")

    if stats["saturation"] <= NEUTRAL_SATURATION:
        tags.append("neutral palette")
    elif stats["saturation"] >= SATURATED_SATURATION:
        tags.append("saturated palette")
    else:
        tags.append("warm palette")

    if stats["contrast"] <= FLAT_CONTRAST:
        tags.append("soft contrast")
    elif stats["contrast"] >= HIGH_CONTRAST:
        tags.append("high contrast")

    tags.append("calm detail" if stats["edge"] < CALM_EDGE else "busy detail")
    return tags
```

main

Python · UTF-8 · LF · lines 127–150

5 Control boundary: backend/app/api

A router function is the HTTP edge. It validates the body with a schema, asks the service to do the work, and translates a domain error into a status code.

5.1 _to_http()

backend/app/api/admin.py · lines 22–26

Map a domain refusal to the matching response.

admin.py — backend/app/api/admin.py — CSIT314

backend › app › api › admin.py › _to_http

```python
def _to_http(exc: Exception) -> HTTPException:
    """Map a domain refusal to the matching response."""
    if isinstance(exc, AccountNotFound):
        return HTTPException(status_code=http_status.HTTP_404_NOT_FOUND, detail=exc.message)
    return HTTPException(status_code=http_status.HTTP_403_FORBIDDEN, detail=exc.message)
```

main — Python · UTF-8 · LF · lines 22–26

5.2 list_accounts()

backend/app/api/admin.py · lines 34–44

@router.get('/accounts', response_model=list[AccountPublic], summary='List accounts for an administrator')

Return every account, optionally filtered by status.

admin.py — backend/app/api/admin.py — CSIT314

backend › app › api › admin.py › list_accounts

```python
def list_accounts(
    actor: CurrentAccountDep,
    service: ServiceDep,
    account_status: Annotated[AccountStatus | None, Query(alias="status")] = None,
) -> list[AccountPublic]:
    """Return every account, optionally filtered by status."""
    try:
        accounts = service.list_accounts(actor, account_status)
    except NotPermitted as exc:
        raise _to_http(exc) from exc
    return [AccountPublic.model_validate(account) for account in accounts]
```

main — Python · UTF-8 · LF · lines 34–44

5.3 approve_account()

backend/app/api/admin.py · lines 52–60

@router.post('/accounts/{account_id}/approve', response_model=AccountPublic, summary='Approve an account')

Activate the account so it may sign in.

admin.py — backend/app/api/admin.py — CSIT314

backend › app › api › admin.py › approve_account

```python
def approve_account(
    account_id: str, actor: CurrentAccountDep, service: ServiceDep
) -> AccountPublic:
    """Activate the account so it may sign in."""
    try:
        account = service.approve(actor, account_id)
    except (AccountNotFound, NotPermitted) as exc:
        raise _to_http(exc) from exc
    return AccountPublic.model_validate(account)
```

main — Python · UTF-8 · LF · lines 52–60

5.4 suspend_account()

backend/app/api/admin.py · lines 68–76

@router.post('/accounts/{account_id}/suspend', response_model=AccountPublic, summary='Suspend an account')

Suspend the account so it cannot sign in again.

admin.py — backend/app/api/admin.py — CSIT314

backend › app › api › admin.py › suspend_account

```python
def suspend_account(
    account_id: str, actor: CurrentAccountDep, service: ServiceDep
) -> AccountPublic:
    """Suspend the account so it cannot sign in again."""
    try:
        account = service.suspend(actor, account_id)
    except (AccountNotFound, NotPermitted) as exc:
        raise _to_http(exc) from exc
    return AccountPublic.model_validate(account)
```

main — Python · UTF-8 · LF · lines 68–76

5.5 _fail()

backend/app/api/appointments.py · lines 28–42

Map a domain refusal to the matching response.

appointments.py — backend/app/api/appointments.py — CSIT314

backend › app › api › appointments.py › _fail

```python
def _fail(exc: Exception) -> HTTPException:
    """Map a domain refusal to the matching response."""
    if isinstance(exc, (AppointmentNotFound, CompanyNotFound)):
        return HTTPException(
            status_code=http_status.HTTP_404_NOT_FOUND, detail=exc.message
        )
    if isinstance(exc, NotPermitted):
        return HTTPException(
            status_code=http_status.HTTP_403_FORBIDDEN, detail=exc.message
        )
    if isinstance(exc, InvalidState):
        return HTTPException(
            status_code=http_status.HTTP_409_CONFLICT, detail=exc.message
        )
    return HTTPException(status_code=http_status.HTTP_400_BAD_REQUEST, detail=str(exc))
```

main — Python · UTF-8 · LF · lines 28–42

5.6 _public()

backend/app/api/appointments.py · lines 45–61

Return one appointment with the customer's name and the visible place.

appointments.py — backend/app/api/appointments.py — CSIT314

backend › app › api › appointments.py › _public

```python
def _public(
    service: AppointmentService, appointment, actor: Account
) -> AppointmentPublic:
    """Return one appointment with the customer's name and the visible place.

    A customer does not see the room address of an online booking until the
    designer accepts it. The designer always sees it.
    """
    public = AppointmentPublic.model_validate(appointment)
    public.customer_name = service.customer_name(appointment)
    if (
        actor.role is Role.CUSTOMER
        and appointment.mode is ConsultationMode.ONLINE
        and appointment.state is not AppointmentState.ACCEPTED
    ):
        public.location = ""
    return public
```

main — Python · UTF-8 · LF · lines 45–61

5.7 read_slots()

backend/app/api/appointments.py · lines 69–80

@router.get('/slots', response_model=SlotsPublic, summary="Show the free hours on one company's day")

Return the hours a customer may still pick.

appointments.py — backend/app/api/appointments.py — CSIT314

backend › app › api › appointments.py › read_slots

```python
def read_slots(
    actor: CurrentAccountDep,
    service: ServiceDep,
    company_id: str,
    day: date = Query(..., alias="date"),
) -> SlotsPublic:
    """Return the hours a customer may still pick."""
    try:
        slots = service.available_slots(actor, company_id, day)
    except (CompanyNotFound, ValueError) as exc:
        raise _fail(exc) from exc
    return SlotsPublic(date=day, slots=slots)
```

main — Python · UTF-8 · LF · lines 69–80

5.8 book()

backend/app/api/appointments.py · lines 89–106

@router.post('', response_model=AppointmentPublic, status_code=http_status.HTTP_201_CREATED, summary='Book a consultation')

A customer keeps one hour in a designer's diary.

appointments.py — backend/app/api/appointments.py — CSIT314

backend › app › api › appointments.py › book

```python
def book(
    payload: BookRequest,
    actor: CurrentAccountDep,
    service: ServiceDep,
) -> AppointmentPublic:
    """A customer keeps one hour in a designer's diary."""
    try:
        appointment = service.book(
            actor,
            payload.company_id,
            payload.date,
            payload.time,
            payload.mode,
            payload.requirements,
        )
    except (NotPermitted, CompanyNotFound, InvalidState, ValueError) as exc:
        raise _fail(exc) from exc
    return _public(service, appointment, actor)
```

main — Python · UTF-8 · LF · lines 89–106

5.9 list_appointments()

backend/app/api/appointments.py · lines 114–125

@router.get('', response_model=list[AppointmentPublic], summary='List the appointments you may see')

Customers see their bookings; designers see their company diary.

appointments.py — backend/app/api/appointments.py — CSIT314

backend › app › api › appointments.py › list_appointments

```python
def list_appointments(
    actor: CurrentAccountDep, service: ServiceDep
) -> list[AppointmentPublic]:
    """Customers see their bookings; designers see their company diary."""
    try:
        if actor.role.value == "CUSTOMER":
            appointments = service.list_for_customer(actor)
        else:
            appointments = service.list_for_designer(actor)
    except (NotPermitted, CompanyNotFound) as exc:
        raise _fail(exc) from exc
    return [_public(service, entry, actor) for entry in appointments]
```

main — Python · UTF-8 · LF · lines 114–125

5.10 accept_appointment()

backend/app/api/appointments.py · lines 133–141

@router.post('/{appointment_id}/accept', response_model=AppointmentPublic, summary='Accept a consultation')

The designer confirms the hour.

appointments.py — backend/app/api/appointments.py — CSIT314

backend › app › api › appointments.py › accept_appointment

```python
def accept_appointment(
    appointment_id: str, actor: CurrentAccountDep, service: ServiceDep
) -> AppointmentPublic:
    """The designer confirms the hour."""
    try:
        appointment = service.accept(actor, appointment_id)
    except (AppointmentNotFound, NotPermitted, CompanyNotFound, InvalidState) as exc:
        raise _fail(exc) from exc
    return _public(service, appointment, actor)
```

main — Python · UTF-8 · LF · lines 133–141

5.11 cancel_appointment()

backend/app/api/appointments.py · lines 149–157

@router.post('/{appointment_id}/cancel', response_model=AppointmentPublic, summary='Cancel a consultation')

Either party gives the hour back.

appointments.py — backend/app/api/appointments.py — CSIT314

backend › app › api › appointments.py › cancel_appointment

```python
def cancel_appointment(
    appointment_id: str, actor: CurrentAccountDep, service: ServiceDep
) -> AppointmentPublic:
    """Either party gives the hour back."""
    try:
        appointment = service.cancel(actor, appointment_id)
    except (AppointmentNotFound, NotPermitted, InvalidState) as exc:
        raise _fail(exc) from exc
    return _public(service, appointment, actor)
```

main — Python · UTF-8 · LF · lines 149–157

5.12 register()

backend/app/api/auth.py · lines 40–55

@router.post('/register', response_model=AccountPublic, status_code=status.HTTP_201_CREATED, summary='Register a customer or designer account')

Create a self service account.

auth.py — backend/app/api/auth.py — CSIT314

backend › app › api › auth.py › register

```python
def register(payload: RegisterRequest, service: ServiceDep) -> AccountPublic:
    """Create a self service account."""
    try:
        account = service.register(
            email=payload.email,
            password=payload.password,
            display_name=payload.display_name,
            role=payload.role,
        )
    except EmailAlreadyRegistered as exc:
        raise HTTPException(status_code=status.HTTP_409_CONFLICT, detail=exc.message) from exc
    except (InvalidRoleForSelfRegistration, WeakPassword) as exc:
        raise HTTPException(
            status_code=status.HTTP_400_BAD_REQUEST, detail=exc.message
        ) from exc
    return AccountPublic.model_validate(account)
```

main — Python · UTF-8 · LF · lines 40–55

5.13 login()

backend/app/api/auth.py · lines 59–76

@router.post('/login', response_model=TokenResponse, summary='Exchange credentials for a token')

Authenticate an account and issue an access token.

auth.py — backend/app/api/auth.py — CSIT314

backend › app › api › auth.py › login

```python
def login(payload: LoginRequest, service: ServiceDep) -> TokenResponse:
    """Authenticate an account and issue an access token."""
    try:
        account = service.authenticate(payload.email, payload.password)
    except InvalidCredentials as exc:
        raise HTTPException(
            status_code=status.HTTP_401_UNAUTHORIZED, detail=exc.message
        ) from exc
    except AccountNotActive as exc:
        raise HTTPException(status_code=status.HTTP_403_FORBIDDEN, detail=exc.message) from exc
    minutes = get_token_minutes()
    token = create_access_token(account.id, account.role.value, minutes)
    return TokenResponse(
        access_token=token,
        token_type="bearer",
        expires_in=minutes * 60,
        account=AccountPublic.model_validate(account),
    )
```

main — Python · UTF-8 · LF · lines 59–76

5.14 read_current_account()

backend/app/api/auth.py · lines 80–82

@router.get('/me', response_model=AccountPublic, summary='Return the authenticated account')

Return the account the bearer token belongs to.

auth.py — backend/app/api/auth.py — CSIT314

backend › app › api › auth.py › read_current_account

```python
def read_current_account(account: CurrentAccountDep) -> AccountPublic:
    """Return the account the bearer token belongs to."""
    return AccountPublic.model_validate(account)
```

main — Python · UTF-8 · LF · lines 80–82

5.15 BudgetRange

backend/app/api/catalogue.py · lines 17–22

The slider bounds for the budget filter.

catalogue.py — backend/app/api/catalogue.py — CSIT314

backend › app › api › catalogue.py › BudgetRange

```python
class BudgetRange(BaseModel):
    """The slider bounds for the budget filter."""

    min: int = Field(description="Lowest selectable amount")
    max: int = Field(description="Highest selectable amount")
    step: int = Field(description="Slider step in the same currency unit")
```

main — Python · UTF-8 · LF · lines 17–22

5.16 CatalogueResponse

backend/app/api/catalogue.py · lines 25–30

Everything a filter screen needs to build its controls.

catalogue.py — backend/app/api/catalogue.py — CSIT314

backend › app › api › catalogue.py › CatalogueResponse

```python
class CatalogueResponse(BaseModel):
    """Everything a filter screen needs to build its controls."""

    categories: list[str]
    styles: list[str]
    budget: BudgetRange
```

main — Python · UTF-8 · LF · lines 25–30

5.17 read_catalogue()

backend/app/api/catalogue.py · lines 38–50

@router.get('', response_model=CatalogueResponse, summary='Read the fixed category and style lists')

Return the platform vocabulary. No sign in needed.

catalogue.py — backend/app/api/catalogue.py — CSIT314

backend › app › api › catalogue.py › read_catalogue

```python
def read_catalogue(
    categories: Annotated[CategoryRepository, Depends(get_category_repository)],
) -> CatalogueResponse:
    """Return the platform vocabulary. No sign in needed."""
    return CatalogueResponse(
        categories=[entry.name for entry in categories.list_active()],
        styles=list(catalogue.STYLES),
        budget=BudgetRange(
            min=catalogue.BUDGET_MIN,
            max=catalogue.BUDGET_MAX,
            step=catalogue.BUDGET_STEP,
        ),
    )
```

main — Python · UTF-8 · LF · lines 38–50

5.18 CategoryPublic

backend/app/api/categories.py · lines 25–32

One category as the screens read it.

categories.py — backend/app/api/categories.py — CSIT314

backend › app › api › categories.py › CategoryPublic

```python
class CategoryPublic(BaseModel):
    """One category as the screens read it."""

    id: str
    name: str
    active: bool
    created_at: str
    updated_at: str
```

main — Python · UTF-8 · LF · lines 25–32

5.19 CategoryInput

backend/app/api/categories.py · lines 35–38

Payload to create or rename a category.

categories.py — backend/app/api/categories.py — CSIT314

backend › app › api › categories.py › CategoryInput

```python
class CategoryInput(BaseModel):
    """Payload to create or rename a category."""

    name: str = Field(min_length=1, max_length=60)
```

main — Python · UTF-8 · LF · lines 35–38

5.20 CategoryPatch

backend/app/api/categories.py · lines 41–45

Payload to rename, archive or restore.

categories.py — backend/app/api/categories.py — CSIT314

backend › app › api › categories.py › CategoryPatch

```python
class CategoryPatch(BaseModel):
    """Payload to rename, archive or restore."""

    name: str | None = Field(default=None, min_length=1, max_length=60)
    active: bool | None = None
```

main — Python · UTF-8 · LF · lines 41–45

5.21 _to_public()

backend/app/api/categories.py · lines 48–55

categories.py — backend/app/api/categories.py — CSIT314

backend › app › api › categories.py › _to_public

```python
def _to_public(category) -> CategoryPublic:
    return CategoryPublic(
        id=category.id,
        name=category.name,
        active=category.active,
        created_at=category.created_at.isoformat(),
        updated_at=category.updated_at.isoformat() if category.updated_at else "",
    )
```

main — Python · UTF-8 · LF · lines 48–55

5.22 _fail()

backend/app/api/categories.py · lines 58–65

categories.py — backend/app/api/categories.py — CSIT314

backend › app › api › categories.py › _fail

```python
def _fail(exc: Exception) -> HTTPException:
    if isinstance(exc, CategoryNotFound):
        return HTTPException(status_code=http_status.HTTP_404_NOT_FOUND, detail=str(exc))
    if isinstance(exc, CategoryExists):
        return HTTPException(status_code=http_status.HTTP_409_CONFLICT, detail=str(exc))
    if isinstance(exc, NotPermitted):
        return HTTPException(status_code=http_status.HTTP_403_FORBIDDEN, detail=exc.message)
    return HTTPException(status_code=http_status.HTTP_400_BAD_REQUEST, detail=str(exc))
```

main — Python · UTF-8 · LF · lines 58–65

5.23 list_categories()

backend/app/api/categories.py · lines 73–75

@router.get('', response_model=list[CategoryPublic], summary='List the categories a dropdown should show')

Public list of active categories.

categories.py — backend/app/api/categories.py — CSIT314

backend › app › api › categories.py › list_categories

```python
def list_categories(service: ServiceDep) -> list[CategoryPublic]:
    """Public list of active categories."""
    return [_to_public(category) for category in service.list_active()]
```

main — Python · UTF-8 · LF · lines 73–75

5.24 list_all_categories()

backend/app/api/categories.py · lines 83–91

@router.get('/all', response_model=list[CategoryPublic], summary='List every category, archived ones included')

Staff only.

categories.py — backend/app/api/categories.py — CSIT314

backend › app › api › categories.py › list_all_categories

```python
def list_all_categories(
    actor: CurrentAccountDep, service: ServiceDep
) -> list[CategoryPublic]:
    """Staff only."""
    try:
        categories = service.list_all(actor)
    except NotPermitted as exc:
        raise _fail(exc) from exc
    return [_to_public(category) for category in categories]
```

main — Python · UTF-8 · LF · lines 83–91

5.25 create_category()

backend/app/api/categories.py · lines 100–108

@router.post('', response_model=CategoryPublic, status_code=http_status.HTTP_201_CREATED, summary='Create a category')

Staff only.

categories.py — backend/app/api/categories.py — CSIT314

backend › app › api › categories.py › create_category

```python
def create_category(
    payload: CategoryInput, actor: CurrentAccountDep, service: ServiceDep
) -> CategoryPublic:
    """Staff only."""
    try:
        category = service.add(actor, payload.name)
    except (NotPermitted, CategoryExists, ValueError) as exc:
        raise _fail(exc) from exc
    return _to_public(category)
```

main — Python · UTF-8 · LF · lines 100–108

5.26 update_category()

backend/app/api/categories.py · lines 116–132

@router.patch('/{category_id}', response_model=CategoryPublic, summary='Rename, archive or restore a category')

Staff only.

categories.py — backend/app/api/categories.py — CSIT314

backend › app › api › categories.py › update_category

```python
def update_category(
    category_id: str,
    payload: CategoryPatch,
    actor: CurrentAccountDep,
    service: ServiceDep,
) -> CategoryPublic:
    """Staff only."""
    try:
        if payload.name is not None:
            service.rename(actor, category_id, payload.name)
        if payload.active is not None:
            category = service.set_active(actor, category_id, payload.active)
        else:
            category = service.get(actor, category_id)
    except (NotPermitted, CategoryNotFound, CategoryExists, ValueError) as exc:
        raise _fail(exc) from exc
    return _to_public(category)
```

main — Python · UTF-8 · LF · lines 116–132

5.27 _public()

backend/app/api/companies.py · lines 27–34

Return the public view, holding back the call link until it is earned.

companies.py — backend/app/api/companies.py — CSIT314

backend › app › api › companies.py › _public


```python
def _public(
    company, actor: Account, appointments: AppointmentService
) -> CompanyPublic:
    """Return the public view, holding back the call link until it is earned."""
    public = CompanyPublic.model_validate(company)
    if not appointments.may_read_call_link(actor, company.id):
        public.call_link = ""
    return public
```

main — Python · UTF-8 · LF · lines 27–34

5.28 _to_http()

backend/app/api/companies.py · lines 37–47

Map a domain refusal to the matching response.




5.29 create_company()

backend/app/api/companies.py · lines 56–67

@router.post('', response_model=CompanyPublic, status_code=http_status.HTTP_201_CREATED, summary='Create the company profile of the signed in designer')

Create the one profile this designer may hold.




5.30 read_my_company()

backend/app/api/companies.py · lines 75–83

@router.get('/me', response_model=CompanyPublic, summary='Read the company profile of the signed in designer')

Return the caller's own profile.




5.31 update_my_company()

backend/app/api/companies.py · lines 91–103

@router.patch('/me', response_model=CompanyPublic, summary="Change fields of the signed in designer's profile")

Write only the fields that were supplied.



5.32 list_companies()

backend/app/api/companies.py · lines 111–118

@router.get('', response_model=list[CompanyPublic], summary='List every company profile')

Return the published profiles so a customer can browse them.

companies.py — backend/app/api/companies.py — CSIT314

backend › app › api › companies.py › list_companies

```python
def list_companies(
    actor: CurrentAccountDep, service: ServiceDep, appointments: AppointmentsDep
) -> list[CompanyPublic]:
    """Return the published profiles so a customer can browse them."""
    return [
        _public(company, actor, appointments)
        for company in service.list_companies()
    ]
```

main · Python · UTF-8 · LF · lines 111–118

5.33 read_company()

backend/app/api/companies.py · lines 126–137

@router.get('/{company_id}', response_model=CompanyPublic, summary='Read any company profile by id')

Return a profile. Any signed in account may read it.

companies.py — backend/app/api/companies.py — CSIT314

backend › app › api › companies.py › read_company

```python
def read_company(
    company_id: str,
    actor: CurrentAccountDep,
    service: ServiceDep,
    appointments: AppointmentsDep,
) -> CompanyPublic:
    """Return a profile. Any signed in account may read it."""
    try:
        company = service.get(company_id)
    except CompanyNotFound as exc:
        raise _to_http(exc) from exc
    return _public(company, actor, appointments)
```

main · Python · UTF-8 · LF · lines 126–137

5.34 get_account_repository()

backend/app/api/deps.py · lines 51–53

Return the process wide account store.

deps.py — backend/app/api/deps.py — CSIT314

backend › app › api › deps.py › get_account_repository


```python
def get_account_repository() -> AccountRepository:
    """Return the process wide account store."""
    return _account_repository
```

main · Python · UTF-8 · LF · lines 51–53

5.35 get_account_service()

backend/app/api/deps.py · lines 56–58


Return a service bound to the shared account store.



5.36 get_company_repository()

backend/app/api/deps.py · lines 61–63

Return the process wide company store.



5.37 get_company_service()

backend/app/api/deps.py · lines 66–68

Return a service bound to the shared company store.



5.38 get_project_repository()

backend/app/api/deps.py · lines 71–73


Return the process wide project store.



5.39 get_project_service()

backend/app/api/deps.py · lines 76–78


Return a service bound to the shared project and company stores.



5.40 get_project_search_service()

backend/app/api/deps.py · lines 81–83

Return a search service bound to the shared project store.



5.41 get_shortlist_repository()

backend/app/api/deps.py · lines 86–88


Return the process wide shortlist store.



5.42 get_shortlist_service()

backend/app/api/deps.py · lines 91–93

Return a service bound to the shared shortlist and project stores.



5.43 get_quote_request_repository()

backend/app/api/deps.py · lines 96–98


Return the process wide quote request store.



5.44 get_quote_repository()

backend/app/api/deps.py · lines 101–103


Return the process wide quote store.



5.45 get_quote_service()

backend/app/api/deps.py · lines 106–113


Return a service bound to the shared quote, company and project stores.



5.46 get_appointment_repository()

backend/app/api/deps.py · lines 116–118


Return the process wide appointment store.



5.47 get_appointment_service()

backend/app/api/deps.py · lines 121–127

Return a service bound to the appointment, company and account stores.



5.48 get_report_repository()

backend/app/api/deps.py · lines 130–132


Return the process wide project report store.



5.49 get_project_report_service()

backend/app/api/deps.py · lines 135–141

Return a service bound to the report, project and account stores.



5.50 get_category_repository()

backend/app/api/deps.py · lines 144–146

Return the process wide category store.

deps.py — backend/app/api/deps.py — CSIT314

backend › app › api › deps.py › get_category_repository

```python
def get_category_repository() -> CategoryRepository:
    """Return the process wide category store."""
    return _category_repository
```

main — Python · UTF-8 · LF · lines 144–146

5.51 get_category_service()

backend/app/api/deps.py · lines 149–151

Return a service bound to the shared category store.

deps.py — backend/app/api/deps.py — CSIT314

backend › app › api › deps.py › get_category_service

```python
def get_category_service() -> CategoryService:
    """Return a service bound to the shared category store."""
    return CategoryService(get_category_repository())
```

main — Python · UTF-8 · LF · lines 149–151

5.52 get_report_service()

backend/app/api/deps.py · lines 154–161

Return a report service bound to the four stores that hold timestamps.

deps.py — backend/app/api/deps.py — CSIT314

backend › app › api › deps.py › get_report_service

```python
def get_report_service() -> ReportService:
    """Return a report service bound to the four stores that hold timestamps."""
    return ReportService(
        get_account_repository(),
        get_project_repository(),
        get_quote_request_repository(),
        get_quote_repository(),
    )
```

main — Python · UTF-8 · LF · lines 154–161

5.53 get_current_account()

backend/app/api/deps.py · lines 164–198

Return the account named by the bearer token.

deps.py — backend/app/api/deps.py — CSIT314

backend › app › api › deps.py › get_current_account

```python
# backend/app/api/deps.py — lines 164–198, first 20 lines of 35
def get_current_account(
    credentials: Annotated[HTTPAuthorizationCredentials | None, Depends(_bearer_scheme)],
    service: Annotated[AccountService, Depends(get_account_service)],
) -> Account:
    """Return the account named by the bearer token.

    Raises 401 for a missing, malformed, expired or orphaned token.
    """
    if credentials is None:
        raise HTTPException(
            status_code=status.HTTP_401_UNAUTHORIZED,
            detail="Not authenticated",
            headers={"WWW-Authenticate": "Bearer"},
        )
    try:
        claims = decode_access_token(credentials.credentials)
    except ValueError as exc:
        raise HTTPException(
            status_code=status.HTTP_401_UNAUTHORIZED,
            detail=str(exc),
    ...
```

main — Python · UTF-8 · LF · lines 164–198

5.54 HealthResponse

backend/app/api/health.py · lines 16–21

Liveness payload returned by the platform.

health.py — backend/app/api/health.py — CSIT314

backend › app › api › health.py › HealthResponse

```python
class HealthResponse(BaseModel):
    """Liveness payload returned by the platform."""

    status: Literal["ok"]
    version: str
    time: datetime
```

main — Python · UTF-8 · LF · lines 16–21

5.55 read_health()

backend/app/api/health.py · lines 25–31

@router.get('/health', response_model=HealthResponse, summary='Service liveness')

Report that the API is running.

health.py — backend/app/api/health.py — CSIT314

backend › app › api › health.py › read_health

```python
def read_health() -> HealthResponse:
    """Report that the API is running."""
    return HealthResponse(
        status="ok",
        version=APP_VERSION,
        time=datetime.now(timezone.utc),
    )
```

main — Python · UTF-8 · LF · lines 25–31

5.56 _read_photo()

backend/app/api/images.py · lines 58–78

Return the bytes of an allowed photo, or raise the refusal.

images.py — backend/app/api/images.py — CSIT314

backend › app › api › images.py › _read_photo

```python
async def _read_photo(file: UploadFile) -> bytes:
    """Return the bytes of an allowed photo, or raise the refusal."""
    declared = (file.content_type or "").lower()
    if declared and declared not in CONTENT_TYPES:
        raise HTTPException(
            status_code=http_status.HTTP_415_UNSUPPORTED_MEDIA_TYPE,
            detail="Upload a JPEG, PNG or WebP photo",
        )

    data = await file.read(MAX_UPLOAD_BYTES + 1)
    if len(data) > MAX_UPLOAD_BYTES:
        raise HTTPException(
            status_code=http_status.HTTP_413_REQUEST_ENTITY_TOO_LARGE,
            detail="The photo is larger than 5 MB",
        )
    if not data:
        raise HTTPException(
            status_code=http_status.HTTP_422_UNPROCESSABLE_ENTITY,
            detail="The file is empty",
        )
    return data
```

main — Python · UTF-8 · LF · lines 58–78

5.57 store_upload()

backend/app/api/images.py · lines 86–114

@router.post('', response_model=StoredImagePublic, summary='Store an uploaded photo and return its address')

Keep a designer's photo so the project can show it later.

images.py — backend/app/api/images.py — CSIT314

backend › app › api › images.py › store_upload

```python
async def store_upload(
    actor: CurrentAccountDep,
    file: UploadFile = File(...),
) -> StoredImagePublic:
    """Keep a designer's photo so the project can show it later.

    The file is checked the same way as the tag reader: Pillow decodes it, so a
    renamed text file is refused. The name is random, so two designers can both
    upload ``kitchen.jpg`` without meeting.
    """
    data = await _read_photo(file)

    try:
        with Image.open(io.BytesIO(data)) as probe:
            probe.verify()
        with Image.open(io.BytesIO(data)) as probe:
            width, height = probe.size
    except Exception as exc:  # Pillow raises several unrelated types
        raise HTTPException(
            status_code=http_status.HTTP_422_UNPROCESSABLE_ENTITY,
            detail="That file is not an image",
        ) from exc

    declared = (file.content_type or "").lower()
    name = f"{uuid.uuid4().hex}{EXTENSIONS.get(declared, '.jpg')}"
    UPLOAD_ROOT.mkdir(parents=True, exist_ok=True)
    (UPLOAD_ROOT / name).write_bytes(data)

    return StoredImagePublic(url=f"/uploads/{name}", width=width, height=height)
```

main — Python · UTF-8 · LF · lines 86–114

5.58 tags_for_upload()

backend/app/api/images.py · lines 122–169

@router.post('/tags', response_model=TagSuggestionPublic, summary='Read an uploaded photo and return catalogue tags')

Describe an uploaded photo. Any signed-in account may call this.

images.py — backend/app/api/images.py — CSIT314

backend › app › api › images.py › tags_for_upload

```python
# backend/app/api/images.py — lines 122–169, first 20 lines of 48
async def tags_for_upload(
    actor: CurrentAccountDep,
    file: UploadFile = File(...),
) -> TagSuggestionPublic:
    """Describe an uploaded photo. Any signed-in account may call this.

    The bytes are checked by Pillow, not by the declared type alone: a renamed
    text file is refused with 422.
    """
    declared = (file.content_type or "").lower()
    if declared and declared not in CONTENT_TYPES:
        raise HTTPException(
            status_code=http_status.HTTP_415_UNSUPPORTED_MEDIA_TYPE,
            detail="Upload a JPEG, PNG or WebP photo",
        )

    data = await file.read(MAX_UPLOAD_BYTES + 1)
    if len(data) > MAX_UPLOAD_BYTES:
        raise HTTPException(
            status_code=http_status.HTTP_413_REQUEST_ENTITY_TOO_LARGE,
    ...
```

main — Python · UTF-8 · LF · lines 122–169

5.59 _fail()

backend/app/api/project_reports.py · lines 28–42

Map a domain refusal to the matching response.

project_reports.py — backend/app/api/project_reports.py — CSIT314

backend › app › api › project_reports.py › _fail

```python
def _fail(exc: Exception) -> HTTPException:
    """Map a domain refusal to the matching response."""
    if isinstance(exc, (ReportNotFound, ProjectNotFound, AccountNotFound)):
        return HTTPException(
            status_code=http_status.HTTP_404_NOT_FOUND, detail=exc.message
        )
    if isinstance(exc, NotPermitted):
        return HTTPException(
            status_code=http_status.HTTP_403_FORBIDDEN, detail=exc.message
        )
    if isinstance(exc, InvalidState):
        return HTTPException(
            status_code=http_status.HTTP_409_CONFLICT, detail=exc.message
        )
    return HTTPException(status_code=http_status.HTTP_400_BAD_REQUEST, detail=str(exc))
```

main — Python · UTF-8 · LF · lines 28–42

5.60 _public()

backend/app/api/project_reports.py · lines 45–58

Return one report with the names the staff screen shows.

project_reports.py — backend/app/api/project_reports.py — CSIT314

backend › app › api › project_reports.py › _public

```python
def _public(
    service: ProjectReportService, report: ProjectReport
) -> ProjectReportPublic:
    """Return one report with the names the staff screen shows."""
    public = ProjectReportPublic.model_validate(report)
    public.project_title = service.project_title(report)
    designer = service.designer_of(report)
    if designer is not None:
        public.designer_name = designer.display_name
        public.designer_email = designer.email
    customer = service.customer_of(report)
    if customer is not None:
        public.customer_name = customer.display_name
    return public
```

main — Python · UTF-8 · LF · lines 45–58

5.61 list_reasons()

backend/app/api/project_reports.py · lines 66–68

@router.get('/reasons', response_model=list[str], summary='List the reasons the report form offers')

Return the fixed vocabulary, so the screen and the entity agree.

project_reports.py — backend/app/api/project_reports.py — CSIT314

backend › app › api › project_reports.py › list_reasons

```python
def list_reasons() -> list[str]:
    """Return the fixed vocabulary, so the screen and the entity agree."""
    return list(REPORT_REASONS)
```

main — Python · UTF-8 · LF · lines 66–68

5.62 report_project()

backend/app/api/project_reports.py · lines 77–87

@router.post('', response_model=ProjectReportPublic, status_code=http_status.HTTP_201_CREATED, summary='Report a project')

A customer flags a project for the administrator.

project_reports.py — backend/app/api/project_reports.py — CSIT314

backend › app › api › project_reports.py › report_project

```python
def report_project(
    payload: SubmitReport, actor: CurrentAccountDep, service: ServiceDep
) -> ProjectReportPublic:
    """A customer flags a project for the administrator."""
    try:
        report = service.submit(
            actor, payload.project_id, payload.reason, payload.comments
        )
    except (NotPermitted, ProjectNotFound, InvalidState, ValueError) as exc:
        raise _fail(exc) from exc
    return _public(service, report)
```

main — Python · UTF-8 · LF · lines 77–87

5.63 list_reports()

backend/app/api/project_reports.py · lines 95–103

@router.get('', response_model=list[ProjectReportPublic], summary='List every project report')

Return the report queue, newest first. Platform staff only.

project_reports.py — backend/app/api/project_reports.py — CSIT314

backend › app › api › project_reports.py › list_reports

```python
def list_reports(
    actor: CurrentAccountDep, service: ServiceDep
) -> list[ProjectReportPublic]:
    """Return the report queue, newest first. Platform staff only."""
    try:
        reports = service.list_reports(actor)
    except NotPermitted as exc:
        raise _fail(exc) from exc
    return [_public(service, report) for report in reports]
```

main — Python · UTF-8 · LF · lines 95–103

5.64 resolve_report()

backend/app/api/project_reports.py · lines 111–136

@router.post('/{report_id}/resolve', response_model=ProjectReportPublic, summary='Take a project down, suspend the designer, or dismiss')

Close one report, applying the chosen actions.

project_reports.py — backend/app/api/project_reports.py — CSIT314

backend › app › api › project_reports.py › resolve_report

```python
def resolve_report(
    report_id: str,
    payload: ResolveReport,
    actor: CurrentAccountDep,
    service: ServiceDep,
) -> ProjectReportPublic:
    """Close one report, applying the chosen actions.

    Both flags may be set. Neither flag dismisses the report.
    """
    try:
        report = service.resolve(
            actor,
            report_id,
            take_down=payload.take_down,
            suspend_designer=payload.suspend_designer,
        )
    except (
        ReportNotFound,
        ProjectNotFound,
        AccountNotFound,
        NotPermitted,
        InvalidState,
    ) as exc:
        raise _fail(exc) from exc
    return _public(service, report)
```

main — Python · UTF-8 · LF · lines 111–136

5.65 _to_http()

backend/app/api/projects.py · lines 43–51

Map a domain refusal to the matching response.

projects.py — backend/app/api/projects.py — CSIT314

backend › app › api › projects.py › _to_http

```python
def _to_http(exc: Exception) -> HTTPException:
    """Map a domain refusal to the matching response."""
    if isinstance(exc, ProjectNotFound):
        return HTTPException(status_code=http_status.HTTP_404_NOT_FOUND, detail=exc.message)
    if isinstance(exc, (CompanyNotFound, NotPermitted)):
        return HTTPException(status_code=http_status.HTTP_403_FORBIDDEN, detail=exc.message)
    if isinstance(exc, ValueError):
        return HTTPException(status_code=http_status.HTTP_400_BAD_REQUEST, detail=str(exc))
    return HTTPException(status_code=http_status.HTTP_400_BAD_REQUEST, detail=str(exc))
```

main — Python · UTF-8 · LF · lines 43–51

5.66 create_project()

backend/app/api/projects.py · lines 60–68

@router.post('', response_model=ProjectPublic, status_code=http_status.HTTP_201_CREATED, summary='Publish a project under the designer company')

Publish one portfolio project for the signed in designer.

projects.py — backend/app/api/projects.py — CSIT314

backend › app › api › projects.py › create_project

```python
def create_project(
    payload: ProjectCreate, actor: CurrentAccountDep, service: ServiceDep
) -> ProjectPublic:
    """Publish one portfolio project for the signed in designer."""
    try:
        project = service.create(actor, **payload.model_dump())
    except (NotPermitted, CompanyNotFound, ValueError) as exc:
        raise _to_http(exc) from exc
    return ProjectPublic.model_validate(project)
```

main — Python · UTF-8 · LF · lines 60–68

5.67 list_my_projects()

backend/app/api/projects.py · lines 76–95

@router.get('/mine', response_model=list[ProjectPublic], summary="List the signed in designer's portfolio")

Return the owner's projects filtered by status and title.

projects.py — backend/app/api/projects.py — CSIT314

backend › app › api › projects.py › list_my_projects

```python
def list_my_projects(
    actor: CurrentAccountDep,
    service: ServiceDep,
    status: ProjectStatus | None = None,
    name: str = "",
) -> list[ProjectPublic]:
    """Return the owner's projects filtered by status and title."""
    try:
        projects = service.list_for_owner(
            actor,
            status=status,
            name=name,
        )
    except NotPermitted as exc:
        raise _to_http(exc) from exc

    return [
        ProjectPublic.model_validate(project)
        for project in projects
    ]
```

main — Python · UTF-8 · LF · lines 76–95

5.68 list_company_projects()

backend/app/api/projects.py · lines 102–107

@router.get('/company/{company_id}', response_model=list[ProjectPublic], summary='List the published projects of one company')

Return the portfolio a customer browsing a designer would see.

projects.py — backend/app/api/projects.py — CSIT314

backend › app › api › projects.py › list_company_projects

```python
def list_company_projects(
    company_id: str, actor: CurrentAccountDep, service: ServiceDep
) -> list[ProjectPublic]:
    """Return the portfolio a customer browsing a designer would see."""
    projects = service.list_for_company(company_id)
    return [ProjectPublic.model_validate(project) for project in projects]
```

main — Python · UTF-8 · LF · lines 102–107

5.69 search_projects()

backend/app/api/projects.py · lines 115–153

@router.get('/search', response_model=SearchResponse, summary='Search the project catalogue')

Return one page of projects that match the filters.

projects.py — backend/app/api/projects.py — CSIT314

backend › app › api › projects.py › search_projects

```python
# backend/app/api/projects.py — lines 115-153, first 20 lines of 39
def search_projects(
    actor: CurrentAccountDep,
    service: SearchDep,
    keyword: str = "",
    category: str = "",
    style: str = "",
    budget_min: int | None = None,
    budget_max: int | None = None,
    tags: str = "",
    page: int = 1,
    page_size: int = 12,
) -> SearchResponse:
    """Return one page of projects that match the filters.

    ``tags`` takes a comma separated list. A project must carry at least one of
    them, and the closest match comes first.
    """
    try:
        result = service.search(
            keyword=keyword,
    ...
```

main — Python · UTF-8 · LF · lines 115–153

5.70 read_project()

backend/app/api/projects.py · lines 161–169

@router.get('/{project_id}', response_model=ProjectPublic, summary='Read one project')

Return a project. Any signed in account may read it, unless it was taken down.

projects.py — backend/app/api/projects.py — CSIT314

backend › app › api › projects.py › read_project

```python
def read_project(
    project_id: str, actor: CurrentAccountDep, service: ServiceDep
) -> ProjectPublic:
    """Return a project. Any signed in account may read it, unless it was taken down."""
    try:
        project = service.get(project_id, actor)
    except ProjectNotFound as exc:
        raise _to_http(exc) from exc
    return ProjectPublic.model_validate(project)
```

main — Python · UTF-8 · LF · lines 161–169

5.71 update_project()

backend/app/api/projects.py · lines 177–189

@router.patch('/{project_id}', response_model=ProjectPublic, summary='Change fields of your own project')

Write only the supplied fields.

projects.py — backend/app/api/projects.py — CSIT314

backend › app › api › projects.py › update_project

```python
def update_project(
    project_id: str,
    payload: ProjectUpdate,
    actor: CurrentAccountDep,
    service: ServiceDep,
) -> ProjectPublic:
    """Write only the supplied fields."""
    changes = payload.model_dump(exclude_unset=True)
    try:
        project = service.update(actor, project_id, **changes)
    except (ProjectNotFound, NotPermitted, ValueError) as exc:
        raise _to_http(exc) from exc
    return ProjectPublic.model_validate(project)
```

main — Python · UTF-8 · LF · lines 177–189

5.72 delete_project()

backend/app/api/projects.py · lines 197–205

@router.delete('/{project_id}', status_code=http_status.HTTP_204_NO_CONTENT, summary='Delete your own project')

Remove a project from the portfolio.

projects.py — backend/app/api/projects.py — CSIT314

backend › app › api › projects.py › delete_project

```python
def delete_project(
    project_id: str, actor: CurrentAccountDep, service: ServiceDep
) -> Response:
    """Remove a project from the portfolio."""
    try:
        service.delete(actor, project_id)
    except (ProjectNotFound, NotPermitted) as exc:
        raise _to_http(exc) from exc
    return Response(status_code=http_status.HTTP_204_NO_CONTENT)
```

main — Python · UTF-8 · LF · lines 197–205

5.73 record_project_view()

backend/app/api/projects.py · lines 213–222

@router.post('/{project_id}/view', status_code=http_status.HTTP_204_NO_CONTENT, summary='Count one look at a project')

Raise the view counter. The read endpoint stays free of side effects.

projects.py — backend/app/api/projects.py — CSIT314

backend › app › api › projects.py › record_project_view

```python
def record_project_view(
    project_id: str, actor: CurrentAccountDep, service: ServiceDep
) -> Response:
    """Raise the view counter. The read endpoint stays free of side effects."""
    try:
        project = service.get(project_id)
    except ProjectNotFound as exc:
        raise _to_http(exc) from exc
    project.record_view()
    return Response(status_code=http_status.HTTP_204_NO_CONTENT)
```

main — Python · UTF-8 · LF · lines 213–222

5.74 suggest_project_tags()

backend/app/api/projects.py · lines 230–281

@router.post('/{project_id}/suggest-tags', response_model=TagSuggestionPublic, summary='Suggest description tags for one of your project photos')

Read one photo of your project and offer palette and mood tags.

projects.py — backend/app/api/projects.py — CSIT314

backend › app › api › projects.py › suggest_project_tags

```python
# backend/app/api/projects.py — lines 230–281, first 20 lines of 52
def suggest_project_tags(
    project_id: str,
    actor: CurrentAccountDep,
    service: ServiceDep,
    image_index: int = 0,
) -> TagSuggestionPublic:
    """Read one photo of your project and offer palette and mood tags.

    Nothing is saved. The designer accepts what fits and edits the rest.
    """
    try:
        project = service.require_owned(actor, project_id)
    except (ProjectNotFound, NotPermitted) as exc:
        raise _to_http(exc) from exc

    if not project.images:
        raise HTTPException(
            status_code=http_status.HTTP_400_BAD_REQUEST,
            detail="The project has no photo to analyse",
        )
    ...
```

main — Python · UTF-8 · LF · lines 230–281

5.75 _fail()

backend/app/api/quotes.py · lines 37–45

Map a domain refusal to the matching response.

quotes.py — backend/app/api/quotes.py — CSIT314

backend › app › api › quotes.py › _fail

```python
def _fail(exc: Exception) -> HTTPException:
    """Map a domain refusal to the matching response."""
    if isinstance(exc, (QuoteRequestNotFound, QuoteNotFound, CompanyNotFound, ProjectNotFound)):
        return HTTPException(status_code=http_status.HTTP_404_NOT_FOUND, detail=exc.message)
    if isinstance(exc, NotPermitted):
        return HTTPException(status_code=http_status.HTTP_403_FORBIDDEN, detail=exc.message)
    if isinstance(exc, InvalidState):
        return HTTPException(status_code=http_status.HTTP_409_CONFLICT, detail=exc.message)
    return HTTPException(status_code=http_status.HTTP_400_BAD_REQUEST, detail=str(exc))
```

main — Python · UTF-8 · LF · lines 37–45

5.76 _detail()

backend/app/api/quotes.py · lines 48–54

quotes.py — backend/app/api/quotes.py — CSIT314

backend › app › api › quotes.py › _detail

```python
def _detail(service: QuoteService, actor: Account, request_id: str) -> QuoteRequestDetail:
    request = service.get_request(actor, request_id)
    quotes = service.quotes_for(actor, request_id)
    return QuoteRequestDetail(
        **QuoteRequestPublic.model_validate(request).model_dump(),
        quotes=[QuotePublic.model_validate(quote) for quote in quotes],
    )
```

main — Python · UTF-8 · LF · lines 48–54

5.77 submit_request()

backend/app/api/quotes.py · lines 63–71

@router.post('/requests', response_model=QuoteRequestPublic, status_code=http_status.HTTP_201_CREATED, summary='Send a quote request to one company')

A customer asks one company for a price.

quotes.py — backend/app/api/quotes.py — CSIT314

backend › app › api › quotes.py › submit_request

```python
def submit_request(
    payload: SubmitRequest, actor: CurrentAccountDep, service: ServiceDep
) -> QuoteRequestPublic:
    """A customer asks one company for a price."""
    try:
        request = service.submit(actor, **payload.model_dump())
    except (NotPermitted, CompanyNotFound, ProjectNotFound, InvalidState, ValueError) as exc:
        raise _fail(exc) from exc
    return QuoteRequestPublic.model_validate(request)
```

main — Python · UTF-8 · LF · lines 63–71

5.78 list_requests()

backend/app/api/quotes.py · lines 79–92

@router.get('/requests', response_model=list[QuoteRequestPublic], summary='List the requests you may see')

Customers see what they sent; designers see what their company received.

quotes.py — backend/app/api/quotes.py — CSIT314

backend › app › api › quotes.py › list_requests

```python
def list_requests(
    actor: CurrentAccountDep,
    service: ServiceDep,
    state: QuoteRequestState | None = None,
) -> list[QuoteRequestPublic]:
    """Customers see what they sent; designers see what their company received."""
    try:
        if actor.role.value == "CUSTOMER":
            requests = service.list_for_customer(actor, state)
        else:
            requests = service.list_for_designer(actor, state)
    except (NotPermitted, CompanyNotFound) as exc:
        raise _fail(exc) from exc
    return [QuoteRequestPublic.model_validate(request) for request in requests]
```

main — Python · UTF-8 · LF · lines 79–92

5.79 read_request()

backend/app/api/quotes.py · lines 100–107

@router.get('/requests/{request_id}', response_model=QuoteRequestDetail, summary='Read one request with every quote version')

Return one request to a customer, the company, or platform staff.

quotes.py — backend/app/api/quotes.py — CSIT314

backend › app › api › quotes.py › read_request

```python
def read_request(
    request_id: str, actor: CurrentAccountDep, service: ServiceDep
) -> QuoteRequestDetail:
    """Return one request to a customer, the company, or platform staff."""
    try:
        return _detail(service, actor, request_id)
    except (QuoteRequestNotFound, NotPermitted) as exc:
        raise _fail(exc) from exc
```

main — Python · UTF-8 · LF · lines 100–107

5.80 counter_request()

backend/app/api/quotes.py · lines 115–126

@router.post('/requests/{request_id}/counter', response_model=QuoteRequestDetail, summary='Name a target price')

The customer records the price they want. It does not bind the designer.

quotes.py — backend/app/api/quotes.py — CSIT314

backend › app › api › quotes.py › counter_request

```python
def counter_request(
    request_id: str,
    payload: CounterRequest,
    actor: CurrentAccountDep,
    service: ServiceDep,
) -> QuoteRequestDetail:
    """The customer records the price they want. It does not bind the designer."""
    try:
        service.counter(actor, request_id, payload.target_cents, payload.note)
        return _detail(service, actor, request_id)
    except (QuoteRequestNotFound, NotPermitted, InvalidState) as exc:
        raise _fail(exc) from exc
```

main — Python · UTF-8 · LF · lines 115–126

5.81 cancel_request()

backend/app/api/quotes.py · lines 134–145

@router.post('/requests/{request_id}/cancel', response_model=QuoteRequestPublic, summary='Cancel your request')

Stop an open request.

quotes.py — backend/app/api/quotes.py — CSIT314

backend › app › api › quotes.py › cancel_request

```python
def cancel_request(
    request_id: str,
    payload: ReasonRequest,
    actor: CurrentAccountDep,
    service: ServiceDep,
) -> QuoteRequestPublic:
    """Stop an open request."""
    try:
        request = service.cancel(actor, request_id, payload.reason)
    except (QuoteRequestNotFound, NotPermitted, InvalidState) as exc:
        raise _fail(exc) from exc
    return QuoteRequestPublic.model_validate(request)
```

main — Python · UTF-8 · LF · lines 134–145

5.82 refuse_request()

backend/app/api/quotes.py · lines 153–164

@router.post('/requests/{request_id}/refuse', response_model=QuoteRequestPublic, summary='Decline to quote')

The company declines the request.

quotes.py — backend/app/api/quotes.py — CSIT314

backend › app › api › quotes.py › refuse_request

```python
def refuse_request(
    request_id: str,
    payload: ReasonRequest,
    actor: CurrentAccountDep,
    service: ServiceDep,
) -> QuoteRequestPublic:
    """The company declines the request."""
    try:
        request = service.refuse(actor, request_id, payload.reason)
    except (QuoteRequestNotFound, NotPermitted, CompanyNotFound, InvalidState) as exc:
        raise _fail(exc) from exc
    return QuoteRequestPublic.model_validate(request)
```

main — Python · UTF-8 · LF · lines 153–164

5.83 answer_request()

backend/app/api/quotes.py · lines 173–184

@router.post('/requests/{request_id}/quotes', response_model=QuotePublic, status_code=http_status.HTTP_201_CREATED, summary='Answer a request with a total')

The company sends version one of the quote.

quotes.py — backend/app/api/quotes.py — CSIT314

backend › app › api › quotes.py › answer_request

```python
def answer_request(
    request_id: str,
    payload: AnswerRequest,
    actor: CurrentAccountDep,
    service: ServiceDep,
) -> QuotePublic:
    """The company sends version one of the quote."""
    try:
        quote = service.answer(actor, request_id, **payload.model_dump())
    except (QuoteRequestNotFound, NotPermitted, CompanyNotFound, InvalidState) as exc:
        raise _fail(exc) from exc
    return QuotePublic.model_validate(quote)
```

main — Python · UTF-8 · LF · lines 173–184

5.84 list_quotes()

backend/app/api/quotes.py · lines 192–200

@router.get('/requests/{request_id}/quotes', response_model=list[QuotePublic], summary="List every version of a request's quote")

Return the versions, oldest first.

quotes.py — backend/app/api/quotes.py — CSIT314

backend › app › api › quotes.py › list_quotes

```python
def list_quotes(
    request_id: str, actor: CurrentAccountDep, service: ServiceDep
) -> list[QuotePublic]:
    """Return the versions, oldest first."""
    try:
        quotes = service.quotes_for(actor, request_id)
    except (QuoteRequestNotFound, NotPermitted) as exc:
        raise _fail(exc) from exc
    return [QuotePublic.model_validate(quote) for quote in quotes]
```

main — Python · UTF-8 · LF · lines 192–200

5.85 revise_quote()

backend/app/api/quotes.py · lines 209–220

@router.post('/{quote_id}/revise', response_model=QuotePublic, status_code=http_status.HTTP_201_CREATED, summary='Send the next version of a quote')

Replace the offered total with a new version.

quotes.py — backend/app/api/quotes.py — CSIT314

backend › app › api › quotes.py › revise_quote

```python
def revise_quote(
    quote_id: str,
    payload: AnswerRequest,
    actor: CurrentAccountDep,
    service: ServiceDep,
) -> QuotePublic:
    """Replace the offered total with a new version."""
    try:
        quote = service.revise(actor, quote_id, **payload.model_dump())
    except (QuoteNotFound, QuoteRequestNotFound, NotPermitted, InvalidState) as exc:
        raise _fail(exc) from exc
    return QuotePublic.model_validate(quote)
```

main — Python · UTF-8 · LF · lines 209–220

5.86 accept_quote()

backend/app/api/quotes.py · lines 228–236

@router.post('/{quote_id}/accept', response_model=QuotePublic, summary='Accept a quote')

Accept one quote. Other open requests stay open.

quotes.py — backend/app/api/quotes.py — CSIT314

backend › app › api › quotes.py › accept_quote

```python
def accept_quote(
    quote_id: str, actor: CurrentAccountDep, service: ServiceDep
) -> QuotePublic:
    """Accept one quote. Other open requests stay open."""
    try:
        quote = service.accept(actor, quote_id)
    except (QuoteNotFound, QuoteRequestNotFound, NotPermitted, InvalidState) as exc:
        raise _fail(exc) from exc
    return QuotePublic.model_validate(quote)
```

main — Python · UTF-8 · LF · lines 228–236

5.87 decline_quote()

backend/app/api/quotes.py · lines 244–255

@router.post('/{quote_id}/decline', response_model=QuotePublic, summary='Decline a quote')

Turn one quote down with an optional reason.

quotes.py — backend/app/api/quotes.py — CSIT314

backend › app › api › quotes.py › decline_quote

```python
def decline_quote(
    quote_id: str,
    payload: ReasonRequest,
    actor: CurrentAccountDep,
    service: ServiceDep,
) -> QuotePublic:
    """Turn one quote down with an optional reason."""
    try:
        quote = service.decline(actor, quote_id, payload.reason)
    except (QuoteNotFound, QuoteRequestNotFound, NotPermitted, InvalidState) as exc:
        raise _fail(exc) from exc
    return QuotePublic.model_validate(quote)
```

main — Python · UTF-8 · LF · lines 244–255

5.88 BucketPublic

backend/app/api/reports.py · lines 22–31

One period of activity.

reports.py — backend/app/api/reports.py — CSIT314

backend › app › api › reports.py › BucketPublic

```python
class BucketPublic(BaseModel):
    """One period of activity."""

    label: str
    start: str
    end: str
    accounts: int
    projects: int
    quote_requests: int
    quotes: int
```

main — Python · UTF-8 · LF · lines 22–31

5.89 ReportPublic

backend/app/api/reports.py · lines 34–38

A report with its period and buckets.

reports.py — backend/app/api/reports.py — CSIT314

backend › app › api › reports.py › ReportPublic

```python
class ReportPublic(BaseModel):
    """A report with its period and buckets."""

    period: str
    buckets: list[BucketPublic]
```

main — Python · UTF-8 · LF · lines 34–38

5.90 read_report()

backend/app/api/reports.py · lines 46–83

@router.get('', response_model=ReportPublic, summary='Read the activity report')

Staff only. Buckets run oldest first and end at now.

reports.py — backend/app/api/reports.py — CSIT314

backend › app › api › reports.py › read_report

```python
# backend/app/api/reports.py — lines 46–83, first 20 lines of 38
def read_report(
    actor: CurrentAccountDep,
    service: ServiceDep,
    period: str = "daily",
    buckets: int = DEFAULT_BUCKETS,
) -> ReportPublic:
    """Staff only. Buckets run oldest first and end at now."""
    if actor.role not in PRIVILEGED_ROLES:
        raise HTTPException(
            status_code=http_status.HTTP_403_FORBIDDEN,
            detail="Only platform staff may read reports",
        )
    if buckets < 1 or buckets > MAX_BUCKETS:
        raise HTTPException(
            status_code=http_status.HTTP_400_BAD_REQUEST,
            detail=f"Buckets must sit between 1 and {MAX_BUCKETS}",
        )
    try:
        report = service.build(period=period, buckets=buckets)
    except ValueError as exc:
    ...
```

main — Python · UTF-8 · LF · lines 46–83

5.91 _forbidden()

backend/app/api/shortlist.py · lines 22–23

shortlist.py — backend/app/api/shortlist.py — CSIT314

backend › app › api › shortlist.py › _forbidden

```python
def _forbidden(exc: NotPermitted) -> HTTPException:
    return HTTPException(status_code=http_status.HTTP_403_FORBIDDEN, detail=exc.message)
```

main — Python · UTF-8 · LF · lines 22–23

5.92 read_shortlist()

backend/app/api/shortlist.py · lines 31–41

@router.get('', response_model=ShortlistResponse, summary='Read the saved projects of the signed in customer')

Return the caller's saved projects, oldest save first.

shortlist.py — backend/app/api/shortlist.py — CSIT314

backend › app › api › shortlist.py › read_shortlist

```python
def read_shortlist(actor: CurrentAccountDep, service: ServiceDep) -> ShortlistResponse:
    """Return the caller's saved projects, oldest save first."""
    try:
        projects = service.list_for(actor)
        project_ids = service.ids_for(actor)
    except NotPermitted as exc:
        raise _forbidden(exc) from exc
    return ShortlistResponse(
        project_ids=project_ids,
        items=[ProjectPublic.model_validate(project) for project in projects],
    )
```

main — Python · UTF-8 · LF · lines 31–41

5.93 save_project()

backend/app/api/shortlist.py · lines 50–67

@router.post('/{project_id}', response_model=ShortlistResponse, status_code=http_status.HTTP_201_CREATED, summary='Save a project for the signed in customer')

Save one project. Saving a saved project changes nothing.

shortlist.py — backend/app/api/shortlist.py — CSIT314

backend › app › api › shortlist.py › save_project

```python
def save_project(
    project_id: str, actor: CurrentAccountDep, service: ServiceDep
) -> ShortlistResponse:
    """Save one project. Saving a saved project changes nothing."""
    try:
        service.add(actor, project_id)
        projects = service.list_for(actor)
        project_ids = service.ids_for(actor)
    except NotPermitted as exc:
        raise _forbidden(exc) from exc
    except ProjectNotFound as exc:
        raise HTTPException(
            status_code=http_status.HTTP_404_NOT_FOUND, detail=exc.message
        ) from exc
    return ShortlistResponse(
        project_ids=project_ids,
        items=[ProjectPublic.model_validate(project) for project in projects],
    )
```

main — Python · UTF-8 · LF · lines 50–67

5.94 unsave_project()

backend/app/api/shortlist.py · lines 75–83

@router.delete('/{project_id}', status_code=http_status.HTTP_204_NO_CONTENT, summary="Drop a project from the signed in customer's shortlist")

Drop one project. Dropping an absent project changes nothing.

shortlist.py — backend/app/api/shortlist.py — CSIT314

backend › app › api › shortlist.py › unsave_project

```python
def unsave_project(
    project_id: str, actor: CurrentAccountDep, service: ServiceDep
) -> Response:
    """Drop one project. Dropping an absent project changes nothing."""
    try:
        service.remove(actor, project_id)
    except NotPermitted as exc:
        raise _forbidden(exc) from exc
    return Response(status_code=http_status.HTTP_204_NO_CONTENT)
```

main — Python · UTF-8 · LF · lines 75–83

6 Data transfer shapes: backend/app/schemas

A schema is not a domain object. It states what the browser may send and what it receives. The validators in these classes reject a bad request before any use case runs.

Schema	File	Lines	Fields
AccountPublic	account.py	12–22	id, email, display_name, role, status, created_at
RegisterRequest	account.py	25–48	email, password, display_name, role
LoginRequest	account.py	51–55	email, password
TokenResponse	account.py	58–64	access_token, token_type, expires_in, account
AppointmentPublic	appointment.py	12–29	id, customer_id, company_id, appointment_date, appointment_time, mode,
SlotsPublic	appointment.py	32–36	date, slots
BookRequest	appointment.py	39–46	company_id, date, time, mode, requirements
CompanyPublic	company.py	10–27	id, owner_id, name, description, contact_email, contact_phone, locatio
CompanyCreate	company.py	30–40	name, description, contact_email, contact_phone, location, meeting_add
CompanyUpdate	company.py	43–57	name, description, contact_email, contact_phone, location, meeting_add
ProjectPublic	project.py	12–32	id, owner_id, company_id, title, description, style, category, budget_
ProjectCreate	project.py	35–45	title, description, style, category, budget_min, budget_max, images, t
ProjectUpdate	project.py	48–62	title, description, style, category, budget_min, budget_max, status, i
SearchResponse	project.py	65–72	items, total, page, page_size, pages
PaletteEntryPublic	project.py	75–79	hex, percent
TagSuggestionPublic	project.py	82–91	palette, tags, width, height, engine, subject, objects
StoredImagePublic	project.py	94–99	url, width, height
CounterPublic	quote.py	12–20	id, target_cents, note, created_at
QuotePublic	quote.py	23–39	id, request_id, version, total_cents, gst_included, gst_rate_bp, gst_c
QuoteRequestPublic	quote.py	42–60	id, customer_id, company_id, project_id, title, scope, budget_min_cent
QuoteRequestDetail	quote.py	63–66	quotes
SubmitRequest	quote.py	69–78	company_id, title, scope, budget_min_cents, budget_max_cents, target_c
CounterRequest	quote.py	81–85	target_cents, note
AnswerRequest	quote.py	88–94	total_cents, valid_days, gst_included, note
ReasonRequest	quote.py	97–100	reason
ProjectReportPublic	report.py	12–28	id, customer_id, project_id, reason, comments, status, created_at, res
SubmitReport	report.py	31–36	project_id, reason, comments
ResolveReport	report.py	39–46	take_down, suspend_designer
ShortlistResponse	shortlist.py	10–14	project_ids, items

The matching front-end types live in frontend/src/types.ts. They mirror these shapes and add the enum values the browser needs.

Kind	Name	Where
type	Role	frontend/src/types.ts:1
type	Status	frontend/src/types.ts:3
type	RegistrationRole	frontend/src/types.ts:6
interface	AccountPublic	frontend/src/types.ts:8
interface	HealthResponse	frontend/src/types.ts:17
interface	CompanyPublic	frontend/src/types.ts:23
interface	CompanyInput	frontend/src/types.ts:39
type	ProjectStatus	frontend/src/types.ts:50

interface	ProjectPublic	frontend/src/types.ts:52
interface	SearchResponse	frontend/src/types.ts:71
interface	SearchParams	frontend/src/types.ts:79
interface	BudgetRange	frontend/src/types.ts:90
interface	Catalogue	frontend/src/types.ts:96
interface	RegisterRequest	frontend/src/types.ts:102
interface	LoginRequest	frontend/src/types.ts:109
interface	TokenResponse	frontend/src/types.ts:114
interface	ProjectInput	frontend/src/types.ts:121
interface	TagSuggestion	frontend/src/types.ts:132
interface	StoredImage	frontend/src/types.ts:142
interface	ShortlistResponse	frontend/src/types.ts:148
type	QuoteRequestState	frontend/src/types.ts:153
type	QuoteState	frontend/src/types.ts:162
interface	QuoteCounter	frontend/src/types.ts:169
interface	QuotePublic	frontend/src/types.ts:176
interface	QuoteRequestPublic	frontend/src/types.ts:191
interface	QuoteRequestDetail	frontend/src/types.ts:208
interface	CategoryPublic	frontend/src/types.ts:212
interface	ReportBucket	frontend/src/types.ts:220
interface	Report	frontend/src/types.ts:230
type	AppointmentState	frontend/src/types.ts:235
type	ConsultationMode	frontend/src/types.ts:238
interface	AppointmentPublic	frontend/src/types.ts:241
interface	SlotsResponse	frontend/src/types.ts:258
type	ReportStatus	frontend/src/types.ts:263
interface	ProjectReportPublic	frontend/src/types.ts:266

7 Boundary layer: the browser

Each page is a boundary object. It draws the screen, holds the form state and calls one function in api.ts per endpoint. The table under each page names the calls it makes, so a sequence diagram can draw the message from page to API.

Route	Component	Who may open it
/	Home	any
/login	Login	any
/register	Register	any
/dashboard	Dashboard	signed in
/search	Search	signed in
/designers	Designers	signed in
/designers/:companyId	DesignerDetail	signed in
/profile	Profile	DESIGNER
/admin	Admin	ADMIN
/projects/new	ProjectEditor	DESIGNER
/projects/:projectId/edit	ProjectEditor	DESIGNER
/projects/:projectId	ProjectDetail	signed in
/saved	Saved	CUSTOMER
/projects	MyProjects	DESIGNER
/designers/:companyId/book	BookConsultation	CUSTOMER
/appointments	Appointments	CUSTOMER, DESIGNER
/quotes/new/:companyId	RequestQuote	CUSTOMER
/quotes/:requestId	QuoteDetail	signed in
/quotes	Quotes	signed in
/platform	Platform	ADMIN, PLATFORM_MANAGER
*	redirect	any

7.1 App

frontend/src/App.tsx · line 24

App.tsx — frontend/src/App.tsx — CSIT314

frontend › src › App.tsx › App

```tsx
export default function App() {
  const { account, loading, logout } = useAuth();

  return (
    <div className="shell">
      <header className="site-header">
        <div className="container header-inner">
          <Link className="brand" to="/">
            Interior Design Platform
          </Link>
          <nav className="nav" aria-label="Main">
            <NavLink to="/" end>
              Home
            </NavLink>
            {account !== null && (
              <>
                <NavLink to="/dashboard">Dashboard</NavLink>
                <NavLink to="/search">Find a project</NavLink>
                <NavLink to="/designers">Designers</NavLink>
                {account.role === 'CUSTOMER' && <NavLink to="/saved">Saved</NavLink>}
                {(account.role === 'CUSTOMER' || account.role === 'DESIGNER') && (
                  <NavLink to="/quotes">
                    {account.role === 'DESIGNER' ? 'Quote inbox' : 'Requests'}
                  </NavLink>
                )}
                {(account.role === 'CUSTOMER' || account.role === 'DESIGNER') && (
                  <NavLink to="/appointments">
                    {account.role === 'DESIGNER' ? 'Consultations' : 'Appointments'}
                  </NavLink>
```

main — TypeScript React · UTF-8 · LF · lines 24–24

Calls: no endpoint directly; it composes other components.

7.2 AuthProvider

frontend/src/auth.tsx · line 25

auth.tsx — frontend/src/auth.tsx — CSIT314

frontend › src › auth.tsx › AuthProvider

```tsx
export function AuthProvider({ children }: { children: ReactNode }) {
  const [account, setAccount] = useState<AccountPublic | null>(null);
  const [token, setTokenState] = useState<string | null>(() => getToken());
  const [loading, setLoading] = useState(true);

  useEffect(() => {
    let cancelled = false;

    async function restoreSession() {
      if (getToken() === null) {
        setLoading(false);
        return;
      }
      try {
        const current = await me();
        if (cancelled) return;
        setAccount(current);
        setTokenState(getToken());
      } catch (error) {
        if (cancelled) return;
        // Only a rejected token ends the session. A network failure keeps the
        // token so the next reload can retry instead of forcing a new sign in.
        if (error instanceof ApiError && (error.status === 401 || error.status === 403)) {
          clearToken();
        }
        setTokenState(getToken());
        setAccount(null);
      } finally {
        if (!cancelled) setLoading(false);
```

main — TypeScript React · UTF-8 · LF · lines 25–25

Calls: clearToken, getToken, login, me, register, setToken.

React hooks: useContext, useEffect, useState.

Function	Line
async function restoreSession() {	33

7.3 ProtectedRoute

frontend/src/components/ProtectedRoute.tsx · line 11

ProtectedRoute.tsx — frontend/src/components/ProtectedRoute.tsx — CSIT314

frontend › src › components › ProtectedRoute.tsx › ProtectedRoute

```tsx
export default function ProtectedRoute({ children, roles }: ProtectedRouteProps) {
  const { account, loading } = useAuth();
  const location = useLocation();

  if (loading) {
    return (
      <div className="page-state" role="status">
        Checking your session…
      </div>
    );
  }

  if (account === null) {
    return <Navigate to="/login" replace state={{ from: location.pathname }} />;
  }

  if (roles !== undefined && !roles.includes(account.role)) {
    return <Navigate to="/dashboard" replace />;
  }

  return <>{children}</>;
}
```

main — TypeScript React · UTF-8 · LF · lines 11–11

Calls: no endpoint directly; it composes other components.

7.4 Home

frontend/src/pages/Home.tsx · line 19

Home.tsx frontend/src/pages/Home.tsx — CSIT314

frontend › src › pages › Home.tsx › Home

```tsx
export default function Home() {
  const { account } = useAuth();
  const [state, setState] = useState<HealthState>('loading');
  const [info, setInfo] = useState<HealthResponse | null>(null);
  const [error, setError] = useState<string | null>(null);

  useEffect(() => {
    let cancelled = false;

    health()
      .then((result) => {
        if (cancelled) return;
        setInfo(result);
        setState('online');
      })
      .catch((caught: unknown) => {
        if (cancelled) return;
        setError(describeFailure(caught));
        setState('offline');
      });

    return () => {
      cancelled = true;
    };
  }, []);

  return (
    <div className="stack">
      <section className="card hero">
```

main TypeScript React · UTF-8 · LF · lines 19–19

Calls: health.

React hooks: useEffect, useState.

Function	Line
function describeFailure(caught: unknown): string {	9

7.5 Login

frontend/src/pages/Login.tsx · line 7

Login.tsx frontend/src/pages/Login.tsx — CSIT314

frontend › src › pages › Login.tsx › Login

```tsx
export default function Login() {
  const { account, loading, login } = useAuth();
  const navigate = useNavigate();
  const location = useLocation();
  const destination = (location.state as { from?: string } | null)?.from ?? '/dashboard';
  const [email, setEmail] = useState('');
  const [password, setPassword] = useState('');
  const [error, setError] = useState<string | null>(null);
  const [submitting, setSubmitting] = useState(false);

  if (!loading && account !== null) {
    return <Navigate to={destination} replace />;
  }

  async function handleSubmit(event: FormEvent<HTMLFormElement>) {
    event.preventDefault();
    setError(null);
    setSubmitting(true);
    try {
      await login({ email: email.trim(), password });
      navigate(destination, { replace: true });
    } catch (caught) {
      setError(caught instanceof ApiError ? caught.detail : 'Unable to sign in. Try again.');
    } finally {
      setSubmitting(false);
    }
  }

  return (
```

main TypeScript React · UTF-8 · LF · lines 7–7

Calls: no endpoint directly; it composes other components.

React hooks: useNavigate, useState.

Function	Line
async function handleSubmit(event: FormEvent<HTMLFormElement>) {	21

7.6 Register

frontend/src/pages/Register.tsx · line 8

Register.tsx — frontend/src/pages/Register.tsx — CSIT314

frontend › src › pages › Register.tsx › Register

```tsx
export default function Register() {
  const { register } = useAuth();
  const [email, setEmail] = useState('');
  const [displayName, setDisplayName] = useState('');
  const [password, setPassword] = useState('');
  const [role, setRole] = useState<RegistrationRole>('CUSTOMER');
  const [error, setError] = useState<string | null>(null);
  const [submitting, setSubmitting] = useState(false);
  const [created, setCreated] = useState(false);

  function handleRoleChange(event: ChangeEvent<HTMLSelectElement>) {
    const value = event.target.value;
    if (value === 'CUSTOMER' || value === 'DESIGNER') {
      setRole(value);
    }
  }

  async function handleSubmit(event: FormEvent<HTMLFormElement>) {
    event.preventDefault();
    setError(null);
    setSubmitting(true);
    try {
      await register({
        email: email.trim(),
        password,
        display_name: displayName.trim(),
        role,
      });
      setCreated(true);
```

main — TypeScript React · UTF-8 · LF · lines 8–8

Calls: no endpoint directly; it composes other components.

React hooks: useState.

Function	Line
function handleRoleChange(event: ChangeEvent<HTMLSelectElement>) {	18
async function handleSubmit(event: FormEvent<HTMLFormElement>) {	25

7.7 Dashboard

frontend/src/pages/Dashboard.tsx · line 24

Dashboard.tsx — frontend/src/pages/Dashboard.tsx — CSIT314

frontend › src › pages › Dashboard.tsx › Dashboard

```tsx
export default function Dashboard() {
  const { account, logout } = useAuth();
  const navigate = useNavigate();

  if (account === null) {
    return null;
  }

  function handleLogout() {
    logout();
    navigate('/login', { replace: true });
  }

  return (
    <div className="stack">
      <div className="page-head">
        <div>
          <h1>Dashboard</h1>
          <p className="muted">Signed in as {account.email}</p>
        </div>
        <button type="button" className="button button-secondary" onClick={handleLogout}>
          Log out
        </button>
      </div>

      {account.status === 'PENDING' && (
        <p className="alert alert-notice" role="status">
          Your account is waiting for admin approval. Designer accounts become active once an
          administrator reviews them.
```

main — TypeScript React · UTF-8 · LF · lines 24–24

Calls: no endpoint directly; it composes other components.

React hooks: useNavigate.

Function	Line
function formatDate(value: string): string {	18
function handleLogout() {	32

7.8 Search

frontend/src/pages/Search.tsx · line 18

Search.tsx frontend/src/pages/Search.tsx — CSIT314

frontend › src › pages › Search.tsx › Search

```tsx
export default function Search() {
  const [catalogue, setCatalogue] = useState<Catalogue | null>(null);
  const [designers, setDesigners] = useState<Record<string, string>>({});
  const [keyword, setKeyword] = useState('');
  const [category, setCategory] = useState('');
  const [style, setStyle] = useState('');
  const [low, setLow] = useState(0);
  const [high, setHigh] = useState(200000);
  const [result, setResult] = useState<SearchResponse | null>(null);
  const [loading, setLoading] = useState(false);
  const [error, setError] = useState<string | null>(null);
  const [tags, setTags] = useState<string[]>([]);
  const [uploading, setUploading] = useState(false);
  const [photoNote, setPhotoNote] = useState<string | null>(null);
  const [preview, setPreview] = useState<string | null>(null);

  useEffect(() => {
    let live = true;
    getCatalogue()
      .then((data) => {
        if (!live) return;
        setCatalogue(data);
        setLow(data.budget.min);
        setHigh(data.budget.max);
      })
      .catch(() => {
        if (live) setError('Cannot load the filters. Check that the backend is running.');
      });
    listCompanies()
```

main TypeScript React · UTF-8 · LF · lines 18–18

Calls: getCatalogue, listCompanies, searchProjects, suggestTagsFromUpload.

React hooks: useEffect, useState.

Function	Line
function formatBudget(value: number): string {	14
function submit(event: FormEvent<HTMLFormElement>) {	91
function clear() {	96
async function analysePhoto(event: ChangeEvent<HTMLInputElement>) {	111

7.9 ProjectDetail

frontend/src/pages/ProjectDetail.tsx · line 22

ProjectDetail.tsx — frontend/src/pages/ProjectDetail.tsx — CSIT314

frontend › src › pages › ProjectDetail.tsx › ProjectDetail

```tsx
export default function ProjectDetail() {
  const { projectId } = useParams<{ projectId: string }>();
  const { account } = useAuth();
  const [project, setProject] = useState<ProjectPublic | null>(null);
  const [companies, setCompanies] = useState<CompanyPublic[]>([]);
  const [active, setActive] = useState(0);
  const [saved, setSaved] = useState(false);
  const [busy, setBusy] = useState(false);
  const [loading, setLoading] = useState(true);
  const [error, setError] = useState<string | null>(null);
  const [reportOpen, setReportOpen] = useState(false);
  const [reasons, setReasons] = useState<string[]>([]);
  const [reason, setReason] = useState('');
  const [comments, setComments] = useState('');
  const [reportBusy, setReportBusy] = useState(false);
  const [reportNotice, setReportNotice] = useState<string | null>(null);
  const [reportError, setReportError] = useState<string | null>(null);
  const counted = useRef(false);

  useEffect(() => {
    if (!projectId) return;
    let live = true;
    setLoading(true);
    setError(null);

    getProject(projectId)
      .then((data) => {
        if (!live) return;
        setProject(data);
```

main — TypeScript React · UTF-8 · LF · lines 22–22

Calls: getProject, getShortlist, listCompanies, recordView, reportProject, reportReasons, saveProject, unsaveProject.

React hooks: useEffect, useParams, useRef, useState.

Function	Line
function formatBudget(value: number): string {	18
async function openReport() {	85
async function submitReport(event: FormEvent<HTMLFormElement>) {	96
async function toggleSaved() {	116

7.10 Saved

frontend/src/pages/Saved.tsx · line 10

Saved.tsx — frontend/src/pages/Saved.tsx — CSIT314

frontend › src › pages › Saved.tsx › Saved

```tsx
export default function Saved() {
  const [items, setItems] = useState<ProjectPublic[]>([]);
  const [loading, setLoading] = useState(true);
  const [busy, setBusy] = useState<string | null>(null);
  const [error, setError] = useState<string | null>(null);

  useEffect(() => {
    let live = true;
    getShortlist()
      .then((data) => {
        if (live) setItems(data.items);
      })
      .catch((caught: unknown) => {
        if (live) {
          setError(caught instanceof ApiError ? caught.detail : 'Unable to load saved projects.');
        }
      })
      .finally(() => {
        if (live) setLoading(false);
      });
    return () => {
      live = false;
    };
  }, []);

  async function remove(project: ProjectPublic) {
    setBusy(project.id);
    setError(null);
    try {
```

main — TypeScript React · UTF-8 · LF · lines 10–10

Calls: getShortlist, unsaveProject.

React hooks: useEffect, useState.

Function	Line
function formatBudget(value: number): string {	6
async function remove(project: ProjectPublic) {	35

7.11 Designers

frontend/src/pages/Designers.tsx · line 6

Designers.tsx — frontend/src/pages/Designers.tsx — CSIT314

frontend › src › pages › Designers.tsx › Designers

```tsx
export default function Designers() {
  const [companies, setCompanies] = useState<CompanyPublic[]>([]);
  const [loading, setLoading] = useState(true);
  const [error, setError] = useState<string | null>(null);

  useEffect(() => {
    let cancelled = false;

    listCompanies()
      .then((rows) => {
        if (!cancelled) setCompanies(rows);
      })
      .catch((caught: unknown) => {
        if (cancelled) return;
        setError(caught instanceof ApiError ? caught.detail : 'Unable to load designers.');
      })
      .finally(() => {
        if (!cancelled) setLoading(false);
      });

    return () => {
      cancelled = true;
    };
  }, []);

  return (
    <div className="stack">
      <div className="page-head">
        <div>
```

main — TypeScript React · UTF-8 · LF · lines 6–6

Calls: listCompanies.

React hooks: useEffect, useState.

7.12 DesignerDetail

frontend/src/pages/DesignerDetail.tsx · line 7

DesignerDetail.tsx — frontend/src/pages/DesignerDetail.tsx — CSIT314

frontend › src › pages › DesignerDetail.tsx › DesignerDetail

```tsx
export default function DesignerDetail() {
  const { companyId } = useParams<{ companyId: string }>();
  const { account } = useAuth();
  const [company, setCompany] = useState<CompanyPublic | null>(null);
  const [loading, setLoading] = useState(true);
  const [error, setError] = useState<string | null>(null);

  useEffect(() => {
    if (companyId === undefined) {
      setError('No designer was named.');
      setLoading(false);
      return;
    }

    let cancelled = false;

    companyById(companyId)
      .then((found) => {
        if (!cancelled) setCompany(found);
      })
      .catch((caught: unknown) => {
        if (cancelled) return;
        setError(caught instanceof ApiError ? caught.detail : 'Unable to load the profile.');
      })
      .finally(() => {
        if (!cancelled) setLoading(false);
      });

    return () => {
```

main — TypeScript React · UTF-8 · LF · lines 7–7

Calls: companyById.

React hooks: useEffect, useParams, useState.

7.13 RequestQuote

frontend/src/pages/RequestQuote.tsx · line 7

RequestQuote.tsx — frontend/src/pages/RequestQuote.tsx — CSIT314

frontend › src › pages › RequestQuote.tsx › RequestQuote

```tsx
export default function RequestQuote() {
  const { companyId } = useParams<{ companyId: string }>();
  const navigate = useNavigate();
  const [company, setCompany] = useState<CompanyPublic | null>(null);
  const [title, setTitle] = useState('');
  const [scope, setScope] = useState('');
  const [budgetMin, setBudgetMin] = useState('20000');
  const [budgetMax, setBudgetMax] = useState('40000');
  const [target, setTarget] = useState('');
  const [busy, setBusy] = useState(false);
  const [error, setError] = useState<string | null>(null);

  useEffect(() => {
    let live = true;
    listCompanies()
      .then((rows) => {
        if (live) setCompany(rows.find((row) => row.id === companyId) ?? null);
      })
      .catch(() => undefined);
    return () => {
      live = false;
    };
  }, [companyId]);

  async function submit(event: FormEvent<HTMLFormElement>) {
    event.preventDefault();
    if (!companyId || busy) return;
    setBusy(true);
    setError(null);
```

main — TypeScript React · UTF-8 · LF · lines 7–7

Calls: listCompanies, submitQuoteRequest.

React hooks: useEffect, useNavigate, useParams, useState.

Function	Line
async function submit(event: FormEvent<HTMLFormElement>) {	31

7.14 Quotes

frontend/src/pages/Quotes.tsx · line 8

Quotes.tsx frontend/src/pages/Quotes.tsx — CSIT314

frontend › src › pages › Quotes.tsx › Quotes

```tsx
export default function Quotes() {
  const { account } = useAuth();
  const [requests, setRequests] = useState<QuoteRequestPublic[]>([]);
  const [loading, setLoading] = useState(true);
  const [error, setError] = useState<string | null>(null);

  useEffect(() => {
    let live = true;
    listQuoteRequests()
      .then((data) => {
        if (live) setRequests(data);
      })
      .catch((caught: unknown) => {
        if (live) {
          setError(caught instanceof ApiError ? caught.detail : 'Unable to load requests.');
        }
      })
      .finally(() => {
        if (live) setLoading(false);
      });
    return () => {
      live = false;
    };
  }, []);

  const isDesigner = account?.role === 'DESIGNER';

  if (loading) return <p className="page-state">Loading requests…</p>;

```

main TypeScript React · UTF-8 · LF · lines 8–8

Calls: listQuoteRequests.

React hooks: useEffect, useState.

7.15 QuoteDetail

frontend/src/pages/QuoteDetail.tsx · line 19

QuoteDetail.tsx frontend/src/pages/QuoteDetail.tsx — CSIT314

frontend › src › pages › QuoteDetail.tsx › QuoteDetail

```tsx
export default function QuoteDetail() {
  const { requestId } = useParams<{ requestId: string }>();
  const { account } = useAuth();
  const [request, setRequest] = useState<QuoteRequestDetail | null>(null);
  const [loading, setLoading] = useState(true);
  const [busy, setBusy] = useState(false);
  const [error, setError] = useState<string | null>(null);
  const [notice, setNotice] = useState<string | null>(null);

  const [total, setTotal] = useState('');
  const [validDays, setValidDays] = useState('14');
  const [gstIncluded, setGstIncluded] = useState(false);
  const [note, setNote] = useState('');
  const [target, setTarget] = useState('');
  const [counterNote, setCounterNote] = useState('');
  const [reason, setReason] = useState('');

  const load = useCallback(async () => {
    if (!requestId) return;
    setError(null);
    try {
      const data = await getQuoteRequest(requestId);
      setRequest(data);
      const current = data.quotes.find((entry) => entry.state === 'OFFERED');
      if (current) {
        setTotal((current.total_cents / 100).toString());
        setGstIncluded(current.gst_included);
      }
    } catch (caught) {
```

main TypeScript React · UTF-8 · LF · lines 19–19

Calls: acceptQuote, answerQuoteRequest, cancelQuoteRequest, counterQuoteRequest, declineQuote, getQuoteRequest, refuseQuoteRequest, reviseQuote.

React hooks: useEffect, useParams, useState.

Function	Line
async function run(action: () => Promise<unknown>, message: string) {	58
function centsFromInput(value: string): number {	73
function submitAnswer(event: FormEvent<HTMLFormElement>, reviseId?: string) {	77

7.16 MyProjects

frontend/src/pages/MyProjects.tsx · line 12

MyProjects.tsx — frontend/src/pages/MyProjects.tsx — CSIT314

frontend › src › pages › MyProjects.tsx › MyProjects

```tsx
export default function MyProjects() {
  const [projects, setProjects] = useState<ProjectPublic[]>([]);

  // Filters
  const [searchName, setSearchName] = useState('');
  const [statusFilter, setStatusFilter] =
    useState<ProjectStatus | ''>('');

  // Page status
  const [loading, setLoading] = useState(true);
  const [busyId, setBusyId] = useState<string | null>(null);
  const [error, setError] = useState<string | null>(null);
  const [notice, setNotice] = useState<string | null>(null);

  // Retrieve projects whenever the filters change.
  useEffect(() => {
    let active = true;

    const timer = setTimeout(() => {
      setLoading(true);
      setError(null);

      myProjects({
        name: searchName,
        status: statusFilter || undefined,
      })
        .then((data) => {
          if (active) setProjects(data);
        })
```

main — TypeScript React · UTF-8 · LF · lines 12–12

Calls: deleteProject, myProjects, updateProject.

React hooks: useEffect, useState.

Function	Line
async function handleDelete(project: ProjectPublic) {	62
async function handleStatusChange(project: ProjectPublic) {	94

7.17 ProjectEditor

frontend/src/pages/ProjectEditor.tsx · line 44

ProjectEditor.tsx frontend/src/pages/ProjectEditor.tsx — CSIT314

frontend › src › pages › ProjectEditor.tsx › ProjectEditor

```tsx
export default function ProjectEditor() {
  const { projectId } = useParams<{ projectId: string }>();
  const navigate = useNavigate();
  const editing = projectId !== undefined;

  const [title, setTitle] = useState('');
  const [description, setDescription] = useState('');
  const [category, setCategory] = useState('');
  const [style, setStyle] = useState('');
  const [budgetMin, setBudgetMin] = useState('0');
  const [budgetMax, setBudgetMax] = useState('0');
  const [queue, setQueue] = useState<QueueItem[]>([]);
  const [tags, setTags] = useState('');
  const [uploading, setUploading] = useState(false);

  const [catalogue, setCatalogue] = useState<Catalogue | null>(null);
  const [loading, setLoading] = useState(editing);
  const [saving, setSaving] = useState(false);
  const [error, setError] = useState<string | null>(null);
  const [success, setSuccess] = useState<string | null>(null);

  // Load the available categories and styles.
  useEffect(() => {
    let active = true;

    getCatalogue()
      .then((data) => {
        if (active) setCatalogue(data);
      })
```

main TypeScript React · UTF-8 · LF · lines 44–44

Calls: createProject, getCatalogue, getProject, suggestTagsFromUpload, updateProject, uploadImage.

React hooks: useEffect, useNavigate, useParams, useState.

Function	Line
function splitTags(value: string): string[] {	24
function mergeTags(current: string[], extra: string[]): string[] {	31
async function handleSubmit(event: FormEvent<HTMLFormElement>) {	122
async function handleAdd(event: ChangeEvent<HTMLInputElement>) {	193
function removeImage(item: QueueItem) {	241
function takeTag(tag: string) {	247

7.18 Profile

frontend/src/pages/Profile.tsx · line 31

Profile.tsx — frontend/src/pages/Profile.tsx — CSIT314

frontend › src › pages › Profile.tsx › Profile

```tsx
export default function Profile() {
  const { account } = useAuth();
  const [company, setCompany] = useState<CompanyPublic | null>(null);
  const [form, setForm] = useState<CompanyInput>(EMPTY);
  const [loading, setLoading] = useState(true);
  const [saving, setSaving] = useState(false);
  const [error, setError] = useState<string | null>(null);
  const [notice, setNotice] = useState<string | null>(null);

  useEffect(() => {
    let cancelled = false;

    myCompany()
      .then((found) => {
        if (cancelled) return;
        setCompany(found);
        setForm(toInput(found));
      })
      .catch((caught: unknown) => {
        if (cancelled) return;
        if (caught instanceof ApiError && caught.status === 404) {
          setCompany(null);
          return;
        }
        setError(caught instanceof ApiError ? caught.detail : 'Unable to load the profile.');
      })
      .finally(() => {
        if (!cancelled) setLoading(false);
      });
```

main — TypeScript React · UTF-8 · LF · lines 31–31

Calls: createCompany, myCompany, updateMyCompany.

React hooks: useEffect, useState.

Function	Line
function toInput(company: CompanyPublic): CompanyInput {	18
function change(field: keyof CompanyInput) {	66
async function submit(event: FormEvent<HTMLFormElement>) {	73

7.19 Admin

frontend/src/pages/Admin.tsx · line 28

Admin.tsx — frontend/src/pages/Admin.tsx — CSIT314

frontend › src › pages › Admin.tsx › Admin

```tsx
export default function Admin() {
  const { account } = useAuth();
  const [rows, setRows] = useState<AccountPublic[]>([]);
  const [filter, setFilter] = useState<Filter>('PENDING');
  const [error, setError] = useState<string | null>(null);
  const [loading, setLoading] = useState(true);
  const [busyId, setBusyId] = useState<string | null>(null);
  const [reports, setReports] = useState<ProjectReportPublic[]>([]);
  const [reportBusy, setReportBusy] = useState<string | null>(null);
  const [takeDown, setTakeDown] = useState<Record<string, boolean>>({});
  const [suspend, setSuspend] = useState<Record<string, boolean>>({});

  const load = useCallback(async () => {
    setLoading(true);
    setError(null);
    try {
      const next = await adminListAccounts(filter === 'ALL' ? undefined : filter);
      setRows(next);
    } catch (caught) {
      setError(caught instanceof ApiError ? caught.detail : 'Unable to load accounts.');
      setRows([]);
    } finally {
      setLoading(false);
    }
  }, [filter]);

  const loadReports = useCallback(async () => {
    try {
      setReports(await listProjectReports());
```

main — TypeScript React · UTF-8 · LF · lines 28–28

Calls: adminApprove, adminListAccounts, adminSuspend, listProjectReports, resolveProjectReport.

React hooks: useEffect, useState.

Function	Line
function badgeClass(status: Status): string {	24
async function closeReport(reportId: string, take: boolean, susp: boolean) {	68
async function change(accountId: string, action: (id: string) => Promise<AccountPublic>) {	85

7.20 Platform

frontend/src/pages/Platform.tsx · line 14

Platform.tsx — frontend/src/pages/Platform.tsx — CSIT314

frontend › src › pages › Platform.tsx › Platform

```tsx
export default function Platform() {
  const [categories, setCategories] = useState<CategoryPublic[]>([]);
  const [report, setReport] = useState<Report | null>(null);
  const [period, setPeriod] = useState<(typeof PERIODS)[number]>('daily');
  const [buckets, setBuckets] = useState('14');
  const [newName, setNewName] = useState('');
  const [busy, setBusy] = useState(false);
  const [error, setError] = useState<string | null>(null);
  const [notice, setNotice] = useState<string | null>(null);

  const loadCategories = useCallback(async () => {
    try {
      setCategories(await listAllCategories());
    } catch (caught) {
      setError(caught instanceof ApiError ? caught.detail : 'Unable to load categories.');
    }
  }, []);

  const loadReport = useCallback(async (nextPeriod: string, nextBuckets: string) => {
    try {
      setReport(await getReport(nextPeriod, Number(nextBuckets)));
    } catch (caught) {
      setError(caught instanceof ApiError ? caught.detail : 'Unable to load the report.');
    }
  }, []);

  useEffect(() => {
    void loadCategories();
  }, [loadCategories]);
```

main — TypeScript React · UTF-8 · LF · lines 14–14

Calls: createCategory, getReport, listAllCategories, patchCategory.

React hooks: useEffect, useState.

Function	Line
async function addCategory(event: FormEvent<HTMLFormElement>) {	48
async function toggle(category: CategoryPublic) {	66

7.21 BudgetSlider

frontend/src/components/BudgetSlider.tsx · line 13

BudgetSlider.tsx — frontend/src/components/BudgetSlider.tsx — CSIT314

frontend › src › components › BudgetSlider.tsx › BudgetSlider

```tsx
export default function BudgetSlider({
  min,
  max,
  step,
  low,
  high,
  onChange,
}: BudgetSliderProps) {
  const span = max - min;
  const lowPercent = span === 0 ? 0 : ((low - min) / span) * 100;
  const highPercent = span === 0 ? 100 : ((high - min) / span) * 100;

  return (
    <div className="range">
      <div className="range-track" aria-hidden="true" />
      <div
        className="range-fill"
        aria-hidden="true"
        style={{ left: `${lowPercent}%`, width: `${highPercent - lowPercent}%` }}
      />
      <input
        type="range"
        aria-label="Minimum budget"
        min={min}
        max={max}
        step={step}
        value={low}
        onChange={(event) => {
          const next = Number(event.target.value);
```

main — TypeScript React · UTF-8 · LF · lines 13–13

Calls: no endpoint directly; it composes other components.

7.22 Appointments

frontend/src/pages/Appointments.tsx · line 21

Appointments.tsx — frontend/src/pages/Appointments.tsx — CSIT314

frontend › src › pages › Appointments.tsx › Appointments

```tsx
export default function Appointments() {
  const { account } = useAuth();
  const isDesigner = account?.role === 'DESIGNER';
  const [rows, setRows] = useState<AppointmentPublic[]>([]);
  const [companies, setCompanies] = useState<CompanyPublic[]>([]);
  const [loading, setLoading] = useState(true);
  const [error, setError] = useState<string | null>(null);
  const [busy, setBusy] = useState<string | null>(null);

  useEffect(() => {
    let live = true;
    Promise.all([listAppointments(), listCompanies()])
      .then(([appointments, found]) => {
        if (!live) return;
        setRows(appointments);
        setCompanies(found);
      })
      .catch((caught: unknown) => {
        if (live) {
          setError(caught instanceof ApiError ? caught.detail : 'Unable to load appointments.');
        }
      })
      .finally(() => {
        if (live) setLoading(false);
      });
    return () => {
      live = false;
    };
  }, []);
```

main — TypeScript React · UTF-8 · LF · lines 21–21

Calls: acceptAppointment, cancelAppointment, listAppointments, listCompanies.

React hooks: useEffect, useState.

Function	Line
function longDay(iso: string): string {	13
function companyName(companyId: string): string {	51
async function act(appointmentId: string, action: 'accept' | 'cancel') {	56

7.23 BookConsultation

frontend/src/pages/BookConsultation.tsx · line 36

BookConsultation.tsx — frontend/src/pages/BookConsultation.tsx — CSIT314

frontend › src › pages › BookConsultation.tsx › BookConsultation

```tsx
export default function BookConsultation() {
  const { companyId } = useParams<{ companyId: string }>();
  const days = useMemo(bookingDays, []);
  const [company, setCompany] = useState<CompanyPublic | null>(null);
  const [day, setDay] = useState<string>(isoDay(days[0]));
  const [mode, setMode] = useState<ConsultationMode>('IN_PERSON');
  const [slots, setSlots] = useState<string[]>([]);
  const [time, setTime] = useState<string>('');
  const [requirements, setRequirements] = useState<string>('');
  const [loadingSlots, setLoadingSlots] = useState<boolean>(true);
  const [saving, setSaving] = useState<boolean>(false);
  const [error, setError] = useState<string | null>(null);
  const [booked, setBooked] = useState<AppointmentPublic | null>(null);

  useEffect(() => {
    if (companyId === undefined) return;
    companyById(companyId)
      .then(setCompany)
      .catch((caught: unknown) => {
        setError(caught instanceof ApiError ? caught.detail : 'Unable to load the designer.');
      });
  }, [companyId]);

  const hasAddress = company !== null && company.meeting_address !== '';
  const hasLink = company !== null && company.offers_online;

  useEffect(() => {
    if (company === null) return;
    if (!hasAddress && hasLink) setMode('ONLINE');
```

main — TypeScript React · UTF-8 · LF · lines 36–36

Calls: bookAppointment, companyById, listSlots.

React hooks: useEffect, useParams, useState.

Function	Line
function isoDay(day: Date): string {	14
function dayLabel(day: Date): string {	20
function bookingDays(): Date[] {	29
async function submit(event: FormEvent<HTMLFormElement>) {	91

7.99 The API client

frontend/src/api.ts · one function per endpoint, all of them typed.

Client function	Line
function getToken()	46
function setToken(token: string)	50
function clearToken()	54
function health()	117
function register(body: RegisterRequest)	121
function login(body: LoginRequest)	128

function me()	135
function adminListAccounts(status?: Status)	139
function adminApprove(accountId: string)	144
function adminSuspend(accountId: string)	148
function myCompany()	152
function createCompany(body: CompanyInput)	156
function updateMyCompany(body: CompanyInput)	163
function companyById(companyId: string)	170
function listCompanies()	174
function searchProjects(params: SearchParams)	178
function getCatalogue()	188
function createProject(body: ProjectInput)	192
function getProject(projectId: string)	201
function updateProject(projectId: string, body: Partial<ProjectInput> & { stat	209
function myProjects(filters: { status?: ProjectStatus; name?: string;	222
function suggestTags(projectId: string, imageIndex = 0)	245
function suggestTagsFromUpload(file: File)	255
function uploadImage(file: File)	261
function recordView(projectId: string)	267
function getShortlist()	273
function saveProject(projectId: string)	277
function unsaveProject(projectId: string)	284
function submitQuoteRequest(body: { company_id: string; title: string; sco	290
function listQuoteRequests(state?: QuoteRequestState)	305
function getQuoteRequest(requestId: string)	310
function counterQuoteRequest(requestId: string, targetCents: number, note: s	316
function cancelQuoteRequest(requestId: string, reason: string)	327
function answerQuoteRequest(requestId: string, body: { total_cents: number; va	337
function reviseQuote(quoteId: string, body: { total_cents: number; valid_days:	347
function refuseQuoteRequest(requestId: string, reason: string)	357
function acceptQuote(quoteId: string)	367
function declineQuote(quoteId: string, reason: string)	373
function listSlots(companyId: string, day: string)	380
function bookAppointment(body: { company_id: string; date: string; time: s	385
function listAppointments()	398
function acceptAppointment(appointmentId: string)	402
function cancelAppointment(appointmentId: string)	409
function reportReasons()	416
function reportProject(body: { project_id: string; reason: string; comment	420
function listProjectReports()	431
function resolveProjectReport(reportId: string,	435

body: { take_down: boolean; su	
function listAllCategories()	445
function createCategory(name: string)	449
function patchCategory(categoryId: string, body: { name?: string; active?: boo	456
function getReport(period: string, buckets: number)	466
function deleteProject(projectId: string)	470

8 Sequence walks

Each walk lists the objects in order: boundary, control, entity access, entity. Every step names the file and the line, so a drawing can be traced back to the code. The names below are the names in the source, not summaries.

8.1 A customer searches by photo

#	Role	Object and function	Where	What happens
1	Boundary	Search.tsx · analysePhoto	frontend/src/pages/Search.tsx:111	Reads the chosen file and shows the preview
2	Boundary	api.ts · suggestTagsFromUpload	frontend/src/api.ts:255	POST /api/images/tags with the file
3	Control	images.py · tags_for_upload	backend/app/api/images.py:122	Checks the size and the type, then reads the bytes
4	Control	tag_suggestion_service.py · suggest_tags	backend/app/services/tag_suggestion_service.py:55	Colour palette, object labels, tag list
5	Boundary	Search.tsx · results	frontend/src/pages/Search.tsx	Chips render; searchProjects ranks the catalogue

8.2 A customer requests a quote

#	Role	Object and function	Where	What happens
1	Boundary	RequestQuote.tsx · submit	frontend/src/pages/RequestQuote.tsx:31	Validates the form fields
2	Boundary	api.ts · submitQuoteRequest	frontend/src/api.ts:290	POST /api/quotes/requests
3	Control	quotes.py · submit_request	backend/app/api/quotes.py:63	Rejects a non-customer, maps errors to codes
4	Control	quote_service.py · QuoteService.submit	backend/app/services/quote_service.py:49–88	Builds the request from the payload
5	Entity (access)	quote_repository.py · QuoteRequestRepository.add	backend/app/repositories/quote_repository.py:18–24	Stores the request

8.3 A designer answers a request

#	Role	Object and function	Where	What happens
1	Boundary	QuoteDetail.tsx · submitAnswer	frontend/src/pages/QuoteDetail.tsx:77	Reads total, validity and the GST choice
2	Boundary	api.ts · answerQuoteRequest	frontend/src/api.ts:337	POST /api/quotes/requests/{id}/quotes
3	Control	quotes.py · answer_request	backend/app/api/quotes.py:173	Checks that the caller owns the company
4	Control	quote_service.py · QuoteService.answer	backend/app/services/quote_service.py:138–165	Sends version one when the request is PENDING
5	Entity (access)	quote_repository.py · QuoteRepository.add	backend/app/repositories/quote_repository.py:58–64	Stores the version

8.4 An administrator approves an account

#	Role	Object and function	Where	What happens
1	Boundary	Admin.tsx · change	frontend/src/pages/Admin.tsx:47	Runs the chosen action on one account
2	Boundary	api.ts · adminApprove	frontend/src/api.ts:144	POST /api/admin/accounts/{id}/approve
3	Control	admin.py · approve_account	backend/app/api/admin.py:52	Requires the administrator role
4	Control	account_service.py · AccountService.approve	backend/app/services/account_service.py:86–90	Loads the account and calls the entity
5	Entity	account.py · Account.activate	backend/app/domain/account.py:39–41	Sets the status to ACTIVE

8.5 An administrator reads a report

#	Role	Object and function	Where	What happens
1	Boundary	Platform.tsx · load effect	frontend/src/pages/Platform.tsx:34	Reads period and bucket count
2	Boundary	api.ts · getReport	frontend/src/api.ts:466	GET /api/reports/{period}?buckets={n}
3	Control	reports.py · read_report	backend/app/api/reports.py:46	Requires the administrator role
4	Control	report_service.py · ReportService.build	backend/app/services/report_service.py:57–85	Counts accounts, projects, requests and quotes per bucket
5	Entity (access)	repositories · all()	backend/app/repositories	Supplies the rows to count

9 Appendix: every file and what it holds

The index answers the reverse question: given a file, which classes and functions does it contain, and on which lines?

backend/app/api/admin.py _to_http() (22–26) · list_accounts() (34–44) · approve_account() (52–60) · suspend_account() (68–76)

backend/app/api/appointments.py _fail() (28–42) · _public() (45–61) · read_slots() (69–80) · book() (89–106) · list_appointments() (114–125) · accept_appointment() (133–141) · cancel_appointment() (149–157)

backend/app/api/auth.py register() (40–55) · login() (59–76) · read_current_account() (80–82)

backend/app/api/catalogue.py BudgetRange (17–22) · CatalogueResponse (25–30) · read_catalogue() (38–50)

backend/app/api/categories.py CategoryPublic (25–32) · CategoryInput (35–38) · CategoryPatch (41–45) · _to_public() (48–55) · _fail() (58–65) · list_categories() (73–75) · list_all_categories() (83–91) · create_category() (100–108) · update_category() (116–132)

backend/app/api/companies.py _public() (27–34) · _to_http() (37–47) · create_company() (56–67) · read_my_company() (75–83) · update_my_company() (91–103) · list_companies() (111–118) · read_company() (126–137)

backend/app/api/deps.py get_account_repository() (51–53) · get_account_service() (56–58) · get_company_repository() (61–63) · get_company_service() (66–68) · get_project_repository() (71–73) · get_project_service() (76–78) · get_project_search_service() (81–83) · get_shortlist_repository() (86–88) · get_shortlist_service() (91–93) · get_quote_request_repository() (96–98) · get_quote_repository() (101–103) · get_quote_service() (106–113) · get_appointment_repository() (116–118) · get_appointment_service() (121–127) · get_report_repository() (130–132) · get_project_report_service() (135–141) · get_category_repository() (144–146) · get_category_service() (149–151) · get_report_service() (154–161) · get_current_account() (164–198)

backend/app/api/health.py HealthResponse (16–21) · read_health() (25–31)

backend/app/api/images.py _read_photo() (58–78) · store_upload() (86–114) · tags_for_upload() (122–169)

backend/app/api/project_reports.py _fail() (28–42) · _public() (45–58) · list_reasons() (66–68) · report_project() (77–87) · list_reports() (95–103) · resolve_report() (111–136)

backend/app/api/projects.py _to_http() (43–51) · create_project() (60–68) · list_my_projects() (76–95) · list_company_projects() (102–107) · search_projects() (115–153) · read_project() (161–169) · update_project() (177–189) · delete_project() (197–205) · record_project_view() (213–222) · suggest_project_tags() (230–281)

backend/app/api/quotes.py _fail() (37–45) · _detail() (48–54) · submit_request() (63–71) · list_requests() (79–92) · read_request() (100–107) · counter_request() (115–126) · cancel_request() (134–145) · refuse_request() (153–164) · answer_request() (173–184) · list_quotes() (192–200) · revise_quote() (209–220) · accept_quote() (228–236) · decline_quote() (244–255)

backend/app/api/reports.py BucketPublic (22–31) · ReportPublic (34–38) · read_report() (46–83)

backend/app/api/shortlist.py _forbidden() (22–23) · read_shortlist() (31–41) · save_project() (50–67) · unsave_project() (75–83)

backend/app/config.py Settings (30–38) · app_environment() (19–21) · is_production() (24–26) · load_settings() (41–51) · get_secret_key() (54–56) · get_token_minutes() (59–61) · is_default_secret() (64–66) · get_bootstrap_admin_email() (69–71) · get_bootstrap_admin_password() (74–76) · get_bootstrap_admins() (82–100) · _parse_admin_list() (103–120)

backend/app/domain/account.py Account (19–64)

backend/app/domain/appointment.py ConsultationAppointment (55–122) · _now() (35–36) · local_today() (39–45) · is_bookable_date() (48–51)

backend/app/domain/category.py Category (22–58) · _now() (17–18)

backend/app/domain/company.py Company (20–129)

backend/app/domain/enums.py Role (8–24) · AccountStatus (27–32) · ProjectStatus (35–40) · QuoteRequestState (43–52) · QuoteState (55–62) · AppointmentState (65–70) · ConsultationMode (73–77) · ReportStatus (80–85)

backend/app/domain/errors.py DomainError (12–19) · EmailAlreadyRegistered (22–25) · InvalidCredentials (28–31) · AccountNotActive (34–41) · InvalidRoleForSelfRegistration (53–56) · WeakPassword (59–62) · NotPermitted (65–68) · AccountNotFound (71–74) · CompanyAlreadyExists (77–80) · CompanyNotFound (83–86) · ProjectNotFound (89–92) · QuoteRequestNotFound (95–98) · QuoteNotFound (101–104) · AppointmentNotFound (107–110) · ReportNotFound (113–116) · InvalidState (119–122) · inactive_message() (44–50)

backend/app/domain/money.py gst_component() (20–29) · grand_total() (32–36) · format_cents() (39–43)

backend/app/domain/passwords.py hash_password() (19–23) · verify_password() (26–46)

backend/app/domain/project.py SearchCriteria (44–69) · Project (73–318)

backend/app/domain/quote.py Quote (38–131) · _now() (23–24) · _today() (27–34)

backend/app/domain/quote_request.py Counter (28–40) · QuoteRequest (44–163) · _now() (23–24)

backend/app/domain/report.py ProjectReport (32–69) · _now() (27–28)

backend/app/domain/shortlist.py Shortlist (17–68)

backend/app/main.py _bootstrap_administrators() (45–53) · create_app() (56–95)

backend/app/repositories/account_repository.py AccountRepository (10–59)

backend/app/repositories/appointment_repository.py AppointmentRepository (12–86)

backend/app/repositories/category_repository.py CategoryRepository (11–62)

backend/app/repositories/company_repository.py CompanyRepository (10–57)

backend/app/repositories/project_repository.py ProjectRepository (10–57)

backend/app/repositories/quote_repository.py QuoteRequestRepository (11–48) · QuoteRepository (51–92)

backend/app/repositories/report_repository.py ReportRepository (10–53)

backend/app/repositories/shortlist_repository.py ShortlistRepository (10–35)

backend/app/schemas/account.py AccountPublic (12–22) · RegisterRequest (25–48) · LoginRequest (51–55) · TokenResponse (58–64)

backend/app/schemas/appointment.py AppointmentPublic (12–29) · SlotsPublic (32–36) · BookRequest (39–46)

backend/app/schemas/company.py CompanyPublic (10–27) · CompanyCreate (30–40) · CompanyUpdate (43–57)

backend/app/schemas/project.py ProjectPublic (12–32) · ProjectCreate (35–45) · ProjectUpdate (48–62) · SearchResponse (65–72) · PaletteEntryPublic (75–79) · TagSuggestionPublic (82–91) · StoredImagePublic (94–99)

backend/app/schemas/quote.py CounterPublic (12–20) · QuotePublic (23–39) · QuoteRequestPublic (42–60) · QuoteRequestDetail (63–66) · SubmitRequest (69–78) · CounterRequest (81–85) · AnswerRequest (88–94) · ReasonRequest (97–100)

backend/app/schemas/report.py ProjectReportPublic (12–28) · SubmitReport (31–36) · ResolveReport (39–46)

backend/app/schemas/shortlist.py ShortlistResponse (10–14)

backend/app/security.py create_access_token() (19–28) · decode_access_token() (31–44)

backend/app/services/account_service.py AccountService (31–141)

backend/app/services/appointment_service.py AppointmentService (40–220)

backend/app/services/category_service.py CategoryNotFound (12–16) · CategoryExists (19–23) · CategoryService (26–87)

backend/app/services/company_service.py CompanyService (12–112)

backend/app/services/image_source.py ImageUnavailable (28–29) · load_image_bytes() (32–39) · _read_local() (42–51) · _read_remote() (54–82) · _resolve() (85–90) · _is_public() (93–105)

backend/app/services/object_labels.py Reading (162–169) · is_animal() (122–129) · _session() (133–153) · available() (156–158) · read() (172–231) · object_tags() (234–241) · engine_name() (244–246)

backend/app/services/project_report_service.py ProjectReportService (28–124)

backend/app/services/project_search_service.py SearchResult (21–34) · ProjectSearchService (37–98)

backend/app/services/project_service.py ProjectService (13–201)

backend/app/services/quote_service.py QuoteService (32–312)

backend/app/services/report_service.py Bucket (22–31) · Report (35–39) · ReportService (42–133)

backend/app/services/shortlist_service.py ShortlistService (14–76)

backend/app/services/tag_suggestion_service.py PaletteEntry (36–40) · TagSuggestion (44–52) · suggest_tags() (55–82) · _merge() (85–91) · _palette() (94–109) · _stats() (112–124) · _tags() (127–150)