



National
Semiconductor™

NPN Darlington Transistors

Discrete POWER & Signal
Technologies

Device No.	Case Style	V _{CE} (V) Min	V _{CE} (V) Min	V _{EB} (V) Min	I _{CBO} (μA) Max	V _{CE} (V) Min	I _{CE} (mA) Max	V _{CE(SAT)} (V) Max	V _{BE(SAT)} (V) Min	I _C (mA) Max	C _{ob} (pF) Max	f _T (MHz) Min	I _C (mA) Max	Process No.
MPSA27	TO-92 (92)	60	60		0.1	50	10,000 10,000	1.5	2	100		125	10	03
MPSA28	TO-92 (92)	80	80	12	0.1	60	10,000 10,000	1.2 1.5	2	100	8	125	10	03 (5-168)
MPSA29	TO-92 (92)	100	100	12	0.1	80	10,000 10,000	1.2 1.5	2	100	8	125	10	03
2N5306	TO-92 (94)	25	25	12	0.1	25	7000	1.4		200	10	60	2	05
2N5307	TO-92 (94)	40	40	12	0.1	40	2000	1.4		200	10	60	2	05
2N5308	TO-92 (94)	40	40	12	0.1	40	7000	1.4		200	10	60	2	05
2N6426	TO-92 (92)	40	40	12	0.05	30	20,000 30,000 20,000	1.2 1.5		50 500	7	150	10	05
2N6427	TO-92 (92)	40	40	12	0.05	30	10,000 20,000 14,000	1.2 1.5		50 500	7	130	10	05
MPSA12	TO-92 (92)		20	10	100	15	20,000	1		10				05
MPSA13	TO-92 (92)		30	10	100	30	10,000 5000	1.5		100		125	10	05

NOTE: National preferred device for each process in **bold**. Number shown in parentheses indicates location (**section-page**) of device datasheet.