

Read the chart at a glance.

ENGINE OUTPUT QUICK REFERENCE			REVIEWABLE BY DESIGN	
	Element (i)	Information / status notice Light unlit, reported depths, moorings, communication or service notices.	Orange	WARNING
	Element (i)	Drifting hazard Drifting objects or hazards, shown with the separate (i) symbol.	Red	DANGER
	Element (i)	Offshore activity / deployment An offshore operation or deployment notice shown as an information symbol.	Blue	NON-DANGER
	Element (triangle)	Active / established navigation buoy An active, established navigation buoy or other aid at one position.	Yellow	NON-DANGER
	Element (triangle)	Degraded / missing navigation aid A navigation aid reported degraded, missing, unlit or otherwise changed from its established state.	Orange	WARNING
	Element (triangle)	Isolated danger buoy A red isolated-danger mark at a hazard position.	Red	DANGER
	Element (diamond)	Offshore structure FPSO, FSO, MODU, offshore rig, platform or drillship.	Blue	NON-DANGER
	Element (diamond)	Pilot station A pilot station shown with a magenta diamond.	Magenta	NON-DANGER
	Element (diamond)	Security incident Piracy, armed robbery or another security incident at a reported position.	Red	DANGER
	Element (point)	Danger point Wreck, obstruction, aground vessel, derelict, submerged object or iceberg marker.	Red	DANGER
	Element (Line)	Navigation or operational line Recommended route, trackline, cable, pipeline, channel or survey line.	Orange	WARNING
	Element (Line)	Danger line An iceberg danger trackline or another explicitly dangerous operational line.	Red	DANGER
	Element (Area)	Non-danger area Survey, work, anchorage, waiting, holding, temporary-stay or no-anchoring area.	Orange	WARNING
	Element (Area)	Danger area War-risk, mine-danger, firing, military, prohibited, exclusion or other hazard area.	Red	DANGER
	Element (Circle)	Scientific / survey radius Scientific or survey activity with a published centre and distance.	Orange	WARNING
	Element (Circle)	Radius warning A warning, rocket-launch or explosives radius with a published centre and distance.	Red	DANGER
SAFETY RULES Circle only when the source publishes both a centre and a radius. FROM / TO movement stays as separate points. Operation-only text without usable geometry creates no chart object. Colours and styles shown are the author's default settings; users can change the colour code and styles at their discretion.				