FOORT

1.0

Generated by Doxygen 1.14.0

1 Namespace Index 1
1.1 Namespace List . . . 1

2 Hierarchical Index 3
2.1 Class Hierarchy . . . 3

3 Class Index 5
3.1 Class List . . . 5

4 File Index 9
4.1 File List . . . 9

5 Namespace Documentation 11
5.1 Config Namespace Reference . . . 11
5.1.1 Detailed Description . . . 12
5.1.2 Typedef Documentation . . . 12
5.1.2.1 ConfigCollection . . . 12
5.1.2.2 SettingError . . . 12
5.1.3 Function Documentation . . . 12
5.1.3.1 GetGeodesicIntegrator() . . . 12
5.1.3.2 GetMesh() . . . 12
5.1.3.3 GetMetric() . . . 13
5.1.3.4 GetOutputHandler() . . . 13
5.1.3.5 GetSource() . . . 13
5.1.3.6 GetViewScreen() . . . 14
5.1.3.7 InitializeDiagnostics() . . . 14
5.1.3.8 InitializeScreenOutput() . . . 14
5.1.3.9 InitializeTerminations() . . . 15
5.1.4 Variable Documentation . . . 15
5.1.4.1 Output_Important_Default . . . 15
5.1.4.2 Output_Other_Default . . . 15
5.2 ConfigReader Namespace Reference . . . 15
5.2.1 Detailed Description . . . 16
5.2.2 Variable Documentation . . . 16
5.2.2.1 MaxStreamSize . . . 16
5.3 Integrators Namespace Reference . . . 16
5.3.1 Function Documentation . . . 16
5.3.1.1 GetAdaptiveStep() . . . 16
5.3.1.2 GetFullIntegratorDescription() . . . 17
5.3.1.3 IntegrateGeodesicStep_RK4() . . . 17
5.3.1.4 IntegrateGeodesicStep_Verlet() . . . 17
5.3.2 Variable Documentation . . . 18
5.3.2.1 delta_nodiv0 . . . 18
5.3.2.2 Derivative_hval . . . 18

5.3.2.3 epsilon . . . 18
5.3.2.4 IntegratorDescription . . . 18
5.3.2.5 SmallestPossibleStepsize . . . 18
5.3.2.6 VerletMaxIterations . . . 19
5.3.2.7 VerletVelocityTolerance . . . 19
5.4 tk Namespace Reference . . . 19
5.5 tk::internal Namespace Reference . . . 19
5.6 Utilities Namespace Reference . . . 19
5.6.1 Detailed Description . . . 20
5.6.2 Function Documentation . . . 20
5.6.2.1 GetDiagNameStrings() . . . 20
5.6.2.2 GetFirstLineInfoString() . . . 20
5.6.2.3 GetTimeStampString() . . . 21

6 Class Documentation **23**

6.1 tk::internal::band_matrix Class Reference . . . 23
6.1.1 Constructor & Destructor Documentation . . . 23
6.1.1.1 band_matrix() [1/2] . . . 23
6.1.1.2 band_matrix() [2/2] . . . 24
6.1.1.3 ∼band_matrix() . . . 24
6.1.2 Member Function Documentation . . . 24
6.1.2.1 dim() . . . 24
6.1.2.2 l_solve() . . . 24
6.1.2.3 lu_decompose() . . . 24
6.1.2.4 lu_solve() . . . 24
6.1.2.5 num_lower() . . . 24
6.1.2.6 num_upper() . . . 24
6.1.2.7 operator()() [1/2] . . . 24
6.1.2.8 operator()() [2/2] . . . 25
6.1.2.9 r_solve() . . . 25
6.1.2.10 resize() . . . 25
6.1.2.11 saved_diag() [1/2] . . . 25
6.1.2.12 saved_diag() [2/2] . . . 25
6.1.3 Member Data Documentation . . . 25
6.1.3.1 m_lower . . . 25
6.1.3.2 m_upper . . . 25
6.2 BosonStarMetric Class Reference . . . 26
6.2.1 Detailed Description . . . 27
6.2.2 Constructor & Destructor Documentation . . . 27
6.2.2.1 BosonStarMetric() . . . 27
6.2.3 Member Function Documentation . . . 28
6.2.3.1 getFullDescriptionStr() . . . 28

6.2.3.2 getMetric_dd() . . . 28
6.2.3.3 getMetric_uu() . . . 28
6.2.3.4 read_data() . . . 29
6.2.4 Member Data Documentation . . . 29
6.2.4.1 m_m_filename . . . 29
6.2.4.2 m_mSpline . . . 29
6.2.4.3 m_num_lines . . . 29
6.2.4.4 m_Phi_filename . . . 29
6.2.4.5 m_Phi_infinity . . . 29
6.2.4.6 m_PhiSpline . . . 29
6.3 BoundarySphereTermination Class Reference . . . 30
6.3.1 Detailed Description . . . 31
6.3.2 Constructor & Destructor Documentation . . . 31
6.3.2.1 BoundarySphereTermination() . . . 31
6.3.3 Member Function Documentation . . . 31
6.3.3.1 CheckTermination() . . . 31
6.3.3.2 getFullDescriptionStr() . . . 31
6.3.4 Member Data Documentation . . . 31
6.3.4.1 TermOptions . . . 31
6.4 BoundarySphereTermOptions Struct Reference . . . 32
6.4.1 Detailed Description . . . 32
6.4.2 Constructor & Destructor Documentation . . . 32
6.4.2.1 BoundarySphereTermOptions() . . . 32
6.4.3 Member Data Documentation . . . 33
6.4.3.1 rLogScale . . . 33
6.4.3.2 SphereRadius . . . 33
6.5 ClosestRadiusDiagnostic Class Reference . . . 33
6.5.1 Detailed Description . . . 34
6.5.2 Constructor & Destructor Documentation . . . 34
6.5.2.1 ClosestRadiusDiagnostic() . . . 34
6.5.3 Member Function Documentation . . . 34
6.5.3.1 FinalDataValDistance() . . . 34
6.5.3.2 getFinalDataVal() . . . 35
6.5.3.3 getFullDataStr() . . . 35
6.5.3.4 getFullDescriptionStr() . . . 35
6.5.3.5 getNameStr() . . . 36
6.5.3.6 Reset() . . . 36
6.5.3.7 UpdateData() . . . 36
6.5.4 Member Data Documentation . . . 36
6.5.4.1 DiagOptions . . . 36
6.5.4.2 m_ClosestRadius . . . 36
6.6 ClosestRadiusOptions Struct Reference . . . 37

6.6.1 Detailed Description . . . 37
6.6.2 Constructor & Destructor Documentation . . . 37
6.6.2.1 ClosestRadiusOptions() . . . 37
6.6.3 Member Data Documentation . . . 38
6.6.3.1 RLogScale . . . 38
6.7 ConfigReader::ConfigCollection Class Reference . . . 38
6.7.1 Member Typedef Documentation . . . 39
6.7.1.1 ConfigSettingValue . . . 39
6.7.2 Member Function Documentation . . . 40
6.7.2.1 DisplayCollection() . . . 40
6.7.2.2 DisplaySetting() . . . 40
6.7.2.3 DisplayTabs() . . . 40
6.7.2.4 Exists() . . . 40
6.7.2.5 GetSettingIndex() . . . 41
6.7.2.6 IsCollection() [1/2] . . . 41
6.7.2.7 IsCollection() [2/2] . . . 41
6.7.2.8 LookupValue() [1/2] . . . 42
6.7.2.9 LookupValue() [2/2] . . . 42
6.7.2.10 LookupValueInteger() [1/7] . . . 43
6.7.2.11 LookupValueInteger() [2/7] . . . 43
6.7.2.12 LookupValueInteger() [3/7] . . . 44
6.7.2.13 LookupValueInteger() [4/7] . . . 44
6.7.2.14 LookupValueInteger() [5/7] . . . 44
6.7.2.15 LookupValueInteger() [6/7] . . . 45
6.7.2.16 LookupValueInteger() [7/7] . . . 45
6.7.2.17 NrSettings() . . . 45
6.7.2.18 operator[]() [1/2] . . . 45
6.7.2.19 operator[]() [2/2] . . . 46
6.7.2.20 ReadCollection() . . . 46
6.7.2.21 ReadFile() . . . 46
6.7.2.22 ReadSettingName() . . . 47
6.7.2.23 ReadSettingSpecificChar() . . . 47
6.7.2.24 ReadSettingValue() . . . 47
6.7.3 Member Data Documentation . . . 48
6.7.3.1 m_Settings . . . 48
6.8 ConfigReader::ConfigReaderException Class Reference . . . 48
6.8.1 Constructor & Destructor Documentation . . . 48
6.8.1.1 ConfigReaderException() . . . 48
6.8.2 Member Function Documentation . . . 48
6.8.2.1 trace() . . . 48
6.8.3 Member Data Documentation . . . 49
6.8.3.1 m_settingtrace . . . 49

6.9 ConfigReader::ConfigCollection::ConfigSetting Struct Reference . . . 49
6.9.1 Member Data Documentation . . . 49
6.9.1.1 SettingName . . . 49
6.9.1.2 SettingValue . . . 49
6.10 Diagnostic Class Reference . . . 49
6.10.1 Detailed Description . . . 50
6.10.2 Constructor & Destructor Documentation . . . 50
6.10.2.1 Diagnostic() [1/2] . . . 50
6.10.2.2 Diagnostic() [2/2] . . . 50
6.10.2.3 ∼Diagnostic() . . . 50
6.10.3 Member Function Documentation . . . 50
6.10.3.1 DecideUpdate() . . . 50
6.10.3.2 FinalDataValDistance() . . . 51
6.10.3.3 getFinalDataVal() . . . 51
6.10.3.4 getFullDataStr() . . . 51
6.10.3.5 getFullDescriptionStr() . . . 51
6.10.3.6 getNameStr() . . . 52
6.10.3.7 Reset() . . . 52
6.10.3.8 UpdateData() . . . 52
6.10.4 Member Data Documentation . . . 52
6.10.4.1 m_OwnerGeodesic . . . 52
6.10.4.2 m_StepsSinceUpdated . . . 52
6.11 DiagnosticOptions Struct Reference . . . 53
6.11.1 Detailed Description . . . 53
6.11.2 Constructor & Destructor Documentation . . . 53
6.11.2.1 DiagnosticOptions() . . . 53
6.11.2.2 ∼DiagnosticOptions() . . . 53
6.11.3 Member Data Documentation . . . 53
6.11.3.1 theUpdateFrequency . . . 53
6.12 EmissionModel Struct Reference . . . 54
6.12.1 Detailed Description . . . 54
6.12.2 Constructor & Destructor Documentation . . . 54
6.12.2.1 ∼EmissionModel() . . . 54
6.12.3 Member Function Documentation . . . 54
6.12.3.1 GetEmission() . . . 54
6.12.3.2 getFullDescriptionStr() . . . 55
6.13 EquatorialEmissionDiagnostic Class Reference . . . 55
6.13.1 Detailed Description . . . 57
6.13.2 Constructor & Destructor Documentation . . . 57
6.13.2.1 EquatorialEmissionDiagnostic() . . . 57
6.13.3 Member Function Documentation . . . 57
6.13.3.1 FinalDataValDistance() . . . 57

6.13.3.2 getFinalDataVal() . . . 57
6.13.3.3 getFullDataStr() . . . 58
6.13.3.4 getFullDescriptionStr() . . . 58
6.13.3.5 getNameStr() . . . 58
6.13.3.6 Reset() . . . 58
6.13.3.7 UpdateData() . . . 59
6.13.4 Member Data Documentation . . . 59
6.13.4.1 DiagOptions . . . 59
6.13.4.2 m_Intensity . . . 59
6.14 EquatorialEmissionOptions Struct Reference . . . 59
6.14.1 Detailed Description . . . 60
6.14.2 Constructor & Destructor Documentation . . . 60
6.14.2.1 EquatorialEmissionOptions() . . . 60
6.14.3 Member Data Documentation . . . 61
6.14.3.1 EquatPassUpperBound . . . 61
6.14.3.2 GeometricFudgeFactor . . . 61
6.14.3.3 RedShiftPower . . . 61
6.14.3.4 RLogScale . . . 61
6.14.3.5 TheEmissionModel . . . 61
6.14.3.6 TheFluidVelocityModel . . . 61
6.15 EquatorialPassesDiagnostic Class Reference . . . 61
6.15.1 Detailed Description . . . 63
6.15.2 Constructor & Destructor Documentation . . . 63
6.15.2.1 EquatorialPassesDiagnostic() . . . 63
6.15.3 Member Function Documentation . . . 63
6.15.3.1 FinalDataValDistance() . . . 63
6.15.3.2 getFinalDataVal() . . . 63
6.15.3.3 getFullDataStr() . . . 64
6.15.3.4 getFullDescriptionStr() . . . 64
6.15.3.5 getNameStr() . . . 64
6.15.3.6 Reset() . . . 64
6.15.3.7 UpdateData() . . . 65
6.15.4 Member Data Documentation . . . 65
6.15.4.1 DiagOptions . . . 65
6.15.4.2 m_EquatPasses . . . 65
6.15.4.3 m_PrevTheta . . . 65
6.16 EquatorialPassesOptions Struct Reference . . . 65
6.16.1 Detailed Description . . . 66
6.16.2 Constructor & Destructor Documentation . . . 66
6.16.2.1 EquatorialPassesOptions() . . . 66
6.16.3 Member Data Documentation . . . 66
6.16.3.1 Threshold . . . 66

6.17 FlatSpaceMetric Class Reference . . . 67
6.17.1 Detailed Description . . . 68
6.17.2 Constructor & Destructor Documentation . . . 68
6.17.2.1 FlatSpaceMetric() . . . 68
6.17.3 Member Function Documentation . . . 68
6.17.3.1 getFullDescriptionStr() . . . 68
6.17.3.2 getMetric_dd() . . . 68
6.17.3.3 getMetric_uu() . . . 68
6.18 FluidVelocityModel Struct Reference . . . 69
6.18.1 Detailed Description . . . 69
6.18.2 Constructor & Destructor Documentation . . . 70
6.18.2.1 FluidVelocityModel() . . . 70
6.18.2.2 ∼FluidVelocityModel() . . . 70
6.18.3 Member Function Documentation . . . 70
6.18.3.1 GetFourVelocityd() . . . 70
6.18.3.2 getFullDescriptionStr() . . . 70
6.18.4 Member Data Documentation . . . 70
6.18.4.1 m_theMetric . . . 70
6.19 FourColorScreenDiagnostic Class Reference . . . 71
6.19.1 Detailed Description . . . 72
6.19.2 Constructor & Destructor Documentation . . . 72
6.19.2.1 FourColorScreenDiagnostic() . . . 72
6.19.3 Member Function Documentation . . . 72
6.19.3.1 FinalDataValDistance() . . . 72
6.19.3.2 getFinalDataVal() . . . 72
6.19.3.3 getFullDataStr() . . . 73
6.19.3.4 getFullDescriptionStr() . . . 73
6.19.3.5 getNameStr() . . . 73
6.19.3.6 Reset() . . . 73
6.19.3.7 UpdateData() . . . 74
6.19.4 Member Data Documentation . . . 74
6.19.4.1 m_quadrant . . . 74
6.20 GeneralCircularRadialFluid Struct Reference . . . 74
6.20.1 Detailed Description . . . 76
6.20.2 Constructor & Destructor Documentation . . . 76
6.20.2.1 GeneralCircularRadialFluid() . . . 76
6.20.3 Member Function Documentation . . . 76
6.20.3.1 FindISCO() . . . 76
6.20.3.2 GetChristrRaisedDer() . . . 76
6.20.3.3 GetCircularVelocityd() . . . 77
6.20.3.4 GetFourVelocityd() . . . 77
6.20.3.5 getFullDescriptionStr() . . . 77

6.20.3.6 GetInsideISCOCircularVelocityd() . . . 77
6.20.3.7 GetRadialVelocityd() . . . 78
6.20.3.8 WarnOnce() . . . 78
6.20.4 Member Data Documentation . . . 78
6.20.4.1 m_betaPhi . . . 78
6.20.4.2 m_betaR . . . 78
6.20.4.3 m_ISCOexists . . . 79
6.20.4.4 m_ISCOlowerbound . . . 79
6.20.4.5 m_ISCOpphi . . . 79
6.20.4.6 m_ISCOpt . . . 79
6.20.4.7 m_ISCOr . . . 79
6.20.4.8 m_ISCOupperbound . . . 79
6.20.4.9 m_subKeplerParam . . . 79
6.20.4.10 m_WarnedInsideISCO . . . 79
6.20.4.11 m_WarnedNaN . . . 80
6.20.4.12 m_WarnedNoCircular . . . 80
6.20.4.13 m_WarnedNormalization . . . 80
6.20.4.14 m_WarnedSubkeplerianRescaling . . . 80
6.21 GeneralSingularityTermination Class Reference . . . 80
6.21.1 Detailed Description . . . 81
6.21.2 Constructor & Destructor Documentation . . . 81
6.21.2.1 GeneralSingularityTermination() . . . 81
6.21.3 Member Function Documentation . . . 82
6.21.3.1 CheckTermination() . . . 82
6.21.3.2 getFullDescriptionStr() . . . 82
6.21.3.3 SingularityToString() . . . 82
6.21.4 Member Data Documentation . . . 82
6.21.4.1 TermOptions . . . 82
6.22 GeneralSingularityTermOptions Struct Reference . . . 83
6.22.1 Detailed Description . . . 83
6.22.2 Constructor & Destructor Documentation . . . 84
6.22.2.1 GeneralSingularityTermOptions() . . . 84
6.22.3 Member Data Documentation . . . 84
6.22.3.1 Epsilon . . . 84
6.22.3.2 OutputToConsole . . . 84
6.22.3.3 rLogScale . . . 84
6.22.3.4 Singularities . . . 84
6.23 Geodesic Class Reference . . . 84
6.23.1 Detailed Description . . . 86
6.23.2 Constructor & Destructor Documentation . . . 86
6.23.2.1 Geodesic() [1/3] . . . 86
6.23.2.2 Geodesic() [2/3] . . . 86

6.23.2.3 Geodesic() [3/3] . . . 86
6.23.3 Member Function Documentation . . . 86
6.23.3.1 getAllOutputStr() . . . 86
6.23.3.2 getCurrentLambda() . . . 87
6.23.3.3 getCurrentPos() . . . 87
6.23.3.4 getCurrentVel() . . . 87
6.23.3.5 getDiagnosticFinalValue() . . . 87
6.23.3.6 getScreenIndex() . . . 87
6.23.3.7 getTermCondition() . . . 88
6.23.3.8 operator=() . . . 88
6.23.3.9 Reset() . . . 88
6.23.3.10 Update() . . . 88
6.23.4 Member Data Documentation . . . 89
6.23.4.1 m_AllDiagnostics . . . 89
6.23.4.2 m_AllTerminations . . . 89
6.23.4.3 m_curLambda . . . 89
6.23.4.4 m_CurrentPos . . . 89
6.23.4.5 m_CurrentVel . . . 89
6.23.4.6 m_ScreenIndex . . . 89
6.23.4.7 m_TermCond . . . 89
6.23.4.8 m_theIntegrator . . . 90
6.23.4.9 m_theMetric . . . 90
6.23.4.10 m_theSource . . . 90
6.24 GeodesicOutputHandler Class Reference . . . 90
6.24.1 Detailed Description . . . 91
6.24.2 Constructor & Destructor Documentation . . . 91
6.24.2.1 GeodesicOutputHandler() [1/2] . . . 91
6.24.2.2 GeodesicOutputHandler() [2/2] . . . 92
6.24.3 Member Function Documentation . . . 92
6.24.3.1 GetFileName() . . . 92
6.24.3.2 getFullDescriptionStr() . . . 92
6.24.3.3 NewGeodesicOutput() . . . 93
6.24.3.4 OpenForFirstTime() . . . 94
6.24.3.5 OutputFinished() . . . 94
6.24.3.6 PrepareForOutput() . . . 94
6.24.3.7 WriteCachedOutputToFile() . . . 94
6.24.4 Member Data Documentation . . . 94
6.24.4.1 m_AllCachedData . . . 94
6.24.4.2 m_CurrentFullFiles . . . 95
6.24.4.3 m_CurrentGeodesicsInFile . . . 95
6.24.4.4 m_DiagNames . . . 95
6.24.4.5 m_FileExtension . . . 95

6.24.4.6 m_FilePrefix . . . 95
6.24.4.7 m_FirstLineInfoString . . . 95
6.24.4.8 m_nrGeodesicsPerFile . . . 95
6.24.4.9 m_nrOutputsToCache . . . 95
6.24.4.10 m_PrevCached . . . 96
6.24.4.11 m_PrintFirstLineInfo . . . 96
6.24.4.12 m_TimeStamp . . . 96
6.24.4.13 m_WriteToConsole . . . 96
6.25 GeodesicPositionDiagnostic Class Reference . . . 96
6.25.1 Detailed Description . . . 97
6.25.2 Constructor & Destructor Documentation . . . 98
6.25.2.1 GeodesicPositionDiagnostic() . . . 98
6.25.3 Member Function Documentation . . . 98
6.25.3.1 FinalDataValDistance() . . . 98
6.25.3.2 getFinalDataVal() . . . 98
6.25.3.3 getFullDataStr() . . . 98
6.25.3.4 getFullDescriptionStr() . . . 99
6.25.3.5 getNameStr() . . . 99
6.25.3.6 Reset() . . . 99
6.25.3.7 UpdateData() . . . 99
6.25.4 Member Data Documentation . . . 99
6.25.4.1 DiagOptions . . . 99
6.25.4.2 m_AllSavedPoints . . . 100
6.26 GeodesicPositionOptions Struct Reference . . . 100
6.26.1 Detailed Description . . . 100
6.26.2 Constructor & Destructor Documentation . . . 101
6.26.2.1 GeodesicPositionOptions() . . . 101
6.26.3 Member Data Documentation . . . 101
6.26.3.1 OutputNrSteps . . . 101
6.26.3.2 RLogScale . . . 101
6.27 GLMJohnsonSUEmission Struct Reference . . . 101
6.27.1 Detailed Description . . . 102
6.27.2 Constructor & Destructor Documentation . . . 102
6.27.2.1 GLMJohnsonSUEmission() . . . 102
6.27.3 Member Function Documentation . . . 102
6.27.3.1 GetEmission() . . . 102
6.27.3.2 getFullDescriptionStr() . . . 103
6.27.4 Member Data Documentation . . . 103
6.27.4.1 m_gamma . . . 103
6.27.4.2 m_mu . . . 103
6.27.4.3 m_sigma . . . 103
6.28 HorizonTermination Class Reference . . . 103

6.28.1 Detailed Description . . . 104
6.28.2 Constructor & Destructor Documentation . . . 104
6.28.2.1 HorizonTermination() . . . 104
6.28.3 Member Function Documentation . . . 105
6.28.3.1 CheckTermination() . . . 105
6.28.3.2 getFullDescriptionStr() . . . 105
6.28.4 Member Data Documentation . . . 105
6.28.4.1 TermOptions . . . 105
6.29 HorizonTermOptions Struct Reference . . . 105
6.29.1 Detailed Description . . . 106
6.29.2 Constructor & Destructor Documentation . . . 106
6.29.2.1 HorizonTermOptions() . . . 106
6.29.3 Member Data Documentation . . . 106
6.29.3.1 AtHorizonEps . . . 106
6.29.3.2 HorizonRadius . . . 107
6.29.3.3 rLogScale . . . 107
6.30 InputCertainPixelsMesh Class Reference . . . 107
6.30.1 Detailed Description . . . 108
6.30.2 Constructor & Destructor Documentation . . . 108
6.30.2.1 InputCertainPixelsMesh() [1/3] . . . 108
6.30.2.2 InputCertainPixelsMesh() [2/3] . . . 108
6.30.2.3 InputCertainPixelsMesh() [3/3] . . . 108
6.30.3 Member Function Documentation . . . 109
6.30.3.1 EndCurrentLoop() . . . 109
6.30.3.2 GeodesicFinished() . . . 109
6.30.3.3 getCurNrGeodesics() . . . 109
6.30.3.4 getFullDescriptionStr() . . . 110
6.30.3.5 getNewInitConds() . . . 110
6.30.3.6 IsFinished() . . . 110
6.30.4 Member Data Documentation . . . 110
6.30.4.1 m_Finished . . . 110
6.30.4.2 m_PixelsToIntegrate . . . 111
6.30.4.3 m_RowColumnSize . . . 111
6.30.4.4 m_TotalPixels . . . 111
6.31 JohannsenMetric Class Reference . . . 111
6.31.1 Detailed Description . . . 113
6.31.2 Constructor & Destructor Documentation . . . 113
6.31.2.1 JohannsenMetric() [1/2] . . . 113
6.31.2.2 JohannsenMetric() [2/2] . . . 113
6.31.3 Member Function Documentation . . . 113
6.31.3.1 getFullDescriptionStr() . . . 113
6.31.3.2 getMetric_dd() . . . 114

6.31.3.3 getMetric_uu() . . . 115
6.31.4 Member Data Documentation . . . 115
6.31.4.1 m_alpha13Param . . . 115
6.31.4.2 m_alpha22Param . . . 115
6.31.4.3 m_alpha52Param . . . 115
6.31.4.4 m_aParam . . . 116
6.31.4.5 m_eps3Param . . . 116
6.32 KerrMetric Class Reference . . . 116
6.32.1 Detailed Description . . . 117
6.32.2 Constructor & Destructor Documentation . . . 118
6.32.2.1 KerrMetric() [1/2] . . . 118
6.32.2.2 KerrMetric() [2/2] . . . 118
6.32.3 Member Function Documentation . . . 118
6.32.3.1 getFullDescriptionStr() . . . 118
6.32.3.2 getMetric_dd() . . . 118
6.32.3.3 getMetric_uu() . . . 118
6.32.4 Member Data Documentation . . . 119
6.32.4.1 m_aParam . . . 119
6.32.4.2 m_mParam . . . 119
6.33 KerrSchildMetric Class Reference . . . 119
6.33.1 Detailed Description . . . 121
6.33.2 Constructor & Destructor Documentation . . . 121
6.33.2.1 KerrSchildMetric() [1/2] . . . 121
6.33.2.2 KerrSchildMetric() [2/2] . . . 121
6.33.3 Member Function Documentation . . . 121
6.33.3.1 getFullDescriptionStr() . . . 121
6.33.3.2 getMetric_dd() . . . 121
6.33.3.3 getMetric_uu() . . . 122
6.33.4 Member Data Documentation . . . 122
6.33.4.1 m_aParam . . . 122
6.34 MankoNovikovMetric Class Reference . . . 122
6.34.1 Detailed Description . . . 124
6.34.2 Constructor & Destructor Documentation . . . 124
6.34.2.1 MankoNovikovMetric() [1/2] . . . 124
6.34.2.2 MankoNovikovMetric() [2/2] . . . 124
6.34.3 Member Function Documentation . . . 124
6.34.3.1 getFullDescriptionStr() . . . 124
6.34.3.2 getMetric_dd() . . . 124
6.34.3.3 getMetric_uu() . . . 125
6.34.4 Member Data Documentation . . . 125
6.34.4.1 m_alpha3Param . . . 125
6.34.4.2 m_alphaParam . . . 125

6.34.4.3 m_aParam . . . 125
6.34.4.4 m_kParam . . . 126
6.35 Mesh Class Reference . . . 126
6.35.1 Detailed Description . . . 126
6.35.2 Constructor & Destructor Documentation . . . 127
6.35.2.1 Mesh() . . . 127
6.35.2.2 ~Mesh() . . . 127
6.35.3 Member Function Documentation . . . 127
6.35.3.1 EndCurrentLoop() . . . 127
6.35.3.2 GeodesicFinished() . . . 127
6.35.3.3 getCurNrGeodesics() . . . 127
6.35.3.4 getFullDescriptionStr() . . . 127
6.35.3.5 getNewInitConds() . . . 128
6.35.3.6 IsFinished() . . . 128
6.35.4 Member Data Documentation . . . 128
6.35.4.1 m_DistanceDiagnostic . . . 128
6.36 Metric Class Reference . . . 128
6.36.1 Detailed Description . . . 129
6.36.2 Constructor & Destructor Documentation . . . 129
6.36.2.1 ~Metric() . . . 129
6.36.2.2 Metric() . . . 129
6.36.3 Member Function Documentation . . . 129
6.36.3.1 getChristoffel_udd() . . . 129
6.36.3.2 getFullDescriptionStr() . . . 130
6.36.3.3 getKretschmann() . . . 130
6.36.3.4 getMetric_dd() . . . 130
6.36.3.5 getMetric_uu() . . . 131
6.36.3.6 getRiemann_uddd() . . . 131
6.36.3.7 getrLogScale() . . . 131
6.36.4 Member Data Documentation . . . 131
6.36.4.1 m_rLogScale . . . 131
6.36.4.2 m_Symmetries . . . 132
6.37 NaNTermination Class Reference . . . 132
6.37.1 Detailed Description . . . 133
6.37.2 Constructor & Destructor Documentation . . . 133
6.37.2.1 NaNTermination() . . . 133
6.37.3 Member Function Documentation . . . 133
6.37.3.1 CheckTermination() . . . 133
6.37.3.2 getFullDescriptionStr() . . . 133
6.37.4 Member Data Documentation . . . 134
6.37.4.1 TermOptions . . . 134
6.38 NaNTermOptions Struct Reference . . . 134

6.38.1 Detailed Description . . . 135
6.38.2 Constructor & Destructor Documentation . . . 135
6.38.2.1 NaNTermOptions() . . . 135
6.38.3 Member Data Documentation . . . 135
6.38.3.1 OutputToConsole . . . 135
6.39 NoSource Class Reference . . . 135
6.39.1 Detailed Description . . . 136
6.39.2 Constructor & Destructor Documentation . . . 136
6.39.2.1 NoSource() . . . 136
6.39.3 Member Function Documentation . . . 136
6.39.3.1 getFullDescriptionStr() . . . 136
6.39.3.2 getSource() . . . 136
6.40 SquareSubdivisionMesh::PixelInfo Struct Reference . . . 137
6.40.1 Detailed Description . . . 138
6.40.2 Constructor & Destructor Documentation . . . 138
6.40.2.1 PixelInfo() . . . 138
6.40.3 Member Data Documentation . . . 138
6.40.3.1 DiagValue . . . 138
6.40.3.2 DownNbr . . . 138
6.40.3.3 Index . . . 138
6.40.3.4 LeftNbr . . . 138
6.40.3.5 RightNbr . . . 138
6.40.3.6 SEdiagNbr . . . 139
6.40.3.7 SubdivideLevel . . . 139
6.40.3.8 UpNbr . . . 139
6.40.3.9 Weight . . . 139
6.41 RasheedLarsenMetric Class Reference . . . 139
6.41.1 Detailed Description . . . 141
6.41.2 Constructor & Destructor Documentation . . . 141
6.41.2.1 RasheedLarsenMetric() [1/2] . . . 141
6.41.2.2 RasheedLarsenMetric() [2/2] . . . 141
6.41.3 Member Function Documentation . . . 141
6.41.3.1 getFullDescriptionStr() . . . 141
6.41.3.2 getMetric_dd() . . . 142
6.41.3.3 getMetric_uu() . . . 143
6.41.4 Member Data Documentation . . . 143
6.41.4.1 m_aParam . . . 143
6.41.4.2 m_mParam . . . 143
6.41.4.3 m_pParam . . . 143
6.41.4.4 m_qParam . . . 144
6.42 SimpleSquareMesh Class Reference . . . 144
6.42.1 Detailed Description . . . 145

6.42.2 Constructor & Destructor Documentation . . . 145
6.42.2.1 SimpleSquareMesh() [1/2] . . . 145
6.42.2.2 SimpleSquareMesh() [2/2] . . . 145
6.42.3 Member Function Documentation . . . 145
6.42.3.1 EndCurrentLoop() . . . 145
6.42.3.2 GeodesicFinished() . . . 145
6.42.3.3 getCurNrGeodesics() . . . 146
6.42.3.4 getFullDescriptionStr() . . . 146
6.42.3.5 getNewInitConds() . . . 146
6.42.3.6 IsFinished() . . . 147
6.42.4 Member Data Documentation . . . 147
6.42.4.1 m_Finished . . . 147
6.42.4.2 m_RowColumnSize . . . 147
6.42.4.3 m_TotalPixels . . . 147
6.43 SingularityMetric Class Reference . . . 147
6.43.1 Detailed Description . . . 148
6.43.2 Constructor & Destructor Documentation . . . 148
6.43.2.1 SingularityMetric() . . . 148
6.43.3 Member Function Documentation . . . 149
6.43.3.1 getSingularities() . . . 149
6.43.4 Member Data Documentation . . . 149
6.43.4.1 m_AllSingularities . . . 149
6.44 Source Class Reference . . . 149
6.44.1 Detailed Description . . . 150
6.44.2 Constructor & Destructor Documentation . . . 150
6.44.2.1 Source() . . . 150
6.44.2.2 ∼Source() . . . 150
6.44.3 Member Function Documentation . . . 150
6.44.3.1 getFullDescriptionStr() . . . 150
6.44.3.2 getSource() . . . 151
6.44.4 Member Data Documentation . . . 151
6.44.4.1 m_theMetric . . . 151
6.45 SphericalHorizonMetric Class Reference . . . 151
6.45.1 Detailed Description . . . 152
6.45.2 Constructor & Destructor Documentation . . . 152
6.45.2.1 SphericalHorizonMetric() [1/2] . . . 152
6.45.2.2 SphericalHorizonMetric() [2/2] . . . 152
6.45.3 Member Function Documentation . . . 153
6.45.3.1 getHorizonRadius() . . . 153
6.45.4 Member Data Documentation . . . 153
6.45.4.1 m_HorizonRadius . . . 153
6.46 tk::spline Class Reference . . . 153

6.46.1 Member Enumeration Documentation . . . 154
6.46.1.1 bd_type . . . 154
6.46.1.2 spline_type . . . 154
6.46.2 Constructor & Destructor Documentation . . . 155
6.46.2.1 spline() [1/2] . . . 155
6.46.2.2 spline() [2/2] . . . 155
6.46.3 Member Function Documentation . . . 155
6.46.3.1 deriv() . . . 155
6.46.3.2 find_closest() . . . 155
6.46.3.3 get_x() . . . 155
6.46.3.4 get_x_max() . . . 155
6.46.3.5 get_x_min() . . . 156
6.46.3.6 get_y() . . . 156
6.46.3.7 make_monotonic() . . . 156
6.46.3.8 operator()() . . . 156
6.46.3.9 set_boundary() . . . 156
6.46.3.10 set_coeffs_from_b() . . . 156
6.46.3.11 set_points() . . . 156
6.46.4 Member Data Documentation . . . 156
6.46.4.1 m_b . . . 156
6.46.4.2 m_c . . . 157
6.46.4.3 m_c0 . . . 157
6.46.4.4 m_d . . . 157
6.46.4.5 m_left . . . 157
6.46.4.6 m_left_value . . . 157
6.46.4.7 m_made_monotonic . . . 157
6.46.4.8 m_right . . . 157
6.46.4.9 m_right_value . . . 157
6.46.4.10 m_type . . . 157
6.46.4.11 m_x . . . 157
6.46.4.12 m_y . . . 158
6.47 SquareSubdivisionMesh Class Reference . . . 158
6.47.1 Detailed Description . . . 160
6.47.2 Constructor & Destructor Documentation . . . 160
6.47.2.1 SquareSubdivisionMesh() [1/2] . . . 160
6.47.2.2 SquareSubdivisionMesh() [2/2] . . . 160
6.47.3 Member Function Documentation . . . 160
6.47.3.1 EndCurrentLoop() . . . 160
6.47.3.2 ExpInt() . . . 161
6.47.3.3 GeodesicFinished() . . . 161
6.47.3.4 getCurNrGeodesics() . . . 161
6.47.3.5 GetDown() . . . 161

6.47.3.6 getFullDescriptionStr() . . . 162
6.47.3.7 GetLeft() . . . 162
6.47.3.8 getNewInitConds() . . . 162
6.47.3.9 GetRight() . . . 163
6.47.3.10 GetUp() . . . 163
6.47.3.11 InitializeFirstGrid() . . . 163
6.47.3.12 IsFinished() . . . 164
6.47.3.13 SubdivideAndQueue() . . . 164
6.47.3.14 UpdateAllWeights() . . . 164
6.47.4 Member Data Documentation . . . 164
6.47.4.1 m_ActivePixels . . . 164
6.47.4.2 m_AllPixels . . . 165
6.47.4.3 m_CurrentPixelQueue . . . 165
6.47.4.4 m_CurrentPixelQueueDone . . . 165
6.47.4.5 m_CurrentPixelUpdating . . . 165
6.47.4.6 m_InfinitePixels . . . 165
6.47.4.7 m_InitialPixels . . . 165
6.47.4.8 m_InitialSubDividideToFinal . . . 165
6.47.4.9 m_IterationPixels . . . 166
6.47.4.10 m_MaxPixels . . . 166
6.47.4.11 m_MaxSubdivide . . . 166
6.47.4.12 m_PixelsIntegrated . . . 166
6.47.4.13 m_PixelsLeft . . . 166
6.47.4.14 m_RowColumnSize . . . 166
6.48 ST3CrMetric Class Reference . . . 167
6.48.1 Detailed Description . . . 168
6.48.2 Constructor & Destructor Documentation . . . 168
6.48.2.1 ST3CrMetric() . . . 168
6.48.3 Member Function Documentation . . . 169
6.48.3.1 f_om_phi() . . . 169
6.48.3.2 f_phi() . . . 169
6.48.3.3 get_omega() . . . 170
6.48.3.4 getFullDescriptionStr() . . . 170
6.48.3.5 getMetric_dd() . . . 170
6.48.3.6 getMetric_uu() . . . 170
6.48.4 Member Data Documentation . . . 171
6.48.4.1 m_lambda . . . 171
6.48.4.2 m_P . . . 171
6.48.4.3 m_q0 . . . 171
6.49 Termination Class Reference . . . 171
6.49.1 Detailed Description . . . 172
6.49.2 Constructor & Destructor Documentation . . . 172

6.49.2.1 Termination() [1/2] . . . 172
6.49.2.2 Termination() [2/2] . . . 172
6.49.2.3 ~Termination() . . . 172
6.49.3 Member Function Documentation . . . 173
6.49.3.1 CheckTermination() . . . 173
6.49.3.2 DecideUpdate() . . . 173
6.49.3.3 getFullDescriptionStr() . . . 173
6.49.3.4 Reset() . . . 173
6.49.4 Member Data Documentation . . . 173
6.49.4.1 m_OwnerGeodesic . . . 173
6.49.4.2 m_StepsSinceUpdated . . . 174
6.50 TerminationOptions Struct Reference . . . 174
6.50.1 Detailed Description . . . 174
6.50.2 Constructor & Destructor Documentation . . . 174
6.50.2.1 TerminationOptions() . . . 174
6.50.2.2 ~TerminationOptions() . . . 175
6.50.3 Member Data Documentation . . . 175
6.50.3.1 UpdateEveryNSteps . . . 175
6.51 ThetaSingularityTermination Class Reference . . . 175
6.51.1 Detailed Description . . . 176
6.51.2 Constructor & Destructor Documentation . . . 176
6.51.2.1 ThetaSingularityTermination() . . . 176
6.51.3 Member Function Documentation . . . 176
6.51.3.1 CheckTermination() . . . 176
6.51.3.2 getFullDescriptionStr() . . . 177
6.51.4 Member Data Documentation . . . 177
6.51.4.1 TermOptions . . . 177
6.52 ThetaSingularityTermOptions Struct Reference . . . 177
6.52.1 Detailed Description . . . 178
6.52.2 Constructor & Destructor Documentation . . . 178
6.52.2.1 ThetaSingularityTermOptions() . . . 178
6.52.3 Member Data Documentation . . . 178
6.52.3.1 ThetaSingEpsilon . . . 178
6.53 TimeOutTermination Class Reference . . . 178
6.53.1 Detailed Description . . . 179
6.53.2 Constructor & Destructor Documentation . . . 180
6.53.2.1 TimeOutTermination() . . . 180
6.53.3 Member Function Documentation . . . 180
6.53.3.1 CheckTermination() . . . 180
6.53.3.2 getFullDescriptionStr() . . . 180
6.53.3.3 Reset() . . . 180
6.53.4 Member Data Documentation . . . 180

6.53.4.1 m_CurNrSteps . . . 180
6.53.4.2 TermOptions . . . 181
6.54 TimeOutTermOptions Struct Reference . . . 181
6.54.1 Detailed Description . . . 182
6.54.2 Constructor & Destructor Documentation . . . 182
6.54.2.1 TimeOutTermOptions() . . . 182
6.54.3 Member Data Documentation . . . 182
6.54.3.1 MaxSteps . . . 182
6.55 Utilities::Timer Class Reference . . . 182
6.55.1 Detailed Description . . . 183
6.55.2 Member Typedef Documentation . . . 183
6.55.2.1 Clock . . . 183
6.55.2.2 Second . . . 183
6.55.3 Member Function Documentation . . . 183
6.55.3.1 elapsed() . . . 183
6.55.3.2 reset() . . . 183
6.55.4 Member Data Documentation . . . 184
6.55.4.1 m_beg . . . 184
6.56 UpdateFrequency Struct Reference . . . 184
6.56.1 Detailed Description . . . 184
6.56.2 Member Data Documentation . . . 184
6.56.2.1 UpdateFinish . . . 184
6.56.2.2 UpdateNSteps . . . 184
6.56.2.3 UpdateStart . . . 185
6.57 ViewScreen Class Reference . . . 185
6.57.1 Detailed Description . . . 186
6.57.2 Constructor & Destructor Documentation . . . 186
6.57.2.1 ViewScreen() [1/2] . . . 186
6.57.2.2 ViewScreen() [2/2] . . . 186
6.57.3 Member Function Documentation . . . 187
6.57.3.1 ConstructVielbein() . . . 187
6.57.3.2 EndCurrentLoop() . . . 187
6.57.3.3 GeodesicFinished() . . . 187
6.57.3.4 getCurNrGeodesics() . . . 187
6.57.3.5 getFullDescriptionStr() . . . 187
6.57.3.6 IsFinished() . . . 188
6.57.3.7 SetNewInitialConditions() . . . 188
6.57.4 Member Data Documentation . . . 188
6.57.4.1 m_Direction . . . 188
6.57.4.2 m_GeodType . . . 188
6.57.4.3 m_Metric_dd . . . 188
6.57.4.4 m_Pos . . . 189

6.57.4.5 m_rLogScale . . . 189
6.57.4.6 m_ScreenCenter . . . 189
6.57.4.7 m_ScreenSize . . . 189
6.57.4.8 m_theMesh . . . 189
6.57.4.9 m_theMetric . . . 189
6.57.4.10 m_Vielbein . . . 189

7 File Documentation **191**

7.1 FOORT/src/Config.cpp File Reference . . . 191
7.1.1 Detailed Description . . . 191
7.2 FOORT/src/Config.h File Reference . . . 191
7.2.1 Detailed Description . . . 193
7.3 Config.h . . . 193
7.4 FOORT/src/ConfigReader.cpp File Reference . . . 194
7.4.1 Detailed Description . . . 194
7.5 FOORT/src/ConfigReader.h File Reference . . . 195
7.5.1 Detailed Description . . . 195
7.6 ConfigReader.h . . . 196
7.7 FOORT/src/Diagnostics.cpp File Reference . . . 198
7.7.1 Detailed Description . . . 198
7.7.2 Function Documentation . . . 199
7.7.2.1 CreateDiagnosticVector() . . . 199
7.8 FOORT/src/Diagnostics.h File Reference . . . 199
7.8.1 Detailed Description . . . 200
7.8.2 Typedef Documentation . . . 201
7.8.2.1 DiagBitflag . . . 201
7.8.2.2 DiagnosticUniqueVector . . . 201
7.8.3 Function Documentation . . . 201
7.8.3.1 CreateDiagnosticVector() . . . 201
7.8.4 Variable Documentation . . . 201
7.8.4.1 Diag_ClosestRadius . . . 201
7.8.4.2 Diag_EquatorialEmission . . . 202
7.8.4.3 Diag_EquatorialPasses . . . 202
7.8.4.4 Diag_FourColorScreen . . . 202
7.8.4.5 Diag_GeodesicPosition . . . 202
7.8.4.6 Diag_None . . . 202
7.9 Diagnostics.h . . . 202
7.10 FOORT/src/DiagnosticsEmission.cpp File Reference . . . 207
7.10.1 Detailed Description . . . 208
7.11 FOORT/src/DiagnosticsEmission.h File Reference . . . 208
7.11.1 Detailed Description . . . 209
7.12 DiagnosticsEmission.h . . . 209

7.13 FOORT/src/Geodesic.cpp File Reference . . . 211
7.13.1 Detailed Description . . . 211
7.14 FOORT/src/Geodesic.h File Reference . . . 211
7.14.1 Detailed Description . . . 212
7.15 Geodesic.h . . . 212
7.16 FOORT/src/Geometry.h File Reference . . . 214
7.16.1 Detailed Description . . . 215
7.16.2 Macro Definition Documentation . . . 216
7.16.2.1 LARGECOUNTER_MAX . . . 216
7.16.2.2 PIXEL_MAX . . . 216
7.16.3 Typedef Documentation . . . 216
7.16.3.1 FourIndex . . . 216
7.16.3.2 largecounter . . . 216
7.16.3.3 OneIndex . . . 216
7.16.3.4 pixelcoord . . . 216
7.16.3.5 Point . . . 216
7.16.3.6 real . . . 217
7.16.3.7 ScreenIndex . . . 217
7.16.3.8 ScreenPoint . . . 217
7.16.3.9 Singularity . . . 217
7.16.3.10 SingularityCoord . . . 217
7.16.3.11 ThreeIndex . . . 217
7.16.3.12 TwoIndex . . . 217
7.16.4 Function Documentation . . . 217
7.16.4.1 operator∗() [1/2] . . . 217
7.16.4.2 operator∗() [2/2] . . . 218
7.16.4.3 operator+() . . . 218
7.16.4.4 operator-() . . . 219
7.16.4.5 operator/() . . . 219
7.16.4.6 toString() [1/3] . . . 220
7.16.4.7 toString() [2/3] . . . 220
7.16.4.8 toString() [3/3] . . . 221
7.16.5 Variable Documentation . . . 221
7.16.5.1 dimension . . . 221
7.16.5.2 pi . . . 221
7.17 Geometry.h . . . 222
7.18 FOORT/src/InputOutput.cpp File Reference . . . 223
7.18.1 Detailed Description . . . 224
7.18.2 Function Documentation . . . 224
7.18.2.1 GetLoopMessageFrequency() . . . 224
7.18.2.2 ScreenOutput() . . . 224
7.18.2.3 SetLoopMessageFrequency() . . . 225

7.18.2.4 SetOutputLevel() . . . 225
7.19 FOORT/src/InputOutput.h File Reference . . . 225
7.19.1 Detailed Description . . . 226
7.19.2 Enumeration Type Documentation . . . 226
7.19.2.1 OutputLevel . . . 226
7.19.3 Function Documentation . . . 227
7.19.3.1 GetLoopMessageFrequency() . . . 227
7.19.3.2 ScreenOutput() . . . 227
7.19.3.3 SetLoopMessageFrequency() . . . 227
7.19.3.4 SetOutputLevel() . . . 228
7.20 InputOutput.h . . . 228
7.21 FOORT/src/Integrators.cpp File Reference . . . 229
7.21.1 Detailed Description . . . 230
7.22 FOORT/src/Integrators.h File Reference . . . 230
7.22.1 Detailed Description . . . 231
7.22.2 Typedef Documentation . . . 231
7.22.2.1 GeodesicIntegratorFunc . . . 231
7.23 Integrators.h . . . 232
7.24 FOORT/src/Main.cpp File Reference . . . 232
7.24.1 Detailed Description . . . 233
7.24.2 Function Documentation . . . 233
7.24.2.1 main() . . . 233
7.25 FOORT/src/Mesh.cpp File Reference . . . 233
7.25.1 Detailed Description . . . 234
7.26 FOORT/src/Mesh.h File Reference . . . 234
7.26.1 Detailed Description . . . 235
7.27 Mesh.h . . . 235
7.28 FOORT/src/Metric.cpp File Reference . . . 238
7.29 FOORT/src/Metric.h File Reference . . . 238
7.29.1 Detailed Description . . . 239
7.30 Metric.h . . . 240
7.31 FOORT/src/Spline.cpp File Reference . . . 243
7.31.1 Detailed Description . . . 243
7.32 FOORT/src/Spline.h File Reference . . . 244
7.32.1 Detailed Description . . . 244
7.33 Spline.h . . . 245
7.34 FOORT/src/Terminations.cpp File Reference . . . 247
7.34.1 Detailed Description . . . 247
7.34.2 Function Documentation . . . 247
7.34.2.1 CreateTerminationVector() . . . 247
7.35 FOORT/src/Terminations.h File Reference . . . 248
7.35.1 Detailed Description . . . 249

7.35.2 Typedef Documentation . . . 250
7.35.2.1 TermBitflag . . . 250
7.35.2.2 TerminationUniqueVector . . . 250
7.35.3 Enumeration Type Documentation . . . 250
7.35.3.1 Term . . . 250
7.35.4 Function Documentation . . . 250
7.35.4.1 CreateTerminationVector() . . . 250
7.35.5 Variable Documentation . . . 251
7.35.5.1 Term_BoundarySphere . . . 251
7.35.5.2 Term_GeneralSingularity . . . 251
7.35.5.3 Term_Horizon . . . 251
7.35.5.4 Term_NaN . . . 251
7.35.5.5 Term_None . . . 251
7.35.5.6 Term_ThetaSingularity . . . 251
7.35.5.7 Term_TimeOut . . . 252
7.36 Terminations.h . . . 252
7.37 FOORT/src/Utilities.cpp File Reference . . . 256
7.37.1 Detailed Description . . . 256
7.38 FOORT/src/Utilities.h File Reference . . . 257
7.38.1 Detailed Description . . . 257
7.39 Utilities.h . . . 258
7.40 FOORT/src/ViewScreen.cpp File Reference . . . 258
7.40.1 Detailed Description . . . 258
7.41 FOORT/src/ViewScreen.h File Reference . . . 259
7.41.1 Detailed Description . . . 259
7.41.2 Enumeration Type Documentation . . . 260
7.41.2.1 GeodesicType . . . 260
7.42 ViewScreen.h . . . 260

Index **263**

Chapter 1

Namespace Index

1.1 Namespace List

Here is a list of all namespaces with brief descriptions:

Config
: Namespace for all configuration functions that initialize objects based on configuration file . . . 11

ConfigReader
: Namespace to put all ConfigReader objects . . . 15

Integrators . . . 16

tk . . . 19

tk::internal . . . 19

Utilities
: Namespace that contains our utility functions . . . 19

Chapter 2

Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

tk::internal::band_matrix . . . 23
ConfigReader::ConfigCollection . . . 38
ConfigReader::ConfigCollection::ConfigSetting . . . 49
Diagnostic . . . 49
ClosestRadiusDiagnostic . . . 33
EquatorialPassesDiagnostic . . . 61
EquatorialEmissionDiagnostic . . . 55
FourColorScreenDiagnostic . . . 71
GeodesicPositionDiagnostic . . . 96
DiagnosticOptions . . . 53
ClosestRadiusOptions . . . 37
EquatorialPassesOptions . . . 65
EquatorialEmissionOptions . . . 59
GeodesicPositionOptions . . . 100
EmissionModel . . . 54
GLMJohnsonSUEmission . . . 101
FluidVelocityModel . . . 69
GeneralCircularRadialFluid . . . 74
Geodesic . . . 84
GeodesicOutputHandler . . . 90
Mesh . . . 126
InputCertainPixelsMesh . . . 107
SimpleSquareMesh . . . 144
SquareSubdivisionMesh . . . 158
Metric . . . 128
BosonStarMetric . . . 26
FlatSpaceMetric . . . 67
SingularityMetric . . . 147
ST3CrMetric . . . 167
SphericalHorizonMetric . . . 151
JohannsenMetric . . . 111
KerrMetric . . . 116
KerrSchildMetric . . . 119

MankoNovikovMetric . . . 122
RasheedLarsenMetric . . . 139
SquareSubdivisionMesh::PixelInfo . . . 137
std::runtime_error
ConfigReader::ConfigReaderException . . . 48
Source . . . 149
NoSource . . . 135
tk::spline . . . 153
Termination . . . 171
BoundarySphereTermination . . . 30
GeneralSingularityTermination . . . 80
HorizonTermination . . . 103
NaNTermination . . . 132
ThetaSingularityTermination . . . 175
TimeOutTermination . . . 178
TerminationOptions . . . 174
BoundarySphereTermOptions . . . 32
GeneralSingularityTermOptions . . . 83
HorizonTermOptions . . . 105
NaNTermOptions . . . 134
ThetaSingularityTermOptions . . . 177
TimeOutTermOptions . . . 181
Utilities::Timer . . . 182
UpdateFrequency . . . 184
ViewScreen . . . 185

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

tk::internal::band_matrix . . . 23
BosonStarMetric
Boson star metric with solitonic potential . . . 26
BoundarySphereTermination
BoundarySphereTermination: Terminate geodesics if they reach outside of a boundary sphere 30
BoundarySphereTermOptions
Options for BoundarySphereTermination . . . 32
ClosestRadiusDiagnostic
Diagnostic that keeps track of the closest (true, not log) radius that the geodesic passes through 33
ClosestRadiusOptions
Options for ClosestRadiusDiagnostic . . . 37
ConfigReader::ConfigCollection . . . 38
ConfigReader::ConfigReaderException . . . 48
ConfigReader::ConfigCollection::ConfigSetting . . . 49
Diagnostic
Abstract base class for all diagnostics . . . 49
DiagnosticOptions
Base class for DiagnosticOptions. Other Diagnostics can inherit from here if they require more options . . . 53
EmissionModel
Emmision model abstract base class . . . 54
EquatorialEmissionDiagnostic
Diagnostic that calculates brightness intensity for the geodesic, based on a specified equatorial disc emission model . . . 55
EquatorialEmissionOptions
Options for EquatorialEmissionDiagnostic . . . 59
EquatorialPassesDiagnostic
Diagnostic that counts the number of passes through the equatorial plane . . . 61
EquatorialPassesOptions
Options for EquatorialPassesDiagnostic . . . 65
FlatSpaceMetric
Flat space metric in 4D . . . 67
FluidVelocityModel
Fluid velocity model abstract base class . . . 69
FourColorScreenDiagnostic
The four color screen diagnostic . . . 71

GeneralCircularRadialFluid
General circular radial fluid velocity model . . . 74
GeneralSingularityTermination
GeneralSingularityTermination: Terminate geodesics if they get too close to one of a number of singularities (of arbitrary codimension) . . . 80
GeneralSingularityTermOptions
Options for GeneralSingularityTermination . . . 83
Geodesic
Geodesic class: an instance of this class is created for each Geodesic that is integrated . . . 84
GeodesicOutputHandler
// GeodesicOutputHandler handles all of the output to file. It gets passed all of the output strings for every Geodesic, it then stores this data until it eventually writes all data to the appropriate files 90
GeodesicPositionDiagnostic
Geodesic position tracker . . . 96
GeodesicPositionOptions
Options for GeodesicPositionDiagnostic . . . 100
GLMJohnsonSUEmission
The Johnson SU emission model used in GLM 2020, PRD 102(12):124004 . . . 101
HorizonTermination
HorizonTermination: Terminate geodesics if they get too close to the horizon . . . 103
HorizonTermOptions
Options for HorizonTermination . . . 105
InputCertainPixelsMesh
Mesh which integrates only certain user-inputted pixels . . . 107
JohannsenMetric
Johannsen black hole metric . . . 111
KerrMetric
The Kerr metric . . . 116
KerrSchildMetric
Kerr metric in Kerr-Schild coordinates . . . 119
MankoNovikovMetric
Mano-Novikov metric (with angular momentum and M3 parameter turned on) . . . 122
Mesh
Abstract base Mesh class . . . 126
Metric
The abstract base class for all Metrics . . . 128
NaNTermination
NaNTermination: Terminate geodesics if they contain a NaN in position or velocity . . . 132
NaNTermOptions
Options for NaNTermination . . . 134
NoSource
NoSource class . . . 135
SquareSubdivisionMesh::PixelInfo
A struct the Mesh uses to keep all information about a given pixel . . . 137
RasheedLarsenMetric
Rasheed-Larsen black hole . . . 139
SimpleSquareMesh
A simple square mesh that will integrate a square of evenly spaced pixels . . . 144
SingularityMetric
Abstract base class for a metric with an arbitrary number of singularities (of arbitrary codimension) . . . 147
Source
Abstract Source base class . . . 149
SphericalHorizonMetric
Abstract base class for a metric with a spherical horizon (i.e. horizon at constant radius r) . . . 151
tk::spline . . . 153
SquareSubdivisionMesh
Adaptive subdivision Mesh . . . 158

ST3CrMetric
Ring fuzzball metric . . . 167
Termination
Abstract base class for all Terminations . . . 171
TerminationOptions
Base class for all TerminationOptions structs. Other TerminationOptions can inherit from here if they require more options . . . 174
ThetaSingularityTermination
ThetaSingularityTermination: Terminate geodesics if they get too close to a polar coordinate singularity . . . 175
ThetaSingularityTermOptions
Options for ThetaSingularityTermination . . . 177
TimeOutTermination
TimeOutTermination: Terminate geodesics if they take too many steps . . . 178
TimeOutTermOptions
Options for TimeOutTermination . . . 181
Utilities::Timer
Timer class to keep track of elapsed time . . . 182
UpdateFrequency
Struct to hold the information for a Diagnostic to update itself . . . 184
ViewScreen
This class is in charge of converting a pixel on the screen into physical initial conditions for a geodesic . . . 185

Chapter 4

File Index

4.1 File List

Here is a list of all files with brief descriptions:

FOORT/src/Config.cpp . . . 191
FOORT/src/Config.h
Functions that read the configuration file and initialize all objects . . . 191
FOORT/src/ConfigReader.cpp . . . 194
FOORT/src/ConfigReader.h
Classes used to read in a configuration file and store the settings . . . 195
FOORT/src/Diagnostics.cpp . . . 198
FOORT/src/Diagnostics.h
Declarations of abstract base Diagnostic class and all its descendants. All Definitions in Diagnostics.cpp . . . 199
FOORT/src/DiagnosticsEmission.cpp . . . 207
FOORT/src/DiagnosticsEmission.h
Declarations of emission and fluid velocity models used for equatorial disc emission . . . 208
FOORT/src/Geodesic.cpp . . . 211
FOORT/src/Geodesic.h
Declarations of abstract base Source class and all its descendants. Declaration of Geodesic class . . . 211
FOORT/src/Geometry.h
Definitions and some operations with geometric objects.alignas . . . 214
FOORT/src/InputOutput.cpp . . . 223
FOORT/src/InputOutput.h
Declarations of functions & classes that deal with the output to files and to the screen . . . 225
FOORT/src/Integrators.cpp . . . 229
FOORT/src/Integrators.h
Declarations of integrator functions that integrate geodesic equation . . . 230
FOORT/src/Main.cpp
Main function for FOORT . . . 232
FOORT/src/Mesh.cpp . . . 233
FOORT/src/Mesh.h
Declarations of abstract base Mesh class and all its descendants . . . 234
FOORT/src/Metric.cpp . . . 238
FOORT/src/Metric.h
Declarations of abstract base Metric class and all its descendants . . . 238
FOORT/src/Spline.cpp
Simple cubic spline interpolation library without external dependencies . . . 243

FOORT/src/Spline.h
Simple cubic spline interpolation library without external dependencies . . . 244
FOORT/src/Terminations.cpp . . . 247
FOORT/src/Terminations.h
Declarations of abstract base Termination class and all its descendants . . . 248
FOORT/src/Utilities.cpp . . . 256
FOORT/src/Utilities.h
Declarations of various utility functions, in a Utilities namespace . . . 257
FOORT/src/ViewScreen.cpp . . . 258
FOORT/src/ViewScreen.h
Declarations of ViewScreen class . . . 259

Chapter 5

Namespace Documentation

5.1 Config Namespace Reference

Namespace for all configuration functions that initialize objects based on configuration file.

Typedefs

- using ConfigCollection = ConfigReader::ConfigCollection
- using SettingError = std::invalid_argument

Functions

- void InitializeScreenOutput (const ConfigCollection &theCfg)

  Initialize screen output options.
- std::unique_ptr< Metric > GetMetric (const ConfigCollection &theCfg)

  Use configuration to create the correct Metric with specified parameters.
- std::unique_ptr< Source > GetSource (const ConfigCollection &theCfg, const Metric *const theMetric)

  Use configuration to create the correct Source with specified parameters.
- void InitializeDiagnostics (const ConfigCollection &theCfg, DiagBitflag &alldiags, DiagBitflag &valdiag, const Metric *const theMetric)

  Use configuration to set the Diagnostics bitflag appropriately; initialize all DiagnosticOptions for all Diagnostics that are turned on; and set bitflag for diagnostic to be used for coarseness evaluating in Mesh.
- void InitializeTerminations (const ConfigCollection &theCfg, TermBitflag &allterms, const Metric *const the↩ Metric)

  Use configuration to set the Termination bitflag appropriately; and initialize all TerminationOptions for all Terminations that are turned on.
- std::unique_ptr< ViewScreen > GetViewScreen (const ConfigCollection &theCfg, DiagBitflag valdiag, const Metric *const theMetric)

  Use configuration to create the ViewScreen object with specified parameters.
- std::unique_ptr< Mesh > GetMesh (const ConfigCollection &theCfg, DiagBitflag valdiag)

  Use configuration to create the Mesh object with specified parameters.
- GeodesicIntegratorFunc GetGeodesicIntegrator (const ConfigCollection &theCfg)

  Use configuration to set the GeodesicIntegratorFunc pointer to the correct integrator function.
- std::unique_ptr< GeodesicOutputHandler > GetOutputHandler (const ConfigCollection &theCfg, DiagBitflag alldiags, DiagBitflag valdiag, std::string FirstLineInfo)

  Use configuration to create the GeodesicOutputHandler object with specified parameters.

Variables

- constexpr auto Output_Important_Default = OutputLevel::Level_0_WARNING
- constexpr auto Output_Other_Default = OutputLevel::Level_1_PROC

5.1.1 Detailed Description

Namespace for all configuration functions that initialize objects based on configuration file.

5.1.2 Typedef Documentation

5.1.2.1 ConfigCollection

```
using Config::ConfigCollection = ConfigReader::ConfigCollection
```

5.1.2.2 SettingError

```
using Config::SettingError = std::invalid_argument
```

5.1.3 Function Documentation

5.1.3.1 GetGeodesicIntegrator()

```
GeodesicIntegratorFunc Config::GetGeodesicIntegrator (
            const ConfigCollection & theCfg)
```

Use configuration to set the GeodesicIntegratorFunc pointer to the correct integrator function.

Parameters

theCfg	Pointer to the configuration object

Returns

GeodesicIntegratorFunc function

5.1.3.2 GetMesh()

```
std::unique_ptr< Mesh > Config::GetMesh (
            const ConfigCollection & theCfg,
            DiagBitflag valdiag)
```

Use configuration to create the Mesh object with specified parameters.

Parameters

theCfg	Pointer to the configuration object
valdiag	Diagnostic bitflag used for coarseness evaluation in the Mesh

Returns

Pointer to the Mesh object

5.1.3.3 GetMetric()

```
std::unique_ptr< Metric > Config::GetMetric (
            const ConfigCollection & theCfg)
```

Use configuration to create the correct Metric with specified parameters.

Parameters

theCfg	Pointer to the configuration object

Returns

Metric pointer

5.1.3.4 GetOutputHandler()

```
std::unique_ptr< GeodesicOutputHandler > Config::GetOutputHandler (
            const ConfigCollection & theCfg,
            DiagBitflag alldiags,
            DiagBitflag valdiag,
            std::string FirstLineInfo)
```

Use configuration to create the GeodesicOutputHandler object with specified parameters.

Parameters

theCfg	Pointer to the configuration object
alldiags	Diagnostics bitflags
valdiag	Diagnostic bitflag used for coarseness evaluation in the Mesh
FirstLineInfo	String to be written as the first line in the output file

Returns

Pointer to the GeodesicOutputHandler object

5.1.3.5 GetSource()

```
std::unique_ptr< Source > Config::GetSource (
            const ConfigCollection & theCfg,
            const Metric *const theMetric)
```

Use configuration to create the correct Source with specified parameters.

Parameters

theCfg	Pointer to the configuration object
theMetric	Pointer to the Metric object

Returns

Pointer to the Source object

5.1.3.6 GetViewScreen()

```
std::unique_ptr< ViewScreen > Config::GetViewScreen (
            const ConfigCollection & theCfg,
            DiagBitflag valdiag,
            const Metric *const theMetric)
```

Use configuration to create the ViewScreen object with specified parameters.

Parameters

theCfg	Pointer to the configuration object
valdiag	Diagnostic bitflag used for coarseness evaluation in the Mesh
theMetric	Pointer to the Metric object

Returns

Pointer to the ViewScreen object

5.1.3.7 InitializeDiagnostics()

```
void Config::InitializeDiagnostics (
            const ConfigCollection & theCfg,
            DiagBitflag & alldiags,
            DiagBitflag & valdiag,
            const Metric *const theMetric)
```

Use configuration to set the Diagnostics bitflag appropriately; initialize all DiagnosticOptions for all Diagnostics that are turned on; and set bitflag for diagnostic to be used for coarseness evaluating in Mesh.

Parameters

theCfg	Pointer to the configuration object
alldiags	Pointer to the diagnostics bitflags
valdiag	Pointer to the diagnostics used for coarseness evaluation in the Mesh
theMetric	Pointer to the Metric object

5.1.3.8 InitializeScreenOutput()

```
void Config::InitializeScreenOutput (
            const ConfigCollection & theCfg)
```

Initialize screen output options.

Parameters

theCfg	Pointer to the configuration object

5.1.3.9 InitializeTerminations()

```
void Config::InitializeTerminations (
            const ConfigCollection & theCfg,
            TermBitflag & allterms,
            const Metric *const theMetric)
```

Use configuration to set the Termination bitflag appropriately; and initialize all TerminationOptions for all Terminations that are turned on.

Parameters

theCfg	Pointer to the configuration object
allterms	Pointer to the termination bitflags
theMetric	Pointer to the Metric object

5.1.4 Variable Documentation

5.1.4.1 Output_Important_Default

```
auto Config::Output_Important_Default = OutputLevel::Level_0_WARNING  [constexpr]
```

5.1.4.2 Output_Other_Default

```
auto Config::Output_Other_Default = OutputLevel::Level_1_PROC  [constexpr]
```

5.2 ConfigReader Namespace Reference

Namespace to put all ConfigReader objects.

Classes

- class ConfigCollection
- class ConfigReaderException

Variables

- const long long MaxStreamSize {std::numeric_limits<std::streamsize>::max()}

5.2.1 Detailed Description

Namespace to put all ConfigReader objects.

5.2.2 Variable Documentation

5.2.2.1 MaxStreamSize

```
const long long ConfigReader::MaxStreamSize {std::numeric_limits<std::streamsize>::max()}
```

5.3 Integrators Namespace Reference

Functions

- std::string GetFullIntegratorDescription ()

  Description string getter for the Integrator.
- real GetAdaptiveStep (Point curpos, OneIndex curvel)

  Determine the (affine parameter) step size to take.
- void IntegrateGeodesicStep_RK4 (Point curpos, OneIndex curvel, Point &nextpos, OneIndex &nextvel, real &stepsize, const Metric *theMetric, const Source *theSource)

  Integrate the geodesic equation by one step using Runge-Kutta-4.
- void IntegrateGeodesicStep_Verlet (Point curpos, OneIndex curvel, Point &nextpos, OneIndex &nextvel, real &stepsize, const Metric *theMetric, const Source *theSource)

  Integrate the geodesic equation by one step using the Verlet algorithm.

Variables

- constexpr real delta_nodiv0 = 1e-20

  This is used to avoid dividing by zero.
- real Derivative_hval {1e-7}

  The spacing used in stencils for the calculation of numerical derivatives (e.g. in Christoffel symbols)
- std::string IntegratorDescription {"Verlet"}

  The name of the integrator selected.
- real epsilon {0.03}

  This is the base step size to be taken (the integrator will adapt this if necessary)
- real SmallestPossibleStepsize {1e-12}

  The affine parameter must always go forward by at least this amount.
- real VerletVelocityTolerance {-1.0}
- largecounter VerletMaxIterations {100}

5.3.1 Function Documentation

5.3.1.1 GetAdaptiveStep()

```
real Integrators::GetAdaptiveStep (
            Point curpos,
            OneIndex curvel)
```

Determine the (affine parameter) step size to take.

algorithm as in Raptor (eqs (21)-(24)), which is taken from Noble et al. (2007) & Dolence et al. (2009)

Parameters

curpos	current position
curvel	current velocity

Returns

real

5.3.1.2 GetFullIntegratorDescription()

```
std::string Integrators::GetFullIntegratorDescription ()
```

Description string getter for the Integrator.

Returns

std::string

5.3.1.3 IntegrateGeodesicStep_RK4()

```
void Integrators::IntegrateGeodesicStep_RK4 (
            Point curpos,
            OneIndex curvel,
            Point & nextpos,
            OneIndex & nextvel,
            real & stepsize,
            const Metric * theMetric,
            const Source * theSource)
```

Integrate the geodesic equation by one step using Runge-Kutta-4.

Parameters

curpos	current position
curvel	current velocity
nextpos	reference to next position
nextvel	reference to next velocity
stepsize	reference to the stepsize
theMetric	pointer to the Metric object
theSource	pointer to the Source object

5.3.1.4 IntegrateGeodesicStep_Verlet()

```
void Integrators::IntegrateGeodesicStep_Verlet (
            Point curpos,
            OneIndex curvel,
            Point & nextpos,
            OneIndex & nextvel,
            real & stepsize,
            const Metric * theMetric,
            const Source * theSource)
```

Integrate the geodesic equation by one step using the Verlet algorithm.

Parameters

curpos	current position
curvel	current velocity
nextpos	reference to next position
nextvel	reference to next velocity
stepsize	reference to the stepsize
theMetric	pointer to the Metric object
theSource	pointer to the Source object

5.3.2 Variable Documentation

5.3.2.1 delta_nodiv0

```
real Integrators::delta_nodiv0 = 1e-20  [constexpr]
```

This is used to avoid dividing by zero.

5.3.2.2 Derivative_hval

```
real Integrators::Derivative_hval {1e-7}  [inline]
```

The spacing used in stencils for the calculation of numerical derivatives (e.g. in Christoffel symbols)

5.3.2.3 epsilon

```
real Integrators::epsilon {0.03}  [inline]
```

This is the base step size to be taken (the integrator will adapt this if necessary)

5.3.2.4 IntegratorDescription

```
std::string Integrators::IntegratorDescription {"Verlet"}  [inline]
```

The name of the integrator selected.

5.3.2.5 SmallestPossibleStepsize

```
real Integrators::SmallestPossibleStepsize {1e-12}  [inline]
```

The affine parameter must always go forward by at least this amount.

5.3.2.6 VerletMaxIterations

```
largecounter Integrators::VerletMaxIterations {100}  [inline]
```

Maximum number of fixed-point iterations per step in the Verlet velocity loop (only used if VerletVelocityTolerance $>$ 0; the last iterate is kept if the cap is reached)

5.3.2.7 VerletVelocityTolerance

```
real Integrators::VerletVelocityTolerance {-1.0}  [inline]
```

Tolerance on the change in velocity in the iteration loop of the Verlet integration algorithm (default -1.0: no iteration; any positive value enables the fixed-point iteration)

5.4 tk Namespace Reference

Namespaces

- namespace internal

Classes

- class spline

5.5 tk::internal Namespace Reference

Classes

- class band_matrix

5.6 Utilities Namespace Reference

Namespace that contains our utility functions.

Classes

- class Timer

  Timer class to keep track of elapsed time.

Functions

- std::string GetTimeStampString ()

  Get a string of the current time (in a format that can be used to append to file names)
- std::vector< std::string > GetDiagNameStrings (DiagBitflag alldiags, DiagBitflag valdiag)

  Helper function to get all Diagnostic Names (for outputting to files)
- std::string GetFirstLineInfoString (const Metric *theMetric, const Source *theSource, DiagBitflag alldiags, DiagBitflag valdiag, TermBitflag allterms, const ViewScreen *theView)

  This returns the full string to be written to every output file as its first line.

5.6.1 Detailed Description

Namespace that contains our utility functions.

5.6.2 Function Documentation

5.6.2.1 GetDiagNameStrings()

```
std::vector< std::string > Utilities::GetDiagNameStrings (
            DiagBitflag alldiags,
            DiagBitflag valdiag)
```

Helper function to get all Diagnostic Names (for outputting to files)

Parameters

alldiags	bitflag for all Diagnostics
valdiag	bitflag for the value diagnostic

Returns

std::vector<std::string>

5.6.2.2 GetFirstLineInfoString()

```
std::string Utilities::GetFirstLineInfoString (
            const Metric * theMetric,
            const Source * theSource,
            DiagBitflag alldiags,
            DiagBitflag valdiag,
            TermBitflag allterms,
            const ViewScreen * theView)
```

This returns the full string to be written to every output file as its first line.

Parameters

theMetric	pointer to the Metric object
theSource	pointer to the Source object
alldiags	bitflag for all Diagnostics
valdiag	bitflag for the value diagnostic
allterms	bitflag for all Terminations
theView	pointer to the ViewScreen object

Returns

std::string

5.6.2.3 GetTimeStampString()

```
std::string Utilities::GetTimeStampString ()
```

Get a string of the current time (in a format that can be used to append to file names)

Returns

std::string

Chapter 6

Class Documentation

6.1 tk::internal::band_matrix Class Reference

`#include <Spline.h>`

Public Member Functions

- band_matrix ()
- band_matrix (int dim, int n_u, int n_l)
- ~band_matrix ()
- void resize (int dim, int n_u, int n_l)
- int dim () const
- int num_upper () const
- int num_lower () const
- double & operator() (int i, int j)
- double operator() (int i, int j) const
- double & saved_diag (int i)
- double saved_diag (int i) const
- void lu_decompose ()
- std::vector< double > r_solve (const std::vector< double > &b) const
- std::vector< double > l_solve (const std::vector< double > &b) const
- std::vector< double > lu_solve (const std::vector< double > &b, bool is_lu_decomposed=false)

Private Attributes

- std::vector< std::vector< double > > m_upper
- std::vector< std::vector< double > > m_lower

6.1.1 Constructor & Destructor Documentation

6.1.1.1 band_matrix() [1/2]

`tk::internal::band_matrix::band_matrix () [inline]`

6.1.1.2 band_matrix() [2/2]

```
tk::internal::band_matrix::band_matrix (
            int dim,
            int n_u,
            int n_l)
```

6.1.1.3 ~band_matrix()

```
tk::internal::band_matrix::~band_matrix ()  [inline]
```

6.1.2 Member Function Documentation

6.1.2.1 dim()

```
int tk::internal::band_matrix::dim () const
```

6.1.2.2 l_solve()

```
std::vector< double > tk::internal::band_matrix::l_solve (
            const std::vector< double > & b) const
```

6.1.2.3 lu_decompose()

```
void tk::internal::band_matrix::lu_decompose ()
```

6.1.2.4 lu_solve()

```
std::vector< double > tk::internal::band_matrix::lu_solve (
            const std::vector< double > & b,
            bool is_lu_decomposed = false)
```

6.1.2.5 num_lower()

```
int tk::internal::band_matrix::num_lower () const
```

6.1.2.6 num_upper()

```
int tk::internal::band_matrix::num_upper () const
```

6.1.2.7 operator()() [1/2]

```
double & tk::internal::band_matrix::operator() (
            int i,
            int j)
```

6.1.2.8 operator()() [2/2]

```
double tk::internal::band_matrix::operator() (
            int i,
            int j) const
```

6.1.2.9 r_solve()

```
std::vector< double > tk::internal::band_matrix::r_solve (
            const std::vector< double > & b) const
```

6.1.2.10 resize()

```
void tk::internal::band_matrix::resize (
            int dim,
            int n_u,
            int n_l)
```

6.1.2.11 saved_diag() [1/2]

```
double & tk::internal::band_matrix::saved_diag (
            int i)
```

6.1.2.12 saved_diag() [2/2]

```
double tk::internal::band_matrix::saved_diag (
            int i) const
```

6.1.3 Member Data Documentation

6.1.3.1 m_lower

```
std::vector<std::vector<double> > tk::internal::band_matrix::m_lower  [private]
```

6.1.3.2 m_upper

```
std::vector<std::vector<double> > tk::internal::band_matrix::m_upper  [private]
```

The documentation for this class was generated from the following files:


- FOORT/src/Spline.h
- FOORT/src/Spline.cpp

6.2 BosonStarMetric Class Reference

Boson star metric with solitonic potential.

`#include <Metric.h>`

Inheritance diagram for BosonStarMetric:



Public Member Functions

- BosonStarMetric (double Phi_infinity, int num_lines, bool rLogScale=false, std::string Phi_filename="Phi.dat", std::string m_filename="m.dat")

  Construct a new Boson Star Metric object.
- TwoIndex getMetric_dd (const Point &p) const final

  BosonStar metric getter, indices down.
- TwoIndex getMetric_uu (const Point &p) const final

  BosonStar metric getter, indices up.
- std::string getFullDescriptionStr () const final

  BosonStar metric description string getter.

Public Member Functions inherited from Metric

- virtual ~Metric ()=default
- Metric (bool rlogscale=false)

  Construct a new Metric object.
- virtual ThreeIndex getChristoffel_udd (const Point &p) const

  Return the Christoffel symbols of the metric (indices up, down, down)
- virtual FourIndex getRiemann_uddd (const Point &p) const

  Riemann tensor of the metric (indices up, down, down, down)
- virtual real getKretschmann (const Point &p) const

  Get the Kretschmann scalar at a point.
- bool getrLogScale () const

  Get whether we are using a logarithmic radial scale.

Protected Member Functions

- void read_data ()

  function to read the data

Protected Attributes

- const double m_Phi_infinity

  The value of Phi at infinity, before rescaling.
- const int m_num_lines
- std::string m_Phi_filename

  filename with Phi data
- std::string m_m_filename

  filename with m data
- tk::spline m_PhiSpline

  The spline interpolator for Phi.
- tk::spline m_mSpline

  The spline interpolator for m.

Protected Attributes inherited from Metric

- std::vector< int > m_Symmetries {}

  The symmetries (coordinate Killing vectors) of the metric. Should be set by descendant constructor.
- const bool m_rLogScale

  Are we using a logarithmic r coordinate?

6.2.1 Detailed Description

Boson star metric with solitonic potential.

Note

Implementation by Seppe Staelens

The default files correspond to sigma = 0.06 and phi_c = 0.044

6.2.2 Constructor & Destructor Documentation

6.2.2.1 BosonStarMetric()

```
BosonStarMetric::BosonStarMetric (
            double Phi_infinity,
            int num_lines,
            bool rLogScale = false,
            std::string Phi_filename = "Phi.dat",
            std::string m_filename = "m.dat")
```

Construct a new Boson Star Metric object.

Parameters

Phi_infinity	value of Phi = log(lapse) at infinity
num_lines	number of lines in the data files
rLogScale	whether we are using a logarithmic radial scale
Phi_filename	filename for the Phi data
m_filename	filename for the mass aspect data

6.2.3 Member Function Documentation

6.2.3.1 getFullDescriptionStr()

```
std::string BosonStarMetric::getFullDescriptionStr () const  [final], [virtual]
```

BosonStar metric description string getter.

Returns

std::string

Reimplemented from Metric.

6.2.3.2 getMetric_dd()

```
TwoIndex BosonStarMetric::getMetric_dd (
            const Point & p) const  [final], [virtual]
```

BosonStar metric getter, indices down.

Parameters

p	Point at which to evaluate the metric

Returns

TwoIndex

Implements Metric.

6.2.3.3 getMetric_uu()

```
TwoIndex BosonStarMetric::getMetric_uu (
            const Point & p) const  [final], [virtual]
```

BosonStar metric getter, indices up.

Parameters

p	Point at which to evaluate the metric

Returns

TwoIndex

Implements Metric.

6.2.3.4 read_data()

```
void BosonStarMetric::read_data ()  [protected]
```

function to read the data

Read the numerically obtained boson star metric data from the files.

6.2.4 Member Data Documentation

6.2.4.1 m_m_filename

```
std::string BosonStarMetric::m_m_filename  [protected]
```

filename with m data

6.2.4.2 m_mSpline

```
tk::spline BosonStarMetric::m_mSpline  [protected]
```

The spline interpolator for m.

6.2.4.3 m_num_lines

```
const int BosonStarMetric::m_num_lines  [protected]
```

Number of lines to be read from the data files. Mainly to avoid reading the data at extreme distances, which could upset the spline interpolation.

6.2.4.4 m_Phi_filename

```
std::string BosonStarMetric::m_Phi_filename  [protected]
```

filename with Phi data

6.2.4.5 m_Phi_infinity

```
const double BosonStarMetric::m_Phi_infinity  [protected]
```

The value of Phi at infinity, before rescaling.

6.2.4.6 m_PhiSpline

```
tk::spline BosonStarMetric::m_PhiSpline  [protected]
```

The spline interpolator for Phi.

The documentation for this class was generated from the following files:


- FOORT/src/Metric.h
- FOORT/src/Metric.cpp

6.3 BoundarySphereTermination Class Reference

BoundarySphereTermination: Terminate geodesics if they reach outside of a boundary sphere.

`#include <Terminations.h>`

Inheritance diagram for BoundarySphereTermination:



Public Member Functions

- BoundarySphereTermination (Geodesic ∗const theGeodesic)
- Term CheckTermination () final

  Check if the boundary sphere has been reached.
- std::string getFullDescriptionStr () const final

  Description string getter for the Boundary Sphere Termination.

Public Member Functions inherited from Termination

- Termination ()=delete
- Termination (Geodesic ∗const theGeodesic)
- virtual void Reset ()

  Reset to 0 to start integrating a new geodesic.
- virtual ∼Termination ()=default

Static Public Attributes

- static std::unique_ptr< BoundarySphereTermOptions > TermOptions

  The options that the BoundarySphereTermination keeps (contains the radius of the boundary sphere)

Additional Inherited Members

Protected Member Functions inherited from Termination

- bool DecideUpdate (largecounter UpdateNSteps)

  Returns true if the Termination should update its internal status.

Protected Attributes inherited from Termination

- Geodesic ∗const m_OwnerGeodesic

  The geodesic that owns the Termination (a const pointer to the Geodesic)
- largecounter m_StepsSinceUpdated {}

  The termination is itself in charge of keeping track of how many steps it has been since it has been updated. The Termination's TerminationOptions struct tells it how many steps it needs to wait between updates.

6.3.1 Detailed Description

BoundarySphereTermination: Terminate geodesics if they reach outside of a boundary sphere.

6.3.2 Constructor & Destructor Documentation

6.3.2.1 BoundarySphereTermination()

```
BoundarySphereTermination::BoundarySphereTermination (
            Geodesic *const theGeodesic)  [inline]
```

6.3.3 Member Function Documentation

6.3.3.1 CheckTermination()

```
Term BoundarySphereTermination::CheckTermination ()  [final], [virtual]
```

Check if the boundary sphere has been reached.

Returns

Term

Implements Termination.

6.3.3.2 getFullDescriptionStr()

```
std::string BoundarySphereTermination::getFullDescriptionStr () const  [final], [virtual]
```

Description string getter for the Boundary Sphere Termination.

Returns

std::string

Implements Termination.

6.3.4 Member Data Documentation

6.3.4.1 TermOptions

```
std::unique_ptr< BoundarySphereTermOptions > BoundarySphereTermination::TermOptions  [static]
```

The options that the BoundarySphereTermination keeps (contains the radius of the boundary sphere)

The documentation for this class was generated from the following files:


- FOORT/src/Terminations.h
- FOORT/src/Config.cpp
- FOORT/src/Terminations.cpp

6.4 BoundarySphereTermOptions Struct Reference

Options for BoundarySphereTermination.

`#include <Terminations.h>`

Inheritance diagram for BoundarySphereTermOptions:



Public Member Functions

- BoundarySphereTermOptions (real theRadius, bool therLogScale, largecounter Nsteps)

Public Member Functions inherited from TerminationOptions

- TerminationOptions (largecounter Nsteps)
- virtual ~TerminationOptions ()=default

Public Attributes

- const real SphereRadius

  Radius of the boundary sphere.
- const bool rLogScale

  Whether we are using a logarithmic r coordinate.

Public Attributes inherited from TerminationOptions

- const largecounter UpdateEveryNSteps

  Number of steps between updates.

6.4.1 Detailed Description

Options for BoundarySphereTermination.

Keeps track of the boundary sphere radius, whether we are using a logarithmic r coordinate.

6.4.2 Constructor & Destructor Documentation

6.4.2.1 BoundarySphereTermOptions()

```
BoundarySphereTermOptions::BoundarySphereTermOptions (
            real theRadius,
            bool therLogScale,
            largecounter Nsteps)  [inline]
```

6.4.3 Member Data Documentation

6.4.3.1 rLogScale

```
const bool BoundarySphereTermOptions::rLogScale
```

Whether we are using a logarithmic r coordinate.

6.4.3.2 SphereRadius

```
const real BoundarySphereTermOptions::SphereRadius
```

Radius of the boundary sphere.

The documentation for this struct was generated from the following file:


- FOORT/src/Terminations.h

6.5 ClosestRadiusDiagnostic Class Reference

Diagnostic that keeps track of the closest (true, not log) radius that the geodesic passes through.

```
#include <Diagnostics.h>
```

Inheritance diagram for ClosestRadiusDiagnostic:



Public Member Functions

- ClosestRadiusDiagnostic (Geodesic *const theGeodesic)
- void Reset () final

  ClosestRadiusDiagnostic functions.
- void UpdateData () final

  Check to see if we have travelled closer to the center and update the closest radius.
- std::string getFullDataStr () const final

  Return the closest radius as a string.
- std::vector< real > getFinalDataVal () const final

  Return the closest radius as a vector of size one.
- real FinalDataValDistance (const std::vector< real > &val1, const std::vector< real > &val2) const final

  Return the absolute value of the difference between the closest radii.
- std::string getNameStr () const final

  Simple name without spaces.
- std::string getFullDescriptionStr () const final

  More descriptive string (with spaces)

Public Member Functions inherited from Diagnostic

- Diagnostic ()=delete
- Diagnostic (Geodesic *const theGeodesic)
- virtual ~Diagnostic ()=default

Static Public Attributes

- static std::unique_ptr< ClosestRadiusOptions > DiagOptions

Private Attributes

- real m_ClosestRadius {-1}

Additional Inherited Members

Protected Member Functions inherited from Diagnostic

- bool DecideUpdate (const UpdateFrequency &myUpdateFrequency)

  Returns true if the Diagnostic should update its initial status.

Protected Attributes inherited from Diagnostic

- Geodesic *const m_OwnerGeodesic
- largecounter m_StepsSinceUpdated {}

6.5.1 Detailed Description

Diagnostic that keeps track of the closest (true, not log) radius that the geodesic passes through.

6.5.2 Constructor & Destructor Documentation

6.5.2.1 ClosestRadiusDiagnostic()

```
ClosestRadiusDiagnostic::ClosestRadiusDiagnostic (
            Geodesic *const theGeodesic)  [inline]
```

6.5.3 Member Function Documentation

6.5.3.1 FinalDataValDistance()

```
real ClosestRadiusDiagnostic::FinalDataValDistance (
            const std::vector< real > & val1,
            const std::vector< real > & val2) const  [final], [virtual]
```

Return the absolute value of the difference between the closest radii.

Parameters

val1	first closest radius
val2	second closest radius

Returns

real

Implements Diagnostic.

6.5.3.2 getFinalDataVal()

```
std::vector< real > ClosestRadiusDiagnostic::getFinalDataVal () const  [final], [virtual]
```

Return the closest radius as a vector of size one.

Returns

std::vector<real>

Implements Diagnostic.

6.5.3.3 getFullDataStr()

```
std::string ClosestRadiusDiagnostic::getFullDataStr () const  [final], [virtual]
```

Return the closest radius as a string.

Returns

std::string

Implements Diagnostic.

6.5.3.4 getFullDescriptionStr()

```
std::string ClosestRadiusDiagnostic::getFullDescriptionStr () const  [final], [virtual]
```

More descriptive string (with spaces)

Returns

std::string

Reimplemented from Diagnostic.

6.5.3.5 getNameStr()

```
std::string ClosestRadiusDiagnostic::getNameStr () const  [final], [virtual]
```

Simple name without spaces.

Returns

std::string

Implements Diagnostic.

6.5.3.6 Reset()

```
void ClosestRadiusDiagnostic::Reset ()  [final], [virtual]
```

ClosestRadiusDiagnostic functions.

Reset the closest radius to -1 and call base class Reset function

Reimplemented from Diagnostic.

6.5.3.7 UpdateData()

```
void ClosestRadiusDiagnostic::UpdateData ()  [final], [virtual]
```

Check to see if we have travelled closer to the center and update the closest radius.

Implements Diagnostic.

6.5.4 Member Data Documentation

6.5.4.1 DiagOptions

```
std::unique_ptr< ClosestRadiusOptions > ClosestRadiusDiagnostic::DiagOptions  [static]
```

6.5.4.2 m_ClosestRadius

```
real ClosestRadiusDiagnostic::m_ClosestRadius {-1}  [private]
```

The documentation for this class was generated from the following files:


- FOORT/src/Diagnostics.h
- FOORT/src/Config.cpp
- FOORT/src/Diagnostics.cpp

6.6 ClosestRadiusOptions Struct Reference

Options for ClosestRadiusDiagnostic.

`#include <Diagnostics.h>`

Inheritance diagram for ClosestRadiusOptions:



Public Member Functions

- ClosestRadiusOptions (bool rlog, UpdateFrequency thefrequency)

Public Member Functions inherited from DiagnosticOptions

- DiagnosticOptions (UpdateFrequency thefrequency)
- virtual ~DiagnosticOptions ()=default

Public Attributes

- const bool RLogScale

Public Attributes inherited from DiagnosticOptions

- const UpdateFrequency theUpdateFrequency

6.6.1 Detailed Description

Options for ClosestRadiusDiagnostic.

Inherits from DiagnosticOptions, and adds the flag for using log(r) scale.

6.6.2 Constructor & Destructor Documentation

6.6.2.1 ClosestRadiusOptions()

```
ClosestRadiusOptions::ClosestRadiusOptions (
            bool rlog,
            UpdateFrequency thefrequency)  [inline]
```

6.6.3 Member Data Documentation

6.6.3.1 RLogScale

```
const bool ClosestRadiusOptions::RLogScale
```

The documentation for this struct was generated from the following file:

- FOORT/src/Diagnostics.h

6.7 ConfigReader::ConfigCollection Class Reference

```
#include <ConfigReader.h>
```

Classes

- struct ConfigSetting

Public Member Functions

- bool Exists (std::string_view SettingName) const

  Check if a setting with the given name exists in the collection.
- int NrSettings () const

  Return the total number of settings in the collection.
- bool IsCollection (std::string_view SettingName) const

  Check if a setting with the given name is a collection.
- bool IsCollection (int SettingIndex) const

  Check if a setting with the given index is a collection.
- const ConfigCollection & operator[ ] (std::string_view CollectionName) const

  Access a subcollection by name.
- const ConfigCollection & operator[ ] (int CollectionIndex) const

  Access a subcollection by index.
- template<class OutputType>
  bool LookupValue (std::string_view SettingName, OutputType &theOutput) const

  Looks up the value of a setting with the given name and puts it in the output variable.
- template<class OutputType>
  bool LookupValue (int SettingIndex, OutputType &theOutput) const

  Looks up the value of a setting with the given index and puts it in the output variable.
- bool LookupValueInteger (std::string_view SettingName, int &theOutput) const

  If the output is int, we only look up to see if the value is an int.
- bool LookupValueInteger (std::string_view SettingName, long &theOutput) const

  If the output is long, the setting value can either be a long or an int, so we check for both.
- bool LookupValueInteger (std::string_view SettingName, long long &theOutput) const

  If the output is long long, the setting value can either be a long long, a long, or an int, so we check for all.
- bool LookupValueInteger (std::string_view SettingName, unsigned int &theOutput) const

  If the output is unsigned int, the setting value can either be an unsigned int, an int, a long, or a long long, so we check for all.
- bool LookupValueInteger (std::string_view SettingName, unsigned long &theOutput) const

If the output is unsigned long, the setting value can either be an unsigned long, an unsigned int, an int, a long, or a long long, so we check for all.

- bool LookupValueInteger (std::string_view SettingName, unsigned long long &theOutput) const

  If the output is unsigned long long, the setting value can either be an unsigned long long, an unsigned long, an unsigned int, an int, a long, or a long long, so we check for all.

- template<class OutputType>
  bool LookupValueInteger (int SettingIndex, OutputType &theOutput) const

  This simply defers to the setting-name-based implementation of the function with given output type.

- void DisplayCollection (std::ostream &OutputStream, int Indent=0) const

  Output the entire collection to a given output stream.

- bool ReadFile (const std::string &FileName)

  Read in a configuration file.

Private Types

- using ConfigSettingValue

Private Member Functions

- int GetSettingIndex (std::string_view SettingName) const

  Return the index of a specific setting in the collection.

- void DisplaySetting (std::ostream &OutputStream, int SettingIndex, int Indent) const

  Output a single setting to the output stream.

- void DisplayTabs (std::ostream &OutputStream, int NrTabs) const

  Output a given number of tabs to the output stream.

- void ReadCollection (std::ifstream &InputFile)

  Read in an entire collection (including subcollections). Pre: stream is positioned right after '{' (or at beginning of file). Post: stream is positioned right after '}' (or at EOF).

- void ReadSettingName (std::ifstream &InputFile, std::string &theName)

  Read in a setting name. Pre: next non-whitespace character in stream is beginning of name. Post: stream has just read in all characters of name (but no more); returns "" if there is no more setting to read in the current collection, in this case '}' has been read in (for subcollections).

- void ReadSettingSpecificChar (std::ifstream &InputFile, char theChar) const

  Read in one specific character only (not '/'). Pre: next non-whitespace character in stream is this character. Post: stream is just after character.

- void ReadSettingValue (std::ifstream &InputFile, ConfigSettingValue &theValue)

  Read in setting value (could be subcollection). Pre: next non-whitespace character in stream is beginning of value (can be '{' for subcollection, digit or '-' or '.' or 'e' for number, "" for string, or 't'/'f' for boolean). Post: Value has entirely been read in (i.e. next character should be ';').

Private Attributes

- std::vector< ConfigSetting > m_Settings {}

6.7.1 Member Typedef Documentation

6.7.1.1 ConfigSettingValue

```
using ConfigReader::ConfigCollection::ConfigSettingValue  [private]
```

Initial value:

```
std::variant<bool,
                                        int, long, long long,
                                        double,
                                        std::string,
                                        std::unique_ptr<ConfigCollection>>
```

6.7.2 Member Function Documentation

6.7.2.1 DisplayCollection()

```
void ConfigCollection::DisplayCollection (
            std::ostream & OutputStream,
            int Indent = 0) const
```

Output the entire collection to a given output stream.

Parameters

OutputStream	pointer to an outputstream
Indent	indentation level

6.7.2.2 DisplaySetting()

```
void ConfigCollection::DisplaySetting (
            std::ostream & OutputStream,
            int SettingIndex,
            int Indent) const  [private]
```

Output a single setting to the output stream.

Parameters

OutputStream	pointer to an outputstream
SettingIndex	index of the setting to output
Indent	indentation level

6.7.2.3 DisplayTabs()

```
void ConfigCollection::DisplayTabs (
            std::ostream & OutputStream,
            int NrTabs) const  [private]
```

Output a given number of tabs to the output stream.

Parameters

OutputStream	pointer to an outputstream
NrTabs	number of tabs to output

6.7.2.4 Exists()

```
bool ConfigCollection::Exists (
            std::string_view SettingName) const
```

Check if a setting with the given name exists in the collection.

Parameters

SettingName	The name of the setting to check

Returns

true

false

6.7.2.5 GetSettingIndex()

```
int ConfigCollection::GetSettingIndex (
            std::string_view SettingName) const  [private]
```

Return the index of a specific setting in the collection.

Parameters

SettingName	The name of the setting to find

Returns

int

6.7.2.6 IsCollection() [1/2]

```
bool ConfigCollection::IsCollection (
            int SettingIndex) const
```

Check if a setting with the given index is a collection.

Parameters

SettingIndex	The index of the setting to check

Returns

true

false

6.7.2.7 IsCollection() [2/2]

```
bool ConfigCollection::IsCollection (
            std::string_view SettingName) const
```

Check if a setting with the given name is a collection.

Parameters

SettingName	The name of the setting to check

Returns

true

false

6.7.2.8 LookupValue() [1/2]

```
template<class OutputType>
bool ConfigReader::ConfigCollection::LookupValue (
            int SettingIndex,
            OutputType & theOutput) const
```

Looks up the value of a setting with the given index and puts it in the output variable.

Template Parameters

OutputType	

Parameters

SettingIndex	Setting index
theOutput	Pointer to the output variable

Returns

true

false

6.7.2.9 LookupValue() [2/2]

```
template<class OutputType>
bool ConfigReader::ConfigCollection::LookupValue (
            std::string_view SettingName,
            OutputType & theOutput) const
```

Looks up the value of a setting with the given name and puts it in the output variable.

Template Parameters

OutputType	

Parameters

SettingName	Setting name
theOutput	Pointer to the output variable

Returns

true

false

6.7.2.10 LookupValueInteger() [1/7]

```
template<class OutputType>
bool ConfigReader::ConfigCollection::LookupValueInteger (
            int SettingIndex,
            OutputType & theOutput) const
```

This simply defers to the setting-name-based implementation of the function with given output type.

Template Parameters

OutputType	

Parameters

SettingIndex	Setting index
theOutput	Pointer to the output variable

Returns

true

false

6.7.2.11 LookupValueInteger() [2/7]

```
bool ConfigCollection::LookupValueInteger (
            std::string_view SettingName,
            int & theOutput) const
```

If the output is int, we only look up to see if the value is an int.

Parameters

SettingName	Name of the setting to look up
theOutput	integer ouput

Returns

true

false

6.7.2.12 LookupValueInteger() [3/7]

```
bool ConfigCollection::LookupValueInteger (
            std::string_view SettingName,
            long & theOutput) const
```

If the output is long, the setting value can either be a long or an int, so we check for both.

Parameters

SettingName	Name of the setting to look up
theOutput	long output

Returns

true

false

6.7.2.13 LookupValueInteger() [4/7]

```
bool ConfigCollection::LookupValueInteger (
            std::string_view SettingName,
            long long & theOutput) const
```

If the output is long long, the setting value can either be a long long, a long, or an int, so we check for all.

Parameters

SettingName	Name of the setting to look up
theOutput	long long output

Returns

true

false

6.7.2.14 LookupValueInteger() [5/7]

```
bool ConfigCollection::LookupValueInteger (
            std::string_view SettingName,
            unsigned int & theOutput) const
```

If the output is unsigned int, the setting value can either be an unsigned int, an int, a long, or a long long, so we check for all.

Parameters

SettingName	Name of the setting to look up
theOutput	unsigned int output

Returns

true

false

6.7.2.15 LookupValueInteger() [6/7]

```
bool ConfigCollection::LookupValueInteger (
            std::string_view SettingName,
            unsigned long & theOutput) const
```

If the output is unsigned long, the setting value can either be an unsigned long, an unsigned int, an int, a long, or a long long, so we check for all.

Parameters

SettingName	Name of the setting to look up
theOutput	unsigned long output

Returns

true

false

6.7.2.16 LookupValueInteger() [7/7]

```
bool ConfigCollection::LookupValueInteger (
            std::string_view SettingName,
            unsigned long long & theOutput) const
```

If the output is unsigned long long, the setting value can either be an unsigned long long, an unsigned long, an unsigned int, an int, a long, or a long long, so we check for all.

Parameters

SettingName	Name of the setting to look up
theOutput	unsigned long long output

Returns

true

false

6.7.2.17 NrSettings()

```
int ConfigCollection::NrSettings () const
```

Return the total number of settings in the collection.

Returns

int

6.7.2.18 operator[]() [1/2]

```
const ConfigCollection & ConfigCollection::operator[] (
            int CollectionIndex) const
```

Access a subcollection by index.

Parameters

CollectionIndex	The index of the subcollection to access

Returns

const ConfigCollection&

6.7.2.19 operator[]() [2/2]

```
const ConfigCollection & ConfigCollection::operator[] (
            std::string_view CollectionName) const
```

Access a subcollection by name.

Parameters

CollectionName	The name of the subcollection to access

Returns

const ConfigCollection&

6.7.2.20 ReadCollection()

```
void ConfigCollection::ReadCollection (
            std::ifstream & InputFile)  [private]
```

Read in an entire collection (including subcollections). Pre: stream is positioned right after '{' (or at beginning of file). Post: stream is positioned right after '}' (or at EOF).

Parameters

InputFile	pointer to an input file stream

6.7.2.21 ReadFile()

```
bool ConfigCollection::ReadFile (
            const std::string & FileName)
```

Read in a configuration file.

Parameters

FileName	File name of the configuration file

Returns

true if succesful

false if the file does not exist, or if there is a parse/syntax error

6.7.2.22 ReadSettingName()

```
void ConfigCollection::ReadSettingName (
            std::ifstream & InputFile,
            std::string & theName)  [private]
```

Read in a setting name. Pre: next non-whitespace character in stream is beginning of name. Post: stream has just read in all characters of name (but no more); returns "" if there is no more setting to read in the current collection, in this case '}' has been read in (for subcollections).

Parameters

InputFile	Pointer to the input file stream
theName	Pointer to the name of the setting

6.7.2.23 ReadSettingSpecificChar()

```
void ConfigCollection::ReadSettingSpecificChar (
            std::ifstream & InputFile,
            char theChar) const  [private]
```

Read in one specific character only (not '/'). Pre: next non-whitespace character in stream is this character. Post: stream is just after character.

Parameters

InputFile	Pointer to the input file stream
theChar	The character to read in

6.7.2.24 ReadSettingValue()

```
void ConfigCollection::ReadSettingValue (
            std::ifstream & InputFile,
            ConfigSettingValue & theValue)  [private]
```

Read in setting value (could be subcollection). Pre: next non-whitespace character in stream is beginning of value (can be '{' for subcollection, digit or '-' or '.' or 'e' for number, "" for string, or 't'/'f' for boolean). Post: Value has entirely been read in (i.e. next character should be ';').

Parameters

InputFile	Pointer to the input file stream
theValue	Pointer to the setting value

6.7.3 Member Data Documentation

6.7.3.1 m_Settings

```
std::vector<ConfigSetting> ConfigReader::ConfigCollection::m_Settings {}  [private]
```


The documentation for this class was generated from the following files:

- FOORT/src/ConfigReader.h
- FOORT/src/ConfigReader.cpp

6.8 ConfigReader::ConfigReaderException Class Reference

```
#include <ConfigReader.h>
```

Inheritance diagram for ConfigReader::ConfigReaderException:



Public Member Functions

- ConfigReaderException (const std::string &error, std::vector< int > settingtrace={})
- std::vector< int > trace () const

Private Attributes

- std::vector< int > m_settingtrace

6.8.1 Constructor & Destructor Documentation

6.8.1.1 ConfigReaderException()

```
ConfigReader::ConfigReaderException::ConfigReaderException (
            const std::string & error,
            std::vector< int > settingtrace = {})  [inline]
```

6.8.2 Member Function Documentation

6.8.2.1 trace()

```
std::vector< int > ConfigReader::ConfigReaderException::trace () const  [inline]
```

6.8.3 Member Data Documentation

6.8.3.1 m_settingtrace

```
std::vector<int> ConfigReader::ConfigReaderException::m_settingtrace  [private]
```

The documentation for this class was generated from the following file:

- FOORT/src/ConfigReader.h

6.9 ConfigReader::ConfigCollection::ConfigSetting Struct Reference

Public Attributes

- std::string SettingName
- ConfigSettingValue SettingValue

6.9.1 Member Data Documentation

6.9.1.1 SettingName

```
std::string ConfigReader::ConfigCollection::ConfigSetting::SettingName
```

6.9.1.2 SettingValue

```
ConfigSettingValue ConfigReader::ConfigCollection::ConfigSetting::SettingValue
```

The documentation for this struct was generated from the following file:


- FOORT/src/ConfigReader.h

6.10 Diagnostic Class Reference

Abstract base class for all diagnostics.

```
#include <Diagnostics.h>
```

Inheritance diagram for Diagnostic:



Public Member Functions

- Diagnostic ()=delete
- Diagnostic (Geodesic ∗const theGeodesic)
- virtual void Reset ()

  Diagnostic (abstract base class) functions.
- virtual ∼Diagnostic ()=default
- virtual void UpdateData ()=0
- virtual std::string getFullDataStr () const =0
- virtual std::vector< real > getFinalDataVal () const =0
- virtual real FinalDataValDistance (const std::vector< real > &val1, const std::vector< real > &val2) const =0
- virtual std::string getNameStr () const =0
- virtual std::string getFullDescriptionStr () const

  Base class just returns the short name of the Diagnostic.

Protected Member Functions

- bool DecideUpdate (const UpdateFrequency &myUpdateFrequency)

  Returns true if the Diagnostic should update its initial status.

Protected Attributes

- Geodesic ∗const m_OwnerGeodesic
- largecounter m_StepsSinceUpdated {}

6.10.1 Detailed Description

Abstract base class for all diagnostics.

6.10.2 Constructor & Destructor Documentation

6.10.2.1 Diagnostic() [1/2]

```
Diagnostic::Diagnostic ()  [delete]
```

6.10.2.2 Diagnostic() [2/2]

```
Diagnostic::Diagnostic (
            Geodesic *const theGeodesic)  [inline]
```

6.10.2.3 ∼Diagnostic()

```
virtual Diagnostic::~Diagnostic ()  [virtual], [default]
```

6.10.3 Member Function Documentation

6.10.3.1 DecideUpdate()

```
bool Diagnostic::DecideUpdate (
            const UpdateFrequency & myUpdateFrequency)  [protected]
```

Returns true if the Diagnostic should update its initial status.

Should be called from within UpdateData() with the appropriate DiagnosticOptions::theUpdateFrequency.

Parameters

myUpdateFrequency	UpdateFrequency struct

Returns

true

false

6.10.3.2 FinalDataValDistance()

```
virtual real Diagnostic::FinalDataValDistance (
            const std::vector< real > & val1,
            const std::vector< real > & val2) const  [pure virtual]
```

Implemented in ClosestRadiusDiagnostic, EquatorialEmissionDiagnostic, EquatorialPassesDiagnostic, FourColorScreenDiagnostic, and GeodesicPositionDiagnostic.

6.10.3.3 getFinalDataVal()

```
virtual std::vector< real > Diagnostic::getFinalDataVal () const  [pure virtual]
```

Implemented in ClosestRadiusDiagnostic, EquatorialEmissionDiagnostic, EquatorialPassesDiagnostic, FourColorScreenDiagnostic, and GeodesicPositionDiagnostic.

6.10.3.4 getFullDataStr()

```
virtual std::string Diagnostic::getFullDataStr () const  [pure virtual]
```

Implemented in ClosestRadiusDiagnostic, EquatorialEmissionDiagnostic, EquatorialPassesDiagnostic, FourColorScreenDiagnostic, and GeodesicPositionDiagnostic.

6.10.3.5 getFullDescriptionStr()

```
std::string Diagnostic::getFullDescriptionStr () const  [virtual]
```

Base class just returns the short name of the Diagnostic.

This function is pure virtual in the base class.

Returns

std::string

Reimplemented in ClosestRadiusDiagnostic, EquatorialEmissionDiagnostic, EquatorialPassesDiagnostic, FourColorScreenDiagnostic, and GeodesicPositionDiagnostic.

6.10.3.6 getNameStr()

```
virtual std::string Diagnostic::getNameStr () const  [pure virtual]
```

Implemented in ClosestRadiusDiagnostic, EquatorialEmissionDiagnostic, EquatorialPassesDiagnostic, FourColorScreenDiagnostic, and GeodesicPositionDiagnostic.

6.10.3.7 Reset()

```
void Diagnostic::Reset ()  [virtual]
```

Diagnostic (abstract base class) functions.

Reset Diagnostic object steps to zero.

Reimplemented in ClosestRadiusDiagnostic, EquatorialEmissionDiagnostic, EquatorialPassesDiagnostic, FourColorScreenDiagnostic, and GeodesicPositionDiagnostic.

6.10.3.8 UpdateData()

```
virtual void Diagnostic::UpdateData ()  [pure virtual]
```

Implemented in ClosestRadiusDiagnostic, EquatorialEmissionDiagnostic, EquatorialPassesDiagnostic, FourColorScreenDiagnostic, and GeodesicPositionDiagnostic.

6.10.4 Member Data Documentation

6.10.4.1 m_OwnerGeodesic

```
Geodesic* const Diagnostic::m_OwnerGeodesic  [protected]
```

6.10.4.2 m_StepsSinceUpdated

```
largecounter Diagnostic::m_StepsSinceUpdated {}  [protected]
```

The documentation for this class was generated from the following files:


- FOORT/src/Diagnostics.h
- FOORT/src/Diagnostics.cpp

6.11 DiagnosticOptions Struct Reference

Base class for DiagnosticOptions. Other Diagnostics can inherit from here if they require more options.

`#include <Diagnostics.h>`

Inheritance diagram for DiagnosticOptions:



Public Member Functions

- DiagnosticOptions (UpdateFrequency thefrequency)
- virtual ~DiagnosticOptions ()=default

Public Attributes

- const UpdateFrequency theUpdateFrequency

6.11.1 Detailed Description

Base class for DiagnosticOptions. Other Diagnostics can inherit from here if they require more options.

6.11.2 Constructor & Destructor Documentation

6.11.2.1 DiagnosticOptions()

```
DiagnosticOptions::DiagnosticOptions (
            UpdateFrequency thefrequency)  [inline]
```

6.11.2.2 ~DiagnosticOptions()

```
virtual DiagnosticOptions::~DiagnosticOptions ()  [virtual], [default]
```

6.11.3 Member Data Documentation

6.11.3.1 theUpdateFrequency

```
const UpdateFrequency DiagnosticOptions::theUpdateFrequency
```

The documentation for this struct was generated from the following file:


- FOORT/src/Diagnostics.h

6.12 EmissionModel Struct Reference

Emmision model abstract base class.

`#include <DiagnosticsEmission.h>`

Inheritance diagram for EmissionModel:



Public Member Functions

- virtual ~EmissionModel ()=default
- virtual real GetEmission (const Point &p) const =0
- virtual std::string getFullDescriptionStr () const

  Emission model functions.

6.12.1 Detailed Description

Emmision model abstract base class.

6.12.2 Constructor & Destructor Documentation

6.12.2.1 ~EmissionModel()

```
virtual EmissionModel::~EmissionModel ()  [virtual], [default]
```

6.12.3 Member Function Documentation

6.12.3.1 GetEmission()

```
virtual real EmissionModel::GetEmission (
            const Point & p) const  [pure virtual]
```

Implemented in GLMJohnsonSUEmission.

6.12.3.2 getFullDescriptionStr()

```
std::string EmissionModel::getFullDescriptionStr () const  [virtual]
```

Emission model functions.

Base class default string getter

Returns

std::string

Reimplemented in GLMJohnsonSUEmission.

The documentation for this struct was generated from the following files:


- FOORT/src/DiagnosticsEmission.h
- FOORT/src/DiagnosticsEmission.cpp

6.13 EquatorialEmissionDiagnostic Class Reference

Diagnostic that calculates brightness intensity for the geodesic, based on a specified equatorial disc emission model.

```
#include <Diagnostics.h>
```

Inheritance diagram for EquatorialEmissionDiagnostic:



Public Member Functions

- EquatorialEmissionDiagnostic (Geodesic *const theGeodesic)
- void Reset () final

  EquatorialEmissionDiagnostic functions.
- void UpdateData () final

  Update the intensity based on the emission model and the number of equatorial passes.
- std::string getFullDataStr () const final

  Return the intensity and number of equatorial passes as a string.
- std::vector< real > getFinalDataVal () const final

  Return the intensity and number of equatorial passes as a vector of size two.
- real FinalDataValDistance (const std::vector< real > &val1, const std::vector< real > &val2) const final

  Return the distance between two geodesics based on their intensity and number of equatorial passes.
- std::string getNameStr () const final

  Simple name without spaces.
- std::string getFullDescriptionStr () const final

  More descriptive string (with spaces)

Public Member Functions inherited from EquatorialPassesDiagnostic

- EquatorialPassesDiagnostic (Geodesic *const theGeodesic)
- void Reset () override

  EquatorialPassesDiagnostic functions.
- void UpdateData () override

  Check to see if we have crossed the equatorial plane and update the number of passes.
- std::string getFullDataStr () const override

  Return the number of equatorial passes as a string.
- std::vector< real > getFinalDataVal () const override

  Return the number of equatorial passes as a vector of size one.
- real FinalDataValDistance (const std::vector< real > &val1, const std::vector< real > &val2) const override

  Return the absolute value of the difference between the number of equatorial passes.
- std::string getNameStr () const override

  Simple name without spaces.
- std::string getFullDescriptionStr () const override

  More descriptive string (with spaces)

Public Member Functions inherited from Diagnostic

- Diagnostic ()=delete
- Diagnostic (Geodesic *const theGeodesic)
- virtual ~Diagnostic ()=default

Static Public Attributes

- static std::unique_ptr< EquatorialEmissionOptions > DiagOptions

Static Public Attributes inherited from EquatorialPassesDiagnostic

- static std::unique_ptr< EquatorialPassesOptions > DiagOptions

  Needs the extra option of a threshold.

Private Attributes

- real m_Intensity {0.0}

Additional Inherited Members

Protected Member Functions inherited from Diagnostic

- bool DecideUpdate (const UpdateFrequency &myUpdateFrequency)

  Returns true if the Diagnostic should update its initial status.

Protected Attributes inherited from EquatorialPassesDiagnostic

- int m_EquatPasses {0}

  Keeps track of how many passes have been made.

Protected Attributes inherited from Diagnostic

- Geodesic *const m_OwnerGeodesic
- largecounter m_StepsSinceUpdated {}

6.13.1 Detailed Description

Diagnostic that calculates brightness intensity for the geodesic, based on a specified equatorial disc emission model.

Inherits from EquatorialPassesDiagnostic, since it needs to keep track of when it passes through the equatorial plane. As a result it also keeps track of the number of equatorial passes. Both the intensity profile and fluid velocity profile are specified in the options struct.

6.13.2 Constructor & Destructor Documentation

6.13.2.1 EquatorialEmissionDiagnostic()

```
EquatorialEmissionDiagnostic::EquatorialEmissionDiagnostic (
            Geodesic *const theGeodesic)  [inline]
```

6.13.3 Member Function Documentation

6.13.3.1 FinalDataValDistance()

```
real EquatorialEmissionDiagnostic::FinalDataValDistance (
            const std::vector< real > & val1,
            const std::vector< real > & val2) const  [final], [virtual]
```

Return the distance between two geodesics based on their intensity and number of equatorial passes.

Parameters

val1	first geodesic intensity and number of equatorial passes
val2	second geodesic intensity and number of equatorial passes

Returns

real

Implements Diagnostic.

6.13.3.2 getFinalDataVal()

```
std::vector< real > EquatorialEmissionDiagnostic::getFinalDataVal () const  [final], [virtual]
```

Return the intensity and number of equatorial passes as a vector of size two.

Returns

std::vector<real>

Implements Diagnostic.

6.13.3.3 getFullDataStr()

```
std::string EquatorialEmissionDiagnostic::getFullDataStr () const  [final], [virtual]
```

Return the intensity and number of equatorial passes as a string.

Returns

std::string

Implements Diagnostic.

6.13.3.4 getFullDescriptionStr()

```
std::string EquatorialEmissionDiagnostic::getFullDescriptionStr () const  [final], [virtual]
```

More descriptive string (with spaces)

Returns

std::string

Reimplemented from Diagnostic.

6.13.3.5 getNameStr()

```
std::string EquatorialEmissionDiagnostic::getNameStr () const  [final], [virtual]
```

Simple name without spaces.

Returns

std::string

Implements Diagnostic.

6.13.3.6 Reset()

```
void EquatorialEmissionDiagnostic::Reset ()  [final], [virtual]
```

EquatorialEmissionDiagnostic functions.

Reset the intensity and number of equatorial passes to zero and call base class Reset function

Reimplemented from Diagnostic.

6.13.3.7 UpdateData()

```
void EquatorialEmissionDiagnostic::UpdateData ()  [final], [virtual]
```

Update the intensity based on the emission model and the number of equatorial passes.

Implements Diagnostic.

6.13.4 Member Data Documentation

6.13.4.1 DiagOptions

```
std::unique_ptr< EquatorialEmissionOptions > EquatorialEmissionDiagnostic::DiagOptions  [static]
```

6.13.4.2 m_Intensity

```
real EquatorialEmissionDiagnostic::m_Intensity {0.0}  [private]
```

The documentation for this class was generated from the following files:


- FOORT/src/Diagnostics.h
- FOORT/src/Config.cpp
- FOORT/src/Diagnostics.cpp

6.14 EquatorialEmissionOptions Struct Reference

Options for EquatorialEmissionDiagnostic.

```
#include <Diagnostics.h>
```

Inheritance diagram for EquatorialEmissionOptions:



Public Member Functions

- EquatorialEmissionOptions (real thefudgefactor, int equatupper, std::unique_ptr< EmissionModel > theemission, std::unique_ptr< FluidVelocityModel > thefluidmodel, bool rlog, int theredshiftpower, real thethreshold, UpdateFrequency thefrequency)

Public Member Functions inherited from EquatorialPassesOptions

- EquatorialPassesOptions (real thethreshold, UpdateFrequency thefrequency)

Public Member Functions inherited from DiagnosticOptions

- DiagnosticOptions (UpdateFrequency thefrequency)
- virtual ~DiagnosticOptions ()=default

Public Attributes

- const real GeometricFudgeFactor
- const int EquatPassUpperBound
- const bool RLogScale
- const int RedShiftPower
- const std::unique_ptr< EmissionModel > TheEmissionModel
- const std::unique_ptr< FluidVelocityModel > TheFluidVelocityModel

Public Attributes inherited from EquatorialPassesOptions

- const real Threshold

Public Attributes inherited from DiagnosticOptions

- const UpdateFrequency theUpdateFrequency

6.14.1 Detailed Description

Options for EquatorialEmissionDiagnostic.

Inherits from EquatorialPassesOptions, and adds the fudge factor, upper bound, emission model, fluid velocity model, redshift power, and threshold.

6.14.2 Constructor & Destructor Documentation

6.14.2.1 EquatorialEmissionOptions()

```
EquatorialEmissionOptions::EquatorialEmissionOptions (
            real thefudgefactor,
            int equatupper,
            std::unique_ptr< EmissionModel > theemission,
            std::unique_ptr< FluidVelocityModel > thefluidmodel,
            bool rlog,
            int theredshiftpower,
            real thethreshold,
            UpdateFrequency thefrequency)  [inline]
```

6.14.3 Member Data Documentation

6.14.3.1 EquatPassUpperBound

```
const int EquatorialEmissionOptions::EquatPassUpperBound
```

6.14.3.2 GeometricFudgeFactor

```
const real EquatorialEmissionOptions::GeometricFudgeFactor
```

6.14.3.3 RedShiftPower

```
const int EquatorialEmissionOptions::RedShiftPower
```

6.14.3.4 RLogScale

```
const bool EquatorialEmissionOptions::RLogScale
```

6.14.3.5 TheEmissionModel

```
const std::unique_ptr<EmissionModel> EquatorialEmissionOptions::TheEmissionModel
```

6.14.3.6 TheFluidVelocityModel

```
const std::unique_ptr<FluidVelocityModel> EquatorialEmissionOptions::TheFluidVelocityModel
```

The documentation for this struct was generated from the following file:


- FOORT/src/Diagnostics.h

6.15 EquatorialPassesDiagnostic Class Reference

Diagnostic that counts the number of passes through the equatorial plane.

```
#include <Diagnostics.h>
```

Inheritance diagram for EquatorialPassesDiagnostic:



Public Member Functions

- EquatorialPassesDiagnostic (Geodesic ∗const theGeodesic)
- void Reset () override

  EquatorialPassesDiagnostic functions.
- void UpdateData () override

  Check to see if we have crossed the equatorial plane and update the number of passes.
- std::string getFullDataStr () const override

  Return the number of equatorial passes as a string.
- std::vector< real > getFinalDataVal () const override

  Return the number of equatorial passes as a vector of size one.
- real FinalDataValDistance (const std::vector< real > &val1, const std::vector< real > &val2) const override

  Return the absolute value of the difference between the number of equatorial passes.
- std::string getNameStr () const override

  Simple name without spaces.
- std::string getFullDescriptionStr () const override

  More descriptive string (with spaces)

Public Member Functions inherited from Diagnostic

- Diagnostic ()=delete
- Diagnostic (Geodesic ∗const theGeodesic)
- virtual ∼Diagnostic ()=default

Static Public Attributes

- static std::unique_ptr< EquatorialPassesOptions > DiagOptions

  Needs the extra option of a threshold.

Protected Attributes

- int m_EquatPasses {0}

  Keeps track of how many passes have been made.

Protected Attributes inherited from Diagnostic

- Geodesic ∗const m_OwnerGeodesic
- largecounter m_StepsSinceUpdated {}

Private Attributes

- real m_PrevTheta {-1}

  Keeps track of the previous theta angle, so that we can compare with current theta angle.

Additional Inherited Members

Protected Member Functions inherited from Diagnostic

- bool DecideUpdate (const UpdateFrequency &myUpdateFrequency)

  Returns true if the Diagnostic should update its initial status.

6.15.1 Detailed Description

Diagnostic that counts the number of passes through the equatorial plane.

6.15.2 Constructor & Destructor Documentation

6.15.2.1 EquatorialPassesDiagnostic()

```
EquatorialPassesDiagnostic::EquatorialPassesDiagnostic (
            Geodesic *const theGeodesic)  [inline]
```

6.15.3 Member Function Documentation

6.15.3.1 FinalDataValDistance()

```
real EquatorialPassesDiagnostic::FinalDataValDistance (
            const std::vector< real > & val1,
            const std::vector< real > & val2) const  [override], [virtual]
```

Return the absolute value of the difference between the number of equatorial passes.

Parameters

val1	first number of equatorial passes
val2	second number of equatorial passes

Returns

real

Implements Diagnostic.

6.15.3.2 getFinalDataVal()

```
std::vector< real > EquatorialPassesDiagnostic::getFinalDataVal () const  [override], [virtual]
```

Return the number of equatorial passes as a vector of size one.

Returns

std::vector<real>

Implements Diagnostic.

6.15.3.3 getFullDataStr()

```
std::string EquatorialPassesDiagnostic::getFullDataStr () const  [override], [virtual]
```

Return the number of equatorial passes as a string.

Returns

std::string

Implements Diagnostic.

6.15.3.4 getFullDescriptionStr()

```
std::string EquatorialPassesDiagnostic::getFullDescriptionStr () const  [override], [virtual]
```

More descriptive string (with spaces)

Returns

std::string

Reimplemented from Diagnostic.

6.15.3.5 getNameStr()

```
std::string EquatorialPassesDiagnostic::getNameStr () const  [override], [virtual]
```

Simple name without spaces.

Returns

std::string

Implements Diagnostic.

6.15.3.6 Reset()

```
void EquatorialPassesDiagnostic::Reset ()  [override], [virtual]
```

EquatorialPassesDiagnostic functions.

Reset the number of equatorial passes and the previous theta angle and call base class Reset function

Reimplemented from Diagnostic.

6.15.3.7 UpdateData()

```
void EquatorialPassesDiagnostic::UpdateData ()  [override], [virtual]
```

Check to see if we have crossed the equatorial plane and update the number of passes.

Implements Diagnostic.

6.15.4 Member Data Documentation

6.15.4.1 DiagOptions

```
std::unique_ptr< EquatorialPassesOptions > EquatorialPassesDiagnostic::DiagOptions  [static]
```

Needs the extra option of a threshold.

6.15.4.2 m_EquatPasses

```
int EquatorialPassesDiagnostic::m_EquatPasses {0}  [protected]
```

Keeps track of how many passes have been made.

6.15.4.3 m_PrevTheta

```
real EquatorialPassesDiagnostic::m_PrevTheta {-1}  [private]
```

Keeps track of the previous theta angle, so that we can compare with current theta angle.

The documentation for this class was generated from the following files:


- FOORT/src/Diagnostics.h
- FOORT/src/Config.cpp
- FOORT/src/Diagnostics.cpp

6.16 EquatorialPassesOptions Struct Reference

Options for EquatorialPassesDiagnostic.

```
#include <Diagnostics.h>
```

Inheritance diagram for EquatorialPassesOptions:



Public Member Functions

- EquatorialPassesOptions (real thethreshold, UpdateFrequency thefrequency)

Public Member Functions inherited from DiagnosticOptions

- DiagnosticOptions (UpdateFrequency thefrequency)
- virtual ~DiagnosticOptions ()=default

Public Attributes

- const real Threshold

Public Attributes inherited from DiagnosticOptions

- const UpdateFrequency theUpdateFrequency

6.16.1 Detailed Description

Options for EquatorialPassesDiagnostic.

Inherits from DiagnosticOptions, and adds the threshold for counting passes.

6.16.2 Constructor & Destructor Documentation

6.16.2.1 EquatorialPassesOptions()

```
EquatorialPassesOptions::EquatorialPassesOptions (
            real thethreshold,
            UpdateFrequency thefrequency)  [inline]
```

6.16.3 Member Data Documentation

6.16.3.1 Threshold

```
const real EquatorialPassesOptions::Threshold
```

The documentation for this struct was generated from the following file:


- FOORT/src/Diagnostics.h

6.17 FlatSpaceMetric Class Reference

Flat space metric in 4D.

`#include <Metric.h>`

Inheritance diagram for FlatSpaceMetric:



Public Member Functions

- FlatSpaceMetric (bool rlogscale=false)

  Construct a new Flat Space Metric object.
- TwoIndex getMetric_dd (const Point &p) const final

  Flat metric getter, indices down.
- TwoIndex getMetric_uu (const Point &p) const final

  Flat metric getter, indices up.
- std::string getFullDescriptionStr () const final

  Flat metric description string getter.

Public Member Functions inherited from Metric

- virtual ~Metric ()=default
- Metric (bool rlogscale=false)

  Construct a new Metric object.
- virtual ThreeIndex getChristoffel_udd (const Point &p) const

  Return the Christoffel symbols of the metric (indices up, down, down)
- virtual FourIndex getRiemann_uddd (const Point &p) const

  Riemann tensor of the metric (indices up, down, down, down)
- virtual real getKretschmann (const Point &p) const

  Get the Kretschmann scalar at a point.
- bool getrLogScale () const

  Get whether we are using a logarithmic radial scale.

Additional Inherited Members

Protected Attributes inherited from Metric

- std::vector< int > m_Symmetries {}

  The symmetries (coordinate Killing vectors) of the metric. Should be set by descendant constructor.
- const bool m_rLogScale

  Are we using a logarithmic r coordinate?

6.17.1 Detailed Description

Flat space metric in 4D.

6.17.2 Constructor & Destructor Documentation

6.17.2.1 FlatSpaceMetric()

```
FlatSpaceMetric::FlatSpaceMetric (
            bool rlogscale = false)
```

Construct a new Flat Space Metric object.

Parameters

rlogscale	

6.17.3 Member Function Documentation

6.17.3.1 getFullDescriptionStr()

```
std::string FlatSpaceMetric::getFullDescriptionStr () const  [final], [virtual]
```

Flat metric description string getter.

Returns

std::string

Reimplemented from Metric.

6.17.3.2 getMetric_dd()

```
TwoIndex FlatSpaceMetric::getMetric_dd (
            const Point & p) const  [final], [virtual]
```

Flat metric getter, indices down.

Parameters

p	Point at which to evaluate the metric

Returns

TwoIndex

Implements Metric.

6.17.3.3 getMetric_uu()

```
TwoIndex FlatSpaceMetric::getMetric_uu (
            const Point & p) const  [final], [virtual]
```

Flat metric getter, indices up.

Parameters

p	Point at which to evaluate the metric

Returns

TwoIndex

Implements Metric.

The documentation for this class was generated from the following files:


- FOORT/src/Metric.h
- FOORT/src/Metric.cpp

6.18 FluidVelocityModel Struct Reference

Fluid velocity model abstract base class.

`#include <DiagnosticsEmission.h>`

Inheritance diagram for FluidVelocityModel:



Public Member Functions

- FluidVelocityModel (const Metric *const theMetric)
- virtual ~FluidVelocityModel ()=default
- virtual OneIndex GetFourVelocityd (const Point &p) const =0
- virtual std::string getFullDescriptionStr () const

  Base class default string getter.

Protected Attributes

- const Metric *const m_theMetric

6.18.1 Detailed Description

Fluid velocity model abstract base class.

6.18.2 Constructor & Destructor Documentation

6.18.2.1 FluidVelocityModel()

```
FluidVelocityModel::FluidVelocityModel (
            const Metric *const theMetric)  [inline]
```

6.18.2.2 ~FluidVelocityModel()

```
virtual FluidVelocityModel::~FluidVelocityModel ()  [virtual], [default]
```

6.18.3 Member Function Documentation

6.18.3.1 GetFourVelocityd()

```
virtual OneIndex FluidVelocityModel::GetFourVelocityd (
            const Point & p) const  [pure virtual]
```

Implemented in GeneralCircularRadialFluid.

6.18.3.2 getFullDescriptionStr()

```
std::string FluidVelocityModel::getFullDescriptionStr () const  [virtual]
```

Base class default string getter.

Returns

std::string

Reimplemented in GeneralCircularRadialFluid.

6.18.4 Member Data Documentation

6.18.4.1 m_theMetric

```
const Metric* const FluidVelocityModel::m_theMetric  [protected]
```

The documentation for this struct was generated from the following files:


- FOORT/src/DiagnosticsEmission.h
- FOORT/src/DiagnosticsEmission.cpp

6.19 FourColorScreenDiagnostic Class Reference

The four color screen diagnostic.

`#include <Diagnostics.h>`

Inheritance diagram for FourColorScreenDiagnostic:



Public Member Functions

- FourColorScreenDiagnostic (Geodesic *const theGeodesic)
- void Reset () final

  FourColorScreen functions.
- void UpdateData () override

  Update the quadrant based on the geodesic's final position.
- std::string getFullDataStr () const final

  Return the value of the quadrant as a string.
- std::vector< real > getFinalDataVal () const final

  Return the value of the quadrant as a vector of size one.
- real FinalDataValDistance (const std::vector< real > &val1, const std::vector< real > &val2) const final

  Discrete metric for distance: return 0 if the quadrants are the same, 1 if they are not.
- std::string getNameStr () const final

  Simple name without spaces.
- std::string getFullDescriptionStr () const final

  Return full name, possibly with spaces.

Public Member Functions inherited from Diagnostic

- Diagnostic ()=delete
- Diagnostic (Geodesic *const theGeodesic)
- virtual ~Diagnostic ()=default

Private Attributes

- int m_quadrant {0}

  Note initialization to 0; this means the default value returned will be 0 (e.g. if Term::BoundarySphere is not reached)

Additional Inherited Members

Protected Member Functions inherited from Diagnostic

- bool DecideUpdate (const UpdateFrequency &myUpdateFrequency)

  Returns true if the Diagnostic should update its initial status.

Protected Attributes inherited from Diagnostic

- Geodesic *const m_OwnerGeodesic
- largecounter m_StepsSinceUpdated {}

6.19.1 Detailed Description

The four color screen diagnostic.

This diagnostic associates one of four colors based on the quadrant that the geodesic finishes in. Will ONLY return a color if the geodesic indeed finishes because it passes through the boundary sphere!

6.19.2 Constructor & Destructor Documentation

6.19.2.1 FourColorScreenDiagnostic()

```
FourColorScreenDiagnostic::FourColorScreenDiagnostic (
            Geodesic *const theGeodesic)  [inline]
```

6.19.3 Member Function Documentation

6.19.3.1 FinalDataValDistance()

```
real FourColorScreenDiagnostic::FinalDataValDistance (
            const std::vector< real > & val1,
            const std::vector< real > & val2) const  [final], [virtual]
```

Discrete metric for distance: return 0 if the quadrants are the same, 1 if they are not.

Parameters

val1	first quadrant value
val2	second quadrant value

Returns

real

Implements Diagnostic.

6.19.3.2 getFinalDataVal()

```
std::vector< real > FourColorScreenDiagnostic::getFinalDataVal () const  [final], [virtual]
```

Return the value of the quadrant as a vector of size one.

Returns

std::vector<real>

Implements Diagnostic.

6.19.3.3 getFullDataStr()

```
std::string FourColorScreenDiagnostic::getFullDataStr () const  [final], [virtual]
```

Return the value of the quadrant as a string.

Returns

std::string

Implements Diagnostic.

6.19.3.4 getFullDescriptionStr()

```
std::string FourColorScreenDiagnostic::getFullDescriptionStr () const  [final], [virtual]
```

Return full name, possibly with spaces.

Returns

std::string

Reimplemented from Diagnostic.

6.19.3.5 getNameStr()

```
std::string FourColorScreenDiagnostic::getNameStr () const  [final], [virtual]
```

Simple name without spaces.

Returns

std::string

Implements Diagnostic.

6.19.3.6 Reset()

```
void FourColorScreenDiagnostic::Reset ()  [final], [virtual]
```

FourColorScreen functions.

Reset the quadrant to its default option; also call base class Reset function

Reimplemented from Diagnostic.

6.19.3.7 UpdateData()

```
void FourColorScreenDiagnostic::UpdateData ()  [override], [virtual]
```

Update the quadrant based on the geodesic's final position.

Implements Diagnostic.

6.19.4 Member Data Documentation

6.19.4.1 m_quadrant

```
int FourColorScreenDiagnostic::m_quadrant {0}  [private]
```

Note initialization to 0; this means the default value returned will be 0 (e.g. if Term::BoundarySphere is not reached)

The documentation for this class was generated from the following files:


- FOORT/src/Diagnostics.h
- FOORT/src/Diagnostics.cpp

6.20 GeneralCircularRadialFluid Struct Reference

General circular radial fluid velocity model.

```
#include <DiagnosticsEmission.h>
```

Inheritance diagram for GeneralCircularRadialFluid:



Public Member Functions

- GeneralCircularRadialFluid (real subKeplerParam, real betar, real betaphi, const Metric *const theMetric, real ISCO_lowerbound, real ISCO_upperbound)
- OneIndex GetFourVelocityd (const Point &p) const final

  Get the local four-velocity of the fluid according to the GeneralCircularRadial model.
- std::string getFullDescriptionStr () const final

  Description string getter for the GeneralCircularRadial fluid velocity model.

Public Member Functions inherited from FluidVelocityModel

- FluidVelocityModel (const Metric *const theMetric)
- virtual ~FluidVelocityModel ()=default

Private Member Functions

- OneIndex GetCircularVelocityd (const Point &p, bool subKeplerianOn=true) const

  Get the circular velocity for a point, with optional subKeplerian rescaling.
- OneIndex GetInsideISCOCircularVelocityd (const Point &p) const

  Returns velocity for non-geodetic motion where E,L = (E,L)_ISCO and radially falling inward.
- OneIndex GetRadialVelocityd (const Point &p) const

  Returns radial velocity for pure infalling matter with E = 1 and L = 0 at infinity.
- void FindISCO ()

  Helper function to find the ISCO of the spacetime, if it exists.
- TwoIndex GetChristrRaisedDer (real r) const

  Helper function to get \partial_r(g^{ab}\Gamma^r_{bc}g^{cd})
- void WarnOnce (std::atomic< bool > &flag, const std::string &msg, const Point &p) const

Private Attributes

- const real m_subKeplerParam

  Sub-Keplerian parameter (1 = Keplerian)
- const real m_betaR

  Radial velocity parameter.
- const real m_betaPhi

  Azimuthal velocity parameter.
- bool m_ISCOexists {false}

  Flag to indicate if ISCO exists for this Metric.
- real m_ISCOr {-1.0}

  ISCO radius.
- real m_ISCOlowerbound

  Lower bound for ISCO radius search.
- real m_ISCOupperbound

  Upper bound for ISCO radius search.
- real m_ISCOpt {}

  ISCO t momentum.
- real m_ISCOpphi {}

  ISCO phi momentum.
- std::atomic< bool > m_WarnedNoCircular {false}
- std::atomic< bool > m_WarnedNormalization {false}
- std::atomic< bool > m_WarnedNaN {false}
- std::atomic< bool > m_WarnedInsideISCO {false}
- std::atomic< bool > m_WarnedSubkeplerianRescaling {false}

Additional Inherited Members

Protected Attributes inherited from FluidVelocityModel

- const Metric *const m_theMetric

6.20.1 Detailed Description

General circular radial fluid velocity model.

This fluid velocity model has three tuneable parameters and represents fluid travelling at a mix of (sub)Keplerian circular orbits and radially infalling orbits in the equatorial plane. Details can be found in e.g. https://doi.org/10.1103/PhysRevD.107.043030 .

6.20.2 Constructor & Destructor Documentation

6.20.2.1 GeneralCircularRadialFluid()

```
GeneralCircularRadialFluid::GeneralCircularRadialFluid (
            real subKeplerParam,
            real betar,
            real betaphi,
            const Metric *const theMetric,
            real ISCO_lowerbound,
            real ISCO_upperbound)  [inline]
```

6.20.3 Member Function Documentation

6.20.3.1 FindISCO()

```
void GeneralCircularRadialFluid::FindISCO ()  [private]
```

Helper function to find the ISCO of the spacetime, if it exists.

This helper function finds the ISCO. We use a binary search to converge on the ISCO value between the search bounds m_ISCOlowerbound and m_ISCOupperbound (true radii, not log(r) coordinates; set via ISCOLowerBound/ISCOUpperBound, see Config.cpp for the defaults). A warning is issued if the resulting ISCO lies within 1% of the search interval of either bound, since the search then likely converged onto the bound rather than onto the true ISCO.

6.20.3.2 GetChristrRaisedDer()

```
TwoIndex GeneralCircularRadialFluid::GetChristrRaisedDer (
            real r) const  [private]
```

Helper function to get \partial_r(g^{ab}\Gamma^r_{bc}g^{cd})

This function calculates \partial_r(g^ { ab }\Gamma ^ r_{ bc }g^ { cd }). We do so by calculating the central difference with O(h^4) accuracy, but taking the sqrt of the usual h used for derivatives

Parameters

r	Radius at which to calculate the derivative

Returns

TwoIndex

6.20.3.3 GetCircularVelocityd()

```
OneIndex GeneralCircularRadialFluid::GetCircularVelocityd (
            const Point & p,
            bool subKeplerianOn = true) const  [private]
```

Get the circular velocity for a point, with optional subKeplerian rescaling.

Returns the velocity for circular (sub)Keplerian motion (outside the ISCO). First the circular geodesic is calculated, then if subKeplerianOn == true, the orbit is reparametrized to non-geodetic subKeplerian circular motion according to the subKeplerian parameter

Parameters

p	Point at which to calculate the velocity
subKeplerianOn	Boolean to indicate whether to rescale the angular momentum for sub-Keplerian motion

Returns

OneIndex circular velocity with index down. If no solution, returns all zeros

6.20.3.4 GetFourVelocityd()

```
OneIndex GeneralCircularRadialFluid::GetFourVelocityd (
            const Point & p) const  [final], [virtual]
```

Get the local four-velocity of the fluid according to the GeneralCircularRadial model.

Parameters

p	Point at which to calculate the four-velocity

Returns

OneIndex Local four-velocity with index down

Implements FluidVelocityModel.

6.20.3.5 getFullDescriptionStr()

```
std::string GeneralCircularRadialFluid::getFullDescriptionStr () const  [final], [virtual]
```

Description string getter for the GeneralCircularRadial fluid velocity model.

Returns

std::string

Reimplemented from FluidVelocityModel.

6.20.3.6 GetInsideISCOCircularVelocityd()

```
OneIndex GeneralCircularRadialFluid::GetInsideISCOCircularVelocityd (
            const Point & p) const  [private]
```

Returns velocity for non-geodetic motion where E,L = (E,L)_ISCO and radially falling inward.

Parameters

p	Point at which to calculate the velocity

Returns

OneIndex

6.20.3.7 GetRadialVelocityd()

```
OneIndex GeneralCircularRadialFluid::GetRadialVelocityd (
            const Point & p) const  [private]
```

Returns radial velocity for pure infalling matter with E = 1 and L = 0 at infinity.

Parameters

p	Point at which to calculate the velocity

Returns

OneIndex

6.20.3.8 WarnOnce()

```
void GeneralCircularRadialFluid::WarnOnce (
            std::atomic< bool > & flag,
            const std::string & msg,
            const Point & p) const  [private]
```

6.20.4 Member Data Documentation

6.20.4.1 m_betaPhi

```
const real GeneralCircularRadialFluid::m_betaPhi  [private]
```

Azimuthal velocity parameter.

6.20.4.2 m_betaR

```
const real GeneralCircularRadialFluid::m_betaR  [private]
```

Radial velocity parameter.

6.20.4.3 m_ISCOexists

```
bool GeneralCircularRadialFluid::m_ISCOexists {false}  [private]
```

Flag to indicate if ISCO exists for this Metric.

6.20.4.4 m_ISCOlowerbound

```
real GeneralCircularRadialFluid::m_ISCOlowerbound  [private]
```

Lower bound for ISCO radius search.

6.20.4.5 m_ISCOpphi

```
real GeneralCircularRadialFluid::m_ISCOpphi {}  [private]
```

ISCO phi momentum.

6.20.4.6 m_ISCOpt

```
real GeneralCircularRadialFluid::m_ISCOpt {}  [private]
```

ISCO t momentum.

6.20.4.7 m_ISCOr

```
real GeneralCircularRadialFluid::m_ISCOr {-1.0}  [private]
```

ISCO radius.

6.20.4.8 m_ISCOupperbound

```
real GeneralCircularRadialFluid::m_ISCOupperbound  [private]
```

Upper bound for ISCO radius search.

6.20.4.9 m_subKeplerParam

```
const real GeneralCircularRadialFluid::m_subKeplerParam  [private]
```

Sub-Keplerian parameter (1 = Keplerian)

6.20.4.10 m_WarnedInsideISCO

```
std::atomic<bool> GeneralCircularRadialFluid::m_WarnedInsideISCO {false}  [mutable], [private]
```

6.20.4.11 m_WarnedNaN

```
std::atomic<bool> GeneralCircularRadialFluid::m_WarnedNaN {false}  [mutable], [private]
```

6.20.4.12 m_WarnedNoCircular

```
std::atomic<bool> GeneralCircularRadialFluid::m_WarnedNoCircular {false}  [mutable], [private]
```

6.20.4.13 m_WarnedNormalization

```
std::atomic<bool> GeneralCircularRadialFluid::m_WarnedNormalization {false}  [mutable], [private]
```

6.20.4.14 m_WarnedSubkeplerianRescaling

```
std::atomic<bool> GeneralCircularRadialFluid::m_WarnedSubkeplerianRescaling {false}  [mutable],
[private]
```

The documentation for this struct was generated from the following files:


- FOORT/src/DiagnosticsEmission.h
- FOORT/src/DiagnosticsEmission.cpp

6.21 GeneralSingularityTermination Class Reference

GeneralSingularityTermination: Terminate geodesics if they get too close to one of a number of singularities (of arbitrary codimension)

```
#include <Terminations.h>
```

Inheritance diagram for GeneralSingularityTermination:



Public Member Functions

- GeneralSingularityTermination (Geodesic *const theGeodesic)
- Term CheckTermination () final

  Check if the geodesic is too close to a singularity.
- std::string getFullDescriptionStr () const final

  Description string getter for the General Singularity Termination.

Public Member Functions inherited from Termination

- Termination ()=delete
- Termination (Geodesic ∗const theGeodesic)
- virtual void Reset ()

  Reset to 0 to start integrating a new geodesic.
- virtual ∼Termination ()=default

Static Public Attributes

- static std::unique_ptr< GeneralSingularityTermOptions > TermOptions

  Options (contains horizon radius, if we are using logarithmic r coordinate, and distance allowed from the horizon)

Private Member Functions

- std::string SingularityToString (int singnr) const

  List the singularities in a human-readable format.

Additional Inherited Members

Protected Member Functions inherited from Termination

- bool DecideUpdate (largecounter UpdateNSteps)

  Returns true if the Termination should update its internal status.

Protected Attributes inherited from Termination

- Geodesic ∗const m_OwnerGeodesic

  The geodesic that owns the Termination (a const pointer to the Geodesic)
- largecounter m_StepsSinceUpdated {}

  The termination is itself in charge of keeping track of how many steps it has been since it has been updated. The Termination's TerminationOptions struct tells it how many steps it needs to wait between updates.

6.21.1 Detailed Description

GeneralSingularityTermination: Terminate geodesics if they get too close to one of a number of singularities (of arbitrary codimension)

6.21.2 Constructor & Destructor Documentation

6.21.2.1 GeneralSingularityTermination()

```
GeneralSingularityTermination::GeneralSingularityTermination (
            Geodesic *const theGeodesic)  [inline]
```

6.21.3 Member Function Documentation

6.21.3.1 CheckTermination()

```
Term GeneralSingularityTermination::CheckTermination ()  [final], [virtual]
```

Check if the geodesic is too close to a singularity.

Returns

Term

Implements Termination.

6.21.3.2 getFullDescriptionStr()

```
std::string GeneralSingularityTermination::getFullDescriptionStr () const  [final], [virtual]
```

Description string getter for the General Singularity Termination.

Returns

std::string

Implements Termination.

6.21.3.3 SingularityToString()

```
std::string GeneralSingularityTermination::SingularityToString (
            int singnr) const  [private]
```

List the singularities in a human-readable format.

Returns

std::string

6.21.4 Member Data Documentation

6.21.4.1 TermOptions

```
std::unique_ptr< GeneralSingularityTermOptions > GeneralSingularityTermination::TermOptions
[static]
```

Options (contains horizon radius, if we are using logarithmic r coordinate, and distance allowed from the horizon)

The documentation for this class was generated from the following files:


- FOORT/src/Terminations.h
- FOORT/src/Config.cpp
- FOORT/src/Terminations.cpp

6.22 GeneralSingularityTermOptions Struct Reference

Options for GeneralSingularityTermination.

`#include <Terminations.h>`

Inheritance diagram for GeneralSingularityTermOptions:



Public Member Functions

- GeneralSingularityTermOptions (std::vector< Singularity > sings, real eps, bool consoleoutputon, bool therlogscale, largecounter Nsteps)

Public Member Functions inherited from TerminationOptions

- TerminationOptions (largecounter Nsteps)
- virtual ~TerminationOptions ()=default

Public Attributes

- const std::vector< Singularity > Singularities

  Vector of singularities.
- const real Epsilon

  Minimum flat distance the geodesic is allowed to be from any singularity.
- const bool OutputToConsole

  Whether to output a message to the console when a singularity is encountered.
- const bool rLogScale

  Whether we are using a logarithmic r coordinate or not.

Public Attributes inherited from TerminationOptions

- const largecounter UpdateEveryNSteps

  Number of steps between updates.

6.22.1 Detailed Description

Options for GeneralSingularityTermination.

Keeps track of the singularities, allowed distance and whether we are using a logarithmic r coordinate.

6.22.2 Constructor & Destructor Documentation

6.22.2.1 GeneralSingularityTermOptions()

```
GeneralSingularityTermOptions::GeneralSingularityTermOptions (
            std::vector< Singularity > sings,
            real eps,
            bool consoleoutputon,
            bool therlogscale,
            largecounter Nsteps)  [inline]
```

6.22.3 Member Data Documentation

6.22.3.1 Epsilon

```
const real GeneralSingularityTermOptions::Epsilon
```

Minimum flat distance the geodesic is allowed to be from any singularity.

6.22.3.2 OutputToConsole

```
const bool GeneralSingularityTermOptions::OutputToConsole
```

Whether to output a message to the console when a singularity is encountered.

6.22.3.3 rLogScale

```
const bool GeneralSingularityTermOptions::rLogScale
```

Whether we are using a logarithmic r coordinate or not.

6.22.3.4 Singularities

```
const std::vector<Singularity> GeneralSingularityTermOptions::Singularities
```

Vector of singularities.

The documentation for this struct was generated from the following file:

- FOORT/src/Terminations.h

6.23 Geodesic Class Reference

Geodesic class: an instance of this class is created for each Geodesic that is integrated.

```
#include <Geodesic.h>
```

Public Member Functions

- Geodesic ()=delete
- Geodesic (const Geodesic &)=delete
- Geodesic & operator= (const Geodesic &)=delete
- Geodesic (const Metric *const theMetric, const Source *const theSource, DiagBitflag diagbit, DiagBitflag valdiagbit, TermBitflag termbit, GeodesicIntegratorFunc theIntegrator)

  Construct a new Geodesic object. Arguments initialize private member variables that remain the same over all geodesics.
- void Reset (ScreenIndex scrindex, Point initpos, OneIndex initvel)

  Geodesic (and descendant classes) functions.
- Term Update ()

  This makes the Geodesic integrate itself one step; then the Geodesic loops through all Terminations and Diagnostics to update.
- Term getTermCondition () const

  Get the current termination condition.
- Point getCurrentPos () const

  Get the current position.
- OneIndex getCurrentVel () const

  Get the current velocity.
- real getCurrentLambda () const

  Get the current value of the affine parameter.
- ScreenIndex getScreenIndex () const

  Get the screen index.
- std::vector< std::string > getAllOutputStr () const

  Get the complete output that should be written to the output files.
- std::vector< real > getDiagnosticFinalValue () const

  Get the "value" (from the Diagnostic that was set to the value Diagnostic) that is associated to the Geodesic.

Private Attributes

- Term m_TermCond {Term::Uninitialized}

  As long as this is Term::Continue, not done integrating yet.
- Point m_CurrentPos {}

  Current position.
- OneIndex m_CurrentVel {}

  Current proper velocity.
- real m_curLambda {0.0}

  Current value of affine parameter (starts at 0.0)
- ScreenIndex m_ScreenIndex {}
- const Metric *const m_theMetric

  const pointer to the Metric
- const Source *const m_theSource

  const pointer to the Source for the rhs of the geodesic equation
- const DiagnosticUniqueVector m_AllDiagnostics

  Vector of unique pointers to Diagnostics. An instance of each Diagnostic is created for the Geodesic, so the Geodesic is the owner of these objects.
- const TerminationUniqueVector m_AllTerminations

  Vector of unique pointers to Terminations. An instance of each Termination is created for the Geodesic, so the Geodesic is the owner of these objects.
- const GeodesicIntegratorFunc m_theIntegrator

  This is the function that will integrate the geodesic equation one step.

6.23.1 Detailed Description

Geodesic class: an instance of this class is created for each Geodesic that is integrated.

The Geodesic is in charge of integrating itself until termination, updating its Diagnostics accordingly, and (after termination) returing the appropriate output

6.23.2 Constructor & Destructor Documentation

6.23.2.1 Geodesic() [1/3]

```
Geodesic::Geodesic ()  [delete]
```

6.23.2.2 Geodesic() [2/3]

```
Geodesic::Geodesic (
            const Geodesic & )  [delete]
```

6.23.2.3 Geodesic() [3/3]

```
Geodesic::Geodesic (
            const Metric *const theMetric,
            const Source *const theSource,
            DiagBitflag diagbit,
            DiagBitflag valdiagbit,
            TermBitflag termbit,
            GeodesicIntegratorFunc theIntegrator)  [inline]
```

Construct a new Geodesic object. Arguments initialize private member variables that remain the same over all geodesics.

Parameters

theMetric	Pointer to the Metric object.
theSource	Pointer to the Source object.
diagbit	Diagnostic bitflag.
valdiagbit	Value diagnostic bitflag.
termbit	Termination bitflag.
theIntegrator	Geoedesic integrator function to use for integrating geodesic equation.

6.23.3 Member Function Documentation

6.23.3.1 getAllOutputStr()

```
std::vector< std::string > Geodesic::getAllOutputStr () const
```

Get the complete output that should be written to the output files.

There is one string more than the count of Diagnostics: one string per Diagnostic, PLUS the first string is the screen index.

Returns

std::vector<std::string>

6.23.3.2 getCurrentLambda()

```
real Geodesic::getCurrentLambda () const
```

Get the current value of the affine parameter.

Returns

real

6.23.3.3 getCurrentPos()

```
Point Geodesic::getCurrentPos () const
```

Get the current position.

Returns

Point

6.23.3.4 getCurrentVel()

```
OneIndex Geodesic::getCurrentVel () const
```

Get the current velocity.

Returns

OneIndex

6.23.3.5 getDiagnosticFinalValue()

```
std::vector< real > Geodesic::getDiagnosticFinalValue () const
```

Get the "value" (from the Diagnostic that was set to the value Diagnostic) that is associated to the Geodesic.

Will be used to determine "distance" between Geodesics which is used in Mesh refinement.

Returns

std::vector<real>

6.23.3.6 getScreenIndex()

```
ScreenIndex Geodesic::getScreenIndex () const
```

Get the screen index.

Returns

ScreenIndex

6.23.3.7 getTermCondition()

```
Term Geodesic::getTermCondition () const
```

Get the current termination condition.

Returns

Term

6.23.3.8 operator=()

```
Geodesic & Geodesic::operator= (
            const Geodesic & )  [delete]
```

6.23.3.9 Reset()

```
void Geodesic::Reset (
            ScreenIndex scrindex,
            Point initpos,
            OneIndex initvel)
```

Geodesic (and descendant classes) functions.

This initializes/resets the geodesic with a given ScreenIndex, initial position, and initial velocity

Also resets all Diagnostics and Terminations, resets the TermCondition to Term::Continue, and puts the Geodesic back to lambda = 0.0.

Parameters

scrindex	ScreenIndex
initpos	Initial position
initvel	Initial velocity

6.23.3.10 Update()

```
Term Geodesic::Update ()
```

This makes the Geodesic integrate itself one step; then the Geodesic loops through all Terminations and Diagnostics to update.

Returns

Term

6.23.4 Member Data Documentation

6.23.4.1 m_AllDiagnostics

```
const DiagnosticUniqueVector Geodesic::m_AllDiagnostics  [private]
```

Vector of unique pointers to Diagnostics. An instance of each Diagnostic is created for the Geodesic, so the Geodesic is the owner of these objects.

6.23.4.2 m_AllTerminations

```
const TerminationUniqueVector Geodesic::m_AllTerminations  [private]
```

Vector of unique pointers to Terminations. An instance of each Termination is created for the Geodesic, so the Geodesic is the owner of these objects.

6.23.4.3 m_curLambda

```
real Geodesic::m_curLambda {0.0}  [private]
```

Current value of affine parameter (starts at 0.0)

6.23.4.4 m_CurrentPos

```
Point Geodesic::m_CurrentPos {}  [private]
```

Current position.

6.23.4.5 m_CurrentVel

```
OneIndex Geodesic::m_CurrentVel {}  [private]
```

Current proper velocity.

6.23.4.6 m_ScreenIndex

```
ScreenIndex Geodesic::m_ScreenIndex {}  [private]
```

The Geodesic keeps track of what index it has been assigned; it outputs this information in its final output string

6.23.4.7 m_TermCond

```
Term Geodesic::m_TermCond {Term::Uninitialized}  [private]
```

As long as this is Term::Continue, not done integrating yet.

6.23.4.8 m_theIntegrator

```
const GeodesicIntegratorFunc Geodesic::m_theIntegrator  [private]
```

This is the function that will integrate the geodesic equation one step.

6.23.4.9 m_theMetric

```
const Metric* const Geodesic::m_theMetric  [private]
```

const pointer to the Metric

6.23.4.10 m_theSource

```
const Source* const Geodesic::m_theSource  [private]
```

const pointer to the Source for the rhs of the geodesic equation

The documentation for this class was generated from the following files:

- FOORT/src/Geodesic.h
- FOORT/src/Geodesic.cpp

6.24 GeodesicOutputHandler Class Reference

// GeodesicOutputHandler handles all of the output to file. It gets passed all of the output strings for every Geodesic, it then stores this data until it eventually writes all data to the appropriate files

```
#include <InputOutput.h>
```

Public Member Functions

- GeodesicOutputHandler ()=delete
- GeodesicOutputHandler (std::string FilePrefix, std::string TimeStamp, std::string FileExtension, std::vector< std::string > DiagNames, largecounter nroutputstocache=LARGECOUNTER_MAX - 1, largecounter geodperfile=LARGECOUNTER_MAX, std::string firstlineinfo="")

  Construct a new Geodesic Output Handler object and initialize all const member variables.
- void PrepareForOutput (largecounter nrOutputToCome)

  prepare the cache for output
- void NewGeodesicOutput (largecounter index, std::vector< std::string > theOutput)
- void OutputFinished ()

  There is no more output, so we write anything that is cached to file to clean up and finalize.
- std::string getFullDescriptionStr () const

  full description string getter for the geodesic output handler

Private Member Functions

- void WriteCachedOutputToFile ()

  Write cached output to a file.
- void OpenForFirstTime (const std::string &filename)

  We check here to see if the files are being put in a (sub)directory; if so, we create the directory/directories first to make sure creating/opening the file will succeed.
- std::string GetFileName (int diagnr, unsigned short filenr) const

  Get the file name based on the various parts of the file name stored in the member variables.

Private Attributes

- const std::string m_FilePrefix

  Const string for file prefix.
- const std::string m_TimeStamp

  Const string for timestamp.
- const std::string m_FileExtension

  Const string for file extension.
- const std::vector< std::string > m_DiagNames

  Const string for the diagnostic names.
- const bool m_PrintFirstLineInfo

  Const variable that control whether we write a descriptive first line in every output file or not.
- const std::string m_FirstLineInfoString

  Const string for the first line info.
- const largecounter m_nrOutputsToCache {}
- const largecounter m_nrGeodesicsPerFile {}

  Const setting the max number of geodesics per file.
- bool m_WriteToConsole {false}

  If this is false, then we are writing to file(s). At any time, if a file I/O error occurs, the output handler switches to outputting everything to the console.
- largecounter m_PrevCached {0}

  How many outputs are already cached in m_nrOutputsToCache before the current iteration of output.
- largecounter m_CurrentGeodesicsInFile {0}

  The number of geodesics already written to the current file (once this hits m_nrGeodesicsPerFile, this file is full)
- unsigned short m_CurrentFullFiles {0}

  The current counter of completely full files (this is kept track of so that it knows what the next file to write output to is). (We had better not have more than 60k files!)
- std::vector< std::vector< std::string > > m_AllCachedData {}

  Cached data that has not been written to a file yet (once this hits a size of > m_nrOutputsToCache, this must be written to file(s))

6.24.1 Detailed Description

// GeodesicOutputHandler handles all of the output to file. It gets passed all of the output strings for every Geodesic, it then stores this data until it eventually writes all data to the appropriate files

6.24.2 Constructor & Destructor Documentation

6.24.2.1 GeodesicOutputHandler() [1/2]

```
GeodesicOutputHandler::GeodesicOutputHandler ()  [delete]
```

6.24.2.2 GeodesicOutputHandler() [2/2]

```
GeodesicOutputHandler::GeodesicOutputHandler (
            std::string FilePrefix,
            std::string TimeStamp,
            std::string FileExtension,
            std::vector< std::string > DiagNames,
            largecounter nroutputstocache = LARGECOUNTER_MAX - 1,
            largecounter geodperfile = LARGECOUNTER_MAX,
            std::string firstlineinfo = "")
```

Construct a new Geodesic Output Handler object and initialize all const member variables.

Parameters

FilePrefix	file prefix
TimeStamp	time stamp
FileExtension	file extensions
DiagNames	diagnostics names
nroutputstocache	number of geodesics to put to the cache
geodperfile	max number of geodesics per output file
firstlineinfo	the info to print on the first line

6.24.3 Member Function Documentation

6.24.3.1 GetFileName()

```
std::string GeodesicOutputHandler::GetFileName (
            int diagnr,
            unsigned short filenr) const  [private]
```

Get the file name based on the various parts of the file name stored in the member variables.

Parameters

diagnr	
filenr	

Returns

std::string

6.24.3.2 getFullDescriptionStr()

```
std::string GeodesicOutputHandler::getFullDescriptionStr () const
```

full description string getter for the geodesic output handler

Returns

std::string

6.24.3.3 NewGeodesicOutput()

```
void GeodesicOutputHandler::NewGeodesicOutput (
            largecounter index,
            std::vector< std::string > theOutput)
```

Parameters

index	
theOutput	

6.24.3.4 OpenForFirstTime()

```
void GeodesicOutputHandler::OpenForFirstTime (
            const std::string & filename)  [private]
```

We check here to see if the files are being put in a (sub)directory; if so, we create the directory/directories first to make sure creating/opening the file will succeed.

Parameters

filename	Filename to be found / created

6.24.3.5 OutputFinished()

```
void GeodesicOutputHandler::OutputFinished ()
```

There is no more output, so we write anything that is cached to file to clean up and finalize.

6.24.3.6 PrepareForOutput()

```
void GeodesicOutputHandler::PrepareForOutput (
            largecounter nrOutputToCome)
```

prepare the cache for output

Parameters

nrOutputToCome	number of outputs to come into the cache

6.24.3.7 WriteCachedOutputToFile()

```
void GeodesicOutputHandler::WriteCachedOutputToFile ()  [private]
```

Write cached output to a file.

6.24.4 Member Data Documentation

6.24.4.1 m_AllCachedData

```
std::vector<std::vector<std::string> > GeodesicOutputHandler::m_AllCachedData {}  [private]
```

Cached data that has not been written to a file yet (once this hits a size of $>$ m_nrOutputsToCache, this must be written to file(s))

6.24.4.2 m_CurrentFullFiles

```
unsigned short GeodesicOutputHandler::m_CurrentFullFiles {0}  [private]
```

The current counter of completely full files (this is kept track of so that it knows what the next file to write output to is). (We had better not have more than 60k files!)

6.24.4.3 m_CurrentGeodesicsInFile

```
largecounter GeodesicOutputHandler::m_CurrentGeodesicsInFile {0}  [private]
```

The number of geodesics already written to the current file (once this hits m_nrGeodesicsPerFile, this file is full)

6.24.4.4 m_DiagNames

```
const std::vector<std::string> GeodesicOutputHandler::m_DiagNames  [private]
```

Const string for the diagnostic names.

6.24.4.5 m_FileExtension

```
const std::string GeodesicOutputHandler::m_FileExtension  [private]
```

Const string for file extension.

6.24.4.6 m_FilePrefix

```
const std::string GeodesicOutputHandler::m_FilePrefix  [private]
```

Const string for file prefix.

6.24.4.7 m_FirstLineInfoString

```
const std::string GeodesicOutputHandler::m_FirstLineInfoString  [private]
```

Const string for the first line info.

6.24.4.8 m_nrGeodesicsPerFile

```
const largecounter GeodesicOutputHandler::m_nrGeodesicsPerFile {}  [private]
```

Const setting the max number of geodesics per file.

6.24.4.9 m_nrOutputsToCache

```
const largecounter GeodesicOutputHandler::m_nrOutputsToCache {}  [private]
```

6.24.4.10 m_PrevCached

```
largecounter GeodesicOutputHandler::m_PrevCached {0}  [private]
```

How many outputs are already cached in m_nrOutputsToCache before the current iteration of output.

6.24.4.11 m_PrintFirstLineInfo

```
const bool GeodesicOutputHandler::m_PrintFirstLineInfo  [private]
```

Const variable that control whether we write a descriptive first line in every output file or not.

6.24.4.12 m_TimeStamp

```
const std::string GeodesicOutputHandler::m_TimeStamp  [private]
```

Const string for timestamp.

6.24.4.13 m_WriteToConsole

```
bool GeodesicOutputHandler::m_WriteToConsole {false}  [private]
```

If this is false, then we are writing to file(s). At any time, if a file I/O error occurs, the output handler switches to outputting everything to the console.

The documentation for this class was generated from the following files:


- FOORT/src/InputOutput.h
- FOORT/src/InputOutput.cpp

6.25 GeodesicPositionDiagnostic Class Reference

Geodesic position tracker.

```
#include <Diagnostics.h>
```

Inheritance diagram for GeodesicPositionDiagnostic:



Public Member Functions

- GeodesicPositionDiagnostic (Geodesic *const theGeodesic)
- void Reset () final

  GeodesicPositionDiagnostic functions.
- void UpdateData () final

  Update the saved points vector with the current position of the geodesic.
- std::string getFullDataStr () const final

  Return full data string of all saved points.
- std::vector< real > getFinalDataVal () const final

  Return the final (theta, phi) value of the geodesic.
- real FinalDataValDistance (const std::vector< real > &val1, const std::vector< real > &val2) const final

  Return the angular distance between two geodesics.
- std::string getNameStr () const final

  Simple name without spaces.
- std::string getFullDescriptionStr () const final

  More descriptive string (with spaces)

Public Member Functions inherited from Diagnostic

- Diagnostic ()=delete
- Diagnostic (Geodesic *const theGeodesic)
- virtual ~Diagnostic ()=default

Static Public Attributes

- static std::unique_ptr< GeodesicPositionOptions > DiagOptions

Private Attributes

- std::vector< Point > m_AllSavedPoints {}

Additional Inherited Members

Protected Member Functions inherited from Diagnostic

- bool DecideUpdate (const UpdateFrequency &myUpdateFrequency)

  Returns true if the Diagnostic should update its initial status.

Protected Attributes inherited from Diagnostic

- Geodesic *const m_OwnerGeodesic
- largecounter m_StepsSinceUpdated {}

6.25.1 Detailed Description

Geodesic position tracker.

6.25.2 Constructor & Destructor Documentation

6.25.2.1 GeodesicPositionDiagnostic()

```
GeodesicPositionDiagnostic::GeodesicPositionDiagnostic (
            Geodesic *const theGeodesic)  [inline]
```

6.25.3 Member Function Documentation

6.25.3.1 FinalDataValDistance()

```
real GeodesicPositionDiagnostic::FinalDataValDistance (
            const std::vector< real > & val1,
            const std::vector< real > & val2) const  [final], [virtual]
```

Return the angular distance between two geodesics.

This is based on their final angles on the boundary sphere (theta, phi)

Parameters

val1	first geodesic final position
val2	second geodesic final position

Returns

real

Implements Diagnostic.

6.25.3.2 getFinalDataVal()

```
std::vector< real > GeodesicPositionDiagnostic::getFinalDataVal () const  [final], [virtual]
```

Return the final (theta, phi) value of the geodesic.

Returns

std::vector<real>

Implements Diagnostic.

6.25.3.3 getFullDataStr()

```
std::string GeodesicPositionDiagnostic::getFullDataStr () const  [final], [virtual]
```

Return full data string of all saved points.

The full output string looks like this: "(total nr steps) ;; (step 1) (step 2) (step 3) ..." where each step is a (space-separated) output of the geodesic coordinates at that step

Returns

std::string

Implements Diagnostic.

6.25.3.4 getFullDescriptionStr()

```
std::string GeodesicPositionDiagnostic::getFullDescriptionStr () const  [final], [virtual]
```

More descriptive string (with spaces)

Returns

std::string

Reimplemented from Diagnostic.

6.25.3.5 getNameStr()

```
std::string GeodesicPositionDiagnostic::getNameStr () const  [final], [virtual]
```

Simple name without spaces.

Returns

std::string

Implements Diagnostic.

6.25.3.6 Reset()

```
void GeodesicPositionDiagnostic::Reset ()  [final], [virtual]
```

GeodesicPositionDiagnostic functions.

Empty out vector of points and call base Reset function

Reimplemented from Diagnostic.

6.25.3.7 UpdateData()

```
void GeodesicPositionDiagnostic::UpdateData ()  [final], [virtual]
```

Update the saved points vector with the current position of the geodesic.

Implements Diagnostic.

6.25.4 Member Data Documentation

6.25.4.1 DiagOptions

```
std::unique_ptr< GeodesicPositionOptions > GeodesicPositionDiagnostic::DiagOptions  [static]
```

6.25.4.2 m_AllSavedPoints

```
std::vector<Point> GeodesicPositionDiagnostic::m_AllSavedPoints {}  [private]
```

The documentation for this class was generated from the following files:


- FOORT/src/Diagnostics.h
- FOORT/src/Config.cpp
- FOORT/src/Diagnostics.cpp

6.26 GeodesicPositionOptions Struct Reference

Options for GeodesicPositionDiagnostic.

```
#include <Diagnostics.h>
```

Inheritance diagram for GeodesicPositionOptions:



Public Member Functions

- GeodesicPositionOptions (bool rlog, largecounter outputsteps, UpdateFrequency thefrequency)

Public Member Functions inherited from DiagnosticOptions

- DiagnosticOptions (UpdateFrequency thefrequency)
- virtual ~DiagnosticOptions ()=default

Public Attributes

- const bool RLogScale
- const largecounter OutputNrSteps

Public Attributes inherited from DiagnosticOptions

- const UpdateFrequency theUpdateFrequency

6.26.1 Detailed Description

Options for GeodesicPositionDiagnostic.

Inherits from DiagnosticOptions, and adds the number of steps to output.

6.26.2 Constructor & Destructor Documentation

6.26.2.1 GeodesicPositionOptions()

```
GeodesicPositionOptions::GeodesicPositionOptions (
            bool rlog,
            largecounter outputsteps,
            UpdateFrequency thefrequency)  [inline]
```

6.26.3 Member Data Documentation

6.26.3.1 OutputNrSteps

```
const largecounter GeodesicPositionOptions::OutputNrSteps
```

6.26.3.2 RLogScale

```
const bool GeodesicPositionOptions::RLogScale
```

The documentation for this struct was generated from the following file:


- FOORT/src/Diagnostics.h

6.27 GLMJohnsonSUEmission Struct Reference

The Johnson SU emission model used in GLM 2020, PRD 102(12):124004.

`#include <DiagnosticsEmission.h>`

Inheritance diagram for GLMJohnsonSUEmission:



Public Member Functions

- GLMJohnsonSUEmission (real mu, real gamma, real sigma)
- real GetEmission (const Point &p) const final

  Get the emission at a point according to the Johnson SU model used in GLM.
- std::string getFullDescriptionStr () const final

  Description string getter for the Johnson SU emission model.

Public Member Functions inherited from EmissionModel

- virtual ~EmissionModel ()=default

Private Attributes

- const real m_mu
  mu parameter
- const real m_gamma
  gamma parameter
- const real m_sigma
  sigma parameter

6.27.1 Detailed Description

The Johnson SU emission model used in GLM 2020, PRD 102(12):124004.

6.27.2 Constructor & Destructor Documentation

6.27.2.1 GLMJohnsonSUEmission()

```
GLMJohnsonSUEmission::GLMJohnsonSUEmission (
            real mu,
            real gamma,
            real sigma)  [inline]
```

6.27.3 Member Function Documentation

6.27.3.1 GetEmission()

```
real GLMJohnsonSUEmission::GetEmission (
            const Point & p) const  [final], [virtual]
```

Get the emission at a point according to the Johnson SU model used in GLM.

Parameters

p	Point at which to calculate the emission

Returns

real Emission at the point

Implements EmissionModel.

6.27.3.2 getFullDescriptionStr()

```
std::string GLMJohnsonSUEmission::getFullDescriptionStr () const  [final], [virtual]
```

Description string getter for the Johnson SU emission model.

Returns

std::string

Reimplemented from EmissionModel.

6.27.4 Member Data Documentation

6.27.4.1 m_gamma

```
const real GLMJohnsonSUEmission::m_gamma  [private]
```

gamma parameter

6.27.4.2 m_mu

```
const real GLMJohnsonSUEmission::m_mu  [private]
```

mu parameter

6.27.4.3 m_sigma

```
const real GLMJohnsonSUEmission::m_sigma  [private]
```

sigma parameter

The documentation for this struct was generated from the following files:


- FOORT/src/DiagnosticsEmission.h
- FOORT/src/DiagnosticsEmission.cpp

6.28 HorizonTermination Class Reference

HorizonTermination: Terminate geodesics if they get too close to the horizon.

```
#include <Terminations.h>
```

Inheritance diagram for HorizonTermination:



Public Member Functions

- HorizonTermination (Geodesic *const theGeodesic)
- Term CheckTermination () final

  Termination checker for the horizon termination.
- std::string getFullDescriptionStr () const final

  Description string getter for the Horizon Termination.

Public Member Functions inherited from Termination

- Termination ()=delete
- Termination (Geodesic *const theGeodesic)
- virtual void Reset ()

  Reset to 0 to start integrating a new geodesic.
- virtual ~Termination ()=default

Static Public Attributes

- static std::unique_ptr< HorizonTermOptions > TermOptions

  Options (contains horizon radius, if we are using logarithmic r coordinate, and distance allowed from the horizon)

Additional Inherited Members

Protected Member Functions inherited from Termination

- bool DecideUpdate (largecounter UpdateNSteps)

  Returns true if the Termination should update its internal status.

Protected Attributes inherited from Termination

- Geodesic *const m_OwnerGeodesic

  The geodesic that owns the Termination (a const pointer to the Geodesic)
- largecounter m_StepsSinceUpdated {}

  The termination is itself in charge of keeping track of how many steps it has been since it has been updated. The Termination's TerminationOptions struct tells it how many steps it needs to wait between updates.

6.28.1 Detailed Description

HorizonTermination: Terminate geodesics if they get too close to the horizon.

6.28.2 Constructor & Destructor Documentation

6.28.2.1 HorizonTermination()

```
HorizonTermination::HorizonTermination (
            Geodesic *const theGeodesic)  [inline]
```

6.28.3 Member Function Documentation

6.28.3.1 CheckTermination()

```
Term HorizonTermination::CheckTermination ()  [final], [virtual]
```

Termination checker for the horizon termination.

Returns

Term

Implements Termination.

6.28.3.2 getFullDescriptionStr()

```
std::string HorizonTermination::getFullDescriptionStr () const  [final], [virtual]
```

Description string getter for the Horizon Termination.

Returns

std::string

Implements Termination.

6.28.4 Member Data Documentation

6.28.4.1 TermOptions

```
std::unique_ptr< HorizonTermOptions > HorizonTermination::TermOptions  [static]
```

Options (contains horizon radius, if we are using logarithmic r coordinate, and distance allowed from the horizon)

The documentation for this class was generated from the following files:


- FOORT/src/Terminations.h
- FOORT/src/Config.cpp
- FOORT/src/Terminations.cpp

6.29 HorizonTermOptions Struct Reference

Options for HorizonTermination.

```
#include <Terminations.h>
```

Inheritance diagram for HorizonTermOptions:



Public Member Functions

- HorizonTermOptions (real theHorizonRadius, bool therLogScale, real theAtHorizonEps, largecounter Nsteps)

Public Member Functions inherited from TerminationOptions

- TerminationOptions (largecounter Nsteps)
- virtual ~TerminationOptions ()=default

Public Attributes

- const real HorizonRadius

  The radius of the horizon.
- const real AtHorizonEps

  The distance allowed from the horizon.
- const bool rLogScale

  Whether we are using a logarithmic r coordinate.

Public Attributes inherited from TerminationOptions

- const largecounter UpdateEveryNSteps

  Number of steps between updates.

6.29.1 Detailed Description

Options for HorizonTermination.

Keeps track of the horizon radius, whether we are using a logarithmic r coordinate, and the distance allowed from the horizon.

6.29.2 Constructor & Destructor Documentation

6.29.2.1 HorizonTermOptions()

```
HorizonTermOptions::HorizonTermOptions (
            real theHorizonRadius,
            bool therLogScale,
            real theAtHorizonEps,
            largecounter Nsteps)  [inline]
```

6.29.3 Member Data Documentation

6.29.3.1 AtHorizonEps

```
const real HorizonTermOptions::AtHorizonEps
```

The distance allowed from the horizon.

6.29.3.2 HorizonRadius

```
const real HorizonTermOptions::HorizonRadius
```

The radius of the horizon.

6.29.3.3 rLogScale

```
const bool HorizonTermOptions::rLogScale
```

Whether we are using a logarithmic r coordinate.

The documentation for this struct was generated from the following file:


- FOORT/src/Terminations.h

6.30 InputCertainPixelsMesh Class Reference

Mesh which integrates only certain user-inputted pixels.

```
#include <Mesh.h>
```

Inheritance diagram for InputCertainPixelsMesh:



Public Member Functions

- InputCertainPixelsMesh ()=delete
- InputCertainPixelsMesh (const InputCertainPixelsMesh &)=delete
- InputCertainPixelsMesh (largecounter totalPixels, DiagBitflag valdiag)

  Constructor for InputCertainPixelsMesh.
- largecounter getCurNrGeodesics () const final

  Get the current number of geodesics to be integrated.
- void getNewInitConds (largecounter index, ScreenPoint &newunitpoint, ScreenIndex &newscreenindex) const final

  Get the initial conditions for the next pixel to be integrated.
- void GeodesicFinished (largecounter index, std::vector< real > finalValues) final

  Function that is called when a geodesic is finished integrating.
- void EndCurrentLoop () final

  End the current loop of integrating pixels.
- bool IsFinished () const final

  Check whether the Mesh is finished integrating.
- std::string getFullDescriptionStr () const final

  Description string getter.

Public Member Functions inherited from Mesh

- Mesh (DiagBitflag valdiag)
- virtual ~Mesh ()=default

Private Attributes

- const pixelcoord m_RowColumnSize

  Total pixel size of the screen (square grid)
- largecounter m_TotalPixels {0}

  How many pixels have been inputted in total, i.e. need integrating.
- std::vector< ScreenIndex > m_PixelsToIntegrate {}

  All pixels' location.
- bool m_Finished {false}

  Are we finished integrating?

Additional Inherited Members

Protected Attributes inherited from Mesh

- const std::unique_ptr< const Diagnostic > m_DistanceDiagnostic

  The Diagnostic (a const pointer to a const Diagnostic object) that is used to calculate distances (using FinalData↩ ValDistance()) between the "values" that are assigned to Geodesics.

6.30.1 Detailed Description

Mesh which integrates only certain user-inputted pixels.

6.30.2 Constructor & Destructor Documentation

6.30.2.1 InputCertainPixelsMesh() [1/3]

```
InputCertainPixelsMesh::InputCertainPixelsMesh ()  [delete]
```

6.30.2.2 InputCertainPixelsMesh() [2/3]

```
InputCertainPixelsMesh::InputCertainPixelsMesh (
            const InputCertainPixelsMesh & )  [delete]
```

6.30.2.3 InputCertainPixelsMesh() [3/3]

```
InputCertainPixelsMesh::InputCertainPixelsMesh (
            largecounter totalPixels,
            DiagBitflag valdiag)
```

Constructor for InputCertainPixelsMesh.

Constructor will ask for pixels to be inputted by the user through the console

Parameters

totalPixels	total number of pixels in the grid
valdiag	value diagnostic bitflag

6.30.3 Member Function Documentation

6.30.3.1 EndCurrentLoop()

```
void InputCertainPixelsMesh::EndCurrentLoop ()  [final], [virtual]
```

End the current loop of integrating pixels.

This Mesh only has one loop; we are now finished integrating

Implements Mesh.

6.30.3.2 GeodesicFinished()

```
void InputCertainPixelsMesh::GeodesicFinished (
            largecounter index,
            std::vector< real > finalValues)  [final], [virtual]
```

Function that is called when a geodesic is finished integrating.

This Mesh doesn't actually have to do anything with the geodesic (values) when it is done!

Parameters

index	index of the geodesic that is finished
finalValues	final values of the geodesic

Implements Mesh.

6.30.3.3 getCurNrGeodesics()

```
largecounter InputCertainPixelsMesh::getCurNrGeodesics () const  [final], [virtual]
```

Get the current number of geodesics to be integrated.

This is the total number of pixels in the grid

Returns

largecounter

Implements Mesh.

6.30.3.4 getFullDescriptionStr()

```
std::string InputCertainPixelsMesh::getFullDescriptionStr () const  [final], [virtual]
```

Description string getter.

Returns

std::string

Reimplemented from Mesh.

6.30.3.5 getNewInitConds()

```
void InputCertainPixelsMesh::getNewInitConds (
            largecounter index,
            ScreenPoint & newunitpoint,
            ScreenIndex & newscreenindex) const  [final], [virtual]
```

Get the initial conditions for the next pixel to be integrated.

The next pixel is the one with index m_CurrentPixel

Parameters

index	index of the pixel to be initialized
newunitpoint	new unit point to be initialized
newscreenindex	new screen index to be initialized

Implements Mesh.

6.30.3.6 IsFinished()

```
bool InputCertainPixelsMesh::IsFinished () const  [final], [virtual]
```

Check whether the Mesh is finished integrating.

Returns

true

false

Implements Mesh.

6.30.4 Member Data Documentation

6.30.4.1 m_Finished

```
bool InputCertainPixelsMesh::m_Finished {false}  [private]
```

Are we finished integrating?

6.30.4.2 m_PixelsToIntegrate

```
std::vector<ScreenIndex> InputCertainPixelsMesh::m_PixelsToIntegrate {}  [private]
```

All pixels' location.

6.30.4.3 m_RowColumnSize

```
const pixelcoord InputCertainPixelsMesh::m_RowColumnSize  [private]
```

Total pixel size of the screen (square grid)

6.30.4.4 m_TotalPixels

```
largecounter InputCertainPixelsMesh::m_TotalPixels {0}  [private]
```

How many pixels have been inputted in total, i.e. need integrating.

The documentation for this class was generated from the following files:


- FOORT/src/Mesh.h
- FOORT/src/Mesh.cpp

6.31 JohannsenMetric Class Reference

Johannsen black hole metric.

`#include <Metric.h>`

Inheritance diagram for JohannsenMetric:



Public Member Functions

- JohannsenMetric ()=delete
- JohannsenMetric (real aParam, real alpha13Param, real alpha22Param, real alpha52Param, real eps3Param, bool rLogScale=false)

  Construct a new Johannsen Metric object. We always have a M = 1 BH.
- TwoIndex getMetric_dd (const Point &p) const final

  Johannsen metric getter, indices down.
- TwoIndex getMetric_uu (const Point &p) const final

  Johannsen metric getter, indices up.
- std::string getFullDescriptionStr () const final

  Johannsen metric description string getter.

Public Member Functions inherited from SphericalHorizonMetric

- SphericalHorizonMetric ()=delete
- SphericalHorizonMetric (real HorizonRadius, bool rLogScale)

  Construct a new Spherical Horizon Metric object.
- real getHorizonRadius () const

  Get the radius of the horizon.

Public Member Functions inherited from Metric

- virtual ~Metric ()=default
- Metric (bool rlogscale=false)

  Construct a new Metric object.
- virtual ThreeIndex getChristoffel_udd (const Point &p) const

  Return the Christoffel symbols of the metric (indices up, down, down)
- virtual FourIndex getRiemann_uddd (const Point &p) const

  Riemann tensor of the metric (indices up, down, down, down)
- virtual real getKretschmann (const Point &p) const

  Get the Kretschmann scalar at a point.
- bool getrLogScale () const

  Get whether we are using a logarithmic radial scale.

Private Attributes

- const real m_aParam

  a parameter for the Johannsen metric
- const real m_alpha13Param

  alpha13 parameter for the Johannsen metric
- const real m_alpha22Param

  alpha22 parameter for the Johannsen metric
- const real m_alpha52Param

  alpha52 parameter for the Johannsen metric
- const real m_eps3Param

  eps3 parameter for the Johannsen metric

Additional Inherited Members

Protected Attributes inherited from SphericalHorizonMetric

- const real m_HorizonRadius

  Radius of the horizon.

Protected Attributes inherited from Metric

- std::vector< int > m_Symmetries {}

  The symmetries (coordinate Killing vectors) of the metric. Should be set by descendant constructor.
- const bool m_rLogScale

  Are we using a logarithmic r coordinate?

6.31.1 Detailed Description

Johannsen black hole metric.

Note

Implementation by Seppe Staelens

6.31.2 Constructor & Destructor Documentation

6.31.2.1 JohannsenMetric() [1/2]

```
JohannsenMetric::JohannsenMetric ()  [delete]
```

6.31.2.2 JohannsenMetric() [2/2]

```
JohannsenMetric::JohannsenMetric (
            real aParam,
            real alpha13Param,
            real alpha22Param,
            real alpha52Param,
            real eps3Param,
            bool rLogScale = false)
```

Construct a new Johannsen Metric object. We always have a M = 1 BH.

Parameters

aParam	a parameter for the Johannsen metric
alpha13Param	alpha13 parameter for the Johannsen metric
alpha22Param	alpha22 parameter for the Johannsen metric
alpha52Param	alpha52 parameter for the Johannsen metric
eps3Param	eps3 parameter for the Johannsen metric
rLogScale	whether we are using a logarithmic radial scale

Note

Implementation by Seppe Staelens

6.31.3 Member Function Documentation

6.31.3.1 getFullDescriptionStr()

```
std::string JohannsenMetric::getFullDescriptionStr () const  [final], [virtual]
```

Johannsen metric description string getter.

Returns

std::string

Reimplemented from Metric.

6.31.3.2 getMetric_dd()

```
TwoIndex JohannsenMetric::getMetric_dd (
            const Point & p) const  [final], [virtual]
```

Johannsen metric getter, indices down.

Parameters

p	Point at which to evaluate the metric

Returns

TwoIndex

Implements Metric.

6.31.3.3 getMetric_uu()

```
TwoIndex JohannsenMetric::getMetric_uu (
            const Point & p) const  [final], [virtual]
```

Johannsen metric getter, indices up.

Parameters

p	Point at which to evaluate the metric

Returns

TwoIndex

Implements Metric.

6.31.4 Member Data Documentation

6.31.4.1 m_alpha13Param

```
const real JohannsenMetric::m_alpha13Param  [private]
```

alpha13 parameter for the Johannsen metric

6.31.4.2 m_alpha22Param

```
const real JohannsenMetric::m_alpha22Param  [private]
```

alpha22 parameter for the Johannsen metric

6.31.4.3 m_alpha52Param

```
const real JohannsenMetric::m_alpha52Param  [private]
```

alpha52 parameter for the Johannsen metric

6.31.4.4 m_aParam

```
const real JohannsenMetric::m_aParam  [private]
```

a parameter for the Johannsen metric

6.31.4.5 m_eps3Param

```
const real JohannsenMetric::m_eps3Param  [private]
```

eps3 parameter for the Johannsen metric

The documentation for this class was generated from the following files:


- FOORT/src/Metric.h
- FOORT/src/Metric.cpp

6.32 KerrMetric Class Reference

The Kerr metric.

```
#include <Metric.h>
```

Inheritance diagram for KerrMetric:



Public Member Functions

- KerrMetric ()=delete
- KerrMetric (real aParam, bool rLogScale=false, real mParam=1.)

  Construct a new Kerr Metric object.
- TwoIndex getMetric_dd (const Point &p) const final

  Kerr metric getter, indices down.
- TwoIndex getMetric_uu (const Point &p) const final

  Kerr metric getter, indices up.
- std::string getFullDescriptionStr () const final

  Kerr metric description string getter.

Public Member Functions inherited from SphericalHorizonMetric

- SphericalHorizonMetric ()=delete
- SphericalHorizonMetric (real HorizonRadius, bool rLogScale)

  Construct a new Spherical Horizon Metric object.
- real getHorizonRadius () const

  Get the radius of the horizon.

Public Member Functions inherited from Metric

- virtual ~Metric ()=default
- Metric (bool rlogscale=false)

  Construct a new Metric object.
- virtual ThreeIndex getChristoffel_udd (const Point &p) const

  Return the Christoffel symbols of the metric (indices up, down, down)
- virtual FourIndex getRiemann_uddd (const Point &p) const

  Riemann tensor of the metric (indices up, down, down, down)
- virtual real getKretschmann (const Point &p) const

  Get the Kretschmann scalar at a point.
- bool getrLogScale () const

  Get whether we are using a logarithmic radial scale.

Private Attributes

- const real m_aParam

  Mass-rescaled rotation parameter for Kerr. Note that this should be between -1 and 1.
- const real m_mParam

  Mass parameter for Kerr. Default is 1.

Additional Inherited Members

Protected Attributes inherited from SphericalHorizonMetric

- const real m_HorizonRadius

  Radius of the horizon.

Protected Attributes inherited from Metric

- std::vector< int > m_Symmetries {}

  The symmetries (coordinate Killing vectors) of the metric. Should be set by descendant constructor.
- const bool m_rLogScale

  Are we using a logarithmic r coordinate?

6.32.1 Detailed Description

The Kerr metric.

6.32.2 Constructor & Destructor Documentation

6.32.2.1 KerrMetric() [1/2]

```
KerrMetric::KerrMetric ()  [delete]
```

6.32.2.2 KerrMetric() [2/2]

```
KerrMetric::KerrMetric (
            real aParam,
            bool rLogScale = false,
            real mParam = 1.)
```

Construct a new Kerr Metric object.

Parameters

aParam	a parameter for the Kerr metric
rLogScale	Whether we are using a logarithmic radial scale
mParam	mass parameter for the Kerr metric

6.32.3 Member Function Documentation

6.32.3.1 getFullDescriptionStr()

```
std::string KerrMetric::getFullDescriptionStr () const  [final], [virtual]
```

Kerr metric description string getter.

Returns

std::string

Reimplemented from Metric.

6.32.3.2 getMetric_dd()

```
TwoIndex KerrMetric::getMetric_dd (
            const Point & p) const  [final], [virtual]
```

Kerr metric getter, indices down.

Parameters

p	Point at which to evaluate the metric

Returns

TwoIndex

Implements Metric.

6.32.3.3 getMetric_uu()

```
TwoIndex KerrMetric::getMetric_uu (
            const Point & p) const  [final], [virtual]
```

Kerr metric getter, indices up.

Parameters

p	Point at which to evaluate the metric

Returns

TwoIndex

Implements Metric.

6.32.4 Member Data Documentation

6.32.4.1 m_aParam

```
const real KerrMetric::m_aParam  [private]
```

Mass-rescaled rotation parameter for Kerr. Note that this should be between -1 and 1.

6.32.4.2 m_mParam

```
const real KerrMetric::m_mParam  [private]
```

Mass parameter for Kerr. Default is 1.

The documentation for this class was generated from the following files:


- FOORT/src/Metric.h
- FOORT/src/Metric.cpp

6.33 KerrSchildMetric Class Reference

Kerr metric in Kerr-Schild coordinates.

```
#include <Metric.h>
```

Inheritance diagram for KerrSchildMetric:



Public Member Functions

- KerrSchildMetric ()=delete
- KerrSchildMetric (real aParam, bool rLogScale=false)

  Construct a new Kerr Schild Metric object. We always have a M = 1 BH.
- TwoIndex getMetric_dd (const Point &p) const final

  Kerr-Schild metric getter, indices down.
- TwoIndex getMetric_uu (const Point &p) const final

  Kerr-Schild metric getter, indices up.
- std::string getFullDescriptionStr () const final

  Kerr-Schild metric description string getter.

Public Member Functions inherited from SphericalHorizonMetric

- SphericalHorizonMetric ()=delete
- SphericalHorizonMetric (real HorizonRadius, bool rLogScale)

  Construct a new Spherical Horizon Metric object.
- real getHorizonRadius () const

  Get the radius of the horizon.

Public Member Functions inherited from Metric

- virtual ~Metric ()=default
- Metric (bool rlogscale=false)

  Construct a new Metric object.
- virtual ThreeIndex getChristoffel_udd (const Point &p) const

  Return the Christoffel symbols of the metric (indices up, down, down)
- virtual FourIndex getRiemann_uddd (const Point &p) const

  Riemann tensor of the metric (indices up, down, down, down)
- virtual real getKretschmann (const Point &p) const

  Get the Kretschmann scalar at a point.
- bool getrLogScale () const

  Get whether we are using a logarithmic radial scale.

Private Attributes

- const real m_aParam

  Rotation parameter for Kerr. Note that this should be between -1 and 1 since M=1.

Additional Inherited Members

Protected Attributes inherited from SphericalHorizonMetric

- const real m_HorizonRadius

  Radius of the horizon.

Protected Attributes inherited from Metric

- std::vector< int > m_Symmetries {}

  The symmetries (coordinate Killing vectors) of the metric. Should be set by descendant constructor.
- const bool m_rLogScale

  Are we using a logarithmic r coordinate?

6.33.1 Detailed Description

Kerr metric in Kerr-Schild coordinates.

Note

Normalized so that M = 1

6.33.2 Constructor & Destructor Documentation

6.33.2.1 KerrSchildMetric() [1/2]

```
KerrSchildMetric::KerrSchildMetric ()  [delete]
```

6.33.2.2 KerrSchildMetric() [2/2]

```
KerrSchildMetric::KerrSchildMetric (
            real aParam,
            bool rLogScale = false)
```

Construct a new Kerr Schild Metric object. We always have a M = 1 BH.

Parameters

aParam	a parameter for the Kerr-Schild metric
rLogScale	whether we are using a logarithmic radial scale

6.33.3 Member Function Documentation

6.33.3.1 getFullDescriptionStr()

```
std::string KerrSchildMetric::getFullDescriptionStr () const  [final], [virtual]
```

Kerr-Schild metric description string getter.

Returns

std::string

Reimplemented from Metric.

6.33.3.2 getMetric_dd()

```
TwoIndex KerrSchildMetric::getMetric_dd (
            const Point & p) const  [final], [virtual]
```

Kerr-Schild metric getter, indices down.

Parameters

p	Point at which to evaluate the metric

Returns

TwoIndex

Implements Metric.

6.33.3.3 getMetric_uu()

```
TwoIndex KerrSchildMetric::getMetric_uu (
            const Point & p) const  [final], [virtual]
```

Kerr-Schild metric getter, indices up.

Parameters

p	Point at which to evaluate the metric

Returns

TwoIndex

Implements Metric.

6.33.4 Member Data Documentation

6.33.4.1 m_aParam

```
const real KerrSchildMetric::m_aParam  [private]
```

Rotation parameter for Kerr. Note that this should be between -1 and 1 since M=1.

The documentation for this class was generated from the following files:


- FOORT/src/Metric.h
- FOORT/src/Metric.cpp

6.34 MankoNovikovMetric Class Reference

Mano-Novikov metric (with angular momentum and M3 parameter turned on)

`#include <Metric.h>`

Inheritance diagram for MankoNovikovMetric:



Public Member Functions

- MankoNovikovMetric ()=delete
- MankoNovikovMetric (real aParam, real alpha3Param, bool rLogScale=false)

  Construct a new Manko Novikov Metric object. We always have a M = 1 BH.
- TwoIndex getMetric_dd (const Point &p) const final

  Manko-Novikov metric getter, indices down.
- TwoIndex getMetric_uu (const Point &p) const final

  Manko-Novikov metric getter, indices up.
- std::string getFullDescriptionStr () const final

  Manko-Novikov metric description string getter.

Public Member Functions inherited from SphericalHorizonMetric

- SphericalHorizonMetric ()=delete
- SphericalHorizonMetric (real HorizonRadius, bool rLogScale)

  Construct a new Spherical Horizon Metric object.
- real getHorizonRadius () const

  Get the radius of the horizon.

Public Member Functions inherited from Metric

- virtual ~Metric ()=default
- Metric (bool rlogscale=false)

  Construct a new Metric object.
- virtual ThreeIndex getChristoffel_udd (const Point &p) const

  Return the Christoffel symbols of the metric (indices up, down, down)
- virtual FourIndex getRiemann_uddd (const Point &p) const

  Riemann tensor of the metric (indices up, down, down, down)
- virtual real getKretschmann (const Point &p) const

  Get the Kretschmann scalar at a point.
- bool getrLogScale () const

  Get whether we are using a logarithmic radial scale.

Private Attributes

- const real m_aParam

  a parameter for the Manko-Novikov metric
- const real m_alpha3Param

  alpha3 parameter for the Manko-Novikov metric
- const real m_alphaParam

  Derived alpha parameter.
- const real m_kParam

  Derived k parameter.

Additional Inherited Members

Protected Attributes inherited from SphericalHorizonMetric

- const real m_HorizonRadius

  Radius of the horizon.

Protected Attributes inherited from Metric

- std::vector< int > m_Symmetries {}

  The symmetries (coordinate Killing vectors) of the metric. Should be set by descendant constructor.
- const bool m_rLogScale

  Are we using a logarithmic r coordinate?

6.34.1 Detailed Description

Mano-Novikov metric (with angular momentum and M3 parameter turned on)

Note

Implementation by Seppe Staelens

6.34.2 Constructor & Destructor Documentation

6.34.2.1 MankoNovikovMetric() [1/2]

```
MankoNovikovMetric::MankoNovikovMetric ()  [delete]
```

6.34.2.2 MankoNovikovMetric() [2/2]

```
MankoNovikovMetric::MankoNovikovMetric (
            real aParam,
            real alpha3Param,
            bool rLogScale = false)
```

Construct a new Manko Novikov Metric object. We always have a M = 1 BH.

The horizon is at r = M + k

Parameters

aParam	a parameter for the Manko-Novikov metric. The angular momentum a = J/M^2
alpha3Param	alpha3 parameter for the Manko-Novikov metric
rLogScale	whether we are using a logarithmic radial scale

6.34.3 Member Function Documentation

6.34.3.1 getFullDescriptionStr()

```
std::string MankoNovikovMetric::getFullDescriptionStr () const  [final], [virtual]
```

Manko-Novikov metric description string getter.

Returns

std::string

Reimplemented from Metric.

6.34.3.2 getMetric_dd()

```
TwoIndex MankoNovikovMetric::getMetric_dd (
            const Point & p) const  [final], [virtual]
```

Manko-Novikov metric getter, indices down.

Parameters

p	Point at which to evaluate the metric

Returns

TwoIndex

Implements Metric.

6.34.3.3 getMetric_uu()

```
TwoIndex MankoNovikovMetric::getMetric_uu (
            const Point & p) const  [final], [virtual]
```

Manko-Novikov metric getter, indices up.

Parameters

p	Point at which to evaluate the metric

Returns

TwoIndex

Implements Metric.

6.34.4 Member Data Documentation

6.34.4.1 m_alpha3Param

```
const real MankoNovikovMetric::m_alpha3Param  [private]
```

alpha3 parameter for the Manko-Novikov metric

6.34.4.2 m_alphaParam

```
const real MankoNovikovMetric::m_alphaParam  [private]
```

Derived alpha parameter.

6.34.4.3 m_aParam

```
const real MankoNovikovMetric::m_aParam  [private]
```

a parameter for the Manko-Novikov metric

6.34.4.4 m_kParam

```
const real MankoNovikovMetric::m_kParam  [private]
```

Derived k parameter.

The documentation for this class was generated from the following files:


- FOORT/src/Metric.h
- FOORT/src/Metric.cpp

6.35 Mesh Class Reference

Abstract base Mesh class.

```
#include <Mesh.h>
```

Inheritance diagram for Mesh:



Public Member Functions

- Mesh (DiagBitflag valdiag)
- virtual ~Mesh ()=default
- virtual largecounter getCurNrGeodesics () const =0
- virtual void getNewInitConds (largecounter index, ScreenPoint &newunitpoint, ScreenIndex &newscreenindex) const =0
- virtual void GeodesicFinished (largecounter index, std::vector< real > finalValues)=0
- virtual void EndCurrentLoop ()=0
- virtual bool IsFinished () const =0
- virtual std::string getFullDescriptionStr () const

  Basic description string getter.

Protected Attributes

- const std::unique_ptr< const Diagnostic > m_DistanceDiagnostic

  The Diagnostic (a const pointer to a const Diagnostic object) that is used to calculate distances (using FinalData↩ ValDistance()) between the "values" that are assigned to Geodesics.

6.35.1 Detailed Description

Abstract base Mesh class.

6.35.2 Constructor & Destructor Documentation

6.35.2.1 Mesh()

```
Mesh::Mesh (
            DiagBitflag valdiag)  [inline]
```

6.35.2.2 ~Mesh()

```
virtual Mesh::~Mesh ()  [virtual], [default]
```

6.35.3 Member Function Documentation

6.35.3.1 EndCurrentLoop()

```
virtual void Mesh::EndCurrentLoop ()  [pure virtual]
```

Implemented in InputCertainPixelsMesh, SimpleSquareMesh, and SquareSubdivisionMesh.

6.35.3.2 GeodesicFinished()

```
virtual void Mesh::GeodesicFinished (
            largecounter index,
            std::vector< real > finalValues)  [pure virtual]
```

Implemented in InputCertainPixelsMesh, SimpleSquareMesh, and SquareSubdivisionMesh.

6.35.3.3 getCurNrGeodesics()

```
virtual largecounter Mesh::getCurNrGeodesics () const  [pure virtual]
```

Implemented in InputCertainPixelsMesh, SimpleSquareMesh, and SquareSubdivisionMesh.

6.35.3.4 getFullDescriptionStr()

```
std::string Mesh::getFullDescriptionStr () const  [virtual]
```

Basic description string getter.

Returns

std::string

Reimplemented in InputCertainPixelsMesh, SimpleSquareMesh, and SquareSubdivisionMesh.

6.35.3.5 getNewInitConds()

```
virtual void Mesh::getNewInitConds (
            largecounter index,
            ScreenPoint & newunitpoint,
            ScreenIndex & newscreenindex) const  [pure virtual]
```

Implemented in InputCertainPixelsMesh, SimpleSquareMesh, and SquareSubdivisionMesh.

6.35.3.6 IsFinished()

```
virtual bool Mesh::IsFinished () const  [pure virtual]
```

Implemented in InputCertainPixelsMesh, SimpleSquareMesh, and SquareSubdivisionMesh.

6.35.4 Member Data Documentation

6.35.4.1 m_DistanceDiagnostic

```
const std::unique_ptr<const Diagnostic> Mesh::m_DistanceDiagnostic  [protected]
```

The Diagnostic (a const pointer to a const Diagnostic object) that is used to calculate distances (using FinalData↩ ValDistance()) between the "values" that are assigned to Geodesics.

The documentation for this class was generated from the following files:

- FOORT/src/Mesh.h
- FOORT/src/Mesh.cpp

6.36 Metric Class Reference

The abstract base class for all Metrics.

```
#include <Metric.h>
```

Inheritance diagram for Metric:



Public Member Functions

- virtual ∼Metric ()=default
- Metric (bool rlogscale=false)

  Construct a new Metric object.
- virtual TwoIndex getMetric_dd (const Point &p) const =0
- virtual TwoIndex getMetric_uu (const Point &p) const =0
- virtual ThreeIndex getChristoffel_udd (const Point &p) const

  Return the Christoffel symbols of the metric (indices up, down, down)
- virtual FourIndex getRiemann_uddd (const Point &p) const

  Riemann tensor of the metric (indices up, down, down, down)
- virtual real getKretschmann (const Point &p) const

  Get the Kretschmann scalar at a point.
- virtual std::string getFullDescriptionStr () const

  Base class description string getter.
- bool getrLogScale () const

  Get whether we are using a logarithmic radial scale.

Protected Attributes

- std::vector< int > m_Symmetries {}

  The symmetries (coordinate Killing vectors) of the metric. Should be set by descendant constructor.
- const bool m_rLogScale

  Are we using a logarithmic r coordinate?

6.36.1 Detailed Description

The abstract base class for all Metrics.

6.36.2 Constructor & Destructor Documentation

6.36.2.1 ∼Metric()

```
virtual Metric::∼Metric ()  [virtual], [default]
```

6.36.2.2 Metric()

```
Metric::Metric (
            bool rlogscale = false)
```

Construct a new Metric object.

Parameters

rlogscale	Whether we are using a logarithmic radial scale

6.36.3 Member Function Documentation

6.36.3.1 getChristoffel_udd()

```
ThreeIndex Metric::getChristoffel_udd (
            const Point & p) const  [virtual]
```

Return the Christoffel symbols of the metric (indices up, down, down)

Parameters

p	Point at which to evaluate the Christoffel symbols

Returns

ThreeIndex

6.36.3.2 getFullDescriptionStr()

```
std::string Metric::getFullDescriptionStr () const  [virtual]
```

Base class description string getter.

Returns

std::string

Reimplemented in BosonStarMetric, FlatSpaceMetric, JohannsenMetric, KerrMetric, KerrSchildMetric, MankoNovikovMetric, RasheedLarsenMetric, and ST3CrMetric.

6.36.3.3 getKretschmann()

```
real Metric::getKretschmann (
            const Point & p) const  [virtual]
```

Get the Kretschmann scalar at a point.

The Kretschmann scalar is defined as R_{abcd} R^{abcd}

Warning

Not implemented yet: always throws std::runtime_error.

Parameters

p	Point at which to evaluate the Kretschmann scalar

Returns

real

6.36.3.4 getMetric_dd()

```
virtual TwoIndex Metric::getMetric_dd (
            const Point & p) const  [pure virtual]
```

Implemented in BosonStarMetric, FlatSpaceMetric, JohannsenMetric, KerrMetric, KerrSchildMetric, MankoNovikovMetric, RasheedLarsenMetric, and ST3CrMetric.

6.36.3.5 getMetric_uu()

```
virtual TwoIndex Metric::getMetric_uu (
            const Point & p) const  [pure virtual]
```

Implemented in BosonStarMetric, FlatSpaceMetric, JohannsenMetric, KerrMetric, KerrSchildMetric, MankoNovikovMetric, RasheedLarsenMetric, and ST3CrMetric.

6.36.3.6 getRiemann_uddd()

```
FourIndex Metric::getRiemann_uddd (
            const Point & p) const  [virtual]
```

Riemann tensor of the metric (indices up, down, down, down)

Parameters

p	Point at which to evaluate the Riemann tensor

Warning

Not implemented yet: always throws std::runtime_error.

Returns

FourIndex

6.36.3.7 getrLogScale()

```
bool Metric::getrLogScale () const
```

Get whether we are using a logarithmic radial scale.

Returns

true

false

6.36.4 Member Data Documentation

6.36.4.1 m_rLogScale

```
const bool Metric::m_rLogScale  [protected]
```

Are we using a logarithmic r coordinate?

6.36.4.2 m_Symmetries

```
std::vector<int> Metric::m_Symmetries {}  [protected]
```

The symmetries (coordinate Killing vectors) of the metric. Should be set by descendant constructor.

The documentation for this class was generated from the following files:


- FOORT/src/Metric.h
- FOORT/src/Metric.cpp

6.37 NaNTermination Class Reference

NaNTermination: Terminate geodesics if they contain a NaN in position or velocity.

```
#include <Terminations.h>
```

Inheritance diagram for NaNTermination:



Public Member Functions

- NaNTermination (Geodesic *const theGeodesic)
- Term CheckTermination () final

  Check if the geodesic contains a NaN.
- std::string getFullDescriptionStr () const final

  Description string getter for the NaN Termination.

Public Member Functions inherited from Termination

- Termination ()=delete
- Termination (Geodesic *const theGeodesic)
- virtual void Reset ()

  Reset to 0 to start integrating a new geodesic.
- virtual ~Termination ()=default

Static Public Attributes

- static std::unique_ptr< NaNTermOptions > TermOptions

  Options (contains horizon radius, if we are using logarithmic r coordinate, and distance allowed from the horizon)

Additional Inherited Members

Protected Member Functions inherited from Termination

- bool DecideUpdate (largecounter UpdateNSteps)

  Returns true if the Termination should update its internal status.

Protected Attributes inherited from Termination

- Geodesic ∗const m_OwnerGeodesic

  The geodesic that owns the Termination (a const pointer to the Geodesic)
- largecounter m_StepsSinceUpdated {}

  The termination is itself in charge of keeping track of how many steps it has been since it has been updated. The Termination's TerminationOptions struct tells it how many steps it needs to wait between updates.

6.37.1 Detailed Description

NaNTermination: Terminate geodesics if they contain a NaN in position or velocity.

6.37.2 Constructor & Destructor Documentation

6.37.2.1 NaNTermination()

```
NaNTermination::NaNTermination (
            Geodesic *const theGeodesic)  [inline]
```

6.37.3 Member Function Documentation

6.37.3.1 CheckTermination()

```
Term NaNTermination::CheckTermination ()  [final], [virtual]
```

Check if the geodesic contains a NaN.

Returns

Term

Implements Termination.

6.37.3.2 getFullDescriptionStr()

```
std::string NaNTermination::getFullDescriptionStr () const  [final], [virtual]
```

Description string getter for the NaN Termination.

Returns

std::string

Implements Termination.

6.37.4 Member Data Documentation

6.37.4.1 TermOptions

```
std::unique_ptr< NaNTermOptions > NaNTermination::TermOptions  [static]
```

Options (contains horizon radius, if we are using logarithmic r coordinate, and distance allowed from the horizon)

The documentation for this class was generated from the following files:


- FOORT/src/Terminations.h
- FOORT/src/Config.cpp
- FOORT/src/Terminations.cpp

6.38 NaNTermOptions Struct Reference

Options for NaNTermination.

```
#include <Terminations.h>
```

Inheritance diagram for NaNTermOptions:



Public Member Functions

- NaNTermOptions (bool consoleoutputon, largecounter Nsteps)

Public Member Functions inherited from TerminationOptions

- TerminationOptions (largecounter Nsteps)
- virtual ~TerminationOptions ()=default

Public Attributes

- const bool OutputToConsole

  Whether to output to the console when a NaN is encountered.

Public Attributes inherited from TerminationOptions

- const largecounter UpdateEveryNSteps

  Number of steps between updates.

6.38.1 Detailed Description

Options for NaNTermination.

6.38.2 Constructor & Destructor Documentation

6.38.2.1 NaNTermOptions()

```
NaNTermOptions::NaNTermOptions (
            bool consoleoutputon,
            largecounter Nsteps)  [inline]
```

6.38.3 Member Data Documentation

6.38.3.1 OutputToConsole

```
const bool NaNTermOptions::OutputToConsole
```

Whether to output to the console when a NaN is encountered.

The documentation for this struct was generated from the following file:


- FOORT/src/Terminations.h

6.39 NoSource Class Reference

NoSource class.

```
#include <Geodesic.h>
```

Inheritance diagram for NoSource:



Public Member Functions

- NoSource (const Metric *const theMetric)
- OneIndex getSource (Point pos, OneIndex vel) const final

  Returns zero source for the geodesic equation: no force felt by geodesic.
- std::string getFullDescriptionStr () const final

  Full description string getter for NoSource class.

Public Member Functions inherited from Source

- Source (const Metric *const theMetric)
- virtual ~Source ()=default

Additional Inherited Members

Protected Attributes inherited from Source

- const Metric *const m_theMetric

  A const pointer to a const metric.

6.39.1 Detailed Description

NoSource class.

There is no source, i.e. the geodesic is indeed a geodesic (and feels no force)

6.39.2 Constructor & Destructor Documentation

6.39.2.1 NoSource()

```
NoSource::NoSource (
            const Metric *const theMetric)  [inline]
```

6.39.3 Member Function Documentation

6.39.3.1 getFullDescriptionStr()

```
std::string NoSource::getFullDescriptionStr () const  [final], [virtual]
```

Full description string getter for NoSource class.

Returns

std::string

Reimplemented from Source.

6.39.3.2 getSource()

```
OneIndex NoSource::getSource (
            Point pos,
            OneIndex vel) const  [final], [virtual]
```

Returns zero source for the geodesic equation: no force felt by geodesic.

Parameters

pos	Position of the geodesic
vel	Velocity of the geodesic

Returns

OneIndex Source for the geodesic

Implements Source.

The documentation for this class was generated from the following files:

- FOORT/src/Geodesic.h
- FOORT/src/Geodesic.cpp

6.40 SquareSubdivisionMesh::PixelInfo Struct Reference

A struct the Mesh uses to keep all information about a given pixel.

Public Member Functions

- PixelInfo (ScreenIndex ind, int subdiv)

Public Attributes

- const ScreenIndex Index {}

  The pixel's screenindex: this gets set by the constructor and cannot change anymore.
- int SubdivideLevel {}

  The level at which the pixel has been subdivided. Note: initial grid pixels are at 1; pixels at 0 are pixels that cannot be subdivided (for example, at the right or lower edges)
- real Weight {-1}

  Weight of the pixel: if negative, this signifies that it needs to be updated/calculated! The weight is determined as the max of the distance (as calculated by the value Diagnostic) between its values and those of its right, lower, and right-lower neighbors.
- std::vector< real > DiagValue {}

  The values associated to this pixel (as calculated by the value Diagnostic)
- PixelInfo * LeftNbr {nullptr}

  Pointer to its left neighbor.
- PixelInfo * RightNbr {nullptr}

  Pointer to its right neighbor.
- PixelInfo * UpNbr {nullptr}

  Pointer to its upper neighbor.
- PixelInfo * DownNbr {nullptr}

  Pointer to its lower neighbor.
- PixelInfo * SEdiagNbr {nullptr}

  Pointer to its lower-rightt neighbor.

6.40.1 Detailed Description

A struct the Mesh uses to keep all information about a given pixel.

6.40.2 Constructor & Destructor Documentation

6.40.2.1 PixelInfo()

```
SquareSubdivisionMesh::PixelInfo::PixelInfo (
            ScreenIndex ind,
            int subdiv)  [inline]
```

6.40.3 Member Data Documentation

6.40.3.1 DiagValue

```
std::vector<real> SquareSubdivisionMesh::PixelInfo::DiagValue {}
```

The values associated to this pixel (as calculated by the value Diagnostic)

6.40.3.2 DownNbr

```
PixelInfo* SquareSubdivisionMesh::PixelInfo::DownNbr {nullptr}
```

Pointer to its lower neighbor.

6.40.3.3 Index

```
const ScreenIndex SquareSubdivisionMesh::PixelInfo::Index {}
```

The pixel's screenindex: this gets set by the constructor and cannot change anymore.

6.40.3.4 LeftNbr

```
PixelInfo* SquareSubdivisionMesh::PixelInfo::LeftNbr {nullptr}
```

Pointer to its left neighbor.

6.40.3.5 RightNbr

```
PixelInfo* SquareSubdivisionMesh::PixelInfo::RightNbr {nullptr}
```

Pointer to its right neighbor.

6.40.3.6 SEdiagNbr

```
PixelInfo* SquareSubdivisionMesh::PixelInfo::SEdiagNbr {nullptr}
```

Pointer to its lower-rightt neighbor.

6.40.3.7 SubdivideLevel

```
int SquareSubdivisionMesh::PixelInfo::SubdivideLevel {}
```

The level at which the pixel has been subdivided. Note: initial grid pixels are at 1; pixels at 0 are pixels that cannot be subdivided (for example, at the right or lower edges)

6.40.3.8 UpNbr

```
PixelInfo* SquareSubdivisionMesh::PixelInfo::UpNbr {nullptr}
```

Pointer to its upper neighbor.

6.40.3.9 Weight

```
real SquareSubdivisionMesh::PixelInfo::Weight {-1}
```

Weight of the pixel: if negative, this signifies that it needs to be updated/calculated! The weight is determined as the max of the distance (as calculated by the value Diagnostic) between its values and those of its right, lower, and right-lower neighbors.

The documentation for this struct was generated from the following file:


- FOORT/src/Mesh.h

6.41 RasheedLarsenMetric Class Reference

Rasheed-Larsen black hole.

```
#include <Metric.h>
```

Inheritance diagram for RasheedLarsenMetric:



Public Member Functions

- RasheedLarsenMetric ()=delete
- RasheedLarsenMetric (real mParam, real aParam, real pParam, real qParam, bool rLogScale=false)

  Construct a new Rasheed Larsen Metric object. All parameters are rescaled by the mass to end up with a M = 1 BH.
- TwoIndex getMetric_dd (const Point &p) const final

  Rasheed-Larsen metric getter, indices down.
- TwoIndex getMetric_uu (const Point &p) const final

  Rasheed-Larsen metric getter, indices up.
- std::string getFullDescriptionStr () const final

  Rasheed-Larsen metric description string getter.

Public Member Functions inherited from SphericalHorizonMetric

- SphericalHorizonMetric ()=delete
- SphericalHorizonMetric (real HorizonRadius, bool rLogScale)

  Construct a new Spherical Horizon Metric object.
- real getHorizonRadius () const

  Get the radius of the horizon.

Public Member Functions inherited from Metric

- virtual ~Metric ()=default
- Metric (bool rlogscale=false)

  Construct a new Metric object.
- virtual ThreeIndex getChristoffel_udd (const Point &p) const

  Return the Christoffel symbols of the metric (indices up, down, down)
- virtual FourIndex getRiemann_uddd (const Point &p) const

  Riemann tensor of the metric (indices up, down, down, down)
- virtual real getKretschmann (const Point &p) const

  Get the Kretschmann scalar at a point.
- bool getrLogScale () const

  Get whether we are using a logarithmic radial scale.

Private Attributes

- const real m_aParam

  a parameter for the Rasheed-Larsen metric
- const real m_mParam

  m parameter for the Rasheed-Larsen metric
- const real m_pParam

  p parameter for the Rasheed-Larsen metric
- const real m_qParam

  q parameter for the Rasheed-Larsen metric

Additional Inherited Members

Protected Attributes inherited from SphericalHorizonMetric

- const real m_HorizonRadius

  Radius of the horizon.

Protected Attributes inherited from Metric

- std::vector< int > m_Symmetries {}

  The symmetries (coordinate Killing vectors) of the metric. Should be set by descendant constructor.
- const bool m_rLogScale

  Are we using a logarithmic r coordinate?

6.41.1 Detailed Description

Rasheed-Larsen black hole.

6.41.2 Constructor & Destructor Documentation

6.41.2.1 RasheedLarsenMetric() [1/2]

```
RasheedLarsenMetric::RasheedLarsenMetric ()  [delete]
```

6.41.2.2 RasheedLarsenMetric() [2/2]

```
RasheedLarsenMetric::RasheedLarsenMetric (
            real mParam,
            real aParam,
            real pParam,
            real qParam,
            bool rLogScale = false)
```

Construct a new Rasheed Larsen Metric object. All parameters are rescaled by the mass to end up with a M = 1 BH.

Parameters

mParam	m parameter for the Rasheed-Larsen metric
aParam	a parameter for the Rasheed-Larsen metric
pParam	p parameter for the Rasheed-Larsen metric
qParam	q parameter for the Rasheed-Larsen metric
rLogScale	whether we are using a logarithmic radial scale

6.41.3 Member Function Documentation

6.41.3.1 getFullDescriptionStr()

```
std::string RasheedLarsenMetric::getFullDescriptionStr () const  [final], [virtual]
```

Rasheed-Larsen metric description string getter.

Returns

std::string

Reimplemented from Metric.

6.41.3.2 getMetric_dd()

```
TwoIndex RasheedLarsenMetric::getMetric_dd (
            const Point & p) const  [final], [virtual]
```

Rasheed-Larsen metric getter, indices down.

Parameters

p	Point at which to evaluate the metric

Returns

TwoIndex

Implements Metric.

6.41.3.3 getMetric_uu()

```
TwoIndex RasheedLarsenMetric::getMetric_uu (
            const Point & p) const  [final], [virtual]
```

Rasheed-Larsen metric getter, indices up.

Parameters

p	Point at which to evaluate the metric

Returns

TwoIndex

Implements Metric.

6.41.4 Member Data Documentation

6.41.4.1 m_aParam

```
const real RasheedLarsenMetric::m_aParam  [private]
```

a parameter for the Rasheed-Larsen metric

6.41.4.2 m_mParam

```
const real RasheedLarsenMetric::m_mParam  [private]
```

m parameter for the Rasheed-Larsen metric

6.41.4.3 m_pParam

```
const real RasheedLarsenMetric::m_pParam  [private]
```

p parameter for the Rasheed-Larsen metric

6.41.4.4 m_qParam

```
const real RasheedLarsenMetric::m_qParam  [private]
```

q parameter for the Rasheed-Larsen metric

The documentation for this class was generated from the following files:


- FOORT/src/Metric.h
- FOORT/src/Metric.cpp

6.42 SimpleSquareMesh Class Reference

A simple square mesh that will integrate a square of evenly spaced pixels.

```
#include <Mesh.h>
```

Inheritance diagram for SimpleSquareMesh:



Public Member Functions

- SimpleSquareMesh ()=delete
- SimpleSquareMesh (largecounter totalPixels, DiagBitflag valdiag)
- largecounter getCurNrGeodesics () const final

  Get the current number of geodesics to be integrated.
- void getNewInitConds (largecounter index, ScreenPoint &newunitpoint, ScreenIndex &newscreenindex) const final

  Get the initial conditions for the next pixel to be integrated.
- void GeodesicFinished (largecounter index, std::vector< real > finalValues) final

  Function that is called when a geodesic is finished integrating.
- void EndCurrentLoop () final

  End the current loop of integrating pixels.
- bool IsFinished () const final

  Check whether the Mesh is finished integrating.
- std::string getFullDescriptionStr () const final

  Description string getter.

Public Member Functions inherited from Mesh

- Mesh (DiagBitflag valdiag)
- virtual ~Mesh ()=default

Private Attributes

- const largecounter m_TotalPixels

  Total amount of pixels in grid (is the square of m_RowColumnSize)
- const pixelcoord m_RowColumnSize

  Amount of pixels per row or column (square grid)
- bool m_Finished {false}

  Are we done integrating or not?

Additional Inherited Members

Protected Attributes inherited from Mesh

- const std::unique_ptr< const Diagnostic > m_DistanceDiagnostic

  The Diagnostic (a const pointer to a const Diagnostic object) that is used to calculate distances (using FinalData↩ ValDistance()) between the "values" that are assigned to Geodesics.

6.42.1 Detailed Description

A simple square mesh that will integrate a square of evenly spaced pixels.

6.42.2 Constructor & Destructor Documentation

6.42.2.1 SimpleSquareMesh() [1/2]

```
SimpleSquareMesh::SimpleSquareMesh ()  [delete]
```

6.42.2.2 SimpleSquareMesh() [2/2]

```
SimpleSquareMesh::SimpleSquareMesh (
            largecounter totalPixels,
            DiagBitflag valdiag)  [inline]
```

6.42.3 Member Function Documentation

6.42.3.1 EndCurrentLoop()

```
void SimpleSquareMesh::EndCurrentLoop ()  [final], [virtual]
```

End the current loop of integrating pixels.

We are done integrating after one loop

Implements Mesh.

6.42.3.2 GeodesicFinished()

```
void SimpleSquareMesh::GeodesicFinished (
            largecounter index,
            std::vector< real > finalValues)  [final], [virtual]
```

Function that is called when a geodesic is finished integrating.

This Mesh doesn't actually have to do anything with the geodesic (values) when it is done!

Parameters

index	index of the geodesic that is finished
finalValues	final values of the geodesic

Implements Mesh.

6.42.3.3 getCurNrGeodesics()

```
largecounter SimpleSquareMesh::getCurNrGeodesics () const  [final], [virtual]
```

Get the current number of geodesics to be integrated.

This is the total number of pixels in the grid

Returns

largecounter

Implements Mesh.

6.42.3.4 getFullDescriptionStr()

```
std::string SimpleSquareMesh::getFullDescriptionStr () const  [final], [virtual]
```

Description string getter.

Returns

std::string

Reimplemented from Mesh.

6.42.3.5 getNewInitConds()

```
void SimpleSquareMesh::getNewInitConds (
            largecounter index,
            ScreenPoint & newunitpoint,
            ScreenIndex & newscreenindex) const  [final], [virtual]
```

Get the initial conditions for the next pixel to be integrated.

The next pixel is the one with index m_CurrentPixel

Parameters

index	index of the pixel to be initialized
newunitpoint	new unit point to be initialized
newscreenindex	new screen index to be initialized

Implements Mesh.

6.42.3.6 IsFinished()

```
bool SimpleSquareMesh::IsFinished () const  [final], [virtual]
```

Check whether the Mesh is finished integrating.

We are done if we have sent all pixels to be integrated (there is only one iteration of pixels)

Returns

true

false

Implements Mesh.

6.42.4 Member Data Documentation

6.42.4.1 m_Finished

```
bool SimpleSquareMesh::m_Finished {false}  [private]
```

Are we done integrating or not?

6.42.4.2 m_RowColumnSize

```
const pixelcoord SimpleSquareMesh::m_RowColumnSize  [private]
```

Amount of pixels per row or column (square grid)

6.42.4.3 m_TotalPixels

```
const largecounter SimpleSquareMesh::m_TotalPixels  [private]
```

Total amount of pixels in grid (is the square of m_RowColumnSize)

The documentation for this class was generated from the following files:


- FOORT/src/Mesh.h
- FOORT/src/Mesh.cpp

6.43 SingularityMetric Class Reference

Abstract base class for a metric with an arbitrary number of singularities (of arbitrary codimension)

`#include <Metric.h>`

Inheritance diagram for SingularityMetric:



Public Member Functions

- SingularityMetric (std::vector< Singularity > thesings, bool rLogScale)

  Construct a new Singularity Metric object.
- std::vector< Singularity > getSingularities () const

  Getters for the singularities.

Public Member Functions inherited from Metric

- virtual ~Metric ()=default
- Metric (bool rlogscale=false)

  Construct a new Metric object.
- virtual TwoIndex getMetric_dd (const Point &p) const =0
- virtual TwoIndex getMetric_uu (const Point &p) const =0
- virtual ThreeIndex getChristoffel_udd (const Point &p) const

  Return the Christoffel symbols of the metric (indices up, down, down)
- virtual FourIndex getRiemann_uddd (const Point &p) const

  Riemann tensor of the metric (indices up, down, down, down)
- virtual real getKretschmann (const Point &p) const

  Get the Kretschmann scalar at a point.
- virtual std::string getFullDescriptionStr () const

  Base class description string getter.
- bool getrLogScale () const

  Get whether we are using a logarithmic radial scale.

Protected Attributes

- const std::vector< Singularity > m_AllSingularities

  All singularities of the metric.

Protected Attributes inherited from Metric

- std::vector< int > m_Symmetries {}

  The symmetries (coordinate Killing vectors) of the metric. Should be set by descendant constructor.
- const bool m_rLogScale

  Are we using a logarithmic r coordinate?

6.43.1 Detailed Description

Abstract base class for a metric with an arbitrary number of singularities (of arbitrary codimension)

6.43.2 Constructor & Destructor Documentation

6.43.2.1 SingularityMetric()

```
SingularityMetric::SingularityMetric (
            std::vector< Singularity > thesings,
            bool rLogScale)
```

Construct a new Singularity Metric object.

Parameters

thesings	The singularities to include in the metric
rLogScale	whether we are using a logarithmic radial scale

6.43.3 Member Function Documentation

6.43.3.1 getSingularities()

```
std::vector< Singularity > SingularityMetric::getSingularities () const
```

Getters for the singularities.

Returns

std::vector<Singularity>

6.43.4 Member Data Documentation

6.43.4.1 m_AllSingularities

```
const std::vector<Singularity> SingularityMetric::m_AllSingularities  [protected]
```

All singularities of the metric.

The documentation for this class was generated from the following files:


- FOORT/src/Metric.h
- FOORT/src/Metric.cpp

6.44 Source Class Reference

Abstract Source base class.

```
#include <Geodesic.h>
```

Inheritance diagram for Source:



Public Member Functions

- Source (const Metric ∗const theMetric)
- virtual ∼Source ()=default
- virtual OneIndex getSource (Point pos, OneIndex vel) const =0
- virtual std::string getFullDescriptionStr () const

  Basic full description string getter for Source base class.

Protected Attributes

- const Metric ∗const m_theMetric

  A const pointer to a const metric.

6.44.1 Detailed Description

Abstract Source base class.

6.44.2 Constructor & Destructor Documentation

6.44.2.1 Source()

```
Source::Source (
            const Metric *const theMetric)  [inline]
```

6.44.2.2 ∼Source()

```
virtual Source::~Source ()  [virtual], [default]
```

6.44.3 Member Function Documentation

6.44.3.1 getFullDescriptionStr()

```
std::string Source::getFullDescriptionStr () const  [virtual]
```

Basic full description string getter for Source base class.

Returns

std::string

Reimplemented in NoSource.

6.44.3.2 getSource()

```
virtual OneIndex Source::getSource (
            Point pos,
            OneIndex vel) const  [pure virtual]
```

Implemented in NoSource.

6.44.4 Member Data Documentation

6.44.4.1 m_theMetric

```
const Metric* const Source::m_theMetric  [protected]
```

A const pointer to a const metric.

The documentation for this class was generated from the following files:


- FOORT/src/Geodesic.h
- FOORT/src/Geodesic.cpp

6.45 SphericalHorizonMetric Class Reference

Abstract base class for a metric with a spherical horizon (i.e. horizon at constant radius r)

```
#include <Metric.h>
```

Inheritance diagram for SphericalHorizonMetric:



Public Member Functions

- SphericalHorizonMetric ()=delete
- SphericalHorizonMetric (real HorizonRadius, bool rLogScale)

  Construct a new Spherical Horizon Metric object.
- real getHorizonRadius () const

  Get the radius of the horizon.

Public Member Functions inherited from Metric

- virtual ~Metric ()=default
- Metric (bool rlogscale=false)

  Construct a new Metric object.
- virtual TwoIndex getMetric_dd (const Point &p) const =0
- virtual TwoIndex getMetric_uu (const Point &p) const =0
- virtual ThreeIndex getChristoffel_udd (const Point &p) const

  Return the Christoffel symbols of the metric (indices up, down, down)
- virtual FourIndex getRiemann_uddd (const Point &p) const

  Riemann tensor of the metric (indices up, down, down, down)
- virtual real getKretschmann (const Point &p) const

  Get the Kretschmann scalar at a point.
- virtual std::string getFullDescriptionStr () const

  Base class description string getter.
- bool getrLogScale () const

  Get whether we are using a logarithmic radial scale.

Protected Attributes

- const real m_HorizonRadius

  Radius of the horizon.

Protected Attributes inherited from Metric

- std::vector< int > m_Symmetries {}

  The symmetries (coordinate Killing vectors) of the metric. Should be set by descendant constructor.
- const bool m_rLogScale

  Are we using a logarithmic r coordinate?

6.45.1 Detailed Description

Abstract base class for a metric with a spherical horizon (i.e. horizon at constant radius r)

6.45.2 Constructor & Destructor Documentation

6.45.2.1 SphericalHorizonMetric() [1/2]

```
SphericalHorizonMetric::SphericalHorizonMetric ()  [delete]
```

6.45.2.2 SphericalHorizonMetric() [2/2]

```
SphericalHorizonMetric::SphericalHorizonMetric (
            real HorizonRadius,
            bool rLogScale)
```

Construct a new Spherical Horizon Metric object.

Parameters

HorizonRadius	Radius of the horizon
rLogScale	Whether we are using a logarithmic radial scale

6.45.3 Member Function Documentation

6.45.3.1 getHorizonRadius()

```
real SphericalHorizonMetric::getHorizonRadius () const
```

Get the radius of the horizon.

Returns

real

6.45.4 Member Data Documentation

6.45.4.1 m_HorizonRadius

```
const real SphericalHorizonMetric::m_HorizonRadius  [protected]
```

Radius of the horizon.

The documentation for this class was generated from the following files:

- FOORT/src/Metric.h
- FOORT/src/Metric.cpp

6.46 tk::spline Class Reference

```
#include <Spline.h>
```

Public Types

- enum spline_type { linear = 10 , cspline = 30 , cspline_hermite = 31 }
- enum bd_type { first_deriv = 1 , second_deriv = 2 }

Public Member Functions

- spline ()
- spline (const std::vector< double > &X, const std::vector< double > &Y, spline_type type=cspline, bool make_monotonic=false, bd_type left=second_deriv, double left_value=0.0, bd_type right=second_deriv, double right_value=0.0)
- void set_boundary (bd_type left, double left_value, bd_type right, double right_value)
- void set_points (const std::vector< double > &x, const std::vector< double > &y, spline_type type=cspline)
- bool make_monotonic ()
- double operator() (double x) const
- double deriv (int order, double x) const
- std::vector< double > get_x () const
- std::vector< double > get_y () const
- double get_x_min () const
- double get_x_max () const

Protected Member Functions

- void set_coeffs_from_b ()
- size_t find_closest (double x) const

Protected Attributes

- std::vector< double > m_x
- std::vector< double > m_y
- std::vector< double > m_b
- std::vector< double > m_c
- std::vector< double > m_d
- double m_c0
- spline_type m_type
- bd_type m_left
- bd_type m_right
- double m_left_value
- double m_right_value
- bool m_made_monotonic

6.46.1 Member Enumeration Documentation

6.46.1.1 bd_type

`enum tk::spline::bd_type`

Enumerator

first_deriv	
second_deriv	

6.46.1.2 spline_type

`enum tk::spline::spline_type`

Enumerator

linear	
cspline	
cspline_hermite	

6.46.2 Constructor & Destructor Documentation

6.46.2.1 spline() [1/2]

```
tk::spline::spline ()
```

6.46.2.2 spline() [2/2]

```
tk::spline::spline (
            const std::vector< double > & X,
            const std::vector< double > & Y,
            spline_type type = cspline,
            bool make_monotonic = false,
            bd_type left = second_deriv,
            double left_value = 0.0,
            bd_type right = second_deriv,
            double right_value = 0.0)
```

6.46.3 Member Function Documentation

6.46.3.1 deriv()

```
double tk::spline::deriv (
            int order,
            double x) const
```

6.46.3.2 find_closest()

```
size_t tk::spline::find_closest (
            double x) const  [protected]
```

6.46.3.3 get_x()

```
std::vector< double > tk::spline::get_x () const
```

6.46.3.4 get_x_max()

```
double tk::spline::get_x_max () const
```

6.46.3.5 get_x_min()

```
double tk::spline::get_x_min () const
```

6.46.3.6 get_y()

```
std::vector< double > tk::spline::get_y () const
```

6.46.3.7 make_monotonic()

```
bool tk::spline::make_monotonic ()
```

6.46.3.8 operator()()

```
double tk::spline::operator() (
            double x) const
```

6.46.3.9 set_boundary()

```
void tk::spline::set_boundary (
            spline::bd_type left,
            double left_value,
            spline::bd_type right,
            double right_value)
```

6.46.3.10 set_coeffs_from_b()

```
void tk::spline::set_coeffs_from_b ()  [protected]
```

6.46.3.11 set_points()

```
void tk::spline::set_points (
            const std::vector< double > & x,
            const std::vector< double > & y,
            spline_type type = cspline)
```

6.46.4 Member Data Documentation

6.46.4.1 m_b

```
std::vector<double> tk::spline::m_b  [protected]
```

6.46.4.2 m_c

```
std::vector<double> tk::spline::m_c  [protected]
```

6.46.4.3 m_c0

```
double tk::spline::m_c0  [protected]
```

6.46.4.4 m_d

```
std::vector<double> tk::spline::m_d  [protected]
```

6.46.4.5 m_left

```
bd_type tk::spline::m_left  [protected]
```

6.46.4.6 m_left_value

```
double tk::spline::m_left_value  [protected]
```

6.46.4.7 m_made_monotonic

```
bool tk::spline::m_made_monotonic  [protected]
```

6.46.4.8 m_right

```
bd_type tk::spline::m_right  [protected]
```

6.46.4.9 m_right_value

```
double tk::spline::m_right_value  [protected]
```

6.46.4.10 m_type

```
spline_type tk::spline::m_type  [protected]
```

6.46.4.11 m_x

```
std::vector<double> tk::spline::m_x  [protected]
```

6.46.4.12 m_y

```
std::vector<double> tk::spline::m_y  [protected]
```

The documentation for this class was generated from the following files:


- FOORT/src/Spline.h
- FOORT/src/Spline.cpp

6.47 SquareSubdivisionMesh Class Reference

Adaptive subdivision Mesh.

```
#include <Mesh.h>
```

Inheritance diagram for SquareSubdivisionMesh:



Classes

- struct PixelInfo

  A struct the Mesh uses to keep all information about a given pixel.

Public Member Functions

- SquareSubdivisionMesh ()=delete
- SquareSubdivisionMesh (largecounter maxPixels, largecounter initialPixels, int maxSubdivide, largecounter iterationPixels, bool initialSubToFinal, DiagBitflag valdiag)
- largecounter getCurNrGeodesics () const final

  Return the current number of geodesics to be integrated.
- void getNewInitConds (largecounter index, ScreenPoint &newunitpoint, ScreenIndex &newscreenindex) const final

  Get the initial conditions for the next pixel to be integrated.
- void GeodesicFinished (largecounter index, std::vector< real > finalValues) final

  Called when a geodesic is finished integrating: the final values are stored.
- void EndCurrentLoop () final

  Called at the end of each integration iteration loop. Wraps up the current iteration and initializes the next one.
- bool IsFinished () const final

  Check whether the Mesh is finished integrating.
- std::string getFullDescriptionStr () const final

  Description string getter.

Public Member Functions inherited from Mesh

- Mesh (DiagBitflag valdiag)
- virtual ~Mesh ()=default

Private Member Functions

- void InitializeFirstGrid ()

  Helper function to initialize the first grid of pixels to integrate.
- void UpdateAllWeights ()

  Helper function to update all pixel weights in m_CurrentPixelUpdating.
- PixelInfo * GetUp (PixelInfo *p, int subdiv) const

  Get the upper neighbor of a pixel at a certain subdivision level.
- PixelInfo * GetDown (PixelInfo *p, int subdiv) const

  Get the lower neighbor of a pixel at a certain subdivision level.
- PixelInfo * GetRight (PixelInfo *p, int subdiv) const

  Get the right neighbor of a pixel at a certain subdivision level.
- PixelInfo * GetLeft (PixelInfo *p, int subdiv) const

  Get the left neighbor of a pixel at a certain subdivision level.
- void SubdivideAndQueue (largecounter ind)

  Subdivide the pixel at index ind and add up to 5 new pixels to the integration queue.
- pixelcoord ExpInt (int base, int exp) const

  Helper function to exponentiate ints.

Private Attributes

- const largecounter m_InitialPixels

  How many initial pixels (spread uniformly over the grid) do we integrate?
- const int m_MaxSubdivide

  How many times are we allowed to subdivide a square? Note: the initial grid is already at 1.
- const pixelcoord m_RowColumnSize

  The total size in pixels of a row or column (square grid)
- const largecounter m_IterationPixels

  How many pixels per iteration can we subdivide?
- const largecounter m_MaxPixels

  How many pixels can we integrate in total over all iterations?
- const bool m_InitialSubDividideToFinal

  If we decide to subdivide a square, do we automatically subdivide it further to the max level?
- const bool m_InfinitePixels

  Are we allowed to integrate as many pixels as we want? (m_MaxPixels == 0)
- largecounter m_PixelsLeft

  How many pixels are we still allowed to integrate (if !m_InfinitePixels)?
- largecounter m_PixelsIntegrated {0}

  How many pixels we have integrated so far.
- std::forward_list< std::unique_ptr< PixelInfo > > m_AllPixels {}

  Master list of all pixels. std::forward_list is more space-efficient than std::list, bidirectional iteration is not needed, no random access supported. This list is only used to store the owner pointers (and thus the objects) of all pixels. The other pixel vectors are used to iterate through (and need random access)
- std::vector< PixelInfo * > m_ActivePixels {}

  List of active pixels, i.e. those that can be subdivided and have non-zero weight.

- std::vector< PixelInfo * > m_CurrentPixelQueue {}

  List of current queue of pixels to be sent to be integrated.
- std::vector< char > m_CurrentPixelQueueDone {}

  A bool for every pixel in the current queue: gets set to true when the pixel is done integrating and gets its values returned.
- std::vector< PixelInfo * > m_CurrentPixelUpdating {}

  List of pixels that are already integrated but need updating weights after current queue is all integrated.

Additional Inherited Members

Protected Attributes inherited from Mesh

- const std::unique_ptr< const Diagnostic > m_DistanceDiagnostic

  The Diagnostic (a const pointer to a const Diagnostic object) that is used to calculate distances (using FinalData↩ ValDistance()) between the "values" that are assigned to Geodesics.

6.47.1 Detailed Description

Adaptive subdivision Mesh.

starts with evenly spaced, square Mesh, then decides to subdivide certain squares of pixels into smaller squares, based on which pixels have a bigger "weight", which is defined as the maximum "distance" (using the Diagnostic value distance) between the upper-left vertex of the square with the other three vertices of the square. (Note: this is V2 of the Mesh, with a new way of dealing with neighbors and looping over pixels compared to V1 which is no longer implemented in FOORT.)

6.47.2 Constructor & Destructor Documentation

6.47.2.1 SquareSubdivisionMesh() [1/2]

```
SquareSubdivisionMesh::SquareSubdivisionMesh ()  [delete]
```

6.47.2.2 SquareSubdivisionMesh() [2/2]

```
SquareSubdivisionMesh::SquareSubdivisionMesh (
            largecounter maxPixels,
            largecounter initialPixels,
            int maxSubdivide,
            largecounter iterationPixels,
            bool initialSubToFinal,
            DiagBitflag valdiag)  [inline]
```

6.47.3 Member Function Documentation

6.47.3.1 EndCurrentLoop()

```
void SquareSubdivisionMesh::EndCurrentLoop ()  [final], [virtual]
```

Called at the end of each integration iteration loop. Wraps up the current iteration and initializes the next one.

Implements Mesh.

6.47.3.2 ExpInt()

```
pixelcoord SquareSubdivisionMesh::ExpInt (
            int base,
            int exp) const  [private]
```

Helper function to exponentiate ints.

Note

The result may be larger than fits in an int, but this is only called with int arguments

Parameters

base	base
exp	exponent

Returns

pixelcoord

6.47.3.3 GeodesicFinished()

```
void SquareSubdivisionMesh::GeodesicFinished (
            largecounter index,
            std::vector< real > finalValues)  [final], [virtual]
```

Called when a geodesic is finished integrating: the final values are stored.

Parameters

index	index of the geodesic that is finished
finalValues	final values of the diagnostics

Implements Mesh.

6.47.3.4 getCurNrGeodesics()

```
largecounter SquareSubdivisionMesh::getCurNrGeodesics () const  [final], [virtual]
```

Return the current number of geodesics to be integrated.

Returns

largecounter

Implements Mesh.

6.47.3.5 GetDown()

```
SquareSubdivisionMesh::PixelInfo * SquareSubdivisionMesh::GetDown (
            PixelInfo * p,
            int subdiv) const  [private]
```

Get the lower neighbor of a pixel at a certain subdivision level.

Parameters

p	PixelInfo pointer to the pixel
subdiv	subdivision level of the neighbor

Returns

SquareSubdivisionMesh::PixelInfo*

6.47.3.6 getFullDescriptionStr()

```
std::string SquareSubdivisionMesh::getFullDescriptionStr () const  [final], [virtual]
```

Description string getter.

Returns

std::string

Reimplemented from Mesh.

6.47.3.7 GetLeft()

```
SquareSubdivisionMesh::PixelInfo * SquareSubdivisionMesh::GetLeft (
            PixelInfo * p,
            int subdiv) const  [private]
```

Get the left neighbor of a pixel at a certain subdivision level.

Parameters

p	PixelInfo pointer to the pixel
subdiv	subdivision level of the neighbor

Returns

SquareSubdivisionMesh::PixelInfo*

6.47.3.8 getNewInitConds()

```
void SquareSubdivisionMesh::getNewInitConds (
            largecounter index,
            ScreenPoint & newunitpoint,
            ScreenIndex & newscreenindex) const  [final], [virtual]
```

Get the initial conditions for the next pixel to be integrated.

The next pixel is the one with index m_CurrentPixel

Parameters

index	index of the pixel to be initialized
newunitpoint	new unit point to be initialized
newscreenindex	new screen index to be initialized

Implements Mesh.

6.47.3.9 GetRight()

```
SquareSubdivisionMesh::PixelInfo * SquareSubdivisionMesh::GetRight (
            PixelInfo * p,
            int subdiv) const  [private]
```

Get the right neighbor of a pixel at a certain subdivision level.

Parameters

p	PixelInfo pointer to the pixel
subdiv	subdivision level of the neighbor

Returns

SquareSubdivisionMesh::PixelInfo*

6.47.3.10 GetUp()

```
SquareSubdivisionMesh::PixelInfo * SquareSubdivisionMesh::GetUp (
            PixelInfo * p,
            int subdiv) const  [private]
```

Get the upper neighbor of a pixel at a certain subdivision level.

Parameters

p	PixelInfo pointer to the pixel
subdiv	subdivision level of the neighbor

Returns

SquareSubdivisionMesh::PixelInfo*

6.47.3.11 InitializeFirstGrid()

```
void SquareSubdivisionMesh::InitializeFirstGrid ()  [private]
```

Helper function to initialize the first grid of pixels to integrate.

6.47.3.12 IsFinished()

```
bool SquareSubdivisionMesh::IsFinished () const  [final], [virtual]
```

Check whether the Mesh is finished integrating.

Returns

true

false

Implements Mesh.

6.47.3.13 SubdivideAndQueue()

```
void SquareSubdivisionMesh::SubdivideAndQueue (
            largecounter ind)  [private]
```

Subdivide the pixel at index ind and add up to 5 new pixels to the integration queue.

The pixels are numbered as 1 2 3 4 5 6 7 8 9 i.e. the initial square is given by (1, 3, 7, 9), and the new pixels are (2, 4, 5, 6, 8).

Parameters

ind	index of the pixel to subdivide

6.47.3.14 UpdateAllWeights()

```
void SquareSubdivisionMesh::UpdateAllWeights ()  [private]
```

Helper function to update all pixel weights in m_CurrentPixelUpdating.

All pixels with weight $>$ 0 will be added to m_ActivePixels

Note

Assumes all pixels have subdiv $>$ 0 and subdiv $<$ m_MaxSubdivide, and all their neighbors assigned correctly

Assumes all pixels have their (and their neighbor's) values assigned correctly

6.47.4 Member Data Documentation

6.47.4.1 m_ActivePixels

```
std::vector<PixelInfo *> SquareSubdivisionMesh::m_ActivePixels {}  [private]
```

List of active pixels, i.e. those that can be subdivided and have non-zero weight.

6.47.4.2 m_AllPixels

```
std::forward_list<std::unique_ptr<PixelInfo> > SquareSubdivisionMesh::m_AllPixels {}  [private]
```

Master list of all pixels. std::forward_list is more space-efficient than std::list, bidirectional iteration is not needed, no random access supported. This list is only used to store the owner pointers (and thus the objects) of all pixels. The other pixel vectors are used to iterate through (and need random access)

6.47.4.3 m_CurrentPixelQueue

```
std::vector<PixelInfo *> SquareSubdivisionMesh::m_CurrentPixelQueue {}  [private]
```

List of current queue of pixels to be sent to be integrated.

6.47.4.4 m_CurrentPixelQueueDone

```
std::vector<char> SquareSubdivisionMesh::m_CurrentPixelQueueDone {}  [private]
```

A bool for every pixel in the current queue: gets set to true when the pixel is done integrating and gets its values returned.

6.47.4.5 m_CurrentPixelUpdating

```
std::vector<PixelInfo *> SquareSubdivisionMesh::m_CurrentPixelUpdating {}  [private]
```

List of pixels that are already integrated but need updating weights after current queue is all integrated.

6.47.4.6 m_InfinitePixels

```
const bool SquareSubdivisionMesh::m_InfinitePixels  [private]
```

Are we allowed to integrate as many pixels as we want? (m_MaxPixels == 0)

6.47.4.7 m_InitialPixels

```
const largecounter SquareSubdivisionMesh::m_InitialPixels  [private]
```

How many initial pixels (spread uniformly over the grid) do we integrate?

6.47.4.8 m_InitialSubDividideToFinal

```
const bool SquareSubdivisionMesh::m_InitialSubDividideToFinal  [private]
```

If we decide to subdivide a square, do we automatically subdivide it further to the max level?

6.47.4.9 m_IterationPixels

```
const largecounter SquareSubdivisionMesh::m_IterationPixels  [private]
```

How many pixels per iteration can we subdivide?

6.47.4.10 m_MaxPixels

```
const largecounter SquareSubdivisionMesh::m_MaxPixels  [private]
```

How many pixels can we integrate in total over all iterations?

6.47.4.11 m_MaxSubdivide

```
const int SquareSubdivisionMesh::m_MaxSubdivide  [private]
```

How many times are we allowed to subdivide a square? Note: the initial grid is already at 1.

6.47.4.12 m_PixelsIntegrated

```
largecounter SquareSubdivisionMesh::m_PixelsIntegrated {0}  [private]
```

How many pixels we have integrated so far.

6.47.4.13 m_PixelsLeft

```
largecounter SquareSubdivisionMesh::m_PixelsLeft  [private]
```

How many pixels are we still allowed to integrate (if !m_InfinitePixels)?

6.47.4.14 m_RowColumnSize

```
const pixelcoord SquareSubdivisionMesh::m_RowColumnSize  [private]
```

The total size in pixels of a row or column (square grid)

The documentation for this class was generated from the following files:


- FOORT/src/Mesh.h
- FOORT/src/Mesh.cpp

6.48 ST3CrMetric Class Reference

Ring fuzzball metric.

`#include <Metric.h>`

Inheritance diagram for ST3CrMetric:



Public Member Functions

- ST3CrMetric (real P, real q0, real lambda, bool rlogscale=false)

  Construct a new ST3Cr Metric object.
- TwoIndex getMetric_dd (const Point &p) const final

  ST3Cr metric getter, indices down.
- TwoIndex getMetric_uu (const Point &p) const final

  ST3Cr metric getter, indices up.
- std::string getFullDescriptionStr () const final

  ST3Cr metric description string getter.

Public Member Functions inherited from SingularityMetric

- SingularityMetric (std::vector< Singularity > thesings, bool rLogScale)

  Construct a new Singularity Metric object.
- std::vector< Singularity > getSingularities () const

  Getters for the singularities.

Public Member Functions inherited from Metric

- virtual ~Metric ()=default
- Metric (bool rlogscale=false)

  Construct a new Metric object.
- virtual ThreeIndex getChristoffel_udd (const Point &p) const

  Return the Christoffel symbols of the metric (indices up, down, down)
- virtual FourIndex getRiemann_uddd (const Point &p) const

  Riemann tensor of the metric (indices up, down, down, down)
- virtual real getKretschmann (const Point &p) const

  Get the Kretschmann scalar at a point.
- bool getrLogScale () const

  Get whether we are using a logarithmic radial scale.

Private Member Functions

- real get_omega (real r, real theta, real l) const

  Get omega for the ST3Cr metric.
- real f_phi (real phi, real r, real theta, real l, real R) const

  *function for prefactor * dphi' for ring*
- real f_om_phi (real phi, real r, real theta, real l, real R) const

  omega_phi ring functions

Private Attributes

- const real m_P
- const real m_q0
- const real m_lambda

Additional Inherited Members

Protected Attributes inherited from SingularityMetric

- const std::vector< Singularity > m_AllSingularities

  All singularities of the metric.

Protected Attributes inherited from Metric

- std::vector< int > m_Symmetries {}

  The symmetries (coordinate Killing vectors) of the metric. Should be set by descendant constructor.
- const bool m_rLogScale

  Are we using a logarithmic r coordinate?

6.48.1 Detailed Description

Ring fuzzball metric.

Note

Implementation by Lies Van Dael

6.48.2 Constructor & Destructor Documentation

6.48.2.1 ST3CrMetric()

```
ST3CrMetric::ST3CrMetric (
            real P,
            real q0,
            real lambda,
            bool rlogscale = false)
```

Construct a new ST3Cr Metric object.

Parameters

P	P parameter for the ST3Cr metric
q0	q0 parameter for the ST3Cr metric
lambda	lambda parameter for the ST3Cr metric
rlogscale	whether we are using a logarithmic radial scale

6.48.3 Member Function Documentation

6.48.3.1 f_om_phi()

```
real ST3CrMetric::f_om_phi (
            real phi,
            real r,
            real theta,
            real l,
            real R) const  [private]
```

omega_phi ring functions

Parameters

phi	
r	
theta	
l	
R	

Returns

real

6.48.3.2 f_phi()

```
real ST3CrMetric::f_phi (
            real phi,
            real r,
            real theta,
            real l,
            real R) const  [private]
```

function for prefactor $*$ dphi' for ring

Parameters

phi	
r	
theta	
l	
R	

Returns

real

6.48.3.3 get_omega()

```
real ST3CrMetric::get_omega (
            real r,
            real theta,
            real l) const  [private]
```

Get omega for the ST3Cr metric.

Parameters

r	r_ij
theta	theta_ij
l	l_ij

Returns

real

6.48.3.4 getFullDescriptionStr()

```
std::string ST3CrMetric::getFullDescriptionStr () const  [final], [virtual]
```

ST3Cr metric description string getter.

Returns

std::string

Reimplemented from Metric.

6.48.3.5 getMetric_dd()

```
TwoIndex ST3CrMetric::getMetric_dd (
            const Point & p) const  [final], [virtual]
```

ST3Cr metric getter, indices down.

Parameters

p	Point at which to evaluate the metric

Returns

TwoIndex

Implements Metric.

6.48.3.6 getMetric_uu()

```
TwoIndex ST3CrMetric::getMetric_uu (
            const Point & p) const  [final], [virtual]
```

ST3Cr metric getter, indices up.

Parameters

p	Point at which to evaluate the metric

Returns

TwoIndex

Implements Metric.

6.48.4 Member Data Documentation

6.48.4.1 m_lambda

```
const real ST3CrMetric::m_lambda  [private]
```

6.48.4.2 m_P

```
const real ST3CrMetric::m_P  [private]
```

6.48.4.3 m_q0

```
const real ST3CrMetric::m_q0  [private]
```

The documentation for this class was generated from the following files:


- FOORT/src/Metric.h
- FOORT/src/Metric.cpp

6.49 Termination Class Reference

Abstract base class for all Terminations.

```
#include <Terminations.h>
```

Inheritance diagram for Termination:



Public Member Functions

- Termination ()=delete
- Termination (Geodesic ∗const theGeodesic)
- virtual void Reset ()

  Reset to 0 to start integrating a new geodesic.
- virtual ∼Termination ()=default
- virtual Term CheckTermination ()=0
- virtual std::string getFullDescriptionStr () const =0

Protected Member Functions

- bool DecideUpdate (largecounter UpdateNSteps)

  Returns true if the Termination should update its internal status.

Protected Attributes

- Geodesic ∗const m_OwnerGeodesic

  The geodesic that owns the Termination (a const pointer to the Geodesic)
- largecounter m_StepsSinceUpdated {}

  The termination is itself in charge of keeping track of how many steps it has been since it has been updated. The Termination's TerminationOptions struct tells it how many steps it needs to wait between updates.

6.49.1 Detailed Description

Abstract base class for all Terminations.

6.49.2 Constructor & Destructor Documentation

6.49.2.1 Termination() [1/2]

```
Termination::Termination ()  [delete]
```

6.49.2.2 Termination() [2/2]

```
Termination::Termination (
            Geodesic *const theGeodesic)  [inline]
```

6.49.2.3 ∼Termination()

```
virtual Termination::~Termination ()  [virtual], [default]
```

6.49.3 Member Function Documentation

6.49.3.1 CheckTermination()

```
virtual Term Termination::CheckTermination ()  [pure virtual]
```

Implemented in BoundarySphereTermination, GeneralSingularityTermination, HorizonTermination, NaNTermination, ThetaSingularityTermination, and TimeOutTermination.

6.49.3.2 DecideUpdate()

```
bool Termination::DecideUpdate (
            largecounter UpdateNSteps)  [protected]
```

Returns true if the Termination should update its internal status.

Should be called from within CheckTermination() with the appropriate TermOptions::UpdateEveryNSteps

Parameters

UpdateNSteps	the number of steps after which the terminations should be updated

Returns

true

false

6.49.3.3 getFullDescriptionStr()

```
virtual std::string Termination::getFullDescriptionStr () const  [pure virtual]
```

Implemented in BoundarySphereTermination, GeneralSingularityTermination, HorizonTermination, NaNTermination, ThetaSingularityTermination, and TimeOutTermination.

6.49.3.4 Reset()

```
void Termination::Reset ()  [virtual]
```

Reset to 0 to start integrating a new geodesic.

Reimplemented in TimeOutTermination.

6.49.4 Member Data Documentation

6.49.4.1 m_OwnerGeodesic

```
Geodesic* const Termination::m_OwnerGeodesic  [protected]
```

The geodesic that owns the Termination (a const pointer to the Geodesic)

6.49.4.2 m_StepsSinceUpdated

```
largecounter Termination::m_StepsSinceUpdated {}  [protected]
```

The termination is itself in charge of keeping track of how many steps it has been since it has been updated. The Termination's TerminationOptions struct tells it how many steps it needs to wait between updates.

The documentation for this class was generated from the following files:


- FOORT/src/Terminations.h
- FOORT/src/Terminations.cpp

6.50 TerminationOptions Struct Reference

Base class for all TerminationOptions structs. Other TerminationOptions can inherit from here if they require more options.

```
#include <Terminations.h>
```

Inheritance diagram for TerminationOptions:



Public Member Functions

- TerminationOptions (largecounter Nsteps)
- virtual ~TerminationOptions ()=default

Public Attributes

- const largecounter UpdateEveryNSteps

  Number of steps between updates.

6.50.1 Detailed Description

Base class for all TerminationOptions structs. Other TerminationOptions can inherit from here if they require more options.

6.50.2 Constructor & Destructor Documentation

6.50.2.1 TerminationOptions()

```
TerminationOptions::TerminationOptions (
            largecounter Nsteps)  [inline]
```

6.50.2.2 ~TerminationOptions()

```
virtual TerminationOptions::~TerminationOptions ()  [virtual], [default]
```

6.50.3 Member Data Documentation

6.50.3.1 UpdateEveryNSteps

```
const largecounter TerminationOptions::UpdateEveryNSteps
```

Number of steps between updates.

The documentation for this struct was generated from the following file:


- FOORT/src/Terminations.h

6.51 ThetaSingularityTermination Class Reference

ThetaSingularityTermination: Terminate geodesics if they get too close to a polar coordinate singularity.

```
#include <Terminations.h>
```

Inheritance diagram for ThetaSingularityTermination:



Public Member Functions

- ThetaSingularityTermination (Geodesic *const theGeodesic)
- Term CheckTermination () final

  Check if the geodesic is too close to a pole.
- std::string getFullDescriptionStr () const final

  Description string getter for the Theta Singularity Termination.

Public Member Functions inherited from Termination

- Termination ()=delete
- Termination (Geodesic *const theGeodesic)
- virtual void Reset ()

  Reset to 0 to start integrating a new geodesic.
- virtual ~Termination ()=default

Static Public Attributes

- static std::unique_ptr< ThetaSingularityTermOptions > TermOptions

  The options that the Termination keeps (will probably be a descendant struct instead, which specifies any additional options the Termination needs)

Additional Inherited Members

Protected Member Functions inherited from Termination

- bool DecideUpdate (largecounter UpdateNSteps)

  Returns true if the Termination should update its internal status.

Protected Attributes inherited from Termination

- Geodesic *const m_OwnerGeodesic

  The geodesic that owns the Termination (a const pointer to the Geodesic)
- largecounter m_StepsSinceUpdated {}

  The termination is itself in charge of keeping track of how many steps it has been since it has been updated. The Termination's TerminationOptions struct tells it how many steps it needs to wait between updates.

6.51.1 Detailed Description

ThetaSingularityTermination: Terminate geodesics if they get too close to a polar coordinate singularity.

6.51.2 Constructor & Destructor Documentation

6.51.2.1 ThetaSingularityTermination()

```
ThetaSingularityTermination::ThetaSingularityTermination (
            Geodesic *const theGeodesic)  [inline]
```

6.51.3 Member Function Documentation

6.51.3.1 CheckTermination()

```
Term ThetaSingularityTermination::CheckTermination ()  [final], [virtual]
```

Check if the geodesic is too close to a pole.

Returns

Term

Implements Termination.

6.51.3.2 getFullDescriptionStr()

```
std::string ThetaSingularityTermination::getFullDescriptionStr () const  [final], [virtual]
```

Description string getter for the Theta Singularity Termination.

Returns

std::string

Implements Termination.

6.51.4 Member Data Documentation

6.51.4.1 TermOptions

```
std::unique_ptr< ThetaSingularityTermOptions > ThetaSingularityTermination::TermOptions  [static]
```

The options that the Termination keeps (will probably be a descendant struct instead, which specifies any additional options the Termination needs)

The documentation for this class was generated from the following files:


- FOORT/src/Terminations.h
- FOORT/src/Config.cpp
- FOORT/src/Terminations.cpp

6.52 ThetaSingularityTermOptions Struct Reference

Options for ThetaSingularityTermination.

```
#include <Terminations.h>
```

Inheritance diagram for ThetaSingularityTermOptions:



Public Member Functions

- ThetaSingularityTermOptions (real epsilon, largecounter Nsteps)

Public Member Functions inherited from TerminationOptions

- TerminationOptions (largecounter Nsteps)
- virtual ~TerminationOptions ()=default

Public Attributes

- const real ThetaSingEpsilon

  Minimum difference between theta and 0 or pi.

Public Attributes inherited from TerminationOptions

- const largecounter UpdateEveryNSteps

  Number of steps between updates.

6.52.1 Detailed Description

Options for ThetaSingularityTermination.

Keeps track of the minimum required distance from the singularity

6.52.2 Constructor & Destructor Documentation

6.52.2.1 ThetaSingularityTermOptions()

```
ThetaSingularityTermOptions::ThetaSingularityTermOptions (
            real epsilon,
            largecounter Nsteps)  [inline]
```

6.52.3 Member Data Documentation

6.52.3.1 ThetaSingEpsilon

```
const real ThetaSingularityTermOptions::ThetaSingEpsilon
```

Minimum difference between theta and 0 or pi.

The documentation for this struct was generated from the following file:


- FOORT/src/Terminations.h

6.53 TimeOutTermination Class Reference

TimeOutTermination: Terminate geodesics if they take too many steps.

```
#include <Terminations.h>
```

Inheritance diagram for TimeOutTermination:



Public Member Functions

- TimeOutTermination (Geodesic ∗const theGeodesic)
- void Reset () final

  Reset m_CurNrSteps to 0 for new geodesic, and call base class implementation to reset base class member variables.
- Term CheckTermination () final

  Check if the geodesic has taken too many steps.
- std::string getFullDescriptionStr () const final

  Description string getter for the Time Out Termination.

Public Member Functions inherited from Termination

- Termination ()=delete
- Termination (Geodesic ∗const theGeodesic)
- virtual ∼Termination ()=default

Static Public Attributes

- static std::unique_ptr< TimeOutTermOptions > TermOptions

  The options that the TimeOutTermination keeps (contains max number of steps allowed)

Private Attributes

- largecounter m_CurNrSteps {0}

  Keep track of the number of steps that the geodesic has taken so far.

Additional Inherited Members

Protected Member Functions inherited from Termination

- bool DecideUpdate (largecounter UpdateNSteps)

  Returns true if the Termination should update its internal status.

Protected Attributes inherited from Termination

- Geodesic ∗const m_OwnerGeodesic

  The geodesic that owns the Termination (a const pointer to the Geodesic)
- largecounter m_StepsSinceUpdated {}

  The termination is itself in charge of keeping track of how many steps it has been since it has been updated. The Termination's TerminationOptions struct tells it how many steps it needs to wait between updates.

6.53.1 Detailed Description

TimeOutTermination: Terminate geodesics if they take too many steps.

6.53.2 Constructor & Destructor Documentation

6.53.2.1 TimeOutTermination()

```
TimeOutTermination::TimeOutTermination (
            Geodesic *const theGeodesic)  [inline]
```

6.53.3 Member Function Documentation

6.53.3.1 CheckTermination()

```
Term TimeOutTermination::CheckTermination ()  [final], [virtual]
```

Check if the geodesic has taken too many steps.

Returns

Term

Implements Termination.

6.53.3.2 getFullDescriptionStr()

```
std::string TimeOutTermination::getFullDescriptionStr () const  [final], [virtual]
```

Description string getter for the Time Out Termination.

Returns

std::string

Implements Termination.

6.53.3.3 Reset()

```
void TimeOutTermination::Reset ()  [final], [virtual]
```

Reset m_CurNrSteps to 0 for new geodesic, and call base class implementation to reset base class member variables.

Reimplemented from Termination.

6.53.4 Member Data Documentation

6.53.4.1 m_CurNrSteps

```
largecounter TimeOutTermination::m_CurNrSteps {0}  [private]
```

Keep track of the number of steps that the geodesic has taken so far.

6.53.4.2 TermOptions

```
std::unique_ptr< TimeOutTermOptions > TimeOutTermination::TermOptions  [static]
```

The options that the TimeOutTermination keeps (contains max number of steps allowed)

The documentation for this class was generated from the following files:


- FOORT/src/Terminations.h
- FOORT/src/Config.cpp
- FOORT/src/Terminations.cpp

6.54 TimeOutTermOptions Struct Reference

Options for TimeOutTermination.

```
#include <Terminations.h>
```

Inheritance diagram for TimeOutTermOptions:



Public Member Functions

- TimeOutTermOptions (largecounter MaxStepsAllowed, largecounter Nsteps)

Public Member Functions inherited from TerminationOptions

- TerminationOptions (largecounter Nsteps)
- virtual ~TerminationOptions ()=default

Public Attributes

- const largecounter MaxSteps

  Max. number of integration steps allowed.

Public Attributes inherited from TerminationOptions

- const largecounter UpdateEveryNSteps

  Number of steps between updates.

6.54.1 Detailed Description

Options for TimeOutTermination.

Keeps track of the max. number of integration steps allowed

6.54.2 Constructor & Destructor Documentation

6.54.2.1 TimeOutTermOptions()

```
TimeOutTermOptions::TimeOutTermOptions (
            largecounter MaxStepsAllowed,
            largecounter Nsteps)  [inline]
```

6.54.3 Member Data Documentation

6.54.3.1 MaxSteps

```
const largecounter TimeOutTermOptions::MaxSteps
```

Max. number of integration steps allowed.

The documentation for this struct was generated from the following file:

- FOORT/src/Terminations.h

6.55 Utilities::Timer Class Reference

Timer class to keep track of elapsed time.

```
#include <Utilities.h>
```

Public Member Functions

- void reset ()

  Reset begin time.
- double elapsed () const

  Returns time elapsed since begin time.

Private Types

- using Clock = std::chrono::steady_clock

  Type alias to make accessing nested type easier.
- using Second = std::chrono::duration<double, std::ratio<1>>

  Type alias to make accessing nested type easier.

Private Attributes

- std::chrono::time_point< Clock > m_beg {Clock::now()}
  begin time

6.55.1 Detailed Description

Timer class to keep track of elapsed time.

6.55.2 Member Typedef Documentation

6.55.2.1 Clock

```
using Utilities::Timer::Clock = std::chrono::steady_clock  [private]
```

Type alias to make accessing nested type easier.

6.55.2.2 Second

```
using Utilities::Timer::Second = std::chrono::duration<double, std::ratio<1>>  [private]
```

Type alias to make accessing nested type easier.

6.55.3 Member Function Documentation

6.55.3.1 elapsed()

```
double Utilities::Timer::elapsed () const
```

Returns time elapsed since begin time.

Returns

double

6.55.3.2 reset()

```
void Utilities::Timer::reset ()
```

Reset begin time.

6.55.4 Member Data Documentation

6.55.4.1 m_beg

```
std::chrono::time_point<Clock> Utilities::Timer::m_beg {Clock::now()}  [private]
```

begin time

The documentation for this class was generated from the following files:

- FOORT/src/Utilities.h
- FOORT/src/Utilities.cpp

6.56 UpdateFrequency Struct Reference

Struct to hold the information for a Diagnostic to update itself.

```
#include <Diagnostics.h>
```

Public Attributes

- largecounter UpdateNSteps {0}
- bool UpdateStart {false}
- bool UpdateFinish {false}

6.56.1 Detailed Description

Struct to hold the information for a Diagnostic to update itself.

If UpdateNsteps $>$ 0, then every so many steps. If UpdateNSteps == 0, then it only updates at the start and/or finish of integration if the appropriate bool is set.

6.56.2 Member Data Documentation

6.56.2.1 UpdateFinish

```
bool UpdateFrequency::UpdateFinish {false}
```

6.56.2.2 UpdateNSteps

```
largecounter UpdateFrequency::UpdateNSteps {0}
```

6.56.2.3 UpdateStart

```
bool UpdateFrequency::UpdateStart {false}
```

The documentation for this struct was generated from the following file:

- FOORT/src/Diagnostics.h

6.57 ViewScreen Class Reference

This class is in charge of converting a pixel on the screen into physical initial conditions for a geodesic.

```
#include <ViewScreen.h>
```

Public Member Functions

- ViewScreen ()=delete
- ViewScreen (Point pos, OneIndex dir, ScreenPoint screensize, ScreenPoint screencenter, std::unique_ptr< Mesh > theMesh, const Metric *const theMetric, GeodesicType thegeodtype=GeodesicType::Null)
- void SetNewInitialConditions (largecounter index, Point &pos, OneIndex &vel, ScreenIndex &scrIndex) const

  Set new initial conditions for geodesic nr index.
- bool IsFinished () const

  Check if the ViewScreen is finished.
- largecounter getCurNrGeodesics () const

  Get the current number of geodesics.
- void EndCurrentLoop ()

  End the current loop of geodesics.
- void GeodesicFinished (largecounter index, std::vector< real > finalValues)

  Pass on information that a geodesic has finished.
- std::string getFullDescriptionStr () const

  Get the full description string of the ViewScreen.

Private Member Functions

- void ConstructVielbein ()

  Construct the vielbein at the position of the camera.

Private Attributes

- TwoIndex m_Metric_dd {}

  The metric at the position of the viewscreen (we only need indices down)
- TwoIndex m_Vielbein {}

  The vielbein used to transform from the curved spacetime at the viewscreen to a locally flat frame.
- const Point m_Pos

  The position of the camera.
- const OneIndex m_Direction

  The looking direction of the camera (always pointing towards the origin)
- const ScreenPoint m_ScreenSize

  The screensize (in physical units of length)
- const ScreenPoint m_ScreenCenter

  The screen center.
- const bool m_rLogScale

  Whether the metric uses a logarithmic r coordinate or not.
- const Metric *const m_theMetric

  const pointer to const Metric
- const GeodesicType m_GeodType {GeodesicType::Null}

  The geodesic type to be integrated.
- const std::unique_ptr< Mesh > m_theMesh

  The const pointer to the Mesh we are using to determine pixels to be integrated.

6.57.1 Detailed Description

This class is in charge of converting a pixel on the screen into physical initial conditions for a geodesic.

The ViewScreen class is in charge of converting a pixel on the screen (which the Mesh wants to integrate) into physical initial conditions for the position and velocity of a geodesic. It owns a Mesh instance, which will tell it which pixels to integrate etc.

6.57.2 Constructor & Destructor Documentation

6.57.2.1 ViewScreen() [1/2]

```
ViewScreen::ViewScreen ()  [delete]
```

6.57.2.2 ViewScreen() [2/2]

```
ViewScreen::ViewScreen (
            Point pos,
            OneIndex dir,
            ScreenPoint screensize,
            ScreenPoint screencenter,
            std::unique_ptr< Mesh > theMesh,
            const Metric *const theMetric,
            GeodesicType thegeodtype = GeodesicType::Null)  [inline]
```

6.57.3 Member Function Documentation

6.57.3.1 ConstructVielbein()

```
void ViewScreen::ConstructVielbein ()  [private]
```

Construct the vielbein at the position of the camera.

6.57.3.2 EndCurrentLoop()

```
void ViewScreen::EndCurrentLoop ()
```

End the current loop of geodesics.

6.57.3.3 GeodesicFinished()

```
void ViewScreen::GeodesicFinished (
            largecounter index,
            std::vector< real > finalValues)
```

Pass on information that a geodesic has finished.

Parameters

index	index of the geodesic
finalValues	final values of the geodesic

6.57.3.4 getCurNrGeodesics()

```
largecounter ViewScreen::getCurNrGeodesics () const
```

Get the current number of geodesics.

Returns

largecounter

6.57.3.5 getFullDescriptionStr()

```
std::string ViewScreen::getFullDescriptionStr () const
```

Get the full description string of the ViewScreen.

Returns

std::string

6.57.3.6 IsFinished()

```
bool ViewScreen::IsFinished () const
```

Check if the ViewScreen is finished.

Returns

true if the ViewScreen is finished, false otherwise

6.57.3.7 SetNewInitialConditions()

```
void ViewScreen::SetNewInitialConditions (
            largecounter index,
            Point & pos,
            OneIndex & vel,
            ScreenIndex & scrIndex) const
```

Set new initial conditions for geodesic nr index.

Parameters

index	index of the geodesic
pos	pointer to the starting position of the geodesic - which is the camera position
vel	pointer to the starting velocity of the geodesic
scrIndex	pointer to the screen index of the geodesic

6.57.4 Member Data Documentation

6.57.4.1 m_Direction

```
const OneIndex ViewScreen::m_Direction  [private]
```

The looking direction of the camera (always pointing towards the origin)

6.57.4.2 m_GeodType

```
const GeodesicType ViewScreen::m_GeodType {GeodesicType::Null}  [private]
```

The geodesic type to be integrated.

6.57.4.3 m_Metric_dd

```
TwoIndex ViewScreen::m_Metric_dd {}  [private]
```

The metric at the position of the viewscreen (we only need indices down)

6.57.4.4 m_Pos

```
const Point ViewScreen::m_Pos  [private]
```

The position of the camera.

6.57.4.5 m_rLogScale

```
const bool ViewScreen::m_rLogScale  [private]
```

Whether the metric uses a logarithmic r coordinate or not.

6.57.4.6 m_ScreenCenter

```
const ScreenPoint ViewScreen::m_ScreenCenter  [private]
```

The screen center.

6.57.4.7 m_ScreenSize

```
const ScreenPoint ViewScreen::m_ScreenSize  [private]
```

The screensize (in physical units of length)

6.57.4.8 m_theMesh

```
const std::unique_ptr<Mesh> ViewScreen::m_theMesh  [private]
```

The const pointer to the Mesh we are using to determine pixels to be integrated.

6.57.4.9 m_theMetric

```
const Metric* const ViewScreen::m_theMetric  [private]
```

const pointer to const Metric

6.57.4.10 m_Vielbein

```
TwoIndex ViewScreen::m_Vielbein {}  [private]
```

The vielbein used to transform from the curved spacetime at the viewscreen to a locally flat frame.

The documentation for this class was generated from the following files:

- FOORT/src/ViewScreen.h
- FOORT/src/ViewScreen.cpp

Chapter 7

File Documentation

7.1 FOORT/src/Config.cpp File Reference

```
#include "Config.h"
#include "Utilities.h"
#include <algorithm>
#include <cctype>
#include <utility>
```

7.1.1 Detailed Description

Author

Daniel R. Mayerson

Version

1.0

Date

2024-12-12

Copyright

Copyright (c) 2024

7.2 FOORT/src/Config.h File Reference

Functions that read the configuration file and initialize all objects.

```
#include "Geometry.h"
#include "Metric.h"
#include "Diagnostics.h"
#include "Terminations.h"
#include "ViewScreen.h"
#include "Geodesic.h"
#include "Integrators.h"
#include <memory>
#include <string>
#include <exception>
#include "ConfigReader.h"
```

Namespaces

- namespace Config

  Namespace for all configuration functions that initialize objects based on configuration file.

Typedefs

- using Config::ConfigCollection = ConfigReader::ConfigCollection
- using Config::SettingError = std::invalid_argument

Functions

- void Config::InitializeScreenOutput (const ConfigCollection &theCfg)

  Initialize screen output options.
- std::unique_ptr< Metric > Config::GetMetric (const ConfigCollection &theCfg)

  Use configuration to create the correct Metric with specified parameters.
- std::unique_ptr< Source > Config::GetSource (const ConfigCollection &theCfg, const Metric *const the↩ Metric)

  Use configuration to create the correct Source with specified parameters.
- void Config::InitializeDiagnostics (const ConfigCollection &theCfg, DiagBitflag &alldiags, DiagBitflag &valdiag, const Metric *const theMetric)

  Use configuration to set the Diagnostics bitflag appropriately; initialize all DiagnosticOptions for all Diagnostics that are turned on; and set bitflag for diagnostic to be used for coarseness evaluating in Mesh.
- void Config::InitializeTerminations (const ConfigCollection &theCfg, TermBitflag &allterms, const Metric *const theMetric)

  Use configuration to set the Termination bitflag appropriately; and initialize all TerminationOptions for all Terminations that are turned on.
- std::unique_ptr< ViewScreen > Config::GetViewScreen (const ConfigCollection &theCfg, DiagBitflag valdiag, const Metric *const theMetric)

  Use configuration to create the ViewScreen object with specified parameters.
- std::unique_ptr< Mesh > Config::GetMesh (const ConfigCollection &theCfg, DiagBitflag valdiag)

  Use configuration to create the Mesh object with specified parameters.
- GeodesicIntegratorFunc Config::GetGeodesicIntegrator (const ConfigCollection &theCfg)

  Use configuration to set the GeodesicIntegratorFunc pointer to the correct integrator function.
- std::unique_ptr< GeodesicOutputHandler > Config::GetOutputHandler (const ConfigCollection &theCfg, DiagBitflag alldiags, DiagBitflag valdiag, std::string FirstLineInfo)

  Use configuration to create the GeodesicOutputHandler object with specified parameters.

Variables

- constexpr auto Config::Output_Important_Default = OutputLevel::Level_0_WARNING
- constexpr auto Config::Output_Other_Default = OutputLevel::Level_1_PROC

7.2.1 Detailed Description

Functions that read the configuration file and initialize all objects.

Author

Daniel R. Mayerson

Version

1.0

Date

2024-12-12

Copyright

Copyright (c) 2024

7.3 Config.h

Go to the documentation of this file.

```
00001 #ifndef _FOORT_CONFIG_H
00002 #define _FOORT_CONFIG_H
00003
00012
00013 #include "Geometry.h"
00014 #include "Metric.h"
00015 #include "Diagnostics.h"
00016 #include "Terminations.h"
00017 #include "ViewScreen.h"
00018 #include "Geodesic.h"
00019 #include "Integrators.h"
00020
00021 #include <memory> // std::unique_ptr
00022 #include <string> // std::string
00023
00024 #include <exception> // needed to define our own configuration error
00025
00026 #include "ConfigReader.h"
00027
00031 namespace Config
00032 {
00033     // Output level for important missing information that will default
00034     // (e.g. no metric selected, no diagnostics selected, ...)
00035     constexpr auto Output_Important_Default = OutputLevel::Level_0_WARNING;
00036     // Output level for less important information that will default
00037     // (e.g. Kerr metric a parameter not specified)
00038     constexpr auto Output_Other_Default = OutputLevel::Level_1_PROC;
00039
00040     // Total configuration object, as loaded from configuration file
00041     using ConfigCollection = ConfigReader::ConfigCollection;
00042
00043     // An exception to throw whenever an important setting is not found
00044     // Always should be caught and then reverted to default settings
00045     using SettingError = std::invalid_argument;
00046
00049
00050     // Use configuration to initialize the screen output level
00051     void InitializeScreenOutput(const ConfigCollection &theCfg);
00052
00053     // Use configuration to create the correct Metric with specified parameters
00054     std::unique_ptr<Metric> GetMetric(const ConfigCollection &theCfg);
00055
00056     // Use configuration to create the correct Source with specified parameters
00057     std::unique_ptr<Source> GetSource(const ConfigCollection &theCfg, const Metric *const theMetric);
00058
```

```
00059     // Use configuration to set the Diagnostics bitflag appropriately;
00060     // initialize all DiagnosticOptions for all Diagnostics that are turned on;
00061     // and set bitflag for diagnostic to be used for coarseness evaluating in Mesh
00062     void InitializeDiagnostics(const ConfigCollection &theCfg, DiagBitflag &alldiags, DiagBitflag
      &valdiag, const Metric *const theMetric);
00063
00064     // Use configuration to set the Terminations bitflag appropriately;
00065     // initialize all TerminationOptions for all Terminations that are turned on;
00066     void InitializeTerminations(const ConfigCollection &theCfg, TermBitflag &allterms, const Metric
      *const theMetric);
00067
00068     // Use configuration to create ViewScreen appropriately
00069     std::unique_ptr<ViewScreen> GetViewScreen(const ConfigCollection &theCfg, DiagBitflag valdiag,
      const Metric *const theMetric);
00070     // GetViewScreen calls GetMesh to create the correct Mesh
00071     std::unique_ptr<Mesh> GetMesh(const ConfigCollection &theCfg, DiagBitflag valdiag);
00072
00073     // Use configuration to return a pointer to the correct integration function to use
00074     GeodesicIntegratorFunc GetGeodesicIntegrator(const ConfigCollection &theCfg);
00075
00076     // Use configuration to initialize the output handler
00077     std::unique_ptr<GeodesicOutputHandler> GetOutputHandler(const ConfigCollection &theCfg,
00078                                                             DiagBitflag alldiags, DiagBitflag valdiag,
      std::string FirstLineInfo);
00079
00080 } // end namespace Config
00081
00082 #endif
```

7.4 FOORT/src/ConfigReader.cpp File Reference

```
#include "ConfigReader.h"
#include <ios>
#include <type_traits>
```

7.4.1 Detailed Description

Author

Daniel R. Mayerson

Version

1.0

Date

2024-12-12

Copyright

Copyright (c) 2024

7.5 FOORT/src/ConfigReader.h File Reference

Classes used to read in a configuration file and store the settings.

```
#include <string_view>
#include <string>
#include <iostream>
#include <fstream>
#include <vector>
#include <variant>
#include <stdexcept>
#include <limits>
#include <memory>
#include <type_traits>
```

Classes

- class ConfigReader::ConfigReaderException
- class ConfigReader::ConfigCollection
- struct ConfigReader::ConfigCollection::ConfigSetting

Namespaces

- namespace ConfigReader

  Namespace to put all ConfigReader objects.

Variables

- const long long ConfigReader::MaxStreamSize {std::numeric_limits<std::streamsize>::max()}

7.5.1 Detailed Description

Classes used to read in a configuration file and store the settings.

Author

Daniel R. Mayerson

Version

1.0

Date

2024-12-12

Copyright

Copyright (c) 2024

7.6 ConfigReader.h

Go to the documentation of this file.

```
00001 #ifndef _CONFIGREADER_H
00002 #define _CONFIGREADER_H
00003
00012
00013 #include <string_view> // std::string_view
00014 #include <string>      // std::string
00015 #include <iostream>    // needed for file and console output
00016 #include <fstream>     // needed for file input
00017 #include <vector>      // needed to create vectors of Settings
00018 #include <variant>     // needed for std::variant
00019 #include <stdexcept>   // needed for exceptions
00020 #include <limits>      // for std::numeric_limits
00021 #include <memory>      // for std::unique_ptr
00022 #include <type_traits> // for std::is_floating_point_v
00023
00027 namespace ConfigReader
00028 {
00029     // Shorthand for the maximum number of characters we can ignore in a stream
00030     const long long MaxStreamSize{std::numeric_limits<std::streamsize>::max()};
00031
00032     // Exception that is thrown if anything bad happens when reading in configuration file
00033     class ConfigReaderException : public std::runtime_error
00034     {
00035     public:
00036         ConfigReaderException(const std::string &error, std::vector<int> settingtrace = {})
00037             : std::runtime_error{error.c_str()}, m_settingtrace{settingtrace}
00038         {
00039         }
00040         // no need to override what() since we can just use std::runtime_error::what()
00041
00042         std::vector<int> trace() const
00043         {
00044             return m_settingtrace;
00045         };
00046
00047     private:
00048         std::vector<int> m_settingtrace;
00049     };
00050
00051     // A collection of configuration settings
00052     class ConfigCollection
00053     {
00054     public:
00056         // Returns true if the collection contains a setting with the given name
00057         bool Exists(std::string_view SettingName) const;
00058         // Returns total number of settings in this collection
00059         int NrSettings() const;
00060
00061         // Returns true if the setting with the given name (resp. index) is a collection of
    subsettings
00062         // (Returns false if this setting name does not exist, or index is out of bounds)
00063         bool IsCollection(std::string_view SettingName) const;
00064         bool IsCollection(int SettingIndex) const;
00065         // If CollectionName (resp. CollectionIndex) is the name (resp. index)
00066         // of a setting that is a subcollection, then this returns
00067         // a const reference to this subcollection; otherwise throws ConfigReaderException
00068         const ConfigCollection &operator[](std::string_view CollectionName) const;
00069         const ConfigCollection &operator[](int CollectionIndex) const;
00070
00072         // Generic functions that look up the value of a given setting
00073         // and put it in the output variable
00074         // Returns true if successful, false if unsuccesful
00075         // (either due to type mismatch of output and setting value, or if setting doesn't exist)
00076         // Templated functions implemented below in .h file!
00077         template <class OutputType>
00078         bool LookupValue(std::string_view SettingName, OutputType &theOutput) const;
00079         template <class OutputType>
00080         bool LookupValue(int SettingIndex, OutputType &theOutput) const;
00081
00082         // Specific functions for looking up signed integral types
00083         // These will first see if the setting value is of the given type, then
00084         // they will try smaller types and then recast to the larger type
00085         // (so e.g. for long long, first long long is tried, then long, then int)
00086         bool LookupValueInteger(std::string_view SettingName, int &theOutput) const;
00087         bool LookupValueInteger(std::string_view SettingName, long &theOutput) const;
00088         bool LookupValueInteger(std::string_view SettingName, long long &theOutput) const;
00089         // Specific functions for looking up unsigned integral types
00090         // These will first test if the setting value is of the signed case, if it is and it is >=0
    then it always fits in
00091         // the unsigned version; then it will test larger (signed) types and see if the result still
    fits in the unsigned version
00092         bool LookupValueInteger(std::string_view SettingName, unsigned int &theOutput) const;
```

```
00093         bool LookupValueInteger(std::string_view SettingName, unsigned long &theOutput) const;
00094         bool LookupValueInteger(std::string_view SettingName, unsigned long long &theOutput) const;
00095         // Templated functions implemented below in .h file!
00096         template <class OutputType>
00097         bool LookupValueInteger(int SettingIndex, OutputType &theOutput) const;
00098 
00100         void DisplayCollection(std::ostream &OutputStream, int Indent = 0) const;
00101 
00103         // this overwrites the current collection with the contents of the config file
00104         // Will throw ConfigReaderException if parse/syntax error in configuration file
00105         // Returns true if successful
00106         bool ReadFile(const std::string &FileName);
00107 
00108     private:
00109         // A configuration setting value can be an integral type, bool, double, string, or a
      (sub)collection of settings
00110         // Note: when reading in a configuration file, an integral value will always be stored in the
      smallest possible type!
00111         using ConfigSettingValue = std::variant<bool,
00112                                                 int, long, long long,
00113                                                 double,
00114                                                 std::string,
00115                                                 std::unique_ptr<ConfigCollection»;
00116         // A setting is a name and setting value
00117         struct ConfigSetting
00118         {
00119             std::string SettingName;
00120             ConfigSettingValue SettingValue;
00121         };
00122         // The vector of all settings in this collection
00123         std::vector<ConfigSetting> m_Settings{};
00124 
00125         // Helper function that returns the index of the setting with the given name
00126         // returns -1 if setting not found
00127         int GetSettingIndex(std::string_view SettingName) const;
00128 
00129         // Helper functions for DisplayCollection
00130         // DisplaySetting displays one setting; if it's a subcollection then it calls
00131         // DisplayCollection on the subcollection
00132         void DisplaySetting(std::ostream &OutputStream, int SettingIndex, int Indent) const;
00133         // Output given number of tabs
00134         void DisplayTabs(std::ostream &OutputStream, int NrTabs) const;
00135 
00136         // Helper functions for ReadFile()
00137         // These all take an ifstream at a given location and will read in one specific object
00138         //
00139         // Read in entire collection (including subcollections)
00140         // Pre: stream is positioned right after { (or at beginning of file)
00141         // Post: stream is positioned right after } (or at EOF)
00142         void ReadCollection(std::ifstream &InputFile);
00143         // Read in a setting name
00144         // Pre: next non-whitespace character in stream is beginning of name
00145         // Post: stream has just read in all characters of name (but no more);
00146         // returns "" if there is no more setting to read in the current collection, in this case
00147         // '}' has been read in (for subcollections)
00148         void ReadSettingName(std::ifstream &InputFile, std::string &theName);
00149         // Read in one specific character only (not '/'!)
00150         // Pre: next non-whitespace character in stream is this character
00151         // Post: stream is just after character
00152         void ReadSettingSpecificChar(std::ifstream &InputFile, char theChar) const;
00153         // Read in setting value (could be subcollection)
00154         // Pre: next non-whitespace character in stream is beginning of value
00155         // (can be '{' for subcollection, digit for number, '"' for string, or 't'/'f' for boolean)
00156         // Post: Value has entirely been read in (i.e. next character should be ';')
00157         void ReadSettingValue(std::ifstream &InputFile, ConfigSettingValue &theValue);
00158     };
00159 
00160 } // end namespace declarations
00161 
00164 
00174 template <class OutputType>
00175 bool ConfigReader::ConfigCollection::LookupValue(int SettingIndex, OutputType &theOutput) const
00176 {
00177     // Get the setting value, if it is indeed of this type
00178     const ConfigSettingValue &theValue{m_Settings[SettingIndex].SettingValue};
00179     const OutputType *OutputPointer{std::get_if<OutputType>(&theValue)};
00180     if (OutputPointer)
00181     {
00182         // Success, the setting is indeed of this type; set the output accordingly
00183         theOutput = *OutputPointer;
00184         return true;
00185     }
00186 
00187     // A real-valued setting may have been written without a decimal point (e.g. "a = 0;"),
00188     // in which case it was stored as an integral type: accept it and convert
00189     if constexpr (std::is_floating_point_v<OutputType>)
00190     {
```

```
00191         if (const int *p{std::get_if<int>(&theValue)})             { theOutput =
      static_cast<OutputType>(*p); return true; }
00192         if (const long *p{std::get_if<long>(&theValue)})           { theOutput =
      static_cast<OutputType>(*p); return true; }
00193         if (const long long *p{std::get_if<long long>(&theValue)}) { theOutput =
      static_cast<OutputType>(*p); return true; }
00194     }
00195     return false;
00196 }
00197
00207 template <class OutputType>
00208 bool ConfigReader::ConfigCollection::LookupValue(std::string_view SettingName, OutputType &theOutput)
      const
00209 {
00210     // Look up setting index and then defer to index-based implementation, if setting exists
00211     int SettingIndex{GetSettingIndex(SettingName)};
00212     if (SettingIndex >= 0)
00213     {
00214         return LookupValue(SettingIndex, theOutput);
00215     }
00216     return false;
00217 }
00218
00229 template <class OutputType>
00230 bool ConfigReader::ConfigCollection::LookupValueInteger(int SettingIndex, OutputType &theOutput) const
00231 {
00232     return LookupValueInteger(m_Settings[SettingIndex].SettingName, theOutput);
00233 }
00234
00235 #endif
```

7.7 FOORT/src/Diagnostics.cpp File Reference

```
#include "Diagnostics.h"
#include "DiagnosticsEmission.h"
#include "Geodesic.h"
#include "InputOutput.h"
#include "Integrators.h"
#include <cmath>
```

Functions

- DiagnosticUniqueVector CreateDiagnosticVector (DiagBitflag diagflags, DiagBitflag valdiag, Geodesic *const theGeodesic)

  Diagnostic helper function.

7.7.1 Detailed Description

Author

Daniel R. Mayerson

Version

1.0

Date

2024-12-16

Copyright

Copyright (c) 2024

7.7.2 Function Documentation

7.7.2.1 CreateDiagnosticVector()

```
DiagnosticUniqueVector CreateDiagnosticVector (
            DiagBitflag diagflags,
            DiagBitflag valdiag,
            Geodesic *const theGeodesic)
```

Diagnostic helper function.

Create a Diagnostic Vector object

Parameters

diagflags	Diagnostic bitflags
valdiag	Value Diagnostic bitflag
theGeodesic	Pointer to the Geodesic object

Returns

DiagnosticUniqueVector

7.8 FOORT/src/Diagnostics.h File Reference

Declarations of abstract base Diagnostic class and all its descendants. All Definitions in Diagnostics.cpp.

```
#include "Geometry.h"
#include "Metric.h"
#include "InputOutput.h"
#include "DiagnosticsEmission.h"
#include <cstdint>
#include <string>
#include <memory>
#include <vector>
```

Classes

- struct UpdateFrequency

  Struct to hold the information for a Diagnostic to update itself.
- class Diagnostic

  Abstract base class for all diagnostics.
- class FourColorScreenDiagnostic

  The four color screen diagnostic.
- class GeodesicPositionDiagnostic

  Geodesic position tracker.
- class EquatorialPassesDiagnostic

  Diagnostic that counts the number of passes through the equatorial plane.
- class ClosestRadiusDiagnostic

Diagnostic that keeps track of the closest (true, not log) radius that the geodesic passes through.

- class EquatorialEmissionDiagnostic

  Diagnostic that calculates brightness intensity for the geodesic, based on a specified equatorial disc emission model.
- struct DiagnosticOptions

  Base class for DiagnosticOptions. Other Diagnostics can inherit from here if they require more options.
- struct GeodesicPositionOptions

  Options for GeodesicPositionDiagnostic.
- struct EquatorialPassesOptions

  Options for EquatorialPassesDiagnostic.
- struct ClosestRadiusOptions

  Options for ClosestRadiusDiagnostic.
- struct EquatorialEmissionOptions

  Options for EquatorialEmissionDiagnostic.

Typedefs

- using DiagBitflag = std::uint16_t

  Diagnostic bitflags.
- using DiagnosticUniqueVector = std::vector<std::unique_ptr<Diagnostic>>

  Owner vector of derived Diagnostics classes.

Functions

- DiagnosticUniqueVector CreateDiagnosticVector (DiagBitflag diagflags, DiagBitflag valdiag, Geodesic *const theGeodesic)

  Diagnostic helper function.

Variables

- constexpr DiagBitflag Diag_None {0b0000'0000'0000'0000}
- constexpr DiagBitflag Diag_GeodesicPosition {0b0000'0000'0000'0001}
- constexpr DiagBitflag Diag_FourColorScreen {0b0000'0000'0000'0010}
- constexpr DiagBitflag Diag_EquatorialPasses {0b0000'0000'0000'0100}
- constexpr DiagBitflag Diag_ClosestRadius {0b0000'0000'0000'1000}
- constexpr DiagBitflag Diag_EquatorialEmission {0b0000'0000'0001'0000}

7.8.1 Detailed Description

Declarations of abstract base Diagnostic class and all its descendants. All Definitions in Diagnostics.cpp.

Author

Daniel R. Mayerson

Version

1.0

Date

2024-12-16

Copyright

Copyright (c) 2024

7.8.2 Typedef Documentation

7.8.2.1 DiagBitflag

```
using DiagBitflag = std::uint16_t
```

Diagnostic bitflags.

Used for constructing vector of Diagnostics ...

7.8.2.2 DiagnosticUniqueVector

```
using DiagnosticUniqueVector = std::vector<std::unique_ptr<Diagnostic>>
```

Owner vector of derived Diagnostics classes.

7.8.3 Function Documentation

7.8.3.1 CreateDiagnosticVector()

```
DiagnosticUniqueVector CreateDiagnosticVector (
            DiagBitflag diagflags,
            DiagBitflag valdiag,
            Geodesic *const theGeodesic)
```

Diagnostic helper function.

Helper to create a new vector of Diagnostic options, based on the bitflag The first diagnostic is the value diagnostic

Create a Diagnostic Vector object

Parameters

diagflags	Diagnostic bitflags
valdiag	Value Diagnostic bitflag
theGeodesic	Pointer to the Geodesic object

Returns

DiagnosticUniqueVector

7.8.4 Variable Documentation

7.8.4.1 Diag_ClosestRadius

```
DiagBitflag Diag_ClosestRadius {0b0000'0000'0000'1000}  [constexpr]
```

7.8.4.2 Diag_EquatorialEmission

```
DiagBitflag Diag_EquatorialEmission {0b0000'0000'0001'0000}  [constexpr]
```

7.8.4.3 Diag_EquatorialPasses

```
DiagBitflag Diag_EquatorialPasses {0b0000'0000'0000'0100}  [constexpr]
```

7.8.4.4 Diag_FourColorScreen

```
DiagBitflag Diag_FourColorScreen {0b0000'0000'0000'0010}  [constexpr]
```

7.8.4.5 Diag_GeodesicPosition

```
DiagBitflag Diag_GeodesicPosition {0b0000'0000'0000'0001}  [constexpr]
```

7.8.4.6 Diag_None

```
DiagBitflag Diag_None {0b0000'0000'0000'0000}  [constexpr]
```

7.9 Diagnostics.h

Go to the documentation of this file.

```
00001 #ifndef _FOORT_DIAGNOSTICS_H
00002 #define _FOORT_DIAGNOSTICS_H
00003
00012
00013 #include "Geometry.h"  // for tensors
00014 #include "Metric.h"      // for metric
00015 #include "InputOutput.h" // for ScreenOutput
00016
00017 #include "DiagnosticsEmission.h" // Emission models
00018
00019 #include <cstdint> // for std::uint16_t
00020 #include <string>  // for strings
00021 #include <memory>  // for std::unique_ptr
00022 #include <vector>  // for std::vector
00023
00024 // Forward declaration of Geodesic class needed here, since Diagnostics are passed a pointer to their
      owner Geodesic
00025 // (note "Geodesic.h" is NOT included to avoid header loop, and we do not need Geodesic member
      functions here!)
00026 class Geodesic;
00027
00030
00031 // Diagnostic bitflags
00032 // Used for constructing vector of Diagnostics
00033 // Note that this means every diagnostic is either "on" or "off";
00034 // it is not possible to have a Diagnostic "on" more than once
00035 // Note: why not std::bitset<size>? Because in this way we can use expressions with DiagBitflag in
      conditional expressions,
00036 // e.g. if ( mydiagbitflag & Diag_FourColorScreen)
00041 using DiagBitflag = std::uint16_t;
00042
00043 // Define a bitflag per existing diagnostic
00044 constexpr DiagBitflag Diag_None{0b0000'0000'0000'0000};
00045 constexpr DiagBitflag Diag_GeodesicPosition{0b0000'0000'0000'0001};
00046 constexpr DiagBitflag Diag_FourColorScreen{0b0000'0000'0000'0010};
00047 constexpr DiagBitflag Diag_EquatorialPasses{0b0000'0000'0000'0100};
00048 constexpr DiagBitflag Diag_ClosestRadius{0b0000'0000'0000'1000};
```

```
00049 constexpr DiagBitflag Diag_EquatorialEmission{0b0000'0000'0001'0000};
00050
00052 // Add a DiagBitflag for your new diagnostic. Make sure you use a bitflag that has not been used
      before!
00053 // Sample code:
00054 /*
00055 constexpr DiagBitflag Diag_MyDiag               { 0b0000'0000'0010'0000 };
00056 */
00058
00063 struct UpdateFrequency
00064 {
00065     largecounter UpdateNSteps{0};
00066     bool UpdateStart{false};
00067     bool UpdateFinish{false};
00068 };
00069
00074 class Diagnostic
00075 {
00076 public:
00077     // Constructor must initialize the pointer to its owner Geodesic
00078     Diagnostic() = delete;
00079     Diagnostic(Geodesic *const theGeodesic) : m_OwnerGeodesic{theGeodesic}
00080     {
00081     }
00082
00083     // Resets Diagnostic object. This is called when the owner Geodesic is reset in order to start
      integrating
00084     // a new geodesic.
00085     // The base class implementation only resets m_StepsSinceUpdated
00086     // Descendants can override this if they need to reset additional internal variables
00087     virtual void Reset();
00088
00089     // virtual destructor to ensure correct destruction of descendants
00090     virtual ~Diagnostic() = default;
00091
00092     // This is the heart of the Diagnostic. It calls the helper function DecideUpdate(), and if this
00093     // returns true, will update its internal status based on the current (new) state of its owner
      geodesic.
00094     virtual void UpdateData() = 0;
00095
00096     // These functions are for use at the end of integration of a geodesic.
00097     // getFullData() returns all the data stored in the Diagnostic as a string (for output to file)
00098     virtual std::string getFullDataStr() const = 0;
00099     // getFinalDataVal() associates a value to the geodesic corresponding to the final value of this
      diagnostic
00100     // (used for determining coarseness of nearby geodesics)
00101     virtual std::vector<real> getFinalDataVal() const = 0;
00102
00103     // Function used to determine distance between two values obtained from getFinalDataVal()
00104     // (for determining coarseness of nearby geodesics)
00105     // This should return a number >=0
00106     virtual real FinalDataValDistance(const std::vector<real> &val1, const std::vector<real> &val2)
      const = 0;
00107
00108     // Getters for descriptions
00109     // This returns the name (only) of the Diagnostic, as a string without spaces that will be
      appended
00110     // to an output file (e.g. prefix_DiagName.ext). Must be implemented!
00111     virtual std::string getNameStr() const = 0;
00112     // This returns the full description of the Diagnostic. Default implementation
00113     // returns GetDiagNameStr()
00114     virtual std::string getFullDescriptionStr() const;
00115
00116 protected:
00117     // The geodesic that owns the Diagnostic (a const pointer to the Geodesic)
00118     Geodesic *const m_OwnerGeodesic;
00119
00120     // Helper function to decide if the Diagnostic should indeed update its status, based on
00121     // its UpdateFrequency struct information (which will come from the Diagnostics's
      DiagnosticOptions)
00122     bool DecideUpdate(const UpdateFrequency &myUpdateFrequency);
00123
00124     // The diagnostic is itself in charge of keeping track of how many steps it has been since it has
      been updated
00125     // The Diagnostic's DiagnosticOptions struct tells it how many steps it needs to wait between
      updates
00126     largecounter m_StepsSinceUpdated{};
00127 };
00128
00130 using DiagnosticUniqueVector = std::vector<std::unique_ptr<Diagnostic>>;
00131
00134 DiagnosticUniqueVector CreateDiagnosticVector(DiagBitflag diagflags, DiagBitflag valdiag, Geodesic
      *const theGeodesic);
00135
00138
00144 class FourColorScreenDiagnostic final : public Diagnostic
00145 {
```

```
00146 public:
00147     // Basic constructor only passes on Geodesic pointer to base class constructor
00148     FourColorScreenDiagnostic(Geodesic *const theGeodesic) : Diagnostic(theGeodesic) {}
00149
00150     // Reset needs to be overridden in order to also reset m_quadrant
00151     void Reset() final;
00152
00153     // Sets the quadrant to the appropriate value, IF the boundary sphere has been reached
00154     void UpdateData() override;
00155
00156     // Both of these output functions simply returns the quadrant number associated with the
      geodesic's end position
00157     std::string getFullDataStr() const final;
00158     std::vector<real> getFinalDataVal() const final;
00159
00160     // Discrete metric for distance: returns 0 if the quadrants are the same, 1 if they are not
00161     real FinalDataValDistance(const std::vector<real> &val1, const std::vector<real> &val2) const
      final;
00162
00163     // Description string getters
00164     std::string getNameStr() const final;
00165     std::string getFullDescriptionStr() const final;
00166
00167     // FourColorScreen does not need any (static) options!
00168
00169 private:
00171     int m_quadrant{0};
00172 };
00173
00175 struct GeodesicPositionOptions;
00179 class GeodesicPositionDiagnostic final : public Diagnostic
00180 {
00181 public:
00182     // Basic constructor only passes on Geodesic pointer to base class constructor
00183     GeodesicPositionDiagnostic(Geodesic *const theGeodesic) : Diagnostic(theGeodesic) {}
00184
00185     // Override Reset to also clear m_AllSavedPoints
00186     void Reset() final;
00187
00188     // Stores the current position of the geodesic
00189     void UpdateData() final;
00190
00191     // This returns as many stored positions as is specified in the options struct
00192     std::string getFullDataStr() const final;
00193     // This returns the final (theta,phi) value of the geodesic
00194     std::vector<real> getFinalDataVal() const final;
00195
00196     // This determines the angular distance between two geodesic
00197     // (based on their final angles on the boundary sphere (theta, phi))
00198     real FinalDataValDistance(const std::vector<real> &val1, const std::vector<real> &val2) const
      final;
00199
00200     // Description string getters
00201     std::string getNameStr() const final;
00202     std::string getFullDescriptionStr() const final;
00203
00204     // The options: specifies the update frequency but also how many points we want to output in the
      end
00205     static std::unique_ptr<GeodesicPositionOptions> DiagOptions;
00206
00207 private:
00208     // Keeps track of the points that are saved
00209     std::vector<Point> m_AllSavedPoints{};
00210 };
00211
00213 struct EquatorialPassesOptions;
00217 class EquatorialPassesDiagnostic : public Diagnostic
00218 {
00219 public:
00220     // Basic constructor only passes on Geodesic pointer to base class constructor
00221     EquatorialPassesDiagnostic(Geodesic *const theGeodesic) : Diagnostic(theGeodesic) {}
00222
00223     // Override Reset to also reset m_EquatPasses and m_PrevTheta
00224     void Reset() override;
00225
00226     // Checks to see if we have a new cross over the equatorial plane
00227     void UpdateData() override;
00228
00229     // Returns the number of passes over the equatorial plane
00230     std::string getFullDataStr() const override;
00231     std::vector<real> getFinalDataVal() const override;
00232
00233     // Simple absolute value of difference of passes
00234     real FinalDataValDistance(const std::vector<real> &val1, const std::vector<real> &val2) const
      override;
00235
00236     // Description string getters
```

```
00237     std::string getNameStr() const override;
00238     std::string getFullDescriptionStr() const override;
00239
00241     static std::unique_ptr<EquatorialPassesOptions> DiagOptions;
00242
00243 protected:
00245     int m_EquatPasses{0};
00246
00247 private:
00249     real m_PrevTheta{-1};
00250 };
00251
00252 // Forward declaration needed before Diagnostic
00253 struct ClosestRadiusOptions;
00257 class ClosestRadiusDiagnostic final : public Diagnostic
00258 {
00259 public:
00260     // Basic constructor only passes on Geodesic pointer to base class constructor
00261     ClosestRadiusDiagnostic(Geodesic *const theGeodesic) : Diagnostic(theGeodesic) {}
00262
00263     // re-initialize closest radius
00264     void Reset() final;
00265
00266     // Check to see if we have travelled closer
00267     void UpdateData() final;
00268
00269     // Return closest radius travelled
00270     std::string getFullDataStr() const final;
00271     std::vector<real> getFinalDataVal() const final;
00272
00273     // Returns the absolute value of the difference between closest radii
00274     real FinalDataValDistance(const std::vector<real> &val1, const std::vector<real> &val2) const
      final;
00275
00276     // Description string getters
00277     std::string getNameStr() const final;
00278     std::string getFullDescriptionStr() const final;
00279
00280     // Option struct to keep track of RLogScale of Metric
00281     static std::unique_ptr<ClosestRadiusOptions> DiagOptions;
00282
00283 private:
00284     // Keeps track of closest radius travelled
00285     real m_ClosestRadius{-1};
00286 };
00287
00288 // Forward declaration needed before Diagnostic
00289 struct EquatorialEmissionOptions;
00296 class EquatorialEmissionDiagnostic final : public EquatorialPassesDiagnostic
00297 {
00298 public:
00299     // Basic constructor only passes on Geodesic pointer to parent class constructor
00300     EquatorialEmissionDiagnostic(Geodesic *const theGeodesic) :
      EquatorialPassesDiagnostic(theGeodesic) {}
00301
00302     // Reset intensity back to 0.0, and call parent class Reset()
00303     void Reset() final;
00304
00305     // Use parent class UpdateData() to decide whether the update the intensity
00306     // using the specified emission model
00307     void UpdateData() final;
00308
00309     // Returns total intensity and total number of equatorial passes (i.e. normal output from
      EquatorialPassesDiagnostic)
00310     std::string getFullDataStr() const final;
00311     std::vector<real> getFinalDataVal() const final;
00312
00313     // Distance is difference in intensities multiplied by a factor magnifying difference in
      equatorial passes
00314     real FinalDataValDistance(const std::vector<real> &val1, const std::vector<real> &val2) const
      final;
00315
00316     // Description string getters
00317     std::string getNameStr() const final;
00318     std::string getFullDescriptionStr() const final;
00319
00320     // Option struct to keep track emission model specifics
00321     static std::unique_ptr<EquatorialEmissionOptions> DiagOptions;
00322
00323 private:
00324     // Brightness intensity of the geodesic
00325     real m_Intensity{0.0};
00326 };
00327
00329 // Declare your Diagnostic class here, inheriting from Diagnostic.
00330 // Sample code:
00331 /*
```

```
00332 // Forward declaration needed before Diagnostic (if using base class DiagnosticOptions, this is
      strictly speaking not necessary)
00333 struct DiagnosticOptions;
00334 // class definition
00335 class MyDiagnostic final : public Diagnostic // good practice to make the class final unless
      descendant classes are possible
00336 {
00337 public:
00338     // constructor must at least take and pass along the const pointer to the owner Geodesic
00339     MyDiagnostic(Geodesic* const theGeodesic) : Diagnostic(theGeodesic) {}
00340
00341     // If you have MyDiagnostic-specific member variables, then they probably need to be reset at the
      beginning
00342     // of integration for each new geodesic; in that case, you need to override Reset() to do so.
00343     // Note: make sure to call the base class implementation Diagnostic::Reset()
00344     // from within your implementation of MyDiagnostic::Reset(), so that the base class internal
      variable is also reset!
00345     void Reset() final;
00346
00347     // This is the heart of the Diagnostic: here the Diagnostic updates its internal state according
      to
00348     // the owner Geodesic's current state
00349     void UpdateData() final;
00350
00351     // This should return the string that is to be outputted to the file as the final output of this
      Diagnostic
00352     // for its owner Geodesic
00353     std::string getFullDataStr() const final;
00354     // This should return a vector of real numbers that indicates the final "value" that should be
      associated to
00355     // the owner Geodesic --- this is then used in FinalDataValDistance() to find "distances" between
      geodesics.
00356     std::vector<real> getFinalDataVal() const final;
00357
00358     // This should return a (positive) distance of two values returned by getFinalDataVal(), indicated
      the
00359     // "distance" of two geodesics (this is used for Mesh refinement)
00360     real FinalDataValDistance(const std::vector<real>& val1, const std::vector<real>& val2) const
      final;
00361
00362     // Must implement getNameStr() (and recommended also to implement getFullDescriptionStr)
00363     // getNameStr() is a simple, short string (without spaces) that will be appended to the file name
00364     // where this Diagnostic's output is written. getFullDescriptionStr() is a descriptive string that
      should list
00365     // all relevant options set; this is outputted to e.g. the screen at runtime.
00366     std::string getNameStr() const final;
00367     std::string getFullDescriptionStr() const final;
00368
00369     // Diagnostic options: basic DiagnosticOptions only contains UpdateFrequency information,
00370     // if needed, can use a descendant class with more options (see e.g. GeodesicPositionDiagnostic)
00371     static std::unique_ptr<DiagnosticOptions> DiagOptions;
00372
00373 private:
00374     // will probably want some private member variable(s) to keep track of whatever geodesic property
      is desired
00375 };
00376 */
00378
00381
00385 struct DiagnosticOptions
00386 {
00387 public:
00388     // Basic constructor only sets the number of steps between updates
00389     DiagnosticOptions(UpdateFrequency thefrequency) : theUpdateFrequency{thefrequency}
00390     {
00391     }
00392
00393     virtual ~DiagnosticOptions() = default;
00394
00395     const UpdateFrequency theUpdateFrequency;
00396 };
00402 struct GeodesicPositionOptions : public DiagnosticOptions
00403 {
00404 public:
00405     GeodesicPositionOptions(bool rlog, largecounter outputsteps, UpdateFrequency thefrequency)
00406         : DiagnosticOptions(thefrequency), RLogScale{rlog}, OutputNrSteps{outputsteps}
00407     {
00408     }
00409
00410     const bool RLogScale;
00411     const largecounter OutputNrSteps;
00412 };
00413
00419 struct EquatorialPassesOptions : public DiagnosticOptions
00420 {
00421 public:
00422     EquatorialPassesOptions(real thethreshold, UpdateFrequency thefrequency) :
```

```
      DiagnosticOptions(thefrequency), Threshold{thethreshold}
00423     {
00424     }
00425
00426     const real Threshold;
00427 };
00428
00434 struct ClosestRadiusOptions : public DiagnosticOptions
00435 {
00436 public:
00437     ClosestRadiusOptions(bool rlog, UpdateFrequency thefrequency) : DiagnosticOptions(thefrequency),
      RLogScale{rlog}
00438     {
00439     }
00440
00441     const bool RLogScale;
00442 };
00443
00444 // Forward declarations of abstract EmissionModel and FluidVelocityModel classes.
00445 // See Diagnostics_Emission.h and .cpp for declarations and definitions of these and their descendant
      classes!
00446 struct EmissionModel;
00447 struct FluidVelocityModel;
00453 struct EquatorialEmissionOptions : public EquatorialPassesOptions
00454 {
00455 public:
00456     EquatorialEmissionOptions(real thefudgefactor, int equatupper,
00457                               std::unique_ptr<EmissionModel> theemission,
      std::unique_ptr<FluidVelocityModel> thefluidmodel,
00458                               bool rlog, int theredshiftpower, real thethreshold, UpdateFrequency
      thefrequency) : EquatorialPassesOptions(thethreshold, thefrequency), // constructor for parent class
00459           GeometricFudgeFactor{thefudgefactor}, EquatPassUpperBound{equatupper}, RLogScale{rlog},
      RedShiftPower{theredshiftpower},
00460           TheEmissionModel{std::move(theemission)}, TheFluidVelocityModel{std::move(thefluidmodel)}
00461     {
00462     }
00463
00464     // Geometric fudge factor for n>0 passes
00465     const real GeometricFudgeFactor;
00466     // Upper bound allowed for contribution to intensity
00467     const int EquatPassUpperBound;
00468
00469     // Logarithmic radius scale used or not
00470     const bool RLogScale;
00471
00472     // Power of redshift in intensity contribution (should be 3 or 4)
00473     const int RedShiftPower;
00474
00475     // The emission model used (see Diagnostics_Emission.h and .cpp for specific models)
00476     const std::unique_ptr<EmissionModel> TheEmissionModel;
00477     // The fluid velocity model used (see Diagnostics_Emission.h and .cpp for specific models)
00478     const std::unique_ptr<FluidVelocityModel> TheFluidVelocityModel;
00479 };
00480
00482 // if necessary, define your new DiagnosticOptions class here
00483 // Sample code:
00484 /*
00485 struct MyDiagnosticOptions : public DiagnosticOptions
00486 {
00487 public:
00488     // Constructor should pass along UpdateFrequency information to base class
00489     MyDiagnosticOptions(UpdateFrequency thefrequency) : DiagnosticOptions(thefrequency) //, (...)
      other initializations
00490     {}
00491
00492     // other member variables here - make them const!
00493     // ...
00494 };
00495 */
00497
00498 #endif
```

7.10 FOORT/src/DiagnosticsEmission.cpp File Reference

```
#include "DiagnosticsEmission.h"
#include "Integrators.h"
#include <cmath>
#include <algorithm>
```

7.10.1 Detailed Description

Author

Daniel R. Mayerson

Version

1.0

Date

2024-12-16

Copyright

Copyright (c) 2024

7.11 FOORT/src/DiagnosticsEmission.h File Reference

Declarations of emission and fluid velocity models used for equatorial disc emission.

```
#include "Geometry.h"
#include "Metric.h"
#include "InputOutput.h"
#include "Integrators.h"
#include <string>
#include <cmath>
#include <stdexcept>
#include <atomic>
```

Classes

- struct EmissionModel

  Emmision model abstract base class.
- struct GLMJohnsonSUEmission

  The Johnson SU emission model used in GLM 2020, PRD 102(12):124004.
- struct FluidVelocityModel

  Fluid velocity model abstract base class.
- struct GeneralCircularRadialFluid

  General circular radial fluid velocity model.

7.11.1 Detailed Description

Declarations of emission and fluid velocity models used for equatorial disc emission.

Author

Daniel R. Mayerson

Version

1.0

Date

2024-12-16

Copyright

Copyright (c) 2024

7.12 DiagnosticsEmission.h

Go to the documentation of this file.

```
00001 #ifndef _FOORT_DIAGNOSTICS_EMISSION_H
00002 #define _FOORT_DIAGNOSTICS_EMISSION_H
00003
00004 #include "Geometry.h"  // Tensor objects
00005 #include "Metric.h"      // for Metric functions
00006 #include "InputOutput.h" // for ScreenOutput
00007 #include "Integrators.h" // for delta_nodiv0
00008
00009 #include <string>    // for strings
00010 #include <cmath>     // for fmax, fmin
00011 #include <stdexcept> // for std::runtime_error
00012 #include <atomic>    // for std::atomic
00013
00022
00027 struct EmissionModel
00028 {
00029 public:
00030     // Virtual destructor to ensure correct destruction
00031     virtual ~EmissionModel() = default;
00032
00033     // Function which returns the emitted brightness intensity at Point p
00034     // Note: always pass the true radius (not log(r)) to EmissionModel!
00035     virtual real GetEmission(const Point &p) const = 0;
00036
00037     // Description string getter
00038     virtual std::string getFullDescriptionStr() const;
00039 };
00040
00044 struct GLMJohnsonSUEmission final : public EmissionModel
00045 {
00046 public:
00047     // Constructor
00048     GLMJohnsonSUEmission(real mu, real gamma, real sigma) : m_mu{mu}, m_gamma{gamma}, m_sigma{sigma}
00049     {
00050     }
00051
00052     // Emitted brightness (only depends on radius)
00053     real GetEmission(const Point &p) const final;
00054
00055     // Description string getter
00056     std::string getFullDescriptionStr() const final;
00057
00058 private:
00060     const real m_mu;
00062     const real m_gamma;
```

```
00064     const real m_sigma;
00065 };
00066
00068
00073 struct FluidVelocityModel
00074 {
00075 public:
00076     // Constructor is passed Metric pointer
00077     FluidVelocityModel(const Metric *const theMetric) : m_theMetric{theMetric} {}
00078
00079     // Virtual destructor to ensure correct destruction
00080     virtual ~FluidVelocityModel() = default;
00081
00082     // Get the local four-velocity (with index down!) of the fluid at Point p
00083     virtual OneIndex GetFourVelocityd(const Point &p) const = 0;
00084
00085     // Description string getter
00086     virtual std::string getFullDescriptionStr() const;
00087
00088 protected:
00089     // Metric pointer, used for e.g. calculating geodesic orbits
00090     const Metric *const m_theMetric;
00091 };
00092
00098 struct GeneralCircularRadialFluid final : public FluidVelocityModel
00099 {
00100     // Constructor with three parameters and Metric pointer (which is passed to base class
      constructor)
00101     GeneralCircularRadialFluid(real subKeplerParam, real betar, real betaphi, const Metric *const
      theMetric,
00102                                real ISCO_lowerbound, real ISCO_upperbound) :
      FluidVelocityModel(theMetric), m_subKeplerParam{fmin(fmax(subKeplerParam, 0.0), 1.0)},
      m_betaR{fmin(fmax(betar, 0.0), 1.0)},
00103           m_betaPhi{fmin(fmax(betaphi, 0.0), 1.0)}, m_ISCOlowerbound{ISCO_lowerbound},
      m_ISCOupperbound{ISCO_upperbound}
00104     {
00105         // Note: all parameters have been checked in the Config.cpp file before this constructor is
      called, so they should be valid here.
00106
00107         // Checking the metric off-diagonal components at the ISCO search bounds to ensure that the
      assumptions of the fluid model are valid
00108         bool rlogscale{theMetric->getrLogScale()};
00109         TwoIndex guu_ISCOlow{theMetric->getMetric_uu({0.0, rlogscale ? log(m_ISCOlowerbound) :
      m_ISCOlowerbound, pi / 2.0, 0.0})};
00110         TwoIndex guu_ISCOhigh{theMetric->getMetric_uu({0.0, rlogscale ? log(m_ISCOupperbound) :
      m_ISCOupperbound, pi / 2.0, 0.0})};
00111         // Check that the off-diagonal r, theta components of the metric are zero at the ISCO bounds,
      as they should be for equatorial circular orbits
00112         auto hasNonzeroOffDiagonalrtheta = [](const TwoIndex &guu)
00113         {
00114             for (int i = 1; i <= 2; ++i) // check r and theta components (i=1,2) for nonzero
      off-diagonal components
00115                 for (int j = 0; j < 4; ++j)
00116                     if (i != j && std::abs(guu[i][j]) > Integrators::delta_nodiv0)
00117                         return true;
00118             return false;
00119         };
00120         if (hasNonzeroOffDiagonalrtheta(guu_ISCOlow) || hasNonzeroOffDiagonalrtheta(guu_ISCOhigh))
00121             ScreenOutput("Metric has nonzero off-diagonal components at the ISCO search bounds; fluid
      model assumptions are violated and emission output is not reliable.", OutputLevel::Level_0_WARNING);
00122             // throw std::runtime_error("Metric has nonzero off-diagonal components at the ISCO search
      bounds");
00123
00124         // Find the (equatorial) ISCO for this Metric
00125         FindISCO();
00126     }
00127
00128     // Get the local four-velocity of the fluid according to this model
00129     // Note: will always calculate with Point p exactly on the equator theta=pi/2, despite what p[2]
      may be passed
00130     OneIndex GetFourVelocityd(const Point &p) const final;
00131
00132     // Description string getter
00133     std::string getFullDescriptionStr() const final;
00134
00135 private:
00136     // Three parameters determining the flow
00138     const real m_subKeplerParam;
00140     const real m_betaR;
00142     const real m_betaPhi;
00143
00144     // Helper function to get circular (sub)Keplerian velocity outside the ISCO
00145     OneIndex GetCircularVelocityd(const Point &p, bool subKeplerianOn = true) const;
00146     // Helper function to get circular and infalling (sub)Keplerian velocity inside ISCO
00147     // (according to prescription of Cunningham)
00148     OneIndex GetInsideISCOCircularVelocityd(const Point &p) const;
00149
```

```
00150     // Helper function to get radial infalling velocity
00151     OneIndex GetRadialVelocityd(const Point &p) const;
00152 
00153     // Helper function to find the ISCO (called in Constructor)
00154     void FindISCO();
00156     bool m_ISCOexists{false};
00158     real m_ISCOr{-1.0};
00160     real m_ISCOlowerbound;
00162     real m_ISCOupperbound;
00164     real m_ISCOpt{};
00166     real m_ISCOpphi{};
00167 
00168     // Helper function which returns \partial_r(g^{ab}\Gamma^r_{bc}g^{cd}),
00169     // whose sign (after contracted with p_a p_d of the corresponding circular orbit)
00170     // tells us if the circular orbit considered is stable or not
00171     TwoIndex GetChristrRaisedDer(real r) const;
00172 
00173     // Flags and helper functions for model to warn (only) once per run if something goes wrong with
      the fluid velocity calculation
00174     mutable std::atomic<bool> m_WarnedNoCircular{false};
00175     mutable std::atomic<bool> m_WarnedNormalization{false};
00176     mutable std::atomic<bool> m_WarnedNaN{false};
00177     mutable std::atomic<bool> m_WarnedInsideISCO{false};
00178     mutable std::atomic<bool> m_WarnedSubkeplerianRescaling{false};
00179     void WarnOnce(std::atomic<bool> &flag, const std::string &msg, const Point &p) const;
00180 };
00181 
00182 #endif
```

7.13 FOORT/src/Geodesic.cpp File Reference

```
#include "Geodesic.h"
#include "InputOutput.h"
```

7.13.1 Detailed Description

Author

Daniel R. Mayerson

Version

1.0

Date

2024-12-16

Copyright

Copyright (c) 2024

7.14 FOORT/src/Geodesic.h File Reference

Declarations of abstract base Source class and all its descendants. Declaration of Geodesic class.

```
#include "Geometry.h"
#include "Metric.h"
#include "Diagnostics.h"
#include "Terminations.h"
#include "Integrators.h"
#include <string>
#include <vector>
```

Classes

- class Source

  Abstract Source base class.
- class NoSource

  NoSource class.
- class Geodesic

  Geodesic class: an instance of this class is created for each Geodesic that is integrated.

7.14.1 Detailed Description

Declarations of abstract base Source class and all its descendants. Declaration of Geodesic class.

Author

Daniel R. Mayerson

Version

1.0

Date

2024-12-16

Copyright

Copyright (c) 2024

7.15 Geodesic.h

Go to the documentation of this file.

```
00001 #ifndef _FOORT_GEODESIC_H
00002 #define _FOORT_GEODESIC_H
00003
00004 #include "Geometry.h"   // for tensor objects
00005 #include "Metric.h"       // for the metric
00006 #include "Diagnostics.h"  // Geodesics own Diagnostics
00007 #include "Terminations.h" // Geodesics own Terminations
00008 #include "Integrators.h"  // Geodesics use an GeodesicIntegratorFunc to integrate itself
00009
00010 #include <string> // for strings
00011 #include <vector> // for std::vector
00012
00021
00024
00029 class Source
00030 {
00031 public:
00032     // Constructor initializes Metric
00033     Source(const Metric *const theMetric) : m_theMetric{theMetric} {}
00034
00035     // Virtual destructor to ensure correct descendant destruction
00036     virtual ~Source() = default;
00037
00038     // Get the source for the current geodesic position and velocity
00039     virtual OneIndex getSource(Point pos, OneIndex vel) const = 0;
00040
00041     // Full description string (space allowed), to be outputted to file
00042     virtual std::string getFullDescriptionStr() const;
```

```
00043
00044 protected:
00046     const Metric *const m_theMetric;
00047 };
00048
00054 class NoSource final : public Source
00055 {
00056 public:
00057     // Simple constructor passes on the Metric pointer to the base constructor
00058     NoSource(const Metric *const theMetric) : Source(theMetric) {}
00059
00060     // Returns zero source
00061     OneIndex getSource(Point pos, OneIndex vel) const final;
00062
00063     // Description string getter
00064     std::string getFullDescriptionStr() const final;
00065 };
00066
00069
00076 class Geodesic
00077 {
00078 public:
00079     // Default constructor not allowed
00080     Geodesic() = delete;
00081     // Copy constructor or copy assignment not allowed
00082     Geodesic(const Geodesic &) = delete;
00083     Geodesic &operator=(const Geodesic &) = delete;
00084
00095     Geodesic(const Metric *const theMetric, const Source *const theSource,
00096              DiagBitflag diagbit, DiagBitflag valdiagbit,
00097              TermBitflag termbit, GeodesicIntegratorFunc theIntegrator) : m_theMetric{theMetric},
     m_theSource{theSource},
00098
     m_AllDiagnostics{CreateDiagnosticVector(diagbit, valdiagbit, this)},
00099
     m_AllTerminations{CreateTerminationVector(termbit, this)},
00100
     m_theIntegrator{theIntegrator}
00101     {
00102     }
00103
00104     // This initializes/resets the geodesic with a given ScreenIndex, initial position, and initial
     velocity
00105     // Also resets all Diagnostics and Terminations, resets the TermCondition to Term::Continue,
00106     // and puts the Geodesic back to lambda = 0.0.
00107     void Reset(ScreenIndex scrindex, Point initpos, OneIndex initvel);
00108
00109     // This makes the Geodesic integrate itself one step; then the Geodesic loops through all
     Terminations and Diagnostics to update
00110     Term Update();
00111
00112     // Getters for properties of its internal state
00113     Term getTermCondition() const;      // Current termination condition (Term::Continue if not done
     integrating)
00114     Point getCurrentPos() const;       // Current position
00115     OneIndex getCurrentVel() const;     // Current velocity
00116     real getCurrentLambda() const;      // Current value of affine parameter
00117     ScreenIndex getScreenIndex() const; // screen index
00118
00119     // Output getters, to be called after the Geodesic terminates
00120     // This gets the complete output that should be written to the output files;
00121     // there is one string more than the count of Diagnostics: one string per Diagnostic,
00122     // PLUS the first string is the screen index.
00123     std::vector<std::string> getAllOutputStr() const;
00124     // This returns the "value" (from the Diagnostic that was set to the value Diagnostic) that is
     associated
00125     // to the Geodesic. Will be used to determine "distance" between Geodesics which is used in Mesh
     refinement.
00126     std::vector<real> getDiagnosticFinalValue() const;
00127
00128 private:
00129     // These variables define its internal state
00131     Term m_TermCond{Term::Uninitialized};
00133     Point m_CurrentPos{};
00135     OneIndex m_CurrentVel{};
00137     real m_curLambda{0.0};
00138
00141     ScreenIndex m_ScreenIndex{};
00142
00143     // These are const pointers (or const vectors of pointers) that contain all the information the
     Geodesic needs
00145     const Metric *const m_theMetric;
00147     const Source *const m_theSource;
00149     const DiagnosticUniqueVector m_AllDiagnostics;
00151     const TerminationUniqueVector m_AllTerminations;
00153     const GeodesicIntegratorFunc m_theIntegrator;
00154 };
```

```
00155
00156 #endif
```

7.16 FOORT/src/Geometry.h File Reference

Definitions and some operations with geometric objects.alignas.

```
#include <limits>
#include <string>
#include <array>
#include <utility>
#include <vector>
```

Macros

- #define LARGECOUNTER_MAX std::numeric_limits<largecounter>::max()

  Macro definition of maximum value that can be held in this large counter.
- #define PIXEL_MAX std::numeric_limits<pixelcoord>::max()

  Macro definition of maximum value that can be held in this large counter.

Typedefs

- using real = double

  A real number (could be changed to use arbitrary precision in the future).
- using largecounter = unsigned long

  This type is used to count geodesics integrated.
- using pixelcoord = largecounter

  A pixel coordinate: always >=0 and integer; we use the largecounter type.
- using Point = std::array<real, dimension>

  A point in spacetime. Note that coordinates are always assumed to be (t, r, theta, phi)
- using ScreenPoint = std::array<real, dimension - 2>

  A point on the ViewScreen; this does not have a time or radial extent.
- using ScreenIndex = std::array<pixelcoord, dimension - 2>

  An index on the ViewScreen (row, column)
- using OneIndex = Point

  Object with one index has the same structure as a Point.
- using TwoIndex = std::array<OneIndex, dimension>

  Object with two indices is an array of OneIndex objects.
- using ThreeIndex = std::array<TwoIndex, dimension>

  Object with three indices is an array of TwoIndex objects.
- using FourIndex = std::array<ThreeIndex, dimension>

  Object with four indices is an array of ThreeIndex objects.
- using SingularityCoord = std::pair<int, real>

  SingularityCoord: pair of (coordinate number, coordinate value)
- using Singularity = std::vector<SingularityCoord>

  Singularity: a number of SingularityCoords together that define a arbitrary codimension surface/line/point.

Functions

- template<size_t TensorDim>
  std::string toString (const std::array< largecounter, TensorDim > &theTensor)
  Base case for single index tensor of unsigned integers (ScreenIndex).
- template<size_t TensorDim>
  std::string toString (const std::array< real, TensorDim > &theTensor)
  Base case for single index tensor of reals (Point, OneIndex, ScreenPoint).
- template<typename Tensor, size_t TensorDim>
  std::string toString (const std::array< Tensor, TensorDim > &theTensor)
  General case for tensors with more than one index (TwoIndex, ThreeIndex, FourIndex).
- template<typename t, size_t TensorDim>
  std::array< t, TensorDim > operator+ (const std::array< t, TensorDim > &a1, const std::array< t, TensorDim > &a2)
  Function to recursively call + on the lower rank tensor (OR the underlying reals/ints, if the tensor is rank 1)
- template<typename t, size_t TensorDim>
  std::array< t, TensorDim > operator- (const std::array< t, TensorDim > &a1, const std::array< t, TensorDim > &a2)
  Function to recursively call - on the lower rank tensor (OR the underlying reals/ints, if the tensor is rank 1)
- template<typename t, size_t TensorDim>
  std::array< t, TensorDim > operator* (const std::array< t, TensorDim > &t1, real lambda)
  Function to recursively scalar multiply the lower-rank tensors (OR the underlying reals/ints for the rank-1 tensor)
- template<typename t, size_t TensorDim>
  std::array< t, TensorDim > operator* (real lambda, const std::array< t, TensorDim > &t1)
  Function to recursively scalar multiply the lower-rank tensors (OR the underlying reals/ints for the rank-1 tensor)
- template<typename t, size_t TensorDim>
  std::array< t, TensorDim > operator/ (const std::array< t, TensorDim > &t1, real lambda)
  Function to recursively scalar divide the lower-rank tensors (OR the underlying reals/ints for the rank-1 tensor)

Variables

- constexpr real pi {3.141592653589793}
  The value of pi.
- constexpr int dimension {4}
  The spacetime dimension.

7.16.1 Detailed Description

Definitions and some operations with geometric objects.alignas.

Author

Daniel R. Mayerson

Defines Point, tensors with 1-4 indices, and the operator toString for them. Also defines basic tensor arithmetic (+, -, *, /). No .cpp with implementations; all functions are inline.

Version

0.1

Date

2025-01-14

Copyright

Copyright (c) 2025

7.16.2 Macro Definition Documentation

7.16.2.1 LARGECOUNTER_MAX

```
#define LARGECOUNTER_MAX std::numeric_limits<largecounter>::max()
```

Macro definition of maximum value that can be held in this large counter.

7.16.2.2 PIXEL_MAX

```
#define PIXEL_MAX std::numeric_limits<pixelcoord>::max()
```

Macro definition of maximum value that can be held in this large counter.

7.16.3 Typedef Documentation

7.16.3.1 FourIndex

```
using FourIndex = std::array<ThreeIndex, dimension>
```

Object with four indices is an array of ThreeIndex objects.

7.16.3.2 largecounter

```
using largecounter = unsigned long
```

This type is used to count geodesics integrated.

7.16.3.3 OneIndex

```
using OneIndex = Point
```

Object with one index has the same structure as a Point.

7.16.3.4 pixelcoord

```
using pixelcoord = largecounter
```

A pixel coordinate: always >=0 and integer; we use the largecounter type.

7.16.3.5 Point

```
using Point = std::array<real, dimension>
```

A point in spacetime. Note that coordinates are always assumed to be (t, r, theta, phi)

7.16.3.6 real

```
using real = double
```

A real number (could be changed to use arbitrary precision in the future).

7.16.3.7 ScreenIndex

```
using ScreenIndex = std::array<pixelcoord, dimension - 2>
```

An index on the ViewScreen (row, column)

7.16.3.8 ScreenPoint

```
using ScreenPoint = std::array<real, dimension - 2>
```

A point on the ViewScreen; this does not have a time or radial extent.

7.16.3.9 Singularity

```
using Singularity = std::vector<SingularityCoord>
```

Singularity: a number of SingularityCoords together that define a arbitrary codimension surface/line/point.

7.16.3.10 SingularityCoord

```
using SingularityCoord = std::pair<int, real>
```

SingularityCoord: pair of (coordinate number, coordinate value)

7.16.3.11 ThreeIndex

```
using ThreeIndex = std::array<TwoIndex, dimension>
```

Object with three indices is an array of TwoIndex objects.

7.16.3.12 TwoIndex

```
using TwoIndex = std::array<OneIndex, dimension>
```

Object with two indices is an array of OneIndex objects.

7.16.4 Function Documentation

7.16.4.1 operator∗() [1/2]

```
template<typename t, size_t TensorDim>
std::array< t, TensorDim > operator* (
            const std::array< t, TensorDim > & t1,
            real lambda)
```

Function to recursively scalar multiply the lower-rank tensors (OR the underlying reals/ints for the rank-1 tensor)

Template Parameters

t	Type of the tensor
TensorDim	Dimension of the tensor

Parameters

t1	Tensor
lambda	Scalar

Returns

std::array<t, TensorDim> Scalar product of t1 and lambda

7.16.4.2 operator*() [2/2]

```
template<typename t, size_t TensorDim>
std::array< t, TensorDim > operator* (
            real lambda,
            const std::array< t, TensorDim > & t1)
```

Function to recursively scalar multiply the lower-rank tensors (OR the underlying reals/ints for the rank-1 tensor)

This function calls the right multiplication operator.

Template Parameters

t	Type of the tensor
TensorDim	Dimension of the tensor

Parameters

lambda	Scalar
t1	Tensor

Returns

std::array<t, TensorDim> Scalar product of lambda and t1

7.16.4.3 operator+()

```
template<typename t, size_t TensorDim>
std::array< t, TensorDim > operator+ (
            const std::array< t, TensorDim > & a1,
            const std::array< t, TensorDim > & a2)
```

Function to recursively call + on the lower rank tensor (OR the underlying reals/ints, if the tensor is rank 1)

Template Parameters

t	data type of the tensor
TensorDim	Dimension of the tensor

Parameters

a1	Tensor 1
a2	Tensor 2

Returns

std::array<t, TensorDim> Tensor sum of a1 and a2

7.16.4.4 operator-()

```
template<typename t, size_t TensorDim>
std::array< t, TensorDim > operator- (
            const std::array< t, TensorDim > & a1,
            const std::array< t, TensorDim > & a2)
```

Function to recursively call - on the lower rank tensor (OR the underlying reals/ints, if the tensor is rank 1)

Template Parameters

t	data type of the tensor
TensorDim	Dimension of the tensor

Parameters

a1	Tensor 1
a2	Tensor 2

Returns

std::array<t, TensorDim> Tensor difference of a1 and a2

7.16.4.5 operator/()

```
template<typename t, size_t TensorDim>
std::array< t, TensorDim > operator/ (
            const std::array< t, TensorDim > & t1,
            real lambda)
```

Function to recursively scalar divide the lower-rank tensors (OR the underlying reals/ints for the rank-1 tensor)

This function calls the right multiplication operator.

Template Parameters

t	Type of the tensor
TensorDim	Dimension of the tensor

Parameters

t1	Tensor
lambda	Scalar

Returns

std::array<t, TensorDim> Scalar division of t1 by lambda

7.16.4.6 toString() [1/3]

```
template<size_t TensorDim>
std::string toString (
            const std::array< largecounter, TensorDim > & theTensor)
```

Base case for single index tensor of unsigned integers (ScreenIndex).

We do not want toString(ScreenIndex) to convert its entries to reals and use the implementation for a single index tensor of reals, because we do not want decimal points in our string for the ints!

Template Parameters

TensorDim	Dimension of the tensor

Parameters

theTensor	Tensor object

Returns

std::string

7.16.4.7 toString() [2/3]

```
template<size_t TensorDim>
std::string toString (
            const std::array< real, TensorDim > & theTensor)
```

Base case for single index tensor of reals (Point, OneIndex, ScreenPoint).

Template Parameters

TensorDim	Dimension of the tensor

Parameters

theTensor	Tensor object

Returns

std::string

7.16.4.8 toString() [3/3]

```
template<typename Tensor, size_t TensorDim>
std::string toString (
            const std::array< Tensor, TensorDim > & theTensor)
```

General case for tensors with more than one index (TwoIndex, ThreeIndex, FourIndex).

This function recursively calls the lower rank tensor to print itself.

Template Parameters

Tensor	The type of the tensor
TensorDim	Dimension of the tensor

Parameters

theTensor	Tensor object

Returns

std::string

7.16.5 Variable Documentation

7.16.5.1 dimension

```
int dimension {4}  [inline], [constexpr]
```

The spacetime dimension.

7.16.5.2 pi

```
real pi {3.141592653589793}  [inline], [constexpr]
```

The value of pi.

7.17 Geometry.h

Go to the documentation of this file.

```
00001 #ifndef _FOORT_GEOMETRY_H
00002 #define _FOORT_GEOMETRY_H
00003
00014
00015 #include <limits>  // for std::numeric_limits
00016 #include <string>  // needed for toString(...) to convert tensors to strings
00017 #include <array>   // needed to define tensors as fixed-size arrays of real or pixelcoord
00018 #include <utility> // needed for std::pair
00019 #include <vector>  // for std::vector
00020
00022 using real = double;
00023
00024 // Note: An unsigned long is guaranteed to be able to hold at least 4 294 967 295 (4.10^10).
00025 // An unsigned int is only guaranteed to be able to hold 65 535, although
00026 // many modern-day implementations will actually make the int 32-bit and so much larger
00027
00029 using largecounter = unsigned long;
00031 using pixelcoord = largecounter;
00032
00034 #ifndef LARGECOUNTER_MAX
00035 #define LARGECOUNTER_MAX std::numeric_limits<largecounter>::max()
00036 #endif
00038 #ifndef PIXEL_MAX
00039 #define PIXEL_MAX std::numeric_limits<pixelcoord>::max()
00040 #endif
00041
00042 // CONSTANTS
00043
00045 inline constexpr real pi{3.141592653589793};
00046
00048 inline constexpr int dimension{4};
00049
00050 // TENSOR DEFINITIONS
00051
00053 using Point = std::array<real, dimension>;
00054
00056 using ScreenPoint = std::array<real, dimension - 2>;
00057
00059 using ScreenIndex = std::array<pixelcoord, dimension - 2>;
00060
00062 using OneIndex = Point;
00064 using TwoIndex = std::array<OneIndex, dimension>;
00066 using ThreeIndex = std::array<TwoIndex, dimension>;
00068 using FourIndex = std::array<ThreeIndex, dimension>;
00069
00070 // Definition used to define singularity of arbitrary codimension
00072 using SingularityCoord = std::pair<int, real>;
00074 using Singularity = std::vector<SingularityCoord>;
00075
00076 // PRINTING TENSORS TO STRING
00077
00087 template <size_t TensorDim>
00088 std::string toString(const std::array<largecounter, TensorDim> &theTensor)
00089 {
00090     std::string theStr{"("}; // no spaces for the innermost brackets
00091     for (int i = 0; i < static_cast<int>(TensorDim) - 1; ++i)
00092     {
00093         // Here we use the std::to_string to convert the real to string
00094         theStr += std::to_string(theTensor[i]);
00095         theStr += ", ";
00096     }
00097     theStr += std::to_string(theTensor[TensorDim - 1]);
00098     theStr += ")"; // no spaces for the innermost brackets
00099
00100     return theStr;
00101 }
00102
00110 template <size_t TensorDim>
00111 std::string toString(const std::array<real, TensorDim> &theTensor)
00112 {
00113     std::string theStr{"("}; // no spaces for the innermost brackets
00114
00115     for (int i = 0; i < static_cast<int>(TensorDim) - 1; ++i)
00116     {
00117         // Here we use the std::to_string to convert the real to string
00118         theStr += std::to_string(theTensor[i]);
00119         theStr += ", ";
00120     }
00121     theStr += std::to_string(theTensor[TensorDim - 1]);
00122     theStr += ")"; // no spaces for the innermost brackets
00123
00124     return theStr;
```

```
00125 }
00126
00135 template <typename Tensor, size_t TensorDim>
00136 std::string toString(const std::array<Tensor, TensorDim> &theTensor)
00137 {
00138     std::string theStr{"( "}; // All but the innermost brackets have an extra space padding the
      bracket
00139
00140     for (int i = 0; i < TensorDim - 1; ++i)
00141     {
00142         theStr += toString(theTensor[i]);
00143         theStr += ", ";
00144     }
00145     theStr += toString(theTensor[TensorDim - 1]); // the last element doesn't have a comma after it
00146
00147     theStr += " )"; // All but the innermost brackets have an extra space padding the bracket
00148
00149     return theStr;
00150 }
00151
00152 // TENSOR ARITHMETIC: addition/subtraction of tensors, scalar multiplication/division
00153
00163 template <typename t, size_t TensorDim>
00164 std::array<t, TensorDim> operator+(const std::array<t, TensorDim> &a1, const std::array<t, TensorDim>
      &a2)
00165 {
00166     std::array<t, TensorDim> temp{a1};
00167     for (int i = 0; i < static_cast<int>(TensorDim); ++i)
00168         temp[i] = temp[i] + a2[i];
00169
00170     return temp;
00171 }
00172
00182 template <typename t, size_t TensorDim>
00183 std::array<t, TensorDim> operator-(const std::array<t, TensorDim> &a1, const std::array<t, TensorDim>
      &a2)
00184 {
00185     std::array<t, TensorDim> temp{a1};
00186     for (int i = 0; i < static_cast<int>(TensorDim); ++i)
00187         temp[i] = temp[i] - a2[i];
00188
00189     return temp;
00190 }
00191
00201 template <typename t, size_t TensorDim>
00202 std::array<t, TensorDim> operator*(const std::array<t, TensorDim> &t1, real lambda)
00203 {
00204     std::array<t, TensorDim> temp{t1};
00205     for (int i = 0; i < static_cast<int>(TensorDim); ++i)
00206         temp[i] = static_cast<t>(temp[i] * lambda); // static_cast necessary if t is integral type!
00207     return temp;
00208 }
00209
00219 template <typename t, size_t TensorDim>
00220 std::array<t, TensorDim> operator*(real lambda, const std::array<t, TensorDim> &t1)
00221 {
00222     return t1 * lambda;
00223 }
00224
00234 template <typename t, size_t TensorDim>
00235 std::array<t, TensorDim> operator/(const std::array<t, TensorDim> &t1, real lambda)
00236 {
00237     return t1 * (1 / lambda);
00238 }
00239
00240 #endif
```

7.18 FOORT/src/InputOutput.cpp File Reference

```
#include "InputOutput.h"
#include <algorithm>
#include <filesystem>
```

Functions

- void SetOutputLevel (OutputLevel theLvl)

Set the Output Level.

- void SetLoopMessageFrequency (largecounter thefreq)

  Set the Loop Message Frequency.
- largecounter GetLoopMessageFrequency ()

  Get the Loop Message Frequency during integration loops.
- void ScreenOutput (std::string_view theOutput, OutputLevel lvl, bool newLine)

  Outputs line to screen console, contingent on it being allowed by the set outputlevel.

7.18.1 Detailed Description

Author

Daniel R. Mayerson

Version

0.1

Date

2025-01-14

Copyright

Copyright (c) 2025

7.18.2 Function Documentation

7.18.2.1 GetLoopMessageFrequency()

```
largecounter GetLoopMessageFrequency ()
```

Get the Loop Message Frequency during integration loops.

Returns

largecounter

7.18.2.2 ScreenOutput()

```
void ScreenOutput (
            std::string_view theOutput,
            OutputLevel lvl,
            bool newLine)
```

Outputs line to screen console, contingent on it being allowed by the set outputlevel.

Defaults are lvl = OutputLevel::Level_3_ALLDETAIL and newLine = true

Parameters

theOutput	output to be put on the screen
lvl	the output level
newLine	indicates whether we want a new line after the output

7.18.2.3 SetLoopMessageFrequency()

```
void SetLoopMessageFrequency (
            largecounter thefreq)
```

Set the Loop Message Frequency.

Parameters

thefreq	the desired frequency

7.18.2.4 SetOutputLevel()

```
void SetOutputLevel (
            OutputLevel theLvl)
```

Set the Output Level.

Parameters

theLvl	The desired level

7.19 FOORT/src/InputOutput.h File Reference

Declarations of functions & classes that deal with the output to files and to the screen.

```
#include "Geometry.h"
#include <string_view>
#include <iostream>
#include <fstream>
#include <string>
#include <vector>
```

Classes

- class GeodesicOutputHandler

  // GeodesicOutputHandler handles all of the output to file. It gets passed all of the output strings for every Geodesic, it then stores this data until it eventually writes all data to the appropriate files

Enumerations

- enum class OutputLevel {
  Level_0_WARNING = 0 , Level_1_PROC = 1 , Level_2_SUBPROC = 2 , Level_3_ALLDETAIL = 3 ,
  Level_4_DEBUG = 4 , MaxLevel }

  The output level determines at what priority level the output is generated to the console.

Functions

- void SetOutputLevel (OutputLevel theLvl)

  Set the Output Level.
- void ScreenOutput (std::string_view theOutput, OutputLevel lvl=OutputLevel::Level_3_ALLDETAIL, bool newLine=true)

  Outputs line to screen console, contingent on it being allowed by the set outputlevel.
- void SetLoopMessageFrequency (largecounter thefreq)

  Set the Loop Message Frequency.
- largecounter GetLoopMessageFrequency ()

  Get the Loop Message Frequency during integration loops.

7.19.1 Detailed Description

Declarations of functions & classes that deal with the output to files and to the screen.

Author

Daniel R. Mayerson

Version

0.1

Date

2025-01-14

Copyright

Copyright (c) 2025

7.19.2 Enumeration Type Documentation

7.19.2.1 OutputLevel

```
enum class OutputLevel  [strong]
```

The output level determines at what priority level the output is generated to the console.

Level_0_WARNING: Only warnings are outputted. Level_1_PROC: Coarsest level output; only the major procedures produce output. Level_2_SUBPROC: Subprocedures can also produce output. Level_3_ALLDETAIL: Finest level output; all details are shown. Level_4_DEBUG: Finest level output AND debug messages as well.

Enumerator

Level_0_WARNING	
Level_1_PROC	
Level_2_SUBPROC	
Level_3_ALLDETAIL	
Level_4_DEBUG	
MaxLevel	

7.19.3 Function Documentation

7.19.3.1 GetLoopMessageFrequency()

```
largecounter GetLoopMessageFrequency ()
```

Get the Loop Message Frequency during integration loops.

Returns

largecounter

7.19.3.2 ScreenOutput()

```
void ScreenOutput (
            std::string_view theOutput,
            OutputLevel lvl,
            bool newLine)
```

Outputs line to screen console, contingent on it being allowed by the set outputlevel.

Defaults are lvl = OutputLevel::Level_3_ALLDETAIL and newLine = true

Parameters

theOutput	output to be put on the screen
lvl	the output level
newLine	indicates whether we want a new line after the output

7.19.3.3 SetLoopMessageFrequency()

```
void SetLoopMessageFrequency (
            largecounter thefreq)
```

Set the Loop Message Frequency.

Parameters

thefreq	the desired frequency

7.19.3.4 SetOutputLevel()

```
void SetOutputLevel (
            OutputLevel theLvl)
```

Set the Output Level.

Parameters

theLvl	The desired level

7.20 InputOutput.h

Go to the documentation of this file.

```
00001 #ifndef _FOORT_INPUTOUTPUT_H
00002 #define _FOORT_INPUTOUTPUT_H
00003
00012
00013 #include "Geometry.h" // for basic tensor objects
00014
00015 #include <string_view> // std::string_view
00016 #include <iostream>    // needed for file and console output
00017 #include <fstream>     // needed for file ouput
00018 #include <string>      // std::string used in various places
00019 #include <vector>      // needed to create vectors of strings
00020
00021 // SCREENOUTPUT
00022
00031 enum class OutputLevel
00032 {
00033     Level_0_WARNING = 0,
00034     Level_1_PROC = 1,
00035     Level_2_SUBPROC = 2,
00036     Level_3_ALLDETAIL = 3,
00037     Level_4_DEBUG = 4,
00038
00039     MaxLevel // (unused)
00040 };
00041
00042 // Set the output level used; note: the output level itself is a static variable in InputOutput.cpp
00043 void SetOutputLevel(OutputLevel theLvl);
00044
00045 // Outputs line to screen console), contingent on it being allowed by the set outputlevel
00046 void ScreenOutput(std::string_view theOutput, OutputLevel lvl = OutputLevel::Level_3_ALLDETAIL, bool
      newLine = true);
00047
00048 // Set and Get for the loop message frequency (messages indicating progress during each integration
      loop)
00049 void SetLoopMessageFrequency(largecounter thefreq);
00050 largecounter GetLoopMessageFrequency();
00051
00052 // FILE OUTPUT
00053
00059 class GeodesicOutputHandler
00060 {
00061 public:
00062     // No default constructor possible
00063     GeodesicOutputHandler() = delete;
00064     // Constructor must pass the following strings that are used to construct the file names of the
      output file:
00065     // FilePrefix, TimeStamp, FileExtension, and a vector of strings DiagNames (the names of each of
      the Diagnostics that will
00066     // be outputting). It must also specify how many outputs to cache before outputting to a file, and
00067     // how many geodesics are allowed per file created
```

```
00068     GeodesicOutputHandler(std::string FilePrefix, std::string TimeStamp, std::string FileExtension,
00069                           std::vector<std::string> DiagNames,
00070                           largecounter nroutputstocache = LARGECOUNTER_MAX - 1, // note -1,
00071                                                                                 // since we will
      actually cache one more then this number before outputting everything
00072                           largecounter geodperfile = LARGECOUNTER_MAX,
00073                           std::string firstlineinfo = "");
00074
00075     // This tells the OutputHandler to prepare for this many geodesic outputs to arrive;
00076     // the internal state needs to be prepared such that they can come in without providing a data
      race
00077     void PrepareForOutput(largecounter nrOutputToCome);
00078
00079     // A new vector of output strings from a (single) Geodesic;
00080     // the length of the vector should be m_DiagNames.size()+1, since the first entry
00081     // is the screen index
00082     // NOTE: this procedure needs to be thread-safe!
00083     void NewGeodesicOutput(largecounter index, std::vector<std::string> theOutput);
00084
00085     // Calling this indicates that there is no further output to be expected;
00086     // this means we will write all remaining cached output to file
00087     void OutputFinished();
00088
00089     // Returns full description string of output handler
00090     std::string getFullDescriptionStr() const;
00091
00092 private:
00093     // Helper function: write everything that is cached to file now (clear the cache)
00094     void WriteCachedOutputToFile();
00095
00096     // Helper function: open the file with name filename for the first time, preparing it to write
00097     // This will effectively clear this file of any pre-existing content.
00098     void OpenForFirstTime(const std::string &filename);
00099
00100     // Helper function: return the full file name for the n-th output file
00101     // for the Diagnostic diagnr (this is an entry in m_DiagNames)
00102     std::string GetFileName(int diagnr, unsigned short filenr) const;
00103
00104     // The const strings that are used to construct the output file names
00106     const std::string m_FilePrefix;
00108     const std::string m_TimeStamp;
00110     const std::string m_FileExtension;
00112     const std::vector<std::string> m_DiagNames;
00113
00115     const bool m_PrintFirstLineInfo;
00117     const std::string m_FirstLineInfoString;
00118
00119     // Const setting the maximum number of outputs that can be cached before writing output to file.
00120     const largecounter m_nrOutputsToCache{};
00122     const largecounter m_nrGeodesicsPerFile{};
00123
00125     bool m_WriteToConsole{false};
00126
00128     largecounter m_PrevCached{0};
00129
00131     largecounter m_CurrentGeodesicsInFile{0};
00132
00134     unsigned short m_CurrentFullFiles{0};
00135
00137     std::vector<std::vector<std::string» m_AllCachedData{};
00138 };
00139
00140 #endif
```

7.21 FOORT/src/Integrators.cpp File Reference

```
#include "Integrators.h"
#include "Geodesic.h"
#include "InputOutput.h"
#include <algorithm>
#include <atomic>
#include <cmath>
#include <sstream>
#include <iostream>
```

7.21.1 Detailed Description

Author

Daniel R. Mayerson

Version

0.1

Date

2025-01-14

Copyright

Copyright (c) 2025

7.22 FOORT/src/Integrators.h File Reference

Declarations of integrator functions that integrate geodesic equation.

```
#include "Geometry.h"
#include "Metric.h"
#include <string>
```

Namespaces

- namespace Integrators

Typedefs

- using GeodesicIntegratorFunc = void (∗)(Point, OneIndex, Point &, OneIndex &, real &, const Metric ∗, const Source ∗)

Functions

- std::string Integrators::GetFullIntegratorDescription ()

  Description string getter for the Integrator.
- real Integrators::GetAdaptiveStep (Point curpos, OneIndex curvel)

  Determine the (affine parameter) step size to take.
- void Integrators::IntegrateGeodesicStep_RK4 (Point curpos, OneIndex curvel, Point &nextpos, OneIndex &nextvel, real &stepsize, const Metric ∗theMetric, const Source ∗theSource)

  Integrate the geodesic equation by one step using Runge-Kutta-4.
- void Integrators::IntegrateGeodesicStep_Verlet (Point curpos, OneIndex curvel, Point &nextpos, OneIndex &nextvel, real &stepsize, const Metric ∗theMetric, const Source ∗theSource)

  Integrate the geodesic equation by one step using the Verlet algorithm.

Variables

- constexpr real Integrators::delta_nodiv0 = 1e-20

  This is used to avoid dividing by zero.
- real Integrators::Derivative_hval {1e-7}

  The spacing used in stencils for the calculation of numerical derivatives (e.g. in Christoffel symbols)
- std::string Integrators::IntegratorDescription {"Verlet"}

  The name of the integrator selected.
- real Integrators::epsilon {0.03}

  This is the base step size to be taken (the integrator will adapt this if necessary)
- real Integrators::SmallestPossibleStepsize {1e-12}

  The affine parameter must always go forward by at least this amount.
- real Integrators::VerletVelocityTolerance {-1.0}
- largecounter Integrators::VerletMaxIterations {100}

7.22.1 Detailed Description

Declarations of integrator functions that integrate geodesic equation.

Author

Daniel R. Mayerson

Version

0.1

Date

2025-01-14

Copyright

Copyright (c) 2025

7.22.2 Typedef Documentation

7.22.2.1 GeodesicIntegratorFunc

```
using GeodesicIntegratorFunc = void (*)(Point, OneIndex, Point &, OneIndex &, real &, const
Metric *, const Source *)
```

7.23 Integrators.h

Go to the documentation of this file.

```
00001 #ifndef _FOORT_INTEGRATORS_H
00002 #define _FOORT_INTEGRATORS_H
00003
00012
00013 #include "Geometry.h" // for basic tensor objects
00014 #include "Metric.h"   // for the metric
00015
00016 #include <string> // std::string
00017
00019 class Source;
00020
00021 // This is the structure of a function that integrates the geodesic equation one step
00022 // It takes as arguments:
00023 // - current position, current velocity
00024 // - references to: next position, next velocity, affine parameter step size (which the functions
      sets)
00025 // - pointers to: the Metric, the Source that are used to evaluate the geodesic equation
00026 using GeodesicIntegratorFunc = void (*)(Point, OneIndex, Point &, OneIndex &, real &, const Metric *,
      const Source *);
00027
00028 // Namespace for integrator constants and functions
00029 namespace Integrators
00030 {
00032     constexpr real delta_nodiv0 = 1e-20;
00033
00035     inline real Derivative_hval{1e-7};
00036
00038     inline std::string IntegratorDescription{"Verlet"};
00039
00040     // Full descriptive string of integrator and all integrator options
00041     std::string GetFullIntegratorDescription();
00042
00044     inline real epsilon{0.03};
00045
00047     inline real SmallestPossibleStepsize{1e-12};
00048
00049     // Function to get  (adaptive) step size
00050     real GetAdaptiveStep(Point curpos, OneIndex curvel);
00051
00052     // This is a GeodesicIntegratorFunc
00053     // Using the Runge-Kutta-4 algorithm to integrate the geodesic equation
00054     void IntegrateGeodesicStep_RK4(Point curpos, OneIndex curvel,
00055                                    Point &nextpos, OneIndex &nextvel, real &stepsize, const Metric
      *theMetric, const Source *theSource);
00056
00059     inline real VerletVelocityTolerance{-1.0};
00060
00063     inline largecounter VerletMaxIterations{100};
00064
00065     // This is a GeodesicIntegratorFunc
00066     // Using the velocity Verlet algorithm to integrate the geodesic equation
00067     void IntegrateGeodesicStep_Verlet(Point curpos, OneIndex curvel,
00068                                       Point &nextpos, OneIndex &nextvel, real &stepsize, const Metric
      *theMetric, const Source *theSource);
00069 }
00070
00071 #endif
```

7.24 FOORT/src/Main.cpp File Reference

Main function for FOORT.

```
#include "Config.h"
#include "Diagnostics.h"
#include "Geodesic.h"
#include "Geometry.h"
#include "InputOutput.h"
#include "Integrators.h"
#include "Metric.h"
#include "Terminations.h"
```

```
#include "Utilities.h"
#include "ViewScreen.h"
#include <omp.h>
#include <iostream>
```

Functions

- int main (int argc, char ∗argv[ ])

7.24.1 Detailed Description

Main function for FOORT.

Author

Daniel R. Mayerson

Version

1.0

Date

2025-1-21

Copyright

Copyright (c) 2025

7.24.2 Function Documentation

7.24.2.1 main()

```
int main (
            int argc,
            char * argv[])
```

7.25 FOORT/src/Mesh.cpp File Reference

```
#include "Mesh.h"
#include "Utilities.h"
#include <algorithm>
#include <limits>
#include <iostream>
```

7.25.1 Detailed Description

Author

Daniel R. Mayerson

Version

0.1

Date

2025-01-14

Copyright

Copyright (c) 2025

7.26 FOORT/src/Mesh.h File Reference

Declarations of abstract base Mesh class and all its descendants.

```
#include "Geometry.h"
#include "Diagnostics.h"
#include "InputOutput.h"
#include <cmath>
#include <utility>
#include <forward_list>
#include <memory>
#include <vector>
#include <array>
#include <string>
```

Classes

- class Mesh

  Abstract base Mesh class.
- class SimpleSquareMesh

  A simple square mesh that will integrate a square of evenly spaced pixels.
- class InputCertainPixelsMesh

  Mesh which integrates only certain user-inputted pixels.
- class SquareSubdivisionMesh

  Adaptive subdivision Mesh.
- struct SquareSubdivisionMesh::PixelInfo

  A struct the Mesh uses to keep all information about a given pixel.

7.26.1 Detailed Description

Declarations of abstract base Mesh class and all its descendants.

Author

Daniel R. Mayerson

Version

0.1

Date

2025-01-14

Copyright

Copyright (c) 2025

7.27 Mesh.h

Go to the documentation of this file.

```
00001 #ifndef _FOORT_MESH_H
00002 #define _FOORT_MESH_H
00003
00012
00013 #include "Geometry.h"  // needed for basic tensor objects
00014 #include "Diagnostics.h" // needed for Diagnostic "value" and "distance" functions
00015 #include "InputOutput.h" // needed for ScreenOutput
00016
00017 #include <cmath>        // needed for sqrt (only on Linux)
00018 #include <utility>      // std::move
00019 #include <forward_list> // std::forward_list
00020 #include <memory>       // std::unique_ptr
00021 #include <vector>       // std::vector
00022 #include <array>        // std::array
00023 #include <string>       // for strings
00024
00028 class Mesh
00029 {
00030 public:
00031     // Basic constructor constructs Diagnostic that is used for determinines "values" and "distances"
      between values
00032     Mesh(DiagBitflag valdiag)
00033         // Calling CreateDiagnosticVector in this way will create a vector with exactly one element in
      it,
00034         // i.e. the Diagnostic we need!
00035         : m_DistanceDiagnostic{std::move((CreateDiagnosticVector(valdiag, valdiag, nullptr))[0])}
00036     {
00037     }
00038
00039     // virtual destructor to ensure correct destruction of descendants
00040     virtual ~Mesh() = default;
00041
00042     // Getter for how many geodesics the Mesh currently wants to integrate in this iteration
00043     virtual largecounter getCurNrGeodesics() const = 0;
00044
00045     // This sets a new initial conditions (in the form of a ScreenPoint and ScreenIndex)
00046     // for a next pixel to be integrated in the current iteration
00047     virtual void getNewInitConds(largecounter index, ScreenPoint &newunitpoint, ScreenIndex
      &newscreenindex) const = 0;
00048
00049     // When a geodesic is finished integrating, it tells the Mesh and passes on its final "value"
00050     // NOTE: despite being a non-const member function, this must be designed to be thread-safe!
00051     virtual void GeodesicFinished(largecounter index, std::vector<real> finalValues) = 0;
00052
```

```
00053     // This is called when the current iteration is finished. The Mesh can now evaluate whether to
      continue or not
00054     virtual void EndCurrentLoop() = 0;
00055
00056     // Returns false if the Mesh wants another iteration of pixels to integrate
00057     virtual bool IsFinished() const = 0;
00058
00059     // Returns a string description of the Mesh (spaces allowed), describing its options
00060     virtual std::string getFullDescriptionStr() const;
00061
00062 protected:
00064     const std::unique_ptr<const Diagnostic> m_DistanceDiagnostic;
00065 };
00066
00070 class SimpleSquareMesh final : public Mesh
00071 {
00072 public:
00073     // Default constructor not possible
00074     SimpleSquareMesh() = delete;
00075     // Constructor initializes total number of pixels and passes valdiag to base constructor
00076     // Note that we static_cast the sqrt() to round off the row/column size to an integer number
00077     SimpleSquareMesh(largecounter totalPixels, DiagBitflag valdiag)
00078         : Mesh(valdiag),
00079           m_TotalPixels{static_cast<pixelcoord>(sqrt(totalPixels)) *
      static_cast<pixelcoord>(sqrt(totalPixels))},
00080           m_RowColumnSize{static_cast<pixelcoord>(sqrt(totalPixels))}
00081     {
00082         if constexpr (dimension != 4)
00083             ScreenOutput("SimpleSquareMesh only defined in 4D!", OutputLevel::Level_0_WARNING);
00084     }
00085
00086     // Declarations of overriding virtual functions
00087
00088     largecounter getCurNrGeodesics() const final;
00089
00090     void getNewInitConds(largecounter index, ScreenPoint &newunitpoint, ScreenIndex &newscreenindex)
      const final;
00091
00092     void GeodesicFinished(largecounter index, std::vector<real> finalValues) final;
00093
00094     void EndCurrentLoop() final;
00095
00096     bool IsFinished() const final;
00097
00098     // Description string getter
00099     std::string getFullDescriptionStr() const final;
00100
00101 private:
00103     const largecounter m_TotalPixels;
00105     const pixelcoord m_RowColumnSize;
00107     bool m_Finished{false};
00108 };
00109
00113 class InputCertainPixelsMesh : public Mesh
00114 {
00115 public:
00116     // Default constructor not possible
00117     InputCertainPixelsMesh() = delete;
00118     // Copy constructor not possible
00119     InputCertainPixelsMesh(const InputCertainPixelsMesh &) = delete;
00120     // Constructor given in Mesh.cpp file; constructor asks for input of pixels
00121     InputCertainPixelsMesh(largecounter totalPixels, DiagBitflag valdiag);
00122
00123     // Declarations of overriding virtual functions
00124
00125     largecounter getCurNrGeodesics() const final;
00126
00127     void getNewInitConds(largecounter index, ScreenPoint &newunitpoint, ScreenIndex &newscreenindex)
      const final;
00128
00129     void GeodesicFinished(largecounter index, std::vector<real> finalValues) final;
00130
00131     void EndCurrentLoop() final;
00132
00133     bool IsFinished() const final;
00134
00135     // Description string getter
00136     std::string getFullDescriptionStr() const final;
00137
00138 private:
00140     const pixelcoord m_RowColumnSize;
00141
00143     largecounter m_TotalPixels{0};
00145     std::vector<ScreenIndex> m_PixelsToIntegrate{};
00147     bool m_Finished{false};
00148 };
00149
```

```
00160 class SquareSubdivisionMesh : public Mesh
00161 {
00162 public:
00163     // default constructor not possible
00164     SquareSubdivisionMesh() = delete;
00165     // Constructor must be called with arguments:
00166     // - maxPixels: max. nr of pixels that can be integrated in TOTAL, over all iterations (if 0, then
      this is infinite,
00167     // i.e. we keep integrating until all squares are maximally subdivided or have weight 0)
00168     // - initialPixels: initial number of pixels to integrate (spaced equally over the screen)
00169     // - maxSubdivide: maximum number of times that we can subdivide squares (note: 1 denotes the
00170     // initial grid, so 2 would be subdividing the squares once)
00171     // - iterationPixels: maximum number of pixels to subdivide in each integration iteration
00172     // (max number of pixels that will be integrates is then 5*iterationPixels)
00173     // - initialSubToFinal: once we decide to subdivide a square, do we automatically keep subdividing
      it
00174     // until we reach maxSubdivision?
00175     // - valdiag: the "value" and "distance" Diagnostic to use
00176     SquareSubdivisionMesh(largecounter maxPixels, largecounter initialPixels, int maxSubdivide,
      largecounter iterationPixels, bool initialSubToFinal,
00177                           DiagBitflag valdiag)
00178         : Mesh(valdiag),
00179           m_InitialPixels{static_cast<pixelcoord>(sqrt(initialPixels)) *
      static_cast<pixelcoord>(sqrt(initialPixels))},
00180           m_MaxSubdivide{maxSubdivide},
00181           m_RowColumnSize{(static_cast<pixelcoord>(sqrt(initialPixels)) - 1) * ExpInt(2, maxSubdivide
      - 1) + 1},
00182           m_IterationPixels{iterationPixels}, m_MaxPixels{maxPixels},
      m_InitialSubDivididetoFinal{initialSubToFinal},
00183           m_InfinitePixels{maxPixels == 0}, m_PixelsLeft{maxPixels}
00184     {
00185         if constexpr (dimension != 4)
00186             ScreenOutput("SquareSubdivisionMesh only defined in 4D!", OutputLevel::Level_0_WARNING);
00187
00188         // Initialize the initial square, equally spaced grid
00189         InitializeFirstGrid();
00190     }
00191
00192     // Declarations of overriding virtual functions
00193
00194     largecounter getCurNrGeodesics() const final;
00195
00196     void getNewInitConds(largecounter index, ScreenPoint &newunitpoint, ScreenIndex &newscreenindex)
      const final;
00197
00198     void GeodesicFinished(largecounter index, std::vector<real> finalValues) final;
00199
00200     void EndCurrentLoop() final;
00201
00202     bool IsFinished() const final;
00203
00204     // Description string getter
00205     std::string getFullDescriptionStr() const final;
00206
00207 private:
00209     const largecounter m_InitialPixels;
00211     const int m_MaxSubdivide;
00213     const pixelcoord m_RowColumnSize;
00215     const largecounter m_IterationPixels;
00217     const largecounter m_MaxPixels;
00219     const bool m_InitialSubDivididetoFinal;
00221     const bool m_InfinitePixels;
00222
00224     largecounter m_PixelsLeft;
00225
00227     largecounter m_PixelsIntegrated{0};
00228
00232     struct PixelInfo
00233     {
00234         // Constructor with its ScreenIndex and current subdivision level
00235         PixelInfo(ScreenIndex ind, int subdiv) : Index{ind}, SubdivideLevel{subdiv} {}
00236
00238         const ScreenIndex Index{};
00239
00241         int SubdivideLevel{};
00242
00244         real Weight{-1};
00245
00247         std::vector<real> DiagValue{};
00248
00250         PixelInfo *LeftNbr{nullptr};
00252         PixelInfo *RightNbr{nullptr};
00254         PixelInfo *UpNbr{nullptr};
00256         PixelInfo *DownNbr{nullptr};
00258         PixelInfo *SEdiagNbr{nullptr};
00259     };
00260
```

```
00262     std::forward_list<std::unique_ptr<PixelInfo» m_AllPixels{};
00263
00265     std::vector<PixelInfo *> m_ActivePixels{};
00267     std::vector<PixelInfo *> m_CurrentPixelQueue{};
00269     // (char instead of bool to avoid race conditions when multiple threads are writing to the same
      bool; std::vector<bool> is the only std::vector that is not thread-safe)
00270     std::vector<char> m_CurrentPixelQueueDone{};
00272     std::vector<PixelInfo *> m_CurrentPixelUpdating{};
00273
00274     // Initializes the first nxn screen and puts them in m_CurrentPixelQueue
00275     void InitializeFirstGrid();
00276
00277     // Updates all weights of the pixels in m_CurrentPixelUpdating;
00278     // these should have subdiv > 0 and subdiv < m_MaxSubdivide, and all their neigbors assigned
      correctly
00279     // All pixels with weight > 0 will be added to m_ActivePixels
00280     void UpdateAllWeights();
00281
00282     // Helper functions that return the appropriate neighbor of p, ONLY if this neighbor exists at the
      subdivision level specified
00283     // Returns nullptr otherwise; also return nullptr if p==nullptr
00284     PixelInfo *GetUp(PixelInfo *p, int subdiv) const;
00285     PixelInfo *GetDown(PixelInfo *p, int subdiv) const;
00286     PixelInfo *GetRight(PixelInfo *p, int subdiv) const;
00287     PixelInfo *GetLeft(PixelInfo *p, int subdiv) const;
00288
00289     // This will take the pixel m_AllPixels[ind] and subdivide it,
00290     // adding up to <=5 pixels to the CurrentPixelQueue
00291     void SubdivideAndQueue(largecounter ind);
00292
00293     // Helper function to exponentiate an int to an int
00294     // Note: the result can be larger than fits in an int, but the base is always 2 and the exp is
      always
00295     // a number <=m_MaxSubdivide (which is an int)
00296     pixelcoord ExpInt(int base, int exp) const;
00297 };
00298
00299 #endif
```

7.28 FOORT/src/Metric.cpp File Reference

```
#include "Metric.h"
#include "InputOutput.h"
#include "Integrators.h"
#include <cmath>
#include <algorithm>
#include <iomanip>
#include <stdexcept>
#include "Spline.h"
#include <sstream>
```

7.29 FOORT/src/Metric.h File Reference

Declarations of abstract base Metric class and all its descendants.

```
#include "Geometry.h"
#include "Spline.h"
#include <string>
#include <vector>
#include <memory>
```

Classes

- class Metric

  The abstract base class for all Metrics.
- class SphericalHorizonMetric

  Abstract base class for a metric with a spherical horizon (i.e. horizon at constant radius r)
- class KerrMetric

  The Kerr metric.
- class FlatSpaceMetric

  Flat space metric in 4D.
- class RasheedLarsenMetric

  Rasheed-Larsen black hole.
- class JohannsenMetric

  Johannsen black hole metric.
- class MankoNovikovMetric

  Mano-Novikov metric (with angular momentum and M3 parameter turned on)
- class KerrSchildMetric

  Kerr metric in Kerr-Schild coordinates.
- class SingularityMetric

  Abstract base class for a metric with an arbitrary number of singularities (of arbitrary codimension)
- class ST3CrMetric

  Ring fuzzball metric.
- class BosonStarMetric

  Boson star metric with solitonic potential.

7.29.1 Detailed Description

Declarations of abstract base Metric class and all its descendants.

Author

Daniel R. Mayerson

Version

0.1

Date

2025-01-14

Copyright

Copyright (c) 2025

7.30 Metric.h

Go to the documentation of this file.

```
00001 #ifndef _FOORT_METRIC_H
00002 #define _FOORT_METRIC_H
00003
00004 #include "Geometry.h" // Needed for basic tensor objects etc.
00005
00006 #include "Spline.h"       // needed for spline interpolation, for the Boson star metric
00007 #include <string>         // for strings
00008 #include <vector>         // needed for the (non-fixed size) vector of symmetries in the metric
00009 #include <memory>         // for std::unique_ptr
00010
00019
00024 class Metric
00025 {
00026 public:
00027     // Virtual destructor to ensure correct destruction of descendants
00028     virtual ~Metric() = default;
00029
00030     Metric(bool rlogscale = false);
00031
00032     // Basic functions that return the metric with indices down or up:
00033     // pure virtual as they must be defined in the descendant classes.
00034     //
00035     // Get the metric at Point p, indices down
00036     virtual TwoIndex getMetric_dd(const Point &p) const = 0;
00037     // Get the metric at Point p, indices up
00038     virtual TwoIndex getMetric_uu(const Point &p) const = 0;
00039
00040     // The following functions return the Christoffel and other derivative quantities of the metric.
00041     // They are implemented for this base class, BUT are left as virtual functions to allow for
00042     // other metrics to implement their own (more efficient)
00043     // way of calculating them, if so desired.
00044     //
00045     // Get the Christoffel symbol, indices up-down-down
00046     virtual ThreeIndex getChristoffel_udd(const Point &p) const;
00047     // Get the Riemann tensor, indices up-down-down-down (NOT IMPLEMENTED YET: throws)
00048     virtual FourIndex getRiemann_uddd(const Point &p) const;
00049     // Get the Kretschmann scalar (NOT IMPLEMENTED YET: throws)
00050     virtual real getKretschmann(const Point &p) const;
00051
00052     // Function to get the description of the metric
00053     // (used for outputting to the screen while running and possibly to the output files)
00054     // There is a base class implementation of this function returning an undescriptive string
00055     virtual std::string getFullDescriptionStr() const;
00056
00057     bool getrLogScale() const;
00058
00059 protected:
00061     std::vector<int> m_Symmetries{};
00063     const bool m_rLogScale;
00064 };
00065
00069 class SphericalHorizonMetric : public Metric
00070 {
00071 public:
00072     // No default construction allowed, must specify horizon radius
00073     SphericalHorizonMetric() = delete;
00074     // Constructor that initializes horizon radius
00075     SphericalHorizonMetric(real HorizonRadius, bool rLogScale);
00076
00077     // Getter functions for the two member variables
00078     real getHorizonRadius() const;
00079
00080 protected:
00082     const real m_HorizonRadius;
00083 };
00084
00088 class KerrMetric final : public SphericalHorizonMetric
00089 {
00090 private:
00092     const real m_aParam;
00093
00095     const real m_mParam;
00096
00097 public:
00098     // No default constructor allowed, must specify a
00099     KerrMetric() = delete;
00100
00101     // Constructor setting parameter a
00102     KerrMetric(real aParam, bool rLogScale = false, real mParam = 1.);
00103
00104     // The override of the basic metric getter functions
00105     TwoIndex getMetric_dd(const Point &p) const final;
```

```
00106     TwoIndex getMetric_uu(const Point &p) const final;
00107
00108     // The override of the description string getter
00109     std::string getFullDescriptionStr() const final;
00110 };
00111
00115 class FlatSpaceMetric final : public Metric
00116 {
00117 public:
00118     // Simple (default) constructor is all that is needed
00119     FlatSpaceMetric(bool rlogscale = false);
00120
00121     // The override of the basic metric getter functions
00122     TwoIndex getMetric_dd(const Point &p) const final;
00123     TwoIndex getMetric_uu(const Point &p) const final;
00124
00125     // The override of the description string getter
00126     std::string getFullDescriptionStr() const final;
00127 };
00128
00132 class RasheedLarsenMetric final : public SphericalHorizonMetric
00133 {
00134 private:
00136     const real m_aParam;
00138     const real m_mParam;
00140     const real m_pParam;
00142     const real m_qParam;
00143
00144 public:
00145     // No default constructor allowed, must specify parameters
00146     RasheedLarsenMetric() = delete;
00147
00148     // Constructor setting parameter a
00149     RasheedLarsenMetric(real mParam, real aParam, real pParam, real qParam, bool rLogScale = false);
00150
00151     // The override of the basic metric getter functions
00152     TwoIndex getMetric_dd(const Point &p) const final;
00153     TwoIndex getMetric_uu(const Point &p) const final;
00154
00155     // The override of the description string getter
00156     std::string getFullDescriptionStr() const final;
00157 };
00158
00163 class JohannsenMetric final : public SphericalHorizonMetric
00164 {
00165 private:
00166     // Johannsen up to first order in deviation function is specified by five parameters (if M=1)
00168     const real m_aParam;
00170     const real m_alpha13Param;
00172     const real m_alpha22Param;
00174     const real m_alpha52Param;
00176     const real m_eps3Param;
00177
00178 public:
00179     // No default constructor allowed, must specify parameters
00180     JohannsenMetric() = delete;
00181
00182     // Constructor setting parameter a
00183     JohannsenMetric(real aParam, real alpha13Param, real alpha22Param, real alpha52Param, real
      eps3Param, bool rLogScale = false);
00184
00185     // The override of the basic metric getter functions
00186     TwoIndex getMetric_dd(const Point &p) const final;
00187     TwoIndex getMetric_uu(const Point &p) const final;
00188
00189     // The override of the description string getter
00190     std::string getFullDescriptionStr() const final;
00191 };
00192
00197 class MankoNovikovMetric final : public SphericalHorizonMetric
00198 {
00199 private:
00200     // Manko-Novikov metric with only alpha3 as symmetry breaking parameter
00202     const real m_aParam;
00204     const real m_alpha3Param;
00205
00206     // These are convenient derived quantities from a
00208     const real m_alphaParam;
00210     const real m_kParam;
00211
00212 public:
00213     // No default constructor allowed, must specify parameters
00214     MankoNovikovMetric() = delete;
00215
00216     // Constructor setting parameter a and alpha3
00217     MankoNovikovMetric(real aParam, real alpha3Param, bool rLogScale = false);
00218
```

```
00219     // The override of the basic metric getter functions
00220     TwoIndex getMetric_dd(const Point &p) const final;
00221     TwoIndex getMetric_uu(const Point &p) const final;
00222
00223     // The override of the description string getter
00224     std::string getFullDescriptionStr() const final;
00225 };
00226
00231 class KerrSchildMetric final : public SphericalHorizonMetric
00232 {
00233 private:
00235     const real m_aParam;
00236
00237 public:
00238     // No default constructor allowed, must specify a
00239     KerrSchildMetric() = delete;
00240
00241     // Constructor setting parameter a
00242     KerrSchildMetric(real aParam, bool rLogScale = false);
00243
00244     // The override of the basic metric getter functions
00245     TwoIndex getMetric_dd(const Point &p) const final;
00246     TwoIndex getMetric_uu(const Point &p) const final;
00247
00248     // The override of the description string getter
00249     std::string getFullDescriptionStr() const final;
00250 };
00251
00255 class SingularityMetric : public Metric
00256 {
00257 public:
00258     // Constructor that initializes singularities
00259     SingularityMetric(std::vector<Singularity> thesings, bool rLogScale);
00260
00261     // Getter functions for the two member variables
00262     std::vector<Singularity> getSingularities() const;
00263
00264 protected:
00266     const std::vector<Singularity> m_AllSingularities;
00267 };
00268
00273 class ST3CrMetric final : public SingularityMetric
00274 {
00275 public:
00276     // Constructor which will be called to initialize all parameters of the metric
00277     ST3CrMetric(real P, real q0, real lambda, bool rlogscale = false);
00278
00279     // The basic getter functions
00280     TwoIndex getMetric_dd(const Point &p) const final;
00281     TwoIndex getMetric_uu(const Point &p) const final;
00282
00283     // The description string getter
00284     std::string getFullDescriptionStr() const final;
00285
00286 private:
00287     const real m_P;
00288     const real m_q0;
00289     const real m_lambda;
00290
00291     real get_omega(real r, real theta, real l) const;
00292     real f_phi(real phi, real r, real theta, real l, real R) const;
00293     real f_om_phi(real phi, real r, real theta, real l, real R) const;
00294 };
00295
00301 class BosonStarMetric final : public Metric
00302 {
00303 public:
00304     // Simple (default) constructor is all that is needed
00305     BosonStarMetric(double Phi_infinity, int num_lines, bool rLogScale = false,
00306                     std::string Phi_filename = "Phi.dat", std::string m_filename = "m.dat");
00307     // The override of the basic metric getter functions
00308     TwoIndex getMetric_dd(const Point &p) const final;
00309     TwoIndex getMetric_uu(const Point &p) const final;
00310     // The override of the description string getter
00311     std::string getFullDescriptionStr() const final;
00312
00313 protected:
00315     const double m_Phi_infinity;
00318     const int m_num_lines;
00319
00321     std::string m_Phi_filename;
00323     std::string m_m_filename;
00324
00326     tk::spline m_PhiSpline;
00328     tk::spline m_mSpline;
00329
00331     void read_data();
```

```
00332 };
00333
00335 // Declare your new Metric class here, publically inheriting from the base class Metric
00336 // (or SphericalHorizonMetric if your Metric has a horizon, or SingularityMetric if your Metric has
      other, arbitrary singularities)
00337 // Give definitions (implementation) of these functions in Metric.cpp (or other source code file)
00338 // Don't forget to set m_Symmetries appropriately (in the constructor),
00339 // if your metric has any symmetry (e.g. stationarity, axisymmetry)!
00340 // Sample code:
00341 /*
00342 class MyMetric final : public Metric // good practice to make the class final unless descendant
      classes are possible
00343 {
00344 public:
00345     // Constructor which will be called to initialize all parameters of the metric
00346     MyMetric(args...);
00347
00348     // The basic getter functions
00349     // These MUST be implemented
00350     TwoIndex getMetric_dd(const Point& p) const final;
00351     TwoIndex getMetric_uu(const Point& p) const final;
00352
00353     // The description string getter
00354     // This is optional (but recommended) to implement; if not implemented,
00355     // the base class Metric::getFullDescriptionStr() will be called instead
00356     std::string getFullDescriptionStr() const final;
00357
00358 private:
00359     // good practice to have all const params (initialized in the constructor)
00360     // since the metric cannot change after initialization
00361     // const params...;
00362
00363 };
00364 */
00366
00367 #endif
```

7.31 FOORT/src/Spline.cpp File Reference

Simple cubic spline interpolation library without external dependencies.

```
#include "Spline.h"
#include <cstdio>
#include <cassert>
#include <cmath>
#include <vector>
#include <algorithm>
```

7.31.1 Detailed Description

Simple cubic spline interpolation library without external dependencies.

This library is not made by the authors of FOORT, but implemented as found in the following link: https://kluge.in-chemnitz.de/opensource/spline/. The main body has been separated into Spline.cpp, however.

Author

Tino Kluge

Date

2021

Copyright

GNU General Public License

7.32 FOORT/src/Spline.h File Reference

Simple cubic spline interpolation library without external dependencies.

```
#include <cstdio>
#include <cassert>
#include <cmath>
#include <vector>
#include <algorithm>
```

Classes

- class tk::spline
- class tk::internal::band_matrix

Namespaces

- namespace tk
- namespace tk::internal

7.32.1 Detailed Description

Simple cubic spline interpolation library without external dependencies.

This library is not made by the authors of FOORT, but implemented as found in the following link: https://kluge.in-chemnitz.de/opensource/spline/. The main body has been separated into Spline.cpp, however.

Author

Tino Kluge

Date

2021

Copyright

GNU General Public License

7.33 Spline.h

Go to the documentation of this file.

```
00001 /*
00002  * spline.h
00003  *
00004  * simple cubic spline interpolation library without external
00005  * dependencies
00006  *
00007  * ---------------------------------------------------------------------
00008  * Copyright (C) 2011, 2014, 2016, 2021 Tino Kluge (ttk448 at gmail.com)
00009  *
00010  *  This program is free software; you can redistribute it and/or
00011  *  modify it under the terms of the GNU General Public License
00012  *  as published by the Free Software Foundation; either version 2
00013  *  of the License, or (at your option) any later version.
00014  *
00015  *  This program is distributed in the hope that it will be useful,
00016  *  but WITHOUT ANY WARRANTY; without even the implied warranty of
00017  *  MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.  See the
00018  *  GNU General Public License for more details.
00019  *
00020  *  You should have received a copy of the GNU General Public License
00021  *  along with this program.  If not, see <http://www.gnu.org/licenses/>.
00022  * ---------------------------------------------------------------------
00023  *
00024  */
00025
00035
00036 #ifndef TK_SPLINE_H
00037 #define TK_SPLINE_H
00038
00039 #include <cstdio>
00040 #include <cassert>
00041 #include <cmath>
00042 #include <vector>
00043 #include <algorithm>
00044 #ifdef HAVE_SSTREAM
00045 #include <sstream>
00046 #include <string>
00047 #endif // HAVE_SSTREAM
00048
00049 // not ideal but disable unused-function warnings
00050 // (we get them because we have implementations in the header file,
00051 // and this is because we want to be able to quickly separate them
00052 // into a cpp file if necessary)
00053 #pragma GCC diagnostic push
00054 #pragma GCC diagnostic ignored "-Wunused-function"
00055 namespace tk
00056 {
00057     // spline interpolation
00058     class spline
00059     {
00060     public:
00061         // spline types
00062         enum spline_type
00063         {
00064             linear = 10,         // linear interpolation
00065             cspline = 30,        // cubic splines (classical C^2)
00066             cspline_hermite = 31 // cubic hermite splines (local, only C^1)
00067         };
00068
00069         // boundary condition type for the spline end-points
00070         enum bd_type
00071         {
00072             first_deriv = 1,
00073             second_deriv = 2
00074         };
00075
00076     protected:
00077         std::vector<double> m_x, m_y; // x,y coordinates of points
00078         // interpolation parameters
00079         // f(x) = a_i + b_i*(x-x_i) + c_i*(x-x_i)^2 + d_i*(x-x_i)^3
00080         // where a_i = y_i, or else it won't go through grid points
00081         std::vector<double> m_b, m_c, m_d; // spline coefficients
00082         double m_c0;                       // for left extrapolation
00083         spline_type m_type;
00084         bd_type m_left, m_right;
00085         double m_left_value, m_right_value;
00086         bool m_made_monotonic;
00087         void set_coeffs_from_b();            // calculate c_i, d_i from b_i
00088         size_t find_closest(double x) const; // closest idx so that m_x[idx]<=x
00089
00090     public:
00091         // default constructor: set boundary condition to be zero curvature
```

```
00092         // at both ends, i.e. natural splines
00093         spline();
00094
00095         spline(const std::vector<double> &X, const std::vector<double> &Y,
00096                spline_type type = cspline,
00097                bool make_monotonic = false,
00098                bd_type left = second_deriv, double left_value = 0.0,
00099                bd_type right = second_deriv, double right_value = 0.0);
00100
00101         // modify boundary conditions: if called it must be before set_points()
00102         void set_boundary(bd_type left, double left_value,
00103                           bd_type right, double right_value);
00104
00105         // set all data points (cubic_spline=false means linear interpolation)
00106         void set_points(const std::vector<double> &x,
00107                         const std::vector<double> &y,
00108                         spline_type type = cspline);
00109
00110         // adjust coefficients so that the spline becomes piecewise monotonic
00111         // where possible
00112         //   this is done by adjusting slopes at grid points by a non-negative
00113         //   factor and this will break C^2
00114         //   this can also break boundary conditions if adjustments need to
00115         //   be made at the boundary points
00116         // returns false if no adjustments have been made, true otherwise
00117         bool make_monotonic();
00118
00119         // evaluates the spline at point x
00120         double operator()(double x) const;
00121         double deriv(int order, double x) const;
00122
00123         // returns the input data points
00124         std::vector<double> get_x() const;
00125         std::vector<double> get_y() const;
00126         double get_x_min() const;
00127         double get_x_max() const;
00128
00129 #ifdef HAVE_SSTREAM
00130         // spline info string, i.e. spline type, boundary conditions etc.
00131         std::string info() const;
00132 #endif // HAVE_SSTREAM
00133     };
00134
00135     namespace internal
00136     {
00137
00138         // band matrix solver
00139         class band_matrix
00140         {
00141         private:
00142             std::vector<std::vector<double> m_upper; // upper band
00143             std::vector<std::vector<double> m_lower; // lower band
00144         public:
00145             band_matrix() {};                          // constructor
00146             band_matrix(int dim, int n_u, int n_l); // constructor
00147             ~band_matrix() {};                         // destructor
00148             void resize(int dim, int n_u, int n_l); // init with dim,n_u,n_l
00149             int dim() const;                           // matrix dimension
00150             int num_upper() const;
00151             int num_lower() const;
00152             // access operator
00153             double &operator()(int i, int j);      // write
00154             double operator()(int i, int j) const; // read
00155             // we can store an additional diagonal (in m_lower)
00156             double &saved_diag(int i);
00157             double saved_diag(int i) const;
00158             void lu_decompose();
00159             std::vector<double> r_solve(const std::vector<double> &b) const;
00160             std::vector<double> l_solve(const std::vector<double> &b) const;
00161             std::vector<double> lu_solve(const std::vector<double> &b,
00162                                          bool is_lu_decomposed = false);
00163         };
00164
00165     } // namespace internal
00166 } // namespace tk
00167 #pragma GCC diagnostic pop
00168
00169 #endif /* TK_SPLINE_H */
```

7.34 FOORT/src/Terminations.cpp File Reference

```
#include "Terminations.h"
#include "Geodesic.h"
#include "InputOutput.h"
#include <cmath>
```

Functions

- TerminationUniqueVector CreateTerminationVector (TermBitflag termflags, Geodesic *const theGeodesic)
  Create a Termination Vector object.

7.34.1 Detailed Description

Author

Daniel R. Mayerson

Version

0.1

Date

2025-01-14

Copyright

Copyright (c) 2025

7.34.2 Function Documentation

7.34.2.1 CreateTerminationVector()

```
TerminationUniqueVector CreateTerminationVector (
            TermBitflag termflags,
            Geodesic *const theGeodesic)
```

Create a Termination Vector object.

Parameters

termflags	bitflags for the terminations
theGeodesic	the geodesic

Returns

TerminationUniqueVector

7.35 FOORT/src/Terminations.h File Reference

Declarations of abstract base Termination class and all its descendants.

```
#include "Geometry.h"
#include <cstdint>
#include <memory>
#include <vector>
#include <utility>
```

Classes

- class Termination

  Abstract base class for all Terminations.
- class HorizonTermination

  HorizonTermination: Terminate geodesics if they get too close to the horizon.
- class BoundarySphereTermination

  BoundarySphereTermination: Terminate geodesics if they reach outside of a boundary sphere.
- class TimeOutTermination

  TimeOutTermination: Terminate geodesics if they take too many steps.
- class ThetaSingularityTermination

  ThetaSingularityTermination: Terminate geodesics if they get too close to a polar coordinate singularity.
- class NaNTermination

  NaNTermination: Terminate geodesics if they contain a NaN in position or velocity.
- class GeneralSingularityTermination

  GeneralSingularityTermination: Terminate geodesics if they get too close to one of a number of singularities (of arbitrary codimension)
- struct TerminationOptions

  Base class for all TerminationOptions structs. Other TerminationOptions can inherit from here if they require more options.
- struct HorizonTermOptions

  Options for HorizonTermination.
- struct BoundarySphereTermOptions

  Options for BoundarySphereTermination.
- struct TimeOutTermOptions

  Options for TimeOutTermination.
- struct ThetaSingularityTermOptions

  Options for ThetaSingularityTermination.
- struct NaNTermOptions

  Options for NaNTermination.
- struct GeneralSingularityTermOptions

  Options for GeneralSingularityTermination.

Typedefs

- using TermBitflag = std::uint16_t

  Used for constructing vector of Terminations. Note that this means every Termination is either "on" or "off"; it is not possible to have a Termination "on" more than once.
- using TerminationUniqueVector = std::vector<std::unique_ptr<Termination>>

  The owner vector of derived Termination classes.

Enumerations

- enum class Term {
  Uninitialized = -1 , Continue = 0 , Horizon , BoundarySphere ,
  TimeOut , ThetaSingularity , NaN , GeneralSingularity ,
  Maxterms }

  Possible termination conditions that can be set by Terminations.

Functions

- TerminationUniqueVector CreateTerminationVector (TermBitflag termflags, Geodesic *const theGeodesic)

  Create a Termination Vector object.

Variables

- constexpr TermBitflag Term_None {0b0000'0000'0000'0000}

  No terminations bitflag.
- constexpr TermBitflag Term_BoundarySphere {0b0000'0000'0000'0001}

  Boundary Sphere termination bitflag.
- constexpr TermBitflag Term_TimeOut {0b0000'0000'0000'0010}

  Time Out termination bitflag.
- constexpr TermBitflag Term_Horizon {0b0000'0000'0000'0100}

  Horizon termination bitflag.
- constexpr TermBitflag Term_ThetaSingularity {0b0000'0000'0000'1000}

  Theta Singularity termination bitflag.
- constexpr TermBitflag Term_NaN {0b0000'0000'0001'0000}

  NaN termination bitflag.
- constexpr TermBitflag Term_GeneralSingularity {0b0000'0000'0010'0000}

  General Singularity termination bitflag.

7.35.1 Detailed Description

Declarations of abstract base Termination class and all its descendants.

Author

Daniel R. Mayerson

Version

0.1

Date

2025-01-14

Copyright

Copyright (c) 2025

7.35.2 Typedef Documentation

7.35.2.1 TermBitflag

```
using TermBitflag = std::uint16_t
```

Used for constructing vector of Terminations. Note that this means every Termination is either "on" or "off"; it is not possible to have a Termination "on" more than once.

7.35.2.2 TerminationUniqueVector

```
using TerminationUniqueVector = std::vector<std::unique_ptr<Termination>>
```

The owner vector of derived Termination classes.

7.35.3 Enumeration Type Documentation

7.35.3.1 Term

```
enum class Term  [strong]
```

Possible termination conditions that can be set by Terminations.

Enumerator

Uninitialized	Geoedesic has not been properly initialized yet with initial position/velocity.
Continue	All is right, continue integrating geodesic.
Horizon	STOP, encountered horizon (set by HorizonTermination)
BoundarySphere	STOP, encountered boundary sphere (set by BoundarySphereTermination)
TimeOut	STOP, taken too many steps (set by TimeOutTermination)
ThetaSingularity	STOP, too close to polar coordinate singularity (theta = 0 or theta = pi/2) (set by ThetaSingularityTermination)
NaN	STOP, NaN encountered in geodesic position or velocity (set by NaNTermination)
GeneralSingularity	STOP, singularity encountered (of any codimension) (set by GeneralSingularityTermination)
Maxterms	

7.35.4 Function Documentation

7.35.4.1 CreateTerminationVector()

```
TerminationUniqueVector CreateTerminationVector (
            TermBitflag termflags,
            Geodesic *const theGeodesic)
```

Create a Termination Vector object.

Parameters

termflags	bitflags for the terminations
theGeodesic	the geodesic

Returns

TerminationUniqueVector

7.35.5 Variable Documentation

7.35.5.1 Term_BoundarySphere

```
TermBitflag Term_BoundarySphere {0b0000'0000'0000'0001}  [constexpr]
```

Boundary Sphere termination bitflag.

7.35.5.2 Term_GeneralSingularity

```
TermBitflag Term_GeneralSingularity {0b0000'0000'0010'0000}  [constexpr]
```

General Singularity termination bitflag.

7.35.5.3 Term_Horizon

```
TermBitflag Term_Horizon {0b0000'0000'0000'0100}  [constexpr]
```

Horizon termination bitflag.

7.35.5.4 Term_NaN

```
TermBitflag Term_NaN {0b0000'0000'0001'0000}  [constexpr]
```

NaN termination bitflag.

7.35.5.5 Term_None

```
TermBitflag Term_None {0b0000'0000'0000'0000}  [constexpr]
```

No terminations bitflag.

7.35.5.6 Term_ThetaSingularity

```
TermBitflag Term_ThetaSingularity {0b0000'0000'0000'1000}  [constexpr]
```

Theta Singularity termination bitflag.

7.35.5.7 Term_TimeOut

```
TermBitflag Term_TimeOut {0b0000'0000'0000'0010}  [constexpr]
```

Time Out termination bitflag.

7.36 Terminations.h

Go to the documentation of this file.

```
00001 #ifndef _FOORT_TERMINATIONS_H
00002 #define _FOORT_TERMINATIONS_H
00003
00012
00013 #include "Geometry.h" // for basic tensor objects
00014
00015 #include <cstdint> // for std::uint16_t
00016 #include <memory>  // for std::unique_ptr
00017 #include <vector>  // for std::vector
00018 #include <utility> // for std::pair
00019
00020 // Forward declaration of Geodesic class needed here, since Diagnostics are passed a pointer to their
      owner Geodesic
00021 // (note "Geodesic.h" is NOT included to avoid header loop, and we do not need Geodesic member
      functions here!)
00022 class Geodesic;
00023
00024 // TERMINATION BITFLAGS
00026 using TermBitflag = std::uint16_t;
00027
00028 // Define a bitflag per existing Termination
00030 constexpr TermBitflag Term_None{0b0000'0000'0000'0000};
00032 constexpr TermBitflag Term_BoundarySphere{0b0000'0000'0000'0001};
00034 constexpr TermBitflag Term_TimeOut{0b0000'0000'0000'0010};
00036 constexpr TermBitflag Term_Horizon{0b0000'0000'0000'0100};
00038 constexpr TermBitflag Term_ThetaSingularity{0b0000'0000'0000'1000};
00040 constexpr TermBitflag Term_NaN{0b0000'0000'0001'0000};
00042 constexpr TermBitflag Term_GeneralSingularity{0b0000'0000'0010'0000};
00043
00045 // Add a TermBitflag for your new Termination. Make sure you use a bitflag that has not been used
      before!
00046 // Sample code:
00047 /*
00048 constexpr TermBitflag Term_MyTerm               { 0b0000'0000'0100'0000 };
00049 */
00051
00052 // TERMINATION CONDITIONS
00053
00057 enum class Term
00058 {
00060     Uninitialized = -1,
00062     Continue = 0,
00064     Horizon,
00066     BoundarySphere,
00068     TimeOut,
00070     ThetaSingularity,
00072     NaN,
00074     GeneralSingularity,
00075
00077     // Add a new Termination condition that your new Termination can set
00078     // Sample code:
00079     /*
00080     MyTermCond,         // STOP, encountered (...)
00081     */
00083
00084     Maxterms // Number of termination conditions that exist
00085 };
00086
00087 // GENERAL DECLARATIONS OF ABSTRACT BASE CLASS
00088
00092 class Termination
00093 {
00094 public:
00095     // Constructor must initialize the pointer to its owner Geodesic
00096     Termination() = delete;
00097     Termination(Geodesic *const theGeodesic) : m_OwnerGeodesic{theGeodesic}
00098     {
00099     }
00100
```

```
00101     // Resets Termination object. This is called when the owner Geodesic is reset in order to start
      integrating
00102     // a new geodesic.
00103     // The base class implementation only resets m_StepsSinceUpdated
00104     // Descendants can override this if they need to reset additional internal variables
00105     virtual void Reset();
00106 
00107     // virtual destructor to ensure correct destruction of descendants
00108     virtual ~Termination() = default;
00109 
00110     // Function that is called to determine whether Termination wants to
00111     // terminate the Geodesic. Returns Term::Continue if no termination wanted,
00112     // otherwise it returns the appropriate Term condition
00113     virtual Term CheckTermination() = 0;
00114 
00115     // This returns the full description of the Termination
00116     virtual std::string getFullDescriptionStr() const = 0;
00117 
00118 protected:
00120     Geodesic *const m_OwnerGeodesic;
00121 
00122     // Helper function to decide if the Termination should indeed update its status, based on
00123     // UpdateNSteps (which is set to 0 if we always update)
00124     bool DecideUpdate(largecounter UpdateNSteps);
00125 
00127     largecounter m_StepsSinceUpdated{};
00128 };
00129 
00131 using TerminationUniqueVector = std::vector<std::unique_ptr<Termination>>;
00132 
00133 // Helper to create a new vector of Termination options, based on the bitflag
00134 TerminationUniqueVector CreateTerminationVector(TermBitflag termflags, Geodesic *const theGeodesic);
00135 
00136 // DECLARATIONS FOR DERIVED TERMINATION CLASSES (DESCENDANTS)
00137 
00138 // Forward declaration needed before Termination
00139 struct HorizonTermOptions;
00140 
00144 class HorizonTermination final : public Termination
00145 {
00146 public:
00147     // Basic constructor only passes on Geodesic pointer to base class constructor
00148     HorizonTermination(Geodesic *const theGeodesic) : Termination(theGeodesic) {}
00149 
00150     // Check if we are too close to the horizon
00151     Term CheckTermination() final;
00152 
00153     // Description string
00154     std::string getFullDescriptionStr() const final;
00155 
00157     static std::unique_ptr<HorizonTermOptions> TermOptions;
00158 };
00159 
00160 // Forward declaration needed before Termination
00161 struct BoundarySphereTermOptions;
00162 
00166 class BoundarySphereTermination final : public Termination
00167 {
00168 public:
00169     // Basic constructor only passes on Geodesic pointer to base class constructor
00170     BoundarySphereTermination(Geodesic *const theGeodesic) : Termination(theGeodesic) {}
00171 
00172     // Check if we have passed the boundary sphere
00173     Term CheckTermination() final;
00174 
00175     // Description string
00176     std::string getFullDescriptionStr() const final;
00177 
00179     static std::unique_ptr<BoundarySphereTermOptions> TermOptions;
00180 };
00181 
00182 // Forward declaration needed before Termination
00183 struct TimeOutTermOptions;
00184 
00188 class TimeOutTermination final : public Termination
00189 {
00190 public:
00191     // Basic constructor only passes on Geodesic pointer to base class constructor
00192     TimeOutTermination(Geodesic *const theGeodesic) : Termination(theGeodesic) {}
00193 
00194     // This descendant needs to override Reset in order to also reset m_CurNrSteps
00195     void Reset() final;
00196 
00197     // Check if we have already taken too many steps
00198     Term CheckTermination() final;
00199 
00200     // Description string
```

```
00201     std::string getFullDescriptionStr() const final;
00202
00204     static std::unique_ptr<TimeOutTermOptions> TermOptions;
00205
00206 private:
00208     largecounter m_CurNrSteps{0};
00209 };
00210
00211 // Forward declaration needed before Termination
00212 struct ThetaSingularityTermOptions;
00213
00217 class ThetaSingularityTermination final : public Termination
00218 {
00219 public:
00220     ThetaSingularityTermination(Geodesic *const theGeodesic) : Termination(theGeodesic) {}
00221
00222     // No override of Reset() necessary
00223
00224     // Check the specific termination condition
00225     Term CheckTermination() final;
00226
00227     // Description string
00228     std::string getFullDescriptionStr() const final;
00229
00231     static std::unique_ptr<ThetaSingularityTermOptions> TermOptions;
00232 };
00233
00234 // Forward declaration needed before Termination
00235 struct NaNTermOptions;
00236
00240 class NaNTermination final : public Termination
00241 {
00242 public:
00243     // Basic constructor only passes on Geodesic pointer to base class constructor
00244     NaNTermination(Geodesic *const theGeodesic) : Termination(theGeodesic) {}
00245
00246     // Check if we are too close to the horizon
00247     Term CheckTermination() final;
00248
00249     // Description string
00250     std::string getFullDescriptionStr() const final;
00251
00253     static std::unique_ptr<NaNTermOptions> TermOptions;
00254 };
00255
00256 // Forward declaration needed before Termination
00257 struct GeneralSingularityTermOptions;
00258
00262 class GeneralSingularityTermination final : public Termination
00263 {
00264 public:
00265     // Basic constructor only passes on Geodesic pointer to base class constructor
00266     GeneralSingularityTermination(Geodesic *const theGeodesic) : Termination(theGeodesic) {}
00267
00268     // Check if we are too close to the horizon
00269     Term CheckTermination() final;
00270
00271     // Description string
00272     std::string getFullDescriptionStr() const final;
00273
00275     static std::unique_ptr<GeneralSingularityTermOptions> TermOptions;
00276
00277 private:
00278     std::string SingularityToString(int singnr) const;
00279 };
00280
00282 // Declare your Termination class here, inheriting from Termination.
00283 // Sample code:
00284 /*
00285 // Forward declaration needed before Termination
00286 struct TerminationOptions; // possibly will instead need to declare descendant options struct
00287 class MyTermination final : public Termination // good practice to make the class final unless
      descendant classes are possible
00288 {
00289 public:
00290     // Constructor must at least pass on Geodesic pointer to base class constructor
00291     MyTermination(Geodesic* const theGeodesic) : Termination(theGeodesic) {}
00292
00293     // Do you need to reset any internal variables specific to MyTermination? If so, override Reset()
      (This is not mandatory)
00294     // Note: make sure to call the base class implementation Termination::Reset()
00295     // from within your implementation of MyTermination::Reset(), so that the base class internal
      variable is also reset!
00296     void Reset() final;
00297
00298     // Check the specific termination condition
00299     Term CheckTermination() final;
```

```
00300
00301     // Description string
00302     std::string getFullDescriptionStr() const final;
00303
00304     // The options that the Termination keeps (will probably be a descendant struct instead, which
      specifies
00305     // any additional options the Termination needs)
00306     static std::unique_ptr<TerminationOptions> TermOptions;
00307
00308 private:
00309     // any private member variables that are needed to keep track of things
00310 };
00311 */
00313
00314 // ALL TERMINATIONOPTIONS STRUCTS
00315
00319 struct TerminationOptions
00320 {
00321 public:
00322     // Basic constructor only sets the number of steps between updates
00323     TerminationOptions(largecounter Nsteps) : UpdateEveryNSteps{Nsteps}
00324     {
00325     }
00326
00327     // virtual destructor to ensure correct destruction of descendants
00328     virtual ~TerminationOptions() = default;
00329
00331     const largecounter UpdateEveryNSteps;
00332 };
00333
00338 struct HorizonTermOptions : public TerminationOptions
00339 {
00340 public:
00341     HorizonTermOptions(real theHorizonRadius, bool therLogScale, real theAtHorizonEps, largecounter
      Nsteps) : TerminationOptions(Nsteps), HorizonRadius{theHorizonRadius}, AtHorizonEps{theAtHorizonEps},
      rLogScale{therLogScale}
00342     {
00343     }
00344
00346     const real HorizonRadius;
00348     const real AtHorizonEps;
00350     const bool rLogScale;
00351 };
00352
00357 struct BoundarySphereTermOptions : public TerminationOptions
00358 {
00359 public:
00360     BoundarySphereTermOptions(real theRadius, bool therLogScale, largecounter Nsteps) :
      TerminationOptions(Nsteps), SphereRadius{theRadius}, rLogScale{therLogScale}
00361     {
00362     }
00363
00365     const real SphereRadius;
00367     const bool rLogScale;
00368 };
00369
00374 struct TimeOutTermOptions : public TerminationOptions
00375 {
00376 public:
00377     TimeOutTermOptions(largecounter MaxStepsAllowed, largecounter Nsteps) :
      TerminationOptions(Nsteps), MaxSteps{MaxStepsAllowed}
00378     {
00379     }
00380
00382     const largecounter MaxSteps;
00383 };
00384
00385 // Options class for ThetaSingularityTermination
00390 struct ThetaSingularityTermOptions : public TerminationOptions
00391 {
00392 public:
00393     ThetaSingularityTermOptions(real epsilon, largecounter Nsteps) : TerminationOptions(Nsteps),
      ThetaSingEpsilon{epsilon}
00394     {
00395     }
00396
00398     const real ThetaSingEpsilon;
00399 };
00400
00404 struct NaNTermOptions : public TerminationOptions
00405 {
00406 public:
00407     NaNTermOptions(bool consoleoutputon, largecounter Nsteps) : TerminationOptions(Nsteps),
      OutputToConsole{consoleoutputon}
00408     {
00409     }
00410
```

```
00412     const bool OutputToConsole;
00413 };
00414
00419 struct GeneralSingularityTermOptions : public TerminationOptions
00420 {
00421 public:
00422     GeneralSingularityTermOptions(std::vector<Singularity> sings,
00423                                   real eps, bool consoleoutputon, bool therlogscale, largecounter
      Nsteps)
00424         : TerminationOptions(Nsteps), Singularities{std::move(sings)}, Epsilon{eps},
      OutputToConsole{consoleoutputon},
00425           rLogScale{therlogscale} {}
00426
00428     const std::vector<Singularity> Singularities;
00430     const real Epsilon;
00432     const bool OutputToConsole;
00434     const bool rLogScale;
00435 };
00436
00438 // Add your new TerminationOptions struct here, inheriting from TerminationOptions (if needed)
00439 // Sample code:
00440 /*
00441 struct MyTermOptions : public TerminationOptions
00442 {
00443 public:
00444     MyTermOptions(..., largecounter Nsteps) : TerminationOptions(Nsteps) //, other initialization
00445     {}
00446
00447     // member variables (const!) here
00448 };
00449 */
00451
00452 #endif
```

7.37 FOORT/src/Utilities.cpp File Reference

```
#include "Utilities.h"
#include <sstream>
#include <iomanip>
```

7.37.1 Detailed Description

Author

Daniel R. Mayerson

Version

0.1

Date

2025-01-14

Copyright

Copyright (c) 2025

7.38 FOORT/src/Utilities.h File Reference

Declarations of various utility functions, in a Utilities namespace.

```
#include "Metric.h"
#include "Diagnostics.h"
#include "Terminations.h"
#include "Geodesic.h"
#include "ViewScreen.h"
#include "Integrators.h"
#include <chrono>
#include <string>
#include <vector>
```

Classes

- class Utilities::Timer

  Timer class to keep track of elapsed time.

Namespaces

- namespace Utilities

  Namespace that contains our utility functions.

Functions

- std::string Utilities::GetTimeStampString ()

  Get a string of the current time (in a format that can be used to append to file names)
- std::vector< std::string > Utilities::GetDiagNameStrings (DiagBitflag alldiags, DiagBitflag valdiag)

  Helper function to get all Diagnostic Names (for outputting to files)
- std::string Utilities::GetFirstLineInfoString (const Metric *theMetric, const Source *theSource, DiagBitflag alldiags, DiagBitflag valdiag, TermBitflag allterms, const ViewScreen *theView)

  This returns the full string to be written to every output file as its first line.

7.38.1 Detailed Description

Declarations of various utility functions, in a Utilities namespace.

Author

Daniel R. Mayerson

Version

0.1

Date

2025-01-14

Copyright

Copyright (c) 2025

7.39 Utilities.h

Go to the documentation of this file.

```
00001 #ifndef _FOORT_UTILITIES_H
00002 #define _FOORT_UTILITIES_H
00003
00012
00013 // We use Metric, Diagnostic, Termination, Geodesic, ViewScreen, and Integrator declarations here
00014 #include "Metric.h"
00015 #include "Diagnostics.h"
00016 #include "Terminations.h"
00017 #include "Geodesic.h"
00018 #include "ViewScreen.h"
00019 #include "Integrators.h"
00020
00021 #include <chrono> // for timer functionality
00022 #include <string> // for strings
00023 #include <vector> // for std::vector
00024
00026 namespace Utilities
00027 {
00031     class Timer
00032     {
00033     private:
00035         using Clock = std::chrono::steady_clock;
00037         using Second = std::chrono::duration<double, std::ratio<1>>;
00038
00040         std::chrono::time_point<Clock> m_beg{Clock::now()};
00041
00042     public:
00043         // reset begin time
00044         void reset();
00045
00046         // returns time elapsed since begin time
00047         double elapsed() const;
00048     };
00049
00050     // Returns a string of the current time (in a format that can be used to append to file names)
00051     std::string GetTimeStampString();
00052
00053     // Helper function to get all Diagnostic Names (for outputting to files)
00054     std::vector<std::string> GetDiagNameStrings(DiagBitflag alldiags, DiagBitflag valdiag);
00055
00056     // This returns the full string to be written to every output file as its first line
00057     // It contains information about all the settings used to produce the output
00058     std::string GetFirstLineInfoString(const Metric *theMetric, const Source *theSource,
00059                                        DiagBitflag alldiags, DiagBitflag valdiag, TermBitflag
      allterms, const ViewScreen *theView);
00060 }
00061
00062 #endif
```

7.40 FOORT/src/ViewScreen.cpp File Reference

```
#include "ViewScreen.h"
#include <algorithm>
```

7.40.1 Detailed Description

Author

Daniel R. Mayerson

Version

0.1

Date

2025-01-14

Copyright

Copyright (c) 2025

7.41 FOORT/src/ViewScreen.h File Reference

Declarations of ViewScreen class.

```
#include "Geometry.h"
#include "Metric.h"
#include "Mesh.h"
#include <memory>
#include <utility>
#include <array>
#include <string>
```

Classes

- class ViewScreen

  This class is in charge of converting a pixel on the screen into physical initial conditions for a geodesic.

Enumerations

- enum class GeodesicType { Null = 0 , Timelike = -1 , Spacelike = 1 }

  Type of geodesic being integrated.

7.41.1 Detailed Description

Declarations of ViewScreen class.

Author

Daniel R. Mayerson

This class is in charge of converting a pixel on the screen (which the Mesh wants to integrate) into physical initial conditions for the position and velocity of a geodesic.

Version

0.1

Date

2025-01-14

Copyright

Copyright (c) 2025

7.41.2 Enumeration Type Documentation

7.41.2.1 GeodesicType

```
enum class GeodesicType  [strong]
```

Type of geodesic being integrated.

Null is the default, Timelike is -1, Spacelike is 1. Only Null is supported/implemented at the moment.

Enumerator

Null	
Timelike	
Spacelike	

7.42 ViewScreen.h

Go to the documentation of this file.

```
00001 #ifndef _FOORT_VIEWSCREEN_H
00002 #define _FOORT_VIEWSCREEN_H
00003
00013
00014 #include "Geometry.h" // For basic tensor objects
00015 #include "Metric.h"   // For the Metric object
00016 #include "Mesh.h"   // For the Mesh object
00017
00018 #include <memory>  // std::unique_ptr
00019 #include <utility> // std::move
00020 #include <array>   // std::array
00021 #include <string>  // strings
00022
00027 enum class GeodesicType
00028 {
00029     Null = 0,
00030     Timelike = -1,
00031     Spacelike = 1,
00032 };
00033
00039 class ViewScreen
00040 {
00041 public:
00042     // No default constructor possible
00043     ViewScreen() = delete;
00044     // constructor must pass following arguments along:
00045     // - physical position and looking direction;
00046     // - screen dimensions (in dimensions of length)
00047     // - the Mesh used (ViewScreen must become a owner of this object!)
00048     // - the Metric used (ViewScreen is NOT the owner of the Metric)
00049     // - the geodesic type to be integrated (null, timelike, spacelike)
00050     ViewScreen(Point pos, OneIndex dir, ScreenPoint screensize, ScreenPoint screencenter,
00051                std::unique_ptr<Mesh> theMesh, const Metric *const theMetric, GeodesicType thegeodtype
      = GeodesicType::Null)
00052         : m_Pos{pos}, m_Direction{dir}, m_ScreenSize{screensize}, m_ScreenCenter{screencenter},
00053           m_rLogScale{theMetric->getrLogScale()},
00054           m_theMetric{theMetric}, m_GeodType{thegeodtype},
00055           m_theMesh{std::move(theMesh)}
00056     {
00057         // At the moment, we don't even use the direction; we are always pointed towards the origin
00058         if (m_Direction != Point{0, -1, 0, 0})
00059         {
00060             ScreenOutput("ViewScreen is only supported pointing inwards at the moment; Direction = {0,
      -1, 0, 0} will be used",
00061                          OutputLevel::Level_0_WARNING);
00062         }
00063         // At the moment, we are only integrating null geodesics
00064         if (m_GeodType != GeodesicType::Null)
00065         {
00066             ScreenOutput("ViewScreen only supports null geodesics at the moment; geodesics integrated
      will be null.",
```

```
00067                           OutputLevel::Level_0_WARNING);
00068         }
00069
00070         ScreenOutput("ViewScreen initialized with position " + toString(m_Pos) + ", looking direction
      " + toString(m_Direction) +
00071                           ", screen size " + toString(m_ScreenSize) + ", screen center " +
      toString(m_ScreenCenter) +
00072                           ", geodesic type " + (m_GeodType == GeodesicType::Null ? "Null" : (m_GeodType
      == GeodesicType::Timelike ? "Timelike" : "Spacelike")) +
00073                           ", and metric: " + m_theMetric->getFullDescriptionStr(),
00074                       OutputLevel::Level_4_DEBUG);
00075         // Construct the vielbein now
00076         ConstructVielbein();
00077     }
00078
00079     // Heart of the ViewScreen: here, the ViewScreen is asked to provide initial conditions
00080     // for the geodesic nr index of the current iteration; based on the screen index
00081     // that the Mesh gives, it sets up these physical initial conditions.
00082     void SetNewInitialConditions(largecounter index, Point &pos, OneIndex &vel, ScreenIndex &scrIndex)
      const;
00083
00084     // These member functions essentially pass on information to/from the Mesh
00085     bool IsFinished() const;              // Does the ViewScreen (i.e. the Mesh) want to integrate
      more geodesics or not?
00086     largecounter getCurNrGeodesics() const; // Current number of geodesics in this iteration
00087     void EndCurrentLoop();                    // The current iteration of geodesics is finished;
      prepare the next one
00088     // NOTE: despite not being const, this function has been designed to be threadsafe!
00089     void GeodesicFinished(largecounter index, std::vector<real> finalValues); // This geodesic has
      been integrated, returning its final "values"
00090
00091     // Description string getter (spaces allowed), also will contain information about the Mesh
00092     std::string getFullDescriptionStr() const;
00093
00094 private:
00096     TwoIndex m_Metric_dd{};
00098     TwoIndex m_Vielbein{};
00099
00100     // Helper function to construct the vielbein given the metric
00101     void ConstructVielbein();
00102
00104     const Point m_Pos;
00106     const OneIndex m_Direction;
00108     const ScreenPoint m_ScreenSize;
00110     const ScreenPoint m_ScreenCenter;
00111
00113     const bool m_rLogScale;
00114
00116     const Metric *const m_theMetric;
00117
00119     const GeodesicType m_GeodType{GeodesicType::Null};
00120
00122     const std::unique_ptr<Mesh> m_theMesh;
00123 };
00124
00125 #endif
```

Index

~Diagnostic
  Diagnostic, 50
~DiagnosticOptions
  DiagnosticOptions, 53
~EmissionModel
  EmissionModel, 54
~FluidVelocityModel
  FluidVelocityModel, 70
~Mesh
  Mesh, 127
~Metric
  Metric, 129
~Source
  Source, 150
~Termination
  Termination, 172
~TerminationOptions
  TerminationOptions, 174
~band_matrix
  tk::internal::band_matrix, 24

AtHorizonEps
  HorizonTermOptions, 106

band_matrix
  tk::internal::band_matrix, 23
bd_type
  tk::spline, 154
BosonStarMetric, 26
  BosonStarMetric, 27
  getFullDescriptionStr, 28
  getMetric_dd, 28
  getMetric_uu, 28
  m_m_filename, 29
  m_mSpline, 29
  m_num_lines, 29
  m_Phi_filename, 29
  m_Phi_infinity, 29
  m_PhiSpline, 29
  read_data, 28
BoundarySphere
  Terminations.h, 250
BoundarySphereTermination, 30
  BoundarySphereTermination, 31
  CheckTermination, 31
  getFullDescriptionStr, 31
  TermOptions, 31
BoundarySphereTermOptions, 32
  BoundarySphereTermOptions, 32
  rLogScale, 33
  SphereRadius, 33

CheckTermination
  BoundarySphereTermination, 31
  GeneralSingularityTermination, 82
  HorizonTermination, 105
  NaNTermination, 133
  Termination, 173
  ThetaSingularityTermination, 176
  TimeOutTermination, 180
Clock
  Utilities::Timer, 183
ClosestRadiusDiagnostic, 33
  ClosestRadiusDiagnostic, 34
  DiagOptions, 36
  FinalDataValDistance, 34
  getFinalDataVal, 35
  getFullDataStr, 35
  getFullDescriptionStr, 35
  getNameStr, 35
  m_ClosestRadius, 36
  Reset, 36
  UpdateData, 36
ClosestRadiusOptions, 37
  ClosestRadiusOptions, 37
  RLogScale, 38
Config, 11
  ConfigCollection, 12
  GetGeodesicIntegrator, 12
  GetMesh, 12
  GetMetric, 13
  GetOutputHandler, 13
  GetSource, 13
  GetViewScreen, 14
  InitializeDiagnostics, 14
  InitializeScreenOutput, 14
  InitializeTerminations, 15
  Output_Important_Default, 15
  Output_Other_Default, 15
  SettingError, 12
ConfigCollection
  Config, 12
ConfigReader, 15
  MaxStreamSize, 16
ConfigReader::ConfigCollection, 38
  ConfigSettingValue, 39
  DisplayCollection, 40
  DisplaySetting, 40
  DisplayTabs, 40
  Exists, 40

GetSettingIndex, 41
IsCollection, 41
LookupValue, 42
LookupValueInteger, 43–45
m_Settings, 48
NrSettings, 45
operator[], 45, 46
ReadCollection, 46
ReadFile, 46
ReadSettingName, 46
ReadSettingSpecificChar, 47
ReadSettingValue, 47
ConfigReader::ConfigCollection::ConfigSetting, 49
SettingName, 49
SettingValue, 49
ConfigReader::ConfigReaderException, 48
ConfigReaderException, 48
m_settingtrace, 49
trace, 48
ConfigReaderException
ConfigReader::ConfigReaderException, 48
ConfigSettingValue
ConfigReader::ConfigCollection, 39
ConstructVielbein
ViewScreen, 187
Continue
Terminations.h, 250
CreateDiagnosticVector
Diagnostics.cpp, 199
Diagnostics.h, 201
CreateTerminationVector
Terminations.cpp, 247
Terminations.h, 250
cspline
tk::spline, 155
cspline_hermite
tk::spline, 155

DecideUpdate
Diagnostic, 50
Termination, 173
delta_nodiv0
Integrators, 18
deriv
tk::spline, 155
Derivative_hval
Integrators, 18
Diag_ClosestRadius
Diagnostics.h, 201
Diag_EquatorialEmission
Diagnostics.h, 201
Diag_EquatorialPasses
Diagnostics.h, 202
Diag_FourColorScreen
Diagnostics.h, 202
Diag_GeodesicPosition
Diagnostics.h, 202
Diag_None
Diagnostics.h, 202
DiagBitflag
Diagnostics.h, 201
Diagnostic, 49
~Diagnostic, 50
DecideUpdate, 50
Diagnostic, 50
FinalDataValDistance, 51
getFinalDataVal, 51
getFullDataStr, 51
getFullDescriptionStr, 51
getNameStr, 51
m_OwnerGeodesic, 52
m_StepsSinceUpdated, 52
Reset, 52
UpdateData, 52
DiagnosticOptions, 53
~DiagnosticOptions, 53
DiagnosticOptions, 53
theUpdateFrequency, 53
Diagnostics.cpp
CreateDiagnosticVector, 199
Diagnostics.h
CreateDiagnosticVector, 201
Diag_ClosestRadius, 201
Diag_EquatorialEmission, 201
Diag_EquatorialPasses, 202
Diag_FourColorScreen, 202
Diag_GeodesicPosition, 202
Diag_None, 202
DiagBitflag, 201
DiagnosticUniqueVector, 201
DiagnosticUniqueVector
Diagnostics.h, 201
DiagOptions
ClosestRadiusDiagnostic, 36
EquatorialEmissionDiagnostic, 59
EquatorialPassesDiagnostic, 65
GeodesicPositionDiagnostic, 99
DiagValue
SquareSubdivisionMesh::PixelInfo, 138
dim
tk::internal::band_matrix, 24
dimension
Geometry.h, 221
DisplayCollection
ConfigReader::ConfigCollection, 40
DisplaySetting
ConfigReader::ConfigCollection, 40
DisplayTabs
ConfigReader::ConfigCollection, 40
DownNbr
SquareSubdivisionMesh::PixelInfo, 138

elapsed
Utilities::Timer, 183
EmissionModel, 54
~EmissionModel, 54
GetEmission, 54
getFullDescriptionStr, 54

EndCurrentLoop
InputCertainPixelsMesh, 109
Mesh, 127
SimpleSquareMesh, 145
SquareSubdivisionMesh, 160
ViewScreen, 187
Epsilon
GeneralSingularityTermOptions, 84
epsilon
Integrators, 18
EquatorialEmissionDiagnostic, 55
DiagOptions, 59
EquatorialEmissionDiagnostic, 57
FinalDataValDistance, 57
getFinalDataVal, 57
getFullDataStr, 57
getFullDescriptionStr, 58
getNameStr, 58
m_Intensity, 59
Reset, 58
UpdateData, 58
EquatorialEmissionOptions, 59
EquatorialEmissionOptions, 60
EquatPassUpperBound, 61
GeometricFudgeFactor, 61
RedShiftPower, 61
RLogScale, 61
TheEmissionModel, 61
TheFluidVelocityModel, 61
EquatorialPassesDiagnostic, 61
DiagOptions, 65
EquatorialPassesDiagnostic, 63
FinalDataValDistance, 63
getFinalDataVal, 63
getFullDataStr, 63
getFullDescriptionStr, 64
getNameStr, 64
m_EquatPasses, 65
m_PrevTheta, 65
Reset, 64
UpdateData, 64
EquatorialPassesOptions, 65
EquatorialPassesOptions, 66
Threshold, 66
EquatPassUpperBound
EquatorialEmissionOptions, 61
Exists
ConfigReader::ConfigCollection, 40
ExpInt
SquareSubdivisionMesh, 160

f_om_phi
ST3CrMetric, 169
f_phi
ST3CrMetric, 169
FinalDataValDistance
ClosestRadiusDiagnostic, 34
Diagnostic, 51
EquatorialEmissionDiagnostic, 57
EquatorialPassesDiagnostic, 63
FourColorScreenDiagnostic, 72
GeodesicPositionDiagnostic, 98
find_closest
tk::spline, 155
FindISCO
GeneralCircularRadialFluid, 76
first_deriv
tk::spline, 154
FlatSpaceMetric, 67
FlatSpaceMetric, 68
getFullDescriptionStr, 68
getMetric_dd, 68
getMetric_uu, 68
FluidVelocityModel, 69
~FluidVelocityModel, 70
FluidVelocityModel, 70
GetFourVelocityd, 70
getFullDescriptionStr, 70
m_theMetric, 70
FOORT/src/Config.cpp, 191
FOORT/src/Config.h, 191, 193
FOORT/src/ConfigReader.cpp, 194
FOORT/src/ConfigReader.h, 195, 196
FOORT/src/Diagnostics.cpp, 198
FOORT/src/Diagnostics.h, 199, 202
FOORT/src/DiagnosticsEmission.cpp, 207
FOORT/src/DiagnosticsEmission.h, 208, 209
FOORT/src/Geodesic.cpp, 211
FOORT/src/Geodesic.h, 211, 212
FOORT/src/Geometry.h, 214, 222
FOORT/src/InputOutput.cpp, 223
FOORT/src/InputOutput.h, 225, 228
FOORT/src/Integrators.cpp, 229
FOORT/src/Integrators.h, 230, 232
FOORT/src/Main.cpp, 232
FOORT/src/Mesh.cpp, 233
FOORT/src/Mesh.h, 234, 235
FOORT/src/Metric.cpp, 238
FOORT/src/Metric.h, 238, 240
FOORT/src/Spline.cpp, 243
FOORT/src/Spline.h, 244, 245
FOORT/src/Terminations.cpp, 247
FOORT/src/Terminations.h, 248, 252
FOORT/src/Utilities.cpp, 256
FOORT/src/Utilities.h, 257, 258
FOORT/src/ViewScreen.cpp, 258
FOORT/src/ViewScreen.h, 259, 260
FourColorScreenDiagnostic, 71
FinalDataValDistance, 72
FourColorScreenDiagnostic, 72
getFinalDataVal, 72
getFullDataStr, 72
getFullDescriptionStr, 73
getNameStr, 73
m_quadrant, 74
Reset, 73
UpdateData, 73

FourIndex
Geometry.h, 216

GeneralCircularRadialFluid, 74
FindISCO, 76
GeneralCircularRadialFluid, 76
GetChristrRaisedDer, 76
GetCircularVelocityd, 76
GetFourVelocityd, 77
getFullDescriptionStr, 77
GetInsideISCOCircularVelocityd, 77
GetRadialVelocityd, 78
m_betaPhi, 78
m_betaR, 78
m_ISCOexists, 78
m_ISCOlowerbound, 79
m_ISCOpphi, 79
m_ISCOpt, 79
m_ISCOr, 79
m_ISCOupperbound, 79
m_subKeplerParam, 79
m_WarnedInsideISCO, 79
m_WarnedNaN, 79
m_WarnedNoCircular, 80
m_WarnedNormalization, 80
m_WarnedSubkeplerianRescaling, 80
WarnOnce, 78
GeneralSingularity
Terminations.h, 250
GeneralSingularityTermination, 80
CheckTermination, 82
GeneralSingularityTermination, 81
getFullDescriptionStr, 82
SingularityToString, 82
TermOptions, 82
GeneralSingularityTermOptions, 83
Epsilon, 84
GeneralSingularityTermOptions, 84
OutputToConsole, 84
rLogScale, 84
Singularities, 84
Geodesic, 84
Geodesic, 86
getAllOutputStr, 86
getCurrentLambda, 86
getCurrentPos, 87
getCurrentVel, 87
getDiagnosticFinalValue, 87
getScreenIndex, 87
getTermCondition, 87
m_AllDiagnostics, 89
m_AllTerminations, 89
m_curLambda, 89
m_CurrentPos, 89
m_CurrentVel, 89
m_ScreenIndex, 89
m_TermCond, 89
m_theIntegrator, 89
m_theMetric, 90
m_theSource, 90
operator=, 88
Reset, 88
Update, 88
GeodesicFinished
InputCertainPixelsMesh, 109
Mesh, 127
SimpleSquareMesh, 145
SquareSubdivisionMesh, 161
ViewScreen, 187
GeodesicIntegratorFunc
Integrators.h, 231
GeodesicOutputHandler, 90
GeodesicOutputHandler, 91
GetFileName, 92
getFullDescriptionStr, 92
m_AllCachedData, 94
m_CurrentFullFiles, 94
m_CurrentGeodesicsInFile, 95
m_DiagNames, 95
m_FileExtension, 95
m_FilePrefix, 95
m_FirstLineInfoString, 95
m_nrGeodesicsPerFile, 95
m_nrOutputsToCache, 95
m_PrevCached, 95
m_PrintFirstLineInfo, 96
m_TimeStamp, 96
m_WriteToConsole, 96
NewGeodesicOutput, 92
OpenForFirstTime, 94
OutputFinished, 94
PrepareForOutput, 94
WriteCachedOutputToFile, 94
GeodesicPositionDiagnostic, 96
DiagOptions, 99
FinalDataValDistance, 98
GeodesicPositionDiagnostic, 98
getFinalDataVal, 98
getFullDataStr, 98
getFullDescriptionStr, 98
getNameStr, 99
m_AllSavedPoints, 99
Reset, 99
UpdateData, 99
GeodesicPositionOptions, 100
GeodesicPositionOptions, 101
OutputNrSteps, 101
RLogScale, 101
GeodesicType
ViewScreen.h, 260
GeometricFudgeFactor
EquatorialEmissionOptions, 61
Geometry.h
dimension, 221
FourIndex, 216
largecounter, 216
LARGECOUNTER_MAX, 216

OneIndex, 216
operator+, 218
operator-, 219
operator/, 219
operator∗, 217, 218
pi, 221
PIXEL_MAX, 216
pixelcoord, 216
Point, 216
real, 216
ScreenIndex, 217
ScreenPoint, 217
Singularity, 217
SingularityCoord, 217
ThreeIndex, 217
toString, 220, 221
TwoIndex, 217
get_omega
ST3CrMetric, 169
get_x
tk::spline, 155
get_x_max
tk::spline, 155
get_x_min
tk::spline, 155
get_y
tk::spline, 156
GetAdaptiveStep
Integrators, 16
getAllOutputStr
Geodesic, 86
getChristoffel_udd
Metric, 129
GetChristrRaisedDer
GeneralCircularRadialFluid, 76
GetCircularVelocityd
GeneralCircularRadialFluid, 76
getCurNrGeodesics
InputCertainPixelsMesh, 109
Mesh, 127
SimpleSquareMesh, 146
SquareSubdivisionMesh, 161
ViewScreen, 187
getCurrentLambda
Geodesic, 86
getCurrentPos
Geodesic, 87
getCurrentVel
Geodesic, 87
GetDiagNameStrings
Utilities, 20
getDiagnosticFinalValue
Geodesic, 87
GetDown
SquareSubdivisionMesh, 161
GetEmission
EmissionModel, 54
GLMJohnsonSUEmission, 102
GetFileName
GeodesicOutputHandler, 92
getFinalDataVal
ClosestRadiusDiagnostic, 35
Diagnostic, 51
EquatorialEmissionDiagnostic, 57
EquatorialPassesDiagnostic, 63
FourColorScreenDiagnostic, 72
GeodesicPositionDiagnostic, 98
GetFirstLineInfoString
Utilities, 20
GetFourVelocityd
FluidVelocityModel, 70
GeneralCircularRadialFluid, 77
getFullDataStr
ClosestRadiusDiagnostic, 35
Diagnostic, 51
EquatorialEmissionDiagnostic, 57
EquatorialPassesDiagnostic, 63
FourColorScreenDiagnostic, 72
GeodesicPositionDiagnostic, 98
getFullDescriptionStr
BosonStarMetric, 28
BoundarySphereTermination, 31
ClosestRadiusDiagnostic, 35
Diagnostic, 51
EmissionModel, 54
EquatorialEmissionDiagnostic, 58
EquatorialPassesDiagnostic, 64
FlatSpaceMetric, 68
FluidVelocityModel, 70
FourColorScreenDiagnostic, 73
GeneralCircularRadialFluid, 77
GeneralSingularityTermination, 82
GeodesicOutputHandler, 92
GeodesicPositionDiagnostic, 98
GLMJohnsonSUEmission, 102
HorizonTermination, 105
InputCertainPixelsMesh, 109
JohannsenMetric, 113
KerrMetric, 118
KerrSchildMetric, 121
MankoNovikovMetric, 124
Mesh, 127
Metric, 130
NaNTermination, 133
NoSource, 136
RasheedLarsenMetric, 141
SimpleSquareMesh, 146
Source, 150
SquareSubdivisionMesh, 162
ST3CrMetric, 170
Termination, 173
ThetaSingularityTermination, 176
TimeOutTermination, 180
ViewScreen, 187
GetFullIntegratorDescription
Integrators, 17

GetGeodesicIntegrator
Config, 12
getHorizonRadius
SphericalHorizonMetric, 153
GetInsideISCOCircularVelocityd
GeneralCircularRadialFluid, 77
getKretschmann
Metric, 130
GetLeft
SquareSubdivisionMesh, 162
GetLoopMessageFrequency
InputOutput.cpp, 224
InputOutput.h, 227
GetMesh
Config, 12
GetMetric
Config, 13
getMetric_dd
BosonStarMetric, 28
FlatSpaceMetric, 68
JohannsenMetric, 113
KerrMetric, 118
KerrSchildMetric, 121
MankoNovikovMetric, 124
Metric, 130
RasheedLarsenMetric, 141
ST3CrMetric, 170
getMetric_uu
BosonStarMetric, 28
FlatSpaceMetric, 68
JohannsenMetric, 115
KerrMetric, 118
KerrSchildMetric, 122
MankoNovikovMetric, 125
Metric, 130
RasheedLarsenMetric, 143
ST3CrMetric, 170
getNameStr
ClosestRadiusDiagnostic, 35
Diagnostic, 51
EquatorialEmissionDiagnostic, 58
EquatorialPassesDiagnostic, 64
FourColorScreenDiagnostic, 73
GeodesicPositionDiagnostic, 99
getNewInitConds
InputCertainPixelsMesh, 110
Mesh, 127
SimpleSquareMesh, 146
SquareSubdivisionMesh, 162
GetOutputHandler
Config, 13
GetRadialVelocityd
GeneralCircularRadialFluid, 78
getRiemann_uddd
Metric, 131
GetRight
SquareSubdivisionMesh, 163
getrLogScale
Metric, 131
getScreenIndex
Geodesic, 87
GetSettingIndex
ConfigReader::ConfigCollection, 41
getSingularities
SingularityMetric, 149
GetSource
Config, 13
getSource
NoSource, 136
Source, 150
getTermCondition
Geodesic, 87
GetTimeStampString
Utilities, 21
GetUp
SquareSubdivisionMesh, 163
GetViewScreen
Config, 14
GLMJohnsonSUEmission, 101
GetEmission, 102
getFullDescriptionStr, 102
GLMJohnsonSUEmission, 102
m_gamma, 103
m_mu, 103
m_sigma, 103

Horizon
Terminations.h, 250
HorizonRadius
HorizonTermOptions, 106
HorizonTermination, 103
CheckTermination, 105
getFullDescriptionStr, 105
HorizonTermination, 104
TermOptions, 105
HorizonTermOptions, 105
AtHorizonEps, 106
HorizonRadius, 106
HorizonTermOptions, 106
rLogScale, 107

Index
SquareSubdivisionMesh::PixelInfo, 138
InitializeDiagnostics
Config, 14
InitializeFirstGrid
SquareSubdivisionMesh, 163
InitializeScreenOutput
Config, 14
InitializeTerminations
Config, 15
InputCertainPixelsMesh, 107
EndCurrentLoop, 109
GeodesicFinished, 109
getCurNrGeodesics, 109
getFullDescriptionStr, 109
getNewInitConds, 110

InputCertainPixelsMesh, 108
IsFinished, 110
m_Finished, 110
m_PixelsToIntegrate, 110
m_RowColumnSize, 111
m_TotalPixels, 111
InputOutput.cpp
GetLoopMessageFrequency, 224
ScreenOutput, 224
SetLoopMessageFrequency, 225
SetOutputLevel, 225
InputOutput.h
GetLoopMessageFrequency, 227
Level_0_WARNING, 227
Level_1_PROC, 227
Level_2_SUBPROC, 227
Level_3_ALLDETAIL, 227
Level_4_DEBUG, 227
MaxLevel, 227
OutputLevel, 226
ScreenOutput, 227
SetLoopMessageFrequency, 227
SetOutputLevel, 228
IntegrateGeodesicStep_RK4
Integrators, 17
IntegrateGeodesicStep_Verlet
Integrators, 17
IntegratorDescription
Integrators, 18
Integrators, 16
delta_nodiv0, 18
Derivative_hval, 18
epsilon, 18
GetAdaptiveStep, 16
GetFullIntegratorDescription, 17
IntegrateGeodesicStep_RK4, 17
IntegrateGeodesicStep_Verlet, 17
IntegratorDescription, 18
SmallestPossibleStepsize, 18
VerletMaxIterations, 18
VerletVelocityTolerance, 19
Integrators.h
GeodesicIntegratorFunc, 231
IsCollection
ConfigReader::ConfigCollection, 41
IsFinished
InputCertainPixelsMesh, 110
Mesh, 128
SimpleSquareMesh, 146
SquareSubdivisionMesh, 163
ViewScreen, 187

JohannsenMetric, 111
getFullDescriptionStr, 113
getMetric_dd, 113
getMetric_uu, 115
JohannsenMetric, 113
m_alpha13Param, 115
m_alpha22Param, 115
m_alpha52Param, 115
m_aParam, 115
m_eps3Param, 116

KerrMetric, 116
getFullDescriptionStr, 118
getMetric_dd, 118
getMetric_uu, 118
KerrMetric, 118
m_aParam, 119
m_mParam, 119
KerrSchildMetric, 119
getFullDescriptionStr, 121
getMetric_dd, 121
getMetric_uu, 122
KerrSchildMetric, 121
m_aParam, 122

l_solve
tk::internal::band_matrix, 24
largecounter
Geometry.h, 216
LARGECOUNTER_MAX
Geometry.h, 216
LeftNbr
SquareSubdivisionMesh::PixelInfo, 138
Level_0_WARNING
InputOutput.h, 227
Level_1_PROC
InputOutput.h, 227
Level_2_SUBPROC
InputOutput.h, 227
Level_3_ALLDETAIL
InputOutput.h, 227
Level_4_DEBUG
InputOutput.h, 227
linear
tk::spline, 155
LookupValue
ConfigReader::ConfigCollection, 42
LookupValueInteger
ConfigReader::ConfigCollection, 43–45
lu_decompose
tk::internal::band_matrix, 24
lu_solve
tk::internal::band_matrix, 24

m_ActivePixels
SquareSubdivisionMesh, 164
m_AllCachedData
GeodesicOutputHandler, 94
m_AllDiagnostics
Geodesic, 89
m_AllPixels
SquareSubdivisionMesh, 164
m_AllSavedPoints
GeodesicPositionDiagnostic, 99
m_AllSingularities
SingularityMetric, 149

m_AllTerminations
Geodesic, 89
m_alpha13Param
JohannsenMetric, 115
m_alpha22Param
JohannsenMetric, 115
m_alpha3Param
MankoNovikovMetric, 125
m_alpha52Param
JohannsenMetric, 115
m_alphaParam
MankoNovikovMetric, 125
m_aParam
JohannsenMetric, 115
KerrMetric, 119
KerrSchildMetric, 122
MankoNovikovMetric, 125
RasheedLarsenMetric, 143
m_b
tk::spline, 156
m_beg
Utilities::Timer, 184
m_betaPhi
GeneralCircularRadialFluid, 78
m_betaR
GeneralCircularRadialFluid, 78
m_c
tk::spline, 156
m_c0
tk::spline, 157
m_ClosestRadius
ClosestRadiusDiagnostic, 36
m_curLambda
Geodesic, 89
m_CurNrSteps
TimeOutTermination, 180
m_CurrentFullFiles
GeodesicOutputHandler, 94
m_CurrentGeodesicsInFile
GeodesicOutputHandler, 95
m_CurrentPixelQueue
SquareSubdivisionMesh, 165
m_CurrentPixelQueueDone
SquareSubdivisionMesh, 165
m_CurrentPixelUpdating
SquareSubdivisionMesh, 165
m_CurrentPos
Geodesic, 89
m_CurrentVel
Geodesic, 89
m_d
tk::spline, 157
m_DiagNames
GeodesicOutputHandler, 95
m_Direction
ViewScreen, 188
m_DistanceDiagnostic
Mesh, 128
m_eps3Param
JohannsenMetric, 116
m_EquatPasses
EquatorialPassesDiagnostic, 65
m_FileExtension
GeodesicOutputHandler, 95
m_FilePrefix
GeodesicOutputHandler, 95
m_Finished
InputCertainPixelsMesh, 110
SimpleSquareMesh, 147
m_FirstLineInfoString
GeodesicOutputHandler, 95
m_gamma
GLMJohnsonSUEmission, 103
m_GeodType
ViewScreen, 188
m_HorizonRadius
SphericalHorizonMetric, 153
m_InfinitePixels
SquareSubdivisionMesh, 165
m_InitialPixels
SquareSubdivisionMesh, 165
m_InitialSubDividideToFinal
SquareSubdivisionMesh, 165
m_Intensity
EquatorialEmissionDiagnostic, 59
m_ISCOexists
GeneralCircularRadialFluid, 78
m_ISCOlowerbound
GeneralCircularRadialFluid, 79
m_ISCOpphi
GeneralCircularRadialFluid, 79
m_ISCOpt
GeneralCircularRadialFluid, 79
m_ISCOr
GeneralCircularRadialFluid, 79
m_ISCOupperbound
GeneralCircularRadialFluid, 79
m_IterationPixels
SquareSubdivisionMesh, 165
m_kParam
MankoNovikovMetric, 125
m_lambda
ST3CrMetric, 171
m_left
tk::spline, 157
m_left_value
tk::spline, 157
m_lower
tk::internal::band_matrix, 25
m_m_filename
BosonStarMetric, 29
m_made_monotonic
tk::spline, 157
m_MaxPixels
SquareSubdivisionMesh, 166
m_MaxSubdivide

SquareSubdivisionMesh, 166
m_Metric_dd
ViewScreen, 188
m_mParam
KerrMetric, 119
RasheedLarsenMetric, 143
m_mSpline
BosonStarMetric, 29
m_mu
GLMJohnsonSUEmission, 103
m_nrGeodesicsPerFile
GeodesicOutputHandler, 95
m_nrOutputsToCache
GeodesicOutputHandler, 95
m_num_lines
BosonStarMetric, 29
m_OwnerGeodesic
Diagnostic, 52
Termination, 173
m_P
ST3CrMetric, 171
m_Phi_filename
BosonStarMetric, 29
m_Phi_infinity
BosonStarMetric, 29
m_PhiSpline
BosonStarMetric, 29
m_PixelsIntegrated
SquareSubdivisionMesh, 166
m_PixelsLeft
SquareSubdivisionMesh, 166
m_PixelsToIntegrate
InputCertainPixelsMesh, 110
m_Pos
ViewScreen, 188
m_pParam
RasheedLarsenMetric, 143
m_PrevCached
GeodesicOutputHandler, 95
m_PrevTheta
EquatorialPassesDiagnostic, 65
m_PrintFirstLineInfo
GeodesicOutputHandler, 96
m_q0
ST3CrMetric, 171
m_qParam
RasheedLarsenMetric, 143
m_quadrant
FourColorScreenDiagnostic, 74
m_right
tk::spline, 157
m_right_value
tk::spline, 157
m_rLogScale
Metric, 131
ViewScreen, 189
m_RowColumnSize
InputCertainPixelsMesh, 111
SimpleSquareMesh, 147
SquareSubdivisionMesh, 166
m_ScreenCenter
ViewScreen, 189
m_ScreenIndex
Geodesic, 89
m_ScreenSize
ViewScreen, 189
m_Settings
ConfigReader::ConfigCollection, 48
m_settingtrace
ConfigReader::ConfigReaderException, 49
m_sigma
GLMJohnsonSUEmission, 103
m_StepsSinceUpdated
Diagnostic, 52
Termination, 173
m_subKeplerParam
GeneralCircularRadialFluid, 79
m_Symmetries
Metric, 131
m_TermCond
Geodesic, 89
m_theIntegrator
Geodesic, 89
m_theMesh
ViewScreen, 189
m_theMetric
FluidVelocityModel, 70
Geodesic, 90
Source, 151
ViewScreen, 189
m_theSource
Geodesic, 90
m_TimeStamp
GeodesicOutputHandler, 96
m_TotalPixels
InputCertainPixelsMesh, 111
SimpleSquareMesh, 147
m_type
tk::spline, 157
m_upper
tk::internal::band_matrix, 25
m_Vielbein
ViewScreen, 189
m_WarnedInsideISCO
GeneralCircularRadialFluid, 79
m_WarnedNaN
GeneralCircularRadialFluid, 79
m_WarnedNoCircular
GeneralCircularRadialFluid, 80
m_WarnedNormalization
GeneralCircularRadialFluid, 80
m_WarnedSubkeplerianRescaling
GeneralCircularRadialFluid, 80
m_WriteToConsole
GeodesicOutputHandler, 96
m_x

tk::spline, 157
m_y
tk::spline, 157
main
Main.cpp, 233
Main.cpp
main, 233
make_monotonic
tk::spline, 156
MankoNovikovMetric, 122
getFullDescriptionStr, 124
getMetric_dd, 124
getMetric_uu, 125
m_alpha3Param, 125
m_alphaParam, 125
m_aParam, 125
m_kParam, 125
MankoNovikovMetric, 124
MaxLevel
InputOutput.h, 227
MaxSteps
TimeOutTermOptions, 182
MaxStreamSize
ConfigReader, 16
Maxterms
Terminations.h, 250
Mesh, 126
∼Mesh, 127
EndCurrentLoop, 127
GeodesicFinished, 127
getCurNrGeodesics, 127
getFullDescriptionStr, 127
getNewInitConds, 127
IsFinished, 128
m_DistanceDiagnostic, 128
Mesh, 127
Metric, 128
∼Metric, 129
getChristoffel_udd, 129
getFullDescriptionStr, 130
getKretschmann, 130
getMetric_dd, 130
getMetric_uu, 130
getRiemann_uddd, 131
getrLogScale, 131
m_rLogScale, 131
m_Symmetries, 131
Metric, 129

NaN
Terminations.h, 250
NaNTermination, 132
CheckTermination, 133
getFullDescriptionStr, 133
NaNTermination, 133
TermOptions, 134
NaNTermOptions, 134
NaNTermOptions, 135
OutputToConsole, 135
NewGeodesicOutput
GeodesicOutputHandler, 92
NoSource, 135
getFullDescriptionStr, 136
getSource, 136
NoSource, 136
NrSettings
ConfigReader::ConfigCollection, 45
Null
ViewScreen.h, 260
num_lower
tk::internal::band_matrix, 24
num_upper
tk::internal::band_matrix, 24

OneIndex
Geometry.h, 216
OpenForFirstTime
GeodesicOutputHandler, 94
operator()
tk::internal::band_matrix, 24
tk::spline, 156
operator+
Geometry.h, 218
operator-
Geometry.h, 219
operator/
Geometry.h, 219
operator=
Geodesic, 88
operator[]
ConfigReader::ConfigCollection, 45, 46
operator∗
Geometry.h, 217, 218
Output_Important_Default
Config, 15
Output_Other_Default
Config, 15
OutputFinished
GeodesicOutputHandler, 94
OutputLevel
InputOutput.h, 226
OutputNrSteps
GeodesicPositionOptions, 101
OutputToConsole
GeneralSingularityTermOptions, 84
NaNTermOptions, 135

pi
Geometry.h, 221
PIXEL_MAX
Geometry.h, 216
pixelcoord
Geometry.h, 216
PixelInfo
SquareSubdivisionMesh::PixelInfo, 138
Point
Geometry.h, 216
PrepareForOutput

GeodesicOutputHandler, 94

r_solve
tk::internal::band_matrix, 25
RasheedLarsenMetric, 139
getFullDescriptionStr, 141
getMetric_dd, 141
getMetric_uu, 143
m_aParam, 143
m_mParam, 143
m_pParam, 143
m_qParam, 143
RasheedLarsenMetric, 141
read_data
BosonStarMetric, 28
ReadCollection
ConfigReader::ConfigCollection, 46
ReadFile
ConfigReader::ConfigCollection, 46
ReadSettingName
ConfigReader::ConfigCollection, 46
ReadSettingSpecificChar
ConfigReader::ConfigCollection, 47
ReadSettingValue
ConfigReader::ConfigCollection, 47
real
Geometry.h, 216
RedShiftPower
EquatorialEmissionOptions, 61
Reset
ClosestRadiusDiagnostic, 36
Diagnostic, 52
EquatorialEmissionDiagnostic, 58
EquatorialPassesDiagnostic, 64
FourColorScreenDiagnostic, 73
Geodesic, 88
GeodesicPositionDiagnostic, 99
Termination, 173
TimeOutTermination, 180
reset
Utilities::Timer, 183
resize
tk::internal::band_matrix, 25
RightNbr
SquareSubdivisionMesh::PixelInfo, 138
RLogScale
ClosestRadiusOptions, 38
EquatorialEmissionOptions, 61
GeodesicPositionOptions, 101
rLogScale
BoundarySphereTermOptions, 33
GeneralSingularityTermOptions, 84
HorizonTermOptions, 107

saved_diag
tk::internal::band_matrix, 25
ScreenIndex
Geometry.h, 217
ScreenOutput
InputOutput.cpp, 224
InputOutput.h, 227
ScreenPoint
Geometry.h, 217
Second
Utilities::Timer, 183
second_deriv
tk::spline, 154
SEdiagNbr
SquareSubdivisionMesh::PixelInfo, 138
set_boundary
tk::spline, 156
set_coeffs_from_b
tk::spline, 156
set_points
tk::spline, 156
SetLoopMessageFrequency
InputOutput.cpp, 225
InputOutput.h, 227
SetNewInitialConditions
ViewScreen, 188
SetOutputLevel
InputOutput.cpp, 225
InputOutput.h, 228
SettingError
Config, 12
SettingName
ConfigReader::ConfigCollection::ConfigSetting, 49
SettingValue
ConfigReader::ConfigCollection::ConfigSetting, 49
SimpleSquareMesh, 144
EndCurrentLoop, 145
GeodesicFinished, 145
getCurNrGeodesics, 146
getFullDescriptionStr, 146
getNewInitConds, 146
IsFinished, 146
m_Finished, 147
m_RowColumnSize, 147
m_TotalPixels, 147
SimpleSquareMesh, 145
Singularities
GeneralSingularityTermOptions, 84
Singularity
Geometry.h, 217
SingularityCoord
Geometry.h, 217
SingularityMetric, 147
getSingularities, 149
m_AllSingularities, 149
SingularityMetric, 148
SingularityToString
GeneralSingularityTermination, 82
SmallestPossibleStepsize
Integrators, 18
Source, 149
∼Source, 150
getFullDescriptionStr, 150

getSource, 150
m_theMetric, 151
Source, 150
Spacelike
ViewScreen.h, 260
SphereRadius
BoundarySphereTermOptions, 33
SphericalHorizonMetric, 151
getHorizonRadius, 153
m_HorizonRadius, 153
SphericalHorizonMetric, 152
spline
tk::spline, 155
spline_type
tk::spline, 154
SquareSubdivisionMesh, 158
EndCurrentLoop, 160
ExpInt, 160
GeodesicFinished, 161
getCurNrGeodesics, 161
GetDown, 161
getFullDescriptionStr, 162
GetLeft, 162
getNewInitConds, 162
GetRight, 163
GetUp, 163
InitializeFirstGrid, 163
IsFinished, 163
m_ActivePixels, 164
m_AllPixels, 164
m_CurrentPixelQueue, 165
m_CurrentPixelQueueDone, 165
m_CurrentPixelUpdating, 165
m_InfinitePixels, 165
m_InitialPixels, 165
m_InitialSubDividideToFinal, 165
m_IterationPixels, 165
m_MaxPixels, 166
m_MaxSubdivide, 166
m_PixelsIntegrated, 166
m_PixelsLeft, 166
m_RowColumnSize, 166
SquareSubdivisionMesh, 160
SubdivideAndQueue, 164
UpdateAllWeights, 164
SquareSubdivisionMesh::PixelInfo, 137
DiagValue, 138
DownNbr, 138
Index, 138
LeftNbr, 138
PixelInfo, 138
RightNbr, 138
SEdiagNbr, 138
SubdivideLevel, 139
UpNbr, 139
Weight, 139
ST3CrMetric, 167
f_om_phi, 169
f_phi, 169
get_omega, 169
getFullDescriptionStr, 170
getMetric_dd, 170
getMetric_uu, 170
m_lambda, 171
m_P, 171
m_q0, 171
ST3CrMetric, 168
SubdivideAndQueue
SquareSubdivisionMesh, 164
SubdivideLevel
SquareSubdivisionMesh::PixelInfo, 139

Term
Terminations.h, 250
Term_BoundarySphere
Terminations.h, 251
Term_GeneralSingularity
Terminations.h, 251
Term_Horizon
Terminations.h, 251
Term_NaN
Terminations.h, 251
Term_None
Terminations.h, 251
Term_ThetaSingularity
Terminations.h, 251
Term_TimeOut
Terminations.h, 251
TermBitflag
Terminations.h, 250
Termination, 171
∼Termination, 172
CheckTermination, 173
DecideUpdate, 173
getFullDescriptionStr, 173
m_OwnerGeodesic, 173
m_StepsSinceUpdated, 173
Reset, 173
Termination, 172
TerminationOptions, 174
∼TerminationOptions, 174
TerminationOptions, 174
UpdateEveryNSteps, 175
Terminations.cpp
CreateTerminationVector, 247
Terminations.h
BoundarySphere, 250
Continue, 250
CreateTerminationVector, 250
GeneralSingularity, 250
Horizon, 250
Maxterms, 250
NaN, 250
Term, 250
Term_BoundarySphere, 251
Term_GeneralSingularity, 251
Term_Horizon, 251

Term_NaN, 251
Term_None, 251
Term_ThetaSingularity, 251
Term_TimeOut, 251
TermBitflag, 250
TerminationUniqueVector, 250
ThetaSingularity, 250
TimeOut, 250
Uninitialized, 250
TerminationUniqueVector
Terminations.h, 250
TermOptions
BoundarySphereTermination, 31
GeneralSingularityTermination, 82
HorizonTermination, 105
NaNTermination, 134
ThetaSingularityTermination, 177
TimeOutTermination, 180
TheEmissionModel
EquatorialEmissionOptions, 61
TheFluidVelocityModel
EquatorialEmissionOptions, 61
ThetaSingEpsilon
ThetaSingularityTermOptions, 178
ThetaSingularity
Terminations.h, 250
ThetaSingularityTermination, 175
CheckTermination, 176
getFullDescriptionStr, 176
TermOptions, 177
ThetaSingularityTermination, 176
ThetaSingularityTermOptions, 177
ThetaSingEpsilon, 178
ThetaSingularityTermOptions, 178
theUpdateFrequency
DiagnosticOptions, 53
ThreeIndex
Geometry.h, 217
Threshold
EquatorialPassesOptions, 66
Timelike
ViewScreen.h, 260
TimeOut
Terminations.h, 250
TimeOutTermination, 178
CheckTermination, 180
getFullDescriptionStr, 180
m_CurNrSteps, 180
Reset, 180
TermOptions, 180
TimeOutTermination, 180
TimeOutTermOptions, 181
MaxSteps, 182
TimeOutTermOptions, 182
tk, 19
tk::internal, 19
tk::internal::band_matrix, 23
~band_matrix, 24
band_matrix, 23
dim, 24
l_solve, 24
lu_decompose, 24
lu_solve, 24
m_lower, 25
m_upper, 25
num_lower, 24
num_upper, 24
operator(), 24
r_solve, 25
resize, 25
saved_diag, 25
tk::spline, 153
bd_type, 154
cspline, 155
cspline_hermite, 155
deriv, 155
find_closest, 155
first_deriv, 154
get_x, 155
get_x_max, 155
get_x_min, 155
get_y, 156
linear, 155
m_b, 156
m_c, 156
m_c0, 157
m_d, 157
m_left, 157
m_left_value, 157
m_made_monotonic, 157
m_right, 157
m_right_value, 157
m_type, 157
m_x, 157
m_y, 157
make_monotonic, 156
operator(), 156
second_deriv, 154
set_boundary, 156
set_coeffs_from_b, 156
set_points, 156
spline, 155
spline_type, 154
toString
Geometry.h, 220, 221
trace
ConfigReader::ConfigReaderException, 48
TwoIndex
Geometry.h, 217

Uninitialized
Terminations.h, 250
Update
Geodesic, 88
UpdateAllWeights
SquareSubdivisionMesh, 164
UpdateData

ClosestRadiusDiagnostic, 36
Diagnostic, 52
EquatorialEmissionDiagnostic, 58
EquatorialPassesDiagnostic, 64
FourColorScreenDiagnostic, 73
GeodesicPositionDiagnostic, 99
UpdateEveryNSteps
TerminationOptions, 175
UpdateFinish
UpdateFrequency, 184
UpdateFrequency, 184
UpdateFinish, 184
UpdateNSteps, 184
UpdateStart, 184
UpdateNSteps
UpdateFrequency, 184
UpdateStart
UpdateFrequency, 184
UpNbr
SquareSubdivisionMesh::PixelInfo, 139
Utilities, 19
GetDiagNameStrings, 20
GetFirstLineInfoString, 20
GetTimeStampString, 21
Utilities::Timer, 182
Clock, 183
elapsed, 183
m_beg, 184
reset, 183
Second, 183

VerletMaxIterations
Integrators, 18
VerletVelocityTolerance
Integrators, 19
ViewScreen, 185
ConstructVielbein, 187
EndCurrentLoop, 187
GeodesicFinished, 187
getCurNrGeodesics, 187
getFullDescriptionStr, 187
IsFinished, 187
m_Direction, 188
m_GeodType, 188
m_Metric_dd, 188
m_Pos, 188
m_rLogScale, 189
m_ScreenCenter, 189
m_ScreenSize, 189
m_theMesh, 189
m_theMetric, 189
m_Vielbein, 189
SetNewInitialConditions, 188
ViewScreen, 186
ViewScreen.h
GeodesicType, 260
Null, 260
Spacelike, 260
Timelike, 260
WarnOnce
GeneralCircularRadialFluid, 78
Weight
SquareSubdivisionMesh::PixelInfo, 139
WriteCachedOutputToFile
GeodesicOutputHandler, 94