

Problem 1. On an hypothetical island, there are three people: knights who always tell the truth, knaves who always lie, and spies (called normals by Smullyan [Sm78]) who can either lie or tell the truth. You encounter three people, A , B , and C . You know one of these people is a knight, one is a knave, and one is a spy. Each of the three people knows the type of person each of other two is. For each of these situations, if possible, determine whether there is a unique solution and determine who the knave, knight, and spy are. When there is no unique solution, list all possible solutions or state that there are no solutions.

A says “I am the knight,” B says “ A is not the knave,” and C says “ B is not the knave.”

Answer.

Username:

CS441

2025-09-12

Name:

Discrete Structures for CS

hw_1

Problem 2. Four friends have been identified as suspects for an unauthorized access into a computer system. They have made statements to the investigating authorities. Alice said, “Carlos did it.” John said, “I did not do it.” Carlos said, “Diana did it.” Diana said, “Carlos lied when he said that I did it.”

- a) If the authorities also know that exactly one of the four suspects is telling the truth, who did it? Explain your reasoning.
- b) If the authorities also know that exactly one is lying, who did it? Explain your reasoning.

Answer.

Username:

CS441

2025-09-12

Name:

Discrete Structures for CS

hw_1

Problem 3. Show that $(p \rightarrow q) \wedge (p \rightarrow r)$ and $p \rightarrow (q \wedge r)$ are logically equivalent.

Answer.

Username:

CS441

2025-09-12

Name:

Discrete Structures for CS

hw_1

Problem 4. Show that $\neg p \rightarrow (q \rightarrow r)$ and $q \rightarrow (p \vee r)$ are logically equivalent.

Answer.

Username:

CS441

2025-09-12

Name:

Discrete Structures for CS

hw_1

Problem 5. Show that $(p \vee q) \wedge (\neg p \vee r) \rightarrow (q \vee r)$ is a tautology.

Answer.

Username:

CS441

2025-09-12

Name:

Discrete Structures for CS

hw_1

Problem 6. Translate these statements into English, where $R(x)$ is “ x is a rabbit” and $H(x)$ is “ x hops” and the domain consists of all animals.

- a) $\forall x [R(x) \rightarrow H(x)]$
- b) $\forall x [R(x) \wedge H(x)]$
- c) $\exists x [R(x) \rightarrow H(x)]$
- d) $\exists x [R(x) \wedge H(x)]$

Answer.

Problem 7. Let $C(x)$ be the statement “ x has a cat,” let $D(x)$ be the statement “ x has a dog,” and let $F(x)$ be the statement “ x has a ferret.” Express each of these statements in terms of $C(x)$, $D(x)$, $F(x)$, quantifiers, and logical connectives. Let the domain consist of all students in your class.

- a) A student in your class has a cat, a dog, and a ferret.
- b) All students in your class have a cat, a dog, or a ferret.
- c) Some student in your class has a cat and a ferret, but not a dog.
- d) No student in your class has a cat, a dog, and a ferret.
- e) For each of the three animals, cats, dogs, and ferrets, there is a student in your class who has this animal as a pet.

Answer.

Username:

CS441

2025-09-12

Name:

Discrete Structures for CS

hw_1

Problem 8. Let $Q(x)$ be the statement “ $x + 1 > 2x$.” If the domain consists of all integers, what are these truth values?

- a) $Q(0)$
- b) $Q(-1)$
- c) $Q(1)$
- d) $\exists x Q(x)$
- e) $\forall x Q(x)$
- f) $\exists x \neg Q(x)$
- g) $\forall x \neg Q(x)$

Answer.

Username:

CS441

2025-09-12

Name:

Discrete Structures for CS

hw_1

Problem 9. Translate in two ways each of these statements into logical expressions using predicates, quantifiers, and logical connectives. First, let the domain consist of the students in your class and second, let it consist of all people.

- a) Everyone in your class has a cellular phone.
- b) Somebody in your class has seen a foreign movie.
- c) There is a person in your class who cannot swim.
- d) All students in your class can solve quadratic equations.
- e) Some student in your class does not want to be rich.

Answer.

Challenge 1.

We now present a group of exercises that involve the logical operators *NAND* and *NOR*. The proposition $p \text{ NAND } q$ is true when either p or q , or both, are false; and it is false when both p and q are true. The proposition $p \text{ NOR } q$ is true when both p and q are false, and it is false otherwise. The propositions $p \text{ NAND } q$ and $p \text{ NOR } q$ are denoted by $p \mid q$ and $p \downarrow q$, respectively. (The operators $\mid$ and $\downarrow$ are called the **Sheffer stroke** and the **Peirce arrow** after H. M. Shefer and C. S. Peirce, respectively.)

Construct a truth table for the logical operator *NAND*.

Answer.

Username:

CS441

2025-09-12

Name:

Discrete Structures for CS

hw_1

Challenge 2. Show that $\{\mid\}$ is a functionally complete collection of logical operators.