

# Creating and Applying an Age-Length Key

*Derek H. Ogle, Northland College*

*5-Mar-2015*

## Preliminaries

```
> # clears objects in R workspace
> rm(list = ls())

> # load needed packages
> library(fishWiDNR) # for setDBClasses()
> library(FSA)       # for lencat(), filterD()
> library(dplyr)      # for select(), mutate(), arrange(), %>%
> library(magrittr)   # for %<>%
> library(lubridate)  # for month()
> library(plotrix)    # for plotH(), histStack()
```

## Loading Data and Initial Manipulations

```
> # Load and prepare data ... copied from previous handout
> setwd("C:/aaaWork/Web/fishR/Courses/WiDNR_Statewide_2015/Day1_IntroR_FMDData")
> d <- read.csv("SAWYER_fish_raw_data_012915.csv", stringsAsFactors=FALSE, na.strings=c("-", "NA", "")) %>%
  setDBClasses(type="RDNR") %>%
  select(County, Waterbody.Name, Survey.Year, Sample.Date, Gear, Fish.Data.Seq.No, Species,
         Length.or.Lower.Length.IN, Gender, Age..observed.annuli., Edge.Counted.Desc, Age.Structure) %>%
  mutate(mon=month(Sample.Date, label=TRUE)) %>%
  mutate(lcat=lencat(Length.or.Lower.Length.IN, w=0.5)) %>%
  arrange(Species, Length.or.Lower.Length.IN)

> wae <- filterD(d, Waterbody.Name=="NELSON LAKE", Survey.Year==2014, mon=="May", Species=="WALLEYE",
  Gender!="U", Length.or.Lower.Length.IN>11.5, Length.or.Lower.Length.IN<21)
>
> waeF <- filterD(wae, Gender=="F")
> waeM <- filterD(wae, Gender=="M")
```

## Construct an Age-Length Key – Males

```
> waeM.aged <- filterD(waeM, !is.na(Age..observed.annuli.))
> waeM.aged$Age..observed.annuli.
[1] 3 2 3 4 3 3 3 3 4 4 3 5 4 4 4 5 5 5 5 4 4 5 4 4 5 4 6 4 4 4 5 5 5 4 5 4 6 5 5 5 6 6 6 7 6 8
[49] 7 5 6 7 7 9
```


```

> ( rawM <- xtabs(~lcat+Age..observed.annuli.,data=waeM) )
      Age..observed.annuli.
lcat   2 3 4 5 6 7 8 9
 11.5 1 1 0 0 0 0 0 0
 12   0 1 1 0 0 0 0 0
 12.5 0 2 0 0 0 0 0 0
 13   0 2 1 0 0 0 0 0
 13.5 0 1 1 0 0 0 0 0
 14   0 0 3 2 0 0 0 0
 14.5 0 0 2 3 0 0 0 0
 15   0 0 3 2 0 0 0 0
 15.5 0 0 3 0 1 0 0 0
 16   0 0 1 4 0 0 0 0
 16.5 0 0 2 2 1 0 0 0
 17   0 0 0 2 0 0 0 0
 17.5 0 0 0 0 3 0 0 0
 18   0 0 0 0 1 2 1 0
 18.5 0 0 0 1 1 1 0 0
 19.5 0 0 0 0 0 1 0 0
 20.5 0 0 0 0 0 0 0 1

> alkM1 <- prop.table(rawM,margin=1)
> print(alkM1,digits=2,zero.print="-")                                     # for display only
      Age..observed.annuli.
lcat   2    3    4    5    6    7    8    9
 11.5 0.50 0.50    -    -    -    -    -
 12   - 0.50 0.50    -    -    -    -    -
 12.5 - 1.00    -    -    -    -    -    -
 13   - 0.67 0.33    -    -    -    -    -
 13.5 - 0.50 0.50    -    -    -    -    -
 14   - - 0.60 0.40    -    -    -    -
 14.5 - - 0.40 0.60    -    -    -    -
 15   - - 0.60 0.40    -    -    -    -
 15.5 - - 0.75    - 0.25    -    -    -
 16   - - 0.20 0.80    -    -    -    -
 16.5 - - 0.40 0.40 0.20    -    -    -
 17   - - - 1.00    -    -    -    -
 17.5 - - - - 1.00    -    -    -
 18   - - - - 0.25 0.50 0.25    -
 18.5 - - - 0.33 0.33 0.33    -    -
 19.5 - - - - - 1.00    -    -
 20.5 - - - - - - - 1.00

```

```
> alkPlot(alkM1,pal="gray",xlab="Total Length (in)")
```



## Apply an Age-Length Key – Males

```
> waeM.unaged <- filter(waeM,is.na(Age..observed.annuli.))
> waeM.unaged <- alkIndivAge(alkM1,Age..observed.annuli.~Length.or.Lower.Length.IN,data=waeM.unaged)
> waeM.fn1 <- rbind(waeM.aged,waeM.unaged)
> waeM.fn1$Age..observed.annuli.
[1] 3 2 3 4 3 3 3 3 4 4 3 5 4 4 4 5 5 5 5 4 4 5 4 4 5 4 6 4 4 4 5 5 5 4 5 4 5 4 6 5 5 5 6 6 6 7 6
[48] 8 7 5 6 7 7 9 3 4 3 3 3 3 3 3 4 4 4 3 3 3 4 4 4 5 4 5 5 5 5 4 4 5 4 5 4 4 4 4 4 5 4 5 5 4
[95] 4 4 5 4 5 5 5 4 5 5 5 4 5 5 5 5 4 5 4 4 4 5 4 4 4 5 4 4 5 4 4 4 6 4 4 4 6 4 4 4 4 4 6 4 6 4
[142] 4 4 4 4 6 4 4 4 6 4 4 4 6 5 4 5 4 4 5 5 5 5 5 5 5 5 5 5 5 5 4 5 6 4 4 5 4 5 5 5 5 5 5 5 5 6 6
[189] 6 6 7 7 7 9 9
```

## Construct and Apply an Age-Length Key – Females

Code is in the script. However, it is mostly a copy-and-paste of the code from above with the 'M's changed to 'F's

## Application Assignment

Create a script that performs the following tasks:

1. Load your FM data into R. Filter your data to a waterbody, species, year, and sampling date such that some sampled fish were aged and some were not. Perhaps, also filter by sex. [Alternatively, use the Sawyer County database and select Walleye in 2014 or 2013 from Lake Chippewa]
2. Construct an **appropriate** age-length key (ALK) from the aged fish. Visualize the ALK in both tabular and graphical form.
3. Apply the ALK to the unaged fish.
4. Combine the fish aged from a structure and those with ages estimated from the ALK to form a combined data.frame.
5. Confirm that all fish in the final data.frame have assigned ages.
6. (*Time Permitting*) Repeat the above for the other sex or another species.

**Save your script!**