


Rendered with the real 337 swatch, laid as 2m wide sheet.

Durafloor Homogeneous Flooring


High-performance sheet flooring for durability, safety and easy maintenance.

Durafloor homogeneous PVC flooring is a high-performance flooring solution designed for durability, safety, and easy maintenance. Ideal for commercial, industrial, educational, and healthcare environments.


Colour selection




331



328



337



322

Durable. Safe. Reliable.

Durable
High wear resistance

Safe
Slip resistant

Easy to clean
Low maintenance

Hygienic
Antibacterial & stain resistant

Fire retardant
Enhanced safety

Printed and on-screen colours are a guide. Please confirm your choice against an actual sample.

Specification and care

Technical specifications

Characteristics	Standard	Unit	Result
Type of flooring	ISO 10581 / EN 649	-	Homogeneous Sheet
Material	-	-	Polyvinyl chloride
Cover	-	-	PUR
Total thickness	ISO 24346 / EN 428	mm	2.0
Sheet width	ISO 24341 / EN 426	m	2
Sheet length	ISO 24341 / EN 426	m	20
Dimensional stability	ISO 23999 / EN 434	%	X ≤ 0.40%, Y ≤ 0.40%
Abrasion group	EN 660-2	group	T
Reaction to fire	EN 13501-1	class	Bfl-s1
Slip resistance	DIN 51130	group	R9
Antibacterial	ISO 22196	-	> 99%
Color fastness	ISO 105-B02	rating	≥ 6
Resistance to staining	EN 423	-	No Stain 0
Classification	ISO 10874 / EN 685	class	23 / 34 / 43

Application

Commercial, Education, Healthcare, Industrial

Roll size

2m (W) x 20m (L), Thickness: 2.0 mm

Installation

Subfloor to be smooth, hard, clean and dry prior to laying. Where applicable the subfloor must incorporate an effective Damp proof membrane. The material must be allowed to acclimatize 24 hours before installation in a room temperature of between 18 - 24°C. Matching welding rods are required for heat welding on ground floor

Maintenance

An emulsion dressing is required. Maintenance should be carried out regularly to retain the appearance and durability of the floor. The floor covering should be maintained with regular sweeping and mopping using a neutral cleanser, more intense cleaning should be carried out using a fine spray cleaning pad under a floor machine, or for larger areas combined machine cleaning.

Durafloor Industries Sdn. Bhd.
(122259-H)
Tel and WhatsApp 012-3222160
durafloor@hotmail.com
www.durafloor.com.my

HQ Wisma Durafloor
65, Jalan PBS 14/2, Taman
Perindustrian Bukit Serdang,
43300 Seri Kembangan, Selangor

Factory
17, Persiaran Zurah 1, Pusat
Perindustrian Zurah,
Mukim Rasa, 44200 Daerah Hulu
Selangor, Selangor