

Rendered with the real R10-007 swatch, laid as 2m wide sheet.


R10 Premium Series

Safety flooring for high-traffic commercial and residential use.


The R10 Premium Series also known for Safety Floor represents the pinnacle of vinyl flooring innovation, combining superior durability with exceptional aesthetic appeal. This premium collection features advanced surface treatments and cutting-edge design technology to deliver outstanding performance in high-traffic commercial and residential applications.

Product Size: 2m x 20m x 2.0mm / 40m^2/roll / 120kg/roll


Design selection




R10-001




R10-002




R10-003




R10-004




R10-005




R10-006




R10-007




R10-008




R10-009



R10-010



R10-011



R10-012



R10 Premium Series in use

Printed and on-screen colours are a guide. Please confirm your choice against an actual sample.

Specification and care

Description

Property	Standard	Unit	Value
Total Thickness	EN 428	mm	2.0
Weight	EN 430	g/m^2	2.0 mm = 120kg/roll
Width	EN 426	m	2
Length of Sheet	EN 426	m	20

Classification

Property	Standard	Unit	Value
European	EN 685 / EN 649		
Classification K			K5
	NF P 92 506		M1
	EN 13 501 - 1		Class Bfl - S1
Fire Rating	DIN 4102		B1
	ASTM E662		< 400
	ASTM E648		class 1
Electrical Resistance	EN 1815	KV	< 2
	EN 1081	Ohm	$>10^{9-10}$
Slip Resistance Dry	EN 13893		≥ 0.3
Slip Resistance Wet	DIN 51130		R10

Performances

Property	Standard	Unit	Value
Abrasion Group	EN 649		P
Abrasion Resistance	EN 660.1	mm	0.15
Castor Wheel Test	EN 425		excellent
Colour Fastness	EN 20105 - B02	>=	7
Chemical products resistance	EN 423		excellent
Dimensional Stability	EN 434	%	≤ 0.25
Flexibility	EN 435		excellent
Hygiene Treatment	MRSA		excellent
Indentation	EN 433	mm	approx. 0.06
Residual Indentation	EN 433	mm	approx. 0.05

Installation

Subfloor must be smooth, hard, clean and dry prior to installation. Where applicable, the subfloor must incorporate an effective damp proof membrane. The material must be allowed to acclimatize for 24 hours before installation in a room temperature between 18 - 24°C. Matching welding rods are required for heat welding applications.

Maintenance

Regular maintenance is essential to retain the appearance and durability of the floor. The floor covering should be maintained with regular sweeping and mopping using a neutral cleanser. For more intensive cleaning, use a fine spray cleaning pad under a floor machine, or for larger areas, combined machine cleaning with appropriate cleaning solutions.

Durafloor Industries Sdn. Bhd.
(122259-H)
Tel and WhatsApp 012-3222160
durafloor@hotmail.com
www.durafloor.com.my

HQ Wisma Durafloor
65, Jalan PBS 14/2, Taman
Perindustrian Bukit Serdang,
43300 Seri Kembangan, Selangor

Factory
17, Persiaran Zurah 1, Pusat
Perindustrian Zurah,
Mukim Rasa, 44200 Daerah Hulu
Selangor, Selangor