
Lecture 9

Part 4: Data Science and AI


Objects, NumPy & Pandas

Build your own type, then use Python's power tools: arrays, photos as numbers, tables



Dror Jacoby

Where we are


Part 1:
Intro and Python Basics
Part 2:
Decisions and Loops
Part 3:
Functions and
Dictionaries
Part 4:
Data Science
and AI
L1
Hello,
Python!
L2
Variables
& Types
L3
Input &
Output
L4
Making
Decisions
L5
Lists
& Sets
L6
Loops
L7
Functions
L8
Dicts &
Debugging
L9
Objects,
NumPy &
Pandas
L10
Plots &
ML
You are here

Looking back: lectures 7 and 8

✓ Lecture 7: Functions

- `def` names a list of steps, a call runs them
- Parameters bring values in, `return` sends an answer out
- `print` shows, `return` hands back. Defaults: “the usual”
- Variables made inside a function stay inside

✓ Lecture 8: Dicts & Debugging

- A dictionary maps keys to values: look up, `in`, `get`, loop
- Tables are lists of rows. Median = middle of the sorted list
- Read errors bottom-up, print values, test AI code
- `try` / `except ValueError`: catch instead of crashing

Warm-up: lectures 7 and 8 in one program

```
def count_votes(votes):
    tally = {}
    for v in votes:
        tally[v] = tally.get(v, 0) + 1
    return tally
votes = ["tea", "tea", "cola", "tea"]
result = count_votes(votes)
print(result)
print(result["tea"])
print(result.get("beer", 0))
```

Warm-up: lectures 7 and 8 in one program

```python
def count_votes(votes):
    tally = {}
    for v in votes:
        tally[v] = tally.get(v, 0) + 1
    return tally
votes = ["tea", "tea", "cola", "tea"]
result = count_votes(votes)
print(result)
print(result["tea"])
print(result.get("beer", 0))
```

OUTPUT

```
{'tea': 3, 'cola': 1}
3
0
```

Quick check: predict the output

```
def to_number(text, default=0):
    try:
        return int(text)
    except ValueError:
        return default

print(to_number("42"))
print(to_number("4.5"))
print(to_number("hi", -1))
```

Quick check: predict the output

```python
def to_number(text, default=0):
    try:
        return int(text)
    except ValueError:
        return default

print(to_number("42"))
print(to_number("4.5"))
print(to_number("hi", -1))
```

OUTPUT

```
42
0
-1
```

Quick check: predict the output

```python
def to_number(text, default=0):
    try:
        return int(text)
    except ValueError:
        return default

print(to_number("42"))
print(to_number("4.5"))
print(to_number("hi", -1))
```

OUTPUT

```
42
0
-1
```

- `int("42")` works, so it returns 42
- `int("4.5")` raises `ValueError`: the default 0 comes back
- `-1` replaces the default for `"hi"`

Your coffee habit, in numbers

- 40 coffee orders this month
- Each order has a drink, a size, a price: one *thing*

Your coffee habit, in numbers

- 40 coffee orders this month
- Each order has a drink, a size, a price: one *thing*
- Add VAT to every price?

Your coffee habit, in numbers

- 40 coffee orders this month
- Each order has a drink, a size, a price: one *thing*
- Add VAT to every price?
- Average price? Most popular drink?

Your coffee habit, in numbers

- 40 coffee orders this month
- Each order has a drink, a size, a price: one *thing*
- Add VAT to every price?
- Average price? Most popular drink?
- And wait: is this cat **also** just numbers?







Today's plan

◎ By the end of today you can...

- Build your own type of object with a `class`
- Do math on many numbers at once with NumPy
- Edit a photo by changing its numbers
- Load a table with Pandas and ask it questions



Today's outline

1 Objects and classes
Every value is an object; build your own: `class`, `__init__`, `self`, methods

2 Libraries & NumPy
`import`, arrays, math on everything at once, filters, statistics, 2-D arrays

3 An image is just numbers
A photo as an array of pixels; filters are just math

4 Pandas: tables in Python
DataFrames, reading CSV files, columns, filtering rows, counting



Every topic: examples, **Try it!** and **Predict the output**. At the end: **Bug Zoo**, **AI Corner**, **Recap**.

Why today matters

Why learn this?

- Classes keep data and actions together. Every library is built from them
- Real data has thousands of rows. Loops are slow, NumPy is fast
- Pandas is Excel with superpowers, and it never crashes on big files

Where you will see it

- Research data in every faculty
- Finance, marketing, sports statistics
- Phone camera filters





Topic 1

Objects and classes

Lecture 9 • Objects, NumPy & Pandas



TODAY

1 **Objects and classes**

2 Libraries & NumPy

3 An image is just numbers

4 Pandas: tables in Python

Every value is an object

```
print(type(5))
print(type("hi"))
print(type([1, 2]))
print(type({"tea": 8}))
```

Every value is an object

```
print(type(5))
print(type("hi"))
print(type([1, 2]))
print(type({"tea": 8}))
```

OUTPUT

```
<class 'int'>
<class 'str'>
<class 'list'>
<class 'dict'>
```

- Remember `type()` from Lecture 2?

Every value is an object

```
print(type(5))
print(type("hi"))
print(type([1, 2]))
print(type({"tea": 8}))
```

OUTPUT

```
<class 'int'>
<class 'str'>
<class 'list'>
<class 'dict'>
```

- Remember `type()` from Lecture 2?
- A **class** = a type, a kind of thing
- An **object** = one value of that type

Every value is an object

```
print(type(5))
print(type("hi"))
print(type([1, 2]))
print(type({"tea": 8}))
```

OUTPUT

```
<class 'int'>
<class 'str'>
<class 'list'>
<class 'dict'>
```

- Remember `type()` from Lecture 2?
- A **class** = a type, a kind of thing
- An **object** = one value of that type
- `5` and `7` are two objects of class `int`



Things have data and actions

Your phone is an object

Data: contacts, battery level
Actions: call, take a photo




Things have data and actions

Your phone is an object

Data: contacts, battery level
Actions: call, take a photo

- Data that belongs to an object = an **attribute**
- An action that belongs to an object = a **method**



Things have data and actions

Your phone is an object

Data: contacts, battery level
Actions: call, take a photo

- Data that belongs to an object = an **attribute**
- An action that belongs to an object = a **method**
- In Python: `thing.data` and `thing.action()`



You have used methods all along

```
cart = ["milk", "eggs"]
cart.append("pita")
print(cart)

name = "dana"
print(name.upper())

menu = {"tea": 8}
print(menu.get("cake", 0))
```

You have used methods all along

```
cart = ["milk", "eggs"]
cart.append("pita")
print(cart)

name = "dana"
print(name.upper())

menu = {"tea": 8}
print(menu.get("cake", 0))
```

OUTPUT

```
['milk', 'eggs',
'pita']
DANA
0
```

You have used methods all along

```
cart = ["milk", "eggs"]
cart.append("pita")
print(cart)

name = "dana"
print(name.upper())

menu = {"tea": 8}
print(menu.get("cake", 0))
```

OUTPUT

```
['milk', 'eggs',
'pita']
DANA
0
```

Each class comes with its own methods: a list can append, a string can upper.

Today: build your own class.

Why build your own?

Two points on a map, with what we know:

```
x1 = 0
y1 = 0
x2 = 3
y2 = 4

home = {"x": 0, "y": 0}
work = {"x": 3, "y": 4}
```

Why build your own?

Two points on a map, with what we know:

```
x1 = 0
y1 = 0
x2 = 3
y2 = 4

home = {"x": 0, "y": 0}
work = {"x": 3, "y": 4}
```

- Four loose variables: easy to mix up

Why build your own?

Two points on a map, with what we know:

```
x1 = 0
y1 = 0
x2 = 3
y2 = 4

home = {"x": 0, "y": 0}
work = {"x": 3, "y": 4}
```

- Four loose variables: easy to mix up
- Dictionaries: better, but `home["x"]` is long, and the actions live somewhere else

Why build your own?

Two points on a map, with what we know:

```
x1 = 0
y1 = 0
x2 = 3
y2 = 4

home = {"x": 0, "y": 0}
work = {"x": 3, "y": 4}
```

- Four loose variables: easy to mix up
- Dictionaries: better, but `home["x"]` is long, and the actions live somewhere else
- A **class**: data *and* actions in one box

A class is a **cookie cutter**. Each object is one cookie: same shape, its own toppings.



`class Point`: your own type

```
class Point:
    def __init__(self, x, y):
        self.x = x
        self.y = y

p = Point(3, 4)
print(p.x, p.y)
print(type(p))
```

`class Point`: your own type

```
class Point:
    def __init__(self, x, y):
        self.x = x
        self.y = y

p = Point(3, 4)
print(p.x, p.y)
print(type(p))
```

OUTPUT

```
3 4
<class '__main__.Point'>
```

`class Point`: your own type

```
class Point:
    def __init__(self, x, y):
        self.x = x
        self.y = y

p = Point(3, 4)
print(p.x, p.y)
print(type(p))
```

OUTPUT

```
3 4
<class '__main__.Point'>
```

- `class Point`: the cookie cutter. Class names start with a capital letter

`class Point`: your own type

```
class Point:
    def __init__(self, x, y):
        self.x = x
        self.y = y

p = Point(3, 4)
print(p.x, p.y)
print(type(p))
```

OUTPUT

```
3 4
<class '__main__.Point'>
```

- `class Point`: the cookie cutter. Class names start with a capital letter
- `Point(3, 4)` makes a new object. Python runs `__init__` (“init” = start)

`class Point`: your own type

```
class Point:
    def __init__(self, x, y):
        self.x = x
        self.y = y

p = Point(3, 4)
print(p.x, p.y)
print(type(p))
```

OUTPUT

```
3 4
<class '__main__.Point'>
```

- **`class Point`**: the cookie cutter. Class names start with a capital letter
- `Point(3, 4)` makes a new object. Python runs `__init__` (“init” = start)
- `self` = “this object”. `self.x = x` stores `x` *inside* it

Add a method: a function inside the class

```
class Point:
    def __init__(self, x, y):
        self.x = x
        self.y = y

    def distance_to(self, other):
        dx = self.x - other.x
        dy = self.y - other.y
        return (dx ** 2 + dy ** 2) ** 0.5

home = Point(0, 0)
work = Point(3, 4)
print(home.distance_to(work))
```

Add a method: a function inside the class

```
class Point:
    def __init__(self, x, y):
        self.x = x
        self.y = y

    def distance_to(self, other):
        dx = self.x - other.x
        dy = self.y - other.y
        return (dx ** 2 + dy ** 2) ** 0.5

home = Point(0, 0)
work = Point(3, 4)
print(home.distance_to(work))
```

OUTPUT

```
5.0
```

Add a method: a function inside the class

```
class Point:
    def __init__(self, x, y):
        self.x = x
        self.y = y

    def distance_to(self, other):
        dx = self.x - other.x
        dy = self.y - other.y
        return (dx ** 2 + dy ** 2) ** 0.5

home = Point(0, 0)
work = Point(3, 4)
print(home.distance_to(work))
```

OUTPUT

```
5.0
```

- A method is a **def** (Lecture 7) inside a class. First parameter: `self`

Add a method: a function inside the class

```python
class Point:
    def __init__(self, x, y):
        self.x = x
        self.y = y

    def distance_to(self, other):
        dx = self.x - other.x
        dy = self.y - other.y
        return (dx ** 2 + dy ** 2) ** 0.5

home = Point(0, 0)
work = Point(3, 4)
print(home.distance_to(work))
```

OUTPUT

```
5.0
```

- A method is a **def** (Lecture 7) inside a class. First parameter: `self`
- In `home.distance_to(work)`, `self` is `home`

Joke break: a very realistic cat

```
class Cat:
    def __init__(self, name):
        self.name = name

    def come_here(self):
        return self.name + " ignores you."

luna = Cat("Luna")
print(luna.come_here())
```

Joke break: a very realistic cat

```python
class Cat:
    def __init__(self, name):
        self.name = name

    def come_here(self):
        return self.name + " ignores you."

luna = Cat("Luna")
print(luna.come_here())
```

OUTPUT

```
Luna ignores you.
```



The method works exactly as designed.

Every cat owner: “realistic.”

Biology: a dish of bacteria

```
class Culture:
    def __init__(self, name, cells):
        self.name = name
        self.cells = cells

    def grow(self, hours):
        for hour in range(hours):
            self.cells = self.cells * 2

    def report(self):
        print(f"{self.name}: {self.cells} cells")
```

```
dish = Culture("E. coli", 100)
dish.report()
dish.grow(3)
dish.report()
```

Biology: a dish of bacteria

```
class Culture:
    def __init__(self, name, cells):
        self.name = name
        self.cells = cells

    def grow(self, hours):
        for hour in range(hours):
            self.cells = self.cells * 2

    def report(self):
        print(f"{self.name}: {self.cells} cells")
```

```
dish = Culture("E. coli", 100)
dish.report()
dish.grow(3)
dish.report()
```

OUTPUT

```
E. coli: 100 cells
E. coli: 800 cells
```

Biology: a dish of bacteria

```
class Culture:
    def __init__(self, name, cells):
        self.name = name
        self.cells = cells

    def grow(self, hours):
        for hour in range(hours):
            self.cells = self.cells * 2

    def report(self):
        print(f"{self.name}: {self.cells} cells")
```

```
dish = Culture("E. coli", 100)
dish.report()
dish.grow(3)
dish.report()
```

OUTPUT

```
E. coli: 100 cells
E. coli: 800 cells
```

A method can **change** the data: `grow` doubles `self.cells`.

Toy model: cells double every hour. 

Money: a bank account in ILS

```python
class BankAccount:
    def __init__(self, owner):
        self.owner = owner
        self.balance = 0

    def deposit(self, amount):
        self.balance = self.balance + amount

    def withdraw(self, amount):
        if amount > self.balance:
            print("Not enough money!")
        else:
            self.balance = self.balance - amount
```

```python
account = BankAccount("Noa")
account.deposit(500)
account.withdraw(800)
account.withdraw(200)
print(account.owner,
      account.balance, "ILS")
```

Money: a bank account in ILS

```python
class BankAccount:
    def __init__(self, owner):
        self.owner = owner
        self.balance = 0

    def deposit(self, amount):
        self.balance = self.balance + amount

    def withdraw(self, amount):
        if amount > self.balance:
            print("Not enough money!")
        else:
            self.balance = self.balance - amount
```

```python
account = BankAccount("Noa")
account.deposit(500)
account.withdraw(800)
account.withdraw(200)
print(account.owner,
      account.balance, "ILS")
```

OUTPUT

```
Not enough money!
Noa 300 ILS
```

Money: a bank account in ILS

```python
class BankAccount:
    def __init__(self, owner):
        self.owner = owner
        self.balance = 0

    def deposit(self, amount):
        self.balance = self.balance + amount

    def withdraw(self, amount):
        if amount > self.balance:
            print("Not enough money!")
        else:
            self.balance = self.balance - amount
```

```python
account = BankAccount("Noa")
account.deposit(500)
account.withdraw(800)
account.withdraw(200)
print(account.owner,
      account.balance, "ILS")
```

OUTPUT

```
Not enough money!
Noa 300 ILS
```

`balance` starts at 0: not every attribute is a parameter. The rule "no negative balance" lives **inside** the class.

Try it!

Try it in Colab notebooks/L09/L09_00_objects_and_classes.ipynb

1. Make two points and print the distance between them
2. Add a method `report()` to `BankAccount`
3. Write a class `Student`: a name, a list of grades, and a method `average()`




Predict the output: two dishes

Predict the output!

```
a = Culture("Yeast", 10)
b = Culture("Yeast", 10)
a.grow(2)
print(a.cells, b.cells)
```

The `Culture` class from two slides back.



Predict the output: two dishes

Predict the output!

```
a = Culture("Yeast", 10)
b = Culture("Yeast", 10)
a.grow(2)
print(a.cells, b.cells)
```

The `Culture` class from two slides back.

Answer

`40 10`

`a` grew twice: $10 \to 20 \to 40$.
`b` is a different object with its own `cells`. It did not change.



Topic 2

Libraries & NumPy

Lecture 9 • Objects, NumPy & Pandas



TODAY

1 Objects and classes


2 **Libraries & NumPy**

3 An image is just numbers

4 Pandas: tables in Python

Libraries: an app store for code

- Someone already wrote the hard parts
- A **library** = ready-made tools
- You **import** it, then use it
- Colab already has them installed



import: open the toolbox

L09_01_numpy_basics.ipynb

```
import numpy as np

print(np.sqrt(16))
print(np.pi)
```

import: open the toolbox

L09_01_numpy_basics.ipynb

```
import numpy as np

print(np.sqrt(16))
print(np.pi)
```

OUTPUT

```
4.0
3.141592653589793
```

import: open the toolbox

L09_01_numpy_basics.ipynb

```
import numpy as np

print(np.sqrt(16))
print(np.pi)
```

OUTPUT

```
4.0
3.141592653589793
```

- `as np` gives NumPy a short nickname
- `np.sqrt` means: the `sqrt` tool *from* NumPy

Meet the array

```
import numpy as np

prices = np.array([12, 15, 9, 20])
print(prices)
print(len(prices))
print(prices[0])
```



An **array** is a list built for math.

No commas when printed. Same indexes as lists.

Meet the array

```python
import numpy as np

prices = np.array([12, 15, 9, 20])
print(prices)
print(len(prices))
print(prices[0])
```

OUTPUT

```
[12 15  9 20]
4
12
```



An **array** is a list built for math.

No commas when printed. Same indexes as lists.

List vs array: same look, different powers

```
import numpy as np

prices_list = [12, 15, 9, 20]
prices = np.array([12, 15, 9, 20])
print(prices_list * 2)
print(prices * 2)
```

List vs array: same look, different powers

```
import numpy as np

prices_list = [12, 15, 9, 20]
prices = np.array([12, 15, 9, 20])
print(prices_list * 2)
print(prices * 2)
```

OUTPUT

```
[12, 15, 9, 20, 12, 15, 9, 20]
[24 30 18 40]
```

List vs array: same look, different powers

```
import numpy as np

prices_list = [12, 15, 9, 20]
prices = np.array([12, 15, 9, 20])
print(prices_list * 2)
print(prices * 2)
```

OUTPUT

```
[12, 15, 9, 20, 12, 15, 9, 20]
[24 30 18 40]
```

List `* 2`: **repeat** the list. Array `* 2`: **double every number**.

Add 18% VAT to every price

The L06 way: a loop

```
prices_list = [12, 15, 9, 20]
with_vat = []
for price in prices_list:
    with_vat.append(price * 1.18)
```

The NumPy way: one line

```
import numpy as np

prices = np.array([12, 15, 9, 20])
with_vat = prices * 1.18
print(with_vat)
```

Add 18% VAT to every price

The L06 way: a loop

```
prices_list = [12, 15, 9, 20]
with_vat = []
for price in prices_list:
    with_vat.append(price * 1.18)
```

The NumPy way: one line

```
import numpy as np

prices = np.array([12, 15, 9, 20])
with_vat = prices * 1.18
print(with_vat)
```

OUTPUT

```
[14.16 17.7  10.62 23.6 ]
```

Add 18% VAT to every price

The L06 way: a loop

```
prices_list = [12, 15, 9, 20]
with_vat = []
for price in prices_list:
    with_vat.append(price * 1.18)
```

The NumPy way: one line

```
import numpy as np

prices = np.array([12, 15, 9, 20])
with_vat = prices * 1.18
print(with_vat)
```

OUTPUT

```
[14.16 17.7  10.62 23.6 ]
```

Math on the whole array = math on every item.

Two arrays, item by item

```
import numpy as np

homework = np.array([90, 80, 100, 70])
exam = np.array([70, 85, 60, 95])

final = 0.3 * homework + 0.7 * exam
print(final)
```



Four students' final grades.
Item 1 with item 1, item 2 with item 2…

Two arrays, item by item

```
import numpy as np

homework = np.array([90, 80, 100, 70])
exam = np.array([70, 85, 60, 95])

final = 0.3 * homework + 0.7 * exam
print(final)
```

OUTPUT

```
[76.  83.5 72.  87.5]
```



Four students' final grades.
Item 1 with item 1, item 2 with item 2…

Ask the array a question

```
import numpy as np

prices = np.array([12, 15, 9, 20])
print(prices > 12)
print(prices[prices > 12])
```

Ask the array a question

```python
import numpy as np

prices = np.array([12, 15, 9, 20])
print(prices > 12)
print(prices[prices > 12])
```

OUTPUT

```
[False  True False  True]
[15 20]
```

Ask the array a question

```python
import numpy as np

prices = np.array([12, 15, 9, 20])
print(prices > 12)
print(prices[prices > 12])
```

OUTPUT

```
[False  True False  True]
[15 20]
```

- `prices > 12` asks *every* price: True or False?

Ask the array a question

```python
import numpy as np

prices = np.array([12, 15, 9, 20])
print(prices > 12)
print(prices[prices > 12])
```

OUTPUT

```
[False  True False  True]
[15 20]
```

- `prices > 12` asks *every* price: True or False?
- `prices[...]` keeps only the `True` ones

Statistics in one word each

```python
import numpy as np

grades = np.array([55, 70, 88, 92, 100])
print(np.mean(grades))
print(np.median(grades))
print(np.percentile(grades, 90))
print(np.max(grades))
```

Statistics in one word each

```python
import numpy as np

grades = np.array([55, 70, 88, 92, 100])
print(np.mean(grades))
print(np.median(grades))
print(np.percentile(grades, 90))
print(np.max(grades))
```

OUTPUT

```
81.0
88.0
96.8
100
```

Statistics in one word each

```python
import numpy as np

grades = np.array([55, 70, 88, 92, 100])
print(np.mean(grades))
print(np.median(grades))
print(np.percentile(grades, 90))
print(np.max(grades))
```

OUTPUT

```
81.0
88.0
96.8
100
```



Remember the median **by hand** in L08? Now it is one line.

`percentile(grades, 90)`: 90% of grades are below this.

A 2-D array is a table

	Test 1	Test 2	Test 3	Test 4
Dana	90	80	70	60
Omer	60	75	85	100
Noa	90	100	85	89

- Rows: students
- Columns: tests

(counting from 0, as always)


A 2-D array is a table

	Test 1	Test 2	Test 3	Test 4
Dana	90	80	70	60
Omer	60	75	85	100
Noa	90	100	85	89

- Rows: students
- Columns: tests
- Row 1, column 2 is **85**

(counting from 0, as always)

A 2-D array is a table



- Rows: students
- Columns: tests
- Row 1, column 2 is **85**

(counting from 0, as always)

2-D arrays in code

```
import numpy as np

grades = np.array([[90, 80, 70, 60],
                   [60, 75, 85, 100],
                   [90, 100, 85, 89]])
print(grades.shape)
print(grades[1, 2])
print(grades.max())
```

2-D arrays in code

```python
import numpy as np

grades = np.array([[90, 80, 70, 60],
                   [60, 75, 85, 100],
                   [90, 100, 85, 89]])
print(grades.shape)
print(grades[1, 2])
print(grades.max())
```

OUTPUT

```
(3, 4)
85
100
```

2-D arrays in code

```python
import numpy as np

grades = np.array([[90, 80, 70, 60],
                   [60, 75, 85, 100],
                   [90, 100, 85, 89]])
print(grades.shape)
print(grades[1, 2])
print(grades.max())
```

OUTPUT

```
(3, 4)
85
100
```

- shape: (rows, columns)
- `grades[row, col]`

Average per student, average per test

```
import numpy as np

grades = np.array([[90, 80, 70, 60],
                   [60, 75, 85, 100],
                   [90, 100, 85, 89]])
print(grades.mean(axis=1))   # each student (row)
print(grades.mean(axis=0))   # each test (column)
```

Average per student, average per test

```python
import numpy as np

grades = np.array([[90, 80, 70, 60],
                   [60, 75, 85, 100],
                   [90, 100, 85, 89]])
print(grades.mean(axis=1))   # each student (row)
print(grades.mean(axis=0))   # each test (column)
```

OUTPUT

```
[75. 80. 91.]
[80. 85. 80. 83.]
```

Average per student, average per test

```python
import numpy as np

grades = np.array([[90, 80, 70, 60],
                   [60, 75, 85, 100],
                   [90, 100, 85, 89]])
print(grades.mean(axis=1))   # each student (row)
print(grades.mean(axis=0))   # each test (column)
```

OUTPUT

```
[75. 80. 91.]
[80. 85. 80. 83.]
```

Dana 75, Omer 80, Noa 91. Test 2 was the easiest (85).

An array is an object too

```
import numpy as np

grades = np.array([55, 70, 88, 92, 100])
print(type(grades))
print(grades.shape)
print(grades.mean())
```

An array is an object too

```python
import numpy as np

grades = np.array([55, 70, 88, 92, 100])
print(type(grades))
print(grades.shape)
print(grades.mean())
```

OUTPUT

```
<class 'numpy.ndarray'>
(5,)
81.0
```

An array is an object too

```python
import numpy as np

grades = np.array([55, 70, 88, 92, 100])
print(type(grades))
print(grades.shape)
print(grades.mean())
```

OUTPUT

```
<class 'numpy.ndarray'>
(5,)
81.0
```

- Someone wrote `class ndarray`, just like our `Point`

An array is an object too

```python
import numpy as np

grades = np.array([55, 70, 88, 92, 100])
print(type(grades))
print(grades.shape)
print(grades.mean())
```

OUTPUT

```
<class 'numpy.ndarray'>
(5,)
81.0
```

- Someone wrote `class ndarray`, just like our `Point`
- `grades.shape`: an **attribute** (data), no `()`
- `grades.mean()`: a **method** (action), with `()`

An array is an object too

```python
import numpy as np

grades = np.array([55, 70, 88, 92, 100])
print(type(grades))
print(grades.shape)
print(grades.mean())
```

OUTPUT

```
<class 'numpy.ndarray'>
(5,)
81.0
```

- Someone wrote `class ndarray`, just like our `Point`
- `grades.shape`: an **attribute** (data), no `()`
- `grades.mean()`: a **method** (action), with `()`
- Pandas tables and AI models (Lecture 10) are objects too

Try it!

Try it in Colab notebooks/L09/L09_01_numpy_basics.ipynb

1. Make an array of 5 coffee prices you paid this week
2. Add 18% VAT to all of them in one line
3. Which prices are above 15? Keep only those
4. Print the mean and the median





Predict the output

Predict the output!

```
import numpy as np

a = np.array([10, 20, 30, 40])
print(a[a > 15] - 10)
```



Predict the output

Predict the output!

```
import numpy as np

a = np.array([10, 20, 30, 40])
print(a[a > 15] - 10)
```

Answer

```
[10 20 30]
```

Keep 20, 30, 40. Then subtract 10 from each.



Topic 3

An image is just numbers

Lecture 9 • Objects, NumPy & Pandas



TODAY


1 Objects and classes

2 Libraries & NumPy

3 An image is just numbers

4 Pandas: tables in Python


Zoom in on a photo



Zoom in enough: tiny squares called **pixels**. Each one is a **number**.

0 = black, 255 = white, in between = gray

Color = three numbers per pixel



- Every pixel: **R**ed, **G**reen, **B**lue
- Each from 0 (none) to 255 (full)

`[255 0 0]` red

`[255 255 0]` yellow

`[255 255 255]` white

`[167 119 73]` the cat's fur

Load a real photo: Chelsea the cat

L09_02_cat_filters.ipynb

```
from skimage import data

cat = data.chelsea()
print(cat.shape)
print(cat[150, 170])
```

`skimage` = scikit-image, a library of photo tools with sample images

Load a real photo: Chelsea the cat

L09_02_cat_filters.ipynb

```
from skimage import data

cat = data.chelsea()
print(cat.shape)
print(cat[150, 170])
```

OUTPUT

```
(300, 451, 3)
[167 119  73]
```

`skimage` = scikit-image, a library of photo tools with sample images

Load a real photo: Chelsea the cat

L09_02_cat_filters.ipynb

```
from skimage import data

cat = data.chelsea()
print(cat.shape)
print(cat[150, 170])
```

OUTPUT

```
(300, 451, 3)
[167 119  73]
```

- 300 rows of pixels
- 451 columns
- 3 colors per pixel

`skimage` = scikit-image, a library of photo tools with sample images

Load a real photo: Chelsea the cat

L09_02_cat_filters.ipynb

```
from skimage import data

cat = data.chelsea()
print(cat.shape)
print(cat[150, 170])
```

OUTPUT

```
(300, 451, 3)
[167 119  73]
```

- 300 rows of pixels
- 451 columns
- 3 colors per pixel
- One pixel: lots of red, less green, little blue

`skimage` = scikit-image, a library of photo tools with sample images

Show the array as a picture

```
from skimage import data
import matplotlib.pyplot as plt

cat = data.chelsea()
plt.imshow(cat)
plt.show()
```

`plt.imshow`: “show this array as an image”.

Matplotlib gets a full tour next week.

Show the array as a picture

```
from skimage import data
import matplotlib.pyplot as plt

cat = data.chelsea()
plt.imshow(cat)
plt.show()
```



`plt.imshow`: “show this array as an image”.

Matplotlib gets a full tour next week.

Filter 1: invert the colors

```
from skimage import data
import matplotlib.pyplot as plt

cat = data.chelsea()
inverted = 255 - cat
plt.imshow(inverted)
plt.show()
```



`255 - cat` changes **every** number:
dark becomes light, light becomes dark.

Filter 1: invert the colors

```
from skimage import data
import matplotlib.pyplot as plt

cat = data.chelsea()
inverted = 255 - cat
plt.imshow(inverted)
plt.show()
```

`255 - cat` changes **every** number:
dark becomes light, light becomes dark.





Filter 2: crop with slicing

```
from skimage import data
import matplotlib.pyplot as plt

cat = data.chelsea()
eyes = cat[70:210, 110:350]
print(eyes.shape)
plt.imshow(eyes)
plt.show()
```

Rows 70 to 210, columns 110 to 350.

Slicing from L05, now in 2-D!


Filter 2: crop with slicing

```
from skimage import data
import matplotlib.pyplot as plt

cat = data.chelsea()
eyes = cat[70:210, 110:350]
print(eyes.shape)
plt.imshow(eyes)
plt.show()
```

OUTPUT

```
(140, 240, 3)
```



Rows 70 to 210, columns 110 to 350.

Slicing from L05, now in 2-D!

Filter 3: black and white

```
from skimage import data
import matplotlib.pyplot as plt

cat = data.chelsea()
gray = cat.mean(axis=2)
print(gray.shape)
plt.imshow(gray, cmap="gray")
plt.show()
```

Average of R, G, B for every pixel.

`axis=2`: the color direction.

Filter 3: black and white

```
from skimage import data
import matplotlib.pyplot as plt

cat = data.chelsea()
gray = cat.mean(axis=2)
print(gray.shape)
plt.imshow(gray, cmap="gray")
plt.show()
```

OUTPUT

```
(300, 451)
```



Average of R, G, B for every pixel.
`axis=2`: the color direction.

Photo filters are just math




`cat[::-1]`

upside down



`cat[:, ::-1]`

mirror



`cat // 2`

darker



`gray > 100`

pure black & white

- Step `-1` reverses, just like in L05
- Phone filters, medical scans, self-driving cars: all pixel math



Try it!

Try it in Colab notebooks/L09/L09_02_cat_filters.ipynb

1. Crop the cat's nose: rows 220 to 300, columns 230 to 330
2. Make it upside down **and** inverted
3. Change `gray > 100` to 50, then 150. What happens?
4. Bonus: upload your own photo and try the same filters




Predict the output

Predict the output!

```
from skimage import data

cat = data.chelsea()
small = cat[0:100, 0:50]
print(small.shape)
```



Predict the output

Predict the output!

```
from skimage import data

cat = data.chelsea()
small = cat[0:100, 0:50]
print(small.shape)
```

Answer

`(100, 50, 3)`

100 rows, 50 columns, still 3 colors.



Topic 4

Pandas: tables in Python

Lecture 9 • Objects, NumPy & Pandas



TODAY

1 Objects and classes

2 Libraries & NumPy

3 An image is just numbers

4 **Pandas: tables in Python**

Pandas = a spreadsheet inside Python

- A **DataFrame** is a table
- Each **column** has a name
- Each **row** is one record (one order)
- Like Excel, but you ask with code

	drink	price
0	Latte	16
1	Tea	8
2	Mocha	18





A DataFrame from a dictionary

L09_03_coffee_pandas.ipynb

```
import pandas as pd

menu = {"drink": ["Latte", "Tea", "Mocha"],
        "price": [16, 8, 18]}
df = pd.DataFrame(menu)
print(df)
```

A DataFrame from a dictionary

L09_03_coffee_pandas.ipynb

```
import pandas as pd

menu = {"drink": ["Latte", "Tea", "Mocha"],
        "price": [16, 8, 18]}
df = pd.DataFrame(menu)
print(df)
```

OUTPUT

```
    drink  price
0  Latte     16
1    Tea      8
2  Mocha     18
```

A DataFrame from a dictionary

L09_03_coffee_pandas.ipynb

```python
import pandas as pd

menu = {"drink": ["Latte", "Tea", "Mocha"],
        "price": [16, 8, 18]}
df = pd.DataFrame(menu)
print(df)
```

OUTPUT

```
    drink  price
0  Latte     16
1    Tea      8
2  Mocha     18
```

- Dictionary keys become **column names**
- The numbers on the left are row numbers (the **index**)

Real data lives in CSV files

coffee_orders.csv

```
day,drink,size,price,rating
Sun,Cappuccino,S,13,5
Sun,Espresso,S,9,5
Sun,Latte,L,18,3
...
```

- CSV = **C**omma-**S**eparated **V**alues
- A plain text file; commas split the columns
- Excel and Google Sheets can save as CSV

Today's data

40 orders from a campus café. **Made-up data**, created for this course.

Read the CSV, peek at the top

```
import pandas as pd
df = pd.read_csv("coffee_orders.csv")
print(df.head())
```

Read the CSV, peek at the top

```python
import pandas as pd
df = pd.read_csv("coffee_orders.csv")
print(df.head())
```

OUTPUT

```
   day       drink size  price  rating
0  Sun  Cappuccino    S     13       5
1  Sun    Espresso    S      9       5
2  Sun       Latte    L     18       3
3  Sun         Tea    S      8       2
4  Sun       Latte    M     16       3
```

Read the CSV, peek at the top

```python
import pandas as pd
df = pd.read_csv("coffee_orders.csv")
print(df.head())
```

- `head()`: the first 5 rows
- In Colab: upload the file first (folder icon, left side)

OUTPUT

```
   day       drink size  price  rating
0  Sun  Cappuccino    S     13       5
1  Sun    Espresso    S      9       5
2  Sun       Latte    L     18       3
3  Sun         Tea    S      8       2
4  Sun       Latte    M     16       3
```

One column = one array of numbers

```python
import pandas as pd

df = pd.read_csv("coffee_orders.csv")
print(df["price"].sum())
print(df["price"].mean())
print(df["price"].median())
print(df["price"].quantile(0.9))
```

One column = one array of numbers

```python
import pandas as pd

df = pd.read_csv("coffee_orders.csv")
print(df["price"].sum())
print(df["price"].mean())
print(df["price"].median())
print(df["price"].quantile(0.9))
```

OUTPUT

```
538
13.45
14.0
18.1
```

One column = one array of numbers

```python
import pandas as pd

df = pd.read_csv("coffee_orders.csv")
print(df["price"].sum())
print(df["price"].mean())
print(df["price"].median())
print(df["price"].quantile(0.9))
```

OUTPUT

```
538
13.45
14.0
18.1
```

Total spent: 538 ILS.
Average order: 13.45 ILS.

`df["price"]` picks one column, like a dictionary key.

Filter rows: only the lattes

```python
import pandas as pd

df = pd.read_csv("coffee_orders.csv")
lattes = df[df["drink"] == "Latte"]
print(len(lattes))
print(round(lattes["price"].mean(), 2))
```



Same trick as `prices[prices > 12]`: a True/False question for every row.

Filter rows: only the lattes

```python
import pandas as pd

df = pd.read_csv("coffee_orders.csv")
lattes = df[df["drink"] == "Latte"]
print(len(lattes))
print(round(lattes["price"].mean(), 2))
```

OUTPUT

```
14
16.14
```



Same trick as `prices[prices > 12]`: a True/False question for every row.

Filter rows: the expensive orders

```python
import pandas as pd

df = pd.read_csv("coffee_orders.csv")
expensive = df[df["price"] >= 19]
print(expensive)
```



Filter rows: the expensive orders

```python
import pandas as pd

df = pd.read_csv("coffee_orders.csv")
expensive = df[df["price"] >= 19]
print(expensive)
```



OUTPUT

```
    day        drink size  price  rating
24  Wed  Iced coffee    L     19       4
30  Wed  Iced coffee    L     19       3
34  Thu  Iced coffee    L     19       5
38  Thu  Iced coffee    L     19       5
```

Filter rows: the expensive orders

```python
import pandas as pd

df = pd.read_csv("coffee_orders.csv")
expensive = df[df["price"] >= 19]
print(expensive)
```



All four: large iced coffee.
Rows keep their numbers.

OUTPUT

```
    day        drink size  price  rating
24  Wed  Iced coffee    L     19       4
30  Wed  Iced coffee    L     19       3
34  Thu  Iced coffee    L     19       5
38  Thu  Iced coffee    L     19       5
```

Which drink is the most popular?

```python
import pandas as pd

df = pd.read_csv("coffee_orders.csv")
print(df["drink"].value_counts())
```



Counts each value, biggest first.
Like the word counter from L08.

Which drink is the most popular?

```python
import pandas as pd

df = pd.read_csv("coffee_orders.csv")
print(df["drink"].value_counts())
```

OUTPUT

```
drink
Latte          14
Espresso       10
Tea             6
Cappuccino      5
Iced coffee     5
Name: count, dtype: int64
```



Counts each value, biggest first.
Like the word counter from L08.

describe(): the whole summary at once

```python
import pandas as pd

df = pd.read_csv("coffee_orders.csv")
print(df.describe())
```

describe(): the whole summary at once

```python
import pandas as pd

df = pd.read_csv("coffee_orders.csv")
print(df.describe())
```

OUTPUT

	price	rating
count	40.000000	40.00000
mean	13.450000	3.82500
std	3.908898	0.98417
min	8.000000	2.00000
25%	9.000000	3.00000
50%	14.000000	4.00000
75%	17.000000	5.00000
max	19.000000	5.00000

describe(): the whole summary at once

```python
import pandas as pd

df = pd.read_csv("coffee_orders.csv")
print(df.describe())
```

OUTPUT

	price	rating
count	40.000000	40.00000
mean	13.450000	3.82500
std	3.908898	0.98417
min	8.000000	2.00000
25%	9.000000	3.00000
50%	14.000000	4.00000
75%	17.000000	5.00000
max	19.000000	5.00000

- `std`: how spread out the values are
- `25%`, `50%`, `75%`: quantiles

Try it!

Try it in Colab notebooks/L09/L09_03_coffee_pandas.ipynb

1. Load `coffee_orders.csv` and print `head()`
2. How many orders were on Wednesday?
3. What is the average `rating` of Tea?
4. Which day had the most orders? (try `value_counts`)




Predict the output

Predict the output!

```
import pandas as pd
menu = {"drink": ["Latte", "Tea", "Mocha"],
        "price": [16, 8, 18]}
df = pd.DataFrame(menu)
cheap = df[df["price"] < 17]
print(len(cheap))
print(cheap["price"].mean())
```

Predict the output

Predict the output!

```
import pandas as pd
menu = {"drink": ["Latte", "Tea", "Mocha"],
        "price": [16, 8, 18]}
df = pd.DataFrame(menu)
cheap = df[df["price"] < 17]
print(len(cheap))
print(cheap["price"].mean())
```

Answer

2

12.0

Latte (16) and Tea (8) are under 17. Their average is 12.

Bug Zoo: the forgotten `self`

BUG ZOO

```
class Point:
    def __init__(self, x, y):
        x = x
        y = y

p = Point(3, 4)
print(p.x)
```

ERROR

```
AttributeError: 'Point' object
has no attribute 'x'
```

Fix: `self.x = x` stores it *in* the object

```
class Culture:
    def __init__(self, name, cells):
        self.name = name
        self.cells = cells

    def report():
        print(self.cells)

Culture("E. coli", 100).report()
```

ERROR

```
TypeError: Culture.report() takes 0
positional arguments but 1 was given
```

Fix: `def report(self):`

Bug Zoo: the forgotten import

BUG ZOO

```
prices = np.array([12, 15, 9, 20])
```

ERROR

```
NameError: name 'np' is not defined
```

Fix: run `import numpy as np` first (top cell!)

```
prices = [12, 15, 9, 20]
with_vat = prices * 1.18
```

ERROR

```
TypeError: can't multiply
sequence by non-int of
type 'float'
```

Fix: a list can't do math on items. Use `np.array(prices)`.

Bug Zoo: file and column names

BUG ZOO

```
df = pd.read_csv("coffee_order.csv")
```

ERROR

```
FileNotFoundError: [Errno 2] No such file or directory: 'coffee_order.csv'
```

Fix: check the spelling, and upload the file to Colab.

```
print(df["Price"].mean())
```

ERROR

```
KeyError: 'Price'
```

Fix: column names are exact: `"price"`. Check `df.columns`.



The intern looked for a file and a column that don't exist.

AI Corner: ask about your table


AI CORNER

A good prompt

"My Pandas table `df` has columns day, drink, size, price. How do I find the average price of each drink? Explain every line simply."

Double-check

Filter one drink and average it yourself. Same number?



Share column names, never private data.

Recap

✓ Today you learned

- A `class` is a cookie cutter: `__init__` stores data in `self`, methods are actions
- NumPy arrays do math on every item at once
- A photo is an array of numbers: edit numbers, edit photo
- Pandas reads CSV tables: filter rows, then `mean()`



Next time: pictures from data, and a taste of AI

- Turn numbers into plots with Matplotlib
- Teach the computer from examples (scikit-learn)
- Code like a pro: a real editor, a debugger, an AI assistant
- Look back at the whole course, and your final project



3D emoji: Microsoft Fluent Emoji (MIT License). Pip the snake: original drawing. Full list: images/CREDITS.md