

Punctual presentability of trees

Dariusz Kalociński

Institute of Computer Science, Polish Academy of Sciences

CSTI workshop, July 17, 2024

Computable presentability

- a countable structure with domain \mathbb{N} is computable if its relations and functions are uniformly Turing computable
[Mal'tsev, 1961, Rabin, 1960, Tennenbaum, 1959]
- \mathcal{A} is computably presentable if \mathcal{A} is isomorphic to some computable structure
- computable presentability of familiar classes of structures (e.g., linear orders, Boolean algebras, and so on) has been studied extensively
- we want to go below computable

Subrecursive model theory

- algebraic structures presented by finite state automata [Khoussainov and Nerode, 1995],
- polynomial-time algebra [Cenzer and Remmel, 1991].
- Kalimullin, Melnikov, and Ng [Kalimullin et al., 2017] initiated the systematic study of punctual presentations, that lies somewhere in the between of computability and complexity theory:

Definition ([Kalimullin et al., 2017])

A structure with domain \mathbb{N} is *punctual* (or, fully primitive recursive) if its relations and functions are uniformly primitive recursive.

- we forbid unbounded loops
- theoretical underpinning of online computation [Bazhenov et al., 2019]

Definition

A class of structures \mathcal{K} is *punctually robust* if every computable member of \mathcal{K} is punctually presentable.

In [Kalimullin et al., 2017]:

- punctually robust:
 - torsion-free abelian groups
 - Boolean algebras
 - equivalence structures
 - abelian p-groups
 - linear orders
- not punctually robust:
 - undirected graphs
 - Archimedean ordered abelian groups
 - torsion abelian groups

- the abstract concept of a tree is consistent across disciplines
- different representations of trees
- how to turn a given representation into a structure?

Trees represented as:

- 1 prefix-closed subsets of $\mathbb{N}^{<\mathbb{N}}$
- 2 (un)directed graphs
- 3 partially ordered sets
- 4 predecessor functions

sequential trees

graph-theoretic trees

partially-ordered trees

predecessor trees

SEQUENTIAL TREES

From sequential trees to structures

Definition (sequential tree)

$T \subseteq \mathbb{N}^{<\mathbb{N}}$ is a tree if for all $\alpha, \beta \in \mathbb{N}^{<\mathbb{N}}$: $\alpha \in T \wedge \beta \subset \alpha \implies \beta \in T$.



Definition (tentative)

Consider τ -structures, where $\tau = \{R_1, R_2, \dots\}$ is a relational vocabulary with R_n being n -ary, for $n > 0$. We say \mathcal{A} is a sequential tree structure if for every n , for every $x_1, \dots, x_n \in \mathcal{A}$, $R_n(x_1, \dots, x_n)$ implies $R_k(x_1, \dots, x_k)$ for $k < n$.

GRAPH-THEORETIC TREES

Definition (graph-theoretic tree)

(V, E) , where E is a binary relation, is a graph-theoretic tree if (V, E) is a connected acyclic (un)directed graph.

Theorem (essentially [Cenzer and Remmel, 1998])

The class of graph-theoretic trees is punctually robust.

Case 1: there is a node with infinitely many children

Case 2: no node has infinitely many children

PARTIALLY-ORDERED TREES

Definition (partially ordered tree)


A partial order (P, \leq) is a tree if (P, \leq) has a unique maximal element and, for every $x \in P$, $P_{\geq x}$ is a finite linear order.

Theorem (K.)


The class of partially-ordered trees is not punctually robust.

- build a computable p.o. tree $\mathcal{T} = (\mathbb{N}, \leq_{\mathcal{T}})$ such that for every $i \in \mathbb{N}$: $\mathcal{T} \not\preceq \mathcal{P}_i = (\mathbb{N}, p_i)$, where p_i is an i -th p.r. binary relation.
- \mathcal{T} will be binary and uniquely branching.
- maintain a dynamic set $F \subset \mathcal{T}$
- a node x is **closed** if for some $y \geq x$, y is in F (stage-sensitive); otherwise x is **open**
- at odd stages the tree grows through open leaves
- at even stages, the strategies for \mathcal{P}_i monitor the relationship between \mathcal{T} and \mathcal{P}_i and change open vs closed nodes to satisfy R_i

Growing the tree



Changing open vs closed nodes



PREDECESSOR TREES


Definition (predecessor tree)

Let A be a set and let $T: A \rightarrow A$. (A, T) is a *predecessor tree*, if there is a unique $r \in A$ such that $T(r) = r$, and for every $x \in A$ there exists $i \in \mathbb{N}$ such that $T^i(x) = r$. The unique r is called the root.

Theorem (MFCS '24 paper with San Mauro & Wrocławski)


The class of predecessor trees is not punctually robust.

- build a computable predecessor tree $\mathcal{T} = (\mathbb{N}, T)$ such that $\mathcal{T} \not\equiv \mathcal{P}_i = (\mathbb{N}, p_i)$, where p_i is the i -th p.r. unary function.
- \mathcal{T} will be binary and uniquely branching (explain)
- approximating (\mathbb{N}, p_i)




Outside-branch strategy (very roughly)

- an approximation of \mathcal{P}_i branches outside the current \mathcal{T}
- avoid this branching length in \mathcal{T} by attaching to the leaves of \mathcal{T} very long binary branchings
- this kills $\mathcal{T} \cong \mathcal{P}_i$



Inside-branch strategy (very roughly)

- an approximation of \mathcal{P}_i branches inside the current \mathcal{T} at a node x
- forbid growing \mathcal{T} from x *from level $i+1$*
- this kills $\mathcal{T} \cong \mathcal{P}_i$



Corollary

The following classes of structures are not punctually robust:

- ① *join semilattices,*
- ② *meet semilattices,*
- ③ *(complemented) lattices.*

This remains valid under order-theoretic and algebraic interpretation.

Add a least element to the computable tree from the result on partially-ordered trees.

Recap and conclusions

- punctual robustness of trees under various structural definitions
- interaction between structure and p.r. computation
- initial (invalid) suspicion: punctual robustness depends on whether a signature is relational or functional
- punctual robustness is contingent on the mode of representation
- (semi)lattices are not punctually robust (previous slide)

Further directions

- ①
 - Boolean algebras are punctually robust [Kalimullin et al., 2017].
 - Complemented lattices are not (this talk)
 - Since Boolean algebras are complemented distributive lattices:

💡 Determine whether the class of distributive lattices is punctually robust.

- ② Consider a more general concept of a partially ordered tree:

Definition (from set theory, e.g. [Jech, 2007])

A partially ordered set (P, \leq) is a set-theoretic tree if it has a least element and for every $x \in P$, $P_{\leq x}$ is well-ordered by \leq .

💡 Investigate punctual robustness of set-theoretic trees.

Thank you for your attention



Bazhenov, N., Downey, R., Kalimullin, I., and Melnikov, A. (2019).
Foundations of online structure theory.
Bulletin of Symbolic Logic, 25(2):141–181.
Publisher: Cambridge University Press.



Cenzer, D. and Remmel, J. (1991).
Polynomial-time versus recursive models.
Annals of Pure and Applied Logic, 54(1):17–58.



Cenzer, D. and Remmel, J. B. (1998).
Feasible graphs with standard universe.
Annals of Pure and Applied Logic, 94(1):21–35.



Jech, T. (2007).
Set Theory: The Third Millennium Edition, revised and expanded.
Springer Monographs in Mathematics. Springer Berlin Heidelberg.



Kalimullin, I., Melnikov, A., and Ng, K. M. (2017).
Algebraic structures computable without delay.
Theoretical Computer Science, 674:73–98.



Khoussainov, B. and Nerode, A. (1995).

Automatic presentations of structures.

In Leivant, D., editor, *Logic and Computational Complexity*, pages 367–392, Berlin, Heidelberg. Springer Berlin Heidelberg.



Mal'tsev, A. I. (1961).

Constructive algebras I.

Russian Mathematical Surveys, 16(3):77.

Publisher: IOP Publishing.



Rabin, M. O. (1960).

Computable algebra, general theory and theory of computable fields.

Transactions of the American Mathematical Society, 95(2):341–360.

Publisher: JSTOR.



Tennenbaum, S. (1959).

Non-archimedean models for arithmetic.

Notices of the American Mathematical Society, 6(270):44.