



## Features

- Multiband L1/L2 active antenna
- High LNA gain (39dB)
- 3.3 to 12V/50mA power supply
- SMA male connector

## Applications

- RTK Base or mobile Rover
- GPS devices
- Precise navigation
- Vehicle mounted GPS

## Description

The DA233 is an affordable and highly efficient multi-band GNSS helical active antenna.

The device allows concurrent reception of GPS / GLONASS / BeiDou & Galileo signals to improve signal availability.

The minimum 2dBi peak gain is amplified using a 39dB LNA gain to ensure the best signal quality in any situation.

The SMA male connector together with the rubber joint sealing make them reliable, robust and waterproof.

Table 1. Device summary

Order ref code	Temperature range [°C]	Product size [mm]
0925	-40 to +70	60 x 27.5

# Contents

1. Specifications	3
2. Absolute maximum ratings	4
5. Mechanical drawings	5
6. Revision history	6

# 1. Specifications

Table 2. DA925 mechanical and electrical specifications

Item		Specifications
Antenna	GNSS bands	GPS L1/L2 GLONASS G1/G2 BeiDou B1/B2/B3 Galileo E1/E2/E5a/E5b/E6
	Polarization	RHCP
	Axial Ratio	$\leq 3.0\text{dB}$
	V.S.W.R.	$\leq 2\text{dB}$
	Peak Gain	$\geq 2.0\text{dBi}$
	Impedance	$50\Omega$
	Horizontal Coverage Angle	$360^\circ$
LNA	Gain	L-upper band $39.0 \pm 2.0\text{dB}$ L-lower band $38.0 \pm 3.0\text{dB}$
	Noise Figure	$\leq 1.5\text{dB}$
	Passband Fluctuation	$\pm 1.0\text{dB}$
	Supply Voltage	3.3~12V DC
	Current Consumption	$\leq 50\text{mA}$
	V.S.W.R.	$\leq 2.0\text{dB}$
Mechanical	Connector	SMA Male
	Dimension	27.5x60mm
Environnemental	Operating Temperature	$-40^\circ\text{C}/+70^\circ\text{C}$
	Relative Humidity	Up to 95%
	Environmentally Friendly	ROHS Compliant

## 2. Absolute maximum ratings


Stresses above those listed as “absolute maximum ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device under these conditions is not implied. Exposure to maximum rating conditions for extended periods may affect device reliability.

Table 3. DA910 absolute maximum ratings

Symbol	Parameter	Maximum value	Unit
Vant	Antenna voltage supply	3.3 to +12	V
Iant	Antenna current supply	50	mA
Hant	Relative humidity	95	%
Tant	Operating temperature	-40 to +70	°C

## 5. Mechanical drawings

Figure 1. DA925 mechanical drawings



## 6. Revision history

Table 4. Document revision history

Date	Revision	Changes
13-Aug-2019	1.0	DrotekDoc_0925 / Initial release

**IMPORTANT NOTICE - PLEASE READ CAREFULLY**

Drotek reserves the right to make changes, corrections, enhancements, modifications, and improvements to Drotek products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on Drotek products before placing orders. Drotek products are sold pursuant to Drotek's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of Drotek products and Drotek assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by Drotek herein.

Resale of Drotek products with provisions different from the information set forth herein shall void any warranty granted by Drotek for such product.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

2020 Drotek - All rights reserved

