



## **PRODUCT NAME**

## G410A

## Short Bright Elite Synthetic Turf

## **MATERIALS**

Primary Yarn Polymer	Polyethylene			
Yarn Cross Section	Diamond Monofilament			
Standard Color	Field Green/Lime Green			
UV Stabilized	Yes			
Fabric Construction	Tufted			
Secondary Yarn Polymer Thatch	100% Polypropylene			
Secondary Yarn Color	Turf Green			
Primary Backing	13 Pic Woven (2)			
Coating Type	Biocel™ Polyurethane			
Polyethylene Yarn Denier / Ends	10,600/6			
Texturized Thatch Denier / Ends	4200/8			
Sustainability	100% Recyclable			
Warranty Period	8 years			

Finish Fabric	English System		Metric S	System	ASTM Test F-1551
Nominal Specification	Value	Units	Value	Units	Method
Pile Height (Nominal)	1 1/2	inches	3.81	cm	D-5823
Face Weight	43	oz/yd²	1423	g/m²	D-5848
Total Fabric Weight	70	oz/yd²	2317	g/m²	D-5848
Primary Backing Weight	7	oz/yd²	232	g/m²	D-5848
Secondary Coating Weight	20	oz/yd²	662	g/m²	D-5848
Tuft Bind	>8	lbs.	>3.63	kg	D-1335
Grab Tear Strength (Average)	>200	lbs.	>91	kg.	D-5034
Lead Content	<50	ppm	<50	ppm	F-2765
<b>Total Yarn Linear Density</b>	14,800	Denier	16280	dtex	D-1577
Elongation to Break	>60	%	>60	%	D-2256
Yarn Breaking Strength	>19	lbs.	>8.62	kg	D-2256
Yarn Melting Point	248	F°	120	C°	D-7138
Stitch Rate	3.3	inches	8.382	cm	D-5793
Machine Guage	1/2	inches	1.27	cm	D-5793
Flammability	Test Passed		Test Pa	assed	D-2859
Water Permeability	>30	in/hr	>76.2	cm/hr	DIN 18-035
Fiber Thickness (Primary / Secondary)	3.9	mils	100	microns	D-3218
Fabric Width	15	ft	4.6	m	None

Note: Any change from the specified values is considered a special product that will require confirmation from manufacturing. All values are ±5%.