



$\partial_t \psi + \frac{M}{\epsilon} \int_{\Omega} \frac{|u(x,t)|^2}{2} \psi \Delta \psi + \int_{\Omega} p = 0, \quad \nabla \psi = 0, \quad \frac{1}{2} \psi(x, 0) = \psi_0(x), \quad \psi(x, t) \in \mathbb{R}$

Planning in Partially Observable Domains with Fuzzy Epistemic States and Probabilistic Dynamics.

N.Drougard, D.Dubois, J-L.Farges, F.Teichteil

ONERA–The French Aerospace Lab, DCSD, Toulouse



retour sur innovation


- 1 Context
- 2 An hybrid POMDP
- 3 Benefiting from factorized structures
- 4 Conclusion/Perspectives

- 1 Context
- 2 An hybrid POMDP
- 3 Benefiting from factorized structures
- 4 Conclusion/Perspectives

Context

Partially Observable Markov Decision Process (POMDP)


POMDP: model for sequential decision making under uncertainty



Context

Partially Observable Markov Decision Process (POMDP)

POMDP: model for sequential decision making under uncertainty




$s \in \mathcal{S}$: **system states;**

Context

Partially Observable Markov Decision Process (POMDP)


POMDP: model for sequential decision making under uncertainty



Context

Partially Observable Markov Decision Process (POMDP)



POMDP: model for sequential decision making under uncertainty



Context

Partially Observable Markov Decision Process (POMDP)



POMDP: model for sequential decision making under uncertainty



Context

Partially Observable Markov Decision Process (POMDP)



POMDP: model for sequential decision making under uncertainty



Context

Partially Observable Markov Decision Process (POMDP)

POMDP: model for sequential decision making under uncertainty



Partially Observable Markov Decision Process (POMDP)

$o \in \mathcal{O}$: observations;

$a \in \mathcal{A}$: agent's actions;

***b*: belief state.**



Context

belief state, strategy, criterion.

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$,

- **transition** function $T(s, a, s') = \mathbf{p}(s' \mid s, a)$;
- **observation** function $O(s', a, o') = \mathbf{p}(o' \mid s', a)$.

Context

belief state, strategy, criterion.

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$,

- **transition** function $T(s, a, s') = \mathbf{p}(s' \mid s, a)$;
- **observation** function $O(s', a, o') = \mathbf{p}(o' \mid s', a)$.

belief state: $b_t(s) = \mathbb{P}(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$

Context

belief state, strategy, criterion.

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$,

- **transition** function $T(s, a, s') = \mathbf{p}(s' | s, a)$;
- **observation** function $O(s', a, o') = \mathbf{p}(o' | s', a)$.

belief state: $b_t(s) = \mathbb{P}(s_t = s | a_0, o_1, \dots, a_{t-1}, o_t)$

probabilistic belief update

$$b_{t+1}(s') \propto \mathbf{p}(o' | s', a) \cdot \sum_{s \in \mathcal{S}} \mathbf{p}(s' | s, a) \cdot b_t(s)$$

Context

belief state, strategy, criterion.

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$,

- **transition** function $T(s, a, s') = \mathbf{p}(s' | s, a)$;
- **observation** function $O(s', a, o') = \mathbf{p}(o' | s', a)$.

belief state: $b_t(s) = \mathbb{P}(s_t = s | a_0, o_1, \dots, a_{t-1}, o_t)$

probabilistic belief update

$$b_{t+1}(s') \propto \mathbf{p}(o' | s', a) \cdot \sum_{s \in \mathcal{S}} \mathbf{p}(s' | s, a) \cdot b_t(s)$$

action choices: strategy $\delta(b_t) = a_t \in \mathcal{A}$

$$\text{maximizing } \mathbb{E}_{s_0 \sim b_0} \left[\sum_{t=0}^{+\infty} \gamma^t \cdot r(s_t, \delta(b_t)) \right], \quad 0 < \gamma < 1.$$

Flaws of the POMDP model

POMDPs in practice

- optimal strategy computation \geq **PSPACE**;
- probabilities are **imprecisely known** in practice;
- agent's **ignorance** not taken into account.

Why model ignorance?

knowledge is not always encouraged with POMDPs

- initial belief deterministic $s_0 = s_A$.


s_A

$$b_0(s_A) = 1$$

Why model ignorance?

knowledge is not always encouraged with POMDPs


- initial belief deterministic $s_0 = s_A$.



Why model ignorance?

knowledge is not always encouraged with POMDPs


- initial belief deterministic $s_0 = s_A$.



Why model ignorance?

knowledge is not always encouraged with POMDPs

- initial belief deterministic $s_0 = s_A$.




- $\{s_B, s_C, s_D\} \xrightarrow{\text{deterministic}} s_E, r(s_E) = 0.$

Why model ignorance?

knowledge is not always encouraged with POMDPs

- initial belief deterministic $s_0 = s_A$.



- $\{s_B, s_C, s_D\} \xrightarrow{\text{deterministic}} s_E, r(s_E) = 0$.

$$\mathbb{E}_{s_0 \sim b_0} \left[\sum_{t=0}^{+\infty} \gamma^t \cdot r(s_t) \mid a_0 = \tilde{a} \text{ ou } a' \right] = r(s_0) + 5\gamma.$$

the safe action is not preferred.

Qualitative Possibility Theory

an hybrid model with possibilistic belief states

Qualitative Possibility Theory

- **simplification/imprecision** taken into account,
BUT frequentist information lost;
- **ignorance** modeling;
- possibilistic belief states already studied: π -POMDP
(*Sabbadin 98, Drougard 13,14*).

Qualitative Possibility Theory

an hybrid model with possibilistic belief states

Qualitative Possibility Theory

- **simplification/imprecision** taken into account,
BUT frequentist information lost;
 - **ignorance** modeling;
 - possibilistic belief states already studied: π -POMDP
(*Sabbadin 98, Drougard 13,14*).
-
- **POMDP with possibilistic belief states**
 - heuristic for POMDP solving;
 - standard MDP.

Qualitative Possibility Theory

an hybrid model with possibilistic belief states

Qualitative Possibility Theory

- **simplification/imprecision** taken into account,
BUT frequentist information lost;
 - **ignorance** modeling;
 - possibilistic belief states already studied: π -POMDP
(*Sabbadin 98, Drougard 13,14*).
-
- **POMDP with possibilistic belief states**
 - heuristic for POMDP solving;
 - standard MDP.
-
- **defined distributions π :**
 $\mathbb{P} \rightarrow \pi$ transformations: pignistic, specific, ...

Qualitative Possibility Theory

presentation

$1 = l_1 > l_2 > \dots > l_{\#\mathcal{L}} = 0$ form the **finite scale** \mathcal{L} .

events $e \subset \Omega$ (universe)

sorted using possibility **degrees** $\pi(e) \in \mathcal{L}$,

\neq

quantified with **frequencies** $\mathbf{p}(e) \in [0, 1]$ (probabilities).

Qualitative Possibility Theory

presentation

$1 = l_1 > l_2 > \dots > l_{\#\mathcal{L}} = 0$ form the **finite scale** \mathcal{L} .

events $e \subset \Omega$ (universe)

sorted using possibility **degrees** $\pi(e) \in \mathcal{L}$,

\neq

quantified with **frequencies** $\mathbf{p}(e) \in [0, 1]$ (probabilities).

$e_1 \neq e_2$, 2 events $\subset \Omega$

■ $\pi(e_1) < \pi(e_2) \Leftrightarrow$ “ e_1 is less plausible than e_2 ”;

Qualitative Possibility Theory

presentation

$1 = l_1 > l_2 > \dots > l_{\#\mathcal{L}} = 0$ form the **finite scale** \mathcal{L} .

events $e \subset \Omega$ (universe)

sorted using possibility **degrees** $\pi(e) \in \mathcal{L}$,

\neq

quantified with **frequencies** $\mathbf{p}(e) \in [0, 1]$ (probabilities).

$e_1 \neq e_2$, 2 events $\subset \Omega$

■ $\pi(e_1) < \pi(e_2) \Leftrightarrow$ “ e_1 is less plausible than e_2 ”;

Probability (\mathbb{P}) / **Possibility (Π):**

| | | |
|----------------|---|--|
| e_1 ou e_2 | $\mathbf{p}(e_1) + \mathbf{p}(e_2 \cap \overline{e_1})$ | $\max \{ \pi(e_1), \pi(e_2) \}$ |
| e_1 et e_2 | $\mathbf{p}(e_1) \cdot \mathbf{p}(e_2 \mid e_1)$ | $\min \{ \pi(e_1), \pi(e_2 \mid e_1) \}$ |

- 1 Context
- 2 An hybrid POMDP
- 3 Benefiting from factorized structures
- 4 Conclusion/Perspectives

A possibilistic belief state

belief space discretization

$$\Pi_S = \left\{ \text{possibility distributions} \right\}: \# \Pi_S < +\infty$$

→ **belief space discretization.**

A possibilistic belief state

belief space discretization

$$\Pi_S = \left\{ \text{possibility distributions} \right\}: \# \Pi_S < +\infty$$

→ **belief space discretization.**

$$b_t^\pi(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

A possibilistic belief state

belief space discretization

$$\Pi_S = \left\{ \text{possibility distributions} \right\}: \# \Pi_S < +\infty$$

→ **belief space discretization.**

$$b_t^\pi(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

update – **possibilistic** belief state

$$b_{t+1}^\pi(s') = \begin{cases} 1 & \text{if } \pi(o', s' \mid b_t^\pi, a) = \pi(o' \mid b_t^\pi, a) \\ \pi(o', s' \mid b_t^\pi, a) & \text{otherwise.} \end{cases}$$

denoted by $b_{t+1}^\pi(s') \propto^\pi \pi(o', s' \mid b_t^\pi, a)$

A possibilistic belief state

belief space discretization

$$\Pi_S = \left\{ \text{possibility distributions} \right\}: \# \Pi_S < +\infty$$

→ **belief space discretization.**

$$b_t^\pi(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

update – **possibilistic** belief state

$$b_{t+1}^\pi(s') = \begin{cases} 1 & \text{if } \pi(o', s' \mid b_t^\pi, a) = \pi(o' \mid b_t^\pi, a) \\ \pi(o', s' \mid b_t^\pi, a) & \text{otherwise.} \end{cases}$$

denoted by $b_{t+1}^\pi(s') \propto^\pi \pi(o', s' \mid b_t^\pi, a)$

- $\pi(o', s' \mid b_t^\pi, a) = \max_{s \in \mathcal{S}} \min \left\{ \pi(o' \mid s', a), \pi(s' \mid s, a), b_t^\pi(s) \right\};$
- $\pi(o' \mid s', a) = \max_{s' \in \mathcal{S}} \pi(o', s' \mid b_t^\pi, a).$

A possibilistic belief state

belief space discretization

$$\Pi_S = \left\{ \text{possibility distributions} \right\}: \# \Pi_S < +\infty$$

→ **belief space discretization.**

$$b_t^\pi(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

update – **possibilistic** belief state

$$b_{t+1}^\pi(s') = \begin{cases} 1 & \text{if } \pi(o', s' \mid b_t^\pi, a) = \pi(o' \mid b_t^\pi, a) \\ \pi(o', s' \mid b_t^\pi, a) & \text{otherwise.} \end{cases}$$

denoted by $b_{t+1}^\pi(s') \propto^\pi \pi(o', s' \mid b_t^\pi, a)$

- the update **only depends on o' and a .**

Pignistic transformation and transitions

Pignistic transformation

numbering of the $n = \#\mathcal{S}$ system states:

$$1 = b^\pi(s_1) \geq \dots \geq b^\pi(s_n) \geq b^\pi(s_{n+1}) = 0.$$





pignistic transformation – $P : \Pi_{\mathcal{S}} \rightarrow \mathbb{P}_{\mathcal{S}}$

$$\overline{b^\pi}(s_i) = \sum_{j=i}^{\#\mathcal{S}} \frac{b^\pi(s_j) - b^\pi(s_{j+1})}{j}.$$

- $\overline{b^\pi} \in \mathcal{B}_{\mathcal{S}}$ gravity center of the represented probabilistic distributions;
- Laplace principle: ignorance \rightarrow uniform probability.

Pignistic transformation

Examples of pignistic transformations (red) of possibility distributions (blue)



Pignistic transformation and transitions

Transition function of epistemic states

Approximation of the probabilities over the observations:

- $\mathbf{p}(o' \mid s, a) = \sum_{s' \in \mathcal{S}} O(s', a, o') \cdot T(s, a, s')$;
- $\mathbf{p}(o' \mid b^\pi, a) := \sum_{s \in \mathcal{S}} \mathbf{p}(o' \mid s, a) \cdot \overline{b^\pi}(s).$

$$\Rightarrow \mathbf{p}\left((b^\pi)' \mid b^\pi, a\right) = \sum_{\substack{o' \text{ t.q.} \\ u(b^\pi, a, o') = (b^\pi)'}} \mathbf{p}(o' \mid b^\pi, a).$$

notation: if $a \in \mathcal{A}$ selected, $o' \in \mathcal{O}$ received,

$$b_{t+1}^\pi = u(o', a, b_t^\pi) = \text{update of } b_t^\pi.$$

Choquet integral and rewards

pessimistic evaluation of the rewards – necessity measure

imprecision of b^π = agent ignorance + discretization:
pessimistic reward about these imprecisions.

Choquet integral and rewards

pessimistic evaluation of the rewards – necessity measure

imprecision of b^π = agent ignorance + discretization:
pessimistic reward about these imprecisions.

Dual measure of $\Pi : 2^{\mathcal{S}} \rightarrow \mathcal{L}$

necessity \mathcal{N} such that $\forall A \subseteq \mathcal{S}, \mathcal{N}(A) = 1 - \Pi(\overline{A})$.

Choquet integral and rewards

pessimistic evaluation of the rewards – necessity measure

imprecision of b^π = agent ignorance + discretization:

pessimistic reward about these imprecisions.

Dual measure of $\Pi : 2^{\mathcal{S}} \rightarrow \mathcal{L}$

necessity \mathcal{N} such that $\forall A \subseteq \mathcal{S}, \mathcal{N}(A) = 1 - \Pi(\bar{A})$.

$r_1 > r_2 > \dots > r_{k+1} = 0$ represents elements of $\{r(s, a) | s \in \mathcal{S}\}$.

Choquet integral of r with respect to \mathcal{N}

$$Ch(r, \mathcal{N}) = \sum_{i=1}^k (r_i - r_{i+1}) \cdot \mathcal{N}(\{r(s) \geq r_i\}) \quad (1)$$

(2)

Choquet integral and rewards

pessimistic evaluation of the rewards – necessity measure

imprecision of b^π = agent ignorance + discretization:

pessimistic reward about these imprecisions.

Dual measure of $\Pi : 2^{\mathcal{S}} \rightarrow \mathcal{L}$

necessity \mathcal{N} such that $\forall A \subseteq \mathcal{S}, \mathcal{N}(A) = 1 - \Pi(\bar{A})$.

$r_1 > r_2 > \dots > r_{k+1} = 0$ represents elements of $\{r(s, a) | s \in \mathcal{S}\}$.

Choquet integral of r with respect to \mathcal{N}


$$Ch(r, \mathcal{N}) = \sum_{i=1}^k (r_i - r_{i+1}) \cdot \mathcal{N}(\{r(s) \geq r_i\}) \quad (1)$$

$$= \sum_{i=1}^{\#\mathcal{L}-1} (l_i - l_{i+1}) \cdot \min_{\substack{s \in \mathcal{S} \text{ s.t.} \\ b^\pi(s) \geq l_i}} r(s). \quad (2)$$

notation $\mathcal{L} = \{l_1 = 1, l_2, l_3, \dots, 0\}$.


Choquet integral and rewards

back to the example about ignorance



Choquet integral and rewards

back to the example about ignorance




- $Ch(r, N_{b_1^\pi} \mid a_0 = \tilde{a}) = r(s_D, a') = 5,$
- $Ch(r, N_{b_1^\pi} \mid a_0 = a') = \min_{s \in \mathcal{S}} r(s, \tilde{a}) = 0.$

the safe action is preferred! **dispersion reduced**

Choquet integral and rewards

back to the example about ignorance



- $Ch(r, N_{b_1^\pi} \mid a_0 = \tilde{a}) = r(s_D, a') = 5,$
- $Ch(r, N_{b_1^\pi} \mid a_0 = a') = \min_{s \in \mathcal{S}} r(s, \tilde{a}) = 0.$

the safe action is preferred! **dispersion reduced**

if $\mathcal{N}_{b_1^\pi}$ replaced by $b_1 \Rightarrow Ch(r, b_1) = \mathbb{E}_{s \sim b_1} [r(s, a)]$.

resulting MDP

translation summary

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

resulting MDP

translation summary

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{S}}$,
the set of the possibility distributions over \mathcal{S} ;

resulting MDP

translation summary

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{S}}$,
the set of the possibility distributions over \mathcal{S} ;
- $\forall b^\pi, (b^\pi)'$ possibilistic belief states $\in \Pi_{\mathcal{S}}, \forall a \in \mathcal{A}$,
transitions $\tilde{T}(b^\pi, a, (b^\pi)') = \mathbf{p}((b^\pi)' | b^\pi, a)$;

resulting MDP

translation summary

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{S}}$,
the set of the possibility distributions over \mathcal{S} ;
- $\forall b^\pi, (b^\pi)'$ possibilistic belief states $\in \Pi_{\mathcal{S}}, \forall a \in \mathcal{A}$,
transitions $\tilde{T}(b^\pi, a, (b^\pi)') = \mathbf{p}((b^\pi)' | b^\pi, a)$;
- **reward** $\tilde{r}(a, b^\pi) = Ch(r(a, \cdot), \mathcal{N}_{b^\pi})$,
 \mathcal{N}_{b^π} necessity measure computed from b^π .

resulting MDP

translation summary

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{S}}$,
the set of the possibility distributions over \mathcal{S} ;
- $\forall b^\pi, (b^\pi)'$ possibilistic belief states $\in \Pi_{\mathcal{S}}, \forall a \in \mathcal{A}$,
transitions $\tilde{T}(b^\pi, a, (b^\pi)') = \mathbf{p}((b^\pi)' | b^\pi, a)$;
- **reward** $\tilde{r}(a, b^\pi) = Ch(r(a, \cdot), \mathcal{N}_{b^\pi})$,
 \mathcal{N}_{b^π} necessity measure computed from b^π .

$$\text{criterion: } \mathbb{E}_{(b_t^\pi) \sim \tilde{T}} \left[\sum_{t=0}^{+\infty} \gamma^t \cdot \tilde{r}(b_t^\pi, d_t) \right].$$

hybrid POMDP and π -POMDP

differences with possibilistic models

| | hybrid POMDP | π -POMDP |
|-------------|------------------------------------|-------------------------------|
| transitions | probabilities | qualitative possibility |
| rewards | quantitative $\in \mathbb{R}$ | qualitative $\in \mathcal{L}$ |
| situation | -some imprecisions -large POMDP | few quantitative |
| issues | π definition | commensurability |
| in practice | MDP | π -MDP |

hybrid POMDP and π -POMDP

differences with possibilistic models

| | hybrid POMDP | π -POMDP |
|-------------|------------------------------------|-------------------------------|
| transitions | probabilities | qualitative possibility |
| rewards | quantitative $\in \mathbb{R}$ | qualitative $\in \mathcal{L}$ |
| situation | -some imprecisions -large POMDP | few quantitative |
| issues | π definition | commensurability |
| in practice | MDP | π -MDP |

hybrid model:

- only belief states are possibilistic:
 - agent knowledge = **possibility** distribution;
- probabilistic dynamics:
 - **approximated** (prob.) transition between epistemic states.

- 1 Context
- 2 An hybrid POMDP
- 3 Benefiting from factorized structures
- 4 Conclusion/Perspectives

factorized POMDP

definition

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;

factorized POMDP

definition

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;
- **transition** function of s'_j ,
 $T_j^a(\mathbb{S}, s'_j) = \mathbf{p}(s'_j \mid \mathbb{S}, a), \forall j \in \{1, \dots, m\}$ et $\forall a \in \mathcal{A}$;

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;
- **transition** function of s'_j ,
 $T_j^a(\mathbb{S}, s'_j) = \mathbf{p}(s'_j \mid \mathbb{S}, a)$, $\forall j \in \{1, \dots, m\}$ et $\forall a \in \mathcal{A}$;
- \mathcal{O} described by $\mathbb{O} = \{o_1, \dots, o_n\}$: $\mathcal{O} = o_1 \times \dots \times o_n$;

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;
- **transition** function of s'_j ,
 $T_j^a(\mathbb{S}, s'_j) = \mathbf{p}(s'_j \mid \mathbb{S}, a)$, $\forall j \in \{1, \dots, m\}$ et $\forall a \in \mathcal{A}$;
- \mathcal{O} described by $\mathbb{O} = \{o_1, \dots, o_n\}$: $\mathcal{O} = o_1 \times \dots \times o_n$;
- **observation** function of o'_i ,
 $O_i^a(\mathbb{S}', o'_i) = \mathbf{p}(o'_i \mid \mathbb{S}', a)$, $\forall i \in \{1, \dots, n\}$ et $\forall a \in \mathcal{A}$.

factorized POMDP

definition

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;
- **transition** function of s'_j ,
 $T_j^a(\mathbb{S}, s'_j) = \mathbf{p}(s'_j \mid \mathbb{S}, a)$, $\forall j \in \{1, \dots, m\}$ et $\forall a \in \mathcal{A}$;
- \mathcal{O} described by $\mathbb{O} = \{o_1, \dots, o_n\}$: $\mathcal{O} = o_1 \times \dots \times o_n$;
- **observation** function of o'_i ,
 $O_i^a(\mathbb{S}', o'_i) = \mathbf{p}(o'_i \mid \mathbb{S}', a)$, $\forall i \in \{1, \dots, n\}$ et $\forall a \in \mathcal{A}$.

independences:

- $\rightarrow \forall s'_i, s'_j \in \mathbb{S}', \quad s'_i \perp\!\!\!\perp s'_j \mid \{\mathbb{S}, a \in \mathcal{A}\},$
- $\rightarrow \forall o'_i, o'_j \in \mathbb{O}', \quad o'_i \perp\!\!\!\perp o'_j \mid \{\mathbb{S}', a \in \mathcal{A}\}.$

Notations

some variables does not interact with each other

variables about the **current** system state,

s_1

\vdots

s_{j_1}

\vdots

s_{j_2}

\vdots

s_{j_k}

\vdots

s_m

variable s'_j about
the **next** state.

s'_j

Notations

some variables does not interact with each other


variables about the **current** system state,

$$s_k \rightarrow s'_j$$



$\exists a \in \mathcal{A}$, such that

$T_j^a(\mathbb{S}, s'_j)$ depends on s_k .




Notations

some variables does not interact with each other

variables about the **current** system state,

$s_k \rightarrow s'_j$
 \Updownarrow
 $\exists a \in \mathcal{A}$, such that
 $T_j^a(\mathbb{S}, s'_j)$ depends on s_k .

variable s'_j about
the **next** state.




the parents of s'_j are:

$$\begin{aligned}\mathcal{P}(s'_j) &= \{s \in \mathbb{S} \mid s \rightarrow s'_j\} \\ &= \{s_{j_1}, s_{j_2}, \dots, s_{j_k}\}.\end{aligned}$$

Notations

concerning observation variables

next state



Notations

concerning observation variables

$$s'_j \rightarrow o'_i$$




$\exists a \in \mathcal{A}$, such that

$$O_i^a(S', o'_i)$$

depends on s'_j .

next state



Notations

concerning observation variables


$$s'_j \rightarrow o'_i$$



$\exists a \in \mathcal{A}$, such that

$$O_i^a(\mathbb{S}', o'_i)$$

depends on s'_j .



Notations


concerning observation variables

$$s'_j \rightarrow o'_i$$




$\exists a \in \mathcal{A}$, such that

$O_i^a(S', o'_i)$
depends on s'_j .



next state



Notations


concerning observation variables

$$s'_j \rightarrow o'_i$$



$\exists a \in \mathcal{A}$, such that

$O_i^a(S', o'_i)$
depends on s'_j .



Notations

concerning observation variables


$$s'_j \rightarrow o'_i$$



$\exists a \in \mathcal{A}$, such that


$$O_i^a(S', o'_i)$$

depends on s'_j .



Notations

concerning observation variables



Rewritings of parameters

PROBABILISTIC parameters

- $T_j^a(\mathbb{S}, s'_j) = T_j^a(\mathcal{P}(s'_j), s'_j);$
- $O_i^a(\mathbb{S}', o'_i) = O_i^a(\mathcal{P}(o'_i), o'_i).$

Rewritings of parameters

PROBABILISTIC parameters

- $T_j^a(\mathbb{S}, s'_j) = T_j^a(\mathcal{P}(s'_j), s'_j);$
- $O_i^a(\mathbb{S}', o'_i) = O_i^a(\mathcal{P}(o'_i), o'_i).$

consequences on the joint distribution

$$\begin{aligned}\mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathbb{S}, a) &= O_i^a(\mathcal{P}(o'_i), o'_i) \cdot \prod_{s'_j \in \mathcal{P}(o'_i)} T_j^a(\mathcal{P}(s'_j), s'_j) \\ &= \mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a).\end{aligned}$$

Rewritings of parameters

PROBABILISTIC parameters

- $T_j^a(\mathbb{S}, s'_j) = T_j^a(\mathcal{P}(s'_j), s'_j);$
- $O_i^a(\mathbb{S}', o'_i) = O_i^a(\mathcal{P}(o'_i), o'_i).$

consequences on the joint distribution

$$\begin{aligned}\mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathbb{S}, a) &= O_i^a(\mathcal{P}(o'_i), o'_i) \cdot \prod_{s'_j \in \mathcal{P}(o'_i)} T_j^a(\mathcal{P}(s'_j), s'_j) \\ &= \mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a).\end{aligned}$$

observation probabilities

epistemic state

$$b^\pi(\mathbb{S}) \xrightarrow{\text{marginalization}} b^\pi(\mathcal{Q}(o'_i)) \xrightarrow{\text{pignistic transformation}} \overline{b}^\pi(\mathcal{Q}(o'_i))$$

$$\mathbf{p}(o'_i \mid b^\pi, a) = \sum_{2^{\mathcal{P}(o'_i)}, 2^{\mathcal{Q}(o'_i)}} \mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a) \cdot \overline{b}^\pi(\mathcal{Q}(o'_i))$$

Parameters rewritings

POSSIBILISTIC parameters

- $\pi(s'_j \mid \mathbb{S}, a) = \pi(s'_j \mid \mathcal{P}(s'_j), a);$
- $\pi(o'_i \mid \mathbb{S}', a) = \pi(o'_i \mid \mathcal{P}(o'_i), a).$

- $\pi(s'_j \mid \mathbb{S}, a) = \pi(s'_j \mid \mathcal{P}(s'_j), a);$
- $\pi(o'_i \mid \mathbb{S}', a) = \pi(o'_i \mid \mathcal{P}(o'_i), a).$

marginal possibilistic belief states

$\forall o'_i \in \mathbb{O},$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) \propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

Parameters rewritings

POSSIBILISTIC parameters

- $\pi(s'_j \mid \mathbb{S}, a) = \pi(s'_j \mid \mathcal{P}(s'_j), a);$
- $\pi(o'_i \mid \mathbb{S}', a) = \pi(o'_i \mid \mathcal{P}(o'_i), a).$

marginal possibilistic belief states

$\forall o'_i \in \mathbb{O},$

$$\begin{aligned} b_{t+1}^\pi(\mathcal{P}(o'_i)) &\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid a_0, o_1, \dots, a_{t-1}, o_t) \\ &= \max_{2^{\mathcal{Q}(o'_i)}} \min \left\{ \pi(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a), b_t^\pi(\mathcal{Q}(o'_i)) \right\} \end{aligned}$$

Parameters rewritings

POSSIBILISTIC parameters

- $\pi(s'_j \mid \mathbb{S}, a) = \pi(s'_j \mid \mathcal{P}(s'_j), a);$
- $\pi(o'_i \mid \mathbb{S}', a) = \pi(o'_i \mid \mathcal{P}(o'_i), a).$

marginal possibilistic belief states

$\forall o'_i \in \mathbb{O},$

$$\begin{aligned} b_{t+1}^\pi(\mathcal{P}(o'_i)) &\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid a_0, o_1, \dots, a_{t-1}, o_t) \\ &= \max_{2^{\mathcal{Q}(o'_i)}} \min \left\{ \pi(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a), b_t^\pi(\mathcal{Q}(o'_i)) \right\} \\ &\quad \text{denoted by} \end{aligned}$$

$$\pi(o'_i, \mathcal{P}(o'_i) \mid b_t^\pi, a).$$

Variable classification

3 classes of state variables

variable: visible $s_v \in \mathbb{S}_v$

s'_v

inferred hidden $s_h \in \mathbb{S}_h$

s'_h


fully hidden $s_f \in \mathbb{S}_f$

s'_f

Variable classification

3 classes of state variables

variable: visible $s_v \in \mathbb{S}_v$



inferred hidden $s_h \in \mathbb{S}_h$




fully hidden $s_f \in \mathbb{S}_f$



Variable classification

3 classes of state variables

variable: **visible** $s_v \in \mathbb{S}_v$



$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b_t^\pi}(\mathcal{P}(s'_v)).$$

inferred hidden $s_h \in \mathbb{S}_h$



fully hidden $s_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables

variable: **visible** $s_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.

$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b}_t^\pi(\mathcal{P}(s'_v)).$$



inferred hidden $s_h \in \mathbb{S}_h$



fully hidden $s_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables


variable: **visible** $s_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.

$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b_t^\pi}(\mathcal{P}(s'_v)).$$



inferred hidden $s_h \in \mathbb{S}_h$



fully hidden $s_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables

variable: **visible** $s_v \in \mathbb{S}_v$


\Leftrightarrow deterministic belief variable.

$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \bar{b}_t^\pi(\mathcal{P}(s'_v)).$$



inferred hidden $s_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$



fully hidden $s_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables

variable: **visible** $s_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v \mid b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \bar{b}_t^\pi(\mathcal{P}(s'_v)).$$



inferred hidden $s_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid b_t^\pi, a).$$



fully hidden $s_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables

variable: **visible** $s_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v \mid b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \bar{b}_t^\pi(\mathcal{P}(s'_v)).$$



inferred hidden $s_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid b_t^\pi, a).$$



⚠ $\mathcal{P}(o'_i)$ may contain visible variables.

fully hidden $s_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables

variable: **visible** $s_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \bar{b}_t^\pi(\mathcal{P}(s'_v)).$$



inferred hidden $s_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) | b_t^\pi, a).$$



⚠ $\mathcal{P}(o'_i)$ may contain visible variables.

fully hidden $s_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables

variable: **visible** $s_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b}_t^\pi(\mathcal{P}(s'_v)).$$



inferred hidden $s_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) | b_t^\pi, a).$$



⚠ $\mathcal{P}(o'_i)$ may contain visible variables.

fully hidden $s_f \in \mathbb{S}_f$



$$b_{t+1}^\pi(s'_f) = \max_{2^{\mathcal{P}(s'_f)}} \min \left\{ \pi(s'_f | \mathcal{P}(s'_f), a), b_t^\pi(\mathcal{P}(s'_f)) \right\}.$$


Variable classification

3 classes of state variables

variable: **visible** $s_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \bar{b}_t^\pi(\mathcal{P}(s'_v)).$$



inferred hidden $s_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) | b_t^\pi, a).$$



⚠ $\mathcal{P}(o'_i)$ may contain visible variables.

fully hidden $s_f \in \mathbb{S}_f$

\rightarrow observations don't
inform belief state on s'_f .

$$b_{t+1}^\pi(s'_f) = \max_{2^{\mathcal{P}(s'_f)}} \min \left\{ \pi(s'_f | \mathcal{P}(s'_f), a), b_t^\pi(\mathcal{P}(s'_f)) \right\}.$$



Possibilistic belief variables

global belief state

$$\mathbb{O}_h = \mathbb{O} \setminus \mathbb{S}_v.$$

bound over the global belief state

$$b_{t+1}(\mathbb{S}') = \pi(\mathbb{S}' \mid a_0, o_1, \dots, a_t, o_{t+1})$$

$$\leq \beta_{t+1}(\mathbb{S}')$$

$$= \min \left\{ \min_{s'_j \in \mathbb{S}_v} \left[\mathbb{1}_{\{s'_j = o'_j\}} \right], \min_{s'_j \in \mathbb{S}_f} \left[b_{t+1}^{\pi}(s'_j) \right], \min_{o'_i \in \mathbb{O}_h} \left[b_{t+1}^{\pi}(\mathcal{P}(o'_i)) \right] \right\}$$

Possibilistic belief variables

global belief state

$$\mathbb{O}_h = \mathbb{O} \setminus \mathbb{S}_v.$$

bound over the global belief state

$$b_{t+1}(\mathbb{S}') = \pi(\mathbb{S}' \mid a_0, o_1, \dots, a_t, o_{t+1})$$

$$\leq \beta_{t+1}(\mathbb{S}')$$

$$= \min \left\{ \min_{s'_j \in \mathbb{S}_v} \left[\mathbb{1}_{\{s'_j = o'_j\}} \right], \min_{s'_j \in \mathbb{S}_f} \left[b_{t+1}^\pi(s'_j) \right], \min_{o'_i \in \mathbb{O}_h} \left[b_{t+1}^\pi(\mathcal{P}(o'_i)) \right] \right\}$$

- β_t = **less informative** version of the belief state:
 $b_t^\pi \leq \beta_t$;
- computed using **marginal belief states** \leftrightarrow **factorization**.

Variables de croyance

different according to the class of the variable

$$\lambda = \#\mathcal{L}$$

Variables de croyance

different according to the class of the variable

$$\lambda = \#\mathcal{L}$$

- $\forall s'_v \in \mathbb{S}_v$, 1 variable β'_v is enough.

Variables de croyance

different according to the class of the variable

$$\lambda = \#\mathcal{L}$$

■ $\forall s'_v \in \mathbb{S}_v$, 1 variable β'_v is enough.

■ $p_i = \#\mathcal{P}(o'_i)$.

$\forall o_i \in \mathbb{O} \setminus \mathbb{S}_v$, $\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}$ belief states,

$\Rightarrow \lceil \log_2(\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}) \rceil$ boolean variables β'_h .

Variables de croyance

different according to the class of the variable

$$\lambda = \#\mathcal{L}$$

■ $\forall s'_v \in \mathbb{S}_v$, 1 variable β'_v is enough.

■ $p_i = \#\mathcal{P}(o'_i)$.

$\forall o_i \in \mathbb{O} \setminus \mathbb{S}_v$, $\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}$ belief states,

$\Rightarrow \lceil \log_2(\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}) \rceil$ boolean variables β'_h .

■ $\forall s'_f \in \mathbb{S}_f$, $\lambda^2 - (\lambda - 1)^2 = 2\lambda - 1$ belief states,

$\Rightarrow \lceil \log_2(2\lambda - 1) \rceil$ boolean variables β'_f .

resulting MDP in practice

trick: “flipflop” variable

boolean variable “*flipflop*” f changes state at each time step
→ defines 2 phases:

- 1 *observation generation*,
- 2 *belief update* (deterministic knowing the observation).

MDP variables:

$\tilde{S} =$


beliefs: $\beta = \beta_v^1 \times \dots \times \beta_v^{m_v} \times \beta_h^1 \times \dots \times \beta_h^{m_h} \times \beta_f^1 \times \dots \times \beta_f^{m_f}$

\times

visible variables : $v = f \times s_v^1 \times \dots \times s_v^{m_v} \times o_1 \times \dots \times o_k.$

resulting MDP in practice

final structured MDP



$\tilde{\mathcal{S}} =$


beliefs: $\beta = \beta_v^1 \times \dots \times \beta_v^{m_v} \times \beta_h^1 \times \dots \times \beta_h^{m_h} \times \beta_f^1 \times \dots \times \beta_f^{m_f}$

\times

visible variables : $v = f \times s_v^1 \times \dots \times s_v^{m_v} \times o_1 \times \dots \times o_k.$

resulting MDP in practice

final structured MDP



factorized model's variables: $\#\mathbb{O} + \#\mathbb{S}_v +$


$$+ \sum_{i=1}^{\#\mathbb{O}_h} \left[\log_2 (\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}) \right] + \#\mathbb{S}_f \cdot \left[\log_2 (2\lambda - 1) \right]$$

\ll # initial hybrid model's variables:

$$\left[\log_2 (\lambda^{2^{\#\mathbb{S}}} - (\lambda - 1)^{2^{\#\mathbb{S}}}) \right]$$

resulting MDP in practice

final structured MDP



factorized model's variables:

$$\leq \#\mathbb{O} + \#S_v + \sum_{i=1}^{\#\mathbb{O}_h} \log_2(\lambda) \cdot 2^{p_i} + \#S_f \cdot (1 + \log_2(\lambda))$$

\ll # initial hybrid model's variables:
 $\geq \log_2(\lambda) \cdot (2^{\#\mathbb{S}} - 1).$

- 1 Context
- 2 An hybrid POMDP
- 3 Benefiting from factorized structures
- 4 Conclusion/Perspectives

POMDP $\xrightarrow{\text{translation}}$ MDP with finite state space

- transition probabilities on the **possibilistic belief states**;

POMDP $\xrightarrow{\text{translation}}$ MDP with finite state space

- transition probabilities on the **possibilistic belief states**;
- **pessimistic** evaluation of the **rewards**
(Choquet integral);

POMDP $\xrightarrow{\text{translation}}$ MDP with finite state space

- transition probabilities on the **possibilistic belief states**;
- **pessimistic** evaluation of the **rewards**
(Choquet integral);
- factorized POMDP $\xrightarrow{\text{translation}}$ factorized MPD.

POMDP $\xrightarrow{\text{translation}}$ MDP with finite state space

- transition probabilities on the **possibilistic belief states**;
- **pessimistic** evaluation of the **rewards** (Choquet integral);
- factorized POMDP $\xrightarrow{\text{translation}}$ factorized MPD.

perspectives:

- IPPC problems (factorized POMDPs);

POMDP $\xrightarrow{\text{translation}}$ MDP with finite state space

- transition probabilities on the **possibilistic belief states**;
- **pessimistic** evaluation of the **rewards** (Choquet integral);
- factorized POMDP $\xrightarrow{\text{translation}}$ factorized MPD.

perspectives:

- IPPC problems (factorized POMDPs);
- test approaches:
 - 1 **simplification**: distributions π definition (π -normalization of \mathbb{P} , pignistic transformation, the more specific, ...);
 - 2 **imprecision**: more robust?

Thank you!