

$\partial_t \psi + \frac{M}{\epsilon} \int_{\Omega} \frac{|u(x,t)|^2}{2} \psi \Delta \psi + \int_{\Omega} p = 0, \quad \nabla \psi = 0, \quad \psi(x,0) = \psi_0(x), \quad \psi(x,t) = \psi_0(x)$

Exploiting Imprecise Information Sources in Sequential Decision Making Problems under Uncertainty

N.Drougard

under D.Dubois, J-L.Farges and F.Teichteil-Königsbuch supervision

doctoral school: EDSYS institution: ISAE-SUPAERO

laboratory: ONERA-The French Aerospace Lab



retour sur innovation

- 1 Context
- 2 Introductory example (HMI)
- 3 Advances in the qualitative possibilistic MDPs
- 4 Symbolic solver and factorization
- 5 A hybrid model
- 6 Conclusion/Perspectives

- 1 Context
- 2 Introductory example (HMI)
- 3 Advances in the qualitative possibilistic MDPs
- 4 Symbolic solver and factorization
- 5 A hybrid model
- 6 Conclusion/Perspectives

Onera, DCSD

Control Engineering, AI, Flight Dynamics, Cognitive Sciences

Onera, DCSD

Control Engineering, AI, Flight Dynamics, Cognitive Sciences


among many other works:

- autonomy and human factors
- decision making, planning
- experimental/industrial applications: UAVs, human-machine interaction, exploration robots



Context


Partially Observable Markov Decision Processes (POMDPs)



POMDP: model for autonomous robotics

Context

Partially Observable Markov Decision Processes (POMDPs)




POMDP: model for autonomous robotics

$s \in \mathcal{S}$: **system states**




Context

Partially Observable Markov Decision Processes (POMDPs)




Context

Partially Observable Markov Decision Processes (POMDPs)




Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)



Context

Partially Observable Markov Decision Processes (POMDPs)



Context

belief state, strategy, criterion

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$ (Smallwood et al. 1973)

■ **transition** function $T(s, a, s') = \mathbf{p}(s' \mid s, a)$

■ **observation** function $O(s', a, o') = \mathbf{p}(o' \mid s', a)$

Context

belief state, strategy, criterion

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$ (Smallwood et al. 1973)

■ **transition** function $T(s, a, s') = \mathbf{p}(s' \mid s, a)$

■ **observation** function $O(s', a, o') = \mathbf{p}(o' \mid s', a)$

belief state: $b_t(s) = \mathbb{P}(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$

Context

belief state, strategy, criterion

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$ (Smallwood et al. 1973)

■ **transition** function $T(s, a, s') = \mathbf{p}(s' | s, a)$

■ **observation** function $O(s', a, o') = \mathbf{p}(o' | s', a)$

belief state: $b_t(s) = \mathbb{P}(s_t = s | a_0, o_1, \dots, a_{t-1}, o_t)$

probabilistic belief update – a selected, o' received

$$b_{t+1}(s') \propto \mathbf{p}(o' | s', a) \cdot \sum_{s \in \mathcal{S}} \mathbf{p}(s' | s, a) \cdot b_t(s)$$

Context

belief state, strategy, criterion

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$ (Smallwood et al. 1973)

■ **transition** function $T(s, a, s') = \mathbf{p}(s' | s, a)$

■ **observation** function $O(s', a, o') = \mathbf{p}(o' | s', a)$

belief state: $b_t(s) = \mathbb{P}(s_t = s | a_0, o_1, \dots, a_{t-1}, o_t)$

probabilistic belief update – a selected, o' received

$$b_{t+1}(s') \propto \mathbf{p}(o' | s', a) \cdot \sum_{s \in \mathcal{S}} \mathbf{p}(s' | s, a) \cdot b_t(s)$$

action choices: strategy $\delta(b_t) = a_t \in \mathcal{A}$

$$\text{maximizing } \mathbb{E}_{s_0 \sim b_0} \left[\sum_{t=0}^{+\infty} \gamma^t \cdot r(s_t, \delta(b_t)) \right], \quad 0 < \gamma < 1$$

Flaws of the POMDP model

POMDPs in practice

- optimal strategy computation \geq **PSPACE**
(*Papadimitriou et al. 1987*)
- probabilities are **imprecisely known** in practice
- **prior ignorance** management?

- **POMDP optimal strategy computation undecidable**
in infinite horizon – *Madani et al. (AAAI-99)*

- **POMDP optimal strategy computation undecidable**

in infinite horizon – *Madani et al. (AAAI-99)*

- optimality for “small” or “structured” POMDPs
- approximate computations

■ POMDP optimal strategy computation undecidable

in infinite horizon – *Madani et al. (AAAI-99)*

→ optimality for “small” or “structured” POMDPs

→ approximate computations

■ Imprecise model, e.g. vision from statistical learning



■ POMDP optimal strategy computation undecidable

in infinite horizon – *Madani et al. (AAAI-99)*

→ optimality for “small” or “structured” POMDPs

→ approximate computations

■ Imprecise model, e.g. vision from statistical learning

→ unknown environments: image variability of the datasets?



■ POMDP optimal strategy computation undecidable

in infinite horizon – *Madani et al. (AAAI-99)*

→ optimality for “small” or “structured” POMDPs

→ approximate computations

■ Imprecise model, e.g. vision from statistical learning

→ unknown environments: image variability of the datasets?



■ Lack of prior information on the system state:

initial belief state b_0

■ POMDP optimal strategy computation undecidable

in infinite horizon – *Madani et al. (AAAI-99)*

→ optimality for “small” or “structured” POMDPs

→ approximate computations

■ Imprecise model, e.g. vision from statistical learning

→ unknown environments: image variability of the datasets?



■ Lack of prior information on the system state:

initial belief state b_0


→ uniform probability distribution \neq ignorance!

Qualitative Possibility Theory

presentation – (max,min) “tropical” algebra

finite scale \mathcal{L}

usually $\{0, \frac{1}{k}, \frac{2}{k}, \dots, 1\}$



events $e \subset \Omega$ (universe)

sorted using possibility **degrees** $\pi(e) \in \mathcal{L}$

\neq


quantified with **frequencies** $\mathbf{p}(e) \in [0, 1]$ (probabilities)

Qualitative Possibility Theory

presentation – (max,min) “tropical” algebra

finite scale \mathcal{L}

usually $\{0, \frac{1}{k}, \frac{2}{k}, \dots, 1\}$



events $e \subset \Omega$ (universe)

sorted using possibility **degrees** $\pi(e) \in \mathcal{L}$

\neq

quantified with **frequencies** $\mathbf{p}(e) \in [0, 1]$ (probabilities)

$e_1 \neq e_2$, 2 events $\subset \Omega$

■ $\pi(e_1) < \pi(e_2) \Leftrightarrow$ “ e_1 is less plausible than e_2 ”

Qualitative Possibility Theory

Criteria from Sugeno integral

Probability / Possibility:

$+$	\max
\times	\min
$X \in \mathbb{R}$	$X \in \mathcal{L}$
$\mathbb{E}[X] = \sum_{x \in X} x \cdot \mathbf{p}(x)$	<p>optimistic:</p> $\mathbb{S}_{\Pi}[X] = \max_{x \in X} \min \{x, \pi(x)\}$ <p>cautious:</p> $\mathbb{S}_{\mathcal{N}}[X] = \min_{x \in X} \max \{x, 1 - \pi(x)\}$

Qualitative Possibility Theory

qualitative possibilistic POMDP (π -POMDP)

Sabbadin (UAI-98) introduces

the qualitative possibilistic POMDP

π -POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T^\pi, O^\pi, \rho \rangle$

Qualitative Possibility Theory

qualitative possibilistic POMDP (π -POMDP)

Sabbadin (UAI-98) introduces

the qualitative possibilistic POMDP

π -POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T^\pi, O^\pi, \rho \rangle$

- **transition** function $T^\pi(s, a, s') = \pi(s' \mid s, a) \in \mathcal{L}$
- **observation** function $O^\pi(s', a, o') = \pi(o' \mid s', a) \in \mathcal{L}$
- **preference** function $\rho : \mathcal{S} \times \mathcal{A} \rightarrow \mathcal{L}$

Qualitative Possibility Theory

qualitative possibilistic POMDP (π -POMDP)

Sabbadin (UAI-98) introduces

the qualitative possibilistic POMDP

π -POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T^\pi, O^\pi, \rho \rangle$

- **transition** function $T^\pi(s, a, s') = \pi(s' \mid s, a) \in \mathcal{L}$
 - **observation** function $O^\pi(s', a, o') = \pi(o' \mid s', a) \in \mathcal{L}$
 - **preference** function $\rho : \mathcal{S} \times \mathcal{A} \rightarrow \mathcal{L}$
-
- belief space trick: POMDP \rightarrow MDP with **infinite** space
 π -POMDP $\rightarrow \pi$ -MDP with **finite** space
 - $\forall s \in \mathcal{S}, \pi(s) = 1 \Leftrightarrow$ total ignorance about s

A possibilistic belief state

finite belief space

$$\Pi_{\mathcal{L}}^{\mathcal{S}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_{\mathcal{L}}^{\mathcal{S}} \sim \# \mathcal{L}^{\# \mathcal{S}} < +\infty$$

→ *i.e.* **finite belief space**

A possibilistic belief state

finite belief space

$$\Pi_{\mathcal{L}}^{\mathcal{S}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_{\mathcal{L}}^{\mathcal{S}} \sim \# \mathcal{L}^{\# \mathcal{S}} < +\infty$$

→ *i.e.* **finite belief space**

$$b_t^{\pi}(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

A possibilistic belief state

finite belief space

$$\Pi_{\mathcal{L}}^{\mathcal{S}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_{\mathcal{L}}^{\mathcal{S}} \sim \# \mathcal{L}^{\# \mathcal{S}} < +\infty$$

→ *i.e.* **finite belief space**

$$b_t^{\pi}(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

possibilistic belief update – a selected, o' received

joint distribution on $\mathcal{S} \times \mathcal{O}$ from b_t^{π} : $\pi(o', s' \mid b_t^{\pi}, a)$

A possibilistic belief state

finite belief space

$$\Pi_{\mathcal{L}}^{\mathcal{S}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_{\mathcal{L}}^{\mathcal{S}} \sim \# \mathcal{L}^{\# \mathcal{S}} < +\infty$$

→ i.e. **finite belief space**

$$b_t^{\pi}(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

possibilistic belief update – a selected, o' received

joint distribution on $\mathcal{S} \times \mathcal{O}$ from b_t^{π} : $\pi(o', s' \mid b_t^{\pi}, a)$

→ **next belief state**: $b_{t+1}^{\pi}(s') = \pi(o', s' \mid b_t^{\pi}, a)$

unless s' maximizes $\pi(o', s' \mid b_t^{\pi}, a)$, then $b_{t+1}^{\pi}(s') = 1$

denoted by $b_{t+1}^{\pi}(s') \propto^{\pi} \pi(o', s' \mid b_t^{\pi}, a)$

A possibilistic belief state

finite belief space

$$\Pi_{\mathcal{L}}^{\mathcal{S}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_{\mathcal{L}}^{\mathcal{S}} \sim \# \mathcal{L}^{\# \mathcal{S}} < +\infty$$

→ i.e. **finite belief space**

$$b_t^{\pi}(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

possibilistic belief update – a selected, o' received

joint distribution on $\mathcal{S} \times \mathcal{O}$ from b_t^{π} : $\pi(o', s' \mid b_t^{\pi}, a)$

→ **next belief state**: $b_{t+1}^{\pi}(s') = \pi(o', s' \mid b_t^{\pi}, a)$

unless s' maximizes $\pi(o', s' \mid b_t^{\pi}, a)$, then $b_{t+1}^{\pi}(s') = 1$

denoted by $b_{t+1}^{\pi}(s') \propto^{\pi} \pi(o', s' \mid b_t^{\pi}, a)$

■ the update **only depends on** o' , a and b_t^{π}

Qualitative Possibility Theory:

→ simplification, imprecision/prior ignorance modeling

Qualitative Possibility Theory:


→ simplification, imprecision/prior ignorance modeling

- 1 example of a qualitative possibilistic model
- 2 advancements and first use of the π -POMDP model
- 3 simplify computation: ADDs and factorization
- 4 probabilistic-possibilistic (hybrid) approach
- 5 conclusion/perspectives

- 1 Context
- 2 Introductory example (HMI)
- 3 Advances in the qualitative possibilistic MDPs
- 4 Symbolic solver and factorization
- 5 A hybrid model
- 6 Conclusion/Perspectives


Example: Human-Machine Interaction

joint work with Sergio Pizziol – Context



Example: Human-Machine Interaction


joint work with Sergio Pizziol – Context



Issue: incorrect human assessment of the machine state
→ **accident**

Example: Human-Machine Interaction

joint work with Sergio Pizziol – Context



Issue: incorrect human assessment of the machine state
→ **accident**

π -POMDP without actions: π -Hidden Markov Process

- **system space** \mathcal{S} : set of human assessments → **hidden**
- **observation space** \mathcal{O} : feedbacks/human manipulations

Example: Human-Machine Interaction

Human error model from expert knowledge

Machine with states A, B, C, \dots

state $s_A \in \mathcal{S}$: "human thinks machine state is A "

Example: Human-Machine Interaction

Human error model from expert knowledge

Machine with states A, B, C, \dots

state $s_A \in \mathcal{S}$: "human thinks machine state is A "

Machine state transition $A \rightarrow B$

■ observation: **machine feedback** $o'_f \in \mathcal{O}$:

human usually aware of feedbacks $\rightarrow \pi(s'_B, o'_f \mid s_A) = 1$

but may lose a feedback $\rightarrow \pi(s'_A, o'_f \mid s_A) = \frac{2}{3}$

Example: Human-Machine Interaction

Human error model from expert knowledge

Machine with states A, B, C, \dots

state $s_A \in \mathcal{S}$: "human thinks machine state is A "

Machine state transition $A \rightarrow B$

■ observation: **machine feedback** $o'_f \in \mathcal{O}$:

human usually aware of feedbacks $\rightarrow \pi(s'_B, o'_f \mid s_A) = 1$

but may lose a feedback $\rightarrow \pi(s'_A, o'_f \mid s_A) = \frac{2}{3}$

■ observation: **human manipulation** $o'_m \in \mathcal{O}$:

manipulation o'_m normal under $s_A \rightarrow \pi(s'_B, o'_m \mid s_A) = 1$

anormal manipulation $= \frac{1}{3}$

Example: Human-Machine Interaction

Human error model from expert knowledge

Machine with states A, B, C, \dots

state $s_A \in \mathcal{S}$: "human thinks machine state is A "

Machine state transition $A \rightarrow B$

■ observation: **machine feedback** $o'_f \in \mathcal{O}$:

human usually aware of feedbacks $\rightarrow \pi(s'_B, o'_f \mid s_A) = 1$

but may lose a feedback $\rightarrow \pi(s'_A, o'_f \mid s_A) = \frac{2}{3}$


■ observation: **human manipulation** $o'_m \in \mathcal{O}$:

manipulation o'_m normal under $s_A \rightarrow \pi(s'_B, o'_m \mid s_A) = 1$


anormal manipulation $= \frac{1}{3}$

■ impossible cases: possibility degree 0

Qualitative Possibilistic Hidden Markov Process: diagnosis tool for Human-Machine interaction (with Sergio Pizziol)



Qualitative Possibilistic Hidden Markov Process: diagnosis tool for Human-Machine interaction (with Sergio Pizziol)




- **estimation** of the human assessment
 \Leftrightarrow **possibilistic belief state**
- **detection** of human assessment errors + **diagnosis**
- validated with pilots on a flight simulator missions

- 1 Context
- 2 Introductory example (HMI)
- 3 Advances in the qualitative possibilistic MDPs
- 4 Symbolic solver and factorization
- 5 A hybrid model
- 6 Conclusion/Perspectives

Mixed-Observability (MOMDP) – Ong et al. (RSS-05)

π -Mixed-Observable Markov Decision Process (π -MOMDP)

contribution (UAI-13):




Mixed-Observability: system state $s \in \mathcal{S} = \mathcal{S}_v \times \mathcal{S}_h$
i.e. state s = visible component s_v & hidden component s_h

Mixed-Observability (MOMDP) – Ong et al. (RSS-05)

π -Mixed-Observable Markov Decision Process (π -MOMDP)

contribution (UAI-13):




Mixed-Observability: system state $s \in \mathcal{S} = \mathcal{S}_v \times \mathcal{S}_h$
i.e. state s = visible component s_v & hidden component s_h

- belief states only over \mathcal{S}_h (component s_v observed)

Mixed-Observability (MOMDP) – Ong et al. (RSS-05)

π -Mixed-Observable Markov Decision Process (π -MOMDP)

contribution (UAI-13):



Mixed-Observability: system state $s \in \mathcal{S} = \mathcal{S}_v \times \mathcal{S}_h$
i.e. state s = visible component s_v & hidden component s_h

- belief states only over \mathcal{S}_h (component s_v observed)
- $\rightarrow \pi$ -POMDP: belief space $\Pi_{\mathcal{L}}^{\mathcal{S}}$ $\#\Pi_{\mathcal{L}}^{\mathcal{S}} \sim \#\mathcal{L}^{\#\mathcal{S}}$
- $\rightarrow \pi$ -MOMDP: computations on $\mathcal{X} = \mathcal{S}_v \times \Pi_{\mathcal{L}}^{\mathcal{S}_h}$
 $\#\mathcal{X} \sim \#\mathcal{S}_v \cdot \#\mathcal{L}^{\#\mathcal{S}_h} \ll \#\Pi_{\mathcal{L}}^{\mathcal{S}}$

contribution (UAI-13): undeterminate Horizon

contribution (UAI-13): undeterminate Horizon

Dynamic Programming scheme: $\# \text{ iterations} < \#\mathcal{X}$

- assumption: \exists artificial “**stay**” action
as in classical planning/ γ counterpart
- criterion **non decreasing** with iterations

contribution (UAI-13): undeterminate Horizon

Dynamic Programming scheme: $\# \text{ iterations} < \#\mathcal{X}$



- assumption: \exists artificial “**stay**” action
as in classical planning/ γ counterpart
- criterion **non decreasing** with iterations
- action update for states increasing the criterion
- proof of optimality

Use of the π -MOMDP in practice

simulations

- **goal:** reach the object $A = T1$ or $T2$
- noisy observations of the location of the object A

Recognition mission: robot on a grid, targets $T1$ & $T2$



in reality, misperception probability in the error zone: $P_{bad} > \frac{1}{2}$


- 1 Context
- 2 Introductory example (HMI)
- 3 Advances in the qualitative possibilistic MDPs
- 4 Symbolic solver and factorization**
- 5 A hybrid model
- 6 Conclusion/Perspectives

Factored π -MOMDP and computations with ADDs

qualitative possibilistic models to reduce complexity

contribution (AAAI-14): factored π -MOMDP

\Leftrightarrow state space $\mathcal{X} = \mathcal{S}_v \times \Pi_{\mathcal{L}}^{\mathcal{S}_h} =$ Boolean variables (X_1, \dots, X_n)
+ independence assumptions \Leftarrow graphical model




Factored π -MOMDP and computations with ADDs

qualitative possibilistic models to reduce complexity

contribution (AAAI-14): factored π -MOMDP


\Leftrightarrow state space $\mathcal{X} = \mathcal{S}_v \times \Pi_{\mathcal{L}}^{\mathcal{S}_h} =$ Boolean variables (X_1, \dots, X_n)
+ independence assumptions \Leftarrow graphical model



- **factorization:** transition functions $T_i^a = \pi(X'_i \mid \text{parents}(X'_i), a)$ stored as **Algebraic Decision Diagrams (ADD)**

probabilistic case:

SPUDD, *Hoey et al., UAI-99*



Simplify computations with π -MOMDPs

Resulting π -MOMDP solver: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created
 \Rightarrow number of ADDs leaves **potentially huge**
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite
 \Rightarrow number of leaves bounded, **ADDs smaller**.

Simplify computations with π -MOMDPs

Resulting π -MOMDP solver: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created
 \Rightarrow number of ADDs leaves **potentially huge**
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite
 \Rightarrow number of leaves bounded, **ADDs smaller**.

PPUDD: Possibilistic Planning Using Decision Diagrams

- factorization \Rightarrow each DP steps divided into n stages
 \rightarrow smaller ADDs \Rightarrow **faster computations**

Simplify computations with π -MOMDPs

Resulting π -MOMDP solver: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created
 \Rightarrow number of ADDs leaves **potentially huge**
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite
 \Rightarrow number of leaves bounded, **ADDs smaller**.

PPUDD: Possibilistic Planning Using Decision Diagrams


- factorization \Rightarrow each DP steps divided into n stages
 \rightarrow smaller ADDs \Rightarrow **faster computations**
- computations on trees: *CU Decision Diagram Package*.

Simplifying computations with π -MOMDPs

Natural factorization: belief independence

contribution (AAAI-14):

independent sensors, hidden states, ... \Rightarrow graphical model



Simplifying computations with π -MOMDPs


Natural factorization: belief independence

contribution (AAAI-14):

independent sensors, hidden states, ... \Rightarrow graphical model

d-Separation $\Rightarrow (s_v, \beta) = (s_{v,1}, \dots, s_{v,m}, \beta_1, \dots, \beta_l)$

$\beta_i \in \Pi_{\mathcal{L}}^{s_{h,i}}$, belief over $s_{h,i}$



Simplify computations with π -MOMDPs

Experiments – perfect sensing: Navigation problem

PPUDD vs SPUDD *Hoey et al.*

Navigation benchmark: reach a goal – spots with accident risk
M1 (resp. M2) optimistic (resp. cautious) criterion

Simplify computations with π -MOMDPs


Experiments – perfect sensing: Navigation problem

PPUDD vs SPUDD *Hoey et al.*


Navigation benchmark: reach a goal – spots with accident risk
M1 (resp. M2) optimistic (resp. cautious) criterion

Performances, function of the instance size

reached goal frequency




steps to reach the goal




Simplify computations with π -MOMDPs

Experiments – perfect sensing: Navigation problem

computation time



max size of ADDs



- PPUDD + M2 (pessimistic criterion)
faster with same performances as SPUDD
- SPUDD only solves the first 5 instances
- verified intuition: ADDs are smaller

Simplify computations with π -MOMDPs

Experiments – imperfect sensing: RockSample problem

PPUDD vs APPL *Kurniawati et al.*, solver MOMDP

symbolic HSVI *Sim et al.*, solver POMDP

RockSample benchmark: recognize and sample “good” rocks

Simplify computations with π -MOMDPs

Experiments – imperfect sensing: RockSample problem


PPUDD vs APPL *Kurniawati et al.*, solver MOMDP

symbolic HSVI *Sim et al.*, solver POMDP

RockSample benchmark: recognize and sample “good” rocks


computation time:

probabilistic solvers, prec. 1
PPUDD, exact resolution



average of rewards

APPL stopped when
PPUDD end



- **approximate model + exact resolution solver**
→ improvement of computation time and performances

IPPC 2014 – ADD-based approaches: PPUDD vs symbolic LRTDP

PPUDD + BDD mask over reachable states.




Figure : average of rewards over simulations

- 1 Context
- 2 Introductory example (HMI)
- 3 Advances in the qualitative possibilistic MDPs
- 4 Symbolic solver and factorization
- 5 A hybrid model**
- 6 Conclusion/Perspectives

Qualitative possibilistic approach: benefits/drawbacks towards a hybrid POMDP

- **granulated** belief space (discrete)
- efficient problem **simplification** (PPUDD 2× better than LRTDP with ADDs)
- **ignorance and imprecision** modeling

Qualitative possibilistic approach: benefits/drawbacks towards a hybrid POMDP

- **granulated** belief space (discrete)
 - efficient problem **simplification** (PPUDD 2× better than LRTDP with ADDs)
 - **ignorance and imprecision** modeling
-
- ADD methods \prec state space search methods
→ winners of IPPC 2014: 2× better than PPUDD
 - choice of the qualitative criterion (optimistic/pessimistic)
 - preference → non additive degrees
→ same scale as possibility degrees (commensurability)
 - coarse approximation of probabilistic model
→ no frequentist information

A hybrid model

a probabilistic POMDP with possibilistic belief states

hybrid approach

- agent knowledge = possibilistic belief states
- probabilistic dynamics & quantitative rewards

A hybrid model

a probabilistic POMDP with possibilistic belief states

hybrid approach

- agent knowledge = possibilistic belief states
- probabilistic dynamics & quantitative rewards

Usefulness

- **heuristic** for solving POMDPs:
results in a standard (finite state space) MDP
- problem with **qualitative** & **quantitative** uncertainty

Transitions and rewards

belief-based transition and reward functions

- possibility distribution $\beta \rightarrow$ probability distribution $\bar{\beta}$
using poss-prob transformations (*Dubois et al., FSS-92*)

Transition function on belief states

$$\Rightarrow \mathbf{p}(\beta' | \bar{\beta}, a) = \sum_{\substack{o' \text{ t.q.} \\ \text{update}(\beta, a, o') = \beta'}} \mathbf{p}(o' | \bar{\beta}, a)$$

Transitions and rewards

belief-based transition and reward functions

- possibility distribution $\beta \rightarrow$ probability distribution $\bar{\beta}$ using poss-prob transformations (*Dubois et al., FSS-92*)

Transition function on belief states

$$\Rightarrow \mathbf{p}(\beta' | \bar{\beta}, a) = \sum_{\substack{o' \text{ t.q.} \\ \text{update}(\beta, a, o') = \beta'}} \mathbf{p}(o' | \bar{\beta}, a)$$

- reward cautious according to β

Pessimistic Choquet Integral

$$r(\beta, a) = \sum_{i=1}^{\#\mathcal{L}-1} (l_i - l_{i+1}) \cdot \min_{\substack{s \in \mathcal{S} \text{ s.t.} \\ \beta(s) \geq l_i}} r(s, a)$$

Resulting MDP

translation from hybrid POMDP to MDP – **contribution (SUM-15):**

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

Resulting MDP

translation from hybrid POMDP to MDP – **contribution** (SUM-15):

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{L}}^{\mathcal{S}}$,
the set of the possibility distributions over \mathcal{S} ;

Resulting MDP

translation from hybrid POMDP to MDP – **contribution** (SUM-15):

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{L}}^{\mathcal{S}}$,
the set of the possibility distributions over \mathcal{S} ;
- $\forall \beta, \beta'$ possibilistic belief states $\in \Pi_{\mathcal{L}}^{\mathcal{S}}, \forall a \in \mathcal{A}$,
transitions $\tilde{T}(\beta, a, \beta') = \mathbf{p}(\beta' | \beta, a)$;

Resulting MDP

translation from hybrid POMDP to MDP – **contribution** (SUM-15):

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{L}}^{\mathcal{S}}$,
the set of the possibility distributions over \mathcal{S} ;
- $\forall \beta, \beta'$ possibilistic belief states $\in \Pi_{\mathcal{L}}^{\mathcal{S}}$, $\forall a \in \mathcal{A}$,
transitions $\tilde{T}(\beta, a, \beta') = \mathbf{p}(\beta' | \beta, a)$;
- **reward** $\tilde{r}(a, \beta) = \underline{Ch}(r(a, .))$,

Resulting MDP

translation from hybrid POMDP to MDP – **contribution (SUM-15)**:

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{L}}^{\mathcal{S}}$,
the set of the possibility distributions over \mathcal{S} ;
- $\forall \beta, \beta'$ possibilistic belief states $\in \Pi_{\mathcal{L}}^{\mathcal{S}}$, $\forall a \in \mathcal{A}$,
transitions $\tilde{T}(\beta, a, \beta') = \mathbf{p}(\beta' | \beta, a)$;
- **reward** $\tilde{r}(a, \beta) = \underline{Ch}(r(a, .))$,

$$\text{criterion: } \mathbb{E}_{\beta_t \sim \tilde{T}} \left[\sum_{t=0}^{+\infty} \gamma^t \cdot \tilde{r}(\beta_t, d_t) \right].$$

General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: visible $s'_v \in \mathbb{S}_v$

s'_v

inferred hidden $s'_h \in \mathbb{S}_h$

s'_h


fully hidden $s'_f \in \mathbb{S}_f$

s'_f

General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: visible $s'_v \in \mathbb{S}_v$



inferred hidden $s'_h \in \mathbb{S}_h$




fully hidden $s'_f \in \mathbb{S}_f$



General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: visible $s'_v \in \mathbb{S}_v$



$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$

inferred hidden $s'_h \in \mathbb{S}_h$



fully hidden $s'_f \in \mathbb{S}_f$




General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable

$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$



fully hidden $s'_f \in \mathbb{S}_f$




General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization


variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable

$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$



fully hidden $s'_f \in \mathbb{S}_f$




General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$


\Leftrightarrow deterministic belief variable

$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$\beta_{t+1}(\text{parents}(o'_i)) = \beta_{t+1}(s_h, s_h^a, s_h^b, s_h^c)$$



fully hidden $s'_f \in \mathbb{S}_f$




General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable


$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$\beta_{t+1}(\text{parents}(o'_i)) = \beta_{t+1}(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \text{parents}(o'_i) | \beta_t, a)$$



fully hidden $s'_f \in \mathbb{S}_f$




General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable


$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$\beta_{t+1}(\text{parents}(o'_i)) = \beta_{t+1}(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \text{parents}(o'_i) | \beta_t, a)$$



⚠ $\mathcal{P}(o'_i)$ may contain visible variables.

fully hidden $s'_f \in \mathbb{S}_f$




General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable


$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$\beta_{t+1}(\text{parents}(o'_i)) = \beta_{t+1}(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \text{parents}(o'_i) | \beta_t, a)$$



⚠ $\mathcal{P}(o'_i)$ may contain visible variables.

fully hidden $s'_f \in \mathbb{S}_f$




General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable

$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$




inferred hidden $s'_h \in \mathbb{S}_h$

$$\beta_{t+1}(\text{parents}(o'_i)) = \beta_{t+1}(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \text{parents}(o'_i) | \beta_t, a)$$

⚠ $\mathcal{P}(o'_i)$ may contain visible variables.



fully hidden $s'_f \in \mathbb{S}_f$



$$\beta_{t+1}(s'_f) = \pi(s'_f | \beta_t, a)$$


General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable


$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$\beta_{t+1}(\text{parents}(o'_i)) = \beta_{t+1}(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \text{parents}(o'_i) | \beta_t, a)$$



⚠ $\mathcal{P}(o'_i)$ may contain visible variables.

fully hidden $s'_f \in \mathbb{S}_f$

\rightarrow observations don't
inform belief state on s'_f .



$$\beta_{t+1}(s'_f) = \pi(s'_f | \beta_t, a)$$

Possibilistic belief variables

global belief state

bound over the global belief state

$$\beta_{t+1}(s'_1, \dots, s'_n) = \pi(s'_1, \dots, s'_n \mid a_0, o_1, \dots, a_t, o_{t+1})$$

$$\leq \min \left\{ \min_{s'_j \in \mathbb{S}_v} \left[\mathbb{1}_{\{s'_j = o'_j\}} \right], \min_{s'_j \in \mathbb{S}_f} \left[\beta_{t+1}(s'_j) \right], \min_{o'_i \in \mathbb{O}_h} \left[\beta_{t+1}(\text{parents}(o'_i)) \right] \right\}$$

Possibilistic belief variables

global belief state

bound over the global belief state

$$\beta_{t+1}(s'_1, \dots, s'_n) = \pi(s'_1, \dots, s'_n \mid a_0, o_1, \dots, a_t, o_{t+1})$$

$$\leq \min \left\{ \min_{s'_j \in \mathbb{S}_v} \left[\mathbb{1}_{\{s'_j = o'_j\}} \right], \min_{s'_j \in \mathbb{S}_f} \left[\beta_{t+1}(s'_j) \right], \min_{o'_i \in \mathbb{O}_h} \left[\beta_{t+1}(\text{parents}(o'_i)) \right] \right\}$$

- min of marginals = a **less informative** belief state
- computed using **marginal belief states**
 - **factorization & smaller state space**

- 1 Context
- 2 Introductory example (HMI)
- 3 Advances in the qualitative possibilistic MDPs
- 4 Symbolic solver and factorization
- 5 A hybrid model
- 6 Conclusion/Perspectives

- **modeling efforts:** → human-machine interaction

- **modeling efforts:** → human-machine interaction
- **advancements:** → mixed-observability modeling
→ undeterminate horizon + optimality proof

- **modeling efforts:** → human-machine interaction
- **advancements:** → mixed-observability modeling
→ undeterminate horizon + optimality proof
- **simplifying computations:** factorization work
& PPUDD algorithm

- **modeling efforts:** → human-machine interaction
- **advancements:** → mixed-observability modeling
→ undeterminate horizon + optimality proof
- **simplifying computations:** factorization work
& PPUDD algorithm
- **experimentations:** real problems
→ robust recognition mission with possibilistic beliefs
→ validation of the computation time reduction
→ IPPC 2014

- **modeling efforts:** → human-machine interaction
- **advancements:** → mixed-observability modeling
→ undeterminate horizon + optimality proof
- **simplifying computations:** factorization work
& PPUDD algorithm
- **experimentations:** real problems
→ robust recognition mission with possibilistic beliefs
→ validation of the computation time reduction
→ IPPC 2014
- **hybrid POMDP** $\xrightarrow{\text{translation}}$ MDP
→ probabilities on possibilistic belief states
pessimistic rewards (Choquet integral)
→ factored POMDP $\xrightarrow{\text{translation}}$ factored MPD

- *Qualitative Possibilistic Mixed-Observable MDPs*, UAI-2013
- *Structured Possibilistic Planning Using Decision Diagrams*, AAAI-2014
- *Planning in Partially Observable Domains with Fuzzy Epistemic States and Probabilistic Dynamics*, SUM-2015
- *Processus Décisionnels de Markov Possibilistes à Observabilité Mixte*, Revue d'Intelligence Artificielle (RIA)
- *A Possibilistic Estimation of Human Attentional Errors*, submitted to IEEE-TFS

- refined criteria (*Weng UAI-05, Dubois et al. EJOR-05*)
⇒ finer π -POMDP
- link with statistical learning in practice

- refined criteria (*Weng UAI-05, Dubois et al. EJOR-05*)
⇒ finer π -POMDP
- link with statistical learning in practice

quantitative information may be available: hybrid work

- IPPC problems (factored POMDPs);
- tests of this approach:
 - 1 **simplification:** π distributions definition?
 - 2 **imprecision:** robust in practice?

Thank you!