

$\partial_t \psi + \frac{M}{\epsilon} \int_{\Omega} \frac{|u(x,t)|^2}{2} \psi \Delta \psi + \int_{\Omega} p = 0, \quad \nabla \psi = 0, \quad \psi(x,0) = \psi_0(x), \quad \psi(x,t) \in \mathbb{R}$

Exploiting Imprecise Information Sources in Sequential Decision Making Problems under Uncertainty

N.Drougard

under D.Dubois, J-L.Farges and F.Teichteil-Königsbuch supervision

doctoral school: EDSYS institution: ISAE-SUPAERO

laboratory: ONERA-The French Aerospace Lab



retour sur innovation

Context

Autonomous robotics

Onera, System Control & Flight Dynamics Department

Control Engineering, Artificial intelligence, Cognitive Sciences

Context

Autonomous robotics

Onera, System Control & Flight Dynamics Department


Control Engineering, Artificial intelligence, Cognitive Sciences

- autonomy and human factors
- decision making, planning
- experimental/industrial applications: UAVs, exploration robots, human-machine interaction



Context


Partially Observable Markov Decision Processes (POMDPs)



POMDP: model for autonomous robotics

Context

Partially Observable Markov Decision Processes (POMDPs)




POMDP: model for autonomous robotics



$s \in \mathcal{S}$: **system states**


Context

Partially Observable Markov Decision Processes (POMDPs)




Context

Partially Observable Markov Decision Processes (POMDPs)




Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)



Context

Partially Observable Markov Decision Processes (POMDPs)



Context

belief state, strategy, criterion

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$ (*Smallwood et al. 1973*)

- **transition** function $T(s, a, s') = \mathbf{p}(s' \mid s, a)$
- **observation** function $O(s', a, o') = \mathbf{p}(o' \mid s', a)$
- **reward** function $r(s, a) \in \mathbb{R}$

Context

belief state, strategy, criterion

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$ (*Smallwood et al. 1973*)

- **transition** function $T(s, a, s') = \mathbf{p}(s' \mid s, a)$
- **observation** function $O(s', a, o') = \mathbf{p}(o' \mid s', a)$
- **reward** function $r(s, a) \in \mathbb{R}$

belief state: $b_t(s) = \mathbb{P}(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$

Context

belief state, strategy, criterion

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$ (Smallwood et al. 1973)

- **transition** function $T(s, a, s') = \mathbf{p}(s' \mid s, a)$
- **observation** function $O(s', a, o') = \mathbf{p}(o' \mid s', a)$
- **reward** function $r(s, a) \in \mathbb{R}$

belief state: $b_t(s) = \mathbb{P}(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$

probabilistic belief update

b_t
 T, O

Context

belief state, strategy, criterion

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$ (Smallwood et al. 1973)

- **transition** function $T(s, a, s') = \mathbf{p}(s' \mid s, a)$
- **observation** function $O(s', a, o') = \mathbf{p}(o' \mid s', a)$
- **reward** function $r(s, a) \in \mathbb{R}$

belief state: $b_t(s) = \mathbb{P}(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$

probabilistic belief update

$$\begin{array}{c} b_t \\ T, O \end{array} \begin{array}{c} \longrightarrow \\ \longrightarrow \end{array} \mathbf{p}(s', o' \mid b_t, a_t)$$

Context



belief state, strategy, criterion

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$ (Smallwood et al. 1973)

- **transition** function $T(s, a, s') = \mathbf{p}(s' | s, a)$
- **observation** function $O(s', a, o') = \mathbf{p}(o' | s', a)$
- **reward** function $r(s, a) \in \mathbb{R}$

belief state: $b_t(s) = \mathbb{P}(s_t = s | a_0, o_1, \dots, a_{t-1}, o_t)$

probabilistic belief update



Context


belief state, strategy, criterion

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$ (Smallwood et al. 1973)


- **transition** function $T(s, a, s') = \mathbf{p}(s' | s, a)$
- **observation** function $O(s', a, o') = \mathbf{p}(o' | s', a)$
- **reward** function $r(s, a) \in \mathbb{R}$

belief state: $b_t(s) = \mathbb{P}(s_t = s | a_0, o_1, \dots, a_{t-1}, o_t)$

probabilistic belief update



probabilistic normalization



Context


belief state, strategy, criterion

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$ (Smallwood et al. 1973)


- **transition** function $T(s, a, s') = \mathbf{p}(s' | s, a)$
- **observation** function $O(s', a, o') = \mathbf{p}(o' | s', a)$
- **reward** function $r(s, a) \in \mathbb{R}$

belief state: $b_t(s) = \mathbb{P}(s_t = s | a_0, o_1, \dots, a_{t-1}, o_t)$

probabilistic belief update



probabilistic normalization



strategy $d_t : b_t \mapsto a_t \in \mathcal{A}$

$$\text{maximizing } \mathbb{E}_{s_0 \sim b_0} \left[\sum_{t=0}^{+\infty} \gamma^t \cdot r(s_t, \delta(b_t)) \right], \quad 0 < \gamma < 1$$

Flaws of the POMDP model

POMDPs in practice

- optimal strategy computation **PSPACE-hard**
(*Papadimitriou et al., 1987*)
- conditional probabilities are **imprecisely known**
- **prior ignorance** semantic/management?

Context

practical issues: Complexity, Vision and Initial Belief

- **POMDP optimal strategy computation undecidable**
in infinite horizon (*Madani et al. 1999*)

Context

practical issues: Complexity, Vision and Initial Belief

- **POMDP optimal strategy computation undecidable**
in infinite horizon (*Madani et al. 1999*)

- optimality for “small” or “structured” POMDPs
- approximate computations

■ Imprecise model, e.g. vision from statistical learning



■ Imprecise model, e.g. vision from statistical learning

→ images in the database representative enough of the reality?



■ Imprecise model, e.g. vision from statistical learning

→ images in the database representative enough of the reality?



■ Lack of prior information on the system state: initial belief state b_0

■ Imprecise model, e.g. vision from statistical learning

→ images in the database representative enough of the reality?



■ Lack of prior information on the system state:

initial belief state b_0


→ uniform probability distribution \neq **ignorance!**

Qualitative Possibility Theory

presentation – (max,min) “tropical” algebra

finite scale \mathcal{L}

usually $\{0, \frac{1}{k}, \frac{2}{k}, \dots, 1\}$



events $E \subset \Omega$ (universe)

sorted using possibility **degrees** $\Pi(E) \in \mathcal{L}$

\neq


quantified with **frequencies** $\mathbb{P}(E) \in [0, 1]$ (probabilities)

Qualitative Possibility Theory

presentation – (max,min) “tropical” algebra

finite scale \mathcal{L}

usually $\{0, \frac{1}{k}, \frac{2}{k}, \dots, 1\}$



events $E \subset \Omega$ (universe)

sorted using possibility **degrees** $\Pi(E) \in \mathcal{L}$

\neq

quantified with **frequencies** $\mathbb{P}(E) \in [0, 1]$ (probabilities)

$$\Pi(E) = \max_{e \in E} \Pi(\{e\}) = \max_{e \in E} \pi(e)$$

Qualitative Possibility Theory

Criteria from special cases of Sugeno integral

Probability / Qualitative Possibility Theories

$+$	\max
\times	\min
$\sum_x \mathbf{p}(x) = 1$	$\max_x \pi(x) = 1$
$X \in \mathbb{R}$	$X \in \mathcal{L}$
$\mathbb{P}(A) = 1 - \mathbb{P}(\bar{A})$	$\mathcal{N}(A) = 1 - \Pi(\bar{A})$ (necessity)
$\mathbb{E}[X] = \sum_x x \cdot \mathbf{p}(x)$	optimistic: $\mathbb{S}_{\Pi}[X] = \max_{x \in X} \min \{x, \pi(x)\}$ pessimistic: $\mathbb{S}_{\mathcal{N}}[X] = \min_{x \in X} \max \{x, 1 - \pi(x)\}$

Qualitative Possibility Theory

qualitative possibilistic POMDP (π -POMDP)

Sabbadin (UAI-98) introduces

the qualitative possibilistic POMDP

π -POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T^\pi, O^\pi, \rho \rangle$

Qualitative Possibility Theory

qualitative possibilistic POMDP (π -POMDP)

Sabbadin (UAI-98) introduces

the qualitative possibilistic POMDP

π -POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T^\pi, O^\pi, \rho \rangle$

- **transition** function $T^\pi(s, a, s') = \pi(s' \mid s, a) \in \mathcal{L}$
- **observation** function $O^\pi(s', a, o') = \pi(o' \mid s', a) \in \mathcal{L}$
- **preference** function $\rho : \mathcal{S} \times \mathcal{A} \rightarrow \mathcal{L}$

Qualitative Possibility Theory

qualitative possibilistic POMDP (π -POMDP)

Sabbadin (UAI-98) introduces

the qualitative possibilistic POMDP

π -POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T^\pi, O^\pi, \rho \rangle$

- **transition** function $T^\pi(s, a, s') = \pi(s' \mid s, a) \in \mathcal{L}$
 - **observation** function $O^\pi(s', a, o') = \pi(o' \mid s', a) \in \mathcal{L}$
 - **preference** function $\rho : \mathcal{S} \times \mathcal{A} \rightarrow \mathcal{L}$
-
- belief space trick: POMDP \Leftrightarrow MDP with **infinite** space
 π -POMDP $\Leftrightarrow \pi$ -MDP with **finite** space
 - problem becomes **decidable**

Qualitative Possibility Theory

qualitative possibilistic POMDP (π -POMDP)

Sabbadin (UAI-98) introduces

the qualitative possibilistic POMDP

π -POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T^\pi, O^\pi, \rho \rangle$

- **transition** function $T^\pi(s, a, s') = \pi(s' \mid s, a) \in \mathcal{L}$
 - **observation** function $O^\pi(s', a, o') = \pi(o' \mid s', a) \in \mathcal{L}$
 - **preference** function $\rho : \mathcal{S} \times \mathcal{A} \rightarrow \mathcal{L}$
-
- belief space trick: POMDP \Leftrightarrow MDP with **infinite** space
 π -POMDP $\Leftrightarrow \pi$ -MDP with **finite** space
 - problem becomes **decidable**

$\forall s \in \mathcal{S}, \pi(s) = 1 \Leftrightarrow$ total ignorance about s
each state possible, **none necessary**

A possibilistic belief state

finite belief space

$$\Pi_{\mathcal{L}}^{\mathcal{S}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_{\mathcal{L}}^{\mathcal{S}} \sim \# \mathcal{L}^{\# \mathcal{S}} < +\infty$$

\rightarrow *i.e.* **finite belief space**

A possibilistic belief state

finite belief space

$$\Pi_{\mathcal{L}}^{\mathcal{S}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_{\mathcal{L}}^{\mathcal{S}} \sim \# \mathcal{L}^{\# \mathcal{S}} < +\infty$$

→ *i.e.* **finite belief space**

$$\beta_t(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

A possibilistic belief state

finite belief space

$$\Pi_{\mathcal{L}}^{\mathcal{S}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_{\mathcal{L}}^{\mathcal{S}} \sim \# \mathcal{L}^{\# \mathcal{S}} < +\infty$$

→ *i.e.* **finite belief space**

$$\beta_t(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

possibilistic belief update

$$\beta_t$$
$$T^{\pi}, O^{\pi}$$

A possibilistic belief state

finite belief space

$$\Pi_{\mathcal{L}}^{\mathcal{S}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_{\mathcal{L}}^{\mathcal{S}} \sim \# \mathcal{L}^{\# \mathcal{S}} < +\infty$$

→ *i.e.* **finite belief space**

$$\beta_t(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

possibilistic belief update

$$\begin{array}{c} \beta_t \\ T^\pi, O^\pi \end{array} \begin{array}{c} \longrightarrow \\ \longrightarrow \end{array} \pi(s', o' \mid \beta_t, a_t)$$



A possibilistic belief state

finite belief space

$\Pi_{\mathcal{L}}^{\mathcal{S}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_{\mathcal{L}}^{\mathcal{S}} \sim \# \mathcal{L}^{\# \mathcal{S}} < +\infty$
 \rightarrow *i.e.* **finite belief space**

$$\beta_t(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

possibilistic belief update



A possibilistic belief state


finite belief space

$$\Pi_{\mathcal{L}}^{\mathcal{S}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_{\mathcal{L}}^{\mathcal{S}} \sim \# \mathcal{L}^{\# \mathcal{S}} < +\infty$$


→ *i.e.* **finite belief space**

$$\beta_t(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

possibilistic belief update



possibilistic normalization



A possibilistic belief state


finite belief space

$$\Pi_{\mathcal{L}}^{\mathcal{S}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_{\mathcal{L}}^{\mathcal{S}} \sim \# \mathcal{L}^{\# \mathcal{S}} < +\infty$$


→ *i.e.* **finite belief space**

$$\beta_t(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

possibilistic belief update



possibilistic normalization



- **Markovian update:** only depends on o_{t+1} , a_t and b_t^π

Overview

Qualitative Possibility Theory:

→ simplification, imprecision/prior ignorance modeling

Overview

Qualitative Possibility Theory:

→ simplification, imprecision/prior ignorance modeling

- context

- 1 introductory example: qualitative **possibilistic modeling**
→ *human-machine interaction (HMI)*
with **Sergio Pizziol**

- 2 **advances** in π -POMDP:
→ *mixed-observability & indefinite horizon*


- 3 **simplifying computations**:
→ *ADD-based solver & factorization*

- 4 **probabilistic-possibilistic** (*hybrid*) approach

- conclusion


Example: Human-Machine Interaction (HMI)

joint work with **Sergio Pizziol** – Context



Example: Human-Machine Interaction (HMI)


joint work with **Sergio Pizziol** – Context



Issue: incorrect human assessment of the machine state
→ **accident risk**

Example: Human-Machine Interaction (HMI)


joint work with **Sergio Pizziol** – Context



Issue: incorrect human assessment of the machine state
→ **accident risk**

Example: Human-Machine Interaction (HMI)

joint work with **Sergio Pizziol** – Context



Issue: incorrect human assessment of the machine state
→ **accident risk**

π -POMDP without actions: π -Hidden Markov Process

- **system space** \mathcal{S} : set of human assessments → **hidden**
- **observation space** \mathcal{O} : feedbacks/human manipulations

Example: Human-Machine Interaction (HMI)

Human error model from expert knowledge

Machine with states A, B, C, \dots

state $s_A \in \mathcal{S}$: “human thinks machine state is A ”

Example: Human-Machine Interaction (HMI)

Human error model from expert knowledge

Machine with states A, B, C, \dots

state $s_A \in \mathcal{S}$: “human thinks machine state is A ”

Machine state transition $A \rightarrow B$

■ observation: **machine feedback** $o'_f \in \mathcal{O}$:

“human usually aware of feedbacks” $\rightarrow \pi(s'_B, o'_f \mid s_A) = 1$

“but may lose a feedback” $\rightarrow \pi(s'_A, o'_f \mid s_A) = \frac{2}{3}$

Example: Human-Machine Interaction (HMI)

Human error model from expert knowledge

Machine with states A, B, C, \dots

state $s_A \in \mathcal{S}$: “human thinks machine state is A ”

Machine state transition $A \rightarrow B$

■ observation: **machine feedback** $o'_f \in \mathcal{O}$:

“human usually aware of feedbacks” $\rightarrow \pi(s'_B, o'_f \mid s_A) = 1$

“but may lose a feedback” $\rightarrow \pi(s'_A, o'_f \mid s_A) = \frac{2}{3}$

■ observation: **human manipulation** $o'_m \in \mathcal{O}$:

“manipulation o'_m is normal under s_A ” $\rightarrow \pi(s'_B, o'_m \mid s_A) = 1$

“is abnormal” $\rightarrow \pi(s'_A, o'_m \mid s_A) = \frac{1}{3}$

Example: Human-Machine Interaction (HMI)

Human error model from expert knowledge

Machine with states A, B, C, \dots

state $s_A \in \mathcal{S}$: “human thinks machine state is A ”

Machine state transition $A \rightarrow B$

■ observation: **machine feedback** $o'_f \in \mathcal{O}$:

“human usually aware of feedbacks” $\rightarrow \pi(s'_B, o'_f \mid s_A) = 1$

“but may lose a feedback” $\rightarrow \pi(s'_A, o'_f \mid s_A) = \frac{2}{3}$

■ observation: **human manipulation** $o'_m \in \mathcal{O}$:

“manipulation o'_m is normal under s_A ” $\rightarrow \pi(s'_B, o'_m \mid s_A) = 1$

“is abnormal” $\rightarrow \pi(s'_A, o'_m \mid s_A) = \frac{1}{3}$

■ impossible cases: possibility degree 0


Qualitative Possibilistic Hidden Markov Process:

π -HMP, detection & diagnosis tool for HMI (with Sergio Pizziol)

feedbacks/manipulations


(visible) {

human {
assessments
(hidden)



Qualitative Possibilistic Hidden Markov Process:

π -HMP, detection & diagnosis tool for HMI (with Sergio Pizziol)



- **estimation** of the human assessment
 \Leftrightarrow **possibilistic belief state**
- **detection** of human assessment errors + **diagnosis**
- validated with pilots on flight simulator missions

Applicability of the π -POMDPs

advances

- **lack of proof of optimality in indefinite horizon settings**
- criterion/proof
- **curse of dimensionality:**
 - belief space size of a π -POMDP: exponential in $\#\mathcal{S}$
- in practice, part of $s \in \mathcal{S}$ is visible
 - ⇒ complexity reduction

Applicability of the π -POMDPs

advances

- **lack of proof of optimality in indefinite horizon settings**
- criterion/proof
- **curse of dimensionality:**
 - belief space size of a π -POMDP: exponential in $\#\mathcal{S}$
- in practice, part of $s \in \mathcal{S}$ is visible
 - ⇒ complexity reduction

Applicability of the π -POMDPs

advances

- **lack of proof of optimality in indefinite horizon settings**
- criterion/proof
- **curse of dimensionality:**
 - belief space size of a π -POMDP: exponential in $\#\mathcal{S}$
- in practice, part of $s \in \mathcal{S}$ is visible
 - ⇒ complexity reduction

Indefinite Horizon, Mixed-Observability, Simulations
contribution UAI 2013

Proof of optimality under Indefinite Horizon

criterion, DP scheme, optimal strategy

indefinite horizon criterion $\Psi : \mathcal{S} \rightarrow \mathcal{L}$ terminal pref. func.

$$\forall s \in \mathcal{S}, \text{ maximizing } \mathbb{S}_{\Pi} \left[\Psi(S_{\# \delta}) \mid S_0 = s \right]$$

with respect to the strategy $\delta : (t, s) \mapsto a_t \in \mathcal{A}$.

Proof of optimality under Indefinite Horizon

criterion, DP scheme, optimal strategy

indefinite horizon criterion $\Psi : \mathcal{S} \rightarrow \mathcal{L}$ terminal pref. func.

$$\forall s \in \mathcal{S}, \text{ maximizing } \mathbb{S}_{\Pi} \left[\Psi(S_{\# \delta}) \mid S_0 = s \right]$$

$$= \max_{(s_1, \dots, s_{\# \delta})} \min \left\{ \min_{t=0}^{\# \delta - 1} \pi(s_{t+1} \mid s_t, \delta_t(s_t)), \Psi(s_{\# \delta}) \right\}$$

with respect to the strategy $\delta : (t, s) \mapsto a_t \in \mathcal{A}$.

Proof of optimality under Indefinite Horizon

criterion, DP scheme, optimal strategy

indefinite horizon criterion $\Psi : \mathcal{S} \rightarrow \mathcal{L}$ terminal pref. func.

$$\forall s \in \mathcal{S}, \text{ maximizing } \mathbb{S}_{\Pi} \left[\Psi(S_{\# \delta}) \mid S_0 = s \right]$$

$$= \max_{(s_1, \dots, s_{\# \delta})} \min \left\{ \min_{t=0}^{\# \delta - 1} \pi(s_{t+1} \mid s_t, \delta_t(s_t)), \Psi(s_{\# \delta}) \right\}$$

with respect to the strategy $\delta : (t, s) \mapsto a_t \in \mathcal{A}$.

Dynamic Programming scheme: $\# \text{ iterations} < \# \mathcal{S}$

- assumption: \exists artificial “**stay**” action
as in classical planning / γ counterpart
- criterion value **non decreasing** with iterations

Proof of optimality under Indefinite Horizon

criterion, DP scheme, optimal strategy

indefinite horizon criterion $\Psi : \mathcal{S} \rightarrow \mathcal{L}$ terminal pref. func.

$$\begin{aligned} \forall s \in \mathcal{S}, \text{ maximizing } \mathbb{S}_{\Pi} \left[\Psi(S_{\# \delta}) \mid S_0 = s \right] \\ = \max_{(s_1, \dots, s_{\# \delta})} \min \left\{ \min_{t=0}^{\# \delta - 1} \pi(s_{t+1} \mid s_t, \delta_t(s_t)), \Psi(s_{\# \delta}) \right\} \end{aligned}$$

with respect to the strategy $\delta : (t, s) \mapsto a_t \in \mathcal{A}$.


Dynamic Programming scheme: $\# \text{ iterations} < \# \mathcal{S}$

- assumption: \exists artificial “**stay**” action
as in classical planning / γ counterpart
- criterion value **non decreasing** with iterations
- action update for states increasing the criterion
- **proof of optimality** of the resulting **stationary** strategy

Scalability capabilities with Mixed-Observability

π -Mixed-Observable Markov Decision Process (π -MOMDP)

graphical model of a π -MOMDP:




Mixed-Observability (Ong et al., 2005): $s \in \mathcal{S} = \mathcal{S}_v \times \mathcal{S}_h$
i.e. state s = visible component s_v & hidden component s_h
 ■ belief states only over \mathcal{S}_h (component s_v observed)

Scalability capabilities with Mixed-Observability

π -Mixed-Observable Markov Decision Process (π -MOMDP)

graphical model of a π -MOMDP:



Mixed-Observability (Ong et al., 2005): $s \in \mathcal{S} = \mathcal{S}_v \times \mathcal{S}_h$
 i.e. state s = visible component s_v & hidden component s_h


- belief states only over \mathcal{S}_h (component s_v observed)
- $\rightarrow \pi$ -POMDP: belief space $\Pi_{\mathcal{L}}^{\mathcal{S}}$ $\# \Pi_{\mathcal{L}}^{\mathcal{S}} \sim \#\mathcal{L}^{\#\mathcal{S}}$
- $\rightarrow \pi$ -MOMDP: computations on $\mathcal{X} = \mathcal{S}_v \times \Pi_{\mathcal{L}}^{\mathcal{S}_h}$
 $\#\mathcal{X} \sim \#\mathcal{S}_v \cdot \#\mathcal{L}^{\#\mathcal{S}_h} \ll \#\Pi_{\mathcal{L}}^{\mathcal{S}}$

Experimental results

π -MOMDP for robotics with imprecise probabilities

- **goal:** reach the object $A = T1$ or $T2$
- noisy observations of the location of the object A

Recognition mission: robot on a grid, targets $T1$ & $T2$




models: observation accuracy decreases with distance to target

Experimental results

π -MOMDP for robotics with imprecise probabilities

- **goal:** reach the object $A = T1$ or $T2$
- noisy observations of the location of the object A

Recognition mission: robot on a grid, targets $T1$ & $T2$





models: observation accuracy decreases with distance to target
real model: takes into account the error zone ($P_{bad} > \frac{1}{2}$)

Experimental results

π -MOMDP for robotics with imprecise probabilities

- **goal:** reach the object $A = T1$ or $T2$
- noisy observations of the location of the object A

Recognition mission: robot on a grid, targets $T1$ & $T2$



models: observation accuracy decreases with distance to target

real model: takes into account the error zone ($P_{bad} > \frac{1}{2}$)



Experimental results

π -MOMDP for robotics with imprecise probabilities

- **goal:** reach the object A
- noisy observations of the

probabilistic model inappropriate when probabilities too imprecise

Recognition mission: robot on a grid, targets $T1$ & $T2$



models: observation accuracy decreases with distance to target


real model: takes into account the error zone ($P_{bad} > \frac{1}{2}$)

Factored π -MOMDP and computations with ADDs

qualitative possibilistic models to reduce complexity

contribution (AAAI-14): factored π -MOMDP

\Leftrightarrow state space $\mathcal{X} = \mathcal{S}_v \times \Pi_{\mathcal{L}}^{\mathcal{S}_h} = \text{Boolean variables } (X_1, \dots, X_n)$
 + independence assumptions \Leftarrow graphical model




Factored π -MOMDP and computations with ADDs

qualitative possibilistic models to reduce complexity

contribution (AAAI-14): factored π -MOMDP


\Leftrightarrow state space $\mathcal{X} = \mathcal{S}_v \times \prod_{\mathcal{L}^h} \mathcal{S}_h = \text{Boolean variables } (X_1, \dots, X_n)$
 + independence assumptions \Leftarrow graphical model



- **factorization:** transition functions $T_i^a = \pi(X'_i \mid \text{parents}(X'_i), a)$ stored as **Algebraic Decision Diagrams (ADD)**

probabilistic case:

SPUDD (Hoey et al., 1999)



example of ADD

Simplify computations with π -MOMDPs

Resulting π -MOMDP solver: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created
 \Rightarrow number of ADDs leaves **potentially huge**
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite
 \Rightarrow number of leaves bounded, **ADDs smaller**.

Simplify computations with π -MOMDPs

Resulting π -MOMDP solver: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created
 \Rightarrow number of ADDs leaves **potentially huge**
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite
 \Rightarrow number of leaves bounded, **ADDs smaller**.

PPUDD: Possibilistic Planning Using Decision Diagrams

- factorization \Rightarrow each DP step divided into n stages
 \rightarrow smaller ADDs \Rightarrow **faster computations**

Simplify computations with π -MOMDPs

Resulting π -MOMDP solver: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created
 \Rightarrow number of ADDs leaves **potentially huge**
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite
 \Rightarrow number of leaves bounded, **ADDs smaller**.

PPUDD: Possibilistic Planning Using Decision Diagrams


- factorization \Rightarrow each DP step divided into n stages
 \rightarrow smaller ADDs \Rightarrow **faster computations**
- computations on trees: *CU Decision Diagram Package*.

Simplifying computations with π -MOMDPs

Natural factorization: belief independence

contribution (AAAI-14):

independent sensors, hidden states, ... \Rightarrow graphical model



Simplifying computations with π -MOMDPs


Natural factorization: belief independence

contribution (AAAI-14):

independent sensors, hidden states, ... \Rightarrow graphical model

d-Separation $\Rightarrow (s_v, \beta) = (s_{v,1}, \dots, s_{v,m}, \beta_1, \dots, \beta_l)$

$\beta_i \in \Pi_{\mathcal{L}}^{s_{h,i}}$, belief over $s_{h,i}$



Simplifying computations with π -MOMDPs


Natural factorization: belief independence

$\perp\!\!\!\perp$ assumptions on state & observation variables

→ belief variable factorization

→ **additional** computation savings

$\beta_i \in \Pi_{\mathcal{L}}^{S_{h,i}}$, belief over $s_{h,i}$



Simplify computations with π -MOMDPs

Experiments – perfect sensing: Navigation problem

PPUDD vs SPUDD (*Hoey et al.*, 1999)

Navigation benchmark: reach a goal – spots with accident risk
M1 (resp. M2) optimistic (resp. pessimistic) criterion

Simplify computations with π -MOMDPs


Experiments – perfect sensing: Navigation problem

PPUDD vs SPUDD (*Hoey et al., 1999*)

Navigation benchmark: reach a goal – spots with accident risk
M1 (resp. M2) optimistic (resp. pessimistic) criterion


Performance, function of the problem index

reached goal frequency



higher is better

steps to reach the goal




lower is better

Simplify computations with π -MOMDPs


Experiments – perfect sensing: Navigation problem

computation time



lower is better

max size of ADDs



lower is better

- PPUDD + M2 (pessimistic criterion)
faster with same performance as SPUDD
- SPUDD only solves the first 5 instances
- verified intuition: ADDs are smaller

Simplify computations with π -MOMDPs

Experiments – imperfect sensing: RockSample problem

PPUDD vs APPL (*Kurniawati et al.*, 2008, solver MOMDP)

symbolic HSVI (*Sim et al.*, 2008, solver POMDP)

RockSample benchmark: recognize and sample “good” rocks

Simplify computations with π -MOMDPs


Experiments – imperfect sensing: RockSample problem

PPUDD vs APPL (*Kurniawati et al.*, 2008, solver MOMDP)

symbolic HSVI (*Sim et al.*, 2008, solver POMDP)


RockSample benchmark: recognize and sample “good” rocks

computation time:



lower is better

average of rewards









higher is better

- approximate model + exact resolution solver can be **better than** exact model + approximate resolution solver

IPPC 2014 – ADD-based approaches: PPUDD vs symbolic LRTDP







PPUDD + BDD mask over reachable states.



average of rewards over simulations — higher is better

IPPC 2014 – ADD-based approaches: PPUDD vs symbolic LRTDP

PPUDD outperforms its probabilistic counterpart



average of rewards over simulations — higher is better

Qualitative possibilistic approach: benefits/drawbacks towards a hybrid POMDP

- **granulated** belief space (discrete)
- efficient problem **simplification** (PPUDD 2× better than LRTDP with ADDs)
- **ignorance and imprecision** modeling

Qualitative possibilistic approach: benefits/drawbacks towards a hybrid POMDP

- **granulated** belief space (discrete)
 - efficient problem **simplification** (PPUDD 2× better than LRTDP with ADDs)
 - **ignorance and imprecision** modeling
-
- ADD methods \prec state space search methods
→ winners of IPPC 2014: 2× better than PPUDD
 - choice of the qualitative criterion (optimistic/pessimistic)
 - preference → non additive degrees
→ same scale as possibility degrees (commensurability)
 - coarse approximation of probabilistic model
→ no frequentist information

A hybrid model

a probabilistic POMDP with possibilistic belief states

hybrid approach

- agent knowledge = possibilistic belief states
- probabilistic dynamics & quantitative rewards

A hybrid model

a probabilistic POMDP with possibilistic belief states

hybrid approach

- agent knowledge = possibilistic belief states
- probabilistic dynamics & quantitative rewards

Usefulness

- **heuristic** for solving POMDPs:
results in a standard (finite state space) MDP
- problem with **qualitative** & **quantitative** uncertainty

Transitions and rewards

belief-based transition and reward functions

- possibility distribution $\beta \rightarrow$ probability distribution $\bar{\beta}$
using poss-prob transformations (*Dubois & Prade 1982*)

Transition function on belief states

$$\Rightarrow \mathbf{p}(\beta' | \bar{\beta}, a) = \sum_{\substack{o' \text{ t.q.} \\ \text{update}(\beta, a, o') = \beta'}} \mathbf{p}(o' | \bar{\beta}, a)$$

Transitions and rewards


belief-based transition and reward functions

- possibility distribution $\beta \rightarrow$ probability distribution $\bar{\beta}$ using poss-prob transformations (*Dubois & Prade 1982*)

Transition function on belief states

$$\Rightarrow \mathbf{p}(\beta' | \bar{\beta}, a) = \sum_{\substack{o' \text{ t.q.} \\ \text{update}(\beta, a, o') = \beta'}} \mathbf{p}(o' | \bar{\beta}, a)$$

- reward pessimistic according to β



Pessimistic Choquet Integral

$$r(\beta, a) = \sum_{i=1}^{\#\mathcal{L}-1} (\pi_i - \pi_{i+1}) \cdot \min_{B_i} r(s, a)$$

$$B_i = \{s \in \mathcal{S} \text{ s.t. } \beta(s) \geq \pi_i\}$$

Resulting MDP

translation from hybrid POMDP to MDP – **contribution (SUM-15):**

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$

Resulting MDP

translation from hybrid POMDP to MDP – **contribution (SUM-15):**

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{L}}^{\mathcal{S}}$

the set of the possibility distributions over \mathcal{S}

Resulting MDP

translation from hybrid POMDP to MDP – **contribution (SUM-15):**

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{L}}^{\mathcal{S}}$
the set of the possibility distributions over \mathcal{S}
- $\forall \beta, \beta'$ possibilistic belief states $\in \Pi_{\mathcal{L}}^{\mathcal{S}}, \forall a \in \mathcal{A}$
transitions $\tilde{T}(\beta, a, \beta') = \mathbf{p}(\beta' | \beta, a)$

Resulting MDP

translation from hybrid POMDP to MDP – **contribution (SUM-15):**

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{L}}^{\mathcal{S}}$
the set of the possibility distributions over \mathcal{S}
- $\forall \beta, \beta'$ possibilistic belief states $\in \Pi_{\mathcal{L}}^{\mathcal{S}}, \forall a \in \mathcal{A}$
transitions $\tilde{T}(\beta, a, \beta') = \mathbf{p}(\beta' | \beta, a)$
- **reward** $\tilde{r}(a, \beta) = \underline{Ch}(r(a, .))$

Resulting MDP

translation from hybrid POMDP to MDP – **contribution (SUM-15):**

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{L}}^{\mathcal{S}}$
the set of the possibility distributions over \mathcal{S}
- $\forall \beta, \beta'$ possibilistic belief states $\in \Pi_{\mathcal{L}}^{\mathcal{S}}, \forall a \in \mathcal{A}$
transitions $\tilde{T}(\beta, a, \beta') = \mathbf{p}(\beta' | \beta, a)$
- **reward** $\tilde{r}(a, \beta) = \underline{Ch}(r(a, .))$

$$\text{criterion: } \mathbb{E}_{\beta_t \sim \tilde{T}} \left[\sum_{t=0}^{+\infty} \gamma^t \cdot \tilde{r}(\beta_t, d_t) \right]$$

Belief variable factorization

3 classes of state variables – **contribution** (SUM-15)

variable: **visible** $s'_v \in \mathbb{S}_v$



inferred hidden $s'_h \in \mathbb{S}_h$




fully hidden $s'_f \in \mathbb{S}_f$



Belief variable factorization

3 classes of state variables – **contribution** (SUM-15)

variable: **visible** $s'_v \in \mathbb{S}_v$



inferred hidden $s'_h \in \mathbb{S}_h$




fully hidden $s'_f \in \mathbb{S}_f$



Belief variable factorization

3 classes of state variables – **contribution** (SUM-15)

variable: **visible** $s'_v \in \mathbb{S}_v$



$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$

inferred hidden $s'_h \in \mathbb{S}_h$



fully hidden $s'_f \in \mathbb{S}_f$




Belief variable factorization

3 classes of state variables – **contribution** (SUM-15)

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable

$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$



fully hidden $s'_f \in \mathbb{S}_f$




Belief variable factorization

3 classes of state variables – **contribution** (SUM-15)


variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable

$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$



fully hidden $s'_f \in \mathbb{S}_f$




Belief variable factorization

3 classes of state variables – contribution (SUM-15)

variable: **visible** $s'_v \in \mathbb{S}_v$


\Leftrightarrow deterministic belief variable

$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$\beta_{t+1}(\text{parents}(o'_i)) = \beta_{t+1}(s_h, s_h^a, s_h^b, s_h^c)$$



fully hidden $s'_f \in \mathbb{S}_f$




Belief variable factorization

3 classes of state variables – contribution (SUM-15)

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable


$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$\beta_{t+1}(\text{parents}(o'_i)) = \beta_{t+1}(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \text{parents}(o'_i) | \beta_t, a)$$



fully hidden $s'_f \in \mathbb{S}_f$




Belief variable factorization

3 classes of state variables – contribution (SUM-15)

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable


$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$\beta_{t+1}(\text{parents}(o'_i)) = \beta_{t+1}(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \text{parents}(o'_i) | \beta_t, a)$$



⚠ $\mathcal{P}(o'_i)$ may contain visible variables.

fully hidden $s'_f \in \mathbb{S}_f$




Belief variable factorization

3 classes of state variables – contribution (SUM-15)

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable


$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$\beta_{t+1}(\text{parents}(o'_i)) = \beta_{t+1}(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \text{parents}(o'_i) | \beta_t, a)$$



⚠ $\mathcal{P}(o'_i)$ may contain visible variables.

fully hidden $s'_f \in \mathbb{S}_f$




Belief variable factorization

3 classes of state variables – contribution (SUM-15)

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable

$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$




inferred hidden $s'_h \in \mathbb{S}_h$

$$\beta_{t+1}(\text{parents}(o'_i)) = \beta_{t+1}(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \text{parents}(o'_i) | \beta_t, a)$$

$\triangle!$ $\mathcal{P}(o'_i)$ may contain visible variables.



fully hidden $s'_f \in \mathbb{S}_f$



$$\beta_{t+1}(s'_f) = \pi(s'_f | \beta_t, a)$$


Belief variable factorization

3 classes of state variables – contribution (SUM-15)

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable


$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$\beta_{t+1}(\text{parents}(o'_i)) = \beta_{t+1}(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \text{parents}(o'_i) | \beta_t, a)$$



$\triangle!$ $\mathcal{P}(o'_i)$ may contain visible variables.

fully hidden $s'_f \in \mathbb{S}_f$

\rightarrow observations don't
inform belief state on s'_f .



$$\beta_{t+1}(s'_f) = \pi(s'_f | \beta_t, a)$$

Belief variable factorization

global belief state from marginal belief variables

bound over the global belief state

$$\beta_{t+1}(s'_1, \dots, s'_n) = \pi(s'_1, \dots, s'_n \mid a_0, o_1, \dots, a_t, o_{t+1})$$

$$\leq \min \left\{ \min_{s'_j \in \mathbb{S}_v} \left[\mathbb{1}_{\{s'_j = o'_j\}} \right], \min_{s'_j \in \mathbb{S}_f} \left[\beta_{t+1}(s'_j) \right], \min_{o'_i \in \mathbb{O}_h} \left[\beta_{t+1}(\text{parents}(o'_i)) \right] \right\}$$

Belief variable factorization

global belief state from marginal belief variables

bound over the global belief state

$$\beta_{t+1}(s'_1, \dots, s'_n) = \pi(s'_1, \dots, s'_n \mid a_0, o_1, \dots, a_t, o_{t+1})$$

$$\leq \min \left\{ \min_{s'_j \in \mathbb{S}_v} \left[\mathbb{1}_{\{s'_j = o'_j\}} \right], \min_{s'_j \in \mathbb{S}_f} \left[\beta_{t+1}(s'_j) \right], \min_{o'_i \in \mathbb{O}_h} \left[\beta_{t+1}(\text{parents}(o'_i)) \right] \right\}$$

- min of marginals = a **less informative** belief state
- computed using **marginal belief states**
→ **factorization & smaller state space**

Conclusion

contributions

- **modeling efforts:** → human-machine interaction

Conclusion

contributions

- **modeling efforts:** → human-machine interaction
- **advances:** → mixed-observability modeling
→ indefinite horizon + optimality proof

Conclusion

contributions

- **modeling efforts:** → human-machine interaction
- **advances:** → mixed-observability modeling
→ indefinite horizon + optimality proof
- **simplifying computations:** factorization work
& PPUDD algorithm

Conclusion

contributions

- **modeling efforts:** → human-machine interaction
- **advances:** → mixed-observability modeling
→ indefinite horizon + optimality proof
- **simplifying computations:** factorization work
& PPUDD algorithm
- **experimentations:** realistic problems
→ robust recognition mission with possibilistic beliefs
→ validation of the computation time reduction
→ IPPC 2014

Conclusion

contributions

- **modeling efforts:** → human-machine interaction
- **advances:** → mixed-observability modeling
→ indefinite horizon + optimality proof
- **simplifying computations:** factorization work
& PPUDD algorithm
- **experimentations:** realistic problems
→ robust recognition mission with possibilistic beliefs
→ validation of the computation time reduction
→ IPPC 2014
- **hybrid POMDP**
→ formalization
→ factored POMDP $\xrightarrow{\text{translation}}$ factored **finite** MPD

Conclusion

perspectives

- refined criteria, intermediate preferences
(*Weng 2005, Dubois & Fortemps 2005*)
 \Rightarrow finer π -POMDP
- state space heuristic search for π -POMDPs
- combination with reinforcement learning (*Sabbadin 2001*)

Conclusion

perspectives

- refined criteria, intermediate preferences
(*Weng 2005, Dubois & Fortemps 2005*)
 \Rightarrow finer π -POMDP
- state space heuristic search for π -POMDPs
- combination with reinforcement learning (*Sabbadin 2001*)

hybrid model

- IPPC problems (factored POMDPs);
- tests of this approach:
 - 1 **simplification:** π distributions definition?
 - 2 **imprecision:** robust in practice?


Thank you!

publications:

- *Qualitative Possibilistic Mixed-Observable MDPs*, **UAI-2013**
- *Structured Possibilistic Planning Using Decision Diagrams*,
AAAI-2014
- *Planning in Partially Observable Domains with Fuzzy Epistemic States and Probabilistic Dynamics*,
SUM-2015
- *Processus Décisionnels de Markov Possibilistes à Observabilité Mixte*,
Revue d'Intelligence Artificielle (**RIA french journal**)
- *A Possibilistic Estimation of Human Attentional Errors*,
submitted to **IEEE-TFS journal**

Uncertainty theories

Most known uncertainty theories and their relations




- IPT: most general uncertainty theory.
Use of sets of probability measures over Ω .
- BFT: use of a mass function $m : 2^\Omega \rightarrow [0, 1]$,
with $\sum_{A \subset \Omega} m(A) = 1$.
 - 1 plausibility measure: $\forall A \subset \Omega, Pl(A) = \sum_{B \cap A \neq \emptyset} m(B)$.
 - 2 belief function: $\forall A \subset \Omega, bel(A) = \sum_{B \subseteq A} m(B)$.

Focal sets of a mass function $m : 2^\Omega \rightarrow [0, 1]$:
subsets A of $\Omega = \{\omega_1, \dots, \omega_7\}$ such that $m(A) > 0$.


- if focal sets are all singletons
→ probability distribution ($bel = Pl = \mathbb{P}$)
- if focal sets are nested, e.g. $F_3 \subset F_2 \subset F_1 = \Omega$,
→ possibility distribution:
 bel =necessity measure, Pl =possibility measure.

probabilistic case

example of focal set
i.e. singleton



possibilistic case



Probabilistic belief update




Figure : Bayesian Network illustrating the belief update

- the **system states** are the gray circular nodes,
- the **action** is the red square node ,
- and the **observation** is the blue circular node.

The belief state b_t (resp. b_{t+1}) is the probabilistic estimation of the current (resp. next) system state s_t (resp. s_{t+1})

probabilistic belief update

$$b_{t+1}(s') \propto p(o' | s', a) \cdot \sum_{s \in S} p(s' | s, a) \cdot b_t(s)$$

Rewritings of parameters

PROBABILISTIC parameters

- $T_j^a(\mathbb{S}, s'_j) = T_j^a(\mathcal{P}(s'_j), s'_j);$
- $O_i^a(\mathbb{S}', o'_i) = O_i^a(\mathcal{P}(o'_i), o'_i).$

Rewritings of parameters

PROBABILISTIC parameters

- $T_j^a(\mathbb{S}, s'_j) = T_j^a(\mathcal{P}(s'_j), s'_j);$
- $O_i^a(\mathbb{S}', o'_i) = O_i^a(\mathcal{P}(o'_i), o'_i).$

consequences on the joint distribution

$$\begin{aligned}\mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathbb{S}, a) &= O_i^a(\mathcal{P}(o'_i), o'_i) \cdot \prod_{s'_j \in \mathcal{P}(o'_i)} T_i^a(\mathcal{P}(s'_j), s'_j) \\ &= \mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a).\end{aligned}$$

Rewritings of parameters

PROBABILISTIC parameters

- $T_j^a(\mathbb{S}, s'_j) = T_j^a(\mathcal{P}(s'_j), s'_j);$
- $O_i^a(\mathbb{S}', o'_i) = O_i^a(\mathcal{P}(o'_i), o'_i).$

consequences on the joint distribution

$$\begin{aligned} \mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathbb{S}, a) &= O_i^a(\mathcal{P}(o'_i), o'_i) \cdot \prod_{s'_j \in \mathcal{P}(o'_i)} T_j^a(\mathcal{P}(s'_j), s'_j) \\ &= \mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a). \end{aligned}$$

observation probabilities

epistemic state

$$b^\pi(\mathbb{S}) \xrightarrow{\text{marginalization}} b^\pi(\mathcal{Q}(o'_i)) \xrightarrow{\text{pignistic transformation}} \overline{b}^\pi(\mathcal{Q}(o'_i))$$

$$\mathbf{p}(o'_i \mid b^\pi, a) = \sum_{\mathcal{P}(o'_i) \cap \mathcal{Q}(o'_i)} \mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a) \cdot \overline{b}^\pi(\mathcal{Q}(o'_i))$$

Parameters rewritings

POSSIBILISTIC parameters

- $\pi(s'_j \mid \mathbb{S}, a) = \pi(s'_j \mid \mathcal{P}(s'_j), a);$
- $\pi(o'_i \mid \mathbb{S}', a) = \pi(o'_i \mid \mathcal{P}(o'_i), a).$

Parameters rewritings

POSSIBILISTIC parameters

- $\pi(s'_j \mid \mathbb{S}, a) = \pi(s'_j \mid \mathcal{P}(s'_j), a);$
- $\pi(o'_i \mid \mathbb{S}', a) = \pi(o'_i \mid \mathcal{P}(o'_i), a).$

marginal possibilistic belief states

$$\forall o'_i \in \mathbb{O},$$
$$b_{t+1}^\pi(\mathcal{P}(o'_i)) \propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

Parameters rewritings

POSSIBILISTIC parameters

- $\pi(s'_j \mid \mathbb{S}, a) = \pi(s'_j \mid \mathcal{P}(s'_j), a);$
- $\pi(o'_i \mid \mathbb{S}', a) = \pi(o'_i \mid \mathcal{P}(o'_i), a).$

marginal possibilistic belief states

$\forall o'_i \in \mathbb{O},$

$$\begin{aligned}
 b_{t+1}^\pi(\mathcal{P}(o'_i)) &\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid a_0, o_1, \dots, a_{t-1}, o_t) \\
 &= \max_{2^{\mathcal{Q}(o'_i)}} \min \left\{ \pi(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a), b_t^\pi(\mathcal{Q}(o'_i)) \right\}
 \end{aligned}$$

Parameters rewritings

POSSIBILISTIC parameters

- $\pi(s'_j \mid \mathbb{S}, a) = \pi(s'_j \mid \mathcal{P}(s'_j), a);$
- $\pi(o'_i \mid \mathbb{S}', a) = \pi(o'_i \mid \mathcal{P}(o'_i), a).$

marginal possibilistic belief states

$\forall o'_i \in \mathbb{O},$

$$\begin{aligned}
 b_{t+1}^\pi(\mathcal{P}(o'_i)) &\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid a_0, o_1, \dots, a_{t-1}, o_t) \\
 &= \max_{2^{\mathcal{Q}(o'_i)}} \min \left\{ \pi(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a), b_t^\pi(\mathcal{Q}(o'_i)) \right\} \\
 &\quad \text{denoted by } \pi(o'_i, \mathcal{P}(o'_i) \mid b_t^\pi, a).
 \end{aligned}$$

A possibilistic belief state

finite belief space

$$\Pi_S^{\mathcal{L}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_S^{\mathcal{L}} < +\infty$$

→ **finite belief space**

A possibilistic belief state

finite belief space

$$\Pi_S^{\mathcal{L}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_S^{\mathcal{L}} < +\infty$$

→ **finite belief space**

$$b_t^{\pi}(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

A possibilistic belief state

finite belief space

$$\Pi_S^{\mathcal{L}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_S^{\mathcal{L}} < +\infty$$

→ **finite belief space**

$$b_t^{\pi}(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

update – **possibilistic** belief state

$$b_{t+1}^{\pi}(s') = \begin{cases} 1 & \text{if } \pi(o', s' \mid b_t^{\pi}, a) = \pi(o' \mid b_t^{\pi}, a) \\ \pi(o', s' \mid b_t^{\pi}, a) & \text{otherwise.} \end{cases}$$

denoted by $b_{t+1}^{\pi}(s') \propto^{\pi} \pi(o', s' \mid b_t^{\pi}, a)$

A possibilistic belief state

finite belief space

$$\Pi_S^{\mathcal{L}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_S^{\mathcal{L}} < +\infty$$

→ **finite belief space**

$$b_t^{\pi}(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

update – **possibilistic belief state**

$$b_{t+1}^{\pi}(s') = \begin{cases} 1 & \text{if } \pi(o', s' \mid b_t^{\pi}, a) = \pi(o' \mid b_t^{\pi}, a) \\ \pi(o', s' \mid b_t^{\pi}, a) & \text{otherwise.} \end{cases}$$

denoted by $b_{t+1}^{\pi}(s') \propto^{\pi} \pi(o', s' \mid b_t^{\pi}, a)$

- $\pi(o', s' \mid b_t^{\pi}, a) = \max_{s \in \mathcal{S}} \min \left\{ \pi(o' \mid s', a), \pi(s' \mid s, a), b_t^{\pi}(s) \right\};$
- $\pi(o' \mid s', a) = \max_{s' \in \mathcal{S}} \pi(o', s' \mid b_t^{\pi}, a).$

A possibilistic belief state

finite belief space

$$\Pi_S^{\mathcal{L}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_S^{\mathcal{L}} < +\infty$$

→ **finite belief space**

$$b_t^{\pi}(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

update – **possibilistic** belief state

$$b_{t+1}^{\pi}(s') = \begin{cases} 1 & \text{if } \pi(o', s' \mid b_t^{\pi}, a) = \pi(o' \mid b_t^{\pi}, a) \\ \pi(o', s' \mid b_t^{\pi}, a) & \text{otherwise.} \end{cases}$$

denoted by $b_{t+1}^{\pi}(s') \propto^{\pi} \pi(o', s' \mid b_t^{\pi}, a)$

- the update **only depends on** o' and a .

Dynamic Programming scheme: $\# \text{ iterations} < \#\mathcal{X}$.

$\forall x \in \mathcal{X}, V_0(x) = \rho(x)$ **preference**,

Dynamic Programming scheme: $\# \text{ iterations} < \#\mathcal{X}$.

$\forall x \in \mathcal{X}, V_0(x) = \rho(x)$ **preference**, and, until convergence,

$$\bullet V_{i+1}(x) = \max_{a \in \mathcal{A}} \max_{x' \in \mathcal{X}} \min \{ \pi(x' | x, a), V_i(x') \},$$

Dynamic Programming scheme: $\# \text{ iterations} < \# \mathcal{X}$.

$\forall x \in \mathcal{X}$, $V_0(x) = \rho(x)$ **preference**, and, until convergence,

• $V_{i+1}(x) = \max_{a \in \mathcal{A}} \max_{x' \in \mathcal{X}} \min \{ \pi(x' \mid x, a), V_i(x') \}$, and

if $V_{i+1}(x) > V_i(x)$, $\delta(x) = \operatorname{argmax}_{a \in \mathcal{A}} \max_{x' \in \mathcal{X}} \min \{ \pi(x' \mid x, a), V_i(x') \}$.

Resulting π -MOMDP solver: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created, number of ADDs leaves **potentially huge**.
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite, number of leaves bounded, **ADDs smaller**.

Resulting π -MOMDP solver: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created, number of ADDs leaves **potentially huge**.
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite, number of leaves bounded, **ADDs smaller**.

PPUDD: Possibilistic Planning Using Decision Diagrams

```

1  $V^* \leftarrow 0$  ;  $V^c \leftarrow \mu$  ;  $\delta \leftarrow \bar{a}$  ;
2 while  $V^* \neq V^c$  do
3    $V^* \leftarrow V^c$  ;
4   for  $a \in \mathcal{A}$  do
5      $q^a \leftarrow$  swap each  $X_i$  variable in  $V^*$  with  $X'_i$  ;
6     for  $1 \leq i \leq n$  do
7        $q^a \leftarrow \boxed{\min} \{ q^a, \pi(X'_i \mid \text{parents}(X'_i), a) \}$  ;
8        $q^a \leftarrow \boxed{\max}_{X'_i} q^a$  ;
9      $V^c \leftarrow \boxed{\max} \{ q^a, V^c \}$  ;
10    update  $\delta$  to  $a$  where  $q^a = V^c$  and  $V^c > V^*$  ;
11 return  $(V^*, \delta)$  ;

```

computations on trees: *CU Decision Diagram Package*.

Resulting π -MOMDP solver: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created, number of ADDs leaves **potentially huge**.
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite, number of leaves bounded, **ADDs smaller**.

PPUDD: Possibilistic Planning Using Decision Diagrams

```

1  $V^* \leftarrow 0$  ;  $V^c \leftarrow \mu$  ;  $\delta \leftarrow \bar{a}$  ;
2 while  $V^* \neq V^c$  do
3    $V^* \leftarrow V^c$  ;
4   for  $a \in \mathcal{A}$  do
5      $q^a \leftarrow$  swap each  $X_i$  variable in  $V^*$  with  $X'_i$  ;
6     for  $1 \leq i \leq n$  do
7        $q^a \leftarrow \boxed{\min} \{ q^a, \pi(X'_i \mid \text{parents}(X'_i), a) \}$  ;
8        $q^a \leftarrow \boxed{\max}_{X'_i} q^a$  ;
9      $V^c \leftarrow \boxed{\max} \{ q^a, V^c \}$  ;
10    update  $\delta$  to  $a$  where  $q^a = V^c$  and  $V^c > V^*$  ;
11 return  $(V^*, \delta)$  ;
```

factorization

\Rightarrow dynamic programming

computations on trees: *CU Decision Diagram Package*.

Resulting π -MOMDP solver: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created, number of ADDs leaves **potentially huge**.
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite, number of leaves bounded, **ADDs smaller**.

PPUDD: Possibilistic Planning Using Decision Diagrams

```

1  $V^* \leftarrow 0$ ;  $V^c \leftarrow \mu$ ;  $\delta \leftarrow \bar{a}$ ;
2 while  $V^* \neq V^c$  do
3    $V^* \leftarrow V^c$ ;
4   for  $a \in \mathcal{A}$  do
5      $q^a \leftarrow$  swap each  $X_i$  variable in  $V^*$  with  $X'_i$ ;
6     for  $1 \leq i \leq n$  do
7        $q^a \leftarrow \min \{ q^a, \pi(X'_i \mid \text{parents}(X'_i), a) \}$ ;
8        $q^a \leftarrow \max_{X'_i} q^a$ ;
9      $V^c \leftarrow \max \{ q^a, V^c \}$ ;
10    update  $\delta$  to  $a$  where  $q^a = V^c$  and  $V^c > V^*$ ;
11 return  $(V^*, \delta)$ ;

```

factorization \Rightarrow dynamic programming divided into n stages

used ADDs smaller \rightarrow **faster computations.**

computations on trees: *CU Decision Diagram Package*.

Pignistic transformation and transitions

Pignistic transformation

numbering of the $n = \#\mathcal{S}$ system states:

$$1 = b^\pi(s_1) \geq \dots \geq b^\pi(s_n) \geq b^\pi(s_{n+1}) = 0.$$





pignistic transformation – $P : \Pi_{\mathcal{S}} \rightarrow \mathbb{P}_{\mathcal{S}}$

$$\overline{b}^\pi(s_i) = \sum_{j=i}^{\#\mathcal{S}} \frac{b^\pi(s_j) - b^\pi(s_{j+1})}{j}.$$

- probability distribution $\overline{b}^\pi =$ **gravity center** of the represented probabilistic distributions;
- **Laplace principle**: ignorance \rightarrow uniform probability.

Pignistic transformation

Examples of pignistic transformations (red) of possibility distributions (blue)



hybrid POMDP and π -POMDP

differences with possibilistic models

	hybrid POMDP	π -POMDP
transitions	probabilities	qualitative possibility
rewards	quantitative $\in \mathbb{R}$	qualitative $\in \mathcal{L}$
situation	-some imprecisions -large POMDP	few quantitative
issues	π definition	commensurability
in practice	MDP	π -MDP

hybrid POMDP and π -POMDP

differences with possibilistic models

	hybrid POMDP	π -POMDP
transitions	probabilities	qualitative possibility
rewards	quantitative $\in \mathbb{R}$	qualitative $\in \mathcal{L}$
situation	-some imprecisions -large POMDP	few quantitative
issues	π definition	commensurability
in practice	MDP	π -MDP

hybrid model:

- only belief states are possibilistic:
 - agent knowledge = **possibility** distribution;
- probabilistic dynamics:
 - **approximated** (prob.) transition between epistemic states.

factorized POMDP

definition

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;

factorized POMDP

definition

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;
- **transition** function of s'_j ,
 $T_j^a(\mathbb{S}, s'_j) = \mathbf{p}(s'_j \mid \mathbb{S}, a), \forall j \in \{1, \dots, m\}$ et $\forall a \in \mathcal{A}$;

factorized POMDP

definition

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;
- **transition** function of s'_j ,
 $T_j^a(\mathbb{S}, s'_j) = \mathbf{p}(s'_j \mid \mathbb{S}, a), \forall j \in \{1, \dots, m\}$ et $\forall a \in \mathcal{A}$;
- \mathcal{O} described by $\mathbb{O} = \{o_1, \dots, o_n\}$: $\mathcal{O} = o_1 \times \dots \times o_n$;

factorized POMDP

definition

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;
- **transition** function of s'_j ,
 $T_j^a(\mathbb{S}, s'_j) = \mathbf{p}(s'_j \mid \mathbb{S}, a), \forall j \in \{1, \dots, m\}$ et $\forall a \in \mathcal{A}$;
- \mathcal{O} described by $\mathbb{O} = \{o_1, \dots, o_n\}$: $\mathcal{O} = o_1 \times \dots \times o_n$;
- **observation** function of o'_i ,
 $O_i^a(\mathbb{S}', o'_i) = \mathbf{p}(o'_i \mid \mathbb{S}', a), \forall i \in \{1, \dots, n\}$ et $\forall a \in \mathcal{A}$.

factorized POMDP

definition

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;
- **transition** function of s'_j ,
 $T_j^a(\mathbb{S}, s'_j) = \mathbf{p}(s'_j \mid \mathbb{S}, a), \forall j \in \{1, \dots, m\}$ et $\forall a \in \mathcal{A}$;
- \mathcal{O} described by $\mathbb{O} = \{o_1, \dots, o_n\}$: $\mathcal{O} = o_1 \times \dots \times o_n$;
- **observation** function of o'_i ,
 $O_i^a(\mathbb{S}', o'_i) = \mathbf{p}(o'_i \mid \mathbb{S}', a), \forall i \in \{1, \dots, n\}$ et $\forall a \in \mathcal{A}$.

independences:

- $\rightarrow \forall s'_i, s'_j \in \mathbb{S}', \quad s'_i \perp\!\!\!\perp s'_j \mid \{\mathbb{S}, a \in \mathcal{A}\},$
- $\rightarrow \forall o'_i, o'_j \in \mathbb{O}', \quad o'_i \perp\!\!\!\perp o'_j \mid \{\mathbb{S}', a \in \mathcal{A}\}.$

Notations

some variables does not interact with each other

variables about the **current** system state,

s_1

\vdots

s_{j_1}

\vdots

s_{j_2}

\vdots

s_{j_k}

\vdots

s_m

variable s'_j about
the **next** state.

s'_j

Notations

some variables does not interact with each other


variables about the **current** system state,

$$s_k \rightarrow s'_j$$



$\exists a \in \mathcal{A}$, such that

$T_j^a(\mathbb{S}, s'_j)$ depends on s_k .




Notations

some variables does not interact with each other

variables about the **current** system state,


$s_k \rightarrow s'_j$
 \Updownarrow
 $\exists a \in \mathcal{A}$, such that
 $T_j^a(\mathbb{S}, s'_j)$ depends on s_k .



Notations

concerning observation variables

next state



Notations

concerning observation variables

$$s'_j \rightarrow o'_i$$




$\exists a \in \mathcal{A}$, such that

$$O_i^a(S', o'_i)$$

depends on s'_j .

next state



Notations

concerning observation variables

$$s'_j \rightarrow o'_i$$




$\exists a \in \mathcal{A}$, such that

$$O_i^a(\mathbb{S}', o'_i)$$

depends on s'_j .

next state



Notations

concerning observation variables


$$s'_j \rightarrow o'_i$$



$\exists a \in \mathcal{A}$, such that

$$O_i^a(S', o'_i)$$

depends on s'_j .



next state

A diagram showing the next state vector S' and an observation variable o'_i . The state vector is a vertical sequence of gray circles labeled s'_1 , s'_{j_1} , s'_{j_2} , s'_{j_m} , and s'_m , with vertical ellipses (\vdots) between s'_1 and s'_{j_1} , between s'_{j_2} and s'_{j_m} , and between s'_{j_m} and s'_m . To the right of this sequence is a gray circle labeled o'_i . Red arrows point from s'_{j_1} , s'_{j_2} , and s'_{j_m} to o'_i . Dashed red arrows also point from s'_1 and s'_m towards o'_i , indicating that only a subset of the state vector is relevant for the observation.

Notations

concerning observation variables


$$s'_j \rightarrow o'_i$$



$\exists a \in \mathcal{A}$, such that

$$O_i^a(S', o'_i)$$

depends on s'_j .



Notations

concerning observation variables


$$s'_j \rightarrow o'_i$$



$\exists a \in \mathcal{A}$, such that


$$O_i^a(S', o'_i)$$

depends on s'_j .



Notations

concerning observation variables



Variables de croyance

different according to the class of the variable

$$\lambda = \#\mathcal{L}$$

Variables de croyance

different according to the class of the variable

$$\lambda = \#\mathcal{L}$$

- $\forall s'_v \in \mathcal{S}_v$, 1 variable β'_v is enough.

Variables de croyance

different according to the class of the variable

$$\lambda = \#\mathcal{L}$$

■ $\forall s'_v \in \mathbb{S}_v$, 1 variable β'_v is enough.

■ $p_i = \#\mathcal{P}(o'_i)$.

$\forall o_i \in \mathbb{O} \setminus \mathbb{S}_v$, $\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}$ belief states,

$\Rightarrow \lceil \log_2(\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}) \rceil$ boolean variables β'_h .

Variables de croyance

different according to the class of the variable

$$\lambda = \#\mathcal{L}$$

■ $\forall s'_v \in \mathbb{S}_v$, 1 variable β'_v is enough.

■ $p_i = \#\mathcal{P}(o'_i)$.

$\forall o_i \in \mathbb{O} \setminus \mathbb{S}_v$, $\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}$ belief states,


$\Rightarrow \lceil \log_2(\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}) \rceil$ boolean variables β'_h .

■ $\forall s'_f \in \mathbb{S}_f$, $\lambda^2 - (\lambda - 1)^2 = 2\lambda - 1$ belief states,

$\Rightarrow \lceil \log_2(2\lambda - 1) \rceil$ boolean variables β'_f .

resulting MDP in practice

final structured MDP



factorized model's variables: $\#\mathbb{O} + \#\mathbb{S}_v +$

$$+ \sum_{i=1}^{\#\mathbb{O}_h} \left[\log_2 (\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}) \right] + \#\mathbb{S}_f \cdot \left[\log_2 (2\lambda - 1) \right]$$


\ll

initial hybrid model's variables:

$$\left[\log_2 (\lambda^{2^{\#\mathbb{S}}} - (\lambda - 1)^{2^{\#\mathbb{S}}}) \right]$$

resulting MDP in practice

final structured MDP



factorized model's variables:

$$\leq \#\mathbb{O} + \#\mathbb{S}_v + \sum_{i=1}^{\#\mathbb{O}_h} \log_2(\lambda) \cdot 2^{p_i} + \#\mathbb{S}_f \cdot (1 + \log_2(\lambda))$$

\ll

initial hybrid model's variables:

$$\geq \log_2(\lambda) \cdot (2^{\#\mathbb{S}} - 1).$$

Variable classification

3 classes of state variables – state space factorization

variable: visible $s'_v \in \mathbb{S}_v$



inferred hidden $s'_h \in \mathbb{S}_h$




fully hidden $s'_f \in \mathbb{S}_f$



Variable classification

3 classes of state variables – state space factorization

variable: visible $s'_v \in \mathbb{S}_v$



inferred hidden $s'_h \in \mathbb{S}_h$




fully hidden $s'_f \in \mathbb{S}_f$



Variable classification

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$



$$\mathbf{p}(s'_v \mid b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b}_t^\pi(\mathcal{P}(s'_v))$$

inferred hidden $s'_h \in \mathbb{S}_h$



fully hidden $s'_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.



$$\mathbf{p}(s'_v \mid b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b}_t^\pi(\mathcal{P}(s'_v))$$

inferred hidden $s'_h \in \mathbb{S}_h$



fully hidden $s'_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables – state space factorization


variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.

$$\mathbf{p}(s'_v \mid b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b}_t^\pi(\mathcal{P}(s'_v))$$



inferred hidden $s'_h \in \mathbb{S}_h$



fully hidden $s'_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$


\Leftrightarrow deterministic belief variable.

$$\mathbf{p}(s'_v \mid b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b_t^\pi}(\mathcal{P}(s'_v))$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$



fully hidden $s'_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v \mid b_t^\pi, a) = \sum_{\mathcal{P}(s'_v)} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b}_t^\pi(\mathcal{P}(s'_v))$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid b_t^\pi, a).$$



fully hidden $s'_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v \mid b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b}_t^\pi(\mathcal{P}(s'_v))$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid b_t^\pi, a).$$



! $\mathcal{P}(o'_i)$ may contain visible variables

fully hidden $s'_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v \mid b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b}_t^\pi(\mathcal{P}(s'_v))$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid b_t^\pi, a).$$



! $\mathcal{P}(o'_i)$ may contain visible variables

fully hidden $s'_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v \mid b_t^\pi, a) = \sum_{\mathcal{P}(s'_v)} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b}_t^\pi(\mathcal{P}(s'_v))$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid b_t^\pi, a).$$



! $\mathcal{P}(o'_i)$ may contain visible variables

fully hidden $s'_f \in \mathbb{S}_f$



$$b_{t+1}^\pi(s'_f) = \max_{\sim \mathcal{P}(s'_f)} \min \left\{ \pi(s'_f \mid \mathcal{P}(s'_f), a), b_t^\pi(\mathcal{P}(s'_f)) \right\}$$


Variable classification

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v \mid b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b}_t^\pi(\mathcal{P}(s'_v))$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid b_t^\pi, a).$$



! $\mathcal{P}(o'_i)$ may contain visible variables

fully hidden $s'_f \in \mathbb{S}_f$

\rightarrow observations don't
inform belief state on s'_f



$$b_{t+1}^\pi(s'_f) = \max_{\sim \mathcal{P}(s'_f)} \min \left\{ \pi(s'_f \mid \mathcal{P}(s'_f), a), b_t^\pi(\mathcal{P}(s'_f)) \right\}$$

Toy example: 2 machine states, 3 occurrences

columns		1	2	3	4	5
SITUATION						
v'	v_A	1				1
	v_B		1			
	v_C	1			1	
h	s_A	1	1		1	
	s_B			1		1
BEHAVIOUR						
h'	s_A					1
	s_B		1		1	
EFFECT		\bar{e}	\tilde{e}	\bar{e}	\hat{e}	\underline{e}
POSSIBILITY		1	ε	1	λ	δ

Probability / Possibility :

e_1 or e_2	$\mathbf{p}(e_1) + \mathbf{p}(e_2 \cap \bar{e}_1)$	$\max \{ \pi(e_1), \pi(e_2) \}$
e_1 and e_2	$\mathbf{p}(e_1) \cdot \mathbf{p}(e_2 e_1)$	$\min \{ \pi(e_1), \pi(e_2 e_1) \}$

Back to general POMDP: Partially Observable Criteria

Rewriting: belief dependent reward (belief trick)

- $r : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$ reward function
- $\rho : \mathcal{S} \times \mathcal{A} \rightarrow \mathcal{L}$ preference function

Probability / Possibility:

$R(b_t, d_t)$ $= \sum_s r(s, d_t) \cdot b_t(s)$	<p>optimistic: $\bar{\Psi}(\beta_t, \delta_t)$</p> $= \max_s \min \{ \rho(s, \delta_t), \beta_t(s) \}$ <p>pessimistic: $\underline{\Psi}(\beta_t, \delta_t)$</p> $= \min_s \max \{ \rho(s, \delta_t), 1 - \beta_t(s) \}$
$\mathbb{E}[r(S_t, d_t)] = \mathbb{E}[R(b_t, d_t)]$	$\mathbb{S}_{\Pi}[\rho(S_t, d_t)] = \mathbb{S}_{\Pi}[\bar{\Psi}(\beta_t, d_t)]$ $\mathbb{S}_{\mathcal{N}}[\rho(S_t, d_t)] = \mathbb{S}_{\mathcal{N}}[\underline{\Psi}(\beta_t, d_t)]$

Note: $\mathbb{S}_{\Pi}[\underline{\Psi}(\beta_t, d_t)]; \mathbb{S}_{\mathcal{N}}[\bar{\Psi}(\beta_t, d_t)]?$

Why model ignorance?

knowledge is not always encouraged with POMDPs

- initial belief deterministic $s_0 = s_A$.




s_A

$$b_0(s_A) = 1$$

Why model ignorance?

knowledge is not always encouraged with POMDPs


- initial belief deterministic $s_0 = s_A$.



Why model ignorance?

knowledge is not always encouraged with POMDPs


- initial belief deterministic $s_0 = s_A$.



Why model ignorance?

knowledge is not always encouraged with POMDPs

- initial belief deterministic $s_0 = s_A$.




- $\{s_B, s_C, s_D\} \xrightarrow{\text{deterministic}} s_E, r(s_E) = 0.$

Why model ignorance?

knowledge is not always encouraged with POMDPs

- initial belief deterministic $s_0 = s_A$.




- $\{s_B, s_C, s_D\} \xrightarrow{\text{deterministic}} s_E, r(s_E) = 0.$

$$\mathbb{E}_{s_0 \sim b_0} \left[\sum_{t=0}^{+\infty} \gamma^t \cdot r(s_t) \mid a_0 = \tilde{a} \text{ or } a' \right] = r(s_0) + 5\gamma.$$

the safe action is not preferred.


Why model ignorance?

Choquet integral and rewards



Why model ignorance?

Choquet integral and rewards




- $Ch(r, N_{b_1^\pi} \mid a_0 = \tilde{a}) = r(s_D, \tilde{a}) = 5,$
- $Ch(r, N_{b_1^\pi} \mid a_0 = a') = \min_{s \in \mathcal{S}} r(s, a') = 0.$

the safe action is preferred! **dispersion reduced**

Why model ignorance?

Choquet integral and rewards



- $Ch(r, N_{b_1^\pi} \mid a_0 = \tilde{a}) = r(s_D, \tilde{a}) = 5,$
- $Ch(r, N_{b_1^\pi} \mid a_0 = a') = \min_{s \in \mathcal{S}} r(s, a') = 0.$

the safe action is preferred! **dispersion reduced**

if $\mathcal{N}_{b_1^\pi}$ replaced by $b_1 \Rightarrow Ch(r, b_1) = \mathbb{E}_{s \sim b_1} [r(s, a)].$

Choquet integral and rewards

pessimistic evaluation of the rewards – necessity measure

imprecision of $b^\pi =$ agent ignorance + discretization:
pessimistic reward about these imprecisions.

Choquet integral and rewards

pessimistic evaluation of the rewards – necessity measure

imprecision of b^π = agent ignorance + discretization:
pessimistic reward about these imprecisions.

Dual measure of $\Pi : 2^{\mathcal{S}} \rightarrow \mathcal{L}$

necessity \mathcal{N} such that $\forall A \subseteq \mathcal{S}, \mathcal{N}(A) = 1 - \Pi(\overline{A})$.

Choquet integral and rewards

pessimistic evaluation of the rewards – necessity measure

imprecision of b^π = agent ignorance + discretization:
pessimistic reward about these imprecisions.

Dual measure of $\Pi : 2^{\mathcal{S}} \rightarrow \mathcal{L}$

necessity \mathcal{N} such that $\forall A \subseteq \mathcal{S}, \mathcal{N}(A) = 1 - \Pi(\overline{A})$.

$r_1 > r_2 > \dots > r_{k+1} = 0$ represents elements of $\{r(s, a) | s \in \mathcal{S}\}$.

Choquet integral of r with respect to \mathcal{N}

$$Ch(r, \mathcal{N}) = \sum_{i=1}^k (r_i - r_{i+1}) \cdot \mathcal{N}(\{r(s) \geq r_i\}) \quad (1)$$

(2)

Choquet integral and rewards

pessimistic evaluation of the rewards – necessity measure

imprecision of b^π = agent ignorance + discretization:
pessimistic reward about these imprecisions.

Dual measure of $\Pi : 2^{\mathcal{S}} \rightarrow \mathcal{L}$

necessity \mathcal{N} such that $\forall A \subseteq \mathcal{S}, \mathcal{N}(A) = 1 - \Pi(\bar{A})$.

$r_1 > r_2 > \dots > r_{k+1} = 0$ represents elements of $\{r(s, a) | s \in \mathcal{S}\}$.

Choquet integral of r with respect to \mathcal{N}

$$Ch(r, \mathcal{N}) = \sum_{i=1}^k (r_i - r_{i+1}) \cdot \mathcal{N}(\{r(s) \geq r_i\}) \quad (1)$$

$$= \sum_{i=1}^{\#\mathcal{L}-1} (l_i - l_{i+1}) \cdot \min_{\substack{s \in \mathcal{S} \text{ s.t.} \\ b^\pi(s) \geq l_i}} r(s) \quad (2)$$

notation $\mathcal{L} = \{l_1 = 1, l_2, l_3, \dots, 0\}$.

resulting MDP in practice

trick: “flipflop” variable

boolean variable “*flipflop*” f changes state at each time step
 \rightarrow defines 2 phases:

- 1 *observation generation*,
- 2 *belief update* (deterministic knowing the observation)

MDP variables:


$\tilde{\mathcal{S}} =$

beliefs: $\beta = \beta_v^1 \times \dots \times \beta_v^{m_v} \times \beta_h^1 \times \dots \times \beta_h^{m_h} \times \beta_f^1 \times \dots \times \beta_f^{m_f}$
 \times

visible variables : $v = f \times s_v^1 \times \dots \times s_v^{m_v} \times o_1 \times \dots \times o_k$.

resulting MDP in practice

final structured MDP


 $\tilde{\mathcal{S}} =$

beliefs: $\beta = \beta_v^1 \times \dots \times \beta_v^{m_v} \times \beta_h^1 \times \dots \times \beta_h^{m_h} \times \beta_f^1 \times \dots \times \beta_f^{m_f}$

 \times

visible variables : $v = f \times s_v^1 \times \dots \times s_v^{m_v} \times o_1 \times \dots \times o_k.$