



Exploiting Imprecise Information Sources in Sequential Decision Making Problems under Uncertainty.

Ph.D defense **N.Drougard**

doctoral school: EDSYS,

institution: ISAE-SUPAERO,

laboratory: ONERA-The French Aerospace Lab.




retour sur innovation

- 1 Context
- 2 Mixed-Observability and unbounded mission durations
- 3 Factored π -MOMDP and computations with ADDs
- 4 Belief factorization
- 5 Human-machine interaction
- 6 An hybrid POMDP
- 7 Benefiting from factorized structures

- 1 Context
- 2 Mixed-Observability and unbounded mission durations
- 3 Factored π -MOMDP and computations with ADDs
- 4 Belief factorization
- 5 Human-machine interaction
- 6 An hybrid POMDP
- 7 Benefiting from factorized structures

Context

Partially Observable Markov Decision Processes (POMDPs)




POMDP: model for autonomous robotics




Context

Partially Observable Markov Decision Processes (POMDPs)



Context

Partially Observable Markov Decision Processes (POMDPs)




POMDP: model for autonomous robotics

$s \in \mathcal{S}$: **system state**;

$o \in \mathcal{O}$: **system observations**;


Context

Partially Observable Markov Decision Processes (POMDPs)




Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)




Context

Partially Observable Markov Decision Processes (POMDPs)



Context

Partially Observable Markov Decision Processes (POMDPs)




POMDP: model for autonomous robotics

$s \in \mathcal{S}$: **system state**;



$o \in \mathcal{O}$: **system observations**;

$a \in \mathcal{A}$: **agent's actions**;




Context

Partially Observable Markov Decision Processes (POMDPs)



Context

Partially Observable Markov Decision Processes (POMDPs)




POMDP: model for autonomous robotics

$s \in \mathcal{S}$: **system state**;


$o \in \mathcal{O}$: **system observations**;

$a \in \mathcal{A}$: **agent's actions**;



Context

Partially Observable Markov Decision Processes (POMDPs)




POMDP: model for autonomous robotics

$s \in \mathcal{S}$: **system state**;


$o \in \mathcal{O}$: **system observations**;

$a \in \mathcal{A}$: **agent's actions**;



Context

Partially Observable Markov Decision Processes (POMDPs)




POMDP: model for autonomous robotics

$s \in \mathcal{S}$: **system state**;

$o \in \mathcal{O}$: **system observations**;

$a \in \mathcal{A}$: **agent's actions**;

b **belief**.



Context

belief state, strategy, criterion.

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$,

- **transition** function $T(s, a, s') = \mathbf{p}(s' \mid s, a)$;
- **observation** function $O(s', a, o') = \mathbf{p}(o' \mid s', a)$.

Context

belief state, strategy, criterion.

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$,

- **transition** function $T(s, a, s') = \mathbf{p}(s' \mid s, a)$;
- **observation** function $O(s', a, o') = \mathbf{p}(o' \mid s', a)$.

belief state: $b_t(s) = \mathbb{P}(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$

Context

belief state, strategy, criterion.

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$,

- **transition** function $T(s, a, s') = \mathbf{p}(s' | s, a)$;
- **observation** function $O(s', a, o') = \mathbf{p}(o' | s', a)$.

belief state: $b_t(s) = \mathbb{P}(s_t = s | a_0, o_1, \dots, a_{t-1}, o_t)$

probabilistic belief update

$$b_{t+1}(s') \propto \mathbf{p}(o' | s', a) \cdot \sum_{s \in \mathcal{S}} \mathbf{p}(s' | s, a) \cdot b_t(s)$$

Context

belief state, strategy, criterion.

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$,

- **transition** function $T(s, a, s') = \mathbf{p}(s' | s, a)$;
- **observation** function $O(s', a, o') = \mathbf{p}(o' | s', a)$.

belief state: $b_t(s) = \mathbb{P}(s_t = s | a_0, o_1, \dots, a_{t-1}, o_t)$

probabilistic belief update

$$b_{t+1}(s') \propto \mathbf{p}(o' | s', a) \cdot \sum_{s \in \mathcal{S}} \mathbf{p}(s' | s, a) \cdot b_t(s)$$

action choices: strategy $\delta(b_t) = a_t \in \mathcal{A}$

$$\text{maximizing } \mathbb{E}_{s_0 \sim b_0} \left[\sum_{t=0}^{+\infty} \gamma^t \cdot r(s_t, \delta(b_t)) \right], \quad 0 < \gamma < 1.$$

Flaws of the POMDP model

POMDPs in practice

- optimal strategy computation \geq **PSPACE**;
- probabilities are **imprecisely known** in practice;
- agent's **ignorance** not taken into account.

Context

practical issues: Complexity, Vision and Initial Belief.

- **strategy computation \geq PSPACE-complete:**

Context

practical issues: Complexity, Vision and Initial Belief.

- **strategy computation \geq PSPACE-complete:**

- optimality for “small” ou “structured” POMDPs;
- approximate computations (no optimality guarantee).

Context

practical issues: Complexity, Vision and Initial Belief.

- **strategy computation** \geq **PSPACE-complete**:

- optimality for “small” ou “structured” POMDPs;
- approximate computations (no optimality guarantee).

- **Computer Vision**, statistical learning: $\mathbf{p}(o' | s', a)$



Context

practical issues: Complexity, Vision and Initial Belief.

■ strategy computation \geq PSPACE-complete:

- optimality for “small” ou “structured” POMDPs;
- approximate computations (no optimality guarantee).

■ Computer Vision, statistical learning: $p(o' | s', a)$

- wide picture variability? \Rightarrow hard extraction of a classifier;
- more observations? \Rightarrow more complex POMDP.



Context

practical issues: Complexity, Vision and Initial Belief.

■ strategy computation \geq PSPACE-complete:

- optimality for “small” ou “structured” POMDPs;
- approximate computations (no optimality guarantee).

■ Computer Vision, statistical learning: $\mathbf{p}(o' | s', a)$

- wide picture variability? \Rightarrow hard extraction of a classifier;
- more observations? \Rightarrow more complex POMDP.



■ Initial belief b_0 (prior information on the system state).

Context

practical issues: Complexity, Vision and Initial Belief.

■ strategy computation \geq PSPACE-complete:

- optimality for “small” ou “structured” POMDPs;
- approximate computations (no optimality guarantee).

■ Computer Vision, statistical learning: $p(o' | s', a)$

- wide picture variability? \Rightarrow hard extraction of a classifier;
- more observations? \Rightarrow more complex POMDP.



■ Initial belief b_0 (prior information on the system state).

uniform = subjectif, mix up with frequencies!

Context

practical issues: Complexity, Vision and Initial Belief.

■ strategy computation \geq PSPACE-complete:

- optimality for “small” ou “structured” POMDPs;
- approximate computations (no optimality guarantee).

■ Computer Vision, statistical learning: $\mathbf{p}(o' | s', a)$

- wide picture variability? \Rightarrow hard extraction of a classifier;
- more observations? \Rightarrow more complex POMDP.



■ Initial belief b_0 (prior information on the system state).

uniform = subjectif, mix up with frequencies!

Qualitative Possibility Theory:

- simplification, ignorance and imprecision modeling.

Why model ignorance?

knowledge is not always encouraged with POMDPs

- initial belief deterministic $s_0 = s_A$.


s_A

$$b_0(s_A) = 1$$

Why model ignorance?

knowledge is not always encouraged with POMDPs


- initial belief deterministic $s_0 = s_A$.



Why model ignorance?

knowledge is not always encouraged with POMDPs


- initial belief deterministic $s_0 = s_A$.



Why model ignorance?

knowledge is not always encouraged with POMDPs

- initial belief deterministic $s_0 = s_A$.




- $\{s_B, s_C, s_D\} \xrightarrow{\text{deterministic}} s_E, r(s_E) = 0$.

Why model ignorance?

knowledge is not always encouraged with POMDPs

- initial belief deterministic $s_0 = s_A$.



- $\{s_B, s_C, s_D\} \xrightarrow{\text{deterministic}} s_E, r(s_E) = 0$.

$$\mathbb{E}_{s_0 \sim b_0} \left[\sum_{t=0}^{+\infty} \gamma^t \cdot r(s_t) \mid a_0 = \tilde{a} \text{ or } a' \right] = r(s_0) + 5\gamma.$$

the safe action is not preferred.

Qualitative Possibility Theory

an hybrid model with possibilistic belief states

Qualitative Possibility Theory

- **simplification/imprecision** taken into account,
BUT frequentist information lost;
- **ignorance** modeling;
- possibilistic belief states already studied: π -POMDP
(Sabbadin UAI98, Drougard UAI13, AAAI14).

Qualitative Possibility Theory

an hybrid model with possibilistic belief states

Qualitative Possibility Theory

- **simplification/imprecision** taken into account,
BUT frequentist information lost;
 - **ignorance** modeling;
 - possibilistic belief states already studied: π -POMDP (Sabbadin UAI98, Drougard UAI13, AAAI14).
-
- **POMDP with possibilistic belief states**
 - heuristic for solving POMDPs;
 - results in a standard MDP.

Qualitative Possibility Theory

an hybrid model with possibilistic belief states

Qualitative Possibility Theory

- **simplification/imprecision** taken into account,
BUT frequentist information lost;
 - **ignorance** modeling;
 - possibilistic belief states already studied: π -POMDP
(Sabbadin UAI98, Drougard UAI13, AAAI14).
-
- **POMDP with possibilistic belief states**
 - heuristic for solving POMDPs;
 - results in a standard MDP.
-
- **defined distributions π :**
 $\mathbb{P} \rightarrow \pi$ transformations: pignistic, specific, ...

Qualitative Possibility Theory

presentation

$1 = l_1 > l_2 > \dots > l_{\#\mathcal{L}} = 0$ form the **finite scale** \mathcal{L} .

events $e \subset \Omega$ (universe)

sorted using possibility **degrees** $\pi(e) \in \mathcal{L}$,

\neq

quantified with **frequencies** $\mathbf{p}(e) \in [0, 1]$ (probabilities).

Qualitative Possibility Theory

presentation

$1 = l_1 > l_2 > \dots > l_{\#\mathcal{L}} = 0$ form the **finite scale** \mathcal{L} .

events $e \subset \Omega$ (universe)

sorted using possibility **degrees** $\pi(e) \in \mathcal{L}$,

\neq

quantified with **frequencies** $\mathbf{p}(e) \in [0, 1]$ (probabilities).

$e_1 \neq e_2$, 2 events $\subset \Omega$

■ $\pi(e_1) < \pi(e_2) \Leftrightarrow$ “ e_1 is less plausible than e_2 ”;

Qualitative Possibility Theory

presentation

$1 = l_1 > l_2 > \dots > l_{\#\mathcal{L}} = 0$ form the **finite scale** \mathcal{L} .

events $e \subset \Omega$ (universe)

sorted using possibility **degrees** $\pi(e) \in \mathcal{L}$,

\neq

quantified with **frequencies** $\mathbf{p}(e) \in [0, 1]$ (probabilities).

$e_1 \neq e_2$, 2 events $\subset \Omega$

■ $\pi(e_1) < \pi(e_2) \Leftrightarrow$ “ e_1 is less plausible than e_2 ”;

Probability (\mathbb{P}) / **Possibility (Π):**

e_1 or e_2	$\mathbf{p}(e_1) + \mathbf{p}(e_2 \cap \overline{e_1})$	$\max \{ \pi(e_1), \pi(e_2) \}$
e_1 and e_2	$\mathbf{p}(e_1) \cdot \mathbf{p}(e_2 \mid e_1)$	$\min \{ \pi(e_1), \pi(e_2 \mid e_1) \}$

- 1 Context
- 2 Mixed-Observability and unbounded mission durations
- 3 Factored π -MOMDP and computations with ADDs
- 4 Belief factorization
- 5 Human-machine interaction
- 6 An hybrid POMDP
- 7 Benefiting from factorized structures

Possibilistic models:

π -MOMDPs

possibilistic POMDPs (π -POMDPs): *Sabbadin UAI-98*.


- finite belief space $\#\mathcal{B} = \#\mathcal{L}^{\#S} - (\#\mathcal{L} - 1)^{\#S}$

Possibilistic models: π -MOMDPs

possibilistic POMDPs (π -POMDPs): *Sabbadin UAI-98*.

- finite belief space $\#\mathcal{B} = \#\mathcal{L}^{\#S} - (\#\mathcal{L} - 1)^{\#S}$

contribution (UAI13):



Mixed-Observability: system state $s \in \mathcal{S} = \mathcal{S}_v \times \mathcal{S}_h$


i.e. state s = visible component s_v & hidden component s_h .

Possibilistic models: π -MOMDPs

possibilistic POMDPs (π -POMDPs): *Sabbadin UAI-98*.

- finite belief space $\#\mathcal{B} = \#\mathcal{L}^{\#S} - (\#\mathcal{L} - 1)^{\#S}$

contribution (UAI13):



Mixed-Observability: system state $s \in \mathcal{S} = \mathcal{S}_v \times \mathcal{S}_h$

i.e. state s = visible component s_v & hidden component s_h .

- beliefs are only over \mathcal{S}_h (component s_v observed),
- computations on $\mathcal{X} = \mathcal{S}_v \times \mathcal{B}_h$ whose size is

$$\#\mathcal{X} = \#\mathcal{S}_v \cdot (\#\mathcal{L}^{\#S_h} - (\#\mathcal{L} - 1)^{\#S_h}) \ll \#\mathcal{B}.$$

contribution (UAI13): Infinite Horizon

Dynamic Programming scheme: $\# \text{ iterations} < \#\mathcal{X}$.

$\forall x \in \mathcal{X}, V_0(x) = \mu(x)$ **preference**,

contribution (UAI13): Infinite Horizon

Dynamic Programming scheme: $\# \text{ iterations} < \#\mathcal{X}$.

$\forall x \in \mathcal{X}, V_0(x) = \mu(x)$ **preference**, and, until convergence,

$$\bullet V_{i+1}(x) = \max_{a \in \mathcal{A}} \max_{x' \in \mathcal{X}} \min \{ \pi(x' | x, a), V_i(x') \},$$

contribution (UAI13): Infinite Horizon

Dynamic Programming scheme: $\# \text{ iterations} < \# \mathcal{X}$.

$\forall x \in \mathcal{X}$, $V_0(x) = \mu(x)$ **preference**, and, until convergence,

• $V_{i+1}(x) = \max_{a \in \mathcal{A}} \max_{x' \in \mathcal{X}} \min \{ \pi(x' | x, a), V_i(x') \}$, and

if $V_{i+1}(x) > V_i(x)$, $\delta(x) = \arg \max_{a \in \mathcal{A}} \max_{x' \in \mathcal{X}} \min \{ \pi(x' | x, a), V_i(x') \}$.

contribution (UAI13): Infinite Horizon

Dynamic Programming scheme: $\# \text{ iterations} < \# \mathcal{X}$.



$\forall x \in \mathcal{X}$, $V_0(x) = \mu(x)$ **preference**, and, until convergence,

• $V_{i+1}(x) = \max_{a \in \mathcal{A}} \max_{x' \in \mathcal{X}} \min \{ \pi(x' | x, a), V_i(x') \}$, and

if $V_{i+1}(x) > V_i(x)$, $\delta(x) = \operatorname{argmax}_{a \in \mathcal{A}} \max_{x' \in \mathcal{X}} \min \{ \pi(x' | x, a), V_i(x') \}$.

Recognition mission: robot on a grid $g \times g$, 2 targets $T1$, $T2$.

- **goal:** reach the object $A = T1$ or $T2$;
- noisy observations of the targets natures: $\mathbf{p}(o' | s', a)$.




Actually, misperception in the error zone is: $P_{bad} > \frac{1}{2}$.

- 1 Context
- 2 Mixed-Observability and unbounded mission durations
- 3 Factored π -MOMDP and computations with ADDs
- 4 Belief factorization
- 5 Human-machine interaction
- 6 An hybrid POMDP
- 7 Benefiting from factorized structures


contribution (AAAI14): factored π -MOMDP

\Leftrightarrow state space $\mathcal{X} = \mathcal{S}_v \times \mathcal{B}_h =$ Boolean variables (X_1, \dots, X_n)
+ independence assumptions \Leftarrow graphical model.



contribution (AAAI14): factored π -MOMDP

\Leftrightarrow state space $\mathcal{X} = \mathcal{S}_v \times \mathcal{B}_h =$ Boolean variables (X_1, \dots, X_n)
+ independence assumptions \Leftarrow graphical model.




- transition functions

$$T_i^a = \pi(X'_i \mid \text{parents}(X'_i), a)$$

represented by **Algebraic Decision Diagrams (ADD)**.

(SPUDD – Hoey et al., UAI-99).



Solver π -MOMDP résultant: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created, number of ADDs leaves **potentially huge**.
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite, number of leaves bounded, **ADDs smaller**.

Solver π -MOMDP résultant: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created, number of ADDs leaves **potentially huge**.
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite, number of leaves bounded, **ADDs smaller**.

PPUDD: Possibilistic Planning Using Decision Diagrams

```
1  $V^* \leftarrow 0$  ;  $V^c \leftarrow \mu$  ;  $\delta \leftarrow \bar{a}$  ;  
2 while  $V^* \neq V^c$  do  
3    $V^* \leftarrow V^c$  ;  
4   for  $a \in \mathcal{A}$  do  
5      $q^a \leftarrow$  swap each  $X_i$  variable in  $V^*$  with  $X'_i$  ;  
6     for  $1 \leq i \leq n$  do  
7        $q^a \leftarrow \boxed{\min} \{ q^a, \pi(X'_i \mid \text{parents}(X'_i), a) \}$  ;  
8        $q^a \leftarrow \boxed{\max}_{X'_i} q^a$  ;  
9      $V^c \leftarrow \boxed{\max} \{ q^a, V^c \}$  ;  
10    update  $\delta$  to  $a$  where  $q^a = V^c$  and  $V^c > V^*$  ;  
11 return  $(V^*, \delta)$  ;
```

computations on trees: *CU Decision Diagram Package*.

Solver π -MOMDP résultant: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created, number of ADDs leaves **potentially huge**.
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite, number of leaves bounded, **ADDs smaller**.

PPUDD: Possibilistic Planning Using Decision Diagrams

```
1  $V^* \leftarrow 0$  ;  $V^c \leftarrow \mu$  ;  $\delta \leftarrow \bar{a}$  ;  
2 while  $V^* \neq V^c$  do  
3    $V^* \leftarrow V^c$  ;  
4   for  $a \in \mathcal{A}$  do  
5      $q^a \leftarrow$  swap each  $X_i$  variable in  $V^*$  with  $X'_i$  ;  
6     for  $1 \leq i \leq n$  do  
7        $q^a \leftarrow \boxed{\min} \{ q^a, \pi(X'_i \mid \text{parents}(X'_i), a) \}$  ;  
8        $q^a \leftarrow \boxed{\max}_{X'_i} q^a$  ;  
9      $V^c \leftarrow \boxed{\max} \{ q^a, V^c \}$  ;  
10    update  $\delta$  to  $a$  where  $q^a = V^c$  and  $V^c > V^*$  ;  
11 return  $(V^*, \delta)$  ;
```

factorization

\Rightarrow dynamic programming

computations on trees: *CU Decision Diagram Package*.

Solver π -MOMDP résultant: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created, number of ADDs leaves **potentially huge**.
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite, number of leaves bounded, **ADDs smaller**.

PPUDD: Possibilistic Planning Using Decision Diagrams


```
1  $V^* \leftarrow 0$  ;  $V^c \leftarrow \mu$  ;  $\delta \leftarrow \bar{a}$  ;  
2 while  $V^* \neq V^c$  do ← factorization  
3    $V^* \leftarrow V^c$  ;  
4   for  $a \in \mathcal{A}$  do ⇒ dynamic programming  
5      $q^a \leftarrow$  swap each  $X_i$  variable in  $V^*$  with  $X'_i$  ;  
6     for  $1 \leq i \leq n$  do ← divided into  $n$  stages  
7        $q^a \leftarrow \boxed{\min} \{ q^a, \pi(X'_i \mid \text{parents}(X'_i), a) \}$  ;  
8        $q^a \leftarrow \boxed{\max}_{X'_i} q^a$  ;  
9        $V^c \leftarrow \boxed{\max} \{ q^a, V^c \}$  ;  
10      update  $\delta$  to  $a$  where  $q^a = V^c$  and  $V^c > V^*$  ; → used ADDs smaller  
11 return  $(V^*, \delta)$  ; → faster computations.
```

computations on trees: *CU Decision Diagram Package*.

Natural factorisation: belief independence.

contribution (AAAI14): π -MOMDP following independence assumptions of the graphical model:

$\Rightarrow (s_v, \beta) = (s_{v,1}, \dots, s_{v,m}, \beta_1, \dots, \beta_l)$, β_i belief over $s_{h,i}$.




Natural factorisation: belief independence.

contribution (AAAI14): π -MOMDP following independence assumptions of the graphical model:

$\Rightarrow (s_v, \beta) = (s_{v,1}, \dots, s_{v,m}, \beta_1, \dots, \beta_l)$, β_i belief over $s_{h,i}$.

assumptions: independent captors, hidden states...



Experiments: Navigation problem – agent = robot.

PPUDD vs SPUDD (*Hoey et al.*)

Navigation benchmark: reach a goal; spots with accident risk.

2 possibilistic translations: M1 (optimistic) et M2 (cautious).


Experiments: Navigation problem – agent = robot.

PPUDD vs SPUDD (*Hoey et al.*)


Navigation benchmark: reach a goal; spots with accident risk.
2 possibilistic translations: M1 (optimistic) et M2 (cautious).

Performances, function of the instance size

reached goal frequency




time to reach the goal




Experiments: Navigation problem – agent = robot.

computation time



max size of ADDs



- PPUDD + M2 (pessimistic translation) **faster and same performances** as SPUDD;
- SPUDD only solves the 5 first instances;
- verified intuition: ADDs are smaller.

Experiments: RockSample problem – agent = robot.

PPUDD vs APPL (*Kurniawati et al.*, solver MOMDP);
symbolic HSVI (*Sim et al.*, solver POMDP).

RockSample benchmark: recognize and sample “good” rocks;


Experiments: RockSample problem – agent = robot.

PPUDD vs APPL (*Kurniawati et al.*, solver MOMDP);
symbolic HSVI (*Sim et al.*, solver POMDP).

RockSample benchmark: recognize and sample “good” rocks;


computation time:

probabilistic solvers, prec. 1;
PPUDD, exact resolution.



average of rewards

APPL stopped when
PPUDD ends.



- **approximate model + exact resolution solver**
→ can improve of computation time and performances.

IPPC 2014 – MDP track. ADDs-based approaches: PPUDD vs symbolic LRTDP (*Bonet et al.*)

PPUDD + BDD mask over reachable states.





Figure : mean of rewards over simulations.

- 1 Context
- 2 Mixed-Observability and unbounded mission durations
- 3 Factored π -MOMDP and computations with ADDs
- 4 Belief factorization
- 5 Human-machine interaction
- 6 An hybrid POMDP
- 7 Benefiting from factorized structures

assumptions of the Dynamic Bayesian Network below has a natural factorization:


$(s_v, \beta) = (s_{v,1}, \dots, s_{v,m}, \beta_1, \dots, \beta_l)$, with β_i belief about $s_{h,i}$.



assumptions of the Dynamic Bayesian Network below has a natural factorization:


$(s_v, \beta) = (s_{v,1}, \dots, s_{v,m}, \beta_1, \dots, \beta_l)$, with β_i belief about $s_{h,i}$.

some assumptions: one observation variable for each hidden state variable, hidden state variables independent on other hidden state variables ...




beginning of the proof:

- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d -separated** by evidence h_t (history)




beginning of the proof:

- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d -separated** by evidence h_t (history)




beginning of the proof:

- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d -separated** by evidence h_t (history)




beginning of the proof:

- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d-separated** by evidence h_t (history)




beginning of the proof:

- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d -separated** by evidence h_t (history)




beginning of the proof:

- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d -separated** by evidence h_t (history)




beginning of the proof:

- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d -separated** by evidence h_t (history)




beginning of the proof:

- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d -separated** by evidence h_t (history)




beginning of the proof:

- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d -separated** by evidence h_t (history)




beginning of the proof:

- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d -separated** by evidence h_t (history)




beginning of the proof:

- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d -separated** by evidence h_t (history)



beginning of the proof:

- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d -separated** by evidence h_t (history)




beginning of the proof:

- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d-separated** by evidence h_t (history)

→ for each time t , hidden state variables $s_{h,i}$ are independent given h_t

i.e. $\beta_t(s_h) = \pi(s_h \mid h_t) = \min_i \pi(s_{h,i} \mid h_t) = \min_i \beta_{t,i}(s_{h,i})$



Possibility Theory:

- **granulated** belief space representation (discretization),
- efficient problem **simplification** (PPUDD 2× better than LRTDP with ADDs);
- **ignorance and imprecision** modeling.


Possibility Theory:

- **granulated** belief space representation (discretization),
 - efficient problem **simplification** (PPUDD 2× better than LRTDP with ADDs);
 - **ignorance and imprecision** modeling.
-
- ADD methods \prec state space search methods: winners of IPPC 2014, (PROST & GOURMAND, 2× better than PPUDD).
 - choice of the qualitative criterion (optimistic/pessimistic);
 - non additive utility degrees, from the same scale as possibility degrees.

- 1 Context
- 2 Mixed-Observability and unbounded mission durations
- 3 Factored π -MOMDP and computations with ADDs
- 4 Belief factorization
- 5 Human-machine interaction**
- 6 An hybrid POMDP
- 7 Benefiting from factorized structures


Processus π -MOMDPs, outils de diagnostic pour l'Interaction Homme-Machine (avec Sergio Pizziol)

- **occurrences:** états de la machine et actions humaines;
- **évaluation humaine** (de l'état de la machine);
- **effets:** transitions, classées par degrés de possibilité.



Processus π -MOMDPs, outils de diagnostic pour l'Interaction Homme-Machine (avec Sergio Pizziol)

- **occurrences:** états de la machine et actions humaines;
- **évaluation humaine** (de l'état de la machine);
- **effets:** transitions, classées par degrés de possibilité.



- **estimation** de l'état selon l'opérateur humain;
- **détection** des erreurs humaines d'évaluation de l'état;
- causes plausibles de ces erreurs (**diagnostique**).

- 1 Context
- 2 Mixed-Observability and unbounded mission durations
- 3 Factored π -MOMDP and computations with ADDs
- 4 Belief factorization
- 5 Human-machine interaction
- 6 An hybrid POMDP
- 7 Benefiting from factorized structures

A possibilistic belief state

belief space discretization

$$\Pi_S = \left\{ \text{possibility distributions} \right\}: \# \Pi_S < +\infty$$

→ **belief space discretization.**

A possibilistic belief state

belief space discretization

$$\Pi_S = \left\{ \text{possibility distributions} \right\}: \# \Pi_S < +\infty$$

→ **belief space discretization.**

$$b_t^\pi(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

A possibilistic belief state

belief space discretization

$$\Pi_S = \left\{ \text{possibility distributions} \right\}: \# \Pi_S < +\infty$$

→ **belief space discretization.**

$$b_t^\pi(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

update – **possibilistic** belief state

$$b_{t+1}^\pi(s') = \begin{cases} 1 & \text{if } \pi(o', s' \mid b_t^\pi, a) = \pi(o' \mid b_t^\pi, a) \\ \pi(o', s' \mid b_t^\pi, a) & \text{otherwise.} \end{cases}$$

denoted by $b_{t+1}^\pi(s') \propto^\pi \pi(o', s' \mid b_t^\pi, a)$

A possibilistic belief state

belief space discretization

$$\Pi_S = \left\{ \text{possibility distributions} \right\}: \# \Pi_S < +\infty$$

→ **belief space discretization.**

$$b_t^\pi(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

update – **possibilistic** belief state

$$b_{t+1}^\pi(s') = \begin{cases} 1 & \text{if } \pi(o', s' \mid b_t^\pi, a) = \pi(o' \mid b_t^\pi, a) \\ \pi(o', s' \mid b_t^\pi, a) & \text{otherwise.} \end{cases}$$

denoted by $b_{t+1}^\pi(s') \propto^\pi \pi(o', s' \mid b_t^\pi, a)$

- $\pi(o', s' \mid b_t^\pi, a) = \max_{s \in \mathcal{S}} \min \left\{ \pi(o' \mid s', a), \pi(s' \mid s, a), b_t^\pi(s) \right\};$
- $\pi(o' \mid s', a) = \max_{s' \in \mathcal{S}} \pi(o', s' \mid b_t^\pi, a).$

A possibilistic belief state

belief space discretization

$$\Pi_S = \left\{ \text{possibility distributions} \right\}: \# \Pi_S < +\infty$$

→ **belief space discretization.**

$$b_t^\pi(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

update – **possibilistic** belief state

$$b_{t+1}^\pi(s') = \begin{cases} 1 & \text{if } \pi(o', s' \mid b_t^\pi, a) = \pi(o' \mid b_t^\pi, a) \\ \pi(o', s' \mid b_t^\pi, a) & \text{otherwise.} \end{cases}$$

denoted by $b_{t+1}^\pi(s') \propto^\pi \pi(o', s' \mid b_t^\pi, a)$

- the update **only depends on o' and a .**

Pignistic transformation and transitions

Pignistic transformation

numbering of the $n = \#\mathcal{S}$ system states:

$$1 = b^\pi(s_1) \geq \dots \geq b^\pi(s_n) \geq b^\pi(s_{n+1}) = 0.$$

pignistic transformation – $P : \Pi_{\mathcal{S}} \rightarrow \mathbb{P}_{\mathcal{S}}$

$$\overline{b^\pi}(s_i) = \sum_{j=i}^{\#\mathcal{S}} \frac{b^\pi(s_j) - b^\pi(s_{j+1})}{j}.$$

- probability distribution $\overline{b^\pi} =$ **gravity center** of the represented probabilistic distributions;
- **Laplace principle**: ignorance \rightarrow uniform probability.

Pignistic transformation

Examples of pignistic transformations (red) of possibility distributions (blue)

Pignistic transformation and transitions

Transition function of epistemic states

Approximation of the probabilities over the observations:

- $\mathbf{p}(o' \mid s, a) = \sum_{s' \in \mathcal{S}} O(s', a, o') \cdot T(s, a, s')$;
- $\mathbf{p}(o' \mid b^\pi, a) := \sum_{s \in \mathcal{S}} \mathbf{p}(o' \mid s, a) \cdot \overline{b^\pi}(s).$

$$\Rightarrow \mathbf{p}\left((b^\pi)' \mid b^\pi, a\right) = \sum_{\substack{o' \text{ t.q.} \\ u(b^\pi, a, o') = (b^\pi)'}} \mathbf{p}(o' \mid b^\pi, a).$$

notation: if $a \in \mathcal{A}$ selected, $o' \in \mathcal{O}$ received,

$$b_{t+1}^\pi = u(o', a, b_t^\pi) = \text{update of } b_t^\pi.$$

Choquet integral and rewards

pessimistic evaluation of the rewards – necessity measure

imprecision of b^π = agent ignorance + discretization:
pessimistic reward about these imprecisions.

Choquet integral and rewards

pessimistic evaluation of the rewards – necessity measure

imprecision of b^π = agent ignorance + discretization:
pessimistic reward about these imprecisions.

Dual measure of $\Pi : 2^{\mathcal{S}} \rightarrow \mathcal{L}$

necessity \mathcal{N} such that $\forall A \subseteq \mathcal{S}, \mathcal{N}(A) = 1 - \Pi(\overline{A})$.

Choquet integral and rewards

pessimistic evaluation of the rewards – necessity measure

imprecision of b^π = agent ignorance + discretization:

pessimistic reward about these imprecisions.

Dual measure of $\Pi : 2^{\mathcal{S}} \rightarrow \mathcal{L}$

necessity \mathcal{N} such that $\forall A \subseteq \mathcal{S}, \mathcal{N}(A) = 1 - \Pi(\bar{A})$.

$r_1 > r_2 > \dots > r_{k+1} = 0$ represents elements of $\{r(s, a) | s \in \mathcal{S}\}$.

Choquet integral of r with respect to \mathcal{N}

$$Ch(r, \mathcal{N}) = \sum_{i=1}^k (r_i - r_{i+1}) \cdot \mathcal{N}(\{r(s) \geq r_i\}) \quad (1)$$

(2)

Choquet integral and rewards

pessimistic evaluation of the rewards – necessity measure

imprecision of b^π = agent ignorance + discretization:
pessimistic reward about these imprecisions.

Dual measure of $\Pi : 2^{\mathcal{S}} \rightarrow \mathcal{L}$

necessity \mathcal{N} such that $\forall A \subseteq \mathcal{S}, \mathcal{N}(A) = 1 - \Pi(\bar{A})$.

$r_1 > r_2 > \dots > r_{k+1} = 0$ represents elements of $\{r(s, a) | s \in \mathcal{S}\}$.

Choquet integral of r with respect to \mathcal{N}


$$Ch(r, \mathcal{N}) = \sum_{i=1}^k (r_i - r_{i+1}) \cdot \mathcal{N}(\{r(s) \geq r_i\}) \quad (1)$$

$$= \sum_{i=1}^{\#\mathcal{L}-1} (l_i - l_{i+1}) \cdot \min_{\substack{s \in \mathcal{S} \text{ s.t.} \\ b^\pi(s) \geq l_i}} r(s). \quad (2)$$

notation $\mathcal{L} = \{l_1 = 1, l_2, l_3, \dots, 0\}$.


Choquet integral and rewards

back to the example about ignorance



Choquet integral and rewards

back to the example about ignorance




- $Ch(r, N_{b_1^\pi} \mid a_0 = \tilde{a}) = r(s_D, \tilde{a}) = 5,$
- $Ch(r, N_{b_1^\pi} \mid a_0 = a') = \min_{s \in \mathcal{S}} r(s, a') = 0.$

the safe action is preferred! **dispersion reduced**

Choquet integral and rewards

back to the example about ignorance



- $Ch(r, N_{b_1^\pi} \mid a_0 = \tilde{a}) = r(s_D, \tilde{a}) = 5,$
- $Ch(r, N_{b_1^\pi} \mid a_0 = a') = \min_{s \in \mathcal{S}} r(s, a') = 0.$

the safe action is preferred! **dispersion reduced**

if $\mathcal{N}_{b_1^\pi}$ replaced by $b_1 \Rightarrow Ch(r, b_1) = \mathbb{E}_{s \sim b_1} [r(s, a)]$.

resulting MDP

translation summary

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

resulting MDP

translation summary

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{S}}$,
the set of the possibility distributions over \mathcal{S} ;

resulting MDP

translation summary

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{S}}$,
the set of the possibility distributions over \mathcal{S} ;
- $\forall b^{\pi}, (b^{\pi})'$ possibilistic belief states $\in \Pi_{\mathcal{S}}, \forall a \in \mathcal{A}$,
transitions $\tilde{T}(b^{\pi}, a, (b^{\pi})') = \mathbf{p}((b^{\pi})' | b^{\pi}, a)$;

resulting MDP

translation summary

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{S}}$,
the set of the possibility distributions over \mathcal{S} ;
- $\forall b^\pi, (b^\pi)'$ possibilistic belief states $\in \Pi_{\mathcal{S}}, \forall a \in \mathcal{A}$,
transitions $\tilde{T}(b^\pi, a, (b^\pi)') = \mathbf{p}((b^\pi)' | b^\pi, a)$;
- **reward** $\tilde{r}(a, b^\pi) = Ch(r(a, \cdot), \mathcal{N}_{b^\pi})$,
 \mathcal{N}_{b^π} necessity measure computed from b^π .

resulting MDP

translation summary

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{S}}$,
the set of the possibility distributions over \mathcal{S} ;
- $\forall b^\pi, (b^\pi)'$ possibilistic belief states $\in \Pi_{\mathcal{S}}, \forall a \in \mathcal{A}$,
transitions $\tilde{T}(b^\pi, a, (b^\pi)') = \mathbf{p}((b^\pi)' | b^\pi, a)$;
- **reward** $\tilde{r}(a, b^\pi) = Ch(r(a, \cdot), \mathcal{N}_{b^\pi})$,
 \mathcal{N}_{b^π} necessity measure computed from b^π .

$$\text{criterion: } \mathbb{E}_{(b_t^\pi) \sim \tilde{T}} \left[\sum_{t=0}^{+\infty} \gamma^t \cdot \tilde{r}(b_t^\pi, d_t) \right].$$

hybrid POMDP and π -POMDP

differences with possibilistic models

	hybrid POMDP	π -POMDP
transitions	probabilities	qualitative possibility
rewards	quantitative $\in \mathbb{R}$	qualitative $\in \mathcal{L}$
situation	-some imprecisions -large POMDP	few quantitative
issues	π definition	commensurability
in practice	MDP	π -MDP

hybrid POMDP and π -POMDP

differences with possibilistic models

	hybrid POMDP	π -POMDP
transitions	probabilities	qualitative possibility
rewards	quantitative $\in \mathbb{R}$	qualitative $\in \mathcal{L}$
situation	-some imprecisions -large POMDP	few quantitative
issues	π definition	commensurability
in practice	MDP	π -MDP

hybrid model:

- only belief states are possibilistic:
 - agent knowledge = **possibility** distribution;
- probabilistic dynamics:
 - **approximated** (prob.) transition between epistemic states.

- 1 Context
- 2 Mixed-Observability and unbounded mission durations
- 3 Factored π -MOMDP and computations with ADDs
- 4 Belief factorization
- 5 Human-machine interaction
- 6 An hybrid POMDP
- 7 Benefiting from factorized structures

factorized POMDP

definition

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;

factorized POMDP

definition

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;
- **transition** function of s'_j ,
 $T_j^a(\mathbb{S}, s'_j) = \mathbf{p}(s'_j \mid \mathbb{S}, a), \forall j \in \{1, \dots, m\}$ et $\forall a \in \mathcal{A}$;

factorized POMDP

definition

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;
- **transition** function of s'_j ,
 $T_j^a(\mathbb{S}, s'_j) = \mathbf{p}(s'_j \mid \mathbb{S}, a)$, $\forall j \in \{1, \dots, m\}$ et $\forall a \in \mathcal{A}$;
- \mathcal{O} described by $\mathbb{O} = \{o_1, \dots, o_n\}$: $\mathcal{O} = o_1 \times \dots \times o_n$;

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;
- **transition** function of s'_j ,
 $T_j^a(\mathbb{S}, s'_j) = \mathbf{p}(s'_j \mid \mathbb{S}, a)$, $\forall j \in \{1, \dots, m\}$ et $\forall a \in \mathcal{A}$;
- \mathcal{O} described by $\mathbb{O} = \{o_1, \dots, o_n\}$: $\mathcal{O} = o_1 \times \dots \times o_n$;
- **observation** function of o'_i ,
 $O_i^a(\mathbb{S}', o'_i) = \mathbf{p}(o'_i \mid \mathbb{S}', a)$, $\forall i \in \{1, \dots, n\}$ et $\forall a \in \mathcal{A}$.

factorized POMDP

definition

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;
- **transition** function of s'_j ,
 $T_j^a(\mathbb{S}, s'_j) = \mathbf{p}(s'_j \mid \mathbb{S}, a)$, $\forall j \in \{1, \dots, m\}$ et $\forall a \in \mathcal{A}$;
- \mathcal{O} described by $\mathbb{O} = \{o_1, \dots, o_n\}$: $\mathcal{O} = o_1 \times \dots \times o_n$;
- **observation** function of o'_i ,
 $O_i^a(\mathbb{S}', o'_i) = \mathbf{p}(o'_i \mid \mathbb{S}', a)$, $\forall i \in \{1, \dots, n\}$ et $\forall a \in \mathcal{A}$.

independences:

- $\rightarrow \forall s'_i, s'_j \in \mathbb{S}', \quad s'_i \perp\!\!\!\perp s'_j \mid \{\mathbb{S}, a \in \mathcal{A}\},$
- $\rightarrow \forall o'_i, o'_j \in \mathbb{O}', \quad o'_i \perp\!\!\!\perp o'_j \mid \{\mathbb{S}', a \in \mathcal{A}\}.$

Notations

some variables does not interact with each other

variables about the **current** system state,

s_1

\vdots

s_{j_1}

\vdots

s_{j_2}

\vdots

\vdots

\vdots

s_{j_k}

\vdots

s_m

variable s'_j about
the **next** state.

s'_j

Notations

some variables does not interact with each other


variables about the **current** system state,

$$s_k \rightarrow s'_j$$



$\exists a \in \mathcal{A}$, such that

$T_j^a(\mathbb{S}, s'_j)$ depends on s_k .




Notations

some variables does not interact with each other

variables about the **current** system state,

$s_k \rightarrow s'_j$
 \Updownarrow
 $\exists a \in \mathcal{A}$, such that
 $T_j^a(\mathbb{S}, s'_j)$ depends on s_k .




the parents of s'_j are:

$$\begin{aligned}\mathcal{P}(s'_j) &= \{s \in \mathbb{S} \mid s \rightarrow s'_j\} \\ &= \{s_{j_1}, s_{j_2}, \dots, s_{j_k}\}.\end{aligned}$$

Notations

concerning observation variables

next state



Notations

concerning observation variables

$$s'_j \rightarrow o'_i$$




$\exists a \in \mathcal{A}$, such that

$$O_i^a(S', o'_i)$$

depends on s'_j .

next state



Notations

concerning observation variables


$$s'_j \rightarrow o'_i$$



$\exists a \in \mathcal{A}$, such that

$$O_i^a(\mathbb{S}', o'_i)$$

depends on s'_j .



Notations


concerning observation variables

$$s'_j \rightarrow o'_i$$




$\exists a \in \mathcal{A}$, such that

$O_i^a(S', o'_i)$
depends on s'_j .



next state



Notations


concerning observation variables

$$s'_j \rightarrow o'_i$$



$\exists a \in \mathcal{A}$, such that

$O_i^a(S', o'_i)$
depends on s'_j .



Notations

concerning observation variables


$$s'_j \rightarrow o'_i$$



$\exists a \in \mathcal{A}$, such that


$$O_i^a(S', o'_i)$$

depends on s'_j .



Notations

concerning observation variables



Rewritings of parameters

PROBABILISTIC parameters

- $T_j^a(\mathbb{S}, s'_j) = T_j^a(\mathcal{P}(s'_j), s'_j);$
- $O_i^a(\mathbb{S}', o'_i) = O_i^a(\mathcal{P}(o'_i), o'_i).$

Rewritings of parameters

PROBABILISTIC parameters

- $T_j^a(\mathbb{S}, s'_j) = T_j^a(\mathcal{P}(s'_j), s'_j);$
- $O_i^a(\mathbb{S}', o'_i) = O_i^a(\mathcal{P}(o'_i), o'_i).$

consequences on the joint distribution

$$\begin{aligned}\mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathbb{S}, a) &= O_i^a(\mathcal{P}(o'_i), o'_i) \cdot \prod_{s'_j \in \mathcal{P}(o'_i)} T_j^a(\mathcal{P}(s'_j), s'_j) \\ &= \mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a).\end{aligned}$$

Rewritings of parameters

PROBABILISTIC parameters

- $T_j^a(\mathbb{S}, s'_j) = T_j^a(\mathcal{P}(s'_j), s'_j);$
- $O_i^a(\mathbb{S}', o'_i) = O_i^a(\mathcal{P}(o'_i), o'_i).$

consequences on the joint distribution

$$\begin{aligned}\mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathbb{S}, a) &= O_i^a(\mathcal{P}(o'_i), o'_i) \cdot \prod_{s'_j \in \mathcal{P}(o'_i)} T_j^a(\mathcal{P}(s'_j), s'_j) \\ &= \mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a).\end{aligned}$$

observation probabilities

epistemic state

$$b^\pi(\mathbb{S}) \xrightarrow{\text{marginalization}} b^\pi(\mathcal{Q}(o'_i)) \xrightarrow{\text{pignistic transformation}} \overline{b}^\pi(\mathcal{Q}(o'_i))$$

$$\mathbf{p}(o'_i \mid b^\pi, a) = \sum_{2^{\mathcal{P}(o'_i)}, 2^{\mathcal{Q}(o'_i)}} \mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a) \cdot \overline{b}^\pi(\mathcal{Q}(o'_i))$$

Parameters rewritings

POSSIBILISTIC parameters

- $\pi(s'_j \mid \mathbb{S}, a) = \pi(s'_j \mid \mathcal{P}(s'_j), a);$
- $\pi(o'_i \mid \mathbb{S}', a) = \pi(o'_i \mid \mathcal{P}(o'_i), a).$

- $\pi(s'_j \mid \mathbb{S}, a) = \pi(s'_j \mid \mathcal{P}(s'_j), a);$
- $\pi(o'_i \mid \mathbb{S}', a) = \pi(o'_i \mid \mathcal{P}(o'_i), a).$

marginal possibilistic belief states

$$\forall o'_i \in \mathbb{O},$$
$$b_{t+1}^{\pi}(\mathcal{P}(o'_i)) \propto^{\pi} \pi(o'_i, \mathcal{P}(o'_i) \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

- $\pi(s'_j \mid \mathbb{S}, a) = \pi(s'_j \mid \mathcal{P}(s'_j), a);$
- $\pi(o'_i \mid \mathbb{S}', a) = \pi(o'_i \mid \mathcal{P}(o'_i), a).$

marginal possibilistic belief states

$$\begin{aligned} \forall o'_i \in \mathbb{O}, \\ b_{t+1}^\pi(\mathcal{P}(o'_i)) &\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid a_0, o_1, \dots, a_{t-1}, o_t) \\ &= \max_{2^{\mathcal{Q}(o'_i)}} \min \left\{ \pi(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a), b_t^\pi(\mathcal{Q}(o'_i)) \right\} \end{aligned}$$

- $\pi(s'_j \mid \mathbb{S}, a) = \pi(s'_j \mid \mathcal{P}(s'_j), a);$
- $\pi(o'_i \mid \mathbb{S}', a) = \pi(o'_i \mid \mathcal{P}(o'_i), a).$

marginal possibilistic belief states

$$\forall o'_i \in \mathbb{O},$$

$$\begin{aligned} b_{t+1}^\pi(\mathcal{P}(o'_i)) &\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid a_0, o_1, \dots, a_{t-1}, o_t) \\ &= \max_{2^{\mathcal{Q}(o'_i)}} \min \left\{ \pi(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a), b_t^\pi(\mathcal{Q}(o'_i)) \right\} \\ &\quad \text{denoted by } \pi(o'_i, \mathcal{P}(o'_i) \mid b_t^\pi, a). \end{aligned}$$

Variable classification

3 classes of state variables

variable: visible $s_v \in \mathbb{S}_v$

s'_v

inferred hidden $s_h \in \mathbb{S}_h$

s'_h


fully hidden $s_f \in \mathbb{S}_f$

s'_f

Variable classification

3 classes of state variables

variable: **visible** $s_v \in \mathbb{S}_v$



inferred hidden $s_h \in \mathbb{S}_h$




fully hidden $s_f \in \mathbb{S}_f$



Variable classification

3 classes of state variables

variable: **visible** $s_v \in \mathbb{S}_v$



$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b_t^\pi}(\mathcal{P}(s'_v)).$$

inferred hidden $s_h \in \mathbb{S}_h$



fully hidden $s_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables

variable: **visible** $s_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.



$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b}_t^\pi(\mathcal{P}(s'_v)).$$

inferred hidden $s_h \in \mathbb{S}_h$



fully hidden $s_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables


variable: **visible** $s_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.

$$\mathbf{p}(s'_v \mid b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b}_t^\pi(\mathcal{P}(s'_v)).$$



inferred hidden $s_h \in \mathbb{S}_h$



fully hidden $s_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables

variable: **visible** $s_v \in \mathbb{S}_v$


\Leftrightarrow deterministic belief variable.

$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b}_t^\pi(\mathcal{P}(s'_v)).$$



inferred hidden $s_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$



fully hidden $s_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables

variable: **visible** $s_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v \mid b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b}_t^\pi(\mathcal{P}(s'_v)).$$



inferred hidden $s_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid b_t^\pi, a).$$



fully hidden $s_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables

variable: **visible** $s_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b}_t^\pi(\mathcal{P}(s'_v)).$$



inferred hidden $s_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) | b_t^\pi, a).$$



\triangle $\mathcal{P}(o'_i)$ may contain visible variables.

fully hidden $s_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables

variable: **visible** $s_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b}_t^\pi(\mathcal{P}(s'_v)).$$



inferred hidden $s_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) | b_t^\pi, a).$$



$\triangle!$ $\mathcal{P}(o'_i)$ may contain visible variables.

fully hidden $s_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables

variable: **visible** $s_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b}_t^\pi(\mathcal{P}(s'_v)).$$



inferred hidden $s_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) | b_t^\pi, a).$$



$\triangle!$ $\mathcal{P}(o'_i)$ may contain visible variables.

fully hidden $s_f \in \mathbb{S}_f$



$$b_{t+1}^\pi(s'_f) = \max_{2^{\mathcal{P}(s'_f)}} \min \left\{ \pi(s'_f | \mathcal{P}(s'_f), a), b_t^\pi(\mathcal{P}(s'_f)) \right\}.$$


Variable classification

3 classes of state variables

variable: **visible** $s_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.

$$\mathbf{p}(s'_v \mid b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b}_t^\pi(\mathcal{P}(s'_v)).$$




inferred hidden $s_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid b_t^\pi, a).$$

$\triangle!$ $\mathcal{P}(o'_i)$ may contain visible variables.



fully hidden $s_f \in \mathbb{S}_f$

\rightarrow observations don't
inform belief state on s'_f .

$$b_{t+1}^\pi(s'_f) = \max_{2^{\mathcal{P}(s'_f)}} \min \left\{ \pi(s'_f \mid \mathcal{P}(s'_f), a), b_t^\pi(\mathcal{P}(s'_f)) \right\}.$$



Possibilistic belief variables

global belief state

$$\mathbb{O}_h = \mathbb{O} \setminus \mathbb{S}_v.$$

bound over the global belief state

$$b_{t+1}^\pi(\mathbb{S}') = \pi(\mathbb{S}' \mid a_0, o_1, \dots, a_t, o_{t+1})$$

$$\leq \beta_{t+1}(\mathbb{S}')$$

$$= \min \left\{ \min_{s'_j \in \mathbb{S}_v} \left[\mathbb{1}_{\{s'_j = o'_j\}} \right], \min_{s'_j \in \mathbb{S}_f} \left[b_{t+1}^\pi(s'_j) \right], \min_{o'_i \in \mathbb{O}_h} \left[b_{t+1}^\pi(\mathcal{P}(o'_i)) \right] \right\}$$

Possibilistic belief variables

global belief state

$$\mathbb{O}_h = \mathbb{O} \setminus \mathbb{S}_v.$$

bound over the global belief state

$$b_{t+1}^\pi(\mathbb{S}') = \pi(\mathbb{S}' \mid a_0, o_1, \dots, a_t, o_{t+1})$$

$$\leq \beta_{t+1}(\mathbb{S}')$$

$$= \min \left\{ \min_{s'_j \in \mathbb{S}_v} \left[\mathbb{1}_{\{s'_j = o'_j\}} \right], \min_{s'_j \in \mathbb{S}_f} \left[b_{t+1}^\pi(s'_j) \right], \min_{o'_i \in \mathbb{O}_h} \left[b_{t+1}^\pi(\mathcal{P}(o'_i)) \right] \right\}$$

- β_t = **less informative** version of the belief state:
 $b_t^\pi \leq \beta_t$;
- computed using **marginal belief states** \leftrightarrow **factorization**.

Variables de croyance

different according to the class of the variable

$$\lambda = \#\mathcal{L}$$

Variables de croyance

different according to the class of the variable

$$\lambda = \#\mathcal{L}$$

- $\forall s'_v \in \mathbb{S}_v$, 1 variable β'_v is enough.

Variables de croyance

different according to the class of the variable

$$\lambda = \#\mathcal{L}$$

■ $\forall s'_v \in \mathbb{S}_v$, 1 variable β'_v is enough.

■ $p_i = \#\mathcal{P}(o'_i)$.

$\forall o_i \in \mathbb{O} \setminus \mathbb{S}_v$, $\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}$ belief states,

$\Rightarrow \lceil \log_2(\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}) \rceil$ boolean variables β'_h .

Variables de croyance

different according to the class of the variable

$$\lambda = \#\mathcal{L}$$

■ $\forall s'_v \in \mathbb{S}_v$, 1 variable β'_v is enough.

■ $p_i = \#\mathcal{P}(o'_i)$.

$\forall o_i \in \mathbb{O} \setminus \mathbb{S}_v$, $\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}$ belief states,

$\Rightarrow \lceil \log_2(\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}) \rceil$ boolean variables β'_h .

■ $\forall s'_f \in \mathbb{S}_f$, $\lambda^2 - (\lambda - 1)^2 = 2\lambda - 1$ belief states,

$\Rightarrow \lceil \log_2(2\lambda - 1) \rceil$ boolean variables β'_f .

resulting MDP in practice

trick: “flipflop” variable

boolean variable “*flipflop*” f changes state at each time step
→ defines 2 phases:

- 1 *observation generation*,
- 2 *belief update* (deterministic knowing the observation).

MDP variables:

$\tilde{S} =$


beliefs: $\beta = \beta_v^1 \times \dots \times \beta_v^{m_v} \times \beta_h^1 \times \dots \times \beta_h^{m_h} \times \beta_f^1 \times \dots \times \beta_f^{m_f}$

\times

visible variables : $v = f \times s_v^1 \times \dots \times s_v^{m_v} \times o_1 \times \dots \times o_k.$

resulting MDP in practice

final structured MDP



$\tilde{\mathcal{S}} =$


beliefs: $\beta = \beta_v^1 \times \dots \times \beta_v^{m_v} \times \beta_h^1 \times \dots \times \beta_h^{m_h} \times \beta_f^1 \times \dots \times \beta_f^{m_f}$

\times

visible variables : $v = f \times s_v^1 \times \dots \times s_v^{m_v} \times o_1 \times \dots \times o_k.$

resulting MDP in practice

final structured MDP



factorized model's variables: $\#\mathbb{O} + \#\mathbb{S}_v +$

$$+ \sum_{i=1}^{\#\mathbb{O}_h} \left[\log_2 (\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}) \right] + \#\mathbb{S}_f \cdot \left[\log_2 (2\lambda - 1) \right]$$


\ll

initial hybrid model's variables:

$$\left[\log_2 (\lambda^{2^{\#\mathbb{S}}} - (\lambda - 1)^{2^{\#\mathbb{S}}}) \right]$$

resulting MDP in practice

final structured MDP



factorized model's variables:

$$\leq \#\mathbb{O} + \#S_v + \sum_{i=1}^{\#\mathbb{O}_h} \log_2(\lambda) \cdot 2^{p_i} + \#S_f \cdot (1 + \log_2(\lambda))$$

\ll # initial hybrid model's variables:
 $\geq \log_2(\lambda) \cdot (2^{\#\mathbb{S}} - 1).$

- 1 Context
- 2 Mixed-Observability and unbounded mission durations
- 3 Factored π -MOMDP and computations with ADDs
- 4 Belief factorization
- 5 Human-machine interaction
- 6 An hybrid POMDP
- 7 Benefiting from factorized structures

POMDP $\xrightarrow{\text{translation}}$ MDP with finite state space

- transition probabilities on the **possibilistic belief states**;

POMDP $\xrightarrow{\text{translation}}$ MDP with finite state space

- transition probabilities on the **possibilistic belief states**;
- **pessimistic** evaluation of the **rewards**
(Choquet integral);

POMDP $\xrightarrow{\text{translation}}$ MDP with finite state space

- transition probabilities on the **possibilistic belief states**;
- **pessimistic** evaluation of the **rewards**
(Choquet integral);
- factorized POMDP $\xrightarrow{\text{translation}}$ **factorized MPD**.

POMDP $\xrightarrow{\text{translation}}$ MDP with finite state space

- transition probabilities on the **possibilistic belief states**;
- **pessimistic** evaluation of the **rewards** (Choquet integral);
- factorized POMDP $\xrightarrow{\text{translation}}$ **factorized MPD**.

perspectives:

- IPPC problems (factorized POMDPs);

POMDP $\xrightarrow{\text{translation}}$ MDP with finite state space

- transition probabilities on the **possibilistic belief states**;
- **pessimistic** evaluation of the **rewards** (Choquet integral);
- factorized POMDP $\xrightarrow{\text{translation}}$ **factorized MPD**.

perspectives:

- IPPC problems (factorized POMDPs);
- tests of this approach:
 - 1 **simplification**: π distributions definition (π -normalization, pignistic transformation, most specific, ...);
 - 2 **imprecision**: robust in practice?

Thank you!