

$\partial_t \psi + \frac{M}{\epsilon} \int_{\Omega} \frac{|u(x,t)|^2}{2} \psi \Delta \psi + \int_{\Omega} p = 0, \quad \nabla \psi = 0, \quad \psi(x,0) = \psi_0(x), \quad \psi(x,t) = \psi_0(x)$

Exploiting Imprecise Information Sources in Sequential Decision Making Problems under Uncertainty

N.Drougard

under D.Dubois, J-L.Farges and F.Teichteil-Königsbuch supervision

doctoral school: EDSYS institution: ISAE-SUPAERO

laboratory: ONERA-The French Aerospace Lab



retour sur innovation

- 1 Context
- 2 Introductory example (HMI)
- 3 Updates of the qualitative possibilistic model
- 4 Symbolic solver and factorization
- 5 An hybrid perspective
- 6 Conclusion/Perspectives

- 1 Context
- 2 Introductory example (HMI)
- 3 Updates of the qualitative possibilistic model
- 4 Symbolic solver and factorization
- 5 An hybrid perspective
- 6 Conclusion/Perspectives

Onera, DCSD

Automatics, AI, Flight Mechanics, Cognitive Sciences

Onera, DCSD

Automatics, AI, Flight Mechanics, Cognitive Sciences


among many other works:

- autonomy, steering architectures and human factors
- decision making, planning
- experimental/industrial applications: UAVs, orbital systems, exploration robots



Context

Partially Observable Markov Decision Processes (POMDPs)




POMDP: model for autonomous robotics



Context

Partially Observable Markov Decision Processes (POMDPs)




POMDP: model for autonomous robotics

$s \in \mathcal{S}$: **system states**




Context

Partially Observable Markov Decision Processes (POMDPs)




Context

Partially Observable Markov Decision Processes (POMDPs)




Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)





Context

Partially Observable Markov Decision Processes (POMDPs)



Context

Partially Observable Markov Decision Processes (POMDPs)



Context

belief state, strategy, criterion

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$ (Smallwood et al. 1973)

■ **transition** function $T(s, a, s') = \mathbf{p}(s' \mid s, a)$

■ **observation** function $O(s', a, o') = \mathbf{p}(o' \mid s', a)$

Context

belief state, strategy, criterion

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$ (Smallwood et al. 1973)

■ **transition** function $T(s, a, s') = \mathbf{p}(s' \mid s, a)$

■ **observation** function $O(s', a, o') = \mathbf{p}(o' \mid s', a)$

belief state: $b_t(s) = \mathbb{P}(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$

Context

belief state, strategy, criterion

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$ (Smallwood et al. 1973)

■ **transition** function $T(s, a, s') = \mathbf{p}(s' | s, a)$

■ **observation** function $O(s', a, o') = \mathbf{p}(o' | s', a)$

belief state: $b_t(s) = \mathbb{P}(s_t = s | a_0, o_1, \dots, a_{t-1}, o_t)$

probabilistic belief update – a selected, o' received

$$b_{t+1}(s') \propto \mathbf{p}(o' | s', a) \cdot \sum_{s \in \mathcal{S}} \mathbf{p}(s' | s, a) \cdot b_t(s)$$

Context

belief state, strategy, criterion

POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$ (Smallwood et al. 1973)

■ **transition** function $T(s, a, s') = \mathbf{p}(s' | s, a)$

■ **observation** function $O(s', a, o') = \mathbf{p}(o' | s', a)$

belief state: $b_t(s) = \mathbb{P}(s_t = s | a_0, o_1, \dots, a_{t-1}, o_t)$

probabilistic belief update – a selected, o' received

$$b_{t+1}(s') \propto \mathbf{p}(o' | s', a) \cdot \sum_{s \in \mathcal{S}} \mathbf{p}(s' | s, a) \cdot b_t(s)$$

action choices: strategy $\delta(b_t) = a_t \in \mathcal{A}$

$$\text{maximizing } \mathbb{E}_{s_0 \sim b_0} \left[\sum_{t=0}^{+\infty} \gamma^t \cdot r(s_t, \delta(b_t)) \right], \quad 0 < \gamma < 1$$

Flaws of the POMDP model

POMDPs in practice

- optimal strategy computation \geq **PSPACE**
(*Papadimitriou et al. 1987*)
- probabilities are **imprecisely known** in practice
- agent's **ignorance** not taken into account

- **POMDP optimal strategy computation undecidable**
in infinite horizon – *Madani et al. (AAAI-99)*

- **POMDP optimal strategy computation undecidable**

in infinite horizon – *Madani et al. (AAAI-99)*

→ optimality for “small” or “structured” POMDPs

→ approximate computations

■ POMDP optimal strategy computation undecidable

in infinite horizon – *Madani et al. (AAAI-99)*

→ optimality for “small” or “structured” POMDPs

→ approximate computations

■ Imprecise model, e.g. vision from statistical learning



■ POMDP optimal strategy computation undecidable

in infinite horizon – *Madani et al. (AAAI-99)*

→ optimality for “small” or “structured” POMDPs

→ approximate computations

■ Imprecise model, e.g. vision from statistical learning

→ unknown environments: image variability of the datasets?



■ POMDP optimal strategy computation undecidable

in infinite horizon – *Madani et al. (AAAI-99)*

→ optimality for “small” or “structured” POMDPs

→ approximate computations

■ Imprecise model, e.g. vision from statistical learning

→ unknown environments: image variability of the datasets?



■ Lack of prior information on the system state:

initial belief state b_0

■ POMDP optimal strategy computation undecidable

in infinite horizon – *Madani et al. (AAAI-99)*

→ optimality for “small” or “structured” POMDPs

→ approximate computations

■ Imprecise model, e.g. vision from statistical learning

→ unknown environments: image variability of the datasets?



■ Lack of prior information on the system state:

initial belief state b_0


→ uniform probability distribution \neq ignorance!

Qualitative Possibility Theory

presentation – (max,min) “tropical” algebra

finite scale \mathcal{L}

usually $\{0, \frac{1}{k}, \frac{2}{k}, \dots, 1\}$



events $e \subset \Omega$ (universe)

sorted using possibility **degrees** $\pi(e) \in \mathcal{L}$

\neq


quantified with **frequencies** $\mathbf{p}(e) \in [0, 1]$ (probabilities)

Qualitative Possibility Theory

presentation – (max,min) “tropical” algebra

finite scale \mathcal{L}

usually $\{0, \frac{1}{k}, \frac{2}{k}, \dots, 1\}$



events $e \subset \Omega$ (universe)

sorted using possibility **degrees** $\pi(e) \in \mathcal{L}$

\neq

quantified with **frequencies** $p(e) \in [0, 1]$ (probabilities)

$e_1 \neq e_2$, 2 events $\subset \Omega$

■ $\pi(e_1) < \pi(e_2) \Leftrightarrow$ “ e_1 is less plausible than e_2 ”

Qualitative Possibility Theory

Criteria from Sugeno integral

Probability / Possibility:

$+$	\max
\times	\min
$X \in \mathbb{R}$	$X \in \mathcal{L}$
$\mathbb{E}[X] = \sum_{x \in X} x \cdot \mathbf{p}(x)$	<p>optimistic:</p> $\mathbb{S}_{\Pi}[X] = \max_{x \in X} \min \{x, \pi(x)\}$ <p>cautious:</p> $\mathbb{S}_{\mathcal{N}}[X] = \min_{x \in X} \max \{x, 1 - \pi(x)\}$

Qualitative Possibility Theory

qualitative possibilistic POMDP (π -POMDP)

Sabbadin (UAI-98) introduces

the qualitative possibilistic POMDP

π -POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T^\pi, O^\pi, \rho \rangle$

Qualitative Possibility Theory

qualitative possibilistic POMDP (π -POMDP)

Sabbadin (UAI-98) introduces

the qualitative possibilistic POMDP

π -POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T^\pi, O^\pi, \rho \rangle$

- **transition** function $T^\pi(s, a, s') = \pi(s' \mid s, a) \in \mathcal{L}$
- **observation** function $O^\pi(s', a, o') = \pi(o' \mid s', a) \in \mathcal{L}$
- **preference** function $\rho : \mathcal{S} \times \mathcal{A} \rightarrow \mathcal{L}$

Qualitative Possibility Theory

qualitative possibilistic POMDP (π -POMDP)

Sabbadin (UAI-98) introduces

the qualitative possibilistic POMDP

π -POMDP: $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T^\pi, O^\pi, \rho \rangle$

- **transition** function $T^\pi(s, a, s') = \pi(s' \mid s, a) \in \mathcal{L}$
 - **observation** function $O^\pi(s', a, o') = \pi(o' \mid s', a) \in \mathcal{L}$
 - **preference** function $\rho : \mathcal{S} \times \mathcal{A} \rightarrow \mathcal{L}$
-
- belief space trick: POMDP \rightarrow MDP with **infinite** \mathcal{S}
 π -POMDP $\rightarrow \pi$ -MDP with **finite** \mathcal{S}
 - $\forall s \in \mathcal{S}, \pi(s) = 1 \Leftrightarrow$ total ignorance about s

A possibilistic belief state

finite belief space

$$\Pi_{\mathcal{L}}^{\mathcal{S}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_{\mathcal{L}}^{\mathcal{S}} \sim \# \mathcal{L}^{\# \mathcal{S}} < +\infty$$

→ *i.e.* **finite belief space**

A possibilistic belief state

finite belief space

$$\Pi_{\mathcal{L}}^{\mathcal{S}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_{\mathcal{L}}^{\mathcal{S}} \sim \# \mathcal{L}^{\# \mathcal{S}} < +\infty$$

→ *i.e.* **finite belief space**

$$b_t^{\pi}(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

A possibilistic belief state

finite belief space

$$\Pi_{\mathcal{L}}^{\mathcal{S}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_{\mathcal{L}}^{\mathcal{S}} \sim \# \mathcal{L}^{\# \mathcal{S}} < +\infty$$

→ *i.e.* **finite belief space**

$$b_t^{\pi}(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

possibilistic belief update – a selected, o' received

joint distribution on $\mathcal{S} \times \mathcal{O}$ from b_t^{π} : $\pi(o', s' \mid b_t^{\pi}, a)$

A possibilistic belief state

finite belief space

$$\Pi_{\mathcal{L}}^{\mathcal{S}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_{\mathcal{L}}^{\mathcal{S}} \sim \# \mathcal{L}^{\# \mathcal{S}} < +\infty$$

→ i.e. **finite belief space**

$$b_t^{\pi}(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

possibilistic belief update – a selected, o' received

joint distribution on $\mathcal{S} \times \mathcal{O}$ from b_t^{π} : $\pi(o', s' \mid b_t^{\pi}, a)$

→ **next belief state:** $b_{t+1}^{\pi}(s') = \pi(o', s' \mid b_t^{\pi}, a)$

unless s' maximizes $\pi(o', s' \mid b_t^{\pi}, a)$, then $b_{t+1}^{\pi}(s') = 1$

denoted by $b_{t+1}^{\pi}(s') \propto^{\pi} \pi(o', s' \mid b_t^{\pi}, a)$

A possibilistic belief state

finite belief space

$$\Pi_{\mathcal{L}}^{\mathcal{S}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_{\mathcal{L}}^{\mathcal{S}} \sim \# \mathcal{L}^{\# \mathcal{S}} < +\infty$$

→ i.e. **finite belief space**

$$b_t^{\pi}(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

possibilistic belief update – a selected, o' received

joint distribution on $\mathcal{S} \times \mathcal{O}$ from b_t^{π} : $\pi(o', s' \mid b_t^{\pi}, a)$

→ **next belief state**: $b_{t+1}^{\pi}(s') = \pi(o', s' \mid b_t^{\pi}, a)$

unless s' maximizes $\pi(o', s' \mid b_t^{\pi}, a)$, then $b_{t+1}^{\pi}(s') = 1$

denoted by $b_{t+1}^{\pi}(s') \propto^{\pi} \pi(o', s' \mid b_t^{\pi}, a)$

■ the update **only depends on** o' , a and b_t^{π}

Qualitative Possibility Theory:

→ simplification, ignorance and imprecision modeling

Qualitative Possibility Theory:


→ simplification, ignorance and imprecision modeling

- 1 introduction
- 2 natural use of a qualitative possibilistic model
- 3 updates and first use of the π -POMDP model
- 4 simplify computation: ADDs and factorization
- 5 probabilistic-possibilistic (hybrid) approach
- 6 conclusion

- 1 Context
- 2 Introductory example (HMI)
- 3 Updates of the qualitative possibilistic model
- 4 Symbolic solver and factorization
- 5 An hybrid perspective
- 6 Conclusion/Perspectives


Example: Human-Machine Interaction

joint work with Sergio Pizziol – Context



Example: Human-Machine Interaction


joint work with Sergio Pizziol – Context



Issue: incorrect human assessment of the machine state
→ accident

Example: Human-Machine Interaction

joint work with Sergio Pizziol – Context



Issue: incorrect human assessment of the machine state
→ accident

π -POMDP without actions: π -Hidden Markov Process

- **system space** \mathcal{S} : set of human assessments → **hidden**
- **observation space** \mathcal{O} : feedbacks/human selections

Example: Human-Machine Interaction

Human error model from expert knowledge

Machine with states A, B, C, \dots

state $s_A \in \mathcal{S}$: "human thinks machine state is A "

Example: Human-Machine Interaction

Human error model from expert knowledge

Machine with states A, B, C, \dots

state $s_A \in \mathcal{S}$: "human thinks machine state is A "

Machine state $A \rightarrow B$

■ **machine feedback** observation $o_f \in \mathcal{O}$:

human usually aware of feedbacks $\rightarrow \pi(s'_B, o'_f \mid s_A) = 1$
but may lost a feedback $\rightarrow \pi(s'_A, o'_f \mid s_A) = \frac{2}{3}$

Example: Human-Machine Interaction

Human error model from expert knowledge

Machine with states A, B, C, \dots

state $s_A \in \mathcal{S}$: "human thinks machine state is A "

Machine state $A \rightarrow B$

■ **machine feedback** observation $o_f \in \mathcal{O}$:

human usually aware of feedbacks $\rightarrow \pi(s'_B, o'_f \mid s_A) = 1$
but may lost a feedback $\rightarrow \pi(s'_A, o'_f \mid s_A) = \frac{2}{3}$

■ **human selection** observation $o_s \in \mathcal{O}$:

selection o'_s normal under $s_A \rightarrow \pi(s'_B, o'_s \mid s_A) = 1$
anormal selection $= \frac{1}{3}$

Example: Human-Machine Interaction

Human error model from expert knowledge

Machine with states A, B, C, \dots

state $s_A \in \mathcal{S}$: "human thinks machine state is A "

Machine state $A \rightarrow B$

■ **machine feedback** observation $o_f \in \mathcal{O}$:

human usually aware of feedbacks $\rightarrow \pi(s'_B, o'_f | s_A) = 1$
but may lost a feedback $\rightarrow \pi(s'_A, o'_f | s_A) = \frac{2}{3}$

■ **human selection** observation $o_s \in \mathcal{O}$:

selection o'_s normal under $s_A \rightarrow \pi(s'_B, o'_s | s_A) = 1$
anormal selection $= \frac{1}{3}$


■ impossible cases: possibility degree 0

Qualitative Possibilistic Hidden Markov Process: diagnosis tool for Human-Machine interaction (with Sergio Pizziol)


feedbacks/selections

(observable) {

human {
assessments
(hidden)



Qualitative Possibilistic Hidden Markov Process: diagnosis tool for Human-Machine interaction (with Sergio Pizziol)




- **estimation** of the human assessment
 \Leftrightarrow **possibilistic belief state**
- **detection** of human assessment errors
- **diagnosis** using *leximin* operator
- results on flight simulator missions with pilots

- 1 Context
- 2 Introductory example (HMI)
- 3 Updates of the qualitative possibilistic model**
- 4 Symbolic solver and factorization
- 5 An hybrid perspective
- 6 Conclusion/Perspectives

Mixed-Observability (MOMDP) – Ong et al. (RSS-05)

π -Mixed-Observable Markov Decision Process (π -MOMDP)

contribution (UAI-13):




Mixed-Observability: system state $s \in \mathcal{S} = \mathcal{S}_v \times \mathcal{S}_h$
i.e. state s = visible component s_v & hidden component s_h

Mixed-Observability (MOMDP) – Ong et al. (RSS-05)

π -Mixed-Observable Markov Decision Process (π -MOMDP)

contribution (UAI-13):




Mixed-Observability: system state $s \in \mathcal{S} = \mathcal{S}_v \times \mathcal{S}_h$
i.e. state s = visible component s_v & hidden component s_h

- belief states only over \mathcal{S}_h (component s_v observed)

Mixed-Observability (MOMDP) – Ong et al. (RSS-05)

π -Mixed-Observable Markov Decision Process (π -MOMDP)

contribution (UAI-13):



Mixed-Observability: system state $s \in \mathcal{S} = \mathcal{S}_v \times \mathcal{S}_h$
i.e. state s = visible component s_v & hidden component s_h

- belief states only over \mathcal{S}_h (component s_v observed)
- $\rightarrow \pi$ -POMDP: belief space $\Pi_{\mathcal{L}}^{\mathcal{S}}$ $\#\Pi_{\mathcal{L}}^{\mathcal{S}} \sim \#\mathcal{L}^{\#\mathcal{S}}$
- $\rightarrow \pi$ -MOMDP: computations on $\mathcal{X} = \mathcal{S}_v \times \Pi_{\mathcal{L}}^{\mathcal{S}_h}$
 $\#\mathcal{X} \sim \#\mathcal{S}_v \cdot \#\mathcal{L}^{\#\mathcal{S}_h} \ll \#\Pi_{\mathcal{L}}^{\mathcal{S}}$

contribution (UAI-13): Undefined Horizon

contribution (UAI-13): Undefined Horizon

Dynamic Programming scheme: $\# \text{ iterations} < \#\mathcal{X}$

- assumption: \exists artificial “stay” action
as in classical planning/ γ counterpart
- value function = criterion: non decreasing with horizon

contribution (UAI-13): Undefined Horizon

Dynamic Programming scheme: $\# \text{ iterations} < \#\mathcal{X}$



- assumption: \exists artificial “stay” action
as in classical planning/ γ counterpart
- value function = criterion: non decreasing with horizon
- action update for states increasing the value function
- proof of optimality

Use of the π -MOMDP in practice

simulations

- **goal:** reach the object $A = T1$ or $T2$
- noisy observations of the location of the object A

Recognition mission: robot on a grid, targets $T1$ & $T2$



in reality, misperception probability in the error zone: $P_{bad} > \frac{1}{2}$


- 1 Context
- 2 Introductory example (HMI)
- 3 Updates of the qualitative possibilistic model
- 4 Symbolic solver and factorization
- 5 An hybrid perspective
- 6 Conclusion/Perspectives

Factored π -MOMDP and computations with ADDs

qualitative possibilistic models to reduce complexity

contribution (AAAI-14): factored π -MOMDP

\Leftrightarrow state space $\mathcal{X} = \mathcal{S}_v \times \Pi_{\mathcal{L}}^{\mathcal{S}_h}$ = Boolean variables (X_1, \dots, X_n)
+ independence assumptions \Leftarrow graphical model




Factored π -MOMDP and computations with ADDs

qualitative possibilistic models to reduce complexity

contribution (AAAI-14): factored π -MOMDP


\Leftrightarrow state space $\mathcal{X} = \mathcal{S}_v \times \Pi_{\mathcal{L}}^{\mathcal{S}_h} =$ Boolean variables (X_1, \dots, X_n)
+ independence assumptions \Leftarrow graphical model



■ **factorization:** transition functions
 $T_i^a = \pi(X'_i \mid \text{parents}(X'_i), a)$ stored as
Algebraic Decision Diagrams (ADD)

probabilistic case:

SPUDD, *Hoey et al., UAI-99*



Simplify computations with π -MOMDPs

Resulting π -MOMDP solver: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created
 \Rightarrow number of ADDs leaves **potentially huge**
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite
 \Rightarrow number of leaves bounded, **ADDs smaller.**

Simplify computations with π -MOMDPs

Resulting π -MOMDP solver: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created
 \Rightarrow number of ADDs leaves **potentially huge**
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite
 \Rightarrow number of leaves bounded, **ADDs smaller**.

PPUDD: Possibilistic Planning Using Decision Diagrams

- factorization \Rightarrow DP steps divided into n stages
 \rightarrow used ADDs smaller \Rightarrow **faster computations**

Simplify computations with π -MOMDPs

Resulting π -MOMDP solver: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created
 \Rightarrow number of ADDs leaves **potentially huge**
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite
 \Rightarrow number of leaves bounded, **ADDs smaller**.

PPUDD: Possibilistic Planning Using Decision Diagrams


- factorization \Rightarrow DP steps divided into n stages
 \rightarrow used ADDs smaller \Rightarrow **faster computations**
- computations on trees: *CU Decision Diagram Package*.

Simplify computations with π -MOMDPs

Natural factorization: belief independence

contribution (AAAI-14):

independent sensors, hidden states, ... \Rightarrow graphical model



Simplify computations with π -MOMDPs


Natural factorization: belief independence

contribution (AAAI-14):

independent sensors, hidden states, ... \Rightarrow graphical model

d-Separation $\Rightarrow (s_v, \beta) = (s_{v,1}, \dots, s_{v,m}, \beta_1, \dots, \beta_l)$

$\beta_i \in \Pi_{\mathcal{L}}^{s_{h,i}}$, belief over $s_{h,i}$



Simplify computations with π -MOMDPs

Experiments – perfect sensing: Navigation problem

PPUDD vs SPUDD *Hoey et al.*

Navigation benchmark: reach a goal – spots with accident risk
M1 (resp. M2) optimistic (resp. cautious) criterion

Simplify computations with π -MOMDPs


Experiments – perfect sensing: Navigation problem

PPUDD vs SPUDD *Hoey et al.*


Navigation benchmark: reach a goal – spots with accident risk
M1 (resp. M2) optimistic (resp. cautious) criterion

Performances, function of the instance size

reached goal frequency




steps to reach the goal




Simplify computations with π -MOMDPs

Experiments – perfect sensing: Navigation problem

computation time



max size of ADDs



- PPUDD + M2 (pessimistic criterion)
faster with same performances as SPUDD
- SPUDD only solves the first 5 instances
- verified intuition: ADDs are smaller

Simplify computations with π -MOMDPs

Experiments – imperfect sensing: RockSample problem

PPUDD vs APPL *Kurniawati et al.*, solver MOMDP

symbolic HSVI *Sim et al.*, solver POMDP

RockSample benchmark: recognize and sample “good” rocks

Simplify computations with π -MOMDPs

Experiments – imperfect sensing: RockSample problem


PPUDD vs APPL *Kurniawati et al.*, solver MOMDP

symbolic HSVI *Sim et al.*, solver POMDP

RockSample benchmark: recognize and sample “good” rocks


computation time:

probabilistic solvers, prec. 1
PPUDD, exact resolution



average of rewards

APPL stopped when
PPUDD end



- **approximate model + exact resolution solver**
→ improvement of computation time and performances

IPPC 2014 – ADD-based approaches: PPUDD vs symbolic LRTDP

PPUDD + BDD mask over reachable states.




Figure : average of rewards over simulations

- 1 Context
- 2 Introductory example (HMI)
- 3 Updates of the qualitative possibilistic model
- 4 Symbolic solver and factorization
- 5 An hybrid perspective**
- 6 Conclusion/Perspectives

Qualitative possibilistic approach: benefits/drawbacks towards a hybrid POMDP

Qualitative Possibilistic models:

- **granulated** belief space (discrete)
- efficient problem **simplification** (PPUDD 2× better than LRTDP with ADDs)
- **ignorance and imprecision** modeling

Qualitative possibilistic approach: benefits/drawbacks towards a hybrid POMDP

Qualitative Possibilistic models:

- **granulated** belief space (discrete)
 - efficient problem **simplification** (PPUDD $2\times$ better than LRTDP with ADDs)
 - **ignorance and imprecision** modeling
-
- ADD methods \prec state space search methods: winners of IPPC 2014, $2\times$ better than PPUDD
 - choice of the qualitative criterion (optimistic/pessimistic)
 - non additive utility degrees
same scale as possibility degrees (commensurability)
 - frequentist information lost

A hybrid model

a probabilistic POMDP with possibilistic belief states

hybrid approach

- agent knowledge = possibilistic belief states
- probabilistic dynamics & quantitative rewards

A hybrid model

a probabilistic POMDP with possibilistic belief states

hybrid approach

- agent knowledge = possibilistic belief states
- probabilistic dynamics & quantitative rewards

→ **heuristic** for solving POMDPs:

results in a standard (finite state space) MDP

→ problem with **qualitative** & **quantitative** uncertainty

Transitions and rewards

belief-based transition and reward functions

- possibility distribution $\beta \rightarrow$ probability distribution $\bar{\beta}$
using poss-prob transformations (Dubois et al., FSS-92)

$$\Rightarrow \mathbf{p}(\beta' | \beta, a) = \sum_{\substack{o' \text{ t.q.} \\ \text{update}(\beta, a, o') = \beta'}} \mathbf{p}(o' | \beta, a)$$

Transitions and rewards

belief-based transition and reward functions

- possibility distribution $\beta \rightarrow$ probability distribution $\bar{\beta}$ using poss-prob transformations (Dubois et al., FSS-92)

$$\Rightarrow \mathbf{p}(\beta' | \beta, a) = \sum_{\substack{o' \text{ t.q.} \\ \text{update}(\beta, a, o') = \beta'}} \mathbf{p}(o' | \beta, a)$$

- reward cautious according to β

Pessimistic Choquet Integral

$$r(\beta, a) = \sum_{i=1}^{\#\mathcal{L}-1} (l_i - l_{i+1}) \cdot \min_{\substack{s \in \mathcal{S} \text{ s.t.} \\ \beta(s) \geq l_i}} r(s, a)$$

Resulting MDP

translation summary **contribution** (SUM-15):

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

Resulting MDP

translation summary **contribution** (SUM-15):

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{L}}^{\mathcal{S}}$,
the set of the possibility distributions over \mathcal{S} ;

Resulting MDP

translation summary **contribution** (SUM-15):

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{L}}^{\mathcal{S}}$,
the set of the possibility distributions over \mathcal{S} ;
- $\forall \beta, \beta'$ possibilistic belief states $\in \Pi_{\mathcal{L}}^{\mathcal{S}}, \forall a \in \mathcal{A}$,
transitions $\tilde{T}(\beta, a, \beta') = \mathbf{p}(\beta' | \beta, a)$;

Resulting MDP

translation summary **contribution** (SUM-15):

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{L}}^{\mathcal{S}}$,
the set of the possibility distributions over \mathcal{S} ;
- $\forall \beta, \beta'$ possibilistic belief states $\in \Pi_{\mathcal{L}}^{\mathcal{S}}, \forall a \in \mathcal{A}$,
transitions $\tilde{T}(\beta, a, \beta') = \mathbf{p}(\beta' | \beta, a)$;
- **reward** $\tilde{r}(a, \beta) = \underline{Ch}(r(a, .))$,

Resulting MDP

translation summary **contribution** (SUM-15):

input: a POMDP $\langle \mathcal{S}, \mathcal{A}, \mathcal{O}, T, O, r, \gamma \rangle$;

output: the MDP $\langle \tilde{\mathcal{S}}, \mathcal{A}, \tilde{T}, \tilde{r}, \gamma \rangle$:

- **state space** $\tilde{\mathcal{S}} = \Pi_{\mathcal{L}}^{\mathcal{S}}$,
the set of the possibility distributions over \mathcal{S} ;
- $\forall \beta, \beta'$ possibilistic belief states $\in \Pi_{\mathcal{L}}^{\mathcal{S}}$, $\forall a \in \mathcal{A}$,
transitions $\tilde{T}(\beta, a, \beta') = \mathbf{p}(\beta' | \beta, a)$;
- **reward** $\tilde{r}(a, \beta) = \underline{Ch}(r(a, .))$,

$$\text{criterion: } \mathbb{E}_{\beta_t \sim \tilde{T}} \left[\sum_{t=0}^{+\infty} \gamma^t \cdot \tilde{r}(\beta_t, d_t) \right].$$

General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: visible $s'_v \in \mathbb{S}_v$

s'_v

inferred hidden $s'_h \in \mathbb{S}_h$

s'_h


fully hidden $s'_f \in \mathbb{S}_f$

s'_f

General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: visible $s'_v \in \mathbb{S}_v$



inferred hidden $s'_h \in \mathbb{S}_h$




fully hidden $s'_f \in \mathbb{S}_f$



General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: visible $s'_v \in \mathbb{S}_v$



$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$

inferred hidden $s'_h \in \mathbb{S}_h$



fully hidden $s'_f \in \mathbb{S}_f$




General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable

$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$



fully hidden $s'_f \in \mathbb{S}_f$




General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization


variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable

$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$



fully hidden $s'_f \in \mathbb{S}_f$




General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$


\Leftrightarrow deterministic belief variable

$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$\beta_{t+1}(\text{parents}(o'_i)) = \beta_{t+1}(s_h, s_h^a, s_h^b, s_h^c)$$



fully hidden $s'_f \in \mathbb{S}_f$




General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable


$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$\beta_{t+1}(\text{parents}(o'_i)) = \beta_{t+1}(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \text{parents}(o'_i) | \beta_t, a)$$



fully hidden $s'_f \in \mathbb{S}_f$




General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable


$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$\beta_{t+1}(\text{parents}(o'_i)) = \beta_{t+1}(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \text{parents}(o'_i) | \beta_t, a)$$



⚠ $\mathcal{P}(o'_i)$ may contain visible variables.

fully hidden $s'_f \in \mathbb{S}_f$




General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable


$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$\beta_{t+1}(\text{parents}(o'_i)) = \beta_{t+1}(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \text{parents}(o'_i) | \beta_t, a)$$



⚠ $\mathcal{P}(o'_i)$ may contain visible variables.

fully hidden $s'_f \in \mathbb{S}_f$




General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable

$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$




inferred hidden $s'_h \in \mathbb{S}_h$

$$\beta_{t+1}(\text{parents}(o'_i)) = \beta_{t+1}(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \text{parents}(o'_i) | \beta_t, a)$$

! $\mathcal{P}(o'_i)$ may contain visible variables.



fully hidden $s'_f \in \mathbb{S}_f$



$$\beta_{t+1}(s'_f) = \pi(s'_f | \beta_t, a)$$


General variable classification contribution (SUM-15):

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable


$$\beta_{t+1}(s'_v) = \mathbb{1}_{\{s'_v=o'_v\}}(s'_v)$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$\beta_{t+1}(\text{parents}(o'_i)) = \beta_{t+1}(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \text{parents}(o'_i) | \beta_t, a)$$



⚠ $\mathcal{P}(o'_i)$ may contain visible variables.

fully hidden $s'_f \in \mathbb{S}_f$

\rightarrow observations don't
inform belief state on s'_f .



$$\beta_{t+1}(s'_f) = \pi(s'_f | \beta_t, a)$$

Possibilistic belief variables

global belief state

bound over the global belief state

$$\beta_{t+1}(s'_1, \dots, s'_n) = \pi(s'_1, \dots, s'_n \mid a_0, o_1, \dots, a_t, o_{t+1})$$

$$\leq \min \left\{ \min_{s'_j \in \mathbb{S}_v} \left[\mathbb{1}_{\{s'_j = o'_j\}} \right], \min_{s'_j \in \mathbb{S}_f} \left[\beta_{t+1}(s'_j) \right], \min_{o'_i \in \mathbb{O}_h} \left[\beta_{t+1}(\text{parents}(o'_i)) \right] \right\}$$

Possibilistic belief variables

global belief state

bound over the global belief state

$$\beta_{t+1}(s'_1, \dots, s'_n) = \pi(s'_1, \dots, s'_n \mid a_0, o_1, \dots, a_t, o_{t+1})$$

$$\leq \min \left\{ \min_{s'_j \in \mathbb{S}_v} \left[\mathbb{1}_{\{s'_j = o'_j\}} \right], \min_{s'_j \in \mathbb{S}_f} \left[\beta_{t+1}(s'_j) \right], \min_{o'_i \in \mathbb{O}_h} \left[\beta_{t+1}(\text{parents}(o'_i)) \right] \right\}$$

- min of marginals = **less informative** belief state
- computed using **marginal belief states**
 - **factorization & smaller state space**

- 1 Context
- 2 Introductory example (HMI)
- 3 Updates of the qualitative possibilistic model
- 4 Symbolic solver and factorization
- 5 An hybrid perspective
- 6 Conclusion/Perspectives

- updates: → mixed-observability modeling
→ undefined horizon
- modeling: → human-machine interaction
→ robust recognition mission with possibilistic beliefs
- computations: factorization work & PPUDD algorithm
(competitive solver, IPPC 2014)

- updates: → mixed-observability modeling
→ undefined horizon
- modeling: → human-machine interaction
→ robust recognition mission with possibilistic beliefs
- computations: factorization work & PPUDD algorithm
(competitive solver, IPPC 2014)

new refined criteria → finer π -POMDP

- updates: → mixed-observability modeling
→ undefined horizon
- modeling: → human-machine interaction
→ robust recognition mission with possibilistic beliefs
- computations: factorization work & PPUDD algorithm
(competitive solver, IPPC 2014)

new refined criteria → finer π -POMDP

quantitative information may be available: hybrid work

POMDP $\xrightarrow{\text{translation}}$ MDP with finite state space

- transition probabilities on the **possibilistic belief states**;

POMDP $\xrightarrow{\text{translation}}$ MDP with finite state space

- transition probabilities on the **possibilistic belief states**;
- **pessimistic** evaluation of the **rewards**
(Choquet integral);

POMDP $\xrightarrow{\text{translation}}$ MDP with finite state space

- transition probabilities on the **possibilistic belief states**;
- **pessimistic** evaluation of the **rewards**
(Choquet integral);
- factored POMDP $\xrightarrow{\text{translation}}$ **factored MPD**.

POMDP $\xrightarrow{\text{translation}}$ MDP with finite state space

- transition probabilities on the **possibilistic belief states**;
- **pessimistic** evaluation of the **rewards** (Choquet integral);
- factored POMDP $\xrightarrow{\text{translation}}$ **factored MPD**.

perspectives:

- IPPC problems (factored POMDPs);

POMDP $\xrightarrow{\text{translation}}$ MDP with finite state space

- transition probabilities on the **possibilistic belief states**;
- **pessimistic** evaluation of the **rewards** (Choquet integral);
- factored POMDP $\xrightarrow{\text{translation}}$ **factored MPD**.


perspectives:

- IPPC problems (factored POMDPs);
- tests of this approach:
 - 1 **simplification**: π distributions definition?
 - 2 **imprecision**: robust in practice?

Thank you!

Uncertainty theories

Most known uncertainty theories and their relations




- IPT: most general uncertainty theory.
Use of sets of probability measures over Ω .
- BFT: use of a mass function $m : 2^\Omega \rightarrow [0, 1]$,
with $\sum_{A \subset \Omega} m(A) = 1$.
 - 1 plausibility measure: $\forall A \subset \Omega, Pl(A) = \sum_{B \cap A \neq \emptyset} m(B)$.
 - 2 belief function: $\forall A \subset \Omega, bel(A) = \sum_{B \subseteq A} m(B)$.

Focal sets of a mass function $m : 2^\Omega \rightarrow [0, 1]$:
subsets A of $\Omega = \{\omega_1, \dots, \omega_7\}$ such that $m(A) > 0$.

- if focal sets are all singletons
→ probability distribution ($bel = Pl = \mathbb{P}$)
- if focal sets are nested, e.g. $F_3 \subset F_2 \subset F_1 = \Omega$,
→ possibility distribution:
 bel =necessity measure, Pl =possibility measure.


probabilistic case

example of focal set
i.e. singleton



possibilistic case

focal sets:



Probabilistic belief update




Figure : Bayesian Network illustrating the belief update

- the **system states** are the gray circular nodes,
- the **action** is the red square node ,
- and the **observation** is the blue circular node.

The belief state b_t (resp. b_{t+1}) is the probabilistic estimation of the current (resp. next) system state s_t (resp. s_{t+1})

probabilistic belief update

$$b_{t+1}(s') \propto p(o' | s', a) \cdot \sum_{s \in \mathcal{S}} p(s' | s, a) \cdot b_t(s)$$

Rewritings of parameters

PROBABILISTIC parameters

- $T_j^a(\mathbb{S}, s'_j) = T_j^a(\mathcal{P}(s'_j), s'_j);$
- $O_i^a(\mathbb{S}', o'_i) = O_i^a(\mathcal{P}(o'_i), o'_i).$

Rewritings of parameters

PROBABILISTIC parameters

- $T_j^a(\mathbb{S}, s'_j) = T_j^a(\mathcal{P}(s'_j), s'_j);$
- $O_i^a(\mathbb{S}', o'_i) = O_i^a(\mathcal{P}(o'_i), o'_i).$

consequences on the joint distribution

$$\begin{aligned}\mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathbb{S}, a) &= O_i^a(\mathcal{P}(o'_i), o'_i) \cdot \prod_{s'_j \in \mathcal{P}(o'_i)} T_j^a(\mathcal{P}(s'_j), s'_j) \\ &= \mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a).\end{aligned}$$

Rewritings of parameters

PROBABILISTIC parameters

- $T_j^a(\mathbb{S}, s'_j) = T_j^a(\mathcal{P}(s'_j), s'_j);$
- $O_i^a(\mathbb{S}', o'_i) = O_i^a(\mathcal{P}(o'_i), o'_i).$

consequences on the joint distribution

$$\begin{aligned}\mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathbb{S}, a) &= O_i^a(\mathcal{P}(o'_i), o'_i) \cdot \prod_{s'_j \in \mathcal{P}(o'_i)} T_j^a(\mathcal{P}(s'_j), s'_j) \\ &= \mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a).\end{aligned}$$

observation probabilities

epistemic state

$$b^\pi(\mathbb{S}) \xrightarrow{\text{marginalization}} b^\pi(\mathcal{Q}(o'_i)) \xrightarrow{\text{pignistic transformation}} \overline{b^\pi}(\mathcal{Q}(o'_i))$$

$$\mathbf{p}(o'_i \mid b^\pi, a) = \sum_{2^{\mathcal{P}(o'_i)}, 2^{\mathcal{Q}(o'_i)}} \mathbf{p}(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a) \cdot \overline{b^\pi}(\mathcal{Q}(o'_i))$$

Parameters rewritings

POSSIBILISTIC parameters

- $\pi(s'_j \mid \mathbb{S}, a) = \pi(s'_j \mid \mathcal{P}(s'_j), a);$
- $\pi(o'_i \mid \mathbb{S}', a) = \pi(o'_i \mid \mathcal{P}(o'_i), a).$

- $\pi(s'_j \mid \mathbb{S}, a) = \pi(s'_j \mid \mathcal{P}(s'_j), a);$
- $\pi(o'_i \mid \mathbb{S}', a) = \pi(o'_i \mid \mathcal{P}(o'_i), a).$

marginal possibilistic belief states

$\forall o'_i \in \mathbb{O},$

$$b_{t+1}^{\pi}(\mathcal{P}(o'_i)) \propto^{\pi} \pi(o'_i, \mathcal{P}(o'_i) \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

- $\pi(s'_j \mid \mathbb{S}, a) = \pi(s'_j \mid \mathcal{P}(s'_j), a);$
- $\pi(o'_i \mid \mathbb{S}', a) = \pi(o'_i \mid \mathcal{P}(o'_i), a).$

marginal possibilistic belief states

$$\begin{aligned} \forall o'_i \in \mathbb{O}, \\ b_{t+1}^\pi(\mathcal{P}(o'_i)) &\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid a_0, o_1, \dots, a_{t-1}, o_t) \\ &= \max_{2^{\mathcal{Q}(o'_i)}} \min \left\{ \pi(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a), b_t^\pi(\mathcal{Q}(o'_i)) \right\} \end{aligned}$$

- $\pi(s'_j \mid \mathbb{S}, a) = \pi(s'_j \mid \mathcal{P}(s'_j), a);$
- $\pi(o'_i \mid \mathbb{S}', a) = \pi(o'_i \mid \mathcal{P}(o'_i), a).$

marginal possibilistic belief states

$$\begin{aligned} \forall o'_i \in \mathbb{O}, \\ b_{t+1}^\pi(\mathcal{P}(o'_i)) &\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid a_0, o_1, \dots, a_{t-1}, o_t) \\ &= \max_{2^{\mathcal{Q}(o'_i)}} \min \left\{ \pi(o'_i, \mathcal{P}(o'_i) \mid \mathcal{Q}(o'_i), a), b_t^\pi(\mathcal{Q}(o'_i)) \right\} \\ &\text{denoted by } \pi(o'_i, \mathcal{P}(o'_i) \mid b_t^\pi, a). \end{aligned}$$

A possibilistic belief state

finite belief space

$$\Pi_S^{\mathcal{L}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_S^{\mathcal{L}} < +\infty$$

→ **finite belief space**

A possibilistic belief state

finite belief space

$$\Pi_{\mathcal{S}}^{\mathcal{L}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_{\mathcal{S}}^{\mathcal{L}} < +\infty$$

→ **finite belief space**

$$b_t^{\pi}(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

A possibilistic belief state

finite belief space

$$\Pi_S^{\mathcal{L}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_S^{\mathcal{L}} < +\infty$$

→ **finite belief space**

$$b_t^{\pi}(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

update – **possibilistic** belief state

$$b_{t+1}^{\pi}(s') = \begin{cases} 1 & \text{if } \pi(o', s' \mid b_t^{\pi}, a) = \pi(o' \mid b_t^{\pi}, a) \\ \pi(o', s' \mid b_t^{\pi}, a) & \text{otherwise.} \end{cases}$$

denoted by $b_{t+1}^{\pi}(s') \propto^{\pi} \pi(o', s' \mid b_t^{\pi}, a)$

A possibilistic belief state

finite belief space

$$\Pi_S^{\mathcal{L}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_S^{\mathcal{L}} < +\infty$$

→ **finite belief space**

$$b_t^{\pi}(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

update – **possibilistic** belief state

$$b_{t+1}^{\pi}(s') = \begin{cases} 1 & \text{if } \pi(o', s' \mid b_t^{\pi}, a) = \pi(o' \mid b_t^{\pi}, a) \\ \pi(o', s' \mid b_t^{\pi}, a) & \text{otherwise.} \end{cases}$$

denoted by $b_{t+1}^{\pi}(s') \propto^{\pi} \pi(o', s' \mid b_t^{\pi}, a)$

- $\pi(o', s' \mid b_t^{\pi}, a) = \max_{s \in \mathcal{S}} \min \left\{ \pi(o' \mid s', a), \pi(s' \mid s, a), b_t^{\pi}(s) \right\};$
- $\pi(o' \mid s', a) = \max_{s' \in \mathcal{S}} \pi(o', s' \mid b_t^{\pi}, a).$

A possibilistic belief state

finite belief space

$$\Pi_S^{\mathcal{L}} = \left\{ \text{possibility distributions} \right\}: \# \Pi_S^{\mathcal{L}} < +\infty$$

→ **finite belief space**

$$b_t^{\pi}(s) = \pi(s_t = s \mid a_0, o_1, \dots, a_{t-1}, o_t)$$

update – **possibilistic** belief state

$$b_{t+1}^{\pi}(s') = \begin{cases} 1 & \text{if } \pi(o', s' \mid b_t^{\pi}, a) = \pi(o' \mid b_t^{\pi}, a) \\ \pi(o', s' \mid b_t^{\pi}, a) & \text{otherwise.} \end{cases}$$

denoted by $b_{t+1}^{\pi}(s') \propto^{\pi} \pi(o', s' \mid b_t^{\pi}, a)$

- the update **only depends on o' and a .**

Dynamic Programming scheme: $\# \text{ iterations} < \#\mathcal{X}$.

$\forall x \in \mathcal{X}, V_0(x) = \rho(x)$ **preference**,

Dynamic Programming scheme: $\# \text{ iterations} < \# \mathcal{X}$.

$\forall x \in \mathcal{X}, V_0(x) = \rho(x)$ **preference**, and, until convergence,

- $V_{i+1}(x) = \max_{a \in \mathcal{A}} \max_{x' \in \mathcal{X}} \min \{ \pi(x' | x, a), V_i(x') \},$

Dynamic Programming scheme: $\# \text{ iterations} < \# \mathcal{X}$.

$\forall x \in \mathcal{X}$, $V_0(x) = \rho(x)$ **preference**, and, until convergence,

• $V_{i+1}(x) = \max_{a \in \mathcal{A}} \max_{x' \in \mathcal{X}} \min \{ \pi(x' \mid x, a), V_i(x') \}$, and

if $V_{i+1}(x) > V_i(x)$, $\delta(x) = \arg \max_{a \in \mathcal{A}} \max_{x' \in \mathcal{X}} \min \{ \pi(x' \mid x, a), V_i(x') \}$.

Resulting π -MOMDP solver: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created, number of ADDs leaves **potentially huge**.
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite, number of leaves bounded, **ADDs smaller**.

Resulting π -MOMDP solver: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created, number of ADDs leaves **potentially huge**.
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite, number of leaves bounded, **ADDs smaller**.

PPUDD: Possibilistic Planning Using Decision Diagrams

```
1  $V^* \leftarrow 0$  ;  $V^c \leftarrow \mu$  ;  $\delta \leftarrow \bar{a}$  ;  
2 while  $V^* \neq V^c$  do  
3    $V^* \leftarrow V^c$  ;  
4   for  $a \in \mathcal{A}$  do  
5      $q^a \leftarrow$  swap each  $X_i$  variable in  $V^*$  with  $X'_i$  ;  
6     for  $1 \leq i \leq n$  do  
7        $q^a \leftarrow \min \{ q^a, \pi(X'_i \mid \text{parents}(X'_i), a) \}$  ;  
8        $q^a \leftarrow \max_{X'_i} q^a$  ;  
9      $V^c \leftarrow \max \{ q^a, V^c \}$  ;  
10    update  $\delta$  to  $a$  where  $q^a = V^c$  and  $V^c > V^*$  ;  
11 return  $(V^*, \delta)$  ;
```

computations on trees: *CU Decision Diagram Package*.

Resulting π -MOMDP solver: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created, number of ADDs leaves **potentially huge**.
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite, number of leaves bounded, **ADDs smaller**.

PPUDD: Possibilistic Planning Using Decision Diagrams

```
1  $V^* \leftarrow 0$  ;  $V^c \leftarrow \mu$  ;  $\delta \leftarrow \bar{a}$  ;  
2 while  $V^* \neq V^c$  do  
3    $V^* \leftarrow V^c$  ;  
4   for  $a \in \mathcal{A}$  do  
5      $q^a \leftarrow$  swap each  $X_i$  variable in  $V^*$  with  $X'_i$  ;  
6     for  $1 \leq i \leq n$  do  
7        $q^a \leftarrow \min \{ q^a, \pi(X'_i \mid \text{parents}(X'_i), a) \}$  ;  
8        $q^a \leftarrow \max_{X'_i} q^a$  ;  
9      $V^c \leftarrow \max \{ q^a, V^c \}$  ;  
10    update  $\delta$  to  $a$  where  $q^a = V^c$  and  $V^c > V^*$  ;  
11 return  $(V^*, \delta)$  ;
```

factorization

\Rightarrow dynamic programming

computations on trees: *CU Decision Diagram Package*.

Resulting π -MOMDP solver: PPUDD

- probabilistic model: $+$ and $\times \Rightarrow$ new values created, number of ADDs leaves **potentially huge**.
- possibilistic model: \min and $\max \Rightarrow$ values $\in \mathcal{L}$ finite, number of leaves bounded, **ADDs smaller**.

PPUDD: Possibilistic Planning Using Decision Diagrams

```
1  $V^* \leftarrow 0$  ;  $V^c \leftarrow \mu$  ;  $\delta \leftarrow \bar{a}$  ;  
2 while  $V^* \neq V^c$  do ← factorization  
3    $V^* \leftarrow V^c$  ;  
4   for  $a \in \mathcal{A}$  do ⇒ dynamic programming  
5      $q^a \leftarrow$  swap each  $X_i$  variable in  $V^*$  with  $X'_i$  ;  
6     for  $1 \leq i \leq n$  do ← divided into  $n$  stages  
7        $q^a \leftarrow \boxed{\min} \{ q^a, \pi(X'_i \mid \text{parents}(X'_i), a) \}$  ;  
8        $q^a \leftarrow \boxed{\max}_{X'_i} q^a$  ;  
9        $V^c \leftarrow \boxed{\max} \{ q^a, V^c \}$  ;  
10      update  $\delta$  to  $a$  where  $q^a = V^c$  and  $V^c > V^*$  ; → used ADDs smaller  
11 return  $(V^*, \delta)$  ; → faster computations.
```

computations on trees: *CU Decision Diagram Package*.

Pignistic transformation and transitions

Pignistic transformation

numbering of the $n = \#\mathcal{S}$ system states:

$$1 = b^\pi(s_1) \geq \dots \geq b^\pi(s_n) \geq b^\pi(s_{n+1}) = 0.$$





pignistic transformation – $P : \Pi_{\mathcal{S}} \rightarrow \mathbb{P}_{\mathcal{S}}$

$$\overline{b^\pi}(s_i) = \sum_{j=i}^{\#\mathcal{S}} \frac{b^\pi(s_j) - b^\pi(s_{j+1})}{j}.$$

- probability distribution $\overline{b^\pi} =$ **gravity center** of the represented probabilistic distributions;
- **Laplace principle**: ignorance \rightarrow uniform probability.

Pignistic transformation

Examples of pignistic transformations (red) of possibility distributions (blue)



hybrid POMDP and π -POMDP

differences with possibilistic models

	hybrid POMDP	π -POMDP
transitions	probabilities	qualitative possibility
rewards	quantitative $\in \mathbb{R}$	qualitative $\in \mathcal{L}$
situation	-some imprecisions -large POMDP	few quantitative
issues	π definition	commensurability
in practice	MDP	π -MDP

hybrid POMDP and π -POMDP

differences with possibilistic models

	hybrid POMDP	π -POMDP
transitions	probabilities	qualitative possibility
rewards	quantitative $\in \mathbb{R}$	qualitative $\in \mathcal{L}$
situation	-some imprecisions -large POMDP	few quantitative
issues	π definition	commensurability
in practice	MDP	π -MDP

hybrid model:

- only belief states are possibilistic:
 - agent knowledge = **possibility** distribution;
- probabilistic dynamics:
 - **approximated** (prob.) transition between epistemic states.

factorized POMDP

definition

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;

factorized POMDP

definition

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;
- **transition** function of s'_j ,
 $T_j^a(\mathbb{S}, s'_j) = \mathbf{p}(s'_j \mid \mathbb{S}, a), \forall j \in \{1, \dots, m\}$ et $\forall a \in \mathcal{A}$;

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;
- **transition** function of s'_j ,
 $T_j^a(\mathbb{S}, s'_j) = \mathbf{p}(s'_j \mid \mathbb{S}, a), \forall j \in \{1, \dots, m\}$ et $\forall a \in \mathcal{A}$;
- \mathcal{O} described by $\mathbb{O} = \{o_1, \dots, o_n\}$: $\mathcal{O} = o_1 \times \dots \times o_n$;

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;
- **transition** function of s'_j ,
 $T_j^a(\mathbb{S}, s'_j) = \mathbf{p}(s'_j \mid \mathbb{S}, a)$, $\forall j \in \{1, \dots, m\}$ et $\forall a \in \mathcal{A}$;
- \mathcal{O} described by $\mathbb{O} = \{o_1, \dots, o_n\}$: $\mathcal{O} = o_1 \times \dots \times o_n$;
- **observation** function of o'_i ,
 $O_i^a(\mathbb{S}', o'_i) = \mathbf{p}(o'_i \mid \mathbb{S}', a)$, $\forall i \in \{1, \dots, n\}$ et $\forall a \in \mathcal{A}$.

factorized POMDP

definition

- \mathcal{S} described by $\mathbb{S} = \{s_1, \dots, s_m\}$: $\mathcal{S} = s_1 \times \dots \times s_m$.
Notation: $\mathbb{S}' = \{s'_1, \dots, s'_m\}$;
- **transition** function of s'_j ,
 $T_j^a(\mathbb{S}, s'_j) = \mathbf{p}(s'_j \mid \mathbb{S}, a)$, $\forall j \in \{1, \dots, m\}$ et $\forall a \in \mathcal{A}$;
- \mathcal{O} described by $\mathbb{O} = \{o_1, \dots, o_n\}$: $\mathcal{O} = o_1 \times \dots \times o_n$;
- **observation** function of o'_i ,
 $O_i^a(\mathbb{S}', o'_i) = \mathbf{p}(o'_i \mid \mathbb{S}', a)$, $\forall i \in \{1, \dots, n\}$ et $\forall a \in \mathcal{A}$.

independences:

- $\rightarrow \forall s'_i, s'_j \in \mathbb{S}', \quad s'_i \perp\!\!\!\perp s'_j \mid \{\mathbb{S}, a \in \mathcal{A}\},$
- $\rightarrow \forall o'_i, o'_j \in \mathbb{O}', \quad o'_i \perp\!\!\!\perp o'_j \mid \{\mathbb{S}', a \in \mathcal{A}\}.$

Notations

some variables does not interact with each other

variables about the **current** system state,

s_1

\vdots

s_{j_1}

\vdots

s_{j_2}

\vdots

\vdots

\vdots

s_{j_k}

\vdots

s_m

variable s'_j about
the **next** state.

s'_j

Notations

some variables does not interact with each other


variables about the **current** system state,

$$s_k \rightarrow s'_j$$



$\exists a \in \mathcal{A}$, such that

$T_j^a(\mathbb{S}, s'_j)$ depends on s_k .




Notations

some variables does not interact with each other

variables about the **current** system state,


$s_k \rightarrow s'_j$
 \Updownarrow
 $\exists a \in \mathcal{A}$, such that
 $T_j^a(\mathbb{S}, s'_j)$ depends on s_k .



Notations

concerning observation variables

next state



Notations

concerning observation variables

$$s'_j \rightarrow o'_i$$




$\exists a \in \mathcal{A}$, such that

$$O_i^a(S', o'_i)$$

depends on s'_j .

next state



Notations

concerning observation variables


$$s'_j \rightarrow o'_i$$



$\exists a \in \mathcal{A}$, such that

$$O_i^a(\mathbb{S}', o'_i)$$

depends on s'_j .



Notations


concerning observation variables

$$s'_j \rightarrow o'_i$$



$\exists a \in \mathcal{A}$, such that

$O_i^a(S', o'_i)$
depends on s'_j .



next state

s'_1
 \vdots
 s'_{j_1}
 \vdots
 s'_{j_2}
 \vdots
 s'_{j_m}
 \vdots
 s'_m

o'_i

Notations


concerning observation variables

$$s'_j \rightarrow o'_i$$



$\exists a \in \mathcal{A}$, such that

$O_i^a(S', o'_i)$
depends on s'_j .



Notations


concerning observation variables

$$s'_j \rightarrow o'_i$$




$\exists a \in \mathcal{A}$, such that

$O_i^a(S', o'_i)$
depends on s'_j .



Notations

concerning observation variables



Variables de croyance

different according to the class of the variable

$$\lambda = \#\mathcal{L}$$

Variables de croyance

different according to the class of the variable

$$\lambda = \#\mathcal{L}$$

- $\forall s'_v \in \mathbb{S}_v$, 1 variable β'_v is enough.

Variables de croyance

different according to the class of the variable

$$\lambda = \#\mathcal{L}$$

■ $\forall s'_v \in \mathbb{S}_v$, 1 variable β'_v is enough.

■ $p_i = \#\mathcal{P}(o'_i)$.

$\forall o_i \in \mathbb{O} \setminus \mathbb{S}_v$, $\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}$ belief states,

$\Rightarrow \lceil \log_2(\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}) \rceil$ boolean variables β'_h .

Variables de croyance

different according to the class of the variable

$$\lambda = \#\mathcal{L}$$

■ $\forall s'_v \in \mathbb{S}_v$, 1 variable β'_v is enough.

■ $p_i = \#\mathcal{P}(o'_i)$.

$\forall o_i \in \mathbb{O} \setminus \mathbb{S}_v$, $\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}$ belief states,


$\Rightarrow \lceil \log_2(\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}) \rceil$ boolean variables β'_h .

■ $\forall s'_f \in \mathbb{S}_f$, $\lambda^2 - (\lambda - 1)^2 = 2\lambda - 1$ belief states,

$\Rightarrow \lceil \log_2(2\lambda - 1) \rceil$ boolean variables β'_f .

resulting MDP in practice

final structured MDP



factorized model's variables: $\#\mathbb{O} + \#\mathbb{S}_v +$


$$+ \sum_{i=1}^{\#\mathbb{O}_h} \left[\log_2 (\lambda^{2^{p_i}} - (\lambda - 1)^{2^{p_i}}) \right] + \#\mathbb{S}_f \cdot \left[\log_2 (2\lambda - 1) \right]$$

\ll # initial hybrid model's variables:

$$\left[\log_2 (\lambda^{2^{\#\mathbb{S}}} - (\lambda - 1)^{2^{\#\mathbb{S}}}) \right]$$

resulting MDP in practice

final structured MDP



factorized model's variables:

$$\leq \# \mathbb{O} + \# S_v + \sum_{i=1}^{\# \mathbb{O}_h} \log_2(\lambda) \cdot 2^{p_i} + \# S_f \cdot (1 + \log_2(\lambda))$$

\ll # initial hybrid model's variables:
 $\geq \log_2(\lambda) \cdot (2^{\# \mathbb{S}} - 1).$

Variable classification

3 classes of state variables – state space factorization

variable: visible $s'_v \in \mathbb{S}_v$

s'_v

inferred hidden $s'_h \in \mathbb{S}_h$

s'_h


fully hidden $s'_f \in \mathbb{S}_f$

s'_f

Variable classification

3 classes of state variables – state space factorization

variable: visible $s'_v \in \mathbb{S}_v$



inferred hidden $s'_h \in \mathbb{S}_h$




fully hidden $s'_f \in \mathbb{S}_f$



Variable classification

3 classes of state variables – state space factorization

variable: visible $s'_v \in \mathbb{S}_v$



$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{\mathcal{P}(s'_v)} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b_t^\pi}(\mathcal{P}(s'_v))$$

inferred hidden $s'_h \in \mathbb{S}_h$



fully hidden $s'_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.



$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b_t^\pi}(\mathcal{P}(s'_v))$$

inferred hidden $s'_h \in \mathbb{S}_h$



fully hidden $s'_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables – state space factorization


variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.

$$\mathbf{p}(s'_v \mid b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b_t^\pi}(\mathcal{P}(s'_v))$$



inferred hidden $s'_h \in \mathbb{S}_h$



fully hidden $s'_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$


\Leftrightarrow deterministic belief variable.

$$\mathbf{p}(s'_v \mid b_t^\pi, a) = \sum_{\mathcal{P}(s'_v)} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b_t^\pi}(\mathcal{P}(s'_v))$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$



fully hidden $s'_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{\mathcal{P}(s'_v)} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b_t^\pi}(\mathcal{P}(s'_v))$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) | b_t^\pi, a).$$



fully hidden $s'_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b_t^\pi}(\mathcal{P}(s'_v))$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) | b_t^\pi, a).$$



⚠ $\mathcal{P}(o'_i)$ may contain visible variables

fully hidden $s'_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v \mid b_t^\pi, a) = \sum_{2^{\mathcal{P}(s'_v)}} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b_t^\pi}(\mathcal{P}(s'_v))$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) \mid b_t^\pi, a).$$



⚠ $\mathcal{P}(o'_i)$ may contain visible variables

fully hidden $s'_f \in \mathbb{S}_f$




Variable classification

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{\mathcal{P}(s'_v)} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b_t^\pi}(\mathcal{P}(s'_v))$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) | b_t^\pi, a).$$



⚠ $\mathcal{P}(o'_i)$ may contain visible variables

fully hidden $s'_f \in \mathbb{S}_f$



$$b_{t+1}^\pi(s'_f) = \max_{\mathcal{P}(s'_f)} \min \left\{ \pi(s'_f | \mathcal{P}(s'_f), a), b_t^\pi(\mathcal{P}(s'_f)) \right\}$$


Variable classification

3 classes of state variables – state space factorization

variable: **visible** $s'_v \in \mathbb{S}_v$

\Leftrightarrow deterministic belief variable.


$$\mathbf{p}(s'_v | b_t^\pi, a) = \sum_{\mathcal{P}(s'_v)} T^a(\mathcal{P}(s'_v), s'_v) \cdot \overline{b_t^\pi}(\mathcal{P}(s'_v))$$



inferred hidden $s'_h \in \mathbb{S}_h$

$$b_{t+1}^\pi(\mathcal{P}(o'_i)) = b_{t+1}^\pi(s_h, s_h^a, s_h^b, s_h^c)$$

$$\propto^\pi \pi(o'_i, \mathcal{P}(o'_i) | b_t^\pi, a).$$



⚠ $\mathcal{P}(o'_i)$ may contain visible variables

fully hidden $s'_f \in \mathbb{S}_f$

\rightarrow observations don't
inform belief state on s'_f



$$b_{t+1}^\pi(s'_f) = \max_{\mathcal{P}(s'_f)} \min \left\{ \pi(s'_f | \mathcal{P}(s'_f), a), b_t^\pi(\mathcal{P}(s'_f)) \right\}$$

Toy example: 2 machine states, 3 occurrences

columns		1	2	3	4	5
SITUATION						
v'	v_A	1				1
	v_B		1			
	v_C	1			1	
h	s_A	1	1		1	
	s_B			1		1
BEHAVIOUR						
h'	s_A					1
	s_B		1		1	
EFFECT		\bar{e}	\tilde{e}	\bar{e}	\hat{e}	\underline{e}
POSSIBILITY		1	ε	1	λ	δ

Probability / Possibility :

e_1 or e_2	$\mathbf{p}(e_1) + \mathbf{p}(e_2 \cap \overline{e_1})$	$\max \{ \pi(e_1), \pi(e_2) \}$
e_1 and e_2	$\mathbf{p}(e_1) \cdot \mathbf{p}(e_2 e_1)$	$\min \{ \pi(e_1), \pi(e_2 e_1) \}$

Back to general POMDP: Partially Observable Criteria

Rewriting: belief dependent reward (belief trick)

- $r : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$ reward function
- $\rho : \mathcal{S} \times \mathcal{A} \rightarrow \mathcal{L}$ preference function

Probability / Possibility:

$R(b_t, d_t)$ $= \sum_s r(s, d_t) \cdot b_t(s)$	<p>optimistic: $\overline{\Psi}(\beta_t, \delta_t)$</p> $= \max_s \min \{ \rho(s, \delta_t), \beta_t(s) \}$ <p>pessimistic: $\underline{\Psi}(\beta_t, \delta_t)$</p> $= \min_s \max \{ \rho(s, \delta_t), 1 - \beta_t(s) \}$
$\mathbb{E}[r(S_t, d_t)] = \mathbb{E}[R(b_t, d_t)]$	$\mathbb{S}_{\Pi}[\rho(S_t, d_t)] = \mathbb{S}_{\Pi}[\overline{\Psi}(\beta_t, d_t)]$ $\mathbb{S}_{\mathcal{N}}[\rho(S_t, d_t)] = \mathbb{S}_{\mathcal{N}}[\underline{\Psi}(\beta_t, d_t)]$

Note: $\mathbb{S}_{\Pi}[\underline{\Psi}(\beta_t, d_t)]; \mathbb{S}_{\mathcal{N}}[\overline{\Psi}(\beta_t, d_t)]?$

Why model ignorance?

knowledge is not always encouraged with POMDPs

- initial belief deterministic $s_0 = s_A$.


s_A

$$b_0(s_A) = 1$$

Why model ignorance?

knowledge is not always encouraged with POMDPs


- initial belief deterministic $s_0 = s_A$.



Why model ignorance?

knowledge is not always encouraged with POMDPs


- initial belief deterministic $s_0 = s_A$.



Why model ignorance?

knowledge is not always encouraged with POMDPs

- initial belief deterministic $s_0 = s_A$.




- $\{s_B, s_C, s_D\} \xrightarrow{\text{deterministic}} s_E, r(s_E) = 0$.

Why model ignorance?

knowledge is not always encouraged with POMDPs

- initial belief deterministic $s_0 = s_A$.




- $\{s_B, s_C, s_D\} \xrightarrow{\text{deterministic}} s_E, r(s_E) = 0$.

$$\mathbb{E}_{s_0 \sim b_0} \left[\sum_{t=0}^{+\infty} \gamma^t \cdot r(s_t) \mid a_0 = \tilde{a} \text{ or } a' \right] = r(s_0) + 5\gamma.$$

the safe action is not preferred.


Why model ignorance?

Choquet integral and rewards



Why model ignorance?

Choquet integral and rewards




- $Ch(r, N_{b_1^\pi} \mid a_0 = \tilde{a}) = r(s_D, \tilde{a}) = 5,$
- $Ch(r, N_{b_1^\pi} \mid a_0 = a') = \min_{s \in \mathcal{S}} r(s, a') = 0.$

the safe action is preferred! **dispersion reduced**

Why model ignorance?

Choquet integral and rewards



- $Ch(r, N_{b_1^\pi} \mid a_0 = \tilde{a}) = r(s_D, \tilde{a}) = 5,$
- $Ch(r, N_{b_1^\pi} \mid a_0 = a') = \min_{s \in \mathcal{S}} r(s, a') = 0.$

the safe action is preferred! **dispersion reduced**

if $\mathcal{N}_{b_1^\pi}$ replaced by $b_1 \Rightarrow Ch(r, b_1) = \mathbb{E}_{s \sim b_1} [r(s, a)]$.

Choquet integral and rewards

pessimistic evaluation of the rewards – necessity measure

imprecision of b^π = agent ignorance + discretization:
pessimistic reward about these imprecisions.

Choquet integral and rewards

pessimistic evaluation of the rewards – necessity measure

imprecision of b^π = agent ignorance + discretization:
pessimistic reward about these imprecisions.

Dual measure of $\Pi : 2^{\mathcal{S}} \rightarrow \mathcal{L}$

necessity \mathcal{N} such that $\forall A \subseteq \mathcal{S}, \mathcal{N}(A) = 1 - \Pi(\overline{A})$.

Choquet integral and rewards

pessimistic evaluation of the rewards – necessity measure

imprecision of b^π = agent ignorance + discretization:

pessimistic reward about these imprecisions.

Dual measure of $\Pi : 2^{\mathcal{S}} \rightarrow \mathcal{L}$

necessity \mathcal{N} such that $\forall A \subseteq \mathcal{S}, \mathcal{N}(A) = 1 - \Pi(\bar{A})$.

$r_1 > r_2 > \dots > r_{k+1} = 0$ represents elements of $\{r(s, a) | s \in \mathcal{S}\}$.

Choquet integral of r with respect to \mathcal{N}

$$Ch(r, \mathcal{N}) = \sum_{i=1}^k (r_i - r_{i+1}) \cdot \mathcal{N}(\{r(s) \geq r_i\}) \quad (1)$$

(2)

Choquet integral and rewards

pessimistic evaluation of the rewards – necessity measure

imprecision of b^π = agent ignorance + discretization:

pessimistic reward about these imprecisions.

Dual measure of $\Pi : 2^{\mathcal{S}} \rightarrow \mathcal{L}$

necessity \mathcal{N} such that $\forall A \subseteq \mathcal{S}, \mathcal{N}(A) = 1 - \Pi(\bar{A})$.

$r_1 > r_2 > \dots > r_{k+1} = 0$ represents elements of $\{r(s, a) | s \in \mathcal{S}\}$.

Choquet integral of r with respect to \mathcal{N}

$$Ch(r, \mathcal{N}) = \sum_{i=1}^k (r_i - r_{i+1}) \cdot \mathcal{N}(\{r(s) \geq r_i\}) \quad (1)$$

$$= \sum_{i=1}^{\#\mathcal{L}-1} (l_i - l_{i+1}) \cdot \min_{\substack{s \in \mathcal{S} \text{ s.t.} \\ b^\pi(s) \geq l_i}} r(s) \quad (2)$$

notation $\mathcal{L} = \{l_1 = 1, l_2, l_3, \dots, 0\}$.

resulting MDP in practice

trick: “flipflop” variable

boolean variable “*flipflop*” f changes state at each time step
→ defines 2 phases:

- 1 *observation generation*,
- 2 *belief update* (deterministic knowing the observation)

MDP variables:

$\tilde{S} =$


beliefs: $\beta = \beta_v^1 \times \dots \times \beta_v^{m_v} \times \beta_h^1 \times \dots \times \beta_h^{m_h} \times \beta_f^1 \times \dots \times \beta_f^{m_f}$

\times

visible variables : $v = f \times s_v^1 \times \dots \times s_v^{m_v} \times o_1 \times \dots \times o_k.$

resulting MDP in practice

final structured MDP



$\tilde{\mathbb{S}} =$

beliefs: $\beta = \beta_v^1 \times \dots \times \beta_v^{m_v} \times \beta_h^1 \times \dots \times \beta_h^{m_h} \times \beta_f^1 \times \dots \times \beta_f^{m_f}$

\times

visible variables : $v = f \times s_v^1 \times \dots \times s_v^{m_v} \times o_1 \times \dots \times o_k.$