



Structured Possibilistic Planning using Decision Diagrams

Nicolas Drougard, Florent Teichteil-Königsbuch,
Jean-Loup Farges and Didier Dubois.

AAAI-14 – July 31st 2014



Mixed-Observable Markov Decision Process (MOMDP)

(Ong et al., RSS-09)

model for **sequential decision making under uncertainty**.



Mixed-Observable Markov Decision Process (MOMDP)

(Ong et al., RSS-09)

model for **sequential decision making under uncertainty**.



- ▶ real problems may be huge → need for compact representation;
- ▶ probabilities may not be known → need for flexible modelling.



We adopt a possibilistic model: π -MOMDP,
counterpart of MOMDP from *Qualitative Possibility Theory*;

We adopt a possibilistic model: π -MOMDP,
counterpart of MOMDP from *Qualitative Possibility Theory*;

Algebraic Decision Diagrams (ADDs)
symbolically represent transition functions.




example of ADD

We adopt a possibilistic model: π -MOMDP,
counterpart of MOMDP from *Qualitative Possibility Theory*;

Algebraic Decision Diagrams (ADDs)
symbolically represent transition functions.

- ▶ probabilistic model: + and \times used (e.g. for \mathbb{E})
⇒ new values created,
number of ADD leaves **potentially huge**.

KEY	
true	false



example of ADD

- ▶ possibilistic model: min and max used
⇒ finite number of values manipulated, number of leaves bounded,
ADDs smaller in practice.

Qualitative Possibility theory

Events $e \subset \Omega$ **sorted** using **possibility degrees** $\pi(e) \in \mathcal{L}$,
where \mathcal{L} finite scale such as $\left\{ 0, \frac{1}{n}, \frac{2}{n}, \dots, 1 \right\}$
 \neq
quantified with **frequencies** $p(e) \in [0, 1]$ (probabilities)

- ▶ $\pi(e_1) \leq \pi(e_2)$ only means “ e_1 is less plausible than e_2 ”;

Qualitative Possibility theory

Events $e \subset \Omega$ sorted using **possibility degrees** $\pi(e) \in \mathcal{L}$,
where \mathcal{L} finite scale such as $\left\{ 0, \frac{1}{n}, \frac{2}{n}, \dots, 1 \right\}$
 \neq
quantified with **frequencies** $p(e) \in [0, 1]$ (probabilities)

- ▶ $\pi(e_1) \leq \pi(e_2)$ only means “ e_1 is less plausible than e_2 ”;

Qualitative Possibilistic translation
 \Updownarrow
approximation that requires less knowledge.



Qualitative Possibility theory

Events $e \subset \Omega$ sorted using **possibility degrees** $\pi(e) \in \mathcal{L}$,
where \mathcal{L} finite scale such as $\left\{0, \frac{1}{n}, \frac{2}{n}, \dots, 1\right\}$
 \neq
quantified with **frequencies** $p(e) \in [0, 1]$ (probabilities)

- $\pi(e_1) \leq \pi(e_2)$ only means “ e_1 is less plausible than e_2 ”;

Qualitative Possibilistic translation



approximation that requires less knowledge.


Probability (\mathbb{P}) / possibility (Π) theories. $e_1 \neq e_2$, two events $\subset \Omega$:

e_1 or e_2 (union)	\mathbb{P} : $p(e_1) + p(e_2 \cap \bar{e}_1)$	Π : $\max \{\pi(e_1), \pi(e_2)\}$
e_1 and e_2 (intersect.)	\mathbb{P} : $p(e_1) \cdot p(e_2 e_1)$	Π : $\min \{\pi(e_1), \pi(e_2 e_1)\}$



π -MOMDPs

system = { an agent selecting actions $a \in \mathcal{A}$, its environment };






π -MOMDPs

system = { an agent selecting actions $a \in \mathcal{A}$, its environment };

system state at step t : $s_t = (s_{v,t}, s_{h,t})$

- ▶ $s_v \in \mathcal{S}_v$ visible to the agent;
- ▶ $s_h \in \mathcal{S}_h$ hidden but producing observation $o_t \in \mathcal{O}$ with possibility degree $\pi(o_t | s_t, a_{t-1}) \in \mathcal{L}$.






π -MOMDPs

system = { an agent selecting actions $a \in \mathcal{A}$, its environment };

system state at step t : $s_t = (s_{v,t}, s_{h,t})$

- ▶ $s_v \in \mathcal{S}_v$ **visible** to the agent;
- ▶ $s_h \in \mathcal{S}_h$ **hidden** but producing observation $o_t \in \mathcal{O}$ with possibility degree $\pi(o_t | s_t, a_{t-1}) \in \mathcal{L}$.
- ▶ Next state s_{t+1} arises with possibility degree $\pi(s_{t+1} | s_t, a_t)$.
- ▶ Goal of the problem modeled with preference $\mu(s) \in \mathcal{L}$.
- ▶ History: $h_t = \{o_1, \dots, o_t, s_{v,0}, \dots, s_{v,t}, a_0, \dots, a_{t-1}\}$.

problem solving = build action **strategy** to achieve a mission.






Bayes' rule + current observation $o \in \mathcal{O}$

→ process **visible to the agent** $x = (s_v, \beta) \in \mathcal{X} = \mathcal{S}_v \times B^\pi$

$\beta \in B^\pi$ belief i.e. possibility distribution over s_h : $\beta_t(s_h) = \pi(s_h | h_t)$.






Bayes' rule + current observation $o \in \mathcal{O}$

→ process **visible to the agent** $x = (s_v, \beta) \in \mathcal{X} = \mathcal{S}_v \times B^\pi$

$\beta \in B^\pi$ belief i.e. possibility distribution over s_h : $\beta_t(s_h) = \pi(s_h | h_t)$.

- ▶ New transition function $\pi(x' | x, a)$ and preference $\mu(x)$.
 - ▶ Resolution space \mathcal{X} **finite** thanks to finite possibilistic scale \mathcal{L} .
- ⇒ finite state space π -MDP! (probabilistic MOMDP: continuous space)





Bayes' rule + current observation $o \in \mathcal{O}$

→ process **visible to the agent** $x = (s_v, \beta) \in \mathcal{X} = \mathcal{S}_v \times B^\pi$

$\beta \in B^\pi$ belief i.e. possibility distribution over s_h : $\beta_t(s_h) = \pi(s_h | h_t)$.


- ▶ New transition function $\pi(x' | x, a)$ and preference $\mu(x)$.
- ▶ Resolution space \mathcal{X} **finite** thanks to finite possibilistic scale \mathcal{L} .

⇒ **finite state space** π -MDP! (probabilistic MOMDP: **continuous space**)

Strategy $\delta : \mathcal{X} \rightarrow \mathcal{A}$ computed using **value iteration**

$$V_{h+1}^*(x) = \max_a \max_{x'} \min \left\{ \pi(x' | x, a), V_h(x') \right\} \text{ with } V_0^* = \mu:$$


$\delta(x)$ is the last $a \in \mathcal{A}$ increasing $V_h^*(x)$. (Drougard et al., UAI-13)



We introduce factored π -MOMDP model

factored π -MOMDP

\Leftrightarrow resolution space \mathcal{X} described with binary variables (X_1, \dots, X_n)
+ dynamic fits in with Dynamic Bayesian Network below.






We introduce factored π -MOMDP model


factored π -MOMDP

\Leftrightarrow resolution space \mathcal{X} described with binary variables (X_1, \dots, X_n)
 + dynamic fits in with Dynamic Bayesian Network below.



- ▶ Transition functions $T_i^a = \pi(X'_i | \text{parents}(X_i), a)$ **represented with Algebraic Decision Diagrams** on finite $\mathcal{L} \subset \mathbb{N}$.
 (see SPUDD – Hoey et al., UAI-99).

KEY
true / false



example of ADD



Proposition: value function qualitative aggregation

$V_h^* : \{0, 1\}^p \rightarrow \mathcal{L}$ value function, $a \in \mathcal{A}$ action.

define: 1) $q_0^a = V_h^*(X'_1, \dots, X'_n)$;

2) for $i : 1..n$, $q_i^a = \max_{X'_i \in \{0,1\}} \min \{ (X'_i \mid \text{parents}(X'_i), a), q_{i-1}^a \}$;

Then, $V_{h+1}^* = \max_{a \in \mathcal{A}} q_n^a$.

Proposition: value function qualitative aggregation

$V_h^* : \{0, 1\}^p \rightarrow \mathcal{L}$ value function, $a \in \mathcal{A}$ action.

define: 1) $q_0^a = V_h^*(X'_1, \dots, X'_n)$;

2) for $i : 1..n$, $q_i^a = \max_{X'_i \in \{0,1\}} \min \{ (X'_i \mid \text{parents}(X'_i), a), q_{i-1}^a \}$;

Then, $V_{h+1}^* = \max_{a \in \mathcal{A}} q_n^a$.

Algorithm PPUDD: Possibilistic Planning Using Decision Diagrams

```

1  $V^* \leftarrow 0 ; V^c \leftarrow \mu ; \delta \leftarrow \bar{a} ;$ 
2 while  $V^* \neq V^c$  do
3    $V^* \leftarrow V^c ;$ 
4   for  $a \in \mathcal{A}$  do
5      $q^a \leftarrow \text{swap each } X_i \text{ variable in } V^* \text{ with } X'_i ;$ 
6     for  $1 \leq i \leq n$  do
7        $q^a \leftarrow \boxed{\min} \{ q^a, \pi(X'_i \mid \text{parents}(X'_i), a) \} ;$ 
8        $q^a \leftarrow \boxed{\max}_{X'_i} q^a ;$ 
9      $V^c \leftarrow \boxed{\max} \{ q^a, V^c \} ;$ 
10    update  $\delta$  to  $a$  where  $q^a = V^c$  and  $V^c > V^*$  ;
11  return  $(V^*, \delta) ;$ 
```



Proposition: value function qualitative aggregation

$V_h^* : \{0, 1\}^p \rightarrow \mathcal{L}$ value function, $a \in \mathcal{A}$ action.

define: 1) $q_0^a = V_h^*(X'_1, \dots, X'_n)$;

2) for $i : 1..n$, $q_i^a = \max_{X'_i \in \{0,1\}} \min \{ (X'_i \mid \text{parents}(X'_i), a), q_{i-1}^a \}$;

Then, $V_{h+1}^* = \max_{a \in \mathcal{A}} q_n^a$.

Algorithm PPUDD: Possibilistic Planning Using Decision Diagrams

```

1  $V^* \leftarrow 0 ; V^c \leftarrow \mu ; \delta \leftarrow \bar{a} ;$ 
2 while  $V^* \neq V^c$  do
3    $V^* \leftarrow V^c ;$ 
4   for  $a \in \mathcal{A}$  do
5      $q^a \leftarrow \text{swap each } X_i \text{ variable in } V^* \text{ with } X'_i ;$ 
6     for  $1 \leq i \leq n$  do
7        $q^a \leftarrow \min \{ q^a, \pi(X'_i \mid \text{parents}(X'_i), a) \} ;$ 
8        $q^a \leftarrow \max_{X'_i} q^a ;$ 
9      $V^c \leftarrow \max \{ q^a, V^c \} ;$ 
10    update  $\delta$  to  $a$  where  $q^a = V^c$  and  $V^c > V^*$  ;
11  return  $(V^*, \delta)$  ;

```

factorization
 +
 previous proposition,
 → value iterations



Proposition: value function qualitative aggregation

$V_h^* : \{0, 1\}^p \rightarrow \mathcal{L}$ value function, $a \in \mathcal{A}$ action.

define: 1) $q_0^a = V_h^*(X'_1, \dots, X'_n)$;

2) for $i : 1..n$, $q_i^a = \max_{X'_i \in \{0,1\}} \min \{ (X'_i \mid \text{parents}(X'_i), a), q_{i-1}^a \}$;

Then, $V_{h+1}^* = \max_{a \in \mathcal{A}} q_n^a$.

Algorithm PPUDD: Possibilistic Planning Using Decision Diagrams

```

1  $V^* \leftarrow 0 ; V^c \leftarrow \mu ; \delta \leftarrow \bar{a} ;$ 
2 while  $V^* \neq V^c$  do
3    $V^* \leftarrow V^c ;$ 
4   for  $a \in \mathcal{A}$  do
5      $q^a \leftarrow \text{swap each } X_i \text{ variable in } V^* \text{ with } X'_i ;$ 
6     for  $1 \leq i \leq n$  do
7        $q^a \leftarrow \min \{ q^a, \pi(X'_i \mid \text{parents}(X'_i), a) \} ,$ 
8        $q^a \leftarrow \max_{X'_i} q^a ;$ 
9      $V^c \leftarrow \max \{ q^a, V^c \} ;$ 
10    update  $\delta$  to  $a$  where  $q^a = V^c$  and  $V^c > V^*$  ;
11 return  $(V^*, \delta)$  ;

```

factorization
 +
 previous proposition,
 → value iterations
 divided into n steps


handled ADDs smaller
 → speeds up computation.



Independent beliefs

A π -MOMDP fulfilling assumptions of the Dynamic Bayesian Network below has a **natural factorization**:

$(s_v, \beta) = (s_{v,1}, \dots, s_{v,m}, \beta_1, \dots, \beta_l)$, with β_i belief about $s_{h,i}$.






Independent beliefs

A π -MOMDP fulfilling assumptions of the Dynamic Bayesian Network below has a **natural factorization**:

$(s_v, \beta) = (s_{v,1}, \dots, s_{v,m}, \beta_1, \dots, \beta_l)$, with β_i belief about $s_{h,i}$.


some assumptions: one observation variable for each hidden state variable, hidden state variables independent on other hidden state variables ...





beginning of the proof:


- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d-separated** by evidence h_t (history)





beginning of the proof:


- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d-separated** by evidence h_t (history)





beginning of the proof:


- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d-separated** by evidence h_t (history)





beginning of the proof:


- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d-separated** by evidence h_t (history)





beginning of the proof:


- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d-separated** by evidence h_t (history)





beginning of the proof:


- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d-separated** by evidence h_t (history)





beginning of the proof:


- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d-separated** by evidence h_t (history)





beginning of the proof:


- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d-separated** by evidence h_t (history)





beginning of the proof:


- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d-separated** by evidence h_t (history)





beginning of the proof:


- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d-separated** by evidence h_t (history)





beginning of the proof:


- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d-separated** by evidence h_t (history)





beginning of the proof:

- $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d-separated** by evidence h_t (history)






beginning of the proof:

- ▶ $\forall 1 \leq i < j \leq l$, $s_{h,i}$ and $s_{h,j}$ are **d-separated** by evidence h_t (history)
- for each time t , hidden state variables $s_{h,i}$ are independent given h_t

$$\text{i.e. } \beta_t(s_h) = \pi(s_h | h_t) = \min_i \pi(s_{h,i} | h_t) = \min_i \beta_{t,i}(s_{h,i})$$

evidence:

history h_t



Experimentations

PPUDD against SPUDD (*Hoey et al., UAI-99*)

Navigation benchmark: robot has to reach a goal;
may disappear in some places.

2 probabilistic translations: M1 (optimistic) and M2 (pessimistic).





Experimentations

PPUDD against SPUDD (*Hoey et al., UAI-99*)

Navigation benchmark: robot has to reach a goal;
may disappear in some places.


2 probabilistic translations: M1 (optimistic) and M2 (pessimistic).

Performances for increasing size of benchmark instances:






Computation time



Max size of ADD “value function”



- ▶ PPUDD + M2 (pessimistic translation)
faster with same quality performances as SPUDD;
- ▶ SPUDD only solve the 5th first instances;
- ▶ verified intuition: ADDs are smaller.



PPUDD against APPL (*Kurniawati et al., RSS-08, MOMDP solver*);
symbolic HSVI (*Sim et al., AAAI-09, POMDP solver*).

RockSample benchmark: a robot has to recognize interesting rocks;
sample only interesting ones.




PPUDD against APPL (*Kurniawati et al., RSS-08, MOMDP solver*);
symbolic HSVI (*Sim et al., AAAI-09, POMDP solver*).

RockSample benchmark: a robot has to recognize interesting rocks;
sample only interesting ones.

Computation time:


probabilistic solvers, prec. 1;
PPUDD, exact resolution.



Expected total reward

APPL stopped at

PPUDD computation time.






PPUDD against APPL (*Kurniawati et al., RSS-08, MOMDP solver*);
symbolic HSVI (*Sim et al., AAAI-09, POMDP solver*).

RockSample benchmark: a robot has to recognize interesting rocks;
sample only interesting ones.

Computation time:


probabilistic solvers, prec. 1;
PPUDD, exact resolution.



Expected total reward

APPL stopped at

PPUDD computation time.



► **approximate model + exact efficient algorithm**

→ beneficial in computation times and performances.

IPPC 2014 results – MDP track

PPUDD + BDD mask for computation over reachable states only

IPPC 2014 results – MDP track

PPUDD + BDD mask for computation over reachable states only

results:

PPUDD 2× better than LRTDP (*Bonet et al.*, ICAPS-03) with ADDs;
2× worse than LRTDP with enumerated states.

IPPC 2014 results – MDP track

PPUDD + BDD mask for computation over reachable states only

results:

PPUDD 2× better than LRTDP (*Bonet et al.*, ICAPS-03) with ADDs;
2× worse than LRTDP with enumerated states.

⇒ ADDs based methods: probabilistic approach (*without* heuristics)
better than probabilistic approach (*with* heuristic).



IPPC 2014 results – MDP track

PPUDD + BDD mask for computation over reachable states only

results:

PPUDD 2× better than LRTDP (*Bonet et al.*, ICAPS-03) with ADDs;
2× worse than LRTDP with enumerated states.

⇒ ADDs based methods: possibilistic approach (*without* heuristics)
better than probabilistic approach (*with* heuristic).

open problems:

- ▶ symbolic methods \prec state space search
 - possibilistic approach with enumerated states and heuristics like winners of IPPC 2014 (PROST and GOURMAND)?
- ▶ **naive $\mathbb{P} \rightarrow \Pi$ automated translation**
 - automatic and efficient translation $\mathbb{P} \rightarrow \Pi$?



IPPC 2014 results – MDP track

PPUDD + BDD mask for computation over reachable states only

results:

PPUDD 2× better than LRTDP (*Bonet et al.*, ICAPS-03) with ADDs;
2× worse than LRTDP with enumerated states.

⇒ ADDs based methods: possibilistic approach (*without* heuristics)
better than probabilistic approach (*with* heuristic).

open problems:

- ▶ symbolic methods \prec state space search
 - possibilistic approach with enumerated states and heuristics like winners of IPPC 2014 (PROST and GOURMAND)?
- ▶ **naive $\mathbb{P} \rightarrow \Pi$ automated translation**
 - automatic and efficient translation $\mathbb{P} \rightarrow \Pi$?
- ▶ time management: PPUDD's total computation time = 15h \ll 24h;
- ▶ ADD instantiation does not fit into memory for 15 in 80 benchmarks.

Conclusion and perspectives

Works called by this one:

- ▶ test POMDP track of IPPC 2014,
- ▶ bring belief factorization to probabilistic framework
(see Boyen, Koller, McAllester, Poupart, Shani ...).

Conclusion and perspectives

Works called by this one:

- ▶ test POMDP track of IPPC 2014,
- ▶ bring belief factorization to probabilistic framework
(see Boyen, Koller, McAllester, Poupart, Shani ...).

PPUDD: probabilistic algorithm taking advantage of π -MOMDP structure.

- ▶ computations stay in finite scale \mathcal{L}
⇒ used **ADDS smaller** than for probabilistic framework;
- ▶ **natural factorization** for π -MOMDP modelling system with few independent sensors;
- ▶ **approximate model and exact resolution can win against exact model and approximate resolution.**

Thank you for your attention!

Any questions?



let $e_1 \neq e_2$ be two events $\subset \Omega$:

meaning or operation	THEORY	
	Probability (\mathbb{P})	Possibility (Π)
normalization	$\sum_{\Omega} \mathbf{p}(e) = 1$	$\max_{\Omega} \pi(e) = 1$
e_1 impossible	$\mathbf{p}(e_1) = 0$	$\pi(e_1) = 0$
e_1 certain	$\mathbf{p}(e_1) = 1$	$\max_{e \notin e_1} \pi(e) = 0$
e_1 or e_2 (union)	$\mathbf{p}(e_1) + \mathbf{p}(e_2)$	$\max \{ \pi(e_1), \pi(e_2) \}$
e_1 and e_2 (intersect.)	$\mathbf{p}(e_1) \cdot \mathbf{p}(e_2 e_1)$	$\min \{ \pi(e_1), \pi(e_2 e_1) \}$
Bayes' rule: $e_1 e_2$	$\frac{\mathbf{p}(e_2 e_1) \cdot \mathbf{p}(e_1)}{\mathbf{p}(e_2)}$	$1 \text{ if } e_1 \in \operatorname{argmax}_{e \subset \Omega} \pi(e_1, e)$ $\pi(e_1, e_2) \text{ otherwise.}$

d -separation

- ⇒ each belief state β_i updated using corresponding observation only;
- ⇒ $s_{v,1}, \dots, s_{v,m}, \beta_1, \dots, \beta_l$ are **independent post-action variables**.

⇒ $m + l$ ADDs (for each subset) instead of a bigger one (over \mathcal{X}).



d -separation

⇒ each belief state β_i updated using corresponding observation only;
⇒ $s_{v,1}, \dots, s_{v,m}, \beta_1, \dots, \beta_l$ are **independent post-action variables**.

⇒ $m + l$ ADDs (for each subset) instead of a bigger one (over \mathcal{X}).

$$\Rightarrow \mathcal{X} = \mathcal{S}_{v,1} \times \dots \times \mathcal{S}_{v,m} \times B_1^\pi \times \dots \times B_l^\pi$$

Size of B_j^π : $\#B_j^\pi = \#\mathcal{L}^{\#\mathcal{S}_{h,j}} - (\#\mathcal{L} - 1)^{\#\mathcal{S}_{h,j}}$.



d -separation

⇒ each belief state β_i updated using corresponding observation only;
⇒ $s_{v,1}, \dots, s_{v,m}, \beta_1, \dots, \beta_l$ are **independent post-action variables**.

⇒ $m + l$ ADDs (for each subset) instead of a bigger one (over \mathcal{X}).

$$\Rightarrow \mathcal{X} = \mathcal{S}_{v,1} \times \dots \times \mathcal{S}_{v,m} \times B_1^\pi \times \dots \times B_l^\pi$$

Size of B_j^π : $\#B_j^\pi = \#\mathcal{L}^{\#\mathcal{S}_{h,j}} - (\#\mathcal{L} - 1)^{\#\mathcal{S}_{h,j}}$.







binary state variables ⇒ $\#B_j^\pi = 2\#\mathcal{L} - 1$
⇒ $\#\mathcal{X} = 2^m(2\#\mathcal{L} - 1)^l$.

hidden and visible state variables → **same impact** on space size:
singly-exponential in the number of state variables ≠ probabilistic settings.



IPPC 2014 results – PPUDD vs symbolic LRTDP

Average of Total Reward for simulated runs





participation in IPPC 2014 – MDP track



participation in IPPC 2014 – MDP track



participation in IPPC 2014 – MDP track



participation in IPPC 2014 – MDP track





$X'_1 = \text{true}$		
true	$\frac{1}{3}$	$\frac{1}{3}$
false	$\frac{1}{3}$	$\frac{2}{3}$

$X'_1 = \text{false}$		
true	1	1
false	1	1

X_1/X_2	true	false

X_1/X_2	true	false





intuition: remains small not creating new leaves/ADDs

