

Restaurant Manager API documentation

Content

1. Endpoints	1
1.1. Any User	1
1.1.1. Restaurant	1
1.2. Authenticated User	8
1.2.1. Profile	8
1.2.2. Vote	15
1.3. Admin	17
1.3.1. Profile	17
1.3.2. Restaurant	34
1.3.3. Menu	52
2. Convention	73
2.1. HTTP verbs	73
2.2. HTTP status codes	73
3. Error processing	74

1. Endpoints

1.1. Any User

1.1.1. Restaurant

Table 1. Response fields

Path	Type	Description
[]	Array	Restaurants
[][.id]	Number	Restaurant id
[][.name]	String	Restaurant name
[][.address]	String	Restaurant address
[][.phone]	String	Restaurant phone
[][.votesQuantity]	Number	Restaurant votes quantity
[][.enabled]	Boolean	Restaurant activity marker
[][.menus]	Array	Restaurant menus
[][.menus][.id]	Number	Menu id
[][.menus][.name]	String	Menu name
[][.menus][.menuDate]	String	Menu date
[][.menus][.enabled]	Boolean	Menu activity marker
[][.menus][.menuItems]	Array	Menu dishes
[][.menus][.menuItems][.id]	Number	Dish id
[][.menus][.menuItems][.name]	String	Dish name
[][.menus][.menuItems][.price]	Number	Dish price

examples

Curl

```
$ curl 'http://localhost:8080/rest/any/restaurants/' -i -X GET
```

HTTP Request

```
GET /rest/any/restaurants/ HTTP/1.1  
Host: localhost:8080
```

HTTP Response

```
HTTP/1.1 200 OK  
Content-Type: application/json;charset=UTF-8  
Content-Length: 512
```

```
[ {  
  "id" : 0,  
  "name" : "rest1",  
  "address" : "address1",  
  "phone" : "+7 (911) 111-1111",  
  "enabled" : true,  
  "votesQuantity" : 4,  
  "menus" : [ {  
    "id" : 1,  
    "name" : "menu2",  
    "menuDate" : "2020-01-27",  
    "enabled" : true,  
    "menuItems" : [ {  
      "id" : 3,  
      "name" : "menItm4",  
      "price" : 103  
    }, {  
      "id" : 4,  
      "name" : "menItm5",  
      "price" : 104  
    }, {  
      "id" : 5,  
      "name" : "menItm6",  
      "price" : 105  
    } ]  
  } ]  
} ]
```



Keep in mind:

- Empty request parameters = getAll.

Table 2. Request parameters

Parameter	Optional	Description
name	false	Restaurant name
address	false	Restaurant address

Table 3. Response fields

Path	Type	Description
[]	Array	Restaurants
[][.id]	Number	Restaurant id
[][.name]	String	Restaurant name
[][.address]	String	Restaurant address
[][.phone]	String	Restaurant phone
[][.votesQuantity]	Number	Restaurant votes quantity
[][.enabled]	Boolean	Restaurant activity marker
[][.menus]	Array	Restaurant menus
[][.menus][.id]	Number	Menu id
[][.menus][.name]	String	Menu name
[][.menus][.menuDate]	String	Menu date
[][.menus][.enabled]	Boolean	Menu activity marker
[][.menus][.menuItems]	Array	Menu dishes
[][.menus][.menuItems][.id]	Number	Dish id
[][.menus][.menuItems][.name]	String	Dish name
[][.menus][.menuItems][.price]	Number	Dish price

examples

Curl

```
$ curl  
'http://localhost:8080/rest/any/restaurants/filter/?name=rest1&address=address1' -i -X GET
```

HTTP Request

```
GET /rest/any/restaurants/filter/?name=rest1&address=address1 HTTP/1.1  
Host: localhost:8080
```

HTTP Response

```
HTTP/1.1 200 OK  
Content-Type: application/json;charset=UTF-8  
Content-Length: 512
```

```
[ {  
  "id" : 0,  
  "name" : "rest1",  
  "address" : "address1",  
  "phone" : "+7 (911) 111-1111",  
  "enabled" : true,  
  "votesQuantity" : 4,  
  "menus" : [ {  
    "id" : 1,  
    "name" : "menu2",  
    "menuDate" : "2020-01-27",  
    "enabled" : true,  
    "menuItems" : [ {  
      "id" : 3,  
      "name" : "menItm4",  
      "price" : 103  
    }, {  
      "id" : 4,  
      "name" : "menItm5",  
      "price" : 104  
    }, {  
      "id" : 5,  
      "name" : "menItm6",  
      "price" : 105  
    } ]  
  } ]  
} ]
```

GET **/rest/any/restaurants/{id}** Get one with day enabled menu

Table 4. */rest/any/restaurants/{id}*

Parameter	Description
id	Restaurant id

Table 5. *Response fields*

Path	Type	Description
id	Number	Restaurant id
name	String	Restaurant name
address	String	Restaurant address
phone	String	Restaurant phone
votesQuantity	Number	Restaurant votes quantity
enabled	Boolean	Restaurant activity marker
menus	Array	Restaurant menus
menus[].id	Number	Menu id
menus[].name	String	Menu name
menus[].menuDate	String	Menu date
menus[].enabled	Boolean	Menu activity marker
menus[].menuItems	Array	Menu dishes
menus[].menuItems[].id	Number	Dish id
menus[].menuItems[].name	String	Dish name
menus[].menuItems[].price	Number	Dish price

examples

Curl

```
$ curl 'http://localhost:8080/rest/any/restaurants/0' -i -X GET
```

HTTP Request

```
GET /rest/any/restaurants/0 HTTP/1.1
Host: localhost:8080
```

Success HTTP Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Content-Length: 508
```

```
{
  "id" : 0,
  "name" : "rest1",
  "address" : "address1",
  "phone" : "+7 (911) 111-1111",
  "enabled" : true,
  "votesQuantity" : 4,
  "menus" : [ {
    "id" : 1,
    "name" : "menu2",
    "menuDate" : "2020-01-27",
    "enabled" : true,
    "menuItems" : [ {
      "id" : 3,
      "name" : "menItm4",
      "price" : 103
    }, {
      "id" : 4,
      "name" : "menItm5",
      "price" : 104
    }, {
      "id" : 5,
      "name" : "menItm6",
      "price" : 105
    } ]
  } ]
}
```

Error HTTP Responses

Get not found

```
HTTP/1.1 422 Unprocessable Entity
Content-Type: application/json;charset=UTF-8
Content-Length: 223
```

```
{
  "url" : "http://localhost:8080/rest/any/restaurants/10",
  "type" : "DATA_NOT_FOUND",
  "detail" : "edu.volkov.restmanager.util.exception.NotFoundException: Not
found entity with restaurant by id: 10dos not exist"
}
```

1.2. Authenticated User

1.2.1. Profile

Table 6. Response fields

Path	Type	Description
id	Number	User id
name	String	User name
email	String	User email
registered	String	User registration date/time
enabled	Boolean	User activity marker
roles.[]	Array	User roles

examples

Curl

```
$ curl 'http://localhost:8080/rest/profile' -i -u 'user1@yandex.ru:password1' -X GET
```

HTTP Request

```
GET /rest/profile HTTP/1.1
Authorization: Basic dXNlcjFAeWFuZGV4LnJ1OnBhc3N3b3JkMQ==
Host: localhost:8080
```

Success HTTP Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
Content-Length: 156

{
  "id" : 0,
  "name" : "User1",
  "email" : "user1@yandex.ru",
  "registered" : "2020-12-23T00:00:00",
  "enabled" : true,
  "roles" : [ "USER" ]
}
```

Error HTTP Responses

Get by unauthorized user

```
HTTP/1.1 401 Unauthorized
WWW-Authenticate: Basic realm="Realm"
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
```

Table 7. Request fields

Path	Type	Optional	Description	Constraints
name	String	false	User name	[Must not be blank, Size must be between 2 and 100 inclusive]
email	String	false	User email	[Must be a well-formed email address, Must not be blank, Size must be between 0 and 100 inclusive]
password	String	false	User password	[Must not be blank, Size must be between 5 and 32 inclusive]

Table 8. Response fields

Path	Type	Description
id	Number	User id
name	String	User name
email	String	User email
registered	String	User registration date/time
enabled	Boolean	User activity marker
roles.[]	Array	User roles

examples

Curl

```
$ curl 'http://localhost:8080/rest/profile/register' -i -X POST \
  -H 'Content-Type: application/json;charset=UTF-8' \
  -d '{
    "name" : "newName",
    "email" : "newemail@ya.ru",
    "password" : "newPassword"
  }'
```

HTTP Request

```
POST /rest/profile/register HTTP/1.1
Content-Type: application/json;charset=UTF-8
Content-Length: 88
Host: localhost:8080

{
  "name" : "newName",
  "email" : "newemail@ya.ru",
  "password" : "newPassword"
}
```

Success HTTP Response

```
HTTP/1.1 201 Created
Location: http://localhost:8080/rest/profile
Content-Type: application/json;charset=UTF-8
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
Content-Length: 161

{
  "id" : 4,
  "name" : "newName",
  "email" : "newemail@ya.ru",
  "registered" : "2020-12-23T16:44:28.964",
  "enabled" : true,
  "roles" : [ "USER" ]
}
```

Table 9. Request fields

Path	Type	Optional	Description	Constraints
name	String	false	User name	[Must not be blank, Size must be between 2 and 100 inclusive]
email	String	false	User email	[Must be a well-formed email address, Must not be blank, Size must be between 0 and 100 inclusive]
password	String	false	User password	[Must not be blank, Size must be between 5 and 32 inclusive]

examples

Curl

```
$ curl 'http://localhost:8080/rest/profile' -i -u 'user1@yandex.ru:password1'
-X PUT \
  -H 'Content-Type: application/json;charset=UTF-8' \
  -d '{
    "name" : "newName",
    "email" : "newemail@ya.ru",
    "password" : "newPassword"
  }'
```

HTTP Request

```
PUT /rest/profile HTTP/1.1
Content-Type: application/json;charset=UTF-8
Content-Length: 88
Authorization: Basic dXNlcjFAeWFuZGV4LnJ10nBhc3N3b3JkMQ==
Host: localhost:8080

{
  "name" : "newName",
  "email" : "newemail@ya.ru",
  "password" : "newPassword"
}
```

Success HTTP Response

```
HTTP/1.1 204 No Content
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
```

DELETE /rest/profile *Delete*

examples

Curl

```
$ curl 'http://localhost:8080/rest/profile' -i -u 'user1@yandex.ru:password1' -X DELETE
```

HTTP Request

```
DELETE /rest/profile HTTP/1.1
Authorization: Basic dXNlcjFAeWFuZGV4LnJ1OnBhc3N3b3JkMQ==
Host: localhost:8080
```

Success HTTP Response

```
HTTP/1.1 204 No Content
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
```

1.2.2. Vote



If user votes again the same day:

- If it is before 11:00 we assume that he changed his mind.
- If it is after 11:00 then it is too late, vote can't be changed.

Table 10. /rest/profile/votes/{restId}

Parameter	Description
restId	Restaurant id

examples

Curl

```
$ curl 'http://localhost:8080/rest/profile/votes/0' -i -u  
'user1@yandex.ru:password1' -X PATCH
```

HTTP Request

```
PATCH /rest/profile/votes/0 HTTP/1.1  
Authorization: Basic dXNlcjFAeWFuZGV4LnJ10nBhc3N3b3JkMQ==  
Host: localhost:8080
```

Success HTTP Response

```
HTTP/1.1 204 No Content  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff
```

Error HTTP Responses

Vote unauthorized

```
HTTP/1.1 401 Unauthorized  
WWW-Authenticate: Basic realm="Realm"  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff
```

1.3. Admin

1.3.1. Profile

Table 11. Response fields

Path	Type	Description
[]	Array	Users
[][.id]	Number	User id
[][.name]	String	User name
[][.email]	String	User email
[][.registered]	String	User registration date/time
[][.enabled]	Boolean	User activity marker
[][.roles.[]]	Array	User roles

examples

Curl

```
$ curl 'http://localhost:8080/rest/admin/users/' -i -u  
'admin@gmail.com:admin' -X GET
```

HTTP Request

```
GET /rest/admin/users/ HTTP/1.1  
Authorization: Basic YWRtaW5AZ21haWwuY29tOmFkbWlu  
Host: localhost:8080
```

HTTP Response

```
HTTP/1.1 200 OK  
Content-Type: application/json;charset=UTF-8  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff  
Content-Length: 485
```

```
[ {  
  "id" : 2,  
  "name" : "Admin",  
  "email" : "admin@gmail.com",  
  "registered" : "2020-12-23T00:00:00",  
  "enabled" : true,  
  "roles" : [ "ADMIN", "USER" ]  
}, {  
  "id" : 0,  
  "name" : "User1",  
  "email" : "user1@yandex.ru",  
  "registered" : "2020-12-23T00:00:00",  
  "enabled" : true,  
  "roles" : [ "USER" ]  
}, {  
  "id" : 1,  
  "name" : "User2",  
  "email" : "user2@yandex.ru",  
  "registered" : "2020-12-23T00:00:00",  
  "enabled" : true,  
  "roles" : [ "USER" ]  
} ]
```

Table 12. **/rest/admin/users/{id}**

Parameter	Description
id	User id

Table 13. Response fields

Path	Type	Description
id	Number	User id
name	String	User name
email	String	User email
registered	String	User registration date/time
enabled	Boolean	User activity marker
roles.[]	Array	User roles

examples

Curl

```
$ curl 'http://localhost:8080/rest/admin/users/2' -i -u  
'admin@gmail.com:admin' -X GET
```

HTTP Request

```
GET /rest/admin/users/2 HTTP/1.1  
Authorization: Basic YWRtaW5AZ21haWwuY29tOmFkbWlu  
Host: localhost:8080
```

Success HTTP Response

```
HTTP/1.1 200 OK  
Content-Type: application/json;charset=UTF-8  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff  
Content-Length: 165  
  
{  
  "id" : 2,  
  "name" : "Admin",  
  "email" : "admin@gmail.com",  
  "registered" : "2020-12-23T00:00:00",  
  "enabled" : true,  
  "roles" : [ "ADMIN", "USER" ]  
}
```

Error HTTP Responses

Get not found

```
HTTP/1.1 422 Unprocessable Entity
Content-Type: application/json;charset=UTF-8
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
Content-Length: 191

{
  "url" : "http://localhost:8080/rest/admin/users/10",
  "type" : "DATA_NOT_FOUND",
  "detail" : "edu.volkov.restmanager.util.exception.NotFoundException: Not
found entity with id=10"
}
```

Get by unauthorized user

```
HTTP/1.1 401 Unauthorized
WWW-Authenticate: Basic realm="Realm"
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
```

Get by forbidden user

```
HTTP/1.1 403 Forbidden
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
```

Table 14. Request parameters

Parameter	Optional	Description
email	false	User email

Table 15. Response fields

Path	Type	Description
id	Number	User id
name	String	User name
email	String	User email
registered	String	User registration date/time
enabled	Boolean	User activity marker
roles.[]	Array	User roles

examples

Curl

```
$ curl 'http://localhost:8080/rest/admin/users/by?email=admin@gmail.com' -i  
-u 'admin@gmail.com:admin' -X GET
```

HTTP Request

```
GET /rest/admin/users/by?email=admin@gmail.com HTTP/1.1  
Authorization: Basic YWRtaW5AZ21haWwuY29tOmFkbWlu  
Host: localhost:8080
```

HTTP Response

```
HTTP/1.1 200 OK  
Content-Type: application/json;charset=UTF-8  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff  
Content-Length: 165  
  
{  
  "id" : 2,  
  "name" : "Admin",  
  "email" : "admin@gmail.com",  
  "registered" : "2020-12-23T00:00:00",  
  "enabled" : true,  
  "roles" : [ "ADMIN", "USER" ]  
}
```


Table 16. Request fields

Path	Type	Optional	Description	Constraints
name	String	false	User name	[Must not be blank, Size must be between 2 and 100 inclusive]
email	String	false	User email	[Must be a well-formed email address, Size must be between 0 and 100 inclusive]
registered	String	false	User registration date/time	[Must not be null]
password	String	false	User registration date/time	[Size must be between 5 and 100 inclusive]
enabled	Boolean	false	User activity marker	[]
roles.[]	Array	false	User roles	[]

Table 17. Response fields

Path	Type	Description
id	Number	User id
name	String	User name
email	String	User email
registered	String	User registration date/time
enabled	Boolean	User activity marker
roles.[]	Array	User roles

examples

Curl

```
$ curl 'http://localhost:8080/rest/admin/users/' -i -u
'admin@gmail.com:admin' -X POST \
  -H 'Content-Type: application/json;charset=UTF-8' \
  -d '{
    "name" : "New",
    "email" : "new@gmail.com",
    "registered" : "2020-12-23T17:15:37.55",
    "enabled" : false,
    "roles" : [ "USER" ],
    "password" : "newPass"
  }'
```

HTTP Request

```
POST /rest/admin/users/ HTTP/1.1
Content-Type: application/json;charset=UTF-8
Content-Length: 170
Authorization: Basic YWRtaW5AZ21haWwuY29tOmFkbWlu
Host: localhost:8080

{
  "name" : "New",
  "email" : "new@gmail.com",
  "registered" : "2020-12-23T17:15:37.55",
  "enabled" : false,
  "roles" : [ "USER" ],
  "password" : "newPass"
}
```

HTTP Response

```
HTTP/1.1 201 Created
Location: http://localhost:8080/rest/admin/users/3
Content-Type: application/json;charset=UTF-8
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
Content-Length: 157
```

```
{
  "id" : 3,
  "name" : "New",
  "email" : "new@gmail.com",
  "registered" : "2020-12-23T17:15:37.562",
  "enabled" : false,
  "roles" : [ "USER" ]
}
```

Table 18. Request fields

Path	Type	Optional	Description	Constraints
id	Number	false	User id	[Must not be blank, Size must be between 2 and 100 inclusive]
name	String	false	User name	[Must not be blank, Size must be between 2 and 100 inclusive]
email	String	false	User email	[Must be a well-formed email address, Size must be between 0 and 100 inclusive]
registered	String	false	User registration date/time	[Must not be null]
enabled	Boolean	false	User activity marker	[]
roles.[]	Array	false	User roles	[]

examples

Curl

```
$ curl 'http://localhost:8080/rest/admin/users/' -i -u  
'admin@gmail.com:admin' -X PUT \  
  -H 'Content-Type: application/json;charset=UTF-8' \  
  -d '{  
    "id" : 0,  
    "name" : "UpdatedName",  
    "email" : "update@gmail.com",  
    "registered" : "2020-12-23T17:15:36.919",  
    "enabled" : false,  
    "roles" : [ "ADMIN" ]  
  }'
```

HTTP Request

```
PUT /rest/admin/users/ HTTP/1.1  
Content-Type: application/json;charset=UTF-8  
Content-Length: 169  
Authorization: Basic YWRtaW5AZ21haWwuY29tOmFkbWlu  
Host: localhost:8080  
  
{  
  "id" : 0,  
  "name" : "UpdatedName",  
  "email" : "update@gmail.com",  
  "registered" : "2020-12-23T17:15:36.919",  
  "enabled" : false,  
  "roles" : [ "ADMIN" ]  
}
```

HTTP Response

```
HTTP/1.1 204 No Content  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff
```

PATCH /rest/admin/users/{id} Set enable

Table 19. /rest/admin/users/{id}

Parameter	Description
id	User id

Table 20. Request parameters

Parameter	Optional	Description
enabled	false	User activity marker

examples

Curl

```
$ curl 'http://localhost:8080/rest/admin/users/0' -i -u  
'admin@gmail.com:admin' -X PATCH \  
-H 'Content-Type: application/json;charset=UTF-8'
```

HTTP Request

```
PATCH /rest/admin/users/0 HTTP/1.1  
Content-Type: application/json;charset=UTF-8  
Authorization: Basic YWRtaW5AZ21haWwuY29tOmFkbWlu  
Host: localhost:8080
```

Success HTTP Response

```
HTTP/1.1 204 No Content  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff
```

Error HTTP Responses

Enable not found

```
HTTP/1.1 422 Unprocessable Entity  
Content-Type: application/json;charset=UTF-8  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff  
Content-Length: 191  
  
{  
  "url" : "http://localhost:8080/rest/admin/users/10",  
  "type" : "DATA_NOT_FOUND",  
  "detail" : "edu.volkov.restmanager.util.exception.NotFoundException: Not  
found entity with id=10"  
}
```

DELETE **/rest/admin/users/{id}** *Delete*

Table 21. /rest/admin/users/{id}

Parameter	Description
id	User id

examples

Curl

```
$ curl 'http://localhost:8080/rest/admin/users/0' -i -u  
'admin@gmail.com:admin' -X DELETE
```

HTTP Request

```
DELETE /rest/admin/users/0 HTTP/1.1  
Authorization: Basic YWRtaW5AZ21haWwuY29tOmFkbWlu  
Host: localhost:8080
```

Success HTTP Response

```
HTTP/1.1 204 No Content  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff
```

Error HTTP Responses

Delete not found

```
HTTP/1.1 422 Unprocessable Entity  
Content-Type: application/json;charset=UTF-8  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff  
Content-Length: 191  
  
{  
  "url" : "http://localhost:8080/rest/admin/users/10",  
  "type" : "DATA_NOT_FOUND",  
  "detail" : "edu.volkov.restmanager.util.exception.NotFoundException: Not  
found entity with id=10"  
}
```

1.3.2. Restaurant

Table 22. Response fields

Path	Type	Description
[]	Array	Restaurants
[][.id]	Number	Restaurant id
[][.name]	String	Restaurant name
[][.address]	String	Restaurant address
[][.phone]	String	Restaurant phone
[][.votesQuantity]	Number	Restaurant votes quantity
[][.enabled]	Boolean	Restaurant activity marker
[][.menus]	Array	Restaurant menus
[][.menus][.id]	Number	Menu id
[][.menus][.name]	String	Menu name
[][.menus][.menuDate]	String	Menu date
[][.menus][.enabled]	Boolean	Menu activity marker
[][.menus][.menuItems]	Array	Menu dishes
[][.menus][.menuItems][.id]	Number	Dish id
[][.menus][.menuItems][.name]	String	Dish name
[][.menus][.menuItems][.price]	Number	Dish price

Curl

```
$ curl 'http://localhost:8080/rest/admin/restaurants/' -i -u  
'admin@gmail.com:admin' -X GET
```

HTTP Request

```
GET /rest/admin/restaurants/ HTTP/1.1  
Authorization: Basic YWRtaW5AZ21haWwuY29tOmFkbWlu  
Host: localhost:8080
```

HTTP Response

```
HTTP/1.1 200 OK  
Content-Type: application/json;charset=UTF-8  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff  
Content-Length: 1030
```

```
[ {  
  "id" : 0,  
  "name" : "rest1",  
  "address" : "address1",  
  "phone" : "+7 (911) 111-1111",  
  "enabled" : true,  
  "votesQuantity" : 4,  
  "menus" : [ {  
    "id" : 1,  
    "name" : "menu2",  
    "menuDate" : "2020-01-27",  
    "enabled" : true,  
    "menuItems" : [ {  
      "id" : 3,  
      "name" : "menItm4",  
      "price" : 103  
    }, {  
      "id" : 4,  
      "name" : "menItm5",  
      "price" : 104  
    }, {  
      "id" : 5,  
      "name" : "menItm6",  
      "price" : 105  
    }  
  ]  
}
```

```
} ]  
, {  
  "id" : 1,  
  "name" : "rest2",  
  "address" : "address2",  
  "phone" : "+7 (922) 222-2222",  
  "enabled" : false,  
  "votesQuantity" : 4,  
  "menus" : [ {  
    "id" : 3,  
    "name" : "menu4",  
    "menuDate" : "2020-01-27",  
    "enabled" : true,  
    "menuItems" : [ {  
      "id" : 9,  
      "name" : "menItm10",  
      "price" : 109  
    }, {  
      "id" : 10,  
      "name" : "menItm11",  
      "price" : 1010  
    }, {  
      "id" : 11,  
      "name" : "menItm12",  
      "price" : 1011  
    } ]  
  } ]  
} ]  
} ]
```

GET **/rest/admin/restaurants/{id}** Get one without menu

Table 23. /rest/admin/restaurants/{id}

Parameter	Description
id	Restaurant id

Table 24. Response fields

Path	Type	Description
id	Number	Restaurant id
name	String	Restaurant name
address	String	Restaurant address
phone	String	Restaurant phone
votesQuantity	Number	Restaurant votes quantity
enabled	Boolean	Restaurant activity marker
menus	Null	Restaurant menus

examples

Curl

```
$ curl 'http://localhost:8080/rest/admin/restaurants/0' -i -u  
'admin@gmail.com:admin' -X GET
```

HTTP Request

```
GET /rest/admin/restaurants/0 HTTP/1.1  
Authorization: Basic YWRtaW5AZ21haWwuY29tOmFkbWlu  
Host: localhost:8080
```

Success HTTP Response

```
HTTP/1.1 200 OK  
Content-Type: application/json;charset=UTF-8  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff  
Content-Length: 162  
  
{  
  "id" : 0,  
  "name" : "rest1",  
  "address" : "address1",  
  "phone" : "+7 (911) 111-1111",  
  "enabled" : true,  
  "votesQuantity" : 4,  
  "menus" : null  
}
```

Error HTTP Responses

Get not found

```
HTTP/1.1 422 Unprocessable Entity
Content-Type: application/json;charset=UTF-8
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
Content-Length: 225

{
  "url" : "http://localhost:8080/rest/admin/restaurants/10",
  "type" : "DATA_NOT_FOUND",
  "detail" : "edu.volkov.restmanager.util.exception.NotFoundException: Not
found entity with restaurant by id: 10dos not exist"
}
```

Get by unauthorized user

```
HTTP/1.1 401 Unauthorized
WWW-Authenticate: Basic realm="Realm"
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
```

Get by forbidden user

```
HTTP/1.1 403 Forbidden
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
```




Keep in mind:

- Empty request parameters = getAll.

Table 25. Request parameters

Parameter	Optional	Description
name	false	Restaurant name
address	false	Restaurant address
enabled	false	Restaurant activity marker

Table 26. Response fields

Path	Type	Description
<code>[]</code>	Array	Restaurants
<code>[][.id]</code>	Number	Restaurant id
<code>[][.name]</code>	String	Restaurant name
<code>[][.address]</code>	String	Restaurant address
<code>[][.phone]</code>	String	Restaurant phone
<code>[][.votesQuantity]</code>	Number	Restaurant votes quantity
<code>[][.enabled]</code>	Boolean	Restaurant activity marker
<code>[][.menus]</code>	Array	Restaurant menus
<code>[][.menus][.id]</code>	Number	Menu id
<code>[][.menus][.name]</code>	String	Menu name
<code>[][.menus][.menuDate]</code>	String	Menu date
<code>[][.menus][.enabled]</code>	Boolean	Menu activity marker
<code>[][.menus][.menuItems]</code>	Array	Menu dishes
<code>[][.menus][.menuItems][.id]</code>	Number	Dish id
<code>[][.menus][.menuItems][.name]</code>	String	Dish name
<code>[][.menus][.menuItems][.price]</code>	Number	Dish price

examples

Curl

```
$ curl  
'http://localhost:8080/rest/admin/restaurants/filter/?name=rest1&address=address1&enabled=&enabled=' -i -u 'admin@gmail.com:admin' -X GET
```

HTTP Request

```
GET  
/rest/admin/restaurants/filter/?name=rest1&address=address1&enabled=&enabled=  
HTTP/1.1  
Authorization: Basic YWRtaW5AZ21haWwY29tOmFkbWlu  
Host: localhost:8080
```

HTTP Response

```
HTTP/1.1 200 OK
Content-Type: application/json;charset=UTF-8
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
Content-Length: 512
```

```
[ {
  "id" : 0,
  "name" : "rest1",
  "address" : "address1",
  "phone" : "+7 (911) 111-1111",
  "enabled" : true,
  "votesQuantity" : 4,
  "menus" : [ {
    "id" : 1,
    "name" : "menu2",
    "menuDate" : "2020-01-27",
    "enabled" : true,
    "menuItems" : [ {
      "id" : 3,
      "name" : "menItm4",
      "price" : 103
    }, {
      "id" : 4,
      "name" : "menItm5",
      "price" : 104
    }, {
      "id" : 5,
      "name" : "menItm6",
      "price" : 105
    } ]
  } ]
} ]
```

Table 27. Request fields

Path	Type	Optional	Description	Constraints
name	String	false	Restaurant name	[Must not be blank, Size must be between 2 and 100 inclusive]
address	String	false	Restaurant address	[Must not be blank, Size must be between 5 and 200 inclusive]
phone	String	false	Restaurant phone	[Must match the regular expression <code>^\+(\d{1})()?(\d{3})</code>]
<code>\d{3}}[-.]?\d{3}[-.]?\d{4}\$`</code> , Must not be blank, Size must be between 0 and 20 inclusive]	enabled	Boolean	false	Restaurant activity marker
[]	votesQuantity	Number	true	Restaurant phone
[]	menus	Array	true	Restaurant phone

Table 28. Response fields

Path	Type	Description
id	Number	Restaurant id
name	String	Restaurant name
address	String	Restaurant address
phone	String	Restaurant phone
votesQuantity	Number	Restaurant votes quantity
enabled	Boolean	Restaurant activity marker
menus	Array	Restaurant menus

examples

Curl

```
$ curl 'http://localhost:8080/rest/admin/restaurants/' -i -u
'admin@gmail.com:admin' -X POST \
  -H 'Content-Type: application/json; charset=UTF-8' \
  -d '{
    "name" : "newRestaurant",
    "address" : "newAddress",
    "phone" : "+7 (977) 777-7777",
    "enabled" : false,
    "votesQuantity" : 0,
    "menus" : [ ]
  }'
```

HTTP Request

```
POST /rest/admin/restaurants/ HTTP/1.1
Content-Type: application/json; charset=UTF-8
Content-Length: 159
Authorization: Basic YWRtaW5AZ21haWwuY29tOmFkbWlu
Host: localhost:8080

{
  "name" : "newRestaurant",
  "address" : "newAddress",
  "phone" : "+7 (977) 777-7777",
  "enabled" : false,
  "votesQuantity" : 0,
  "menus" : [ ]
}
```

HTTP Response

```
HTTP/1.1 201 Created
Location: http://localhost:8080/rest/admin/restaurants/2
Content-Type: application/json;charset=UTF-8
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
Content-Length: 172
```

```
{
  "id" : 2,
  "name" : "newRestaurant",
  "address" : "newAddress",
  "phone" : "+7 (977) 777-7777",
  "enabled" : false,
  "votesQuantity" : 0,
  "menus" : [ ]
}
```

Table 29. /rest/admin/restaurants/{id}

Parameter	Description
id	Restaurant id

Table 30. Request fields

Path	Type	Optional	Description	Constraints
id	Number	false	Restaurant id	[Must not be blank, Size must be between 2 and 100 inclusive]
name	String	false	Restaurant name	[Must not be blank, Size must be between 2 and 100 inclusive]
address	String	false	Restaurant address	[Must not be blank, Size must be between 5 and 200 inclusive]
phone	String	false	Restaurant phone	[Must be in format: +7 (777) 777-7777, Size must be between 0 and 20 inclusive]
enabled	Boolean	false	Restaurant activity marker	[Must not be null]

examples

Curl

```
$ curl 'http://localhost:8080/rest/admin/restaurants/0' -i -u
'admin@gmail.com:admin' -X PUT \
  -H 'Content-Type: application/json;charset=UTF-8' \
  -d '{
  "id" : 0,
  "name" : "updatedRestaurant",
  "address" : "updatedAddress",
  "phone" : "+7 (988) 888-8888",
  "enabled" : true
}'
```

HTTP Request

```
PUT /rest/admin/restaurants/0 HTTP/1.1
Content-Type: application/json;charset=UTF-8
Content-Length: 137
Authorization: Basic YWRtaW5AZ21haWwuY29tOmFkbWlu
Host: localhost:8080

{
  "id" : 0,
  "name" : "updatedRestaurant",
  "address" : "updatedAddress",
  "phone" : "+7 (988) 888-8888",
  "enabled" : true
}
```

HTTP Response

```
HTTP/1.1 204 No Content
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
```


Table 31. /rest/admin/restaurants/{id}

Parameter	Description
id	Restaurant id

Table 32. Request parameters

Parameter	Optional	Description
enabled	false	Restaurant activity marker

examples

Curl

```
$ curl 'http://localhost:8080/rest/admin/restaurants/0' -i -u  
'admin@gmail.com:admin' -X PATCH \  
-H 'Content-Type: application/json;charset=UTF-8'
```

HTTP Request

```
PATCH /rest/admin/restaurants/0 HTTP/1.1  
Content-Type: application/json;charset=UTF-8  
Authorization: Basic YWRtaW5AZ21haWwY29tOmFkbWlu  
Host: localhost:8080
```

HTTP Response

```
HTTP/1.1 204 No Content  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff
```

DELETE **/rest/admin/restaurants/{id}** *Delete*

Table 33. /rest/admin/restaurants/{id}

Parameter	Description
id	Restaurant id

examples

Curl

```
$ curl 'http://localhost:8080/rest/admin/restaurants/0' -i -u  
'admin@gmail.com:admin' -X DELETE
```

HTTP Request

```
DELETE /rest/admin/restaurants/0 HTTP/1.1  
Authorization: Basic YWRtaW5AZ21haWwuY29tOmFkbWlu  
Host: localhost:8080
```

Success HTTP Response

```
HTTP/1.1 204 No Content  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff
```

Error HTTP Responses

Delete not found

```
HTTP/1.1 422 Unprocessable Entity  
Content-Type: application/json;charset=UTF-8  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff  
Content-Length: 197  
  
{  
  "url" : "http://localhost:8080/rest/admin/restaurants/10",  
  "type" : "DATA_NOT_FOUND",  
  "detail" : "edu.volkov.restmanager.util.exception.NotFoundException: Not  
found entity with id=10"  
}
```

1.3.3. Menu

GET **/rest/admin/menus/{restId}** Get all for one restaurant

Table 34. /rest/admin/menus/{restId}

Parameter	Description
restId	Restaurant id

Table 35. Response fields

Path	Type	Description
[]	Array	Menus
[][.id]	Number	Menu id
[][.name]	String	Menu name
[][.menuDate]	String	Menu date
[][.enabled]	Boolean	Menu activity marker
[][.menuItems]	Array	Menu dishes
[][.menuItems][.id]	Number	Dish id
[][.menuItems][.name]	String	Dish name
[][.menuItems][.price]	Number	Dish price

Curl

```
$ curl 'http://localhost:8080/rest/admin/menus/0' -i -u  
'admin@gmail.com:admin' -X GET
```

HTTP Request

```
GET /rest/admin/menus/0 HTTP/1.1  
Authorization: Basic YWRtaW5AZ21haWwuY29tOmFkbWlu  
Host: localhost:8080
```

HTTP Response

```
HTTP/1.1 200 OK  
Content-Type: application/json;charset=UTF-8  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff  
Content-Length: 939
```

```
[ {  
  "id" : 2,  
  "name" : "menu3",  
  "menuDate" : "2020-01-28",  
  "enabled" : true,  
  "menuItems" : [ {  
    "id" : 6,  
    "name" : "menItm7",  
    "price" : 106  
  }, {  
    "id" : 7,  
    "name" : "menItm8",  
    "price" : 107  
  }, {  
    "id" : 8,  
    "name" : "menItm9",  
    "price" : 108  
  } ]  
}, {  
  "id" : 0,  
  "name" : "menu1",  
  "menuDate" : "2020-01-27",  
  "enabled" : false,  
  "menuItems" : [ {  
    "id" : 0,
```

```
    "name" : "menItm1",
    "price" : 100
  }, {
    "id" : 1,
    "name" : "menItm2",
    "price" : 101
  }, {
    "id" : 2,
    "name" : "menItm3",
    "price" : 102
  } ]
}, {
  "id" : 1,
  "name" : "menu2",
  "menuDate" : "2020-01-27",
  "enabled" : true,
  "menuItems" : [ {
    "id" : 3,
    "name" : "menItm4",
    "price" : 103
  }, {
    "id" : 4,
    "name" : "menItm5",
    "price" : 104
  }, {
    "id" : 5,
    "name" : "menItm6",
    "price" : 105
  } ]
} ]
```



Keep in mind:

- Filtering by dates includes left and right borders.
- Empty request parameters = getAll.

Table 36. **/rest/admin/menus/filter/{restId}**

Parameter	Description
restId	Restaurant id

Table 37. Request parameters

Parameter	Optional	Description
startDate	false	Start date
endDate	false	End date
enabled	false	Menu activity marker

Table 38. Response fields

Path	Type	Description
[]	Array	Menus
[][.id]	Number	Menu id
[][.name]	String	Menu name
[][.menuDate]	String	Menu date
[][.enabled]	Boolean	Menu activity marker
[][.menuItems]	Array	Menu dishes
[][.menuItems][.id]	Number	Dish id
[][.menuItems][.name]	String	Dish name
[][.menuItems][.price]	Number	Dish price

examples

Curl

```
$ curl  
'http://localhost:8080/rest/admin/menus/filter/0?startDate=&endDate=&enabled=  
&startDate=&endDate=&enabled=' -i -u 'admin@gmail.com:admin' -X GET
```

HTTP Request

```
GET  
/rest/admin/menus/filter/0?startDate=&endDate=&enabled=&startDate=&endDate=&e  
nabled= HTTP/1.1  
Authorization: Basic YWRtaW5AZ21haWwY29tOmFkbWlu  
Host: localhost:8080
```

HTTP Response

```
HTTP/1.1 200 OK  
Content-Type: application/json;charset=UTF-8  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff  
Content-Length: 939
```

```
[ {  
  "id" : 2,  
  "name" : "menu3",  
  "menuDate" : "2020-01-28",  
  "enabled" : true,  
  "menuItems" : [ {  
    "id" : 6,  
    "name" : "menItm7",  
    "price" : 106  
  }, {  
    "id" : 7,  
    "name" : "menItm8",  
    "price" : 107  
  }, {  
    "id" : 8,  
    "name" : "menItm9",  
    "price" : 108  
  } ]  
}, {  
  "id" : 0,  
  "name" : "menu1",  
  "menuDate" : "2020-01-27",
```

```
"enabled" : false,
"menuItems" : [ {
  "id" : 0,
  "name" : "menItm1",
  "price" : 100
}, {
  "id" : 1,
  "name" : "menItm2",
  "price" : 101
}, {
  "id" : 2,
  "name" : "menItm3",
  "price" : 102
} ]
}, {
  "id" : 1,
  "name" : "menu2",
  "menuDate" : "2020-01-27",
  "enabled" : true,
  "menuItems" : [ {
    "id" : 3,
    "name" : "menItm4",
    "price" : 103
  }, {
    "id" : 4,
    "name" : "menItm5",
    "price" : 104
  }, {
    "id" : 5,
    "name" : "menItm6",
    "price" : 105
  } ]
} ]
```

Table 39. /rest/admin/menus/{restId}/{id}

Parameter	Description
restId	Restaurant id
id	Menu id

Table 40. Response fields

Path	Type	Description
id	Number	Menu id
name	String	Menu name
menuDate	String	Menu date
enabled	Boolean	Menu activity marker
menuItems	Array	Menu dishes
menuItems[].id	Number	Dish id
menuItems[].name	String	Dish name
menuItems[].price	Number	Dish price

examples

Curl

```
$ curl 'http://localhost:8080/rest/admin/menus/0/0' -i -u  
'admin@gmail.com:admin' -X GET
```

HTTP Request

```
GET /rest/admin/restaurants/0 HTTP/1.1  
Authorization: Basic YWRtaW5AZ21haWwuY29tOmFkbWlu  
Host: localhost:8080
```

Success HTTP Response

```
HTTP/1.1 200 OK  
Content-Type: application/json;charset=UTF-8  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff  
Content-Length: 162  
  
{  
  "id" : 0,  
  "name" : "rest1",  
  "address" : "address1",  
  "phone" : "+7 (911) 111-1111",  
  "enabled" : true,  
  "votesQuantity" : 4,  
  "menus" : null  
}
```

Error HTTP Responses

Get not found

```
HTTP/1.1 422 Unprocessable Entity
Content-Type: application/json;charset=UTF-8
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
Content-Length: 225

{
  "url" : "http://localhost:8080/rest/admin/restaurants/10",
  "type" : "DATA_NOT_FOUND",
  "detail" : "edu.volkov.restmanager.util.exception.NotFoundException: Not
found entity with restaurant by id: 10dos not exist"
}
```

Get by unauthorized user

```
HTTP/1.1 401 Unauthorized
WWW-Authenticate: Basic realm="Realm"
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
```

Get by forbidden user

```
HTTP/1.1 403 Forbidden
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
```

Table 41. /rest/admin/menus/{restId}

Parameter	Description
restId	Restaurant id

Table 42. Request fields

Path	Type	Optional	Description	Constraints
name	String	false	Menu name	[Must not be blank, Size must be between 2 and 100 inclusive]
menuDate	String	false	Menu date	[Must not be null]
enabled	Boolean	false	Menu activity marker	[Must not be null]
menuItems	Array	false	Menu dishes	[Must not be null]
menuItems[].id	Number	true	Dish id	[]
menuItems[].name	String	true	Dish name	[Must not be blank, Size must be between 2 and 100 inclusive]
menuItems[].price	Number	true	Dish price	[Must be at least 0, Must not be null]

Table 43. Response fields

Path	Type	Description
id	Number	Menu id
name	String	Menu name
menuDate	String	Menu date
enabled	Boolean	Menu activity marker
menuItems	Array	Menu dishes
menuItems[].id	Number	Dish id
menuItems[].name	String	Dish name
menuItems[].price	Number	Dish price

Curl

```
$ curl 'http://localhost:8080/rest/admin/menus/0' -i -u
'admin@gmail.com:admin' -X POST \
-H 'Content-Type: application/json;charset=UTF-8' \
-d '{
  "name" : "newMenu",
  "menuDate" : "2020-01-28",
  "enabled" : false,
  "menuItems" : [ {
    "id" : 0,
    "name" : "menItm1",
    "price" : 100
  }, {
    "id" : 1,
    "name" : "menItm2",
    "price" : 101
  }, {
    "id" : 2,
    "name" : "menItm3",
    "price" : 102
  } ]
}'
```

HTTP Request

```
POST /rest/admin/menus/0 HTTP/1.1
Content-Type: application/json;charset=UTF-8
Content-Length: 300
Authorization: Basic YWRtaW5AZ21haWwuY29tOmFkbWlu
Host: localhost:8080
```

```
{
  "name" : "newMenu",
  "menuDate" : "2020-01-28",
  "enabled" : false,
  "menuItems" : [ {
    "id" : 0,
    "name" : "menItm1",
    "price" : 100
  }, {
    "id" : 1,
    "name" : "menItm2",
    "price" : 101
  }, {
    "id" : 2,
    "name" : "menItm3",
    "price" : 102
  } ]
}
```


HTTP Response

```
HTTP/1.1 201 Created
Location: http://localhost:8080/rest/admin/menus/6
Content-Type: application/json;charset=UTF-8
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
Content-Length: 313
```

```
{
  "id" : 6,
  "name" : "newMenu",
  "menuDate" : "2020-01-28",
  "enabled" : false,
  "menuItems" : [ {
    "id" : 0,
    "name" : "menItm1",
    "price" : 100
  }, {
    "id" : 1,
    "name" : "menItm2",
    "price" : 101
  }, {
    "id" : 2,
    "name" : "menItm3",
    "price" : 102
  } ]
}
```

Table 44. /rest/admin/menus/{restId}/{id}

Parameter	Description
restId	Restaurant id
id	Menu id

Table 45. Request fields

Path	Type	Optional	Description	Constraints
id	Number	false	Menu id	[Must not be blank, Size must be between 2 and 100 inclusive]
name	String	false	Menu name	[Must not be blank, Size must be between 2 and 100 inclusive]
menuDate	String	false	Menu date	[Must not be null]
enabled	Boolean	false	Menu activity marker	[Must not be null]
menuItemTos	Array	false	Menu dishes	[Must not be null]
menuItemTos[].id	Number	true	Dish id	[]
menuItemTos[].name	String	true	Dish name	[Must not be blank, Size must be between 2 and 100 inclusive]
menuItemTos[].price	Number	true	Dish price	[Must be at least 0, Must not be null]

Curl

```
$ curl 'http://localhost:8080/rest/admin/menus/0/0' -i -u
'admin@gmail.com:admin' -X PUT \
  -H 'Content-Type: application/json;charset=UTF-8' \
  -d '{
    "id" : 0,
    "name" : "updatedName",
    "menuDate" : "2020-01-28",
    "enabled" : false,
    "menuItemTos" : [ {
      "id" : 18,
      "name" : "updatedMenuItem1",
      "price" : 7777
    }, {
      "id" : 19,
      "name" : "updatedMenuItem2",
      "price" : 8888
    }, {
      "id" : 20,
      "name" : "updatedMenuItem3",
      "price" : 9999
    } ]
  }'
```

HTTP Request

```
PUT /rest/admin/menus/0/0 HTTP/1.1
Content-Type: application/json;charset=UTF-8
Content-Length: 352
Authorization: Basic YWRtaW5AZ21haWwuY29tOmFkbWlu
Host: localhost:8080
```

```
{
  "id" : 0,
  "name" : "updatedName",
  "menuDate" : "2020-01-28",
  "enabled" : false,
  "menuItemTos" : [ {
    "id" : 18,
    "name" : "updatedMenuItem1",
    "price" : 7777
  }, {
    "id" : 19,
    "name" : "updatedMenuItem2",
    "price" : 8888
  }, {
    "id" : 20,
    "name" : "updatedMenuItem3",
    "price" : 9999
  } ]
}
```

Success HTTP Response

```
HTTP/1.1 204 No Content
Cache-Control: no-cache, no-store, max-age=0, must-revalidate
Pragma: no-cache
Expires: 0
X-XSS-Protection: 1; mode=block
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
```

PATCH **/rest/admin/menus/{restId}/{id}** Set enable

Table 46. /rest/admin/menus/{restId}/{id}

Parameter	Description
restId	Restaurant id
id	Menu id

Table 47. Request parameters

Parameter	Optional	Description
enabled	false	Menu activity marker

examples

Curl

```
$ curl 'http://localhost:8080/rest/admin/menus/0/0' -i -u  
'admin@gmail.com:admin' -X PATCH \  
-H 'Content-Type: application/json;charset=UTF-8'
```

HTTP Request

```
PATCH /rest/admin/menus/0/0 HTTP/1.1  
Content-Type: application/json;charset=UTF-8  
Authorization: Basic YWRtaW5AZ21haWwuY29tOmFkbWlu  
Host: localhost:8080
```

Success HTTP Response

```
HTTP/1.1 204 No Content  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff
```

Error HTTP Responses

Enable not found

```
HTTP/1.1 422 Unprocessable Entity  
Content-Type: application/json;charset=UTF-8  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff  
Content-Length: 230  
  
{  
  "url" : "http://localhost:8080/rest/admin/menus/0/15",  
  "type" : "DATA_NOT_FOUND",  
  "detail" : "edu.volkov.restmanager.util.exception.NotFoundException: Not  
found entity with menu by id: 15 for restId: 0 dos not exist"  
}
```

DELETE **/rest/admin/menus/{restId}/{id}** Delete

Table 48. /rest/admin/menus/{restId}/{id}

Parameter	Description
restId	Restaurant id
id	Menu id

examples

Curl

```
$ curl 'http://localhost:8080/rest/admin/menus/0/0' -i -u  
'admin@gmail.com:admin' -X DELETE
```

HTTP Request

```
DELETE /rest/admin/menus/0/0 HTTP/1.1  
Authorization: Basic YWRtaW5AZ21haWwuY29tOmFkbWlu  
Host: localhost:8080
```

Success HTTP Response

```
HTTP/1.1 204 No Content  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff
```

Error HTTP Responses

Delete not found

```
HTTP/1.1 422 Unprocessable Entity  
Content-Type: application/json;charset=UTF-8  
Cache-Control: no-cache, no-store, max-age=0, must-revalidate  
Pragma: no-cache  
Expires: 0  
X-XSS-Protection: 1; mode=block  
X-Frame-Options: DENY  
X-Content-Type-Options: nosniff  
Content-Length: 192  
  
{  
  "url" : "http://localhost:8080/rest/admin/menus/0/15",  
  "type" : "DATA_NOT_FOUND",  
  "detail" : "edu.volkov.restmanager.util.exception.NotFoundException: Not  
found entity with id=0"  
}
```


2. Convention

2.1. HTTP verbs

Restaurant Manager tries to adhere as closely as possible to standard HTTP and REST conventions in its use of HTTP verbs.

Verb	Usage
GET	Used to retrieve a resource
POST	Used to create a new resource
PATCH	Used to update an existing resource, including partial updates
PUT	Used to update an existing resource, full updates only
DELETE	Used to delete an existing resource

2.2. HTTP status codes

Restaurant Manager tries to adhere as closely as possible to standard HTTP and REST conventions in its use of HTTP status codes.

Status code	Usage
200 OK	Standard response for successful HTTP requests. The actual response will depend on the request method used. In a GET request, the response will contain an entity corresponding to the requested resource. In a POST request, the response will contain an entity describing or containing the result of the action.
201 Created	The request has been fulfilled and resulted in a new resource being created.
204 No Content	The server successfully processed the request, but is not returning any content.

Status code	Usage
400 Bad Request	The server cannot or will not process the request due to something that is perceived to be a client error (e.g., malformed request syntax, invalid request message framing, or deceptive request routing).
404 Not Found	The requested resource could not be found but may be available again in the future. Subsequent requests by the client are permissible.
409 Conflict	The request could not be completed due to a conflict with the current state of the target resource.
422 Unprocessable Entity	Validation error has happened due to processing the posted entity.

3. Error processing

Table 49. Error response body parameters

Path	Type	Description
url	String	Request url
type	String	Error type
detail	String	Error details