

Machine learning in action

P Harrington - 2012 - library02.embl.de

... Bayes 65 4.5 Classifying text with Python 67 Prepare: making **word vectors** from text 67 • Train: calculating probabilities from **word vectors** 69 • Test ... 6.5 Using kernels for more complex data 118 Mapping data to higher dimensions with kernels 118 • The radial **bias** function as a ...

☆ [🔗](#) Cited by 402 Related articles All 7 versions [🔗](#)

Measuring self-focus **bias** in community-maintained knowledge repositories

B Hecht, D Gergle - [Proceedings of the fourth international conference ...](http://proceedings.of.the.fourth.international.conference....), 2009 - dl.acm.org

... Wikipedia's home countries' delegations, suggesting yet more interesting uses of indegree and PageRank sums as proxies for self-focus **bias** ... Even though this study utilized the article network (WAG), other structures of Wikipedia – such as article **word vectors** and the category ...

☆ [🔗](#) Cited by 79 Related articles All 19 versions

Context-dependent **word** representation for neural machine translation

H Choi, K Cho, Y Bengio - [Computer Speech & Language](http://computer.speech.and.language), 2017 - Elsevier

... Then, we compute a context mask from $c \times$ for each **word** embedding vector before it is fed into an input or output recurrent network ... context to a binary-like mask (ie, a real number between 0 and 1), with $W \times$ and $W \times$ (weight matrices), $b \times$ and $b \times$ (**bias vectors**) being additional ...

☆ [🔗](#) Cited by 40 Related articles All 5 versions

Effective training of a neural network character classifier for **word** recognition

LS Yaeger, RF Lyon, BJ Webb - [Advances in neural information ...](http://advances.in.neural.information....), 1997 - papers.nips.cc

... This result<; in erratic **word** recognition failures as the net fails to accurately represent the legitimate ambiguity between characters ... 0" relative to the "pressure towards 1" as seen at the output unit", and thus reducing the large **bias** towards 0 in target **vectors**, might pennit the ...

☆ [🔗](#) Cited by 63 Related articles All 12 versions [🔗](#)

A critique of **word** similarity as a method for evaluating distributional semantic models

M Batchkarov, T Kober, J Reffin, J Weeds... - [Proceedings of the 1st ...](http://proceedings.of.the.1st....), 2016 - sro.sussex.ac.uk

... high-similarity **word** pairs. However, individual judges exhibit a **bias** towards similarity scores in the middle of the spectrum ... One method of reliably generating poor **word vectors** is to start with a distributional model and decrease its quality by adding random noise. The evalua ...

☆ [🔗](#) Cited by 29 Related articles All 12 versions [🔗](#)

Fine-grained opinion mining with recurrent neural networks and **word** embeddings

P Liu, S Joty, H Meng - [Proceedings of the 2015 Conference on ...](http://proceedings.of.the.2015.conference.on....), 2015 - aclweb.org

... con- secutive cell activations, respectively, which are associated with gate k (ie, input, output, forget and cell), and b_k is the associated **bias** vector ... two **vectors** ... In our example sentence (Table 1), to correctly tag the **word** hard as a B-TARG, it is beneficial for the RNN to know that ...

☆ [🔗](#) Cited by 122 Related articles All 11 versions [🔗](#)

Recursive deep models for semantic compositionality over a sentiment treebank

R Socher, A Perelygin, J Wu, J Chuang... - [Proceedings of the ...](http://proceedings.of.the....), 2013 - aclweb.org

... The **bias** can be added as an extra column to W if an additional 1 is added to the concatenation of the input **vectors** ... Sim- ilar to the random **word vectors**, the parameters of these matrices will be trained to minimize the clas- sification error at each node ...

☆ [🔗](#) Cited by 2682 Related articles All 17 versions [🔗](#)

Deep learning

Y LeCun, Y Bengio, G Hinton - nature, 2015 - nature.com

... multiplication by the product of $\partial y / \partial x$ and $\partial z / \partial x$. It also works when x , y and z are **vectors** (and the ... For simplicity, we have omitted **bias** terms ... location in the input image (middle and bottom; the lighter patches were given more attention) as it generates each **word** (bold), we ...

☆ [🔗](#) Cited by 14232 Related articles All 54 versions

Gaussian lda for topic models with **word** embeddings

R Das, M Zaheer, C Dyer - [Proceedings of the 53rd Annual Meeting of ...](http://proceedings.of.the.53rd.annual.meeting.of....), 2015 - aclweb.org

... While this model can in principle handle unseen words, the only **bias** toward being included in a particular topic comes from the topic ... This has given rise to data-driven learning of **word vectors** that capture lexical and semantic properties, which is now a technique of central ...

☆ [🔗](#) Cited by 141 Related articles All 10 versions [🔗](#)

Prior disambiguation of **word** tensors for constructing sentence **vectors**

D Kartsaklis, M Sadrzadeh - [Proceedings of the 2013 Conference on ...](#), 2013 - [aclweb.org](#)

... In practice, the **bias** \rightarrow b is embedded in adj 2 , hence the above procedure provides us with ...

The context here is a 5-**word** window on both sides of the target **word**. The **vectors** are disambiguated both syntactically and semantically: first, separate **vectors** have been created for ...

☆  Cited by 49 [Related articles](#) [All 15 versions](#) 