

# New consultation

uae\_code\_en, smoke\_control\_and\_management\_systems1742045231307

Generated 2026-09-01T03:51:52.142Z

**PARTIALLY COMPLIANT**

**Evidence coverage** 93%

**Confidence** 45%

## Summary

Reviewed 60 requirements drawn from 1 regulation against 1 project document. 1 met, 4 not met, 55 awaiting evidence. 1.1 - Needs evidence: The project documents partially address 1.1 but do not evidence: area, included, civil, construction, defence, horizontal. 1.2.16 - Needs evidence: The project documents partially address 1.2.16 but do not evidence: certification, ej's, judgment, agency, body, considered. 2.10.12.10.1 - Needs evidence: The project documents partially address 2.10.12.10.1 but do not evidence: type, area, construction, height, structur, unlimited.

## Documents reviewed

- uae\_code\_en (v1.0, governing, 1348 pages)
- smoke\_control\_and\_management\_systems1742045231307 (v1.0, project, 12 pages)

## Assumptions and scope limits

- Only mandatory and prohibitive provisions were treated as testable requirements; recommendations ("should") were not scored as failures.
- This review covers the first 60 testable obligations found in the regulation. A further 494 were detected and NOT examined, so it is not a verdict on the document as a whole.
- uae\_code\_en carries no recorded effective date, so recency could not be weighted for it.

## Evidence matrix

### 1. 1.1 Construction

#### NEEDS EVIDENCE

The project documents partially address 1.1 but do not evidence: area, included, civil, construction, defence, horizontal.

uae\_code\_en (01M1AX15) - Ch. 1 - §1.1 - p. 24 - p. 24 - [verified]

"Building Area

The total area within surrounding exterior walls (or exterior walls and fire walls) exclusive of vent shafts and courts. Areas of the building not provided with surrounding walls shall be included in the building areas if such areas are included within the horizontal projection of the roof or floor above."

## 2. 1.2.16 Engineering Judgments (EJ's)

### NEEDS EVIDENCE

The project documents partially address 1.2.16 but do not evidence: certification, ej's, judgment, agency, body, considered.

uae\_code\_en (01M1AX15) - Ch. 1 - §1.2.16 - p. 30 - p. 30 - [verified]

"Engineering Judgment (EJ) shall be issued essentially by the original testing laboratory/Certification body that listed the system or registered Fire Consultant, Fire Protection Engineer, or an independent certification agency that provides certification services for such systems."

---

## 3. 2.10.12.10.1 Heights and floor areas of 'open parking structures' of Type

### NEEDS EVIDENCE

The project documents partially address 2.10.12.10.1 but do not evidence: type, area, construction, height, structur, unlimited.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.10.12.10.1 - p. 65 - p. 65 - [verified]

"Heights and floor areas of 'open parking structures' of Type I (442 or 332), Type II (222), or Type II (111) construction shall be permitted to be unlimited."

---

## 4. Ch. 2 Hour

### NEEDS EVIDENCE

The project documents partially address Ch. 2 but do not evidence: command, emergency, accessway, along, bms, control.

uae\_code\_en (01M1AX15) - Ch. 2 - p. 73 - p. 73 - [verified]

"iii. Emergency Command Center shall be located at the entrance side of the building and along fire accessway.  
iv. Emergency Command Center shall be permitted to be utilized as building security, BMS, Facility management office or building control room."

---

## 5. Ch. 0 Hour

### NEEDS EVIDENCE

Evidence relating to Ch. 0 is inconsistent across the project documents, so a single verdict cannot be reached.

smoke\_control\_and\_management\_systems1742045231307 (01M1DH7W) - p. 2 - p. 2 - [verified]

"WATER  
TANK  
79.28 m<sup>2</sup>  
PUMP  
ROOM  
Openable  
panels  
water tank capacity 150 m<sup>3</sup>  
clear water column hi. 1.9 m  
clear void 400mm"

---

## 6. Ch. 5 GROUP C

### NEEDS EVIDENCE

The project documents partially address Ch. 5 but do not evidence: barrier, hour, resistance, achieve, area, compartment.

uae\_code\_en (01M1AX15) - Ch. 5 - p. 111 - p. 111 - [verified]

"ii. 1 Hour fire resistance rated smoke barrier corridor shall be provided.  
iii. 1 Hour fire resistance rated smoke barrier shall be provided for every floor exceeding 929 m2 and/or exceeding 465 m2 in area to achieve minimum of 2 smoke compartments.  
| CDGH-OP-25 | September 2018  
Page 111 of 1348"

---

### 7. 2.15.1.2 Fire dampers shall be designed and tested in accordance with

#### NEEDS EVIDENCE

The project documents partially address 2.15.1.2 but do not evidence: designed, tested.

smoke\_control\_and\_management\_systems1742045231307 (01M1DH7W) - p. 1 - p. 1 - [verified]

"FIRE DAMPER"

---

### 8. 2.15.1.3 Fire dampers shall be required in the following locations:

#### NON-COMPLIANT

2.15.1.3 specifies 30 min but the project document states 240 min.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.15.1.3 - p. 116 - p. 116 - [verified]

"c. Ducts and air-transfer openings penetrating floors that are required to have protected openings where the duct is not protected by a shaft enclosure.  
d. Air-transfer openings that occur in walls or partitions that are required to have a fire-resistive rating of 30 minutes or more."

---

### 9. 2.15.1.5 Fire dampers shall not be required in the following locations:

#### COMPLIANT

2.15.1.5 requires 120 min and the project document states 240 min, which satisfies it. Supporting text: "WITH MOTORIZED FIRE DAMPER EX.F-BAS-04 H/L L/L V.D EA.D30"X26" 7200 CFM EA.D,14"X12""

smoke\_control\_and\_management\_systems1742045231307 (01M1DH7W) - Ch. 900 - p. 3 - p. 3 - [verified]

"WITH MOTORIZED FIRE DAMPER  
EX.F-BAS-04  
H/L  
L/L  
V.D  
EA.D30"X26"  
7200 CFM  
EA.D,14"X12""

---

### 10. 2.16.6.3 Smoke dampers shall not be required in the following .

#### NEEDS EVIDENCE

The project documents partially address 2.16.6.3 but do not evidence: system, barrier, control, opening, penetrate, arranged.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.16.6.3 - p. 120 - p. 120 - [verified]

"Where ducts or air-transfer openings are part of an engineered smoke control system and the smoke damper will interfere with the operation of a smoke control system.  
b."

---

### 11. 2.17.2.2 From the finished floor level, Height of the

#### NON-COMPLIANT

2.17.2.2 specifies 1.20 m but the project document states 152.40 m.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.17.2.2 - p. 121 - p. 121 - [verified]

"From the finished floor level, Height of the balcony, terrace railings, elevated space railings (A), shall not be less than 1200 mm."

---

### 12. 2.17.3.1 Openable Windows shall open outward from the top. See Figure 1.17 b.

#### NEEDS EVIDENCE

The project documents partially address 2.17.3.1 but do not evidence: window, outward, see, top.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.17.3.1 - p. 123 - p. 123 - [verified]

"Openable Windows shall open outward from the top. See Figure 1.17 b.  
Openable windows shall not open from below."

---

### 13. 2.17.6.4 Each handrail or guard section shall be supported by a minimum of

#### NEEDS EVIDENCE

The project documents partially address 2.17.6.4 but do not evidence: baluster, guard, one, panel, supported, american.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.17.6.4 - p. 124 - p. 124 - [verified]

"b. The glass balusters shall be laminated glass with two or more glass plies of equal thickness and the same glass type, and each of the piles of the panels shall be designed to withstand the loads specified in ASCE (American Society of Civil Engineers) and any other structural requirements for a top rail."

---

### 14. 4.4.1.4 Curtainwall, Perimeter joints and fire stopping shall be a listed system.

#### NEEDS EVIDENCE

The project documents partially address 4.4.1.4 but do not evidence: curtainwall, listed, perimeter, stopping.

uae\_code\_en (01M1AX15) - Ch. 4 - §4.4.1.4 - p. 138 - p. 138 - [verified]

"Curtainwall, Perimeter joints and fire stopping shall be a listed system."

---

#### 15. 4.5.4.3 Cavity fire barrier shall be of Non combustible material, in accordance

##### NON-COMPLIANT

4.5.4.3 specifies 100 mm but the project document states 2.60 m.

uae\_code\_en (01M1AX15) - Ch. 4 - §4.5.4.3 - p. 142 - p. 142 - [verified]

"The cavity fire barrier shall be 100 mm high and, where the thermal insulation is not of equivalent fire resistance to the cavity barrier, shall run through insulation horizontally at each floor level and vertically on each face of façade as required by Section 4.5.4.2.  
| CDGH-OP-25 | September 2018  
Page 142 of 1348"

---

#### 16. 4.5.8.1 Architectural features shall comply to all the relevant requirements of Section 4.

##### NEEDS EVIDENCE

The project documents partially address 4.5.8.1 but do not evidence: featur.

smoke\_control\_and\_management\_systems1742045231307 (01M1DH7W) - p. 1 - p. 1 - [verified]

"ANY DISCREPANCIES BETWEEN ARCHITECTURAL, STRUCTURAL"

---

#### 17. 4.9.5.4 Thermal barrier shall not be required in masonry or concrete wall, floor or

##### NEEDS EVIDENCE

The project documents partially address 4.9.5.4 but do not evidence: masonry, barrier, construction, covered, face, panel.

uae\_code\_en (01M1AX15) - Ch. 4 - §4.9.5.4 - p. 162 - p. 162 - [verified]

"Thermal barrier shall not be required in masonry or concrete wall, floor or roof constructions where the sandwich panel is covered on each face by concrete or masonry with a minimum thickness of 25 mm."

---

#### 18. 4.10.2 GRP/GRFC and GRP systems may be used in a variety of building exterior envelope

##### NEEDS EVIDENCE

The project documents partially address 4.10.2 but do not evidence: grp, code, design, envelope, exterior, first.

uae\_code\_en (01M1AX15) - Ch. 4 - §4.10.2 - p. 169 - p. 169 - [verified]

"However Manufacturers, Consultants, Design Teams, Contractors and Testing laboratories must ensure that these systems comply in the first instance with the Reaction to Fire, Surface Spread of Flame and Resistance to Fire performance requirements and intent of the UAE Fire and Life Safety Code of Practice."

---

#### 19. 5.3 Glazing Testing and Acceptance

##### NEEDS EVIDENCE

The project documents partially address 5.3 but do not evidence: glazing, fire, acceptance, based, defence, general.

uae\_code\_en (01M1AX15) - Ch. 5 - §5.3 - p. 174 - p. 174 - [verified]

"Glazing Testing and Acceptance  
5.3.1.  
The requirement for fire rated glazing in any building shall be based on the Civil Defence approved Fire and Life Safety Drawings and strategy for the building, which identifies the following.  
a."

---

### 20. 5.4.1.3 In addition to the fire strategy Approved by Civil Defence, the following

#### NEEDS EVIDENCE

The project documents partially address 5.4.1.3 but do not evidence: glazing, application, civil, defence, edge, environment.

uae\_code\_en (01M1AX15) - Ch. 5 - §5.4.1.3 - p. 176 - p. 176 - [verified]

"Considerations for the glazing system design shall include but not be limited to the overall screen size, fenestration layout within the screen, materials used in construction of the profile (such as the gauge, quality, thickness, finish, etc.) and the amount of edge cover and edge clearance.  
i."

---

### 21. 2.4.1 Fire access Roadway Gate width shall be 4500 mm.

#### NEEDS EVIDENCE

The project documents partially address 2.4.1 but do not evidence: gate, roadway, width.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.4.1 - p. 206 - p. 206 - [verified]

"Fire access Roadway Gate width shall be 4500 mm."

---

### 22. 2.9.5 Fire Lift Lobby (Fire Man's Lift Lobby)

#### NON-COMPLIANT

2.9.5 specifies 90.00 m but the project document states 23.73 m.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.9.5 - p. 221 - p. 221 - [verified]

"Fire Lift Lobby (Fire Man's Lift Lobby)

a.

All Super highrise buildings (Having height greater than 90 m from the Fire access level) shall have "Fire Fighter's Lift Lobby" as per Chapter 1., Table 1.9.38. See"

---

### 23. 5.3.4 The Fire station functional areas shall include the following but not limited to,

#### NEEDS EVIDENCE

The project documents partially address 5.3.4 but do not evidence: administrative, apparatus, area, bedroom, control, enclosed.

uae\_code\_en (01M1AX15) - Ch. 5 - §5.3.4 - p. 233 - p. 233 - [verified]

"The Fire station functional areas shall include the following but not limited to,

- a. Control room
- b. Enclosed Fire Apparatus Parking
- c. Maintenance equipment/Store room.
- d. Administrative Office room
- e. Living room.
- f. Bedroom.
- g. Washroom with shower
- h. Locker room
- i. Kitchen
- j. Pump room
- k. Water Tank"

## **24. 2.2.7 No new construction shall be executed unless the building has been designed and approved as per Civil Defence requirements.**

### **NEEDS EVIDENCE**

The project documents partially address 2.2.7 but do not evidence: construction, defence, designed, executed, new, unless.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.2.7 - p. 245 - p. 245 - [verified]

"No new construction shall be executed unless the building has been designed and approved as per Civil Defence requirements."

---

## **25. Ch. 24 SHUTDOWN**

### **NEEDS EVIDENCE**

The project documents partially address Ch. 24 but do not evidence: control, hvac, operation, automatic, combination, door.

uae\_code\_en (01M1AX15) - Ch. 24 - p. 468 - p. 468 - [verified]

"If connected to the fire alarm system serving the protected premises, all detection devices used to cause the operation of HVAC systems' smoke dampers, fire dampers, fan control, smoke doors, and fire doors shall be monitored for integrity.  
ii."

---

## **26. 4.2.1 The Smoke Detection and Alarm System shall comply with Table 8.2. and the General**

### **NEEDS EVIDENCE**

The project documents partially address 4.2.1 but do not evidence: detection.

smoke\_control\_and\_management\_systems1742045231307 (01M1DH7W) - p. 1 - p. 1 - [verified]

"INTERLOCKED WITH FIRE ALARM SYSTEM"

---

## **27. 4.3.1 The Installation and Spacing of Spot Type Smoke Detection and Alarm System shall**

### **NEEDS EVIDENCE**

The project documents partially address 4.3.1 but do not evidence: detection, spot, type, general, spacing.

smoke\_control\_and\_management\_systems1742045231307 (01M1DH7W) - p. 1 - p. 1 - [verified]

"INTERLOCKED WITH FIRE ALARM SYSTEM"

---

## **28. 4.7.1 The Installation and Spacing of Spot Type Smoke Detection and Alarm System shall**

### **NEEDS EVIDENCE**

The project documents partially address 4.7.1 but do not evidence: detection, general, heat, spacing, spot, type.

smoke\_control\_and\_management\_systems1742045231307 (01M1DH7W) - p. 1 - p. 1 - [verified]

"INTERLOCKED WITH FIRE ALARM SYSTEM"

---

## **29. 4.8.1 The Installation and Spacing of Line Type Smoke Detection and Alarm System shall**

### **NEEDS EVIDENCE**

The project documents partially address 4.8.1 but do not evidence: detection, general, heat, line, spacing, type.

smoke\_control\_and\_management\_systems1742045231307 (01M1DH7W) - p. 1 - p. 1 - [verified]

"INTERLOCKED WITH FIRE ALARM SYSTEM"

---

### **30. 4.12.1 The Design, Installation and Spacing of Other Fire Detectors shall comply with Table**

#### **NEEDS EVIDENCE**

The project documents partially address 4.12.1 but do not evidence: design, detection, detector, general, spacing.

smoke\_control\_and\_management\_systems1742045231307 (01M1DH7W) - p. 1 - p. 1 - [verified]

"INTERLOCKED WITH FIRE ALARM SYSTEM"

---

### **31. 4.6 Section 4.6 (Pre-engineered Systems shall be acceptable)**

#### **NEEDS EVIDENCE**

The project documents partially address 4.6 but do not evidence: acceptable, engineered, pre.

uae\_code\_en (01M1AX15) - Ch. 17 - §4.3 - p. 505 - p. 505 - [verified]

"Fire Pump, Fire Water Level, LP Gas detection, CO Monitoring and other interconnected systems like door release, Elevator recall, Smoke Control etc. shall be interfaced with Fire Detection and Alarm System, based on building fire strategy, as per Section 4.1. vii."

---

### **32. 3.10.1 The requirements for Water Mist System material, design, installation shall be as**

#### **NEEDS EVIDENCE**

Evidence relating to 3.10.1 is inconsistent across the project documents, so a single verdict cannot be reached.

uae\_code\_en (01M1AX15) - Ch. 3 - §3.10.1 - p. 669 - p. 669 - [verified]

"The requirements for Water Mist System material, design, installation shall be as per Table 9.12., and the Applicable General Requirements of Table 9.3."

---

### **33. 3.11.1 The requirements for Yard Hydrant System material, design, installation shall be as**

#### **NEEDS EVIDENCE**

The project documents partially address 3.11.1 but do not evidence: design, general, hydrant, yard.

uae\_code\_en (01M1AX15) - Ch. 3 - §3.11.1 - p. 673 - p. 673 - [verified]

"The requirements for Yard Hydrant System material, design, installation shall be as per Table 9.13. and Applicable general requirements of Table 9.3."

---

### **34. 3.15.1 The requirements for various other Extinguishing System material, design, installation shall be as per this section and Table 9.17.**

#### **NEEDS EVIDENCE**

The project documents partially address 3.15.1 but do not evidence: design, extinguishing, various.

uae\_code\_en (01M1AX15) - Ch. 3 - §3.15.1 - p. 691 - p. 691 - [verified]

"The requirements for various other Extinguishing System material, design, installation shall be as per this section and Table 9.17."

---



### 35. 4.1.17 Common Fire Pump and Fire Water Tank

#### NEEDS EVIDENCE

Evidence relating to 4.1.17 is inconsistent across the project documents, so a single verdict cannot be reached.

uae\_code\_en (01M1AX15) - Ch. 4 - §4.1.17 - p. 695 - p. 695 - [verified]

"Common Fire Pump and Fire Water Tank

Where multiple buildings at single plot or multiple plots are owned by a single owner, the fire pump set and fire water tank shall be permitted to be common, provided the arrangement satisfies the required hydraulic calculations and the involved plots and property are managed and maintained by such single owner."

---

### 36. Ch. 90 PLOT AREA EXCEEDING

#### NEEDS EVIDENCE

Evidence relating to Ch. 90 is inconsistent across the project documents, so a single verdict cannot be reached.

uae\_code\_en (01M1AX15) - Ch. 4 - §4.2 - p. 696 - p. 696 - [verified]

"Sprinklers shall be provided throughout the building including basements and podiums (open as well as closed) as per Section 3.5.  
ii. Auxiliary rooms and various areas of the building shall be protected as per Table 9.30.  
iii. The wet riser System shall be provided throughout the building as per Section 3.4.  
iv."

---

### 37. 4.5 Lowrise Building Fire Protection Systems

#### NEEDS EVIDENCE

The project documents partially address 4.5 but do not evidence: lowrise, protection, basement, depth, having, height.

uae\_code\_en (01M1AX15) - Ch. 4 - §4.5 - p. 705 - p. 705 - [verified]

"Lowsrise Building Fire Protection Systems

4.5.1.  
Lowsrise buildings having building height of up to 15 m and low depth underground buildings or basements shall be provided with Fire protection Systems in compliance with Table 9.21.a. and Auxiliary Rooms Fire Protection Systems as per Table 9.30."

---

### **38. Ch. 900 M2 UPTO 2000 M2**

#### **NEEDS EVIDENCE**

The project documents partially address Ch. 900 but do not evidence: hydrant, yard, wet, along, building, exterior.

uae\_code\_en (01M1AX15) - Ch. 900 - p. 714 - p. 714 - [verified]

"Exterior Wet riser System shall be provided throughout the open circulation area, along the fire access road and such that all tenant buildings are within 30 m of the hose outlet, as per Section 3.4.  
ii. Dry landing valves and risers shall not be required.  
iii."

---

### **39. 4.13.1 Various locations in a building shall be protected with Automatic Sprinkler Systems**

#### **NEEDS EVIDENCE**

The project documents partially address 4.13.1 but do not evidence: sprinkler, system, automatic, extended, various.

uae\_code\_en (01M1AX15) - Ch. 4 - §4.13.1 - p. 749 - p. 749 - [verified]

"Various locations in a building shall be protected with Automatic Sprinkler Systems as per Table 9.29. The building sprinkler system shall be extended to comply with requirements of Table 9.29."

---

### **40. 4.14 SYSTEM REQUIREMENTS**

#### **NEEDS EVIDENCE**

The project documents partially address 4.14 but do not evidence: room, protected, agent, clean, separated, electrical.

uae\_code\_en (01M1AX15) - Ch. 4 - §4.14 - p. 753 - p. 753 - [verified]

"Electrical rooms which are less than 10 m2 in area OR are located on typical floors shall not be required to be protected. However, such typical floor electrical rooms shall be 1 hour fire rated enclosures and shall be limited to distribution boards and junction boxes and fully compliant to penetration fire stopping."

---

### **41. 4.15.1 The equipment and machinery shall be protected with options of Fire Protection**

#### **NEEDS EVIDENCE**

The project documents partially address 4.15.1 but do not evidence: machinery, option, protected, protection.

uae\_code\_en (01M1AX15) - Ch. 4 - §4.15.1 - p. 756 - p. 756 - [verified]

"The equipment and machinery shall be protected with options of Fire Protection Systems as per Table 9.31."

#### 42. 2.4.2.4 Smoke containment Systems

##### NEEDS EVIDENCE

The project documents partially address 2.4.2.4 but do not evidence: system, based, building, combination, containment, control.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.4.2.4 - p. 804 - p. 804 - [verified]

"Smoke containment Systems shall be one or a combination of the following systems, based on the building smoke control strategy.

- a. Stairwell Pressurization System
- b. Zoned Smoke Control System
- c. Elevator Pressurization System
- d. Lobby (Vestibule) Pressurization System
- e. Smoke Refuge Area Pressurization System
- f."

---

#### 43. 2.4.3.2 Smoke Management Systems shall be engineered Smoke control systems

##### NEEDS EVIDENCE

The project documents partially address 2.4.3.2 but do not evidence: building, engineered, evaluation, management.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.4.3.2 - p. 805 - p. 805 - [verified]

"Smoke Management Systems shall be engineered Smoke control systems and shall include the following evaluations in a building.

- a. Fire Dynamics
- b. Fire Size and Location
- c. Materials likely to burn
- d. Fire plume geometry
- e. Smoke layer impact on means of egress
- f."

---

#### 44. 2.4.3.3 Smoke Management Systems shall be one or a combination of the following systems, based on the building smoke control strategy.

##### NEEDS EVIDENCE

The project documents partially address 2.4.3.3 but do not evidence: system, control, area, atrium, based, cdgh.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.4.3.3 - p. 805 - p. 805 - [verified]

- "a. Atrium or large volume Smoke Control System
- b. Smoke Extraction System
  - c. Corridor and Open circulation area Smoke Purging System
  - d. Natural Ventilation System
  - e. Mechanical Ventilation System
- | CDGH-OP-25 | September 2018  
Page 805 of 1348"

#### **45. 2.6.1 The stair pressurization system shall comply with the general requirements for**

##### **NEEDS EVIDENCE**

The project documents partially address 2.6.1 but do not evidence: control, smoke.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.6.1 - p. 810 - p. 810 - [verified]

"The stair pressurization system shall comply with the general requirements for smoke control systems as per Section 2.5 and Table 10.4., Stair pressurization requirements."

---

#### **46. 2.7.1 Atrium Smoke Control systems shall comply with the relevant general requirements**

##### **NEEDS EVIDENCE**

The project documents partially address 2.7.1 but do not evidence: system, atrium, large, volume.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.7.1 - p. 816 - p. 816 - [verified]

"Atrium Smoke Control systems shall comply with the relevant general requirements for smoke control systems as per Section 2.5 and Table 10.5., Atrium and Large Volume Smoke Control System requirements."

---

#### **47. 2.9.1 Theaters with legitimate stages shall comply with the relevant general requirements**

##### **NEEDS EVIDENCE**

The project documents partially address 2.9.1 but do not evidence: theater, legitimate, management, stag, system.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.9.1 - p. 827 - p. 827 - [verified]

"Theaters with legitimate stages shall comply with the relevant general requirements for smoke control systems as per Section 2.5 and theater smoke management requirements of Table 10.7."

---

#### **48. 2.11 Smoke Venting System Using Natural Vents on Roof**

##### **NEEDS EVIDENCE**

The project documents partially address 2.11 but do not evidence: system, natural, using, vent, venting, control.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.11 - p. 832 - p. 832 - [verified]

"Smoke Venting System Using Natural Vents on Roof  
2.11.1. Smoke venting systems using natural vents to the outside shall comply with the relevant general requirements for smoke control systems as per Section 2.5 and Table 10.9."

---

#### **49. 2.15.1 The natural Ventilation System shall comply with the relevant general requirements**

##### **NEEDS EVIDENCE**

The project documents partially address 2.15.1 but do not evidence: control, natural.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.7.1 - p. 816 - p. 816 - [verified]

"Atrium Smoke Control systems shall comply with the relevant general requirements for smoke control systems as per Section 2.5 and Table 10.5., Atrium and Large Volume Smoke Control System requirements."

---

## 50. 2.17.1 Mechanical Ventilation System used for smoke exhaust shall comply with the relevant

### NEEDS EVIDENCE

The project documents partially address 2.17.1 but do not evidence: system, control, general, mechanical, used.

smoke\_control\_and\_management\_systems1742045231307 (01M1DH7W) - p. 1 - p. 1 - [verified]

"SMOKE EXHAUST INSTALLATION DETAIL

FE

FE

FE

FE"

---

## 51. 2.18 Ventilation System for Cooking Operations

### NEEDS EVIDENCE

The project documents partially address 2.18 but do not evidence: cooking, operation, control.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.7.1 - p. 816 - p. 816 - [verified]

"Atrium Smoke Control systems shall comply with the relevant general requirements for smoke control systems as per Section 2.5 and Table 10.5., Atrium and Large Volume Smoke Control System requirements."

---

## 52. 2.19 Lift Hoistway Pressurization System

### NEEDS EVIDENCE

The project documents partially address 2.19 but do not evidence: hoistway, control, general, specification, stair.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.19 - p. 851 - p. 851 - [verified]

"Lift Hoistway Pressurization System

2.19.1. Lift Hoistway pressurization systems shall comply with Table 10.17., relevant specifications of Section 2.6., Stair Pressurization and the general requirements for smoke control systems as per Section 2.5."

---

## 53. 2.20 Ventilation for Rooms with Hazardous and Flammable

### NEEDS EVIDENCE

Evidence relating to 2.20 is inconsistent across the project documents, so a single verdict cannot be reached.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.20 - p. 853 - p. 853 - [verified]

"Ventilation for Rooms with Hazardous and Flammable  
Materials

2.20.1. Rooms containing hazardous and flammable materials shall be provided with ventilation system as per Table 10.18. and the relevant general requirements for smoke control systems as per Section 2.5."

## 54. 2.5.2 Piping distribution, Filling and other requirements for all types of LPG Tank

### NEEDS EVIDENCE

Evidence relating to 2.5.2 is inconsistent across the project documents, so a single verdict cannot be reached.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.5.2 - p. 900 - p. 900 - [verified]

"Piping distribution, Filling and other requirements for all types of LPG Tank installations

2.5.2.1.

Piping distribution requirements for any LPG Tank installations shall be as per Table 11. 4."

---

## 55. 2.5.3 Above ground LPG Tank installation

### NEEDS EVIDENCE

Evidence relating to 2.5.3 is inconsistent across the project documents, so a single verdict cannot be reached.

smoke\_control\_and\_management\_systems1742045231307 (01M1DH7W) - p. 2 - p. 2 - [verified]

"GROUND FLOOR EXTENT

E  
E  
I  
I  
17  
17  
8  
8  
9  
9  
12  
12  
13  
13  
3  
3  
11  
11  
5  
5  
H  
H  
10  
10

water tank capacity 150 m3  
clear water column hi. 1.9 m  
clear void 400mm  
78.92 m<sup>2</sup>"

---

## 56. 2.5.4 On Roof LPG Tank installation

### NEEDS EVIDENCE

The project documents partially address 2.5.4 but do not evidence: lpg, elevated, platform, podium.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.5.4 - p. 909 - p. 909 - [verified]

"On Roof LPG Tank installation

2.5.4.1.

On roof, on podium, on elevated platform LPG Tank installation shall comply with requirements of Section 2.5.1., 2.5.2., 2.5.4. and section 6."

---

## 57. 2.5.5 Underground or Mounded LPG Tank installation

### NEEDS EVIDENCE

The project documents partially address 2.5.5 but do not evidence: mounded, underground.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.5.5 - p. 915 - p. 915 - [verified]

"Underground or Mounded LPG Tank installation

2.5.5.1.

Underground or Mounded LPG Tank installation shall comply with requirements of Section 2.5.1., 2.5.2., 2.5.5. and section 6."

---

## 58. 2.5.6 PRDP (Pressure Reducing Distribution Panel) Connections and tapping

### NEEDS EVIDENCE

The project documents partially address 2.5.6 but do not evidence: prdp, distribution, lpg, onward, reducing, tapping.

uae\_code\_en (01M1AX15) - Ch. 2 - §2.5.6 - p. 921 - p. 921 - [verified]

"PRDP (Pressure Reducing Distribution Panel) Connections and tapping

2.5.6.1.

LPG installations from PRDP onwards shall comply with Table 11.11. and"

---

## 59. 6.1.7 LPG Tanks \*Working pressure should not be less than 250 psi (17.57 Kg/Sq. cm)

### NEEDS EVIDENCE

Evidence relating to 6.1.7 is inconsistent across the project documents, so a single verdict cannot be reached.

uae\_code\_en (01M1AX15) - Ch. 6 - §6.1.7 - p. 933 - p. 933 - [verified]

"cm)

and design storage temperature shall be -420C to 550C.+

i.

Regulations of the U.S Department of Transportation (DOT), the "Rules for the Construction of Unfired Pressure Vessels", Section VIII, Division 1

ii.

ASME Boiler and Pressure Vessel Code.

iii."

---

### 60. 3.5.1 Safe Storage and handling Practices shall be followed by all the contractors and suppliers as required by Table 12.5.

#### NEEDS EVIDENCE

The project documents partially address 3.5.1 but do not evidence: handling, practic, safe, supplier.

uae\_code\_en (01M1AX15) - Ch. 3 - §3.5.1 - p. 955 - p. 955 - [verified]

"Safe Storage and handling Practices shall be followed by all the contractors and suppliers as required by Table 12.5."

---

### Recommended actions

[CRITICAL] Amend the project document so the stated value satisfies 2.17.2.2.

[HIGH] Amend the project document so the stated value satisfies 2.15.1.3.

[HIGH] Supply the section that demonstrates system, barrier, control, opening, penetrate, arranged.

[HIGH] Supply the section that demonstrates window, outward, see, top.

[HIGH] Amend the project document so the stated value satisfies 4.5.4.3.

[HIGH] Supply the section that demonstrates masonry, barrier, construction, covered, face, panel.

[HIGH] Supply the section that demonstrates glazing, application, civil, defence, edge, environment.

[HIGH] Amend the project document so the stated value satisfies 2.9.5.

---

### Disclosures

- Generated by deterministic:uxe-extractive-v1 + deterministic:uxe-hashed-ngram-v1.
- Every row is traceable to the source version pinned to this consultation.