

MODERN CRYPTOGRAPHY

STRONGER SECURITY NOTIONS

SEP 4, 2025

Dr Shashank Singh

TABLE OF CONTENT

1. Stronger Seucrity Notions
2. CPA Seucrity
3. Pseudo random function

STRONGER SECURITY NOTIONS

SECURITY FOR MULTIPLE ENCRYPTION

- Consider a scenario where the same key is used for multiple message exchanges by two communicating parties. An adversary, denoted as \mathcal{A} , eavesdrops on all the messages.

SECURITY FOR MULTIPLE ENCRYPTION

- Consider a scenario where the same key is used for multiple message exchanges by two communicating parties. An adversary, denoted as \mathcal{A} , eavesdrops on all the messages.

$\text{PrivK}_{\mathcal{A}, \Pi}^{\text{mult}}(n) :$

1. \mathcal{A} is given $\Pi(n)$. \mathcal{A} outputs $\mathbf{m}_0 := (m_{00}, m_{01}, \dots, m_{0t})$ and $\mathbf{m}_1 := (m_{10}, m_{11}, \dots, m_{1t})$, where $m_{ij} \in \{0, 1\}^*$ with $|m_{0i}| = |m_{1i}| \forall i$.
2. $k \leftarrow \text{GEN}(n)$, $b \xleftarrow{\$} \{0, 1\}$ and $\mathbf{c} := (c_0, c_1, \dots, c_t)$ is given to the \mathcal{A} , where $c_i \leftarrow \text{ENC}(k, m_{bi})$
3. \mathcal{A} return a bit b' .
4. The output of the experiment is $b' \stackrel{?}{=} b$.



Definition 1

A private key encryption scheme $\Pi(n)$ has an **indistinguishable multiple encryption in the presence of an eavesdropper**, or is EAV-secure, if for all PPT adversaries \mathcal{A} , there is a negligible function $\varepsilon()$ such that, for all n ,

$$\Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{mult}}(n) = 1] \leq \frac{1}{2} + \varepsilon(n). \quad (1)$$



Remark

- The one-time pad encryption scheme does not have indistinguishable multiple encryptions in the presence of an eavesdropper.

CPA SECURITY

SECURITY AGAINST CHOSEN-PLAINTEXT ATTACK

Let $\Pi(n)$ be an encryption scheme and \mathcal{A} be a CPA adversary.

$\text{PrivK}_{\mathcal{A}, \Pi}^{\text{cpa}}(n) :$

1. $k \xleftarrow{\$} \text{GEN}(n)$ and the encryption oracle $\text{ENC}_k(\cdot)$ is given to \mathcal{A} .
2. \mathcal{A} outputs $m_0, m_1 \in \{0, 1\}^*$ with $|m_0| = |m_1|$.
3. $b \xleftarrow{\$} \{0, 1\}$ and $c \leftarrow \text{ENC}(k, m_b)$ is given to \mathcal{A} .
4. \mathcal{A} return b' .
5. The output of the experiment is $b' \stackrel{?}{=} b$.



Definition 1

A private key encryption scheme $\Pi(n)$ has an **indistinguishable encryption under the chosen plain text attack**, or is CPA-secure, if for all PPT adversaries \mathcal{A} , there is a negligible function $\varepsilon()$ such that, for all n ,

$$\Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{cpa}}(n) = 1] \leq \frac{1}{2} + \varepsilon(n). \quad (2)$$



Note

- We can also define CPA-security for multiple encryptions in a similar manner.

Theorem 1

Any private-key encryption scheme that is CPA-secure is also CPA-secure for multiple encryptions.



Remark

- The theorem has positive consequences.
- We only need a CPA-secure fixed-length encryption scheme.
- Since multiple encryption is also CPA secure, we can use the same key to encrypt longer messages as needed.

CONSTRUCTION OF CPA SECURE SCHEMES

- We have observed that CPA security (IND-CPA) remains intact even when the same key is used to encrypt multiple messages.
- The key takeaway from this observation is that we should concentrate on designing a CPA-secure scheme for encrypting fixed-length messages only, i.e., for $\mathcal{M} = \{0, 1\}^n$ for some n .
- The encryption schemes for encrypting fixed-length messages will be referred to as block ciphers. A block cipher is represented by an abstract concept known as a Pseudorandom Function, more precisely by Pseudorandom Permutations.
- When we talk about the pseudorandomness of functions, we are essentially referring to the pseudorandomness of a distribution over functions.

PSEUDO RANDOM FUNCTION

PSEUDORANDOM FUNCTION

- We have observed that large discrete distributions are frequently defined by algorithms that efficiently sample elements according to the distribution.
- We are interested in the random functions of the set \mathcal{F}_n .

$$\mathcal{F}_n = \{f : \{0, 1\}^n \mapsto \{0, 1\}^n\}$$

- $|\mathcal{F}_n| = 2^{n \cdot 2^n}$ is very large even for very small n .

KEYED FUNCTION

We define a keyed function as a function

$$F : \{0, 1\}^n \times \{0, 1\}^{\ell_{\text{in}}(n)} \mapsto \{0, 1\}^{\ell_{\text{out}}(n)},$$

which takes as input a key, $k \leftarrow \{0, 1\}^n$, completely specifies function

$$F_k : \{0, 1\}^{\ell_{\text{in}}(n)} \mapsto \{0, 1\}^{\ell_{\text{out}}(n)} \in \mathcal{F}_n.$$

Remark

- ▶ $\left| \{F_k : F_k \text{ is a keyed function and } k \in \{0, 1\}^n\} \right| = 2^n \ll |\mathcal{F}_n|.$
- ▶ If $\ell_{\text{in}}(n) = \ell_{\text{out}}(n) = n$, F_k is called length preserving.
- ▶ The size of the keyed function, though very, very small in comparison to $|\mathcal{F}|$ but is still too large (2^n) for us.

PSEUDORANDOM FUNCTION

Definition 1

An efficient, length-preserving keyed function F_k , where $k \in \{0, 1\}^n$ is said to pseudorandom function if for all probabilistic polynomial-time distinguishers (algorithms) \mathcal{D} , there is a negligible function $\varepsilon()$ such that,

$$\left| \Pr_{k \leftarrow \{0,1\}^n} [\mathcal{D}(F_k(\cdot)) = 1] - \Pr_{f \leftarrow \mathcal{F}} [\mathcal{D}(f(\cdot)) = 1] \right| \leq \varepsilon(n).$$



Informally, if it's nearly impossible to determine whether a given function (oracle access) is a keyed function or a random function from the set \mathcal{F} with a probability better than $\frac{1}{2} + \varepsilon(n)$, then we can consider the distribution of keyed functions to be pseudorandom.