```
agent Researcher(topic: text) -> text {
  role "Senior research analyst"
  goal "Find five facts about {topic}"
  policy { require human when confidence < 0.70 }
}

flow main(topic: text) {
  facts = Researcher(topic)
  [a, b] = par { Writer(facts), Critic(facts) }
  emit a, b
}
```



OFFICIAL DOCUMENTATION

The AlgoLang Programming Language

An open-source, agent-native language for building AI systems

Every unit of work is an agent.

version	0.3.0	license	Apache-2.0	python	≥ 3.9	runs on	Windows · Linux · macOS · Colab	status	preview

Dr. S. Satyanarayana

Ph.D., PDF (AI)

Founder, CEO & Chief Agentic AI Scientist

AlgoProfessor AI R&D Solutions, Hyderabad

www.algoprofessor.com

VERSION 0.3 · NOVEMBER 2026

The AlgoLang Programming Language — Official Documentation
Version 0.3 · November 2026

Author: Dr. S. Satyanarayana, Ph.D., PDF (AI)
Founder, CEO & Chief Agentic AI Scientist, AlgoProfessor AI R&D Solutions, Hyderabad, India
ceo@algoprofessor.com · www.algoprofessor.com

Copyright © 2026 Dr. S. Satyanarayana and AlgoProfessor AI R&D Solutions.

Software licence. The AlgoLang compiler, runtime, notebook extension and examples are open-source software, licensed under the Apache License, Version 2.0. You may use, modify and redistribute them under the terms of that licence.

Documentation licence. This document is licensed under the Creative Commons Attribution 4.0 International licence (CC BY 4.0). You may share and adapt it, including for teaching, provided you give appropriate credit.

How to cite. See Chapter 20, Section 20.7.

Trademarks. Claude is a product of Anthropic. Other names are the property of their respective owners and are used for identification only.

Status. AlgoLang 0.3 adds `uncertain<T>` types, deterministic guards, **`eval`** blocks with trace replay, MCP tool bindings, cost and energy budgets and a language server (Chapter 16), on top of the 0.2 Enterprise features (Chapter 15). Version 0.4 is dedicated to trustworthy AI. It remains a preview release. Language details may change before version 1.0; changes are proposed and discussed through the process in Chapter 20.

Typeset with XeLaTeX in TeX Gyre Pagella, Inter and DejaVu Sans Mono.

Preface

Most of today's AI systems are written in languages designed decades before large language models existed. In those languages the basic unit of work is the *function*: a block of code that runs silently, takes whatever it can reach, and leaves no record of what it did. When the work inside a function is done by an AI model, that silence becomes a problem. Who decided? On what evidence? With how much confidence? Who checked it? Was a protected attribute such as caste or gender used? A function cannot tell us.

AlgoLang starts from a different premise. In **AlgoLang** there are no functions. **Every unit of work is an agent**: a named worker with a stated role, a goal written in plain language, an explicit list of the tools it may use, the model it runs on, and a policy that governs it. Programs are *flows* that connect agents, run them in parallel, and branch on their scores. Governance—budgets, retries, human review, forbidden attributes, audit trails—is part of the language, not an afterthought in a library.

This book is the official documentation for **AlgoLang** version 0.2 Enterprise. It is written for three audiences:

- **Students and teachers** who want a clear, small language for learning how multi-agent AI systems are built, and for discussing responsible AI with real code.
- **Researchers** who want to prototype agentic pipelines with built-in provenance, and to study language-level approaches to AI governance.
- **Engineers** who want to know exactly what the compiler checks, what the runtime enforces, and where the current limits are.

How this book is organised

Part I gets you running: what **AlgoLang** is, how to install it on Windows, Linux, macOS, Google Colab and Jupyter, and a first program. **Part II** is the language reference: lexical structure, types, declarations, policies, flows and every compile-time error. **Part III** covers the toolchain and runtime: the `algo` command, execution semantics, the audit log, notebooks and the compiler's internals. **Part IV** turns to practice: multi-agent design patterns, responsible AI, and ready-to-use teaching material. **Part V** describes the open-source project: roadmap, contribution process, licence and citation. The appendices hold the formal grammar, quick-reference tables and complete example programs.

Conventions

AlgoLang source code appears in light boxes with a navy edge; terminal sessions appear in dark boxes. Every example in this book was compiled and run with **AlgoLang** 0.1.0 and 0.2.0, and the outputs shown are real outputs from the offline (mock) backend unless stated other-

wise.

Note. Notes give extra detail.

Tip. Tips suggest a better or faster way.

Caution. Cautions mark limitations you must understand before relying on a feature.

Responsible AI

Responsible-AI boxes connect a language feature to the ethical principle it supports.

Acknowledgements

AlgoLang grew out of teaching agentic AI and AI ethics to students and research scholars, and out of the research programme at AlgoProfessor AI R&D Solutions. I thank the students, Ph.D. scholars and postdoctoral researchers whose questions shaped its design. Errors that remain are mine; reports and proposals are warmly welcomed through the process in Chapter 20.

Dr. S. Satyanarayana, Ph.D., PDF (AI)
Founder, CEO & Chief Agentic AI Scientist
AlgoProfessor AI R&D Solutions, Hyderabad
October 2026

Contents

Preface ii

I Getting Started

1 Introduction 2

1.1 AlgoLang at a glance 2
1.2 The core idea: agents, not functions 3
1.3 Design goals 3
1.4 How AlgoLang compares 4
1.5 What is in version 0.1 4

2 Installation 5

2.1 Get the distribution 5
2.2 Windows 6
2.3 Linux and macOS 6
2.4 Checking the installation. 6
2.5 Live mode with Claude (optional) 7
2.6 Google Colab 7
2.7 Jupyter on your computer 7
2.8 Docker 8
2.9 Editor support 8
2.10 Troubleshooting 8

3 Three Ways to Work. 9

3.1 Simple: the menu 9
3.2 Simple: the interactive shell 10
3.3 Graphical: AlgoLang Studio. 10
3.4 Agentic: AI writes the program. 11
3.5 Agentic without AI: the wizard 13

4 Your First Program 14

4.1 Create a starter. 14
4.2 Reading the program 15

4.3 Check, then run . . . 15
4.4 What just happened . . . 16
4.5 Try it yourself . . . 16

II The Language

5 Programs and Lexical Structure . . . 18
5.1 Source files . . . 18
5.2 Comments, whitespace and semicolons . . . 18
5.3 Identifiers . . . 18
5.4 Keywords . . . 19
5.5 Literals . . . 19
5.6 Placeholders in goals . . . 19
5.7 Operators . . . 19

6 Types and Results . . . 20
6.1 The five types . . . 20
6.2 Where types matter . . . 20
6.3 Results: value plus provenance . . . 21
6.4 Flow inputs . . . 21

7 Models, Tools and Agents . . . 22
7.1 Models . . . 22
7.2 Tools . . . 22
7.3 Agents . . . 23
7.4 Writing good agents . . . 24

8 Policies . . . 25
8.1 Summary of rules . . . 25
8.2 Token budgets . . . 25
8.3 Retries and timeouts . . . 26
8.4 Human oversight . . . 26
8.5 Forbidden attributes . . . 26
8.6 Where policies are recorded . . . 27

9 Flows . . . 28
9.1 Calling agents . . . 28
9.2 Variables . . . 28
9.3 Parallel blocks: `par` . . . 29
9.4 Parallel map: `par for` . . . 29

9.5 Branching: `if` and `else` . . . 29
9.6 Returning results: `emit` . . . 29
9.7 Complete example . . . 30

10 Compile-Time Errors . . . 31

10.1 Error catalogue . . . 31
10.2 Run-time outcomes . . . 34

III Toolchain and Runtime

11 The `algo` Command . . . 36

11.1 Commands . . . 37
11.2 Options for `run` . . . 37
11.3 Exit codes . . . 38
11.4 Environment variables . . . 38
11.5 Running compiled programs directly . . . 38

12 Runtime Semantics . . . 39

12.1 Lifecycle of a run . . . 39
12.2 Lifecycle of an agent call . . . 39
12.3 Concurrency . . . 40
12.4 Backends . . . 40
12.5 The audit log . . . 40

13 Jupyter and Google Colab . . . 42

13.1 Starting . . . 42
13.2 The `%%algo` cell magic . . . 42
13.3 Building a program cell by cell . . . 43
13.4 Line magics . . . 43
13.5 Results in Python . . . 44
13.6 What a run displays . . . 44
13.7 Live mode in Colab . . . 44

14 Inside the Compiler . . . 45

14.1 Pipeline . . . 45
14.2 Generated code . . . 45
14.3 Extending the language . . . 46

15 Enterprise Edition: Domains, Governance and the SDK . . . 47

15.1 Modules . . . 47

15.2 Organisation policy . . . 48
15.3 The domain library: 120 packs in 20 sectors . . . 48
15.4 Governance. . . . 49
15.5 Executable tools and scale . . . 50
15.6 One SDK, three modes . . . 50

16 Version 0.3: Uncertainty, Evidence and Interoperability . . . 55

16.1 `uncertain<T>` types . . . 55
16.2 Deterministic guards . . . 56
16.3 Eval blocks, traces and replay . . . 56
16.4 MCP tool bindings . . . 57
16.5 Cost and energy budgets. . . . 58
16.6 The language server . . . 58
16.7 Towards v0.4: trustworthy AI . . . 58

IV Patterns and Practice

17 Multi-Agent Design Patterns. . . . 61

17.1 Pipeline . . . 61
17.2 Fan-out / fan-in . . . 61
17.3 Committee . . . 62
17.4 Critic and revise . . . 62
17.5 Router . . . 62
17.6 Guardrail . . . 63
17.7 Human-in-the-loop . . . 63
17.8 Separation of duties. . . . 63
17.9 Choosing a pattern . . . 64

18 Responsible AI with AlgoLang. . . . 65

18.1 Principles and features . . . 65
18.2 Supporting governance frameworks . . . 65
18.3 A responsible design checklist . . . 66
18.4 Known limitations . . . 66
18.5 Teaching AI ethics with AlgoLang . . . 67

19 Teaching with AlgoLang . . . 68

19.1 Suggested lab sequence . . . 68
19.2 Exercises . . . 68
19.3 Assessment ideas . . . 69

19.4 Using the notebook in class . . . 69

V The Project

20 The AlgoLang Project . . . 71
20.1 Versioning . . . 71
20.2 Roadmap . . . 71
20.3 Proposing changes: AEPs . . . 71
20.4 Contributing . . . 72
20.5 Code of conduct . . . 72
20.6 Licence . . . 72
20.7 How to cite AlgoLang . . . 72

A Grammar . . . 74

B Quick Reference . . . 76
B.1 Language card . . . 76
B.2 Error codes . . . 77
B.3 Command line . . . 77
B.4 Notebook . . . 78
B.5 Glossary . . . 78

C Example Programs . . . 79
C.1 research_brief.algo . . . 79
C.2 paper_review.algo . . . 80
C.3 bad_example.algo . . . 81
C.4 Output of research_brief.algo . . . 82

PART I

Getting Started



1

Introduction

AlgoLang is a small, statically checked programming language for building AI systems out of cooperating agents. A program declares agents and connects them in flows; the compiler checks the program; the runtime executes it with policies enforced and every agent call recorded.

1.1 AlgoLang at a glance

brief.algo

```
model fast = "claude-haiku-5-5"

agent Writer(facts: text, tone: text = "academic") -> text {
    role  "Technical writer"
    goal  "Write a 200-word brief from {facts} in a {tone} tone"
    model fast
    policy { budget tokens 4000  retry 1 }
}

agent Reviewer(draft: text) -> score {
    role  "Peer reviewer"
    goal  "Score {draft} from 0 to 1 for accuracy"
    policy { require human when confidence < 0.70 }
}

flow main(facts: text) {
    [formal, simple] = par { Writer(facts), Writer(facts, tone = "plain") }
    if Reviewer(formal) < 0.80 {
        formal = Writer(facts, tone = "rigorous academic")
    }
    emit formal, simple
}
```

In twenty lines this program declares two agents, runs two writers at the same time, asks a reviewer to score the formal draft, sends any low-confidence score to a human, redrafts when the score is low, and returns both drafts. The compiler has already checked that every name, argument, type and tool is correct before anything runs.

1.2 The core idea: agents, not functions

The AlgoLang rule

There are no functions, methods or lambdas. The only thing a program can call is an **`agent`**. An agent must state its **`goal`**; it may state its **`role`**, the **`tools`** it **`uses`**, its **`model`** and its **`policy`**. A **`flow`** orchestrates agents and can do nothing else.

This rule is enforced by the compiler. Calling anything that is not a declared agent is error **E101**, and the message explains why:

terminal

```
$ algo check bad_example.algo
✗ bad_example.algo: 8 error(s)
  line 20: E101 'summarise_text' is not an agent - in AlgoLang every unit
           of work is an agent (declare it with `agent summarise_text(...)
           -> type { goal "..." }`)
```

Why insist on this? Because each requirement of an agent answers a question that matters when AI does the work:

Agent clause	Question it answers
`goal`	What exactly was this worker asked to do?
`role`	In what capacity did it act?
`uses`	Which external capabilities could it touch?
`model`	Which model produced the result?
`policy`	What limits applied: cost, retries, human review, forbidden inputs?
audit record	What happened, when, with what confidence?

1.3 Design goals

1. **Agents only.** Work is always visible and accountable.
2. **No ambient capabilities.** Tools must be declared and then granted to specific agents.
3. **Governance in the language.** Policies are syntax, checked at compile time where possible and enforced at run time.
4. **Uncertainty is visible.** Every agent call returns a value *and* a confidence.
5. **Accountable by default.** Every agent call is written to an audit log without extra code.
6. **Concurrency is a keyword.** **`par`** and **`par for`** express multi-agent parallelism directly.
7. **Small and familiar.** Brace syntax, about two dozen keywords, five types—easy for people and for coding assistants to read and write.
8. **Runs everywhere.** Windows, Linux, macOS, Docker, Jupyter and Google Colab, with an offline backend for teaching and testing.

1.4 How AlgoLang compares

AlgoLang does not replace general-purpose languages. It compiles *to* Python and is meant for the layer where agents are composed and governed.

Concern	General-purpose language + agent library	AlgoLang
Unit of work	Any function; AI calls hidden inside	Declared agents only (**E101**)
Tool access	Whatever the code can import	Declared and granted per agent (**E104**)
Human oversight	Written by hand, if at all	`require human when confidence < x`
Protected attributes	Convention	`forbid`: compile and run-time checks (**E108**)
Cost control	External monitoring	`budget tokens N` per agent
Audit trail	Added logging	Automatic, one record per call
Parallel agents	Thread or async code	`par` and `par for`
Confidence	Rarely exposed	Part of every result

1.5 What is in version 0.1

Component	Description
Grammar	Formal grammar in Lark EBNF (Appendix A)
Compiler `algoc.py`	Parser, semantic checker with 15 error codes, Python code generator
Runtime `algoruntime.py`	Policy enforcement, concurrency, audit log; mock and live (Claude) backends
`algo` command	`check`, `build`, `run`, `new`, `doctor`, `notebook`
Notebook extension	`%%algo` cell magic for Jupyter and Google Colab, with diagrams
Installers	Windows, Linux/macOS, Docker
Editor support	VS Code syntax highlighting and run tasks
Examples	Research brief, paper review, error showcase, starter template

Caution. Version 0.2 Enterprise adds executable tools, modules, organisation policy, 120 domain packs, tamper-evident audit logs, a review queue, a Python SDK and a Prompt UI (Chapter 15). Section 18.4 lists every known limitation.

2

Installation

AlgoLang needs only **Python 3.9 or newer**. The installers create a private virtual environment (`.venv`) inside the **AlgoLang** folder, so they never disturb other Python projects. Choose the route that suits you:

Route	Best for	Install effort
Windows installer	Students and labs on Windows PCs	Double-click
Linux / macOS installer	Developers, servers, Mac laptops	One command
Google Colab	Classrooms, no installation at all	Upload one file
Local Jupyter	Notebook-style work on your own PC	One command
Docker	Identical environments on any machine	Two commands

2.1 Get the distribution

Unzip `AlgoLang_v0.2.zip` to a folder of your choice, for example `D:\algolang` on Windows or `~/algolang` on Linux and macOS. The folder contains:

distribution layout

```
algolang/
├── algo, algo.bat              the `algo` command (Linux/macOS, Windows)
├── install.sh, install.bat     one-time installers
├── algoc.py                    compiler
├── algoruntime.py              runtime
├── algomagic.py                Jupyter / Colab extension
├── grammar.lark                formal grammar
├── AlgoLang_Notebook.ipynb     self-contained notebook
├── requirements.txt            lark
├── requirements-live.txt       lark + anthropic (for --live)
├── Dockerfile
├── RUN_GUIDE.md, README.md
├── examples/                   example programs, compiled output, run logs
├── vscode-algolang/            VS Code syntax highlighting
├── .vscode/tasks.json          Ctrl+Shift+B runs the open .algo file
└── docs/                       this book (LaTeX source and PDF)
```

2.2 Windows

1. Install Python from python.org. On the first installer screen, tick **Add python.exe to PATH**.
2. Open the **AlgoLang** folder and double-click `install.bat`. It creates `.venv`, installs the parser and finishes with an environment check.
3. Open *Command Prompt* in the folder (type `cmd` in the Explorer address bar) and run a program:

```
terminal

D:\algolang> algo run examples\research_brief.algo --arg "topic=Blockchain data integrity"
```

To use `algo` from any folder, add the **AlgoLang** folder to your user `PATH` (*Start → Edit environment variables for your account → Path → New*). The installer prints the exact folder to add.

2.3 Linux and macOS

```
terminal

$ cd ~/algolang
$ bash install.sh
== AlgoLang installer ==
✓ using Python 3.12.3
→ creating virtual environment in .venv
→ installing lark
✓ linked 'algo' command into ~/.local/bin
```

The installer links `algo` into `~/.local/bin`. If that folder is not on your `PATH`, the installer prints the line to add to `~/.bashrc` or `~/.zshrc`. Until then, run `./algo` from inside the folder.

2.4 Checking the installation

Both installers end by running `algo doctor`. Run it again at any time:

```
terminal

$ algo doctor
AlgoLang 0.2.0 environment check
  ✓ Python                 3.12.3
  ✓ lark (parser)          1.3.1
  • anthropic (live mode)  not installed — optional; pip install anthropic for --live
  • ANTHROPIC_API_KEY      not set — optional; needed only for --live
  ✓ runtime                /home/you/algolang/algoruntime.py
  ✓ compiler self-test     examples/research_brief.algo compiles

Ready.
```

A ✓ is required and working; a • is optional and only needed for live mode; a ✗ must be fixed

before **AlgoLang** will run.

2.5 Live mode with Claude (optional)

By default agents run on the *mock* backend: an offline, deterministic simulator that is free and gives the same answer for the same input. To run agents on real Claude models:

1. Create an API key at console.anthropic.com.
2. Install the SDK: `install.bat --live` (Windows) or `bash install.sh --live` (Linux/-macOS).
3. Set the key in the same terminal you will run from:

Shell	Command
Windows Command Prompt	`set ANTHROPIC_API_KEY=sk-ant-...`
Windows PowerShell	`$env:ANTHROPIC_API_KEY="sk-ant-..."`
Linux / macOS	`export ANTHROPIC_API_KEY=sk-ant-...`

Then add `--live` to any `algo run` command.

> **Caution. Live calls consume API credits. Give every agent a `budget tokens` policy (Chapter 8) so that a mistake cannot become expensive. Never commit an API key to a shared folder or repository.**

2.6 Google Colab

No installation is needed. Open colab.research.google.com, choose *File* → *Upload notebook*, select `AlgoLang_Notebook.ipynb`, then *Runtime* → *Run all*. The notebook installs the parser and writes the toolchain into the Colab machine itself. Chapter 13 explains notebook use in full.

2.7 Jupyter on your computer

After installing, run:

```
terminal
$ algo notebook
→ installing Jupyter Notebook (one time, takes a minute)…
→ opening AlgoLang_Notebook.ipynb in your browser (press Ctrl+C here to stop Jupyter)
```

2.8 Docker

```
terminal
$ docker build -t algolang .
$ docker run --rm -v "$PWD:/work" algolang run examples/research_brief.algo --arg "topic=AI
    ↪ ethics"
$ docker run --rm -e ANTHROPIC_API_KEY -v "$PWD:/work" algolang run my.algo --arg "topic=..."
    ↪ --live
```

The image includes the live-mode SDK. Your current folder is mounted at `/work`, so programs and audit logs stay on your machine.

2.9 Editor support

- **Syntax colours:** copy the `vscode-algolang` folder into your VS Code extensions folder (`%USERPROFILE%\.vscode\extensions` on Windows, `~/.vscode/extensions` elsewhere) and restart VS Code. Files ending in `.algo` are then highlighted.
- **Run with a keypress:** open the **AlgoLang** folder in VS Code, open any `.algo` file and press **Ctrl+Shift+B**. VS Code asks for the flow input (for example `topic=AI ethics`) and runs the program. *Terminal* → *Run Task* offers live and check-only variants.

2.10 Troubleshooting

Message	Fix
`'algo' is not recognized` (Windows)	Run from inside the **AlgoLang** folder, or add it to `PATH`
`algo: command not found`	Use `./algo`, or add `~/.local/bin` to `PATH`
`Python 3.9 or newer is required`	Install Python, then rerun the installer
`No module named 'lark'`	Rerun the installer
`--live needs ANTHROPIC_API_KEY`	Set the key in the *same* terminal (Section 2.5)
`--live needs the anthropic package`	Rerun the installer with `--live`
`✗ POLICY VIOLATION`	Not a fault: a policy stopped the run; read the message
`E1xx` messages	Compile errors; see Chapter 10

3

Three Ways to Work

AlgoLang can be used in three ways, from the simplest to the most powerful. All three use the same compiler and runtime, so a program written one way runs unchanged in the others.

Way	Start it with	Best for
Simple	`algo` (menu), `algo shell`, `algo run`	Quick runs, scripts, lab sessions
Graphical	`algo studio`	Writing, running and seeing programs in a browser
Agentic	`algo ask "…"`, `algo wizard`	Letting AI write the program, or answering questions to build one

3.1 Simple: the menu

Type `algo` on its own and a numbered menu offers every option. No commands need to be remembered.

terminal

```
$ algo

  AlgoLang 0.2.0 — every unit of work is an agent

   SIMPLE (command line)
     1  Create a new program          4  Interactive shell
     2  Run a program                 5  Environment check
     3  Check a program for errors
   GRAPHICAL
     6  AlgoLang Studio (opens in your browser)
     7  Jupyter notebook
   AGENTIC
     8  Ask AI to write a program from your description
     9  Wizard: build a program by answering questions (no AI)

     0  Exit

  Choose 0-9:
```

3.2 Simple: the interactive shell

`algo shell` lets you type **AlgoLang** one declaration at a time, like the Python prompt. A block continues until its braces balance. Each declaration is checked as soon as it is complete; one with errors is rejected and explained, and the session is left unchanged. Calling an agent directly runs it at once.

terminal

```
$ algo shell
AlgoLang 0.2.0 shell — every unit of work is an agent
algo> model fast = "claude-haiku-5-5"
✓ model fast
algo> agent Explainer(topic: text) -> text {
...>     goal "Explain {topic} simply"
...>     model fast
...> }
✓ Explainer
algo> agent Bad(x: text) -> text {
...>     goal "use {y}"
...> }
✗ not added — 1 error(s):
  E109 line 1: agent Bad: goal mentions {y} but there is no parameter 'y'
algo> // … QuizMaker and flow main are added the same way …
algo> Explainer("graph neural networks")
▶ flow main  run=f6150c29  backend=mock
  → Explainer          conf=0.64  «Explainer #8884» Explain graph neural networks simply
algo> :graph
  ◇ topic                     flow input
  ■ Explainer                 → lesson                ← topic
  ■ QuizMaker                 → quiz                  ← Explainer
  ◎ emit                      flow output             ← Explainer, QuizMaker
algo> :save lesson.algo
✓ saved lesson.algo
```

Shell command	Effect
`:run topic=AI`	Run `flow main`; missing inputs are asked for
`:check`, `:graph`, `:python`	Check, show agent connections, show generated Python
`:list`, `:show`	List definitions; print the whole program
`:save f.algo`, `:load f.algo`	Save or load a program
`:live on|off`	Switch between real Claude models and the offline mock
`:reset`, `:help`, `:quit`	Start again; help; leave

3.3 Graphical: AlgoLang Studio

`algo studio` starts a small server on your own computer and opens *AlgoLang Studio* in your web browser (Figure 3.1). Nothing leaves your machine unless you switch on live mode.




Figure 3.1: AlgoLang Studio after a run: the editor with highlighting and live error checking (left), and the inputs, emitted results and agent-call table (right).

Area	What it does
Editor	Syntax highlighting, line numbers, automatic indentation; errors marked in red in the margin as you type
▶ Run (Ctrl+Enter)	Fills in a form for `flow main`'s inputs, runs, and shows results, confidences, human-review flags and the audit-log path
Agent Graph	Draws the flow top to bottom (Figure 3.2)
Ask AI	Describe a program in plain English; AI writes it (Section 3.4)
Templates	Start from any of six design patterns, no AI needed
Python	The code the compiler generates
Problems	Every compile error; click one to jump to its line
Open / Save	Your programs in the workspace folder, and the examples
Live Claude	Switches from the offline mock to real models (needs an API key)

Note. Studio listens only on `127.0.0.1` and refuses requests from other web sites, so other pages open in your browser cannot use it. Use `algo studio --port 9000` to choose a port, or `--no-browser` to start it without opening a window.

3.4 Agentic: AI writes the program

`algo ask` turns a description into a working **AlgoLang** program:




Figure 3.2: Agent Graph for the paper-review program (left) and the research-brief program (right). Gold borders mark agents that run in parallel; the dashed box runs only when its condition holds.

```
terminal
$ algo ask "build a team that reviews a research paper and drafts a decision letter"
```

Behind the command is a small agentic loop, shown in Figure 3.3:

1. A model receives your request together with a concise guide to **AlgoLang**'s rules and an example.
2. Its program is compiled by the real **AlgoLang** compiler.
3. If there are errors, the exact compiler messages are sent back to the model to fix.
4. This repeats up to three times. A program is accepted only when it compiles with **zero errors**; then it is saved and printed, and `--run` runs it immediately.




Figure 3.3: The write–compile–repair loop behind `algo ask` and Studio's Ask AI.

The output shows each attempt. Here a first draft used an undefined placeholder and called a function; the compiler's messages were returned to the model, and the second attempt compiled:

```
terminal
→ attempt 1: asking claude-sonnet-5-5 to write the program…
✗ attempt 1: 2 compile error(s) — sending them back to be fixed
    line 2: E109 agent Reviewer: goal mentions {manuscript} but there is no parameter
       ↪  'manuscript'
    line 7: E101 'summarise' is not an agent — in AlgoLang every unit of work is an agent …
→ attempt 2: asking claude-sonnet-5-5 to write the program…
✓ attempt 2: compiles with no errors
```

Generated programs still need review

The compiler guarantees that a generated program is *well-formed*: names, types, tools and policies are consistent. It cannot guarantee that the program does what you intended, or that its goals, thresholds and forbidden attributes are the right ones. Read every generated program before you run it live, exactly as you would review code written by a colleague.

`algo ask` needs `ANTHROPIC_API_KEY` and the `anthropic` package (Section 2.5). The model can be changed with the environment variable `ALGO_ASK_MODEL`.

3.5 Agentic without AI: the wizard

`algo wizard` builds a program by asking six short questions. Pressing Enter accepts each default, so a complete program takes seconds:

```
terminal
$ algo wizard
1. What should your AI system do [answer student questions about AI]: help students prepare
   ↪  for viva exams
2. Choose a design pattern:
   1. Pipeline — research, write, then edit, one after another
   2. Fan-out / fan-in — plan the parts, work on each in parallel, combine
   3. Committee — three experts answer in parallel, a judge decides
   4. Critic & revise — draft, score, redraft if the score is low
   5. Router — classify the input and send it to the right specialist
   6. Guardrail — safety check first, then do the work
   Pattern number [2]: 3
3. Name of the input (one word) [request]: question
4. Send low-confidence decisions to a human? (y/n) [y]:
   Confidence threshold (0-1) [0.75]: 0.8
5. Forbid protected attributes in decisions? (y/n) [y]:
   Which ones [gender, caste, religion, nationality]:
6. Token budget per agent [4000]: 3000
✓ wrote help_students_prepare_for_viva.algo (committee pattern) — it compiles with no errors.
```

The wizard's programs are built from the patterns of Chapter 17, with human review, budgets and protected-attribute rules placed on the agent that makes the final decision. They always compile, and they are a good starting point to edit by hand or in Studio.

4

Your First Program

This chapter builds a small teaching assistant: one agent explains a topic, a second writes quiz questions on the explanation, and a third checks the explanation's accuracy. Along the way you will meet every part of an **AlgoLang** program.

4.1 Create a starter

terminal

```
$ algo new mylesson
✓ created mylesson.algo
  next:  algo run mylesson.algo --arg "topic=Neural networks"
```

Open `mylesson.algo` in any editor:

mylesson.algo

```
model smart = "claude-sonnet-5-5"
model fast  = "claude-haiku-5-5"

agent Explainer(topic: text) -> text {
    role  "Friendly professor"
    goal  "Explain {topic} to a first-year student in 5 sentences"
    model fast
}

agent QuizMaker(lesson: text) -> list {
    role  "Exam setter"
    goal  "Write three short quiz questions on this lesson: {lesson}"
    model fast
}

agent Checker(lesson: text) -> score {
    role  "Senior reviewer"
    goal  "Score this lesson 0 to 1 for accuracy: {lesson}"
    model smart
    policy {
        require human when confidence < 0.70
    }
}
```

```
flow main(topic: text) {
    lesson = Explainer(topic)
    [quiz, quality] = par { QuizMaker(lesson), Checker(lesson) }
    if quality < 0.75 {
        lesson = Explainer(topic)
    }
    emit lesson, quiz
}
```

4.2 Reading the program

Models

model gives a short name to a model identifier. Agents refer to the short name, so changing models later is a one-line edit.

Agents

Each **agent** has typed parameters, a return type after `->`, and clauses. The **goal** is the instruction the model receives; `{topic}` is replaced by the argument's value when the agent runs.

Return types

`Explainer` returns **text**, `QuizMaker` a **list**, and `Checker` a **score**—a number from 0 to 1. Only scores and numbers can be compared.

Policy

`Checker` sends any result whose confidence is below 0.70 for human review.

Flow

`flow main` is the entry point. Its input `topic` comes from the command line.

Parallelism

par runs `QuizMaker` and `Checker` at the same time; their results are bound to `quiz` and `quality` in order.

Branching

If the quality score is below 0.75, the explanation is regenerated.

Output

emit returns the final values from the flow.

4.3 Check, then run

terminal

```
$ algo check mylesson.algo
✓ mylesson.algo: 3 agents, 1 flow(s), 0 tool(s) — no errors

$ algo run mylesson.algo --arg "topic=Neural networks"
▶ flow main  run=a8a5732e  backend=mock
    topic = 'Neural networks'
  → Explainer          conf=0.88  «Explainer #4348» Explain Neural networks to a first-…
  → QuizMaker          conf=0.78  [3 items]
  → Checker            conf=0.89  0.61
```

```
terminal

  → Explainer          conf=0.88  «Explainer #4348» Explain Neural networks to a first-…
■ emitted:
    • «Explainer #4348» Explain Neural networks to a first-year student in 5 sentences
    • item 1 for: Write three short quiz questions on this lesson: …
    • item 2 for: Write three short quiz questions on this lesson: …
    • item 3 for: Write three short quiz questions on this lesson: …
■ 4 agent calls · ~372 tokens · 0 retries · 0 escalated · 0 blocked · audit →
    ↪  runs/mylesson.audit.jsonl
```

Each line beginning with → is one agent call, with its confidence and a preview of its output. The `Checker` scored the lesson 0.61, below the flow's 0.75 bar, so the `Explainer` ran a second time—four calls in total.

> **Note. On the mock backend an agent's output is a labelled echo of its goal, such as `«Explainer #4348» Explain Neural networks…`. The number is a fingerprint of the input, so the same input always gives the same output and confidence. This makes runs repeatable for teaching and testing. Run with `--live` to get real model answers (Section 2.5).**

4.4 What just happened

Before running, `algo` compiled `mylesson.algo` to Python in `build/mylesson.py`, after checking every name, argument count, type, model and tool. At run time each agent call passed through the runtime's policy checks and was written to the audit log `runs/mylesson.audit.jsonl`—one JSON line per call, recording the model, a hash of the inputs, the confidence, the token count and the outcome. Chapter 12 describes this in detail.

4.5 Try it yourself

1. Change `Checker`'s threshold to `0.95` and run again. How many results are now escalated?
2. Add a `Summariser(lesson: text) -> text` agent and **`emit`** its output as a third value.
3. Call an agent that does not exist, for example `x = Translate(lesson)`, and read the compiler's message.

PART II

The Language



5

Programs and Lexical Structure

5.1 Source files

An **AlgoLang** program is a single UTF-8 text file with the extension `.algo`. It consists of top-level declarations in any order:

Declaration	Form	Purpose
`model`	`model name = "id"`	Names a model identifier
`tool`	`tool web.search`	Declares a capability agents may be granted
`agent`	`agent N(p: t) -> t { … }`	Declares a unit of work
`flow`	`flow main(p: t) { … }`	Orchestrates agents

Every program must contain exactly one `flow main`, which is where execution starts (error **E111** otherwise).

5.2 Comments, whitespace and semicolons

- A comment starts with `//` and runs to the end of the line.
- Whitespace, including newlines, separates tokens and is otherwise ignored. Indentation has no meaning.
- Semicolons are allowed and ignored, so `a = A(x); b = B(a)` on one line is the same as two lines.

5.3 Identifiers

Identifiers match `[a-zA-Z_][a-zA-Z0-9_]*`. By convention agents use `PascalCase` (`Researcher`), and variables, parameters and models use `lower_case` (`facts`, `smart`). Names of agents and flows share one namespace; defining the same name twice is error **E107**.

Tool names are *dotted* identifiers with at least two parts, such as `web.search` or `file.read`.

5.4 Keywords

Group	Keywords
Declarations	`model` `tool` `agent` `flow`
Agent clauses	`role` `goal` `uses` `model` `policy`
Policy rules	`budget` `tokens` `retry` `timeout` `require` `human` `when` `confidence` `forbid`
Flow statements	`par` `for` `in` `if` `else` `emit`
Literals	`true` `false`
Types	`text` `score` `list` `json` `bool`

5.5 Literals

- **Strings** are enclosed in double quotes. Backslash escapes such as `\n` and `\"` are supported.
- **Numbers** are written as `6000` or `0.75`. Negative and exponent forms are not part of version 0.1.
- **Booleans** are `true` and `false`.

5.6 Placeholders in goals

Inside a `goal` string, `{name}` is a placeholder for the parameter `name`. When the agent runs, the placeholder is replaced by the argument's value (a list is joined with `"; "`). The compiler checks that every placeholder names a real parameter (**E109**).

```
agent Translator(passage: text, language: text) -> text {
    goal "Translate into {language}, keeping technical terms: {passage}"
}
```

5.7 Operators

Operator	Use
`->`	Separates an agent's parameters from its return type
`=`	Assignment in flows; default values in parameters; keyword arguments
`< <= > >= == !=`	Comparisons in `if` conditions
`[ , ]`	Binds several results of a `par` block

AlgoLang has no arithmetic or string operators. Computation is done by agents; flows only route values between them.

6

Types and Results

6.1 The five types

Every agent parameter, agent return value and flow input has one of five types.

Type	Meaning	Typical use	Mock value
`text`	Free text	Facts, drafts, summaries, letters	labelled echo of the goal
`score`	Number from 0 to 1	Quality, risk, acceptance likelihood	0.55–0.95
`list`	Ordered list of items	Criteria, sub-tasks, questions	3–4 items
`json`	Structured object	Extracted fields, records	small object
`bool`	True or false	Pass/fail checks	true or false

An unknown type name is error **E105**. Literals have their own types: a string literal is `text`, `true` and `false` are `bool`, and a number literal is a *number*, which can be compared with scores.

6.2 Where types matter

The compiler uses types in three places:

1. **Comparisons.** An `if` condition may compare only scores, numbers and booleans. Comparing text is error **E110**:

```
summary = Summariser(doc)          // text
if summary < 0.5 { emit summary }  // E110: 'summary' is text, not a score
```

2. **Parallel loops.** `par for` iterates over a `list`; anything else is error **E114**.
3. **Variables.** Each variable takes the type of the agent that produced it. A `par` block bound to a single name produces a `list`; the loop variable of `par for` is `text`.

Caution. In version 0.1 the compiler does not yet check that an argument's type matches the parameter's declared type (for example, passing a `list` where `text` is expected). Lists passed to text parameters are joined with `"; "` when the goal is rendered. Full argument type checking is planned for version 0.2.

6.3 Results: value plus provenance

Every agent call returns a *Result*, not a bare value. A Result carries:

Field	Meaning
`value`	The agent's output, of its declared return type
`confidence`	A number from 0 to 1 reported with the output
`agent`	Which agent produced it
`call_id`	A short identifier linking it to its audit record
`status`	`ok`, `escalated` (sent for human review) or `approved` (a human approved it)

In flows you use a Result exactly like its value: passing it to another agent passes the value, and comparing it compares the value. The extra fields are visible in the audit log, in notebooks (`algo_calls`), and to Python code that uses the generated program.

Uncertainty is part of the answer

Hiding uncertainty encourages over-trust in AI output. By making confidence part of every result, **AlgoLang** makes it natural to route uncertain results to people (Chapter 8) and to report uncertainty to end users. Remember, however, that a model's *self-reported* confidence is not a calibrated probability (Section 18.4).

6.4 Flow inputs

Flow parameters are declared with types like agent parameters:

```
flow main(topic: text, audience: text) { ... }
```

Values are supplied on the command line with `--arg "name=value"`, in notebooks with the same option, or interactively when omitted.

Note. In version 0.1 every flow input arrives as text, whatever its declared type. Declare flow inputs as `text` and let an agent convert them if needed.

7

Models, Tools and Agents

7.1 Models

```
model smart = "claude-sonnet-5-5"
model fast  = "claude-haiku-5-5"
```

A **model** declaration binds a short name to a model identifier. Agents select a model by short name with the **model** clause; an unknown name is error **E106**. An agent without a **model** clause uses `claude-sonnet-5-5`.

> **Tip.** Name models by their role in your system—`smart`, `fast`, `cheap`—not by product. When a new model is released you change one line, and every agent that uses that role moves with it.

7.2 Tools

```
tool web.search
tool file.read
```

A **tool** declaration announces a capability that the program may grant. Declaring a tool gives it to no one: each agent must list the tools it needs in a **uses** clause, and listing a tool that was never declared is error **E104**.

Least privilege

An agent can only be granted capabilities that the program declares openly at the top of the file, and only the agents that list a tool receive it. A reviewer can see every capability of a program, and which agent holds it, without reading any agent's code. This is the security principle of least privilege applied to AI agents.

> **Caution.** Tools are *capability declarations* that the compiler enforces. Since version 0.2 they are also executable: the runtime calls the registered Python function (built-ins `calc.eval`, `file.read`, `kb.search`, or your own plugin) and records every call in the audit log (Chapter 15). Since version 0.3 a tool can also come from any MCP server: `tool kb.search_policies from mcp "company-kb"` (Chapter 16).

7.3 Agents

An agent declaration has a name, typed parameters, a return type and a body of clauses:

agent anatomy

```
agent CriterionReviewer(criterion: text, paper: text, depth: text = "detailed") ->
    ↪ text {
    role   "Domain reviewer"
    goal   "Give a {depth} review of {paper} strictly on: {criterion}"
    uses   file.read, web.search
    model  fast
    policy {
        budget tokens 4000
        retry 1
    }
}
```

7.3.1 Parameters

Each parameter is `name: type`, optionally with a default literal: `tone: text = "academic"`. A parameter with a default may be omitted by the caller. Parameter names must not appear in the agent's **`forbid`** list (E108).

7.3.2 Clauses

Clause	Required	Meaning
`goal`	**yes**	The work the agent must do, in plain language. Placeholders `{param}` are filled when it runs. Missing goal: E112.
`role`	no	The capacity in which the agent acts; becomes its persona (system prompt in live mode).
`uses`	no	Comma-separated tools the agent may use; each must be declared (E104).
`model`	no	Short name of a declared model (E106).
`policy`	no	Governance rules—see Chapter 8.

Clauses may appear in any order. A clause may be repeated; for **`uses`** the lists are combined, and for the others the last one wins.

7.3.3 What the model receives

At run time the runtime renders the agent into a prompt with three parts:

rendered prompt

```
ROLE: Domain reviewer
GOAL: Give a detailed review of LG-CEF … strictly on: Methodology & rigour
TOOLS: file.read, web.search
```

In live mode the role becomes the system persona and the model is asked to reply with a JSON

object holding its `value` and `confidence`, in the shape required by the agent's return type.

7.4 Writing good agents

1. **One job per agent.** If a goal contains "and then", split it into two agents and connect them in a flow.
2. **Write goals as instructions to a capable colleague.** State the output you expect: length, format, audience.
3. **Choose the narrowest return type.** If the flow will branch on it, return a **`score`** or **`bool`**, not **`text`**.
4. **Grant the fewest tools.** An agent that only rewrites text needs no tools at all.
5. **Always set a budget** for agents that will run live.
6. **Gate decisions that affect people** with **`require human when confidence < …`**.

8

Policies

A **policy** block attaches governance rules to an agent. Policies are part of the agent's declaration, so they travel with it, appear in its audit records and cannot be forgotten by a caller.

```
agent Editor(reports: list, ethics: text) -> score {
    role  "Editor-in-Chief"
    goal  "Weigh {reports} and {ethics}; score acceptance likelihood 0 to 1"
    policy {
        budget tokens 6000
        retry 2
        timeout 60
        require human when confidence < 0.75
        forbid gender, caste, religion, nationality
    }
}
```

8.1 Summary of rules

Rule	Checked	Effect
`budget tokens N`	run time	Stops the call before it is sent if the prompt is estimated above `N` tokens; in live mode also caps the reply length
`retry N`	run time	Retries a failed call up to `N` more times
`timeout S`	run time	Treats a call that took longer than `S` seconds as failed
`require human when confidence < X`	run time	Marks a result with confidence below `X` as `escalated`, or asks a person to approve it
`forbid a, b, …`	compile *and* run time	Rejects agents that take a forbidden attribute as a parameter; stops calls whose inputs mention one

8.2 Token budgets

`budget tokens N` protects against runaway cost. Before every call the runtime estimates the prompt's size (about four characters per token). If the estimate exceeds `N`, the call is not sent: the run stops with a policy violation. In live mode the budget also sets the maximum length of the model's reply (capped at 8,000 tokens; without a budget the reply is limited to 2,000 tokens).

Tip. A budget that is too small for an agent's normal input is a design signal: the agent is being asked to do too much at once. Split the work, or summarise the input with another agent first.

8.3 Retries and timeouts

`retry N` makes the runtime try a failed call up to `N` more times—useful for transient network or service errors. Policy violations are never retried. `timeout S` marks a call as failed if it took longer than `S` seconds; the check is made when the call returns, and a timed-out call can then be retried.

8.4 Human oversight

`require human when confidence < X` is the human-in-the-loop gate. When an agent's result has confidence below `X`:

- By default the result is marked `escalated`: the flow continues, the run summary counts the escalation, and the audit record carries `"status": "escalated"` so that a person can review it afterwards.
- With `--interactive` (terminal or notebook) the run pauses and shows the result. Typing `y` records `approved`; any other answer keeps it `escalated`.

```
terminal

  → Reviewer          conf=0.68  0.78  ⚠ ESCALATED to human (conf < 0.70)
```

Meaningful human oversight

Oversight is only meaningful if people see the right cases. Put the gate on the agents whose outputs affect people—decisions, scores, letters—and choose thresholds deliberately. Review the escalation count in every run summary: if it is always zero, the threshold may be too low to matter; if it is always high, the agent or its model may not be fit for the task.

8.5 Forbidden attributes

`forbid` names attributes that must not influence an agent's work—typically protected characteristics such as gender, caste, religion, nationality or age. It acts twice:

1. **At compile time**, an agent may not declare a parameter with a forbidden name (**E108**):

   ```
   terminal

   line 12: E108 agent Screener takes forbidden attribute 'caste' as an input
   ```

2. **At run time**, before each call, the runtime searches the rendered prompt (role, goal with all arguments filled in, and tools) for each forbidden word, as a whole word and ignoring

case. If one is found, the call is not made and the run stops:

```
terminal

  → EthicsAuditor      conf=0.79  «EthicsAuditor #1139» Check Does author nationality …
✗ POLICY VIOLATION: Editor: input mentions forbidden attribute 'nationality'
```

The blocked call is recorded in the audit log with `"status": "blocked"` and the reason, and the program exits with code 2.

> **Caution. The run-time check is *lexical*: it finds the forbidden words themselves, not their proxies. A surname, a home town or a school can still reveal caste, religion or nationality. `forbid` is a strong safeguard against accidental and obvious leakage and a clear statement of intent, but it is not a guarantee of fairness. Combine it with careful input design and with audits of outcomes across groups (Chapter 18).**

8.6 Where policies are recorded

Every audit record includes the agent's full policy, so a reviewer can see which rules were in force for each call:

from an audit record

```
"status": "ok",
"policy": {"budget_tokens": 6000, "retry": 2}
```

9

Flows

A **flow** connects agents. It has typed parameters and a body of statements, and it can do exactly five things: call an agent, run agents in parallel, map an agent over a list in parallel, branch on a comparison, and emit results. It cannot compute anything itself, and it cannot be called—every program's entry point is `flow main`.

9.1 Calling agents

```
facts  = Researcher(topic)                       // positional
brief  = Writer(facts, tone = "plain-English")   // positional + keyword
letter = DecisionLetter(verdict = v, reports = r) // keywords in any order
```

Positional arguments bind to parameters in order; keyword arguments bind by name. Parameters with defaults may be omitted. The compiler reports too many arguments, unknown names, duplicates and missing required arguments as **E102**.

A call may also stand alone as a statement when only its effect matters, for example an agent that files a report:

```
Notifier(summary)
```

9.2 Variables

Assignment binds a name to an agent's result. Variables need no declaration; a variable's type is its agent's return type. Using a name that has not been assigned (and is not a flow input) is **E103**. A variable may be reassigned, as in the redraft pattern:

```
draft = Writer(facts)
if Reviewer(draft) < 0.8 { draft = Writer(facts, tone = "rigorous") }
```

9.3 Parallel blocks: `par`

```
[formal, simple, hindi] = par {
    Writer(facts),
    Writer(facts, tone = "plain-English"),
    Translator(facts, language = "Hindi")
}
```

All calls inside **`par`** run at the same time. The bracketed names receive the results in the order the calls are written, whatever order they finish in. The number of names must equal the number of calls (**E113**). Assigned to a single name, a **`par`** block yields a **`list`**:

```
opinions = par { ExpertA(q), ExpertB(q), ExpertC(q) }   // list of three results
```

9.4 Parallel map: `par for`

```
criteria = Planner(paper)                                  // list
reports  = par for c in criteria { CriterionReviewer(c, paper) }
```

`par for` runs one call per item of a list, all concurrently, and collects the results in the list's order. The source must be a **`list`** (**E114**); the loop variable is visible only inside the braces. This is the "fan-out / fan-in" pattern of multi-agent systems in one line.

9.5 Branching: `if` and `else`

```
verdict = Editor(reports, ethics)
if verdict >= 0.5 {
    letter = AcceptLetter(reports)
} else {
    letter = RejectLetter(reports)
}
```

A condition compares two values with `<`, `<=`, `>`, `>=`, `==` or `!=`. Each side may be a variable, a number or an agent call that returns a **`score`**, so `if Reviewer(draft) < 0.8 { … }` is valid. Only scores, numbers and booleans can be compared (**E110**).

9.6 Returning results: `emit`

```
emit verdict, letter
```

`emit` adds values to the flow's output. A flow may emit several times; the outputs accumulate in order. The terminal shows them after the run; notebooks place them in `algo_result`; Python callers receive them as a list.

9.7 Complete example

paper_review.algo — flow

```
flow main(paper: text) {
    criteria = Planner(paper)
    reports  = par for c in criteria { CriterionReviewer(c, paper) }
    ethics   = EthicsAuditor(paper)
    verdict  = Editor(reports, ethics)
    letter   = DecisionLetter(reports, verdict)
    emit verdict, letter
}
```

The notebook extension draws this flow as a graph (Chapter 13). Its shape is shown in Figure 9.1.




Figure 9.1: Data flow of `paper_review.algo`. The gold-edged node runs once per criterion, in parallel.

10

Compile-Time Errors

The compiler checks the whole program before generating any code and reports *every* error it finds, each with a code and a line number. A program with errors is never built or run.

terminal

```
$ algo check examples/bad_example.algo
✗ bad_example.algo: 8 error(s)
  line 5: E109 agent Summariser: goal mentions {document} but there is no parameter 'document'
  line 5: E104 agent Summariser uses tool 'email.send', which is not declared (add `tool
     ↪  email.send`)
  line 5: E106 agent Summariser: unknown model 'turbo'
  line 12: E108 agent Screener takes forbidden attribute 'caste' as an input
  line 19: E102 Summariser takes 1 argument(s) (doc), got 2 positional
  line 20: E101 'summarise_text' is not an agent — in AlgoLang every unit of work is an agent
     ↪  …
  line 21: E110 's' is text, not a score — only scores/numbers can be compared
  line 22: E103 undefined variable 'missing'
```

Errors about an agent's declaration are reported at the line where the agent starts.

10.1 Error catalogue

E100 Syntax error

The source does not match the grammar. The message shows the line and column with a pointer. Common causes: a missing `}`, a missing `->` return type, an unquoted goal, or a keyword used as a name.

E101 Not an agent

A call names something that is not a declared agent. This is **AlgoLang**'s central rule. If the name is a flow, the message says that flows orchestrate and cannot be called.

```
t = summarise_text(doc)   // E101 — declare an agent instead
```

Fix: declare `agent summarise_text(doc: text) -> text { goal "…" }`, or call an existing agent.

E102 Wrong arguments

Too many positional arguments, an unknown keyword, a parameter given twice, or a required parameter missing.

```
s = Summariser(doc, doc)        // takes 1 argument(s) (doc), got 2 positional
w = Writer(facts, style = "x")  // Writer has no parameter 'style'
```

E103 Undefined variable

A name is used before it is assigned and is not a flow input. Check spelling and statement order.

E104 Undeclared tool

An agent **`uses`** a tool that the program never declares. **Fix:** add `tool email.send` at top level—a visible, reviewable decision to grant that capability.

E105 Unknown type

A parameter or return type is not one of **`text`**, **`score`**, **`list`**, **`json`**, **`bool`**.

E106 Unknown model

An agent's **`model`** clause names a model that was not declared with **`model`**.

E107 Defined twice

Two agents or flows share a name. Agents and flows share one namespace.

E108 Forbidden attribute as input

An agent declares a parameter whose name appears in its own **`forbid`** list.

```
agent Screener(caste: text) -> score {   // E108
    goal "Score applicant {caste}"
    policy { forbid caste }
}
```

Fix: remove the parameter. If the attribute is genuinely needed—for example, to *audit* outcomes across groups—give that job to a separate auditing agent whose policy does not forbid it, and document why.

E109 Unknown placeholder

A **`goal`** contains `{name}` but the agent has no parameter called `name`. Usually a typo, as in `{document}` for parameter `doc`.

E110 Comparing a non-score

An **`if`** condition compares a value that is not a score, number or boolean—typically **`text`**. **Fix:** add an agent that returns a **`score`** and compare that.

E111 No entry point

The program has no `flow main`.

E112 Agent without a goal

Every agent must state its work in a **`goal`** clause.

E113 Mismatched parallel binding

`[a, b] = …` needs a **`par`** block on the right with the same number of calls.

E114 `par for` over a non-list

The source of **`par for`** must be a **`list`**, such as the output of a planning agent.

E115 Tool not allowed by organisation policy

An agent **`uses`** a tool that is missing from `allowed_tools` in `algo.config.json` (Chapter 15). Ask your administrator to approve the tool, or remove it. Org-forbidden attributes are reported as **E108**, before anything runs.

E116 Circular import

A file imports itself, directly or through other files, with **`use`**. Move the shared agents into a separate module.

E117 Uncertain value compared without its confidence

An `uncertain<T>` result is compared in an **`if`** without also checking its confidence in the same condition. Write `if risk > 0.8 and risk.confidence >= 0.7`. The rule stops a decision from being taken on a score the samples disagree about.

E118 Bad confidence read

Only `<result>.confidence` can be read in a condition, and only on an agent result (not on a flow input).

E119 Eval block error

An **`eval`** block names a flow, an input, an agent, a tool or a status that does not exist, or a case is missing one of the flow's inputs.

E120 Unknown MCP server

`tool x from mcp "server"` names a server that is not listed under `mcp_servers` in `algo.config.json`.

E121 Bad policy value

An unknown currency in `budget cost` (use `usd` or `inr`), an unknown unit in `budget energy` (use `wh` or `kwh`), or `samples` outside 1–15.

10.2 Run-time outcomes

Some problems can only be detected while the program runs. They are not compile errors; each stops the run with a clear message and an exit code (Chapter 11).

Outcome	Exit	Cause
Policy violation	2	A forbidden attribute in an agent's input, or a prompt over its token budget
Agent call failed	3	The model or service failed after all retries, or a timeout
Missing input / bad option	1	A flow input was not supplied, or `--arg` was not `name=value`

PART III

Toolchain and Runtime



11

The `algo` Command

All work with **AlgoLang** outside notebooks goes through one command, `algo`. On Windows it is `algo.bat`; on Linux and macOS it is the shell script `algo`. Both use the private `.venv` created by the installer when it exists.

terminal

```
$ algo --help
usage: algo [-h] [--version] command ...

AlgoLang 0.2.0 — every unit of work is an agent

positional arguments:
  command
    check     check a program for errors
    build     compile to Python
    run       compile and run flow main
    new       create a starter program
    doctor    check that the environment is ready
    notebook  open the AlgoLang notebook in Jupyter (installs Jupyter if needed)
```

11.1 Commands

Command	What it does
`algo check FILE.algo`	Parses and checks the program; reports all errors; writes nothing
`algo build FILE.algo [-o OUT.py]`	Compiles to Python; default output `build/FILE.py` next to the source
`algo run FILE.algo [options]`	Compiles, then runs `flow main`
`algo new NAME`	Creates `NAME.algo` from a ready-to-run three-agent template
`algo doctor`	Checks Python, the parser, live-mode readiness and a compiler self-test
`algo notebook`	Opens `AlgoLang_Notebook.ipynb` in Jupyter, installing Jupyter the first time
`algo`	Numbered menu of every option
`algo shell`	Interactive shell: type declarations one at a time
`algo studio [--port N]`	AlgoLang Studio, the graphical IDE in your browser
`algo ask "…" [-o F] [--run]`	AI writes a program from a description (compile-and-repair loop)
`algo wizard`	Build a program by answering questions, no AI needed
`algo --version`	Prints the version

11.2 Options for `run`

Option	Meaning
`--arg "name=value"`	Supplies a flow input; repeat for several inputs. Inputs not supplied are asked for interactively
`--live`	Runs agents on real Claude models (needs `ANTHROPIC_API_KEY`)
`--interactive`	Pauses on low-confidence results for human approval
`--audit-dir DIR`	Writes audit logs to `DIR` (default `runs`)

terminal

```
$ algo run examples/paper_review.algo \
      --arg "paper=LG-CEF: lesion-guided ensemble for DR grading" \
      --interactive --audit-dir audit/2026-10
```

11.3 Exit codes

Code	Meaning
0	Success
1	Compile errors, a missing file or input, or a malformed option
2	A policy violation stopped the run
3	An agent call failed after its retries

Scripts and continuous-integration jobs can rely on these codes; for example, a CI job can run `algo check` on every `.algo` file and fail the build on exit code 1.

11.4 Environment variables

Variable	Meaning
`ANTHROPIC_API_KEY`	API key for live mode
`ALGO_HOME`	Folder containing the runtime; set automatically by `algo`
`ALGO_LIVE=1`	Live mode (set by `--live`)
`ALGO_INTERACTIVE=1`	Interactive human review (set by `--interactive`)
`ALGO_AUDIT_DIR`	Audit-log folder (set by `--audit-dir`)

11.5 Running compiled programs directly

`algo build` produces an ordinary Python script that can be run, scheduled or shipped without the compiler:

terminal

```
$ algo build research_brief.algo
✓ compiled research_brief.algo → build/research_brief.py
$ python build/research_brief.py --topic "Federated learning in IoT"
```

The script needs only `algoruntime.py`, found through `ALGO_HOME` or the path recorded at compile time.

12

Runtime Semantics

This chapter defines precisely what happens when a compiled program runs. The reference implementation is `algoruntime.py`.

12.1 Lifecycle of a run

1. The runtime is created with the program's name and a fresh *run identifier*; models and tools are registered; the backend is chosen (mock, or live when `ALGO_LIVE=1`).
2. Each agent declaration becomes a governed callable.
3. `flow main` starts with its inputs and prints a header line.
4. Statements execute in order; **`par`** and **`par for`** execute their calls concurrently.
5. Emitted values accumulate; at the end the runtime prints them with a summary line: calls, estimated tokens, retries, escalations and blocked calls.

12.2 Lifecycle of an agent call

Every agent call passes through the same seven steps, shown in Figure 12.1.




Figure 12.1: The seven steps of every agent call. Gold steps enforce policy.

1. **Bind arguments.** Positional and keyword arguments are matched to parameters; defaults fill the rest. Results passed as arguments contribute their values.
2. **Render the prompt.** Placeholders in the goal are replaced with argument values (lists joined with `"; "`), and the prompt is assembled from role, goal and tools.
3. **Forbid check.** If the prompt contains a forbidden attribute as a whole word (ignoring case), the call is recorded as `blocked` and a policy violation stops the run.
4. **Budget check.** If the prompt's estimated size (characters ÷ 4) exceeds the token budget, the call is recorded as `blocked` and a policy violation stops the run.

5. **Call the model** through the backend, retrying failures up to the **`retry`** count and treating calls longer than **`timeout`** as failures. If all attempts fail, the call is recorded as `failed` and the run stops.
6. **Human gate.** If the confidence is below the **`require human`** threshold, the Result's status becomes `escalated`, or `approved` if a reviewer approves it in interactive mode.
7. **Audit and return.** One audit record is written and the Result is returned to the flow.

12.3 Concurrency

`par` and **`par for`** submit their calls to a thread pool sized to the number of calls and wait for all of them. Results are returned in source order, not completion order, so programs are deterministic in structure even when timing varies. Console output and audit writes are serialised by a lock, so lines never interleave.

> **Note.** If one call in a parallel group fails or violates a policy, the error stops the run after the group's other calls have finished; their audit records are still written.

12.4 Backends

	Mock (default)	Live (`--live`)
Purpose	Teaching, testing, CI, offline demos	Real work
Cost	Free	API credits
Determinism	Same input → same output	Varies between runs
Output	Labelled echo of the goal; shaped by return type	The model's answer, in a JSON envelope
Confidence	Derived from a hash of the input (0.62–0.95)	Reported by the model
Tokens	Estimated	Counted by the API

In live mode, the role becomes the system persona, and the model is instructed to reply only with JSON of the form `{"value": …, "confidence": …}`, where the value's shape matches the return type (a number for **`score`**, an array for **`list`**, and so on). If the reply contains no JSON object, the whole reply is used as the value with confidence 0.5.

12.5 The audit log

Every agent call appends one JSON line to `<audit-dir>/<program>.audit.jsonl`:

one audit record (pretty-printed)

```
{
  "call": "d5a1ba",
  "agent": "Researcher",
  "model": "claude-sonnet-5-5",
```

```
  "backend": "mock",
  "inputs_sha": "23cd4baf6ab210a5",
  "returns": "text",
  "confidence": 0.83,
  "tokens": 93,
  "status": "ok",
  "tools": ["web.search"],
  "policy": {"budget_tokens": 6000, "retry": 2},
  "run": "832d55bb",
  "program": "research_brief",
  "ts": "2026-10-28T11:20:13"
}
```

Field	Meaning
`run`, `call`	Identifiers of the run and of this call
`program`, `agent`	What ran
`model`, `backend`	Which model, and mock or live
`inputs_sha`	First 16 hex digits of the SHA-256 hash of the full prompt
`returns`, `confidence`	Declared return type and reported confidence
`tokens`	Tokens used (estimated on mock)
`status`	`ok`, `escalated`, `approved`, `blocked` or `failed`
`tools`, `policy`	Capabilities and rules in force for this call
`reason`, `error`	Present on `blocked` and `failed` records
`ts`	Local timestamp

Accountability without over-collection

The log stores a *hash* of each prompt, not the prompt itself, and does not store outputs. This lets an auditor verify that a given input produced a given decision—by recomputing the hash—without the log becoming a second copy of sensitive data. If your setting requires full records, store prompts and outputs separately under proper access control, keyed by the call identifier.

The log is append-only plain text, one record per line, so it can be loaded directly into a spreadsheet, `pandas` (`pd.read_json(path, lines=True)`) or any log system.

13

Jupyter and Google Colab

The notebook extension `algomagic.py` lets you write **AlgoLang** directly in Jupyter and Google Colab cells. Each run shows live progress, a results table, and optionally a diagram of the flow and the generated Python.

13.1 Starting

- **Colab:** upload `AlgoLang_Notebook.ipynb` (*File* → *Upload notebook*) and choose *Runtime* → *Run all*. The setup cells install the parser and write the toolchain into the Colab machine.
- **Jupyter:** run `algo notebook` in the **AlgoLang** folder.
- **Any other notebook:** with the **AlgoLang** folder on the Python path, run `%load_ext algomagic`.

13.2 The `%%algo` cell magic

A cell whose first line is `%%algo` contains **AlgoLang** source. Options on that first line control what happens:

First line	Effect
`%%algo --arg "topic=AI"`	Compile and run `flow main` with that input
`%%algo --define`	Add the cell's models, tools and agents to the session
`%%algo --check`	Compile only; report errors or a summary
`--graph`	Draw the flow as a diagram before running
`--python`	Show the generated Python
`--interactive`	Ask for approval of low-confidence results in an input box
`--live`	Use real Claude models
`--name NAME`	Name the program (used for the audit-log file)

a notebook cell

```
%%algo --arg "topic=Neural networks" --graph

flow main(topic: text) {
    lesson = Explainer(topic)
    [quiz, quality] = par { QuizMaker(lesson), Checker(lesson) }
```

```
    emit lesson, quiz, quality
}
```

13.3 Building a program cell by cell

Notebooks are at their best when a program is developed in small steps. Cells marked `--define` add declarations to a *session*; every later run cell is compiled together with them.

cell 1

```
%%algo --define
model smart = "claude-sonnet-5-5"
tool  web.search
```

cell 2

```
%%algo --define
agent Researcher(topic: text) -> text {
    goal  "Find five verified facts about {topic}"
    uses  web.search
    model smart
}
```

cell 3

```
%%algo --arg "topic=Graph neural networks"
flow main(topic: text) {
    emit Researcher(topic)
}
```

- Re-running a define cell *replaces* the agents it defined earlier, so you can edit and re-run freely.
- A define cell is checked before it is accepted; a cell with errors leaves the session unchanged.
- Run cells are not stored, so each can contain its own `flow main`.
- Errors are reported with line numbers *within the cell*; an error in an earlier define cell is reported as such.

13.4 Line magics

Magic	Effect
`%algo_run file.algo --arg "…"`	Run an existing `.algo` file (same options as the cell magic)
`%algo_list`	List the session's define cells and what each defines
`%algo_reset`	Clear the session
`%algo_help`	Show help

13.5 Results in Python

After each run, two variables are available to ordinary Python cells:

a Python cell

```
print(algo_result[0])                # first emitted value

import pandas as pd
pd.DataFrame(algo_calls)[["agent", "model", "confidence", "status", "tokens"]]
```

`algo_result` is the list of emitted values. `algo_calls` is a list of dictionaries, one per agent call, with the audit-record fields of Section 12.5 plus the call's `output`.

13.6 What a run displays

1. **Agent graph** (with `--graph`): inputs as cream ovals, agents as navy boxes, parallel agents with gold borders, conditions as gold diamonds, branch agents dashed, and the output. When Graphviz is installed (as on Colab) the graph is drawn with arrows; otherwise a column layout lists what feeds each agent.
2. **Progress lines**: one per agent call as it completes.
3. **Results table**: agent, model, confidence, status (human-review cases highlighted), tokens and output, followed by the emitted values and the audit-log path.
4. **Problems**: compile errors as a table with codes and cell line numbers; policy violations and failures as a red panel above the calls that did run.

13.7 Live mode in Colab

Store your key as a Colab *secret* so that it never appears in the notebook: click the key icon in Colab's left sidebar, add a secret named `ANTHROPIC_API_KEY`, allow notebook access, then run:

```
import os
from google.colab import userdata
os.environ["ANTHROPIC_API_KEY"] = userdata.get("ANTHROPIC_API_KEY")
```

Cells with `--live` then call Claude. Without a key, a live cell stops safely with a message and no charge.

14

Inside the Compiler

The compiler `algoc.py` is about 600 lines of Python. It is deliberately small so that students can read it end to end, and so that new language features can be prototyped in an afternoon.

14.1 Pipeline




Figure 14.1: Compilation pipeline. Any diagnostic stops the pipeline before code generation.

1. **Parse.** The grammar in `grammar.lark` (Appendix A) is loaded by the Lark parser with the Earley algorithm, which tolerates the overlap between keywords and names without extra rules. Syntax errors become **E100** with a source excerpt.
2. **Build the AST.** The parse tree is converted into a `Program` with dictionaries of models, tools, agents (`Agent`: name, parameters, return type, role, goal, uses, model, policy) and flows (`Flow`: name, parameters, body). Duplicate names give **E107**.
3. **Check.** The `Checker` validates each agent (types, placeholders, tools, model, forbidden parameters, goal present) and walks each flow with a type environment, checking calls (**E101**, **E102**), variables (**E103**), comparisons (**E110**), parallel bindings (**E113**) and loops (**E114**). All diagnostics are collected and sorted by line.
4. **Generate.** The `CodeGen` emits a Python module that imports the runtime, registers models and tools, defines one governed callable per agent, and one Python function per flow.

14.2 Generated code

The generated code is readable and is the best way to understand the semantics precisely. For `research_brief.algo`:

build/research_brief.py (excerpt)

```
rt = Runtime(program='research_brief')
rt.model('smart', 'claude-sonnet-5-5')
rt.model('fast', 'claude-haiku-5-5')
```

```
rt.tool('web.search')

Researcher = rt.agent(AgentSpec(
    name='Researcher', params=[('topic', 'text', None)], returns='text',
    role='Senior research analyst',
    goal='Find five verified, recent facts about {topic}, with sources',
    uses=['web.search'], model='smart', policy={'budget_tokens': 6000, 'retry': 2}))

def flow_main(topic):
    rt.begin_flow('main', {'topic': topic})
    facts = Researcher(topic=topic)
    formal, simple = rt.par(lambda: Writer(facts=facts),
                            lambda: Writer(facts=facts, tone='plain-English'))
    quality = Reviewer(draft=formal)
    if rt.value(quality) < rt.value(0.80):
        formal = Writer(facts=facts, tone='rigorous academic')
    rt.emit(formal, simple)
    return rt.end_flow()
```

Observe the translation rules:

AlgoLang	Generated Python
`agent A(…) -> t { … }`	`A = rt.agent(AgentSpec(…))`
`A(x, k = y)`	`A(p1=x, k=y)` — positional arguments become keywords
`par { A(x), B(x) }`	`rt.par(lambda: A(…), lambda: B(…))`
`par for v in xs { A(v) }`	`rt.par_map(lambda v: A(…), xs)`
`if a < 0.8 { … }`	`if rt.value(a) < rt.value(0.80): …`
`emit a, b`	`rt.emit(a, b)`
`flow main(p: t)`	`def flow_main(p): …` plus a command-line entry point

14.3 Extending the language

A typical feature touches four places. Suppose you want a new policy rule `max calls N`:

1. **Grammar:** add `| "max" "calls" NUMBER -> max_calls` to `policy_rule`.
2. **AST:** in `to_ast`, store `a.policy["max_calls"]`.
3. **Checker:** optionally validate the value.
4. **Runtime:** count calls per agent in `_invoke` and raise `PolicyViolation` when the limit is exceeded.

Then add an example, a test, and a paragraph to this book. Chapter 20 explains how to propose such a change for the official language.

15

Enterprise Edition: Domains, Governance and the SDK

Version 0.2 takes **AlgoLang** from the classroom to the organisation. A university, hospital, bank or ministry rarely needs one multi-agent program. It needs dozens of them across many departments, all under the same rules, all auditable, and usable by staff who will never write code. This chapter describes the six additions that make that possible:

1. **Modules**: `use` imports for building large systems from small ones.
2. **Org policy**: one `algo.config.json` that governs every program.
3. **120 domain packs** covering 20 sectors.
4. **Governance**: a hash-chained audit log, a human review queue and reports.
5. **Executable tools and scale**: plugin tools, a live tool-use loop, batch runs and a global concurrency limit.
6. **One SDK, three modes**: command line, graphical Studio and the new Prompt-based UI.

15.1 Modules

A file can import agents from another file, or from a domain pack. Imported agents are used through their alias, so names never clash.

examples/enterprise/claims_pipeline.algo

```
use "common/intake.algo" as intake
use pack insurance.fraud_screening as fraud
use pack insurance.claims_triage as claims

policy {
    budget tokens 8000
    forbid religion, caste
}

flow main(claim: text) {
    c     = intake.Normaliser(claim)
    views = par { fraud.PatternAnalyst(c), fraud.DocumentExaminer(c), fraud.Adjuster
    ↪ (c) }
    risk  = fraud.FraudPanel(views)
    level = claims.Complexity(c)
    if risk > 0.7 {
        note = fraud.Referral(views, risk)
```

```
        emit c, risk, note
    }
    route = claims.Routing(c, level)
    emit c, risk, route
}
```

- `use "path.algo" as x` imports a file. The path is relative to the importing file.
- `use pack sector.name as x` imports a domain pack. Packs are found in `packs/` and in any folder listed in the `ALGO_PACKS` environment variable.
- A top-level **`policy`** block is the file's default. Every agent in the file inherits it, and its own policy can only make it stricter.
- Errors inside an imported file are reported with that file's name. Circular imports are rejected.

15.2 Organisation policy

`algo init` writes `algo.config.json`. The runtime looks for it in the current folder and its parents. Its rules are merged into the policy of *every* agent in *every* program, and **the stricter rule always wins**:

- forbidden attributes are joined together;
- budgets take the smaller value;
- human-review thresholds take the higher value.

No program can relax the organisation's rules.

Key	Effect
`forbid`	Attributes no agent may take as input, checked at compile time (**E108**) and at run time
`max_budget_tokens`	Upper limit on any agent's `budget tokens`
`min_human_below`	Every agent is escalated to a human below this confidence
`allowed_tools`	Only these tools may be declared (`null` allows all)
`max_concurrency`	Global limit on simultaneous model calls, shared by all threads and batch workers
`max_run_tokens`	Token cap for one complete run
`cache`	Reuse identical answers from a SQLite cache at zero tokens
`models`, `tools`, `plugins`	Model aliases, tool settings, Python files that register company tools

15.3 The domain library: 120 packs in 20 sectors

Each pack is an ordinary `.algo` file in `packs/<sector>/`. Every pack passes the compiler and runs offline. Packs follow one of four patterns from Chapter 17:

pipe a chain of specialists;

fan parallel specialists and a synthesiser;
committee parallel reviewers and a scoring panel;
router a classifier that sends work to the right desk.

Policies are set by risk level. High-risk packs escalate below 0.90 confidence, medium-risk below 0.80 and low-risk below 0.70. Healthcare and pharma packs also forbid protected attributes.

Sectors (6 packs each)

Healthcare	Pharma & Life Sciences	Banking	Insurance
Capital Markets	Education	Research & Academia	Government
Legal & Compliance	HR & Workforce	Manufacturing	Supply Chain
Retail & E-commerce	Telecom & IT Ops	Cybersecurity	Energy & Utilities
Agriculture	Media & Marketing	Real Estate	Hospitality & Travel

terminal

```
$ algo domains "our servers are down and customers cannot log in"
  0.49  itops.incident_triage      IT incident triage
  0.35  itops.log_anomaly          Log anomaly detection
  0.33  itops.postmortem           Incident postmortem writer
$ algo run pack:itops.incident_triage --arg "incident=Login API returns 500"
$ algo pack itops.incident_triage --copy      # save an editable copy
```

Search works offline. It uses TF-IDF over each pack's title, description, agents and sector, with a synonym table and sector hints, so *"citizen complaint about water"* finds the government grievance pack. New domains are added as one line in `tools/make_packs.py`.

15.4 Governance

Hash-chained audit log. Every agent call is written to `runs/<program>.audit.jsonl`. Each record stores the SHA-256 hash of the previous record (`prev`) and its own hash (`hash`). Changing, inserting or deleting any line breaks the chain. `algo audit verify` reports the first bad line. Concurrent writers are serialised, so the chain stays valid under batch load.

Human review queue. A result below its confidence threshold is *escalated*:

- it is recorded with status `escalated`;
- it is added to an event-sourced queue (`runs/review_queue.jsonl`);
- it is decided later by a named reviewer with `algo review approve ID --reviewer NAME`, in the Studio's Governance tab, or with `al.review.approve(...)`.

Every decision is itself an audit event.

Reports. `algo report` totals calls, tokens, escalations, blocks, cache hits and average confidence for each program and each agent, and checks every chain.

15.5 Executable tools and scale

Tools are real Python functions. The built-in tools are:

- `calc.eval`: safe arithmetic;
- `file.read`: restricted to the project folder;
- `kb.search`: searches `kb/`.

A company adds its own tools in a plugin file:

```
import algoruntime as rt

@rt.register_tool("company.directory", "Look up which team owns a topic")
def directory(query):
    return lookup_in_hr_system(query)
```

An agent can call a tool only if it declares it with **`uses`**, and only if the org config allows it. In live mode the runtime runs Claude's tool-use loop (up to five rounds) and refuses any tool the agent did not declare.

`algo batch program.algo --input data.csv --workers 16` runs a program once per CSV row and writes a results CSV. In testing, 200 insurance claims ran in 0.6 s offline, with the audit chain intact. Live model calls stay within `max_concurrency`.

15.6 One SDK, three modes

`import algolang` is the public Python SDK. The command line, Studio and Prompt UI all call it, so a program behaves identically in each.

```
import algolang as al

al.configure(forbid=["salary", "caste"], min_human_below=0.75)
best = al.domains.search("triage insurance claims")[0]
prog = al.pack(best["id"])                      # or al.load("x.algo"), al.compile(
    ↪ src)
r = prog.run(claim="Rear-end collision in Pune")
print(r.status, r.values, r.stats, len(r.escalated))

results = prog.run_batch(rows, workers=16)      # list of RunResult
plan = al.compose("screen this CV fairly")      # prompt -> best pack + program
al.review.pending(); al.review.approve(item_id, reviewer="Dr. S")
al.audit.verify("runs/claims_triage.audit.jsonl")
```

15.6.1 Mode 1: command line

Command	Purpose
`algo init acme`	New project: config, plugin tool, knowledge base, sample program and data
`algo domains [words] [--sectors]`	Search the domain library
`algo pack ID [--copy]`	Show or copy a pack
`algo run pack:ID --arg ...`	Run a pack directly
`algo batch FILE --input CSV`	Parallel batch run
`algo review [approve|reject ID]`	Human review queue
`algo audit verify [path]`	Tamper check
`algo report [--json]`	Usage and governance summary
`algo chat`	Prompt mode in the terminal

15.6.2 Mode 2: graphical Studio

Studio (Chapter 3) gains three tabs:

Domains Sector chips, plain-English search, and pack cards with *Open in editor* and *Use in my program*. The latter inserts a `use pack` line.

Batch Upload or paste a CSV, run it, and download the results.

Governance Usage tiles, a per-program table, the review queue with Approve and Reject, and the active org policy.

15.6.3 Mode 3: Prompt-based UI

`algo ui` opens a chat-style page for people who will never open an editor. They describe the problem in plain English. **AlgoLang** picks the best domain program, runs it under the org policy, and shows:

- the chain of agents;
- the governance applied;
- the result and any items waiting for human review;
- a table of what each agent did;
- the program source.

Alternatives are one click away. *Open in Studio* hands the program to the graphical mode, and *Customise with AI* asks Claude to adapt it (live mode).




Figure 15.1: Studio's Domains tab: 120 packs grouped by sector, each showing its pattern, risk level and agents.

Responsible AI

Governance in **AlgoLang** is enforced by the compiler and runtime. It is not left to good intentions. Forbidden attributes cannot reach an agent, low-confidence results wait for a named human, and any attempt to rewrite the audit trail is detected. Organisations should still review each domain pack before production use. The packs are well-governed starting points, not certified decision systems.




Figure 15.2: Studio's Governance tab: usage and audit-chain tiles, usage per program, and the human review queue.




Figure 15.3: The Prompt UI answering an IT outage request with the `itops.incident_triage` pack.

16

Version 0.3: Uncertainty, Evidence and Interoperability

Version 0.3 adds six features. Each one answers a question that people ask about agent systems in production:

Question	v0.3 answer
How sure is the agent?	`uncertain<T>` types: sampled answers, measured agreement, and a compile-time rule that decisions must check confidence (**E117**)
Can a model overrule a hard limit?	Deterministic guards: `if limits contains "BREACH"` is decided in code, never by a model
Did my change break anything?	**`eval`** blocks in the program, traces of every run, and replay with no model calls
Can agents use our existing tools?	MCP tool bindings: `tool x from mcp "server"`
What does it cost, and what does it use?	Cost (USD/INR) and energy (Wh, CO_2) budgets, priced before every call
Can my editor help me?	A language server: `algo lsp`

16.1 `uncertain<T>` types

A model's confidence in its own answer is not proof that the answer is right. A better signal is *agreement*: ask several times and see whether the answers agree. Declaring the return type `uncertain<score>` (or `uncertain<text>`, and so on) asks the runtime to do that.

Sampling and the confidence rule

```
agent RiskJudge(claim: text) -> uncertain<score> {
    role   "Fraud risk judge"
    goal   "Score 0 to 1 the fraud risk of {claim}"
    policy { samples 5 }
}

flow main(claim: text) {
    risk = RiskJudge(claim)
    if risk > 0.8 and risk.confidence >= 0.7 {      // E117 without the confidence
    ↪ check
```

```
        emit Refer(claim)
    } else {
        emit Settle(claim)
    }
}
```

- The agent is called `samples` times (default 3, at most 15).
- Scores are averaged; other types are decided by majority vote.
- Confidence is half the model's own confidence and half the agreement between samples. For scores, agreement is $1 - \sigma/0.25$; for other types, it is the share of samples that match the winner.
- Conditions can combine comparisons with **`and`** and **`or`**, and can read `x.confidence`.
- Every audit record of an uncertain call stores the number of samples and their spread.

16.2 Deterministic guards

Some rules must never depend on a model: a breached risk limit, a failed backtest threshold, a sanctions match. A guard checks text, including the *full* answer of the agent's tools, and is decided in code:

enterprise-apps/algo-trading-desk/programs/pre_trade_check.algo (excerpt)

```
[quote, limits] = par { Quote(order), Limits(order) }
if limits contains "BREACH" {
    emit quote, limits, Reject(order, limits)        // no model is asked
} else {
    gate = RiskGate(order, quote, limits)            // uncertain<score>, 5 samples
    if gate > 0.75 and gate.confidence >= 0.8 { emit Ticket(order, quote) }
    else { emit Reject(order, limits) }
}
```

`contains` and `not contains` are case-insensitive. Because the breach is detected before any model is called, the rejected order above costs about a quarter of the tokens of an accepted one.

16.3 Eval blocks, traces and replay

Tests live next to the code they test:

An eval block

```
eval regression on main {
    case "settles a small claim" (claim = "NS-10571: scratch, estimate INR 6,500") {
        expect status ok
        expect called PayoutEstimator
        expect not called fraud.Referral
        expect output contains "estimated payout"
        expect tokens < 2000
        expect cost < 0.05
        expect energy < 1
    }
```

```
}
```

Expectations cover `status`, `called`, `not called`, `tool`, `output contains`, `emits`, and comparisons on `tokens`, `cost`, `energy`, `escalated` and `confidence` (the lowest confidence of any call).

terminal

```
$ algo eval claims.algo               # offline; records a trace per case
$ algo eval claims.algo --live        # real models; records traces
$ algo eval claims.algo --replay      # re-check from traces: zero tokens, zero cost
$ algo run claims.algo --arg "claim=…" --trace
$ algo replay runs/traces/claims-1a2b3c4d.trace.json
  replayed 7/8 recorded calls · saved ~1,180 tokens ($0.0098)
  ✗ Settle now receives different inputs: Settle … within 7 days
```

A trace stores the inputs, every agent call (with a hash of its prompt), each sample, the tool results and the outputs. Replay answers each call from the recording. When the program has changed so that an agent receives different inputs, replay reports a *replay miss* for that agent: the exact place where behaviour may have changed. Record traces once with real models, then re-check them in CI at no cost.

16.4 MCP tool bindings

The Model Context Protocol (MCP) is an open standard for connecting AI systems to tools. AlgoLang can use any MCP server's tools under the same governance as built-in tools:

examples/v03/expense_desk.algo (excerpt)

```
tool kb.search_policies from mcp "company-kb"
tool fx.convert_to_inr  from mcp "company-kb"
```

algo.config.json (excerpt)

```
"mcp_servers": {
    "company-kb": {"command": "{python}", "args": ["mcp_demo_server.py"]},
    "remote":     {"url": "https://example.com/mcp", "headers": {"Authorization": "
    ↪ Bearer …"}}
}
```

The MCP tool name is the part after the first dot. Stdio servers are started on first use and reused, and HTTP servers use the streamable-HTTP transport. In live mode the model receives the server's own input schema. The program must still declare the tool, the agent must list it under **uses**, and `allowed_tools` must include it. An unknown server is error **E120**. `algo mcp list SERVER` shows a server's tools.

16.5 Cost and energy budgets

Budgets

```
agent Compliance(claim: text, rules: text) -> uncertain<score> {
    goal   "Score how well {claim} complies with {rules}"
    policy { samples 5  budget cost 0.05 usd  budget energy 2 wh }
}
```

Every call is priced from two tables in `algo.config.json`:

- `pricing`: US dollars per million input and output tokens per model, converted to rupees with `usd_to_inr`;
- `energy`: watt-hours per thousand tokens per model, and the grid's CO_2 intensity (India ≈ 0.71 kg per kWh).

Before a call, the runtime estimates its cost from the prompt length, the expected output and the number of samples. A call that would exceed the agent's budget, the organisation's per-call cap (`max_budget_cost_usd`, `max_budget_energy_wh`) or the run cap (`max_run_cost_usd`, `max_run_energy_wh`) is blocked before it runs. After the call, the actual cost is recorded in the audit log, and `algo report` totals money, energy and CO_2 per program.

Responsible AI

The default prices and energy factors are placeholders, not published figures. Set your organisation's contracted prices and the energy estimates you trust. Offline runs show the *estimated* live cost so you can budget before going live.

16.6 The language server

`algo lsp` speaks the Language Server Protocol over standard input and output. It is built on the real compiler, so editors see exactly the errors `algo check` would report, including organisation-policy errors. Features:

- diagnostics as you type;
- hover (an agent's signature, role, goal, tools and policy);
- completion (keywords, agents, tools, models, domain packs after `use pack`, and snippets);
- go to definition, including into imported files and domain packs;
- an outline.

The VS Code extension in `vscode-algolang/` starts it automatically, and Neovim, Helix or Sublime can run the same command.

16.7 Towards v0.4: trustworthy AI

Version 0.4 is dedicated to trustworthy AI. Its objective is to make trustworthiness something a program can *prove*. The compiler will check that each safeguard a system needs is present, and the runtime and **`eval`** blocks will produce evidence that it worked. Planned work packages:

- counterfactual fairness tests (`expect fair across gender […]`);
- robustness tests;
- generated AI system cards (`algo card`);
- `explain with evidence`;
- `redact pii`;
- untrusted-tool mode against prompt injection;
- four-eyes human approval;
- signed audit chains and evidence packs;
- `risk high` program headers with compile-time requirements (**E122**–**E125**);
- an `algo trust report` mapped to the NIST AI Risk Management Framework, the EU AI Act and ISO/IEC 42001.

The plan is in `ROADMAP.md`. Using AlgoLang produces evidence for these frameworks; it does not by itself make a system compliant.

PART IV

Patterns and Practice



17

Multi-Agent Design Patterns

Good multi-agent systems are built from a small number of recurring shapes. This chapter gives each pattern in **AlgoLang**, with guidance on when to use it. All snippets assume suitable agent declarations.

17.1 Pipeline

Each agent refines the previous agent's output.

```
flow main(topic: text) {
    facts   = Researcher(topic)
    outline = Outliner(facts)
    draft   = Writer(outline)
    final   = Editor(draft)
    emit final
}
```

Use when the work has clear stages with different skills. **Tip:** give later, cheaper stages a `fast` model and reserve `smart` for the stage that needs judgement.

17.2 Fan-out / fan-in

A planner splits the work, one worker per part runs in parallel, and an aggregator combines the results.

```
flow main(paper: text) {
    criteria = Planner(paper)                                    // fan-out plan
    reports  = par for c in criteria { CriterionReviewer(c, paper) } // parallel
    ↪ workers
    summary  = Synthesiser(reports)                               // fan-in
    emit summary
}
```

Use when a task decomposes into independent parts. Total time is roughly that of the slowest worker, not the sum of all workers.

17.3 Committee

Several agents with different perspectives answer the same question; a judge weighs their answers.

```
flow main(question: text) {
    [clinician, statistician, ethicist] = par {
        ClinicalExpert(question), StatsExpert(question), EthicsExpert(question)
    }
    verdict = Judge(clinician, statistician, ethicist)
    emit verdict
}
```

Use when decisions benefit from diverse viewpoints, or to reduce the errors of any single agent. Give the members different roles, and if possible different models.

17.4 Critic and revise

A generator drafts, a critic scores, and the generator revises when the score is low.

```
flow main(brief: text) {
    draft = Writer(brief)
    if Critic(draft) < 0.8 {
        draft = Writer(brief, tone = "more rigorous, address the critic's points")
    }
    if Critic(draft) < 0.8 {
        draft = Writer(brief, tone = "concise and fully referenced")
    }
    emit draft
}
```

Note. AlgoLang has no unbounded loops. Revision rounds are written out, so every program is guaranteed to finish and its maximum number of agent calls—and therefore its maximum cost—can be read from the source. This is a deliberate design choice, not an omission.

17.5 Router

A classifier agent decides which specialist handles the input.

```
flow main(query: text) {
    technical = IsTechnical(query)          // returns score
    if technical >= 0.5 {
        answer = TechSupport(query)
    } else {
        answer = GeneralHelp(query)
    }
    emit answer
```

```
}
```

17.6 Guardrail

A checking agent screens input before the main work begins.

```
agent SafetyCheck(request: text) -> bool {
    role "Safety reviewer"
    goal "Answer true only if this request is safe and appropriate to fulfil: {
    ↪ request}"
}

flow main(request: text) {
    safe = SafetyCheck(request)
    if safe == true {
        emit Assistant(request)
    } else {
        emit Refusal(request)
    }
}
```

17.7 Human-in-the-loop

Place a confidence gate on the agent whose output matters most, and run with `--interactive` where a person is present.

```
agent Grader(answer: text, rubric: text) -> score {
    role  "Examiner"
    goal  "Grade {answer} against {rubric}; 0 to 1"
    policy { require human when confidence < 0.85 }
}
```

17.8 Separation of duties

The agent that *decides* must not be the agent that *audits*. Keep them separate, with separate policies.

```
agent Decider(application: text) -> score {
    goal   "Score {application} for the scholarship criteria only"
    policy { forbid gender, caste, religion  require human when confidence < 0.8 }
}

agent FairnessAuditor(decisions: list) -> text {
    role "Independent fairness auditor"
    goal "Review {decisions} for patterns of unfair treatment and explain any
    ↪ concerns"
```

```
}
```

Why separation matters

An agent asked to both decide and justify its own fairness has a conflict of interest, just as a person would. Separate agents make the audit independent, appear as separate entries in the audit log, and can be given different models and different reviewers.

17.9 Choosing a pattern

If you need...	Use
Stages with different skills	Pipeline
Speed on decomposable work	Fan-out / fan-in
Robust decisions	Committee
Higher quality output	Critic and revise
Different handling per input	Router
Safety before work begins	Guardrail
Accountable decisions about people	Human-in-the-loop + separation of duties

18

Responsible AI with AlgoLang

AlgoLang was designed so that the responsible way to build an AI system is also the easiest way. This chapter maps its features to widely used principles of trustworthy AI, shows how to use them together, and states plainly what the language does *not* guarantee.

18.1 Principles and features

Principle	How AlgoLang supports it	Feature
Accountability	Every unit of work is named and has a stated goal; every call is recorded	agents only (**E101**); audit log
Human oversight	Low-confidence results are routed to people; reviewers can approve	`require human when`; `--interactive`
Fairness	Protected attributes cannot be declared as inputs and are blocked in prompts	`forbid` (**E108**, runtime block)
Transparency	Capabilities, models and policies are visible in the source and in each audit record	`tool`, `uses`, `model`, `policy`
Security	Agents receive only explicitly granted capabilities	declared tools (**E104**)
Privacy	The log stores prompt hashes, not prompts or outputs	`inputs_sha`
Sustainability & cost	Per-agent token budgets; bounded programs with no unbounded loops	`budget tokens`; flow design
Reliability	Retries, timeouts; deterministic offline testing	`retry`, `timeout`; mock backend

18.2 Supporting governance frameworks

Organisations increasingly align AI systems with frameworks such as the NIST AI Risk Management Framework (with its functions *Govern*, *Map*, *Measure* and *Manage*) and, in Europe, the AI Act's requirements for high-risk systems, which include record-keeping (Article 12) and human oversight (Article 14). **AlgoLang** does not make a system compliant with any framework—compliance depends on the whole system and its context—but its features produce evidence that such work needs:

- the **source program** documents what each agent does, with which model and capabilities, under which rules;

- the **audit log** records every call, its confidence and its outcome;
- **escalation counts** and **approvals** show where human oversight was exercised;
- **blocked calls** show where safeguards acted.

18.3 A responsible design checklist

1. Does every agent have one clear goal and the narrowest return type?
2. Does each agent hold only the tools it needs?
3. Do agents that affect people have a human-review threshold, chosen deliberately?
4. Are protected attributes listed in `forbid` for every decision-making agent?
5. Is auditing done by a separate agent from deciding?
6. Does every live agent have a token budget?
7. Have you run the program on the mock backend and read the audit log before going live?
8. Who reviews escalated results, how quickly, and where is that recorded?
9. Have you tested outcomes across groups, not only individual cases?

18.4 Known limitations

Version 0.1 is a preview. The following limitations are known and documented so that no one relies on a guarantee the language does not give.

Area	Limitation in v0.1
`forbid`	Lexical: blocks the forbidden words, not proxies (names, places, schools) that may reveal the same attribute. Not a fairness guarantee.
Confidence (live)	Reported by the model itself. It is not a calibrated probability and should be validated against real outcomes before thresholds are trusted.
Confidence (mock)	Synthetic, derived from a hash of the input; useful only for demonstrating behaviour.
Token budget	Estimated at about four characters per token before the call; real counts may differ.
Timeout	Checked when the call returns; a slow call is not interrupted.
Tools	Declared and enforced as capabilities, but not executed by the runtime yet.
Types	Argument types are not yet checked against parameter types; flow inputs arrive as text.
Prompt injection	Text inside inputs can try to steer an agent. Policies limit what an agent may do, but do not detect injected instructions.
Audit log	Local append-only file; it is not tamper-proof. Protect and back it up as you would any record.

Use with care. Do not use AlgoLang 0.1 as the sole basis for decisions with legal or similarly significant effects on people—admissions, hiring, credit, health or justice—without independent validation, human review of every decision, and the governance your institution and law require.

18.5 Teaching AI ethics with AlgoLang

Because policies are code, ethical questions become concrete design exercises that students can run, break and discuss:

- **Proxy discrimination.** Build a screening flow that forbids `caste`, then show that a surname or home-district input can still carry the same information. Discuss what **`forbid`** can and cannot do.
- **Automation bias.** Run with `--interactive` and track how often reviewers approve without reading. Discuss how to design review that is meaningful.
- **Threshold setting.** Vary **`require human`** thresholds and measure escalation rates. Who should choose the threshold, and how should it be justified?
- **Accountability.** Given only an audit log, reconstruct what happened in a run. What is missing that a regulator or an affected person would need?

19

Teaching with AlgoLang

AlgoLang is small enough to learn in one session and rich enough to support a full course module on agentic AI and responsible AI. The mock backend makes every lab free, repeatable and runnable offline; Google Colab removes installation entirely.

19.1 Suggested lab sequence

Lab	Topic	Students build	Concepts
1	First agents	The starter program from `algo new`; change goals and roles	agent, goal, flow
2	Types and scores	A grader that returns a **`score`** and a branch on it	types, **`if`**, E110
3	Reading errors	Fix a broken program with eight errors	compiler diagnostics
4	Parallel agents	A committee of three experts and a judge	**`par`**
5	Planning	A planner and **`par for`** workers	fan-out / fan-in
6	Capabilities	Grant and remove tools; observe E104	least privilege
7	Human oversight	Gate a decision agent; run with `--interactive`	oversight, thresholds
8	Fairness	A screening flow with **`forbid`**; probe it with proxy attributes	fairness limits
9	Audit	Load the audit log into `pandas`; reconstruct a run	accountability
10	Going live	Run a finished flow on Claude with budgets	cost, real outputs

19.2 Exercises

1. **Translator.** Add `Translator(passage: text, language: text) -> text` and produce Hindi and Marathi versions of a brief in one **`par`** block.
2. **Budget discipline.** Give `Writer` the policy `budget tokens 50` and run. Explain the outcome and why it is better to fail before a call than to discover the cost afterwards.
3. **Committee size.** Extend a committee from three to five experts. How does run time change on the mock backend, and why?
4. **Bounded revision.** Write a critic-and-revise flow with at most three revisions. What is the maximum number of agent calls? Prove it from the source.

5. **Scholarship screening.** Design a flow that scores applications without seeing gender or caste, sends uncertain cases to a human, and has a separate fairness auditor. Then try to break it.
6. **Audit questions.** From an audit log alone, answer: which agent was least confident on average? How many results were escalated? Which model handled which agent?
7. **Language design.** Propose a new policy rule (for example, a maximum number of calls per agent). Write the grammar change and describe the runtime check (Chapter 14).

19.3 Assessment ideas

Criterion	Evidence
Correctness	Program compiles with no errors and produces the required outputs
Decomposition	Agents have single, clear goals and appropriate return types
Use of patterns	Parallelism and branching are used where they fit
Governance	Budgets, human-review thresholds and forbidden attributes are present and justified in writing
Evidence	Audit log analysed; escalations and blocks explained
Reflection	A short essay on one limitation from Section 18.4 and how to mitigate it

19.4 Using the notebook in class

Share `AlgoLang_Notebook.ipynb` with students; each opens it in their own Colab session. The notebook's ten sections follow the order of this book and end with exercises. Students can edit the toolchain cells themselves, which makes the notebook suitable for compiler-construction and programming-languages courses as well as AI courses.

PART V

The Project



20

The AlgoLang Project

AlgoLang is an open-source project led by AlgoProfessor AI R&D Solutions. This chapter describes how the project is organised, where it is going and how you can take part.

20.1 Versioning

AlgoLang follows semantic versioning. During the 0.x series, minor versions (0.2, 0.3, ...) may change the language; patch versions (0.1.1, ...) fix defects without changing valid programs. From version 1.0, any program that compiles under $1.x$ will compile under every later $1.y$.

20.2 Roadmap




Figure 20.1: Roadmap. Dates are not fixed; each step ships when its features are complete and documented.

20.3 Proposing changes: AEPs

Significant changes to the language are made through **AlgoLang Enhancement Proposals** (**AEPs**), short design documents in the tradition of other open-source languages.

1. **Discuss** the idea informally first.
2. **Write an AEP** with: motivation; the proposed syntax and semantics; examples; effect on existing programs; implementation sketch (grammar, checker, runtime); and the responsible-AI implications of the change.
3. **Review.** Proposals are reviewed for clarity, consistency with the design goals in Chapter 1, and the impact on accountability and safety.
4. **Decide.** Accepted AEPs are numbered, implemented with tests and documentation, and listed in the release notes.

A required section

Every AEP must include a section on responsible-AI implications. A feature that makes AI work less visible, less accountable or harder to oversee needs a strong justification and compensating safeguards.

20.4 Contributing

Contributions of every size are welcome:

- **Report a problem:** include the `.algo` file, the exact command, the full output and the output of `algo doctor`.
- **Improve documentation or examples:** new examples, teaching material and translations are especially valuable.
- **Change the code:** keep the compiler and runtime small and readable; add an example that exercises the change; run every example with `algo check` and `algo run` on the mock backend before submitting.

Contact: ceo@algoprofessor.com · www.algoprofessor.com.

20.5 Code of conduct

The **AlgoLang** community is open to everyone. Participants are expected to be respectful and constructive, to welcome newcomers and students, to give credit, and to assume good faith. Harassment and discrimination of any kind are not tolerated.

20.6 Licence

The **AlgoLang** software (compiler, runtime, notebook extension, installers and examples) is licensed under the **Apache License, Version 2.0**. This documentation is licensed under **Creative Commons Attribution 4.0 International (CC BY 4.0)**.

20.7 How to cite AlgoLang

If you use **AlgoLang** in research or teaching, please cite this documentation:

BibTeX

```bibtex
@manual{satyanarayana2026algolang,
  title        = {The {AlgoLang} Programming Language: Official Documentation,
     ↪ Version 0.1},
  author       = {Satyanarayana, S.},
  organization = {AlgoProfessor AI R\&D Solutions},
  address      = {Hyderabad, India},
  year         = {2026},
  month        = oct,
  url          = {https://www.algoprofessor.com},
  note         = {Open-source, agent-native programming language for building AI
     ↪ systems}
}
```

A

Grammar

This appendix reproduces `grammar.lark`, the normative grammar of **AlgoLang** 0.1, in Lark's EBNF notation. Quoted strings are keywords and punctuation; upper-case names are terminals; `?rule` inlines a rule with a single child; `-> name` labels an alternative in the parse tree; `%ignore` lists text skipped between tokens.

grammar.lark

```
// ─────────────────────────────────────────────────────────────
//  AlgoLang v0.1 grammar  —  AlgoProfessor AI R&D Solutions
//  Core rule: there are no functions. Every unit of work is an
//  `agent`; a `flow` only orchestrates agents.
// ─────────────────────────────────────────────────────────────

start: item*

?item: model_decl
     | tool_decl
     | agent_decl
     | flow_decl

// model fast = "claude-haiku-5-5"
model_decl: "model" NAME "=" STRING

// tool web.search   (declares a tool agents may be granted)
tool_decl: "tool" DOTTED

// agent Name(p: type, q: type = "x") -> type { ... }
agent_decl: "agent" NAME "(" [params] ")" "->" NAME "{" agent_clause* "}"

params: param ("," param)*
param: NAME ":" NAME ["=" literal]

?agent_clause: "role" STRING            -> role
             | "goal" STRING            -> goal
             | "uses" DOTTED ("," DOTTED)* -> uses
             | "model" NAME             -> model_ref
             | "policy" "{" policy_rule* "}" -> policy

?policy_rule: "budget" "tokens" NUMBER                      -> budget
            | "retry" NUMBER                                -> retry
            | "require" "human" "when" "confidence" "<" NUMBER -> human_gate
            | "forbid" NAME ("," NAME)*                     -> forbid
```

```
            | "timeout" NUMBER                                -> timeout

// flow main(topic: text) { ... }
flow_decl: "flow" NAME "(" [params] ")" "{" stmt* "}"

?stmt: target "=" expr                                      -> assign
     | "if" cond "{" stmt* "}" ["else" "{" stmt* "}"]       -> if_stmt
     | "emit" expr ("," expr)*                              -> emit
     | call                                                 -> expr_stmt

target: NAME                          -> single_target
      | "[" NAME ("," NAME)* "]"      -> multi_target

?expr: call
     | par_block
     | par_for
     | NAME                           -> var
     | literal

call: NAME "(" [args] ")"
args: arg ("," arg)*
?arg: kwarg | expr
kwarg: NAME "=" expr

// [a, b] = par { Writer(x), Critic(x) }
par_block: "par" "{" call ("," call)* "}"

// results = par for t in tasks { Worker(t) }
par_for: "par" "for" NAME "in" NAME "{" call "}"

cond: expr COMPARE expr
COMPARE: "<=" | ">=" | "==" | "!=" | "<" | ">"

?literal: STRING -> string
        | NUMBER -> number
        | "true"  -> true
        | "false" -> false

DOTTED: /[a-zA-Z_][a-zA-Z0-9_]*(\.[a-zA-Z_][a-zA-Z0-9_]*)+/
NAME: /[a-zA-Z_][a-zA-Z0-9_]*/
STRING: /"([^"\\]|\\.)*"/
NUMBER: /\d+(\.\d+)?/

COMMENT: /\/\/[^\n]*/
%ignore COMMENT
%import common.WS
%ignore WS
SEMI: ";"
%ignore SEMI
```

B

Quick Reference

B.1 Language card

everything in one screen

```
// ── declarations ──────────────────────────────────────────
model smart = "claude-sonnet-5-5"          // name a model
tool  web.search                            // declare a capability

agent Name(p: text, q: score = 0.5) -> list {   // types: text score list json bool
    role   "who it acts as"
    goal   "what to do with {p} and {q}"         // {param} placeholders
    uses   web.search                            // granted tools
    model  smart
    policy {
        budget tokens 4000                       // stop if prompt larger
        retry 2                                  // retry failures
        timeout 60                               // seconds
        require human when confidence < 0.75     // human oversight
        forbid gender, caste, religion           // protected attributes
    }
}

// ── flow statements ──────────────────────────────────────
flow main(input: text) {
    x       = Agent(input, q = 0.9)                  // call
    [a, b]  = par { AgentA(x), AgentB(x) }           // parallel block
    rs      = par for item in x { Worker(item) }     // parallel map over list
    if a < 0.8 { b = AgentB(x) } else { b = AgentC(x) }   // branch on score
    Notifier(b)                                       // call for effect
    emit a, rs                                        // output
}
```

B.2 Error codes

Code	Meaning	Code	Meaning
E100	Syntax error	E108	Forbidden attribute as parameter
E101	Not an agent	E109	Unknown `{placeholder}` in goal
E102	Wrong arguments	E110	Comparing a non-score
E103	Undefined variable	E111	No `flow main`
E104	Undeclared tool	E112	Agent without a goal
E105	Unknown type	E113	`[a, b]` does not match **`par`**
E106	Unknown model	E114	**`par for`** over a non-list
E107	Defined twice	E115	Tool not allowed by org policy
E116	Circular import	E117	Uncertain value without confidence check
E118	Bad `.confidence` read	E119	Eval block error
E120	Unknown MCP server	E121	Bad policy value (unit, currency, samples)

B.3 Command line

Command	Purpose
`algo doctor`	Check the environment
`algo new NAME`	Create a starter program
`algo check F.algo`	Find errors
`algo build F.algo [-o out.py]`	Compile to Python
`algo run F.algo --arg "k=v"`	Run on the mock backend
`… --live`	Run on Claude
`… --interactive`	Approve low-confidence results
`… --audit-dir DIR`	Choose where audit logs go
`algo notebook`	Open the Jupyter notebook

B.4 Notebook

Cell or magic	Purpose
`%load_ext algomagic`	Enable **AlgoLang** in a notebook
`%%algo --arg "k=v" [--graph] [--python]`	Run the cell
`%%algo --define`	Add declarations to the session
`%%algo --check`	Check only
`%algo_run F.algo --arg "k=v"`	Run a file
`%algo_list`, `%algo_reset`, `%algo_help`	Session tools
`algo_result`, `algo_calls`	Results for Python cells

B.5 Glossary

Agent A declared unit of work with a goal, optional role, tools, model and policy. The only callable thing in **AlgoLang**.

Audit record One JSON line per agent call describing what ran, under which rules, with what confidence and outcome.

Backend What executes agent calls: *mock* (offline, deterministic) or *live* (Claude models).

Confidence A number from 0 to 1 returned with every result.

Escalated Status of a result whose confidence fell below its agent's human-review threshold.

Flow A sequence of statements that orchestrates agents. `flow main` is the entry point.

Policy Governance rules attached to an agent: budget, retry, timeout, human review, forbidden attributes.

Result The value of an agent call together with its confidence, agent, call identifier and status.

Session In notebooks, the declarations collected from `--define` cells.

Tool A declared capability that agents may be granted with **`uses`**.

C

Example Programs

These programs are distributed in the `examples` folder. Each compiles and runs with **AlgoLang** 0.1.0 exactly as printed.

C.1 research_brief.algo

A research team: a researcher, two writers in parallel, a reviewer with a human-review gate, and a conditional redraft.

research_brief.algo

```
// research_brief.algo — three agents, one flow.
// Every piece of work is an agent; the flow only wires them together.

model smart = "claude-sonnet-5-5"
model fast  = "claude-haiku-5-5"

tool web.search

agent Researcher(topic: text) -> text {
    role  "Senior research analyst"
    goal  "Find five verified, recent facts about {topic}, with sources"
    uses  web.search
    model smart
    policy {
        budget tokens 6000
        retry 2
    }
}

agent Writer(facts: text, tone: text = "academic") -> text {
    role  "Technical writer"
    goal  "Write a 200-word brief from these facts in a {tone} tone: {facts}"
    model fast
}

agent Reviewer(draft: text) -> score {
    role  "Peer reviewer"
    goal  "Score this draft from 0 to 1 for factual accuracy and clarity: {draft}"
    model smart
    policy {
        require human when confidence < 0.70
```

```
    }
}

flow main(topic: text) {
    facts = Researcher(topic)

    // two writers work at the same time
    [formal, simple] = par {
        Writer(facts),
        Writer(facts, tone = "plain-English")
    }

    quality = Reviewer(formal)
    if quality < 0.80 {
        formal = Writer(facts, tone = "rigorous academic")
    }

    emit formal, simple
}
```

C.2 paper_review.algo

An editorial team: a planner, one reviewer per criterion in parallel, a responsible-AI auditor, an editor whose decision may not see author identity, and a letter writer.

paper_review.algo

```
// paper_review.algo — a planner splits the job, worker agents run
// in parallel, a responsible-AI agent audits, an editor decides.

model smart = "claude-sonnet-5-5"
model fast  = "claude-haiku-5-5"

tool file.read
tool web.search

agent Planner(paper: text) -> list {
    role  "Associate editor"
    goal  "List the review criteria that matter most for this manuscript: {paper}"
    uses  file.read
    model smart
}

agent CriterionReviewer(criterion: text, paper: text) -> text {
    role  "Domain reviewer"
    goal  "Review {paper} strictly on: {criterion}. Give strengths, weaknesses,
    ↪ fixes."
    uses  file.read, web.search
    model fast
    policy {
        budget tokens 4000
```

```
        retry 1
    }
}

agent EthicsAuditor(paper: text) -> text {
    role  "Responsible-AI auditor"
    goal  "Check {paper} for dataset consent, bias, reproducibility and dual-use risk
    ↪ "
    model smart
}

agent Editor(reports: list, ethics: text) -> score {
    role  "Editor-in-Chief"
    goal  "Weigh {reports} and {ethics}; score acceptance likelihood 0 to 1"
    model smart
    policy {
        require human when confidence < 0.75
        forbid gender, caste, religion, nationality   // decision must not see author
    ↪  identity
    }
}

agent DecisionLetter(reports: list, verdict: score) -> text {
    role  "Editorial assistant"
    goal  "Draft a courteous decision letter (score {verdict}) summarising {reports}
    ↪ "
    model fast
}

flow main(paper: text) {
    criteria = Planner(paper)

    // one reviewer agent per criterion, all in parallel
    reports = par for c in criteria { CriterionReviewer(c, paper) }

    ethics  = EthicsAuditor(paper)
    verdict = Editor(reports, ethics)
    letter  = DecisionLetter(reports, verdict)

    emit verdict, letter
}
```

C.3 bad_example.algo

A deliberately broken program that triggers eight different compile errors (Chapter 10).

bad_example.algo

```
// bad_example.algo — deliberately broken, to show the compiler's checks.

model smart = "claude-sonnet-5-5"
```

```
agent Summariser(doc: text) -> text {
    role "Summariser"
    goal "Summarise {document}"          // E109: no parameter named 'document'
    uses email.send                      // E104: tool never declared
    model turbo                          // E106: unknown model
}

agent Screener(caste: text) -> score {   // E108: forbidden attribute as input
    role "Loan screener"
    goal "Score applicant {caste}"
    policy { forbid caste }
}

flow main(doc: text) {
    s = Summariser(doc, doc)             // E102: too many arguments
    t = summarise_text(doc)              // E101: not an agent
    if s < 0.5 { emit s }                // E110: 's' is text, not a score
    emit missing                         // E103: undefined variable
}
```

C.4 Output of research_brief.algo

terminal

```
$ algo run examples/research_brief.algo --arg "topic=Blockchain data integrity"
▶ flow main  run=832d55bb  backend=mock
    topic = 'Blockchain data integrity'
  → Researcher         conf=0.83  «Researcher #5704» Find five verified, recent facts about
    ↪  Blockchain dat
  → Writer             conf=0.77  «Writer #6561» Write a 200-word brief from these facts in a
    ↪  plain-Englis
  → Writer             conf=0.71  «Writer #7140» Write a 200-word brief from these facts in a
    ↪  academic ton
  → Reviewer           conf=0.68  0.78  ⚠ ESCALATED to human (conf < 0.70)
  → Writer             conf=0.84  «Writer #7619» Write a 200-word brief from these facts in a
    ↪  rigorous aca
■ emitted:
    • «Writer #7619» Write a 200-word brief from these facts in a rigorous academic tone: «…
    • «Writer #6561» Write a 200-word brief from these facts in a plain-English tone: «Rese…
■ 5 agent calls · ~525 tokens · 0 retries · 1 escalated · 0 blocked · audit →
   ↪  runs/research_brief.audit.jsonl
```