Nathan Donaldson
U0632803

Homework 4

[1] H. Y. Shum, X. He, and D. Li, "From Eliza to XiaoIce: Challenges and Opportunities with Social Chatbots," Microsoft Corp., Available: https://arxiv.org/pdf/1801.01957.pdf.

[2] A. Cervone, C. Lai, S. Pareti, and P. Bell, "Towards automatic detection of reported speech in dialogue using prosodic cues," Sixteenth Annual Conference of the International Speech Communication Association, School of Informatics, University of Edinburgh, Edinburgh EH8 9AB, UK 2Google Inc., 8002 Zurich, Switzerland, 2015, pp. 3061-3065.

[3] R. Levitan, S. Benus, R. H. Galvez, A. Gravano, F. Savoretti, M. Trnka, A. Weise, and J. Hirschberg, "Implementing acoustic-prosodic entrainment in a conversational avatar," Department of Computer and Information Science, Brooklyn College CUNY, USA, Constantine the Philosopher University in Nitra, Slovakia, Institute of Informatics, Slovak Academy of Sciences, Slovakia, Departamento de Computacion, FCEyN, Universidad de Buenos Aires, Argentina, Consejo Nacional de Investigaciones Cient´ıficas y Tecnicas (CONICET), Buenos Aires, Argentinam Department of Computer Science, Columbia University, USA, 2016, pp. 1166-1170.

[4] M. Kotti, A. Papangelis, and Y. Stylianou, "Will this dialogue be unsuccessful? Prediction using audio features," ICTIR' 17 Workshop on Search-Oriented Conversational AI (SCAI' 2017), Amsterdam, Netherlands, 2017.

[5] P. Shah, D. H. Tur, G. Tur, A. Rastogi, A. Bapna, N. Nayak, and L. Heck, "Building a Conversational Agent Overnight with Dialogue Self-Play," Google AI, Mountain View, CA, USA, 2018, arXiv:1801.04871.

[6] T. H. K. Huang, J. C. Chang, and J. P. Bigham, "Evorus: A Crowd-powered Conversational Assistant Built to Automate Itself Over Time," Language Technologies Institute and Human-Computer Interaction Institute Carnegie Mellon University, 2018, arXiv:1801.02668.