

Table of Contents

- [1 FSCR BUSH DIGITAL SPECTROMETER JUPYTER NOTEBOOK](#)
 - [1.1 BDS Header Block](#)
 - [1.2 Importing Libraries and Notebooks](#)
 - [1.3 BDS Configuration Parameters](#)
 - [1.4 BDS File Output Names](#)
 - [1.5 Creating the Spectrometer Camera Object](#)
 - [1.6 Obtaining the Raw Image of the Spectrum](#)
 - [1.7 Draw Visual Aperture and Measure Emission Spectral Peaks](#)
 - [1.8 Display Emission Spectrum and Compare with NIST Standard values](#)

FSCR BUSH DIGITAL SPECTROMETER JUPYTER NOTEBOOK

BDS Header Block

```
In [1]: # BUSH DIGITAL SPECTROMETER SOFTWARE INTERACTIVE VERSION
# Author - Chandru Narayan
# TEMPLATE FOR FCSR STUDENTS
# CN Version_12i 11/25/2019 cloned from automated version v11
#
# 120219 CN "Added function call to print BDS parameters"
# 120419 CN "Added function call to compute peaks in the spectrum wavelengths"
# 120619 CN "Added cell for bdscfg parms"
# 120619 CN "Added Try-Except Block for creating Camera Objects"
```

Importing Libraries and Notebooks

```
In [2]: import import_ipynb
from IPython.core.display import Image
from IPython.core.display import display
from IPython.display import IFrame
#import PIL
from PIL import Image as pilimg
from PIL import ImageOps as pilimgops
from PIL import ImageDraw as pildraw
from PIL import ImageFont as pilfont
import picamera
import os, sys
import time
from datetime import datetime

class StopExecution(Exception):
    def _render_traceback_(self):
        pass
```

```
In [3]: # BUSH LIBRARY FUNCTIONS FOR BUSH DIGITAL SPECTROMETER SOFTWARE INTERACT
IVE VERSION
# Author - Chandru Narayan
# TEMPLATE FOR FCSR STUDENTS
# CN Version_11i 12/1/2019 cloned from automated version v11
# IMPORT BDSLIB AND BDSCFG HERE
import bdslibv2
```

importing Jupyter notebook from bdslibv2.ipynb

BDS Configuration Parameters

```
In [4]: #####  
#      BUSH DIGITAL TELESCOPE SOFTWARE CONFIG SECTION  
#      TO BE USED IN THE INTERACTIVE VERSION ONLY  
#      FOR DETAILED DESCRIPTION OF PARMS SEE BDS CONFIG DOC  
#####  
  
#  
# NAMING  
#  
source = 'fluorescent'  
element = 'mercury'  
desc = 'Flourescent Lamp Spectrum'  
  
#  
# CAMERA  
#  
shutter = 5000  
  
#  
# CALIBRATION  
#  
wavelength_factor = 0.77  
spectrum_angle = 0  
slit_topadj = 100  
slit_botadj = -200  
  
#  
# PLOTS  
#  
samp_th = 0.1  
wlen_th = 10
```

BDS File Output Names

```
In [5]: # STEP 1. SETUP FILE BASENAMES WITH TIMESTAMPS
#         setup the source or basename for files
#         make it indicative of the spectrum you are taking
#         keep it short but meaningful. Do not name "a1" etc!
#source = 'cfls'

# Filenames be appended with date and time
# such that they will not be overwritten
now = datetime.now()
name = source + now.strftime("%m%d%H%M%S")
raw_filename = name + "_raw"
rawinv_filename = name + "_rawinv"
ovl_filename = name + "_ovl"
ovlinv_filename = name + "_ovlinv"
cht_filename = name + "_cht"
chtinv_filename = name + "_chtinv"
tbl_filename = name + "_tbl"
par_filename = name + "_par"
pks_filename = name + "pks"
pksinv_filename = name + "pksinv"
```

```
In [6]: ##### STUDENT TO ADD EDITS BELOW #####
#####
## WRITE A STATEMENT TO PRINT THE 4 OUTPUT NAMES FROM THE BDS SOFTWARE T
O FAMILIARIZE YOURSELF

print(raw_filename)
print(rawinv_filename)
print(ovl_filename)
print(ovlinv_filename)
print(cht_filename)
print(chtinv_filename)
print(tbl_filename)
print(par_filename)
print(pks_filename)
print(pksinv_filename)
```

```
fluorescent0813132435_raw
fluorescent0813132435_rawinv
fluorescent0813132435_ovl
fluorescent0813132435_ovlinv
fluorescent0813132435_cht
fluorescent0813132435_chtinv
fluorescent0813132435_tbl
fluorescent0813132435_par
fluorescent0813132435pks
fluorescent0813132435pksinv
```

```
In [7]: ##### STOP HERE STUDENT/INSTRUCTOR TO VALIDATE STEP 1 #####
#####
## VALIDATE THE NAMES OF FILES TO BE CREATED - DO THEY LOOK RIGHT ??? ##

# DO NOT GO FORWARD UNTIL INSTRUCTOR VALIDATES
```

Creating the Spectrometer Camera Object

```
In [8]: # STEP 2. CREATE THE CAMERA OBJECT
#       CAPTURE THE RAW SPECTRUM IMAGE
#       THIS WILL BE EXAMINED FOR ANY ADJUSTMENTS NEEDED
#       FOR EXAMPLE IMAGE BRIGHTNESS LIGHT LEAKAGE ETC
#       DISPLAY CAPTURED IMAGE
```

```
In [9]: #       Get camera object. Note that this can only be executed ONCE pe
#       r run
#       YOU SHOULD NOT RUN IT AGAIN UNLESS THE CAMERA IS CLOSED WHICH
#       THIS STATEMENT IS AT THE VERY BOTTOM OF THIS FILE
try:
    camera = picamera.PiCamera()
except:
    print("Exception in opening camera object")
    print("Closing and Recreating Camera Object")
    camera.close()
    camera = picamera.PiCamera()
finally:
    print("Camera object created")
```


Camera object created

```
In [10]: #       Set the shutter speed of the camera.
#       Use 100000 for a medium bright spectrum
#shutter = 5000
camera.shutter_speed = shutter
#       flip the image laterally as my analysis software reads with sl
#       it on the right!
camera.hflip = True
#       capture image with a predetermined size suitable for pixel cou
#       nting analysis
raw_jpg_filename = raw_filename + ".jpg"
camera.capture(raw_jpg_filename, resize=(1296, 972))
#camera.capture(raw_jpg_filename, resize=(800, 600))
```

```
In [11]: camera.hflip = False
#       capture image with a predetermined size suitable for pixel cou
#       nting analysis
rawinv_jpg_filename = rawinv_filename + ".jpg"
camera.capture(rawinv_jpg_filename, resize=(1296, 972))
#camera.capture(raw_jpg_filename, resize=(800, 600))
```


Obtaining the Raw Image of the Spectrum

```
In [12]: #      view image and apply putty or tape inside spectroscope to preven  
         #      t light leakage  
         #      remember - image is flipped laterally from left right!  
display(Image(raw_jpg_filename))  
bdslibv2.display_bds_params(name,desc,shutter,slit_topadj,slit_botadj,spectrum_angle,wavelength_factor,samp_th,wlen_th)
```



Title: FLOURESCENT LAMP SPECTRUM
BDS parameters used for this run:
Spectrum Base Name is fluorescent0813132435
Camera Shutter is: 5000
Slit Top Adjustment is: 100
Slit Bottom Adjustment is: -200
Camera Spectrum Angle is: 0
Camera Wavelength Factor is: 0.77
Amplitude Threshold is: 0.1
Wavelength Threshold is: 10

```
In [13]: #      view image and apply putty or tape inside spectroscope to preven
t light leakage
#      remember - image is flipped laterally from left right!
display(Image(rawinv_jpg_filename))
bdslibv2.display_bds_params(name,desc,shutter,slit_topadj,slit_botadj,spectrum_angle,wavelength_factor,samp_th,wlen_th)
```



```
Title:          FLOURESCENT LAMP SPECTRUM
BDS parameters used for this run:
Spectrum Base Name is      fluorescent0813132435
Camera Shutter is:         5000
Slit Top Adjustment is:    100
Slit Bottom Adjustment is: -200
Camera Spectrum Angle is:  0
Camera Wavelength Factor is: 0.77
Amplitude Threshold is:    0.1
Wavelength Threshold is:   10
```

```
In [14]: ##### STOP HERE STUDENT/INSTRUCTOR TO VALIDATE STEP 2 #####
#####
## DID THE IMAGE APPEAR ??
## IS THE IMAGE OF THE SPECTRUM VISIBLE ??
## IS THE IMAGE FLIPPED Laterally ?
## DOES THE SLIT LOOK OVER EXPOSED ??
## DOES THE SPECTRUM LOOK TOO DIM ??

# DO NOT GO FORWARD UNTIL INSTRUCTOR VALIDATES
```

Draw Visual Aperture and Measure Emission Spectral Peaks

```
In [15]: # STEP 3. PROCESS THE IMAGE AND LOCATE THE SLIT (APERTURE)
#         READ RAW JPG FILE OBTAINED IN A PIXEL ARRAY
#         RECORD THE PIXEL WIDTH AND HEIGHT
#         NARROW THE PIXEL WINDOW FOR SLIT TOP AND BOTTOM
#         FOR EXAMPLE IMAGE BRIGHTNESS LIGHT LEAKAGE ETC
#         DISPLAY CAPTURED IMAGE
```

```
In [16]: #         READ RAW JPG FILE OBTAINED IN A PIXEL ARRAY
im = pilimg.open(raw_jpg_filename)
pic_pixels = im.load()
#         record the pixel width and height
width = im.size[0]
height = im.size[1]
print("width is %d, height is %d" % (width, height))
#         The slit needs to be shortened in height at times due to light
leakage
#         inside spectrometer. This small adjustment can be made here.
#         bigger negative numbers for smaller for bottom slit
#         bigger positive numbers for smaller top slit
#         for daylight or bright spectrum we need to narrow the slit grea
tly.
#         default values are set above
#         Adjust and uncomment below if you need
# FINE CALIBRATION
#
#wavelength_factor = 0.77
#spectrum_angle = -0.09
#slit_topadj = 30
#slit_botadj = -35

#         call library function to find the aperture in the raw image (pi
xel array)
aperture = bdslibv2.find_aperture(pic_pixels, width, height, slit_topadj
, slit_botadj)
#         draw the aperture
draw = pildraw.Draw(im)
bdslibv2.draw_aperture(aperture, draw)
```

```
width is 1296, height is 972
aperture_x b4 avg is: 1089
aperture_x1 is: 1086
aperture_x2 is: 1105
avg aperture_x is: 1095.5
spectrum_top is 317 spectrum bottom is 695
adj spectrum_top is 417 adj spectrum bottom is 495
```



```
In [17]: #          Draw scan line using the Spectrum angle
#          This is the angle that the camera and diffraction grating makes
#          with the light path
#          The Spectrum Angle trignometric tangent of the angle the camera
#          and diffraction grating makes
#          with the line of sight to the entry slit. This usually does not
#          need to be changed very much
#          as it manipulates where in the observation area the spectrum falls. It only needs to be
#          approximate such that pixel counter can find it
#          default values are set above
#          Adjust and uncomment below if you need
#          draw the scan lline
bdslibv2.draw_scan_line(aperture, draw, spectrum_angle)
```

```
In [18]: #          The wavelength_factor is the variable used for calibrating the
#          spectroscope such that
#          the calibration spectral line matches the known standard for th
#          at emission spectrum
#          The wavelength_factor is close to 0.90 for the 1000 lines/mm di
#          ffraction grating
#          The wavelength_factor is close to 0.60 for the 500 lines/mm dif
#          fraction grating
#          default values are set above
#          Adjust and uncomment below if you need
#
try:
    results, max_result = bdslibv2.draw_graph(draw, pic_pixels, aperture
, spectrum_angle, wavelength_factor)
except:
    camera.close()
    print("Exception while creating an aperture")
    print("This run **** TERMINATED PREMATURELY **** ...")
    print("Maybe the result of misaligned light path a very dim spectru
m")
    print("Adjust Light Path Alignment OR Increase Shutter parameter and
try again")
    raise StopExecution
else:
    print("Producing graphical result")
```


Producing graphical result

```
In [19]: #          Display actual and ideal targets for camera exposure correction
s
bdslibv2.inform_user_of_exposure(max_result)
```


ideal exposure between 0.15 and 0.30
exposure= 1.9162750198140157
consider reducing shutter time

```
In [20]: from PIL import ImageOps as pilimgops
#         Create the spectrum image overlaid with aperture and scan line
ovl_jpg_filename = ovl_filename + ".jpg"
bdslibv2.save_image_with_overlay(im, ovl_jpg_filename)
#         Create the spectrum image overlaid with aperture and scan line
ovlinv_jpg_filename = ovlinv_filename + ".jpg"
im_mirror = pilimgops.mirror(im)
bdslibv2.save_image_with_overlay(im_mirror, ovlinv_jpg_filename)
```

```
In [21]: #      View the Overlaid image fix parameters and rerun STEP 3 ONLY from the beginning as needed
display(Image(ovl_jpg_filename))
bdslibv2.display_bds_params(name,desc,shutter,slit_topadj,slit_botadj,spectrum_angle,wavelength_factor,samp_th,wlen_th)
display(Image(ovlinv_jpg_filename))
```



Title: FLOURESCENT LAMP SPECTRUM
BDS parameters used for this run:
Spectrum Base Name is fluorescent0813132435
Camera Shutter is: 5000
Slit Top Adjustment is: 100
Slit Bottom Adjustment is: -200
Camera Spectrum Angle is: 0
Camera Wavelength Factor is: 0.77
Amplitude Threshold is: 0.1
Wavelength Threshold is: 10



```
In [22]: ##### STOP HERE STUDENT/INSTRUCTOR TO VALIDATE STEP 3 #####
#####
## IS THE ACTUAL EXPOSURE WITHIN THE TARGET LIMITS ??
## DID A RECTANGULAR WINDOW APPEAR OVERLAID ON THE IMAGE ENCLOSING THE
SPECTRUM ??
## IS THE SCAN LINE VISIBLE ??
## IS THE SCAN LINE ALIGNED WITH THE SLIT ??
## IF NOT WE HAVE TO MAKE ADJUSTMENTS BEFORE PROCEEDING
## READ INSTRUCTIONS IN VARIOUS CELLS ON THIS STEP
## MAKE CHANGES AND ASK FOR ME TO VALIDATE BEFORE PROCEEDING


# DO NOT GO FORWARD UNTIL INSTRUCTOR VALIDATES
```

Display Emission Spectrum and Compare with NIST Standard values


```
In [23]: # STEP 4 FINAL STEP! NORMALIZE AND CREATE/DISPLAY SPECTRUM CHART
# MAKE ADJUSTMENTS AND RERUN FROM THE BEGINNING IF NEEDED
normalized_results = bdslibv2.normalize_results(results, max_result)
```

```
In [24]: #      Create the spectrum chart overlaid with the proper wavelengths  
#      and color map according to frequency  
cht_png_filename = cht_filename + ".png"  
bdslibv2.export_diagram(cht_png_filename, normalized_results)  
chtinv_png_filename = chtinv_filename + ".png"  
bdslibv2.export_inv_diagram(cht_png_filename, chtinv_png_filename)
```

```
In [25]: display(Image(cht_png_filename))
bdslibv2.display_bds_params(name,desc,shutter,slit_topadj,slit_botadj,spectrum_angle,wavelength_factor,samp_th,wlen_th)
display(Image(chtinv_png_filename))
bdslibv2.display_bds_params(name,desc,shutter,slit_topadj,slit_botadj,spectrum_angle,wavelength_factor,samp_th,wlen_th)
```



Title: FLOURESCENT LAMP SPECTRUM
 BDS parameters used for this run:
 Spectrum Base Name is fluorescent0813132435
 Camera Shutter is: 5000
 Slit Top Adjustment is: 100
 Slit Bottom Adjustment is: -200
 Camera Spectrum Angle is: 0
 Camera Wavelength Factor is: 0.77
 Amplitude Threshold is: 0.1
 Wavelength Threshold is: 10



Title: FLOURESCENT LAMP SPECTRUM
 BDS parameters used for this run:
 Spectrum Base Name is fluorescent0813132435
 Camera Shutter is: 5000
 Slit Top Adjustment is: 100
 Slit Bottom Adjustment is: -200
 Camera Spectrum Angle is: 0
 Camera Wavelength Factor is: 0.77
 Amplitude Threshold is: 0.1
 Wavelength Threshold is: 10


```

In [26]: #      Print the Spectral Peaks table of wavelengths
#      for current spectral image obtained
csv_tbl_filename = tbl_filename + ".csv"
bdslibv2.export_csv(tbl_filename, normalized_results)

#      Uncomment and change these thresholds if necessary if
#      you would like to increase or decrease the number
#      of Spectral peaks found

#samp_th = 0.2
#wlen_th = 10
#      Call function to draw the Spectral Peaks which will
#      Plot the peaks and return a list of Peak Wavelengths
pks_png_filename = pks_filename + ".png"
peak_wl, t1, t2 = bdslibv2.draw_spectral_line_peaks(element, csv_tbl_filename, pks_png_filename, desc, samp_th, wlen_th)
bdslibv2.display_bds_params(name, desc, shutter, slit_topadj, slit_botadj, spectrum_angle, wavelength_factor, samp_th, wlen_th)
par_txt_filename = par_filename + ".txt"
bdslibv2.write_bds_params(par_txt_filename, name, desc, shutter, slit_topadj, slit_botadj, spectrum_angle, wavelength_factor, samp_th, wlen_th)


```

Title: FLOURESCENT LAMP SPECTRUM

BDS parameters used for this run:

Spectrum Base Name is	fluorescent0813132435
Camera Shutter is:	5000
Slit Top Adjustment is:	100
Slit Bottom Adjustment is:	-200
Camera Spectrum Angle is:	0
Camera Wavelength Factor is:	0.77
Amplitude Threshold is:	0.1
Wavelength Threshold is:	10

SPECTRAL PEAK WAVELENGTHS FOR MERCURY
 THE MEASURED PEAK WAVELENGTHS FOR MERCURY IN NANO METERS ARE: 404 434 484 542 586 599 612 632
 THE NIST STANDARD STRONG LINE WAVELENGTHS FOR MERCURY ARE: 404 436 546




```
In [27]: pattern = pilimg.open(cht_png_filename).convert('RGBA')
#txt = pilimg.new('RGBA', pattern.size, (255,255,255,0))
size = width, height = pattern.size
draw = pildraw.Draw(pattern, 'RGBA')
font = pilfont.truetype('/usr/share/fonts/truetype/lato/Lato-Regular.ttf', 12)
#print(size)
draw.text((0,0), desc.upper(), font=font, fill='#000')
draw.text((0,20), t1, font=font, fill='#000')
draw.text((0,40), t2, font=font, fill='#000')
#draw.text((0,100), "Hello World", (0, 0, 0, 0), font=font)
pattern.save(cht_png_filename)
```

```
In [28]: display(Image(cht_png_filename))
#bdslibv2.display_bds_params(name,desc,shutter,slit_topadj,slit_botadj,spectrum_angle,wavelength_factor,samp_th,wlen_th)
```

FLOURESCENT LAMP SPECTRUM

THE MEASURED PEAK WAVELENGTHS FOR MERCURY IN NANO_METERS ARE: 404 434 484 542 586 599 61

THE NIST STANDARD STRONG LINE WAVELENGTHS FOR MERCURY ARE: 404 436 546



```
In [29]: camera.close()
```


```
In [30]: pattern = pilimg.open(cht_png_filename).convert('RGBA')
#txt = pilimg.new('RGBA', pattern.size, (255,255,255,0))
size = width, height = pattern.size
draw = pildraw.Draw(pattern, 'RGBA')
font = pilfont.truetype('/usr/share/fonts/truetype/lato/Lato-Regular.ttf', 12)
#print(size)
#draw.text((0,0), desc.upper(), font=font, fill='#000')
#draw.text((0,20), t1, font=font, fill='#000')
#draw.text((0,40), t2, font=font, fill='#000')
#draw.text((0,100), "Hello World", (0, 0, 0, 0), font=font)
pattern.save(cht_png_filename)
```

```
In [31]: display(Image(cht_png_filename))
#bdslibv2.display_bds_params(name,desc,shutter,slit_topadj,slit_botadj,spectrum_angle,wavelength_factor,samp_th,wlen_th)
```

FLOURESCENT LAMP SPECTRUM

THE MEASURED PEAK WAVELENGTHS FOR MERCURY IN NANO_METERS ARE: 404 434 484 542 586 599 61

THE NIST STANDARD STRONG LINE WAVELENGTHS FOR MERCURY ARE: 404 436 546



```
In [32]: ##### STOP HERE STUDENT/INSTRUCTOR TO VALIDATE STEP 4 FINAL
STEP #####
## CONGRATULATIONS - YOU MADE A FANCY DIGITAL SPECTROSCOPE AND MADE YOUR
FIRST MEASUREMENTS!
##
## DID THE SPECTRAL CHART APPEAR ??
## DOES THE CHART LOOK CORRECT ??
## DOES IT MATCH WITH THE STANDARD FOR ELEMENTS FOUND IN THE STANDARD SP
ECTRUM ??
## IF NOT WE WILL MAKE ADJUSTMENTS TO PARAMETERS ABOVE AS DOCUMENTED
## MAKE CHANGES AND ASK FOR ME TO VALIDATE BEFORE PROCEEDING

# DO NOT GO FORWARD UNTIL INSTRUCTOR VALIDATES
# WHEN YOU HAVE GOOD RESULTS PRINT FROM THE "FILE->PRINT PREVIEW" FROM
# THE JUPYTER NOTEBOOK AND GET THIS NOTEBOOK PRINTED FOR VALIDATION!
```