

SD Card Partitioning & Formating

Every storage device having one or more logical partitionings and default mount points. The partition contains information about disk partitions. when your connecting device the partitions will show in /dev like /dev/sda, sdb.....etc. This information is available through linux disk partitioning command **fdisk**.

Disk partitioning

In linux so many tools available for disk partitioning . The widely using tool is **fdisk**. The following steps will give information about disk partition.

- Connect your sd card to system then use **fdisk -l** command to get the information about the sd card.
- This command will show all disks connected to system information.

```
root@veda:/home/documents# fdisk -l

Disk /dev/sda: 500.1 GB, 500107862016 bytes
255 heads, 63 sectors/track, 60801 cylinders, total 976773168 sectors
Units = sectors of 1 * 512 = 512 bytes
Sector size (logical/physical): 512 bytes / 4096 bytes
I/O size (minimum/optimal): 4096 bytes / 4096 bytes
Disk identifier: 0x0004f5d6

   Device Boot      Start         End      Blocks   Id  System
/dev/sda1  *           2048     968718335     484358144    83  Linux
/dev/sda2             968720382     976771071      4025345     5  Extended
Partition 2 does not start on physical sector boundary.
/dev/sda5             968720384     976771071      4025344    82  Linux swap / Solaris

Disk /dev/sdb: 7948 MB, 7948206080 bytes
245 heads, 62 sectors/track, 1021 cylinders, total 15523840 sectors
Units = sectors of 1 * 512 = 512 bytes
Sector size (logical/physical): 512 bytes / 512 bytes
I/O size (minimum/optimal): 512 bytes / 512 bytes
Disk identifier: 0x0004c942

   Device Boot      Start         End      Blocks   Id  System
/dev/sdb1  *           2048      1050623       524288    b  W95 FAT32
/dev/sdb2             1050624      15523839      7236608    83  Linux
root@veda:/home/documents#
```

- Here my device represents with sdb and my device having two active partitions named as

sdb1 and sdb2.

- Now use `fdisk /dev/sdb` this will give one menu

```
root@veda:/home/documents# fdisk /dev/sdb
Command (m for help): m
Command action
  a   toggle a bootable flag
  b   edit bsd disklabel
  c   toggle the dos compatibility flag
  d   delete a partition
  l   list known partition types
  m   print this menu
  n   add a new partition
  o   create a new empty DOS partition table
  p   print the partition table
  q   quit without saving changes
  s   create a new empty Sun disklabel
  t   change a partition's system id
  u   change display/entry units
  v   verify the partition table
  w   write table to disk and exit
  x   extra functionality (experts only)

Command (m for help):
```

- So many commands available first we delete all partitions and create fresh partition table
- press `"d"` for deletion of partition

```
Command (m for help): d
Partition number (1-4): 1

Command (m for help): d
Selected partition 2

Command (m for help): p

Disk /dev/sdb: 7948 MB, 7948206080 bytes
245 heads, 62 sectors/track, 1021 cylinders, total 15523840 sectors
Units = sectors of 1 * 512 = 512 bytes
Sector size (logical/physical): 512 bytes / 512 bytes
I/O size (minimum/optimal): 512 bytes / 512 bytes
Disk identifier: 0x0004c942

   Device Boot      Start         End      Blocks    Id  System
Command (m for help):
```

- Here i deleted existing partitions and “p” is the command to print all existing partitions so here there is no partitions
- Now am creating partitionings using “n” command

```

Command (m for help): n
Partition type:
  p   primary (0 primary, 0 extended, 4 free)
  e   extended
Select (default p): p
Partition number (1-4, default 1):
Using default value 1
First sector (2048-15523839, default 2048):
Using default value 2048
Last sector, +sectors or +size{K,M,G} (2048-15523839, default 15523839): +512M

Command (m for help): n
Partition type:
  p   primary (1 primary, 0 extended, 3 free)
  e   extended
Select (default p): p
Partition number (1-4, default 2):
Using default value 2
First sector (1050624-15523839, default 1050624):
Using default value 1050624
Last sector, +sectors or +size{K,M,G} (1050624-15523839, default 15523839):
Using default value 15523839

Command (m for help): p

Disk /dev/sdb: 7948 MB, 7948206080 bytes
245 heads, 62 sectors/track, 1021 cylinders, total 15523840 sectors
Units = sectors of 1 * 512 = 512 bytes
Sector size (logical/physical): 512 bytes / 512 bytes
I/O size (minimum/optimal): 512 bytes / 512 bytes
Disk identifier: 0x0004c942

   Device Boot      Start         End      Blocks   Id  System
/dev/sdb1            2048        1050623        524288   83   Linux
/dev/sdb2          1050624       15523839       7236608   83   Linux

Command (m for help): █

```

- Here i created two primary partitions in that for first partition i assigned 512MB and rest of the memory assigned to partition two
- In embedded boards u-boot is compatible with FAT file system and in two partitions one is used for loadable files and another used for root filesystem.
- If you want boot your board from sd card you need create one boot partition and one root partition.
- Now change the system id of partition 1 using “t”

```

Command (m for help): t
Partition number (1-4): 1
Hex code (type L to list codes): L

 0 Empty                24 NEC DOS              81 Minix / old Lin   bf Solaris
 1 FAT12                27 Hidden NTFS Win    82 Linux swap / So  c1 DRDOS/sec (FAT-
 2 XENIX root           39 Plan 9              83 Linux             c4 DRDOS/sec (FAT-
 3 XENIX usr            3c PartitionMagic     84 OS/2 hidden C:   c6 DRDOS/sec (FAT-
 4 FAT16 <32M          40 Venix 80286        85 Linux extended   c7 Syrix
 5 Extended            41 PPC PReP Boot      86 NTFS volume set  da Non-FS data
 6 FAT16               42 SFS                87 NTFS volume set  db CP/M / CTOS / .
 7 HPFS/NTFS/exFAT     4d QNX4.x              88 Linux plaintext  de Dell Utility
 8 AIX                 4e QNX4.x 2nd part    8e Linux LVM        df BootIt
 9 AIX bootable        4f QNX4.x 3rd part    93 Amoeba           e1 DOS access
 a OS/2 Boot Manag    50 OnTrack DM         94 Amoeba BBT       e3 DOS R/O
 b W95 FAT32          51 OnTrack DM6 Aux   9f BSD/OS           e4 SpeedStor
 c W95 FAT32 (LBA)    52 CP/M              a0 IBM Thinkpad hi  eb BeOS fs
 e W95 FAT16 (LBA)    53 OnTrack DM6 Aux   a5 FreeBSD          ee GPT
 f W95 Ext'd (LBA)    54 OnTrackDM6        a6 OpenBSD          ef EFI (FAT-12/16/
10 OPUS               55 EZ-Drive          a7 NeXTSTEP         f0 Linux/PA-RISC b
11 Hidden FAT12       56 Golden Bow        a8 Darwin UFS        f1 SpeedStor
12 Compaq diagnost    5c Priam Edisk        a9 NetBSD            f4 SpeedStor
14 Hidden FAT16 <3    61 SpeedStor         ab Darwin boot       f2 DOS secondary
16 Hidden FAT16       63 GNU HURD or Sys   af HFS / HFS+        fb VMWare VMFS
17 Hidden HPFS/NTF    64 Novell Netware     b7 BSDI fs           fc VMWare VMKCORE
18 AST SmartSleep     65 Novell Netware     b8 BSDI swap         fd Linux raid auto
1b Hidden W95 FAT3    70 DiskSecure Mult   bb Boot Wizard hid   fe LANstep
1c Hidden W95 FAT3    75 PC/IX             be Solaris boot      ff BBT
1e Hidden W95 FAT1    80 Old Minix

Hex code (type L to list codes): b
Changed system type of partition 1 to b (W95 FAT32)

```

- I changed my partition 1 id as **W95 FAT32**

```

Command (m for help): p

Disk /dev/sdb: 7948 MB, 7948206080 bytes
245 heads, 62 sectors/track, 1021 cylinders, total 15523840 sectors
Units = sectors of 1 * 512 = 512 bytes
Sector size (logical/physical): 512 bytes / 512 bytes
I/O size (minimum/optimal): 512 bytes / 512 bytes
Disk identifier: 0x0004c942

   Device Boot      Start         End      Blocks   Id  System
/dev/sdb1             2048     1050623       524288    b   W95 FAT32
/dev/sdb2          1050624     15523839       7236608   83   Linux

Command (m for help): ^[[B

```

- Enable the boot flag for partition 1 using “a” command

```
Command (m for help): a
Partition number (1-4): 1

Command (m for help): p

Disk /dev/sdb: 7948 MB, 7948206080 bytes
245 heads, 62 sectors/track, 1021 cylinders, total 15523840 sectors
Units = sectors of 1 * 512 = 512 bytes
Sector size (logical/physical): 512 bytes / 512 bytes
I/O size (minimum/optimal): 512 bytes / 512 bytes
Disk identifier: 0x0004c942
```

Device	Boot	Start	End	Blocks	Id	System
/dev/sdb1	*	2048	1050623	524288	b	W95 FAT32
/dev/sdb2		1050624	15523839	7236608	83	Linux

```
Command (m for help):
```

- Then alter the previous partition table with new partitions using “w” this will overwrite the partition table

```
Command (m for help): w
The partition table has been altered!

Calling ioctl() to re-read partition table.

WARNING: If you have created or modified any DOS 6.x
partitions, please see the fdisk manual page for additional
information.
Syncing disks.
root@veda:/home/documents#
```

SD Card Formating

Formating means creation of file system on the disk for accessing.

Upto now we partitioned the card but its not accessable with out creating any file system .

Here we create Fat file system for boot partition and linux Ext3 file system for root partition.

- For formating in linux widely used tool is mkfs.
- Before doing format unmount the partitions.
- For Fat filesystem command as follows.

- `mkfs.vfat -F 32 /dev/sdb1 -n BOOT`

```
root@veda:/home/documents# mkfs.vfat -F 32 /dev/sdb1 -n BOOT
mkfs.fat 3.0.26 (2014-03-07)
root@veda:/home/documents#
```

- For Ext3 linux filesystem command is

`mkfs.ext3 /dev/sdb2 -L ROOT`

```
root@veda:/home/documents# mkfs.ext3 /dev/sdb2 -L ROOT
mke2fs 1.42.9 (4-Feb-2014)
Filesystem label=ROOT
OS type: Linux
Block size=4096 (log=2)
Fragment size=4096 (log=2)
Stride=0 blocks, Stripe width=0 blocks
452480 inodes, 1809152 blocks
90457 blocks (5.00%) reserved for the super user
First data block=0
Maximum filesystem blocks=1853882368
56 block groups
32768 blocks per group, 32768 fragments per group
8080 inodes per group
Superblock backups stored on blocks:
    32768, 98304, 163840, 229376, 294912, 819200, 884736, 1605632

Allocating group tables: done
Writing inode tables: done
Creating journal (32768 blocks): done
Writing superblocks and filesystem accounting information: done

root@veda:/home/documents#
```