

An Incomplete Overview of some Applications of Game Theory to Patient Flow

Vincent Knight

Cardiff University
Cardiff, UK
knightva@cf.ac.uk

Paul Harper

Cardiff University
Cardiff, UK
harper@cf.ac.uk

Jeff Griffiths

Cardiff University
Cardiff, UK
griffiths@cf.ac.uk

Izabela Komenda

Cardiff University
Cardiff, UK
komendai@cf.ac.uk

Rob Shone

Cardiff University
Cardiff, UK
shoner@cf.ac.uk

ABSTRACT

Describe paper.

KEYWORDS. Patient Flow, Game Theory, Queueing Theory

Main Area: Healthcare

1. Introduction

- Review GT in HC in general (small);
- Review congestion type games;
- PoA;
- Structure.

2. Choosing queues

This section describes how patient choices between various congestion affected services may be modelled. In particular the situation shown diagrammatically in Figure ?? is considered: patients have a choice amongst $M/M/c$ queues.

Show diagram.

There are two approaches to solving this problem: assuming that patients observe or not the system states before choosing a facility. A rigorous comparison of these two approaches for individuals choosing to join an $M/M/1$ queue is given in [].

An unobservable study is given in [] where routing games [?] are used to study the system described. The routing game used is shown in ?? To be able to obtain the PoA for a given instance the following mathematical program must be solved:

OPTMP:
minimise (??)

NASHMP:
minimise (??)

such that:

$$\sum_{j=1}^n \lambda_{ij} \leq \Lambda_i \text{ for all } i \in [m] \quad (1)$$

$$\lambda_{ij} \in \mathbb{R}_{\geq 0}^{m \times n} \text{ for all } i \in [m], j \in [n] \quad (2)$$

$$\sum_{i=1}^m \lambda_{ij} < c_j \mu_j \text{ for all } j \in [n] \quad (3)$$

$$C(\lambda) = \sum_{i=1}^m \alpha_i \sum_j^n d_{ij} \lambda_{ij} + \sum_{j=1}^n \sum_{i=1}^m \lambda_{ij} w_j \left(\sum_{i=1}^m \lambda_{ij} \right) + \sum_{i=1}^m \beta_i \left(\Lambda_i - \sum_{j=1}^n \lambda_{ij} \right) \quad (4)$$

and:

$$\Phi(\lambda) = \sum_{i=1}^m \alpha_i \sum_j^n d_{ij} \lambda_{ij} + \sum_{j=1}^n \int_0^{\sum_{i=1}^m \lambda_{ij}} w_j(x) dx + \sum_{i=1}^m \beta_i \left(\Lambda_i - \sum_{j=1}^n \lambda_{ij} \right) \quad (5)$$

The constant $\alpha_i \in \mathbb{R}_{\geq 0}$ is simply a weighting statistic for the relative importance of travel distances to the other factors (once again allowing for this coefficient to be dependent on population partitioning).

3. CCU Work

- IK Paper

4. EU and EMV Interface

- Describe model;
- Show some results.

5. Conclusions

Referências

Anna, A. (1996), Comunicação, *Atas do XXVIII SBPO*, 123-134.

Gates, B., *Um Livro Muito Bom*, Editor, Local, 2003.

Pelé, E. N. e Romário, R. R., Exemplo de artigo em livro, em Windows, P. T. e Linux, V. G. (Eds.), *Coletânea de Artigos*, Editor, Local, 123-133, 2004.

Silva, A. B., Souza, C. D. e Santos, E. F., Título de um relatório técnico disponível na Internet, *Relatórios de Pesquisa em Engenharia de Produção*, n. 4, Universidade Z, 1999

(www.universidade.br/rel, 4, 2001.

Smith, S. e Jones, J. (2002), A paper on Operations Research, *Pesquisa Operacional*, 32, 5-44.