

Code Explanation

Configuration Settings for E2E Policy Services Data Extraction Pipeline

This code defines the configuration settings for the E2E Policy Services data extraction pipeline, including database connection settings, source and target tables, batch size, and default values.

Overview of the Code

The code is written in Python and is used to configure the data extraction pipeline. It includes settings for connecting to source and target databases, specifying source and target tables, and defining default values.

Step 1: Defining Database Connection Settings

The code starts by defining the database connection settings for both the source and target databases. These settings include the JDBC URL, database name, username, password, and driver.

```
DB_CONFIG = {
    "source": {
        "jdbc_url": "jdbc:sqlserver://source-server:1433",
        "database": "E2E_POLICYSERVICES",
        "user": "${spark.sql.source.user}",
        "password": "${spark.sql.source.password}",
        "driver": "com.microsoft.sqlserver.jdbc.SQLServerDriver"
    },
    "target": {
        "jdbc_url": "jdbc:oracle:thin:@target-server:1521:ORCL",
        "user": "${spark.sql.target.user}",
        "password": "${spark.sql.target.password}",
        "driver": "oracle.jdbc.driver.OracleDriver"
    }
}
```

Step 2: Specifying Source Tables

The next step is to specify the source tables that will be used for data extraction. These tables are defined in a dictionary where the keys are the table aliases and the values are the actual table names.

```
SOURCE_TABLES = {
    "T_TX_REQUEST_POLICY": "E2E_POLICYSERVICES.T_TX_REQUEST_POLICY",
    "T_TX_BASIC": "E2E_POLICYSERVICES.T_TX_BASIC",
    "T_TX_RELATION": "E2E_POLICYSERVICES.T_TX_RELATION",
    "T_TX_REQUEST": "E2E_POLICYSERVICES.T_TX_REQUEST",
    "T_TX_DTL_BENEFICIARY_CHANGE": "E2E_POLICYSERVICES.T_TX_DTL_BENE"
    "FIICIARY_CHANGE"
}
```

Step 3: Defining Target Table

The target table where the extracted data will be loaded is specified.

```
TARGET_TABLE = "STG E2E BC K2H TXDB DATA"
```

Step 4: Setting Batch Size for Processing

The batch size for processing is defined, which determines the number of records to be processed in each batch.

```
BATCH_SIZE = 100000
```

Step 5: Defining Default Values

Finally, default values are defined for certain fields.

```
DEFAULT_VALUES = {  
    "DATA_TYPE": "BENEFICIARY_CHANGE",  
    "POLICY_TYPE": "K2H",  
    "MC_CRNCY": "JPY"  
}
```