

Technical Requirement Document

Here is the Technical Requirement Document (TRD) based on the provided Functional Requirement Document (FRD):

TR-DPACY-001: Execute DPAddressChangeYUYU Workflow

Related Functional Requirement(s): FR-DPACY-001

Objective: Implement a workflow to execute wf_E2E_AC_TXDBH_DP_YUYU_CREATION on demand, triggered by an upstream control.

Target Cluster Configuration:

- Cluster Name: Informatica PowerCenter Cluster
- Informatica PowerCenter Version: 10.5
- Node Type: Application Server
- Driver Node: Primary Node
- Worker Nodes: Multiple Nodes for scalability
- Autoscaling: Enabled
- Auto Termination: Disabled
- Libraries Installed: Informatica PowerCenter SDK, required drivers for database connections

Source Data Details:

- Dataset Name: STG_E2E_AC_TXDBH_DATA
- Location: Relational Database (e.g., Oracle)
- Format: Table
- Description: Staging table for E2E AC TXDBH data

Target Data Details:

- Output Name: DPAddressChangeYUYU Flat File
- Location: Designated File System (e.g., HDFS, NFS)
- Format: Flat File
- Description: Output file for DPAddressChangeYUYU data

Job Flow / Pipeline Stages:

1. Start workflow
2. Execute s_SRC_REC_CNT_CHK session
3. Evaluate TgtSuccessRows and proceed accordingly
4. Execute CMD_TRIGGER_FILE_CREATION or s_YUYU_CREATION session

5. Execute CMD_TRIGGER_DEL after s_YUYU_CREATION

Data Transformations / Business Logic:

- Step: Count incoming records in s_SRC_REC_CNT_CHK session
- Description: Count records from STG_E2E_AC_TXDBH_DATA
- Transformation Logic: Use Aggregator to count records
- Step: Create DPAAddressChangeYUYU File in s_YUYU_CREATION session
- Description: Transform data and generate output file
- Transformation Logic: Use Source Qualifier, LKP_YUYU_CLNT, LKP_YUYUK_CLN, EXP_ADD_CHNG, EXP_YUYU_CHNG, and SEQTRANS

Error Handling and Logging:

- Command tasks fail only their scope, and workflow continues
- Session errors do not trigger rollback; Commit On EOF = YES
- Lookup failures produce null outputs for associated fields, and processing continues

TR-DPACY-002: Count Incoming Records in s_SRC_REC_CNT_CHK Session

Related Functional Requirement(s): FR-DPACY-002

Objective: Implement a session to count incoming records in STG_E2E_AC_TXDBH_DATA.

Target Cluster Configuration: Same as TR-DPACY-001

Source Data Details: Same as TR-DPACY-001

Target Data Details: None

Job Flow / Pipeline Stages:

1. Read data from STG_E2E_AC_TXDBH_DATA using Source Qualifier
2. Count incoming records using Aggregator

Data Transformations / Business Logic:

- Step: Count incoming records
- Description: Count records from STG_E2E_AC_TXDBH_DATA
- Transformation Logic: Use Aggregator to count records

Error Handling and Logging: Same as TR-DPACY-001

TR-DPACY-003: Create DPAAddressChangeYUYU File in s_YUYU_CREATION Session

Related Functional Requirement(s): FR-DPACY-003

Objective: Implement a session to create the DPAddressChangeYUYU file.

Target Cluster Configuration: Same as TR-DPACY-001

Source Data Details: Same as TR-DPACY-001

Target Data Details:

- Output Name: DPAddressChangeYUYU Flat File
- Location: Designated File System (e.g., HDFS, NFS)
- Format: Flat File
- Description: Output file for DPAddressChangeYUYU data

Job Flow / Pipeline Stages:

1. Read data from STG_E2E_AC_TXDBH_DATA using Source Qualifier with SQL override
2. Perform lookups using LKP_YUYU_CLNT and LKP_YUYUK_CLN
3. Apply transformations using EXP_ADD_CHNG and EXP_YUYU_CHNG
4. Generate SEQUENCE_NUMBER using SEQTRANS
5. Write data to DPAddressChangeYUYU flat file and STG_E2E_AC_TXDBH_DATA_TGT table

Data Transformations / Business Logic:

- Step: Transform data and generate output file
- Description: Apply transformations and generate output file
- Transformation Logic: Use Source Qualifier, LKP_YUYU_CLNT, LKP_YUYUK_CLN, EXP_ADD_CHNG, EXP_YUYU_CHNG, and SEQTRANS

Error Handling and Logging: Same as TR-DPACY-001

TR-DPACY-004: Write to DPAddressChangeYUYU Flat File

Related Functional Requirement(s): FR-DPACY-004

Objective: Implement a task to write transformed data to the DPAddressChangeYUYU flat file.

Target Cluster Configuration: Same as TR-DPACY-001

Source Data Details: Transformed data from s_YUYU_CREATION session

Target Data Details:

- Output Name: DPAddressChangeYUYU Flat File
- Location: Designated File System (e.g., HDFS, NFS)
- Format: Flat File
- Description: Output file for DPAddressChangeYUYU data

Job Flow / Pipeline Stages:

1. Write data to DPAddressChangeYUYU file with specified format and naming convention
2. Commit every 10,000 rows

Data Transformations / Business Logic: None

Error Handling and Logging: Same as TR-DPACY-001

TR-DPACY-005: Update Workflow Variables

Related Functional Requirement(s): FR-DPACY-005

Objective: Implement a task to update workflow variables after session success.

Target Cluster Configuration: Same as TR-DPACY-001

Source Data Details: Session success status

Target Data Details: Workflow variables

Job Flow / Pipeline Stages:

1. Update \$\$WF_FILE_TMSTMP with \$\$M_FILE_TMSTMP
2. Update \$\$wf_SOURCE_COUNT with \$\$M_REC_COUNT

Data Transformations / Business Logic: None

Error Handling and Logging: Same as TR-DPACY-001

TR-DPACY-006: Handle Errors and Exceptions

Related Functional Requirement(s): FR-DPACY-006

Objective: Implement error handling and logging mechanisms for workflow execution.

Target Cluster Configuration: Same as TR-DPACY-001

Source Data Details: Error logs and session logs

Target Data Details: Error logs and session logs

Job Flow / Pipeline Stages: None

Data Transformations / Business Logic: None

Error Handling and Logging:

- Command tasks fail only their scope, and workflow continues
- Session errors do not trigger rollback; Commit On EOF = YES
- Lookup failures produce null outputs for associated fields, and processing continues