

Functional Requirement Document

Here is the detailed Functional Requirement Document (FRD) based on the provided Business Requirement Document (BRD) and adhering to the specified template:

FR-E2E-001: Generate DP Address Change YUYU Extract and Update Staging Control/Audit Attributes

1. **Requirement ID:** FR-E2E-001

2. **Title:** Generate DP Address Change YUYU Extract and Update Staging Control/Audit Attributes

3. **Description:** The system must read address change candidate records from an Oracle staging source, generate a flat-file style target dataset containing specific fields, and update the staging table with processing metadata and key identifiers.

4. **Preconditions:**

- The source Oracle staging table `STG\_E2E\_AC\_TXDBH\_DATA` contains address change candidate records.
- The lookup tables `T\_YUYU\_CLNT` and `T\_YUYUK\_CLN` are available and contain the required data.

5. **Main Flow / Functional Steps:**

- Step 1: Source Read
 - Read address change candidate records from `STG\_E2E\_AC\_TXDBH\_DATA`.
- Step 2: Pre-Processing
 - Pass through key and address/phone fields.
 - Expose "PPAY_" fields used as fallback values.
- Step 3: Enrichment
 - Perform lookups on `T\_YUYU\_CLNT` and `T\_YUYUK\_CLN` to enrich owner name components (`POWN\_LNM`, `POWN\_FNM`, `POWN\_KNM`) by policy number (`T\_TX\_BASIC\_POLICY\_ID`).
- Step 4: Business Transformations
 - Derive formatted dates.
 - Normalize postal code (remove hyphens).
 - Apply address fallback logic when ZIP is missing.
 - Format phone numbers.
 - Concatenate owner names.
- Step 5: Outputs

- Generate `DPAAddressChangeYUYU` flat file:
- `SEQUENCE\_NUMBER` using `SEQTRANS.NEXTVAL`.
- `ORIGIN\_REQUEST\_ID`, `POLICY\_ID`, and other fields as specified.
- Update `STG\_E2E\_AC\_TXDBH\_DATA\_TGT` (Oracle staging table) with:
- Processing timestamp (`STG\_PROCESS\_DATE = SYSDATE`).
- Processing user (`STG\_PROCESS\_USERID = \$\$M\_PROCESS\_USERID`).
- Carry forward key identifiers and status fields.

Detailed Requirements in Bullet Points:

For DPAAddressChangeYUYU Flat File Generation:

- Generate a sequence number (`SEQUENCE\_NUMBER`) starting from 0 and incrementing by 1 for each record.
- Map `ORIGIN\_REQUEST\_ID`, `POLICY\_ID`, `RECEPTION\_DATE`, and other fields as per the specified transformation logic.
- Apply business rules for date formatting (BR-03), postal code normalization (BR-05), address fallback logic (BR-04), phone number formatting (BR-06), and policy owner name derivation (BR-07, BR-08).

For Staging Update:

- Update `STG\_E2E\_AC\_TXDBH\_DATA\_TGT` using the `DD\_UPDATE` strategy.
- Stamp `STG\_PROCESS\_DATE` with the current date (`SYSDATE`).
- Stamp `STG\_PROCESS\_USERID` with the mapping parameter/variable `\$\$M\_PROCESS\_USERID`.
- Carry forward key identifiers (`T\_TX\_REQUEST\_REQUEST\_ID`, `T\_TX\_BASIC\_TRANS\_ID`, etc.) and status fields.

Notes:

- The format masks for `RECEPTION\_DATE` conversion should be confirmed for consistency (BR-03).
- Phone formatting rules should be confirmed, especially regarding segment lengths (BR-06).
- Source selection criteria and output file specifications (delimiter, encoding, file naming, header/trailer) need to be confirmed.
- Staging update columns beyond process stamps should be reviewed for additional fields that might need to be updated.