

## Code Explanation

### Configuration Settings for E2E Policy Services Control Processes

The provided code is a Python configuration file named `src/config.py`. It contains various configuration settings for E2E Policy Services Control processes, including Oracle connection settings, default output configuration, and logging configuration.

#### Overview of the Code

The code defines three main configuration dictionaries: `ORACLE\_CONFIG`, `DEFAULT\_OUTPUT\_CONFIG`, and `LOG\_CONFIG`, which store settings for connecting to an Oracle database, specifying output file details, and logging, respectively.

#### ## Step 1: Defining Oracle Connection Configuration

This step involves defining the configuration settings required to connect to an Oracle database. The configuration is stored in the `ORACLE\_CONFIG` dictionary.

```
ORACLE_CONFIG = {  
    "driver": "oracle.jdbc.driver.OracleDriver",  
    "url": "jdbc:oracle:thin:@//oracle-host:1521/service_name",  
    "user": "ZSYSE2EDEV",  
    "password_scope": "oracle",  
    "password_key": "password"  
}
```

#### ## Step 2: Specifying Default Output Configuration

In this step, the default configuration for output files is defined. The settings include the base path for output files, file format, delimiter, and whether to include a header. These settings are stored in the `DEFAULT\_OUTPUT\_CONFIG` dictionary.

```
DEFAULT_OUTPUT_CONFIG = {  
    "base_path": "/mnt/control/source_counts/",  
    "file_format": "csv",  
    "delimiter": ",",  
    "include_header": False  
}
```

#### ## Step 3: Configuring Logging Settings

This step involves defining the logging configuration for the application. The logging level and log message format are specified in the `LOG\_CONFIG` dictionary.

```
LOG_CONFIG = {  
    "level": "INFO",  
    "format": "%(asctime)s - %(name)s - %(levelname)s - %(message)s"  
}
```