

ELECTRO AUTOMOTIVE
P.O. BOX 1113 FELTON CA. 95018-1113
PHONE 408-429-1989 FAX 408-429-1907
DRAWN BY MICHAEL P. BROWN

CHEVY SPRINT / GEO METRO ADAPTOR
1985 to 1992
FOR USE WITH NON-STANDARD 8" RING

DRILL AND TAP AS PER STD 8" PRINT

SEE NOTE A

BORE TO SUIT BUSHING

NOTE A--DRILL 11/64" THROUGH
BUSHING. INSTALL IN HUB TO LOCATE
HOLES IN HUB. THEN TAP 10-24 1"
DEEP

NOTE B-- DRILL 13/64" COUNTERBORE
23/64" x 3/8" DEEP. THEN COUNTERBORE
1 3/16" D. x 1/16" DEEP FOR PILOT
BEARING CLEARANCE RECESS

NOTE C--DRILL 11/32" x 3/4" DEEP
TAP 10-1.25 mm x 5/8" DEEP

NOTE D-- DRILL 17/32" COUNTERSINK TO
TO SUIT 1/2"-13 FLATHEAD BOLT

RING DIAMETERS
AND BOLT CIRCLES
AS PER STD 8" RING
PRINT

SUPPLY 3/8"-16 x 1 1/4"
SOCKET HEAD CAP SCREW
FOR RING TO MOTOR
ASSEMBLY

