

State Review — Version Comparison: Data Dictionary

Companion reference for the **version-comparison results**. The table places two State Data-Quality Review outputs side by side, one row per cell, so each metric can be read as base, new, and the change between them.

Output table	starset-analytics-national.analyst_testing_tables.state_review_comparison_v8_2_vs_preprod_v9_DEV4
Base (_base)	state_data_quality_review_v8_2 — the established version
New (_new)	state_data_quality_review_preprod_v9_DEV4 — the version under evaluation

Orientation. Every `delta_*` and `pct_change_*` is computed as **new** – **base**. A positive value means the new version is higher than the base version.

Grain & coverage

One row per (row_grain, state, msa_id, carrier_plan_name, billing_class, setting_type) — the same grain as the two review tables. The join is a **FULL OUTER JOIN**, so cells that exist in only one version are retained and identified by `presence_status` rather than dropped.

Reading the results. The headline rows are `row_grain` IN ('NATIONAL','STATE') with `billing_class` = 'TOTAL' and `setting_type` = 'TOTAL'. MSA rows are attributed per state, so a multi-state MSA repeats once per state with identical MSA-level metrics (use the multi-state markers below to avoid double-counting). `flag_changed_any` = 1 is the catch-all for "something moved in this cell."

Identity & scope

Identity columns are **COALESCE**d across the two versions, so single-version rows still carry their keys.

Column	Type	Description
row_grain	STRING	'NATIONAL', 'STATE', or 'MSA'
state	STRING	Two-letter state abbreviation; NULL on NATIONAL
msa_id	STRING	MSA identifier; NULL on STATE/NATIONAL
msa_cbsa_name	STRING	MSA name; NULL on STATE/NATIONAL
carrier_plan_name	STRING	One of the four anchor carriers (Aetna Choice POS, BCBS PPO, Cigna OAP, UHC Choice POS Plus)
billing_class	STRING	'institutional', 'professional', or 'TOTAL'
setting_type	STRING	'inpatient', 'outpatient', or 'TOTAL'
pos	STRING	Friendly point-of-service label (All / Inpatient / Outpatient / Professional)
presence_status	STRING	'BOTH' = cell in both versions; 'NEW_ONLY' = appeared in new; 'BASE_ONLY' = dropped from base

Headline spend

Column	Type	Description
total_weighted_rate_base / _new	NUMERIC	Spend per 1,000 population in each version
delta_total_weighted_rate	NUMERIC	new – base (absolute)
pct_change_total_weighted_rate	NUMERIC	(new – base) / base × 100. NULL when base is 0 or the cell is single-version

Source-mix change (percentage points)

Each share carries base, new, and the percentage-point delta. The three shares sum to 100 within a version.

Column	Type	Description
pct_carrier_mrf_spend_base / _new	NUMERIC	Carrier-MRF share in each version
delta_pct_carrier_mrf	NUMERIC	new – base, in percentage points
pct_hospital_mrf_spend_base / _new	NUMERIC	Hospital-MRF share in each version
delta_pct_hospital_mrf	NUMERIC	new – base, in percentage points
pct_imputed_spend_base / _new	NUMERIC	Imputed share in each version
delta_pct_imputed	NUMERIC	new – base, in percentage points

Stoplight (quality) change (percentage points)

Column	Type	Description
pct_greenyellow_base / _new	NUMERIC	Green/Yellow share in each version
delta_pct_greenyellow	NUMERIC	new – base, in percentage points
pct_red_base / _new	NUMERIC	Red share in each version
delta_pct_red	NUMERIC	new – base, in percentage points
pct_missing_base / _new	NUMERIC	Missing share in each version
delta_pct_missing	NUMERIC	new – base, in percentage points

BCBS ratio, sample & multi-state markers

Column	Type	Description
spend_ratio_vs_bcbs_base / _new	NUMERIC	Carrier-vs-BCBS spend ratio in each version
delta_spend_ratio_vs_bcbs	NUMERIC	new – base
n_rates_greenyellow_base / _new	INT64	Green/Yellow rate count backing each version's row
n_msas_base / _new	INT64	MSAs feeding the row in each version (1 on MSA rows; distinct-MSA count on rollups)
n_states_in_msa_base / _new	INT64	State segments the MSA spans, per version; MSA rows only, NULL on STATE/NATIONAL
is_multistate_msa_base / _new	BOOL	n_states_in_msa > 1 per version; MSA rows only
n_states_in_msa / is_multistate_msa	INT64 / BOOL	Resolved (version-stable) marker via COALESCE(new, base) . Use to flag or limit the per-state duplicate rows of the multi-state MSAs so their metrics are not double-summed

Issue-label transitions

The most direct view of which cells changed their data-quality classification.

Column	Type	Description
review_label_base / _new	STRING	Canonical issue label in each version; clean when no canonical condition fired. Canonical conditions: Low Carrier MRF, Low Hospital MRF, High Red, High Missing
supplementary_label_base / _new	STRING	Supplementary reasons in each version (Off vs BCBS / Off vs Peers / Sparse Sample); clean when none fired
label_changed	INT64	1 if the canonical labels differ (including clean ↔ flagged)
label_transition	STRING	Readable transition, e.g. (clean) -> Low Carrier MRF , High Missing . NULL when unchanged
flag_canonical_count_base / _new	INT64	Number of canonical conditions (0–4) in each version
flag_needs_review_base / _new	INT64	Composite review-needed flag per version (1 when any canonical or supplementary condition fired)
review_direction	STRING	Canonical status change base→new: improved (fewer conditions in new), regressed (more), still_clean (zero in both), stable (same non-zero count). NULL when the cell exists in only one version

Change & swing flags

All 0/1 INT64. The three swing flags fire only when [presence_status](#) = 'BOTH' (a delta requires both sides). Thresholds are [DECLAREs](#) at the top of the script.

Column	Type	Fires when	Default threshold
flag_big_spend_swing	INT64	ABS(pct_change_total_weighted_rate) exceeds the relative-percent threshold	10%
flag_stoplight_swing	INT64	ABS delta in any of Green/Yellow, Red, or Missing exceeds the threshold	10 pp

Column	Type	Fires when	Default threshold
flag_source_swing	INT64	ABS delta in any of carrier, hospital, or imputed share exceeds the threshold	10 pp
flag_label_changed	INT64	review_label differs between versions	—
flag_appeared	INT64	Cell present in new only	—
flag_disappeared	INT64	Cell present in base only	—
flag_changed_any	INT64	Any swing flag, label change, or presence change fired — the catch-all filter	—