

Data Visualisation

Bagumaho Dominic

Task 1: Import

The required packages for this homework exercise have already been added.

1. Run the code chunk with the label 'load-packages' to load the required packages. Tipp: Click on the green play button in the top right corner of the code chunk.

```
library(gapminder)
library(ggplot2)
library(dplyr)
library(readr)
library(sf)
library(rnaturalearth)
```

Task 2: Transform for data in 2007

Fill in the gaps

1. A code chunk has already been created below.
2. Start with the `gapminder` object and add the pipe operator at the end of the line.
3. On a new line use the `filter()` function to narrow down the data for observation of the year 2007.
4. Use the assignment operator to assign the data to an object named `gapminder_2007`.
5. Run the code contained in the code chunk and fix any errors.
6. Next to the code chunk option `#| eval:` change the value from `false` to `true`.
7. Render the document and fix any errors.

```
gapminder_2007 <- gapminder |>
  filter(year == 2007)
```

Task 3: Summarize data for life expectancy by continent

Fill in the gaps

1. A code chunk has already been created.
2. Start with the `gapminder_2007` object and add the pipe operator at the end of the line.
3. On a new line use the `group_by()` function to group the operations that follow by continent. Add the pipe operator at the end of the line.
4. On a new line use the `summarise()` function to calculate the number of observations (`count`) and median life expectancy.
5. Use the assignment operator to assign the data to an object named `gapminder_summary_2007`.
6. Run the code contained in the code chunk and fix any errors.
7. Next to the code chunk option `#| eval:` change the value from `false` to `true`.
8. Render the document and fix any errors.

```
gapminder_summary_2007 <- gapminder_2007 |>
  group_by(continent) |>
  summarise(
    count = n(),
    lifeExp = median(lifeExp)
  )
```

Task 4: Summarize data for life expectancy by continent and year

Fill in the gaps

1. A code chunk has already been created.
2. Start with the `gapminder` object and add the pipe operator at the end of the line.
3. On a new line use the `group_by()` function to group the operations that follow by continent and year. Add the pipe operator at the end of the line.
4. On a new line use the `summarise()` function to calculate and median life expectancy.

5. Use the assignment operator to assign the data to an object named `gapminder_summary_continent_year`.
6. Run the code contained in the code chunk and fix any errors.
7. Next to the code chunk option `#| eval:` change the value from `false` to `true`.
8. Render the document and fix any errors.

```
gapminder_summary_continent_year <- gapminder|>
  group_by(continent, year)|>
  summarise(lifeExp = median(lifeExp))
```

Task 5: Data visualization

Thank you for working through the previous tasks. We are convinced that you have done a great job, but because the task descriptions aren't always unambiguous, we have imported the data that we would have expected to be created and stored in the objects `gapminder_2007`, `gapminder_summary_2007` and `gapminder_summary_continent_year` at the previous code chunks. This is to ensure that you can work through the following tasks.

1. Run the code contained in the code chunk below to import the data.

```
gapminder_2007 <- read_rds(here::here("data/gapminder-2007.rds"))

gapminder_summary_2007 <- read_rds(here::here("data/gapminder-summary-2007.rds"))


gapminder_summary_continent_year <- read_rds(here::here("data/gapminder-summary-continent-
```

Task 6: Create a boxplot

1. Add a new code chunk below point 5.
2. Use the `ggplot()` function and the `gapminder_2007` object to create a boxplot with the following aesthetic mappings:
 - continent to the x-axis;
 - life expectancy to the y-axis;
 - continent to color using the `fill = continent` argument inside `aes()`
3. Do not display (ignore) the outliers in the plot. **Note: Use a search engine or an AI tool to find the solution and add the link to the solution you have found.**

4. Run the code contained in the code chunk and fix any errors.
5. What are the data types of the three variables used for aesthetic mappings?


```
ggplot(data=gapminder_2007,  
       mapping=aes(x = continent,  
                   y = lifeExp,  
                   fill = continent)) +  
geom_boxplot(outlier.shape = NA )
```



Task 7: Create a timeseries plot

1. Add a new code chunk below.
2. Use the `ggplot()` function and the `gapminder_summary_continent_year` object to create a connected scatterplot (also called timeseries plot) using the `geom_line()` and `geom_point()` functions with the following aesthetic mappings:
 - year to the x-axis;
 - life expectancy to the y-axis;
 - continent to color using the `color = continent` argument inside `aes()`
3. Run the code contained in the code chunk and fix any errors.

```
ggplot(data = gapminder_summary_continent_year,
       mapping = aes(x = year,
                     y = lifeExp,
                     color = continent)) +
  geom_line() +
  geom_point()
```




Task 8: Create a barplot

with `geom_col()`

1. Add a new code chunk below.
2. Use the `ggplot()` function and the `gapminder_summary_2007` object to create a barplot using the `geom_col()` function with the following aesthetic mappings:
 - `continent` to the x-axis;
 - `count` to the y-axis;
3. Run the code contained in the code chunk and fix any errors.


```
ggplot(data = gapminder_summary_2007,
       mapping = aes(x = continent,
                     y = count,
                     fill = continent)) +
  geom_col()
```



with `geom_bar()`

1. Add a new code chunk below.
2. Use the `ggplot()` function and the `gapminder_2007` object to create a barplot using the `geom_bar()` function with the following aesthetic mappings:
 - `continent` to the x-axis;
3. Run the code contained in the code chunk and fix any errors.
4. The plot is identical to the plot created with `geom_col()`. Why? What does the `geom_bar()` function do? Write your text here:

```
ggplot(data = gapminder_2007,
       mapping = aes(x = continent,
                     fill = continent)) +
```



Answer (By Dominic):

“**geom_bar()**” **function** makes the height of the bars proportional to the number of observations of the variable on the x-axis in the `gap_minder` object.

The “`geom_col()`” function however makes the height of the bars proportional to the data values in the `gap_minder_2007` object (Thus for the “`geom_col()`” function, the y-variable values must be specified in the data object). These two sets of observations and data values being the same, the two plots were the same.

Task 9: Create a histogram

1. Add a new code chunk below.
2. Use the `ggplot()` function and the `gapminder_2007` object to create a histogram using the `geom_histogram()` function with the following aesthetic mappings:
 - life expectancy to the x-axis;
 - continent to color using the `fill = continent` argument inside `aes()`
3. Run the code contained in the code chunk and fix any errors.

4. Inside the `geom_histogram()` function, add the following arguments and values:
 - `col = "grey30"`
 - `breaks = seq(40, 85, 2.5)`
5. Run the code contained in the code chunk and fix any errors.
6. Describe how the `geom_histogram()` function is similar to the `geom_bar()` function.

Answer (By Dominic):


`geom_histogram()` function just like the `geom_bar()` function does not require specifying the dependent(y-) variable as it plots the number of observations of the x-variable in the object

7. What happens by adding the ‘breaks’ argument? Play around with the numbers inside of `seq()` to see what changes. Describe here what you observe:

Answer (By Dominic):

The “breaks” argument helps to create a regularly spaced sequence between numbers for example `Breaks = seq(40,85,2.5)` means that start the values from 40, end at 85 with an increment(interval) of 2.5 each time (40, 42.5, 45,, 85)

```
ggplot(data = gapminder_2007,  
       mapping = aes(x = lifeExp,  
                     fill = continent)) +  
geom_histogram(color = "grey30",  
              breaks = seq(40, 85, 2.5))
```





Task 10: Scatterplot and faceting

1. Add a new code chunk below.
2. Use the `ggplot()` function and assign `gapminder_2007` and create a scatterplot using the `geom_point()` function with the following aesthetic mappings:
 - `gdpPerCap` the x-axis;
 - `lifeExp` to the y-axis;
 - `population` to the size argument;
 - `country` to color using the `color = continent` argument inside `aes()`
4. Run the code contained in the code chunk and fix any errors.
5. Use the variable `continent` to facet the plot by adding: `facet_wrap(~continent)`.
6. Run the code contained in the code chunk and fix any errors.

```
ggplot(data = gapminder_2007,
       mapping = aes(x = gdpPerCap,
                     y = lifeExp,
                     size = pop,
                     color = continent)) +
  geom_point() +
```

```
facet_wrap(~continent)
```



Task 11: Create a lineplot and use facets


1. A code chunk with complete code has already been prepared.
2. Run the code contained in the code chunk and fix any errors.
3. Remove the '#' sign at the line that starts with the `scale_color_manual()` function
4. What is stored in the `country_colors` object? Find out by executing the object in the Console (type it to the Console and hit enter). Do the same again, but with a question mark `?country_colors`.

Notes (By Dominic):

The "country_colors" shows hexadecimal color codes/schemes for countries and continents which describe the different amounts of red, green and blue in each color

5. Next to the code chunk option `#| eval:` change the value from `false` to `true`.
6. Render the document and fix any errors.

```
ggplot(data = gapminder,
       mapping = aes(x = year,
                     y = lifeExp,
                     group = country,
                     color = country)) +
  geom_line(lwd = 1, show.legend = FALSE) +
  facet_wrap(~continent) +
  scale_color_manual(values = country_colors) +
  theme_minimal()
```



Task 12: Create a choropleth Maps

You can also prepare maps with `ggplot2`. It's beyond the scope of the class to teach you the foundations of spatial data in R, but a popular package to work with spatial data is the `sf` (Simple Features) R Package. The `rnatrualearth` R Package facilitates world mapping by making [Natural Earth](#) map data more easily available to R users.

The code chunk below contains code for a world map that shows countries by income group. To view the map, do the following:

1. Run the code contained in the code chunk and fix any errors.
2. Next to the code chunk option `#| eval:` change the value from `false` to `true`.


3. Render the document and fix any errors.

```
world <- ne_countries(scale = "small", returnclass = "sf")

world |>
  mutate(income_grp = factor(income_grp, ordered = T)) |>
  ggplot(aes(fill = income_grp)) +
  geom_sf() +
  theme_void() +
  theme(legend.position = "top") +
  labs(fill = "Income Group:") +
  guides(fill = guide_legend(nrow = 2, byrow = TRUE))
```

Income Group:

	1. High income: OECD		2. High income: nonOECD		3. Upper middle
	4. Lower middle income		5. Low income		



The code for the code chunk is taken from here: More here: https://bookdown.org/alhdzsz/data_viz_ir/maps.ht

Working with spatial data in R

If you are interested in working with spatial data in R, then we recommend the following resources for further study:

- Geocomputation with R - Book: <https://geocompr.robinlovelace.net/>
- Simple Features for R - Article: <https://r-spatial.github.io/sf/articles/sf1.html>
- tmap: thematic maps in R - R Package: <https://r-tmap.github.io/tmap/>

Task 13: Data communication

In the YAML header (between the three dashes at the top of the document)

1. Add your name as the author of this document
2. Render the document and fix any errors

Task 14: Complete assignment

Stage, Commit & Push to GitHub

1. Open the Git pane in RStudio. It's in the top right corner in a separate tab.
2. **Stage** your changes by checking appropriate box next to all files (if you select one file with your mouse, you can then highlight them all with Ctrl + A on your keyboard and check all boxes)
3. Write a meaningful commit message (e.g. "Completed homework assignment 02.") in the **Commit message** box
4. Click **Commit**. Note that every commit needs to have a commit message associated with it.

Open an issue on GitHub

Once you have ensured that the Quarto document renders without errors and you have pushed all your changes to GitHub, you can complete the assignment by opening an issue on

1. Open github.com in your browser.
2. Navigate to the GitHub organisation for the course.
3. Find the repository md-02-assignments that ends with your GitHub username.
4. Click on the "Issues" tab.
5. Click on the green "New issue" button.
6. In the "Title" field write: "Completed module 2 assignments".
7. In the "Leave a comment" field, tag the course instructors @larnsce @mianzg @sskorik01 and ask some questions, if you like.