

# Dependency Parsing

## Data structures and algorithms for Computational Linguistics III

Çağrı Çöltekin  
ccoltekin@sfs.uni-tuebingen.de


University of Tübingen  
Seminar für Sprachwissenschaft

Winter Semester 2018–2019

Introduction Transition-based parsing Classification Graph based parsing Variations/improvements Evaluation

## Dependency grammars

a refresher



- No constituents, units of syntactic structure are words
- The structure of the sentence is represented by *asymmetric, binary* relations between syntactic units
- Each relation defines one of the words as the **head** and the other as **dependent**
- The links (relations) have labels (dependency types)
- Often an artificial *root* node is used for computational convenience

Ç. Çöltekin, SFS / University of Tübingen

WS 18–19 1 / 32

Introduction Transition-based parsing Classification Graph based parsing Variations/improvements Evaluation

## Dependency grammars

common assumptions, variations

- *Single-headed*: most dependency formalisms allow a word to have a single head
- *Acyclic*: most dependency formalism do not allow loops in the graph
- *Connected*: all nodes are reachable from the ‘root’ node
- *Projective*: no crossing dependencies

The above assumptions (except projectivity) are common in dependency parsing.

Ç. Çöltekin, SFS / University of Tübingen

WS 18–19 2 / 32

Introduction Transition-based parsing Classification Graph based parsing Variations/improvements Evaluation

## Dependency parsing

an overview

- Dependency parsing has many similarities with context-free parsing (e.g., the result is a tree)
- They also have some different properties (e.g., number of edges and depth of trees are limited)
- The process involves discovering the relations between words in a sentence
  - Determine the head of each word
  - Determine the relation type
- Dependency parsing can be
  - grammar-driven (hand crafted rules or constraints)
  - data-driven (rules/model is learned from a treebank)

Ç. Çöltekin, SFS / University of Tübingen

WS 18–19 3 / 32

Introduction Transition-based parsing Classification Graph based parsing Variations/improvements Evaluation

## Dependency parsing

common methods for data-driven parsers

There are two main approaches:

Graph-based search for the best tree structure, for example

- find minimum spanning tree (MST)
- adaptations of CF chart parser (e.g., CKY)

(in general, computationally more expensive)

Transition-based similar to shift-reduce parsing (used for programming language parsing)

- Single pass over the sentence, determine an operation (shift or reduce) at each step
- Linear time complexity
- We need an approximate method to determine the operation

Ç. Çöltekin, SFS / University of Tübingen

WS 18–19 4 / 32

Introduction Transition-based parsing Classification Graph based parsing Variations/improvements Evaluation

## Shift-Reduce parsing

a refresher through an example

Grammar  
 $S \rightarrow P \mid S + P \mid S - P$   
 $P \rightarrow \text{Num} \mid P \times \text{Num} \mid P / \text{Num}$

Parser states/actions	Stack	Input buffer	Action
		2 + 3 × 4	shift
	2	+ 3 × 4	reduce ( $P \rightarrow \text{Num}$ )
	P	+ 3 × 4	reduce ( $S \rightarrow P$ )
	S	+ 3 × 4	shift
	S +	3 × 4	shift
	S + 3	× 4	reduce ( $P \rightarrow \text{Num}$ )
	S + P	× 4	shift
	S + P ×	4	shift
	S + P × 4		reduce ( $P \rightarrow P \times \text{Num}$ )
	S + P		reduce ( $S \rightarrow S + P$ )
	S		accept

Ç. Çöltekin, SFS / University of Tübingen

WS 18–19 5 / 32

Introduction Transition-based parsing Classification Graph based parsing Variations/improvements Evaluation

## Transition-based parsing

differences from shift-reduce parsing

- The shift-reduce parsers (for programming languages) are deterministic, actions are determined by a table lookup
- Natural language sentences are ambiguous, hence a dependency parser’s actions cannot be made deterministic
- Operations are (somewhat) different: instead of reduce (using phrase-structure rules) we use *arc* operations connecting two nodes with a label
- Further operations are often defined (e.g., to deal with non-projectivity)

Ç. Çöltekin, SFS / University of Tübingen

WS 18–19 6 / 32

Introduction Transition-based parsing Classification Graph based parsing Variations/improvements Evaluation

## Transition based parsing


- Use a *stack* and a *buffer* of unprocessed words
- Parsing as predicting a sequence of transitions like
  - LEFT-ARC: mark current word as the head of the word on top of the stack
  - RIGHT-ARC: mark current word as a dependent of the word on top of the stack
  - SHIFT: push the current word on to the stack
- Algorithm terminates when all words in the input are processed
- The transitions are not naturally deterministic, best transition is predicted using a machine learning method

(Yamada and Matsumoto 2003; Nivre, Hall, and Nilsson 2004)

Ç. Çöltekin, SFS / University of Tübingen

WS 18–19 7 / 32

## A typical transition system



LEFT-ARC<sub>T</sub>:  $(\sigma \mid w_i, w_j \mid \beta, A) \Rightarrow (\sigma \quad, w_j \mid \beta, A \cup \{(w_j, r, w_i)\})$

- pop  $w_i$ ,
- add arc  $(w_j, r, w_i)$  to  $A$  (keep  $w_j$  in the buffer)

RIGHT-ARC<sub>T</sub>:  $(\sigma \mid w_i, w_j \mid \beta, A) \Rightarrow (\sigma \quad, w_i \mid \beta, A \cup \{(w_i, r, w_j)\})$

- pop  $w_i$ ,
- add arc  $(w_i, r, w_j)$  to  $A$ ,
- move  $w_i$  to the buffer

SHIFT:  $(\sigma \quad, w_j \mid \beta, A) \Rightarrow (\sigma \mid w_j, \quad \beta, A)$


- push  $w_j$  to the stack
- remove it from the buffer

(Kübler, McDonald, and Nivre 2009, p.23)


## Transition based parsing: example




## Transition based parsing: example



## Transition based parsing: example




## Transition based parsing: example




Note: We need **SHIFT** for NP attachment.


## Transition based parsing: example




## Transition based parsing: example




## Transition based parsing: example




## Transition based parsing: example




## Transition based parsing: example



## Transition based parsing: example



## Transition based parsing: example



## Making transition decisions

- In classical shift-reduce parsing the actions are deterministic
- In transition-based dependency parsing, we need to choose among all possible transitions
- The typical method is to train a (discriminative) classifier on features extracted from gold-standard *transition sequences*
- Almost any machine learning method method is applicable. Common choices include
  - Memory-based learning
  - Support vector machines
  - (Deep) neural networks

## Features for transition-based parsing

- The features come from the parser configuration, for example
  - The word at the top of the stack, (peeking towards the bottom of the stack is also fine)
  - The first/second word on the buffer
  - Right/left dependents of the word on top of the stack/buffer
- For each possible ‘address’, we can make use of features like
  - Word form, lemma, POS tag, morphological features, word embeddings
  - Dependency relations –  $(w_i, r, w_j)$  triples
- Note that for some ‘address’-‘feature’ combinations may be missing

## The training data

- We want features like,
  - lemma[Stack] = duck
  - POS[Stack] = NOUN
  - ...
- But treebank gives us:

1	Read	read	VERB	VB	Mood=Imp VerbForm=Fin	0	root
2	on	on	ADV	RB	-	1	advmod
3	to	to	PART	TO	-	4	mark
4	learn	learn	VERB	VB	VerbForm=Inf	1	xcomp
5	the	the	DET	DT	Definite=Def	6	det
6	facts	fact	NOUN	NNS	Number=Plur	4	obj
7	.	.	PUNCT	.	-	1	punct

- The treebank has the outcome of the parser, but none of our features.

## The training data


- The features for transition-based parsing have to be from *parser configurations*
- The data (treebanks) need to be preprocessed for obtaining the training data
- Construct a transition sequence by parsing the sentences, and using treebank annotations (the set  $A$ ) as an ‘oracle’
- Decide for
  - LEFT-ARC<sub>T</sub> if  $(\beta[0], r, \sigma[0]) \in A$
  - RIGHT-ARC<sub>T</sub> if  $(\sigma[0], r, \beta[0]) \in A$
  - and all dependents of  $\beta[0]$  are attached
  - SHIFT otherwise
- There may be multiple sequences that yield the same dependency tree, the above defines a ‘canonical’ transition sequence

## Non-projective parsing


- The transition-based parsing we defined so far works only for projective dependencies
- One way to achieve (limited) non-projective parsing is to add special operations:
  - SWAP operation that swaps tokens in swap and buffer
  - LEFT-ARC and RIGHT-ARC transitions to/from non-top words from the stack
- Another method is pseudo-projective parsing:
  - preprocessing to 'projectivize' the trees before training
    - The idea is to attach the dependents to a higher level head that preserves projectivity, while marking it on the new dependency label
  - post-processing for restoring the projectivity after parsing
    - Re-introduce projectivity for the marked dependencies

## Pseudo-projective parsing

Non-projective tree:



Pseudo-projective tree:



## Transition based parsing: summary/notes

- Linear time, greedy parsing
- Can be extended to non-projective dependencies
- One can use arbitrary features,
- We need some extra work for generating gold-standard transition sequences from treebanks
- Early errors propagate, transition-based parsers make more mistakes on long-distance dependencies
- The greedy algorithm can be extended to beam search for better accuracy (still linear time complexity)


## Classification

### a minimal introduction

- In transition-based parsing, transition decisions come from a classifier
- At each step during parsing, we have features like
  - form[Stack] = saw
  - lemma[Stack] = see
  - POS[Stack] = VERB
  - form[Buff] = her
  - lemma[Buff] = she
  - POS[Buf] = PRON
- We need to make a transition decision such as
  - SHIFT
  - RIGHT-ARC(OBL)
  - RIGHT-ARC(OBJ)
  - LEFT-ARC(ACL)
- We can use any multi-class classifier, examples in the literature include
  - SVMs
  - Decision Trees
  - Neural networks
  - ...

## Supervised learning

with a picture



## A few notes

- In ML, the focus is generalizations outside our training data
- In this class,
  - we will treat classification methods as a black box: no introduction to any particular method
  - we will have a short, hands-on introduction to (linear) classification
- Statistical NLP course (summer semester) includes a more detailed introduction to ML methods

## Graph-based parsing: preliminaries


- Enumerate all possible dependency trees
- Pick the best scoring tree
- Features are based on limited parse history (like CFG parsing)
- Two well-known flavors:
  - Maximum (weight) spanning tree (MST)
  - Chart-parsing based methods

eisner1996; McDonald, Pereira, Ribarov, and Hajič 2005

## MST parsing: preliminaries

### Spanning tree of a graph


- Spanning tree of a connected graph is a sub-graph which is a tree and traverses all the nodes
- For fully-connected graphs, the number of spanning trees are exponential in the size of the graph
- The problem is well studied
- There are efficient algorithms for enumerating and finding the optimum spanning tree on weighted graphs



## MST algorithm for dependency parsing


- For directed graphs, there is a polynomial time algorithm that finds the minimum/maximum spanning tree (MST) of a fully connected graph (Chu-Liu-Edmonds algorithm)
- The algorithm starts with a dense/fully connected graph
- Removes edges until the resulting graph is a tree

## MST example




For each node select the incoming arc with highest weight

## MST example




Detect the cycles, contract them to a 'single node'

## MST example



Pick the best arc into the combined node, break the cycle

## MST example



Once all cycles are eliminated, the result is the MST

## Properties of the MST parser

- The MST parser is non-projective
- There is an algorithm with  $O(n^2)$  time complexity (Tarjan 1977)
- The time complexity increases with typed dependencies (but still close to quadratic)
- The weights/parameters are associated with edges (often called 'arc-factored')
- We can learn the arc weights directly from a treebank
- However, it is difficult to incorporate non-local features

## CKY for dependency parsing

- The CKY algorithm can be adapted to projective dependency parsing
- For a naive implementation the complexity increases drastically  $O(n^6)$ 
  - Any of the words within the span can be the head
  - Inner loop has to consider all possible splits
- For projective parsing, the observation that the left and right dependents of a head are independently generated reduces the complexity to  $O(n^3)$

## Non-local features

- The graph-based dependency parsers use edge-based features
- This limits the use of more global features
- Some extensions for using 'more' global features are possible
- This often leads non-projective parsing to become intractable
- Another option is using beam search, and re-ranking based on different/global features

## External features

- For both type of parsers, one can obtain features that are based on unsupervised methods such as
  - clustering
  - dense vector representations (embeddings)
  - alignment/transfer from bilingual corpora/treebanks

## Evaluation metrics for dependency parsers

- Like CF parsing, exact match is often too strict
- Attachment score* is the ratio of words whose heads are identified correctly.
  - Labeled attachment score* (LAS) requires the dependency type to match
  - Unlabeled attachment score* (UAS) disregards the dependency type

- Precision/recall/F-measure* often used for quantifying success on identifying a particular dependency type

precision is the ratio of correctly identified dependencies (of a certain type)

recall is the ratio of dependencies in the gold standard that parser predicted correctly

f-measure is the harmonic mean of precision and recall

$$\left( \frac{2 \times \text{precision} \times \text{recall}}{\text{precision} + \text{recall}} \right)$$

## Averaging evaluation scores

- Average scores can be
  - macro-averaged over sentences
  - micro-averaged over words

- Consider a two-sentence test set with

	words	correct
sentence 1	30	10
sentence 2	10	10

- word-based average attachment score: 50% (20/40)
- sentence-based average attachment score: 66% ((1 + 1/3)/2)

## References / additional reading material


- Kübler, McDonald, and Nivre (2009) is an accessible book on to dependency parsing
- The new version of Jurafsky and Martin (2009) also includes a [draft chapter](#) on dependency grammars and dependency parsing

## Errors from different parsers

- Different parsers make different errors
  - Transition based parsers do well on local arcs, worse on long-distance arcs
  - Graph based parsers tend to do better on long-distance dependencies
- Parser combination is a good way to combine the powers of different models. Two common methods
  - Majority voting: train parsers separately, use the weighted combination of their results
  - Stacking: use the output of a parser as features for another

(McDonald and Satta 2007; Sagae and Lavie 2006; Nivre and McDonald 2008)

## Evaluation example



UAS	100%
LAS	50%
Precision <sub>nsubj</sub>	50%
Recall <sub>nsubj</sub>	100%
Precision <sub>obj</sub>	0% (assumed)
Recall <sub>obj</sub>	0%

## Dependency parsing: summary

- Dependency relations are often semantically easier to interpret
- It is also claimed that dependency parsers are more suitable for parsing free-word-order languages
- Dependency relations are between words, no phrases or other abstract nodes are postulated
- Two general methods:
  - transition based greedy search, non-local features, fast, less accurate
  - graph based exact search, local features, slower, accurate (within model limitations)
- Combination of different methods often result in better performance
- Non-projective parsing is more difficult
- Most of the recent parsing research has focused on better machine learning methods (mainly using neural networks)

## References / additional reading material (cont.)

- Eisner, Jason (1997). “Bilexical grammars and a cubic-time probabilistic parser”. In: *Proceedings of the Fifth International Conference on Parsing Technologies (IWPT)*.
- Jurafsky, Daniel and James H. Martin (2009). *Speech and Language Processing: An Introduction to Natural Language Processing, Computational Linguistics, and Speech Recognition*. second. Pearson Prentice Hall. isbn: 978-0-13-504196-3.
- Kübler, Sandra, Ryan McDonald, and Joakim Nivre (2009). *Dependency Parsing*. Synthesis lectures on human language technologies. Morgan & Claypool. isbn: 9781598295962.
- McDonald, Ryan, Fernando Pereira, Kiril Ribarov, and Jan Hajič (2005). “Non-projective Dependency Parsing Using Spanning Tree Algorithms”. In: *Proceedings of the Conference on Human Language Technology and Empirical Methods in Natural Language Processing*. HLT '05. Vancouver, British Columbia, Canada: Association for Computational Linguistics, pp. 523–530. doi: 10.3115/1220575.1220641. url: <http://dx.doi.org/10.3115/1220575.1220641>.
- McDonald, Ryan and Giorgio Satta (2007). “On the complexity of non-projective data-driven dependency parsing”. In: *Proceedings of the 10th International Conference on Parsing Technologies*. Association for Computational Linguistics, pp. 121–132.
- Nivre, Joakim, Johan Hall, and Jens Nilsson (2004). “Memory-based dependency parsing”. In: *Proceedings of the 8th Conference on Computational Natural Language Learning (CoNLL)*. Ed. by Hwee Tou Ng and Ellen Riloff, pp. 49–56.

## References / additional reading material (cont.)

- Nivre, Joakim and Ryan McDonald (June 2008). “Integrating Graph-Based and Transition-Based Dependency Parsers”. In: *Proceedings of ACL-08: HLT*. Columbus, Ohio: Association for Computational Linguistics, pp. 950–958. url: <http://www.aclweb.org/anthology/P/P08/P08-1108>.
- Sagae, Kenji and Alon Lavie (June 2006). “Parser Combination by Reparsing”. In: *Proceedings of the Human Language Technology Conference of the NAACL, Companion Volume: Short Papers*. New York City, USA: Association for Computational Linguistics, pp. 129–132. url: <http://www.aclweb.org/anthology/N/N06/N06-2033>.
- Tarjan, R. E. (1977). “Finding optimum branchings”. In: *Networks* 7.1, pp. 25–35. issn: 1097-0037. doi: [10.1002/net.3230070103](https://doi.org/10.1002/net.3230070103).
- Yamada, Hiroyasu and Yuji Matsumoto (2003). “Statistical dependency analysis with support vector machines”. In: *Proceedings of 8th international workshop on parsing technologies (IWPT)*. Ed. by Gertjan Van Noord, pp. 195–206.