

Minimum spanning trees

Data Structures and Algorithms for Computational Linguistics III
(ISCL-BA-07)Çağrı Çöltekin
ccoltekin@ifa.uni-tuebingen.deUniversity of Tübingen
Seminar für Sprachwissenschaft

Winter Semester 2021/22

version: 9a-07201-00221-02-06

So far...

a quick summary

- Recap: arrays, lists, queues, stacks, ...
- Common algorithmic patterns: recursion, brute force, divide and conquer, dynamic programming, greedy algorithms
- Analysis of algorithms: asymptotic, average/worst case analysis, big-O, big-Ω, big-Θ, complexity classes
- Sorting: insertion sort, quicksort, merge sort
- Trees: ordered trees, binary trees, tree traversals, ...
- Priority queues and heaps, heap sort
- Graphs: graph traversal, directed graphs

C. Çöltekin, ISCL | University of Tübingen

Winter Semester 2021/22 1 / 18


Introduction | Introduction | Prim-Jarnik | Kruskal | Directed graphs

Spanning trees

reminder

A spanning tree of a graph is

- A *spanning subgraph*: It includes all nodes
- It is a *tree*: It is *acyclic*, and *connected*



C. Çöltekin, ISCL | University of Tübingen

Winter Semester 2021/22 2 / 18

Introduction | Introduction | Prim-Jarnik | Kruskal | Directed graphs

Weighted graphs

- A *weighted graph* is a graph, where each edge is associated with a weight
- Weights can be any numeric value, but for some algorithms require
 - Non-negative weights
 - "Euclidean" weights: weights that are proper distance metrics
- Weights often indicate distance or cost, but they can also represent positive relations (e.g., affinity between nodes)
- Weight of a path is the sum of weights of the edges on the path



C. Çöltekin, ISCL | University of Tübingen

Winter Semester 2021/22 3 / 18

Introduction | Introduction | Prim-Jarnik | Kruskal | Directed graphs

Minimum spanning trees

- A minimum spanning tree (MST) is a spanning tree of weighted graph with minimum total weight
- MST is a fundamental problem with many applications, including
 - Network design (communication, transportation, electrical, ...)
 - Cluster analysis
 - Approximate solutions to traveling salesman problem
 - Object/network recognition in images
 - Avoiding cycles in broadcasting in communication networks
 - Dithering in images, audio, video
 - Error correction codes
 - DNA sequencing
 - ...



C. Çöltekin, ISCL | University of Tübingen

Winter Semester 2021/22 4 / 18

Introduction | Introduction | Prim-Jarnik | Kruskal | Directed graphs

The 'cut property'

- A cut of a graph is a partition that divides its nodes into two disjoint (non-empty) sets
- Given any cut, the edge with the lowest weight across the cut is in the MST



C. Çöltekin, ISCL | University of Tübingen


Winter Semester 2021/22 5 / 18

Introduction | Introduction | Prim-Jarnik | Kruskal | Directed graphs

Prim-Jarnik algorithm

intuition

- Prim-Jarnik algorithm is a greedy algorithm for finding an MST for a weighted undirected graph
- Algorithm starts with a single 'start' node, and grows the MST greedily
- At each step we consider a cut between nodes visited and the rest of the nodes, and select the minimum edge across the cut
- Repeat the process until all nodes are visited




C. Çöltekin, ISCL | University of Tübingen

Winter Semester 2021/22 6 / 18

Introduction | Introduction | Prim-Jarnik | Kruskal | Directed graphs

Prim-Jarnik algorithm

demonstration



C. Çöltekin, ISCL | University of Tübingen

Winter Semester 2021/22 7 / 18

Introduction | Introduction | Prim-Jarnik | Kruskal | Directed graphs

Prim-Jarnik algorithm

analysis

- pick any node s
 - $C[s] \leftarrow 0$
 - for each node $v \neq s$ do
 - $C[v] \leftarrow \infty$
 - $E[v] \leftarrow \text{None}$
 - $T \leftarrow \emptyset$
 - $Q \leftarrow \text{nodes}$
 - while Q is not empty do
 - Find the node v with min $C[v]$
 - Connect v to T
 - for edge (v, w) in Q do
 - if $\text{cost}(v, w) < C[w]$ then
 - $C[w] \leftarrow \text{cost}(v, w)$
 - $E[w] \leftarrow v$
- Two loops over number of nodes n , $O(n^2)$ if we need to search
 - If we use a priority queue for Q , then complexity becomes $O(m \log m)$

C. Çöltekin, ISCL | University of Tübingen

Winter Semester 2021/22 8 / 18

Introduction | Introduction | Prim-Jarnik | Kruskal | Directed graphs

Kruskal's algorithm

intuition

- Another popular algorithm for finding MST on undirected graphs
- The main idea is starting with each node in its own partition
- At each iteration, we choose the edge with the minimum weight across any two clusters, and join them
- Algorithm terminates when there are no clusters to join

C. Çöltekin, ISCL | University of Tübingen

Winter Semester 2021/22 9 / 18

Introduction | Introduction | Prim-Jarnik | Kruskal | Directed graphs

Kruskal's algorithm

demo



Kruskal's algorithm

analysis

- Loop over edges, but beware of the sorting requirement
 - With simple data structures then complexity is $O(m \log m)$
- $T \leftarrow \emptyset$
 - for each node v do
 - create $\text{cluster}(v)$
 - for (u, v) in edges sorted by weight do
 - if $\text{cluster}(u) \neq \text{cluster}(v)$ then
 - $T \leftarrow T \cup \{(u, v)\}$
 - union($\text{cluster}(u)$, $\text{cluster}(v)$)

C. Çöltekin, ISCL | University of Tübingen

Winter Semester 2021/22 10 / 18

Directed trees

- Trees with directed edges come in few flavors
 - A *rooted directed tree* (arborescence) is an acyclic directed graph where all nodes are reachable from the root node through a single directed path (this is what computational linguists simply call a *tree*)
 - An *anti-arborescence* is a rooted directed tree where all edges are reversed
 - A *polytree* (also called a *directed tree*) is a directed graph where undirected edges form a tree
- The equivalent of finding an MST in a directed graph is finding a rooted directed tree (arborescence)




Chu-Liu/Edmonds algorithm

a sketch

- The MST for a directed graph has to start from a designated root node
 - If selected node has any incoming edges, remove them
 - It is also a common practice to introduce an artificial root node with equal-weight edges to all nodes
- For all non-root nodes, select the incoming edge with lowest weight, remove others
- If the resulting graph has no cycles, it is an MST
- If there are cycles break them
 - Consider the cycle as a single node
 - Select the incoming edge that yields the lowest cost if used for breaking the cycle
- Repeat until no cycles remain

Chu-Liu/Edmonds algorithm

demonstration



Chu-Liu/Edmonds algorithm

analysis

- The algorithm is generally defined recursively: at each step, create new graph with a contracted cycle call the procedure with the new graph
- At most n recursions: the cycle has to include more nodes at every step
- At each call, m steps for finding minimum incoming edge (also finding a cycle with $O(n)$, but $m \geq n$)
- The 'vanilla' algorithm runs in $O(mn)$
- There are improved versions

Chu-Liu/Edmonds algorithm in Computational Linguistics

dependency parsing



- In a dependency analysis, the structure of the sentence is represented by asymmetric binary relations between syntactic units
- Each relation defines one of the words as the head and the other as dependent
- Often an artificial root node is used for computational convenience
- The links (relations) may have labels (dependency types)
- A dependency analysis (parse) is simply a rooted directed tree

Chu-Liu/Edmonds for dependency parsing

- Begin with fully connected weighted graph, except the root node has no incoming edges
- Weights are estimated from a treebank, typically determined by a machine learning method trained on a treebank
- We often use probabilities rather than costs/distances, so, rather than minimizing, maximize the weight of the tree
- Given the fully connected graph, now the parsing becomes finding the MST
- This method is one of the most common (and successful) approaches to dependency parsing

Summary

- Minimum spanning trees have many applications
- An MST of a undirected graph can be found (efficiently) using Prim-Jarník or Kruskal's algorithms
- For directed graph, the corresponding problem can be solved using Chu-Liu/Edmonds algorithm (technically what we find is a rooted directed tree, or arborescence)
- MST also has quite a few applications in CL/NLP

Next:

- Shortest paths

Acknowledgments, credits, references