

## NFA determinization

Data Structures and Algorithms for Computational Linguistics III  
(ISCL-BA-07)

Çağrı Çölkün  
ccolkun@ifa.uni-tuebingen.de

University of Tübingen  
Seminar für Sprachwissenschaft

Winter Semester 2021/22

version: 10/15/2022 02:00

## Recap


- Finite state automata come in two flavors
  - Deterministic (DFA): linear recognition time
  - Deterministic (NFA): sometimes more intuitive, easy to define, but exponential time (worst case) recognition
- The DFA and NFA are equivalent: for any language recognized by an NFA there is also a DFA recognizing the same language
- Then, the question is: how can we *determinize* an NFA to obtain an equivalent DFA

C. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 1/9

### Introduction NFA determinization

## NFA recognition (again)




- Start at  $q_0$
- Take the next input, mark all possible next states
- If an accepting state is marked at the end of the input, accept

C. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 2/9

### Introduction NFA determinization

## NFA recognition (again)




- Start at  $q_0$
- Take the next input, mark all possible next states
- If an accepting state is marked at the end of the input, accept

C. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 2/9

### Introduction NFA determinization

## NFA recognition (again)




- Start at  $q_0$
- Take the next input, mark all possible next states
- If an accepting state is marked at the end of the input, accept

C. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 2/9

### Introduction NFA determinization

## NFA recognition (again)




- Start at  $q_0$
- Take the next input, mark all possible next states
- If an accepting state is marked at the end of the input, accept

C. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 2/9

### Introduction NFA determinization

## NFA recognition (again)




- Start at  $q_0$
- Take the next input, mark all possible next states
- If an accepting state is marked at the end of the input, accept

C. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 2/9

### Introduction NFA determinization

## NFA recognition (again)



- Start at  $q_0$
- Take the next input, mark all possible next states
- If an accepting state is marked at the end of the input, accept

The process is *deterministic*, and *finite-state*.

C. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 2/9

### Introduction NFA determinization

## Determinization

the subset construction

Intuition: remember the parallel NFA recognition. We can consider an NFA being a deterministic machine which is at a *set of states* at any given time.

- Subset construction (sometimes called power set construction) uses this intuition to convert an NFA to a DFA
- The algorithm can be modified to handle  $\epsilon$ -transitions (or we can eliminate  $\epsilon$ 's as a preprocessing step)


C. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 3/9

### Introduction NFA determinization

## The subset construction

by example



transition table with subsets

	symbol	
	a	b
$\rightarrow \{0\}$	$\{0, 1\}$	$\{0, 1\}$
$\{1\}$	$\{1, 2\}$	$\{1\}$
$\{2\}$	$\{0, 2\}$	$\{0\}$
$\{0, 1\}$	$\{0, 1, 2\}$	$\{0, 1\}$
$\{0, 2\}$	$\{0, 1, 2\}$	$\{0, 1\}$
$\{1, 2\}$	$\{0, 1, 2\}$	$\{0, 1\}$
$\{0, 1, 2\}$	$\{0, 1, 2\}$	$\{0, 1\}$

C. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 4/9


### Introduction NFA determinization

## The subset construction

by example: the resulting DFA

transition table without useless/inaccessible states

	symbol	
	a	b
$\rightarrow \{0\}$	$\{0, 1\}$	$\{0, 1\}$
$\{1\}$	$\{0, 1, 2\}$	$\{0, 1\}$
$\{0, 1, 2\}$	$\{0, 1, 2\}$	$\{0, 1\}$



Do you remember the set of states marked during parallel NFA recognition?



C. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 4/9

### Introduction NFA determinization

## The subset construction

by example: side by side



- What language do they recognize?


C. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 4/9

## The subset construction

wrapping up


- In worst case, resulting DFA has  $2^n$  nodes
- Worst case is rather rare, number of nodes in an NFA and the converted DFA are often similar
- In practice, we do not need to enumerate all  $2^n$  subsets
- We've already seen a typical problematic case:



- We can also skip the unreachable states during subset construction

## Yet another exercise

Determine the following automaton



## Summary

- PSA are efficient tools with many applications
- PSA have two flavors: DFA, NFA (or maybe three:  $\epsilon$ -NFA)
- DFA recognition is linear, recognition with NFA may require exponential time
- Reading suggestion: Hopcroft and Ullman (1979, Ch. 2&3), Jurafsky and Martin (2009, Ch. 2)

Next:

- Minimization

## Acknowledgments, credits, references

- Hopcroft, John E. and Jeffrey D. Ullman (1979). *Introduction to Automata Theory, Languages, and Computation*. Addison-Wesley Series in Computer Science and Information Processing. Addison-Wesley. [isac: 9780201029888](#).
- Jurafsky, Daniel and James H. Martin (2009). *Speech and Language Processing: An Introduction to Natural Language Processing, Computational Linguistics, and Speech Recognition*. second edition. Pearson Prentice Hall. [isac: 978-0-13-504196-3](#).