

FSA and regular languages

Data Structures and Algorithms for Computational Linguistics III
(ISCL-BA-07)

Çağrı Çölkün
ccolkun@ifa.uni-tuebingen.de

University of Tübingen
Seminar für Sprachwissenschaft

Winter Semester 2021/22

version: 07/03/2022 00:02:01

Languages and automata Regular expressions Operations on FSA

How to describe a language?

Formal grammars

A formal grammar is a finite specification of a (formal) language.

- Since we consider languages as sets of strings, for a finite language, we can (conceivably) list all strings
- How to define an infinite language?
- Is the definition {ba, baa, baab, baaba, ...} 'formal enough'?
- Using regular expressions, we can define it as **baa***
- But we will introduce a more general method for defining languages

Ç. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 2 / 22

Languages and automata Regular expressions Operations on FSA

Chomsky hierarchy and automata

Grammar class	Rules	Automata
Unrestricted grammars	$\alpha \rightarrow \beta$	Turing machines
Context-sensitive grammars	$\alpha A \beta \rightarrow \alpha \gamma \beta$	Linear-bounded automata
Context-free grammars	$A \rightarrow \alpha$	Pushdown automata
Regular grammars	$A \rightarrow a$ $A \rightarrow aB$	Finite state automata

Ç. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 3 / 22

Languages and automata Regular expressions Operations on FSA

Regular languages: some properties/operations

- $\mathcal{L}_1 \mathcal{L}_2$ Concatenation of two languages \mathcal{L}_1 and \mathcal{L}_2 : any sentence of \mathcal{L}_1 followed by any sentence of \mathcal{L}_2
- \mathcal{L}^* Kleene star of \mathcal{L} : \mathcal{L} concatenated with itself 0 or more times
- \mathcal{L}^R Reverse of \mathcal{L} : reverse of any string in \mathcal{L}
- $\overline{\mathcal{L}}$ Complement of \mathcal{L} : all strings in Σ^* except the ones in \mathcal{L} ($\Sigma^* - \mathcal{L}$)
- $\mathcal{L}_1 \cup \mathcal{L}_2$ Union of languages \mathcal{L}_1 and \mathcal{L}_2 : strings that are in any of the languages
- $\mathcal{L}_1 \cap \mathcal{L}_2$ Intersection of languages \mathcal{L}_1 and \mathcal{L}_2 : strings that are in both languages

Regular languages are closed under all of these operations.

Ç. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 4 / 22

Languages and automata Regular expressions Operations on FSA

Regular expressions

- Every regular language (RL) can be expressed by a regular expression (RE), and every RE defines a RL
- A RE **a** defines a RL **$\mathcal{L}(a)$**
- Relations between RE and RL
 - $\mathcal{L}(\emptyset) = \emptyset$
 - $\mathcal{L}(a) = \{a\}$
 - $\mathcal{L}(a) = a$
 - $\mathcal{L}(ab) = \mathcal{L}(a)\mathcal{L}(b)$
 - $\mathcal{L}(a^*) = \mathcal{L}(a)^*$
- where, $a, b \in \Sigma$, c is empty string, \emptyset is the language that accepts nothing (e.g., $\Sigma^* - \Sigma^*$)
- Note: no standard complement and intersection in RE

Ç. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 5 / 22

Languages and automata Regular expressions Operations on FSA

Some properties of regular expressions

Useful identities for simplifying regular expressions

- $u(v|w) = (u|v)u$
- $u|v = v|u$
- $u(v|w) = uv|uw$
- $u|\emptyset = u$
- $u\epsilon = \epsilon u = u$
- $\emptyset u = \emptyset$
- $u(vw) = (uv)w$
- $\emptyset^* = \epsilon$
- $\epsilon^* = \epsilon$
- $(u^*)^* = u^*$
- $u|u = u$
- $u|\emptyset = u$
- $(u|v)^* = (u^*|v^*)^*$
- $u^*|\epsilon = u^*$

An exercise	
Simplify $a ab^*$	
$a ab^* = ac ab^*$	
$= a(c b^*)$	
$= ab^*$	

Note: some of these are direct statements of Kleene algebra, others can be derived from them.

Ç. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 12 / 22

Languages and automata

- Recognizing strings from a language defined by a grammar is a fundamental question in computer science
- The efficiency of computation, and required properties of computing device depends on the grammar (and the language)
- A well-known hierarchy of grammars both in computer science and linguistics is the *Chomsky hierarchy*
- Each grammar in the Chomsky hierarchy corresponds to an abstract computing device (an automaton)
- The class of *regular grammars* are the class that corresponds to *finite state automata*

Ç. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 1 / 22

Languages and automata Regular expressions Operations on FSA

Phrase structure grammars

- A phrase structure grammar is a generative device
- If a given string can be generated by the grammar, the string is in the language
- The grammar generates all and the only strings that are valid in the language
- A phrase structure grammar has the following components
 - Σ : A set of terminal symbols
 - N : A set of non-terminal symbols
 - $S \in N$: A special non-terminal, called the start symbol
 - R : A set of rewrite rules or production rules of the form:

$$\alpha \rightarrow \beta$$

which means that the sequence α can be rewritten as β (both α and β are sequences of terminal and non-terminal symbols)

Ç. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 3 / 22

Languages and automata Regular expressions Operations on FSA

Regular grammars: definition

A regular grammar is a tuple $G = (\Sigma, N, S, R)$ where

Σ is an alphabet of terminal symbols

N is a set of non-terminal symbols

S is a special 'start' symbol $\in N$

R is a set of rewrite rules following one of the following patterns ($A, B \in N$, $a \in \Sigma$, ϵ is the empty string)

Left regular	Right regular
1. $A \rightarrow a$	1. $A \rightarrow a$
2. $A \rightarrow Ba$	2. $A \rightarrow aB$
3. $A \rightarrow \epsilon$	3. $A \rightarrow \epsilon$

Ç. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 5 / 22

Languages and automata Regular expressions Operations on FSA

Three ways to define a regular language

- A language is regular if there is regular grammar that generates/recognizes it
- A language is regular if there is an FSA that generates/recognizes it
- A language is regular if we can define a regular expressions for the language

Ç. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 7 / 22

Languages and automata Regular expressions Operations on FSA

Regular expressions and some extensions


- Kleene star (a^*), concatenation (ab) and union ($a|b$) are the basic operations
- Parentheses can be used to group the sub-expressions. Otherwise, the priority of the operators are as listed above: $a|bc^* = a|(b(c^*))$
- In practice some short-hand notations are common
 - $\cdot = (a_1|...|a_n)$
 - for $\Sigma = \{a_1, ..., a_n\}$
 - $a^* = a^+ = a^*$
 - $[a^+c] = (a|b|c)$
 - $\cdot = [^+a^+c]$
 - $\cdot = [a|b|c]$
 - $\cdot = [a|b|c]$
 - $\cdot = [a|b|c]$
- And some non-regular extensions, like $(a^*b|1)$ (sometimes the term *regex* is used for expressions with non-regular extensions)

Ç. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 9 / 22

Languages and automata Regular expressions Operations on FSA

Converting regular expressions to FSA



- For more complex expressions, one can replace the paths for individual symbols with corresponding automata
- Using ϵ transitions may ease the task
- The reverse conversion (from automata to regular expressions) is also easy:
 - identify the patterns on the left, collapse paths to single transitions with regular expressions


Ç. Çölkün, ISL / University of Tübingen

Winter Semester 2021/22 11 / 22


Exercise

convert $b(ab)^*a$ to an NFA

Exercise

convert $b(ab)^*a$ to an NFA

Converting FSA to regular expressions



- The general idea: remove (intermediate) states, replacing edge labels with regular expressions
- An exercise: simplify the resulting regular expressions

Two example FSA

what languages do they accept?

$$L_1 = \mathcal{L}(M_1)$$

Odd number of a's over $\{a, b\}$.

$$L_2 = \mathcal{L}(M_2)$$


Odd number of b's over $\{a, b\}$.

We will use these languages and automata for demonstration.

Concatenation


 L_1

 L_2

 $L_1 L_2$


Kleene star

 L_1

 L_1^*


- What if there were more than one accepting states?

Reversal

 L_1


 L_1^R


Complement


 L_1

 $\overline{L_1}$


Union

 $L_1 \cup L_2$


Intersection



...or

$$L_1 \cap L_2 = \overline{\overline{L_1} \cup \overline{L_2}}$$

Closure properties of regular languages

- Since results of all the operations we studied are FSA: Regular languages are closed under
 - Concatenation
 - Kleene star
 - Reversal
 - Complement
 - Union
 - Intersection

Wrapping up

- FSA and regular expressions express regular languages
- Regular languages and FSA are closed under
 - Concatenation
 - Kleene star
 - Complement
 - Reversal
 - Union
 - Intersection
- To prove a language is regular, it is sufficient to find a regular expression or FSA for it
- To prove a language is not regular, we can use pumping lemma (see Appendix)

Next:


- Parsing

Acknowledgments, credits, references

Is a language regular? — or not

- To show that a language is regular, it is sufficient to find an FSA that recognizes it.
- Showing that a language is *not* regular is more involved
- We will study a method based on *pumping lemma*


Pumping lemma intuition



- What is the length of longest string generated by this FSA?
- Any FSA generating an infinite language has to have a loop (application of recursive rule(s) in the grammar)
- Part of every string longer than some number will include repetition of the same substring ('cklm' above)

Pumping lemma definition

- For every regular language L , there exist an integer p such that a string $x \in L$ can be factored as $x = uvw$,
- $uv^i w \in L, \forall i \geq 0$
 - $v \neq \epsilon$
 - $|uv| \leq p$



How to use pumping lemma

- We use pumping lemma to prove that a language is not regular
- Proof is by contradiction:
 - Assume the language is regular
 - Find a string x in the language, for all splits of $x = uvw$, at least one of the pumping lemma conditions does not hold
 - $uv^i w \in L (\forall i \geq 0)$
 - $v \neq \epsilon$
 - $|uv| \leq p$

Pumping lemma example

prove $L := a^n b^n$ is not regular

- Assume L is regular: there must be a p such that, if uvw is in the language
 1. $uv^i w \in L (\forall i \geq 0)$
 2. $v \neq \epsilon$
 3. $|uv| \leq p$
- Pick the string $a^p b^p$
- For the sake of example, assume $p = 5, x = aaaaaabbbb$
- Three different ways to split



Pumping lemma

Slide

C. Gökdeniz, SB | University of Tübingen

Winter Semester 2021/22 A.7

Pumping lemma

Slide

C. Gökdeniz, SB | University of Tübingen

Winter Semester 2021/22 A.8

Pumping lemma

Slide

C. Gökdeniz, SB | University of Tübingen

Winter Semester 2021/22 A.9

Pumping lemma

Slide

C. Gökdeniz, SB | University of Tübingen

Winter Semester 2021/22 A.10