

## NFA determinization

Data Structures and Algorithms for Computational Linguistics III  
(ISCL-BA-07)

Çağrı Çöltekin  
ccoltekin@ifa.uni-tuebingen.de

University of Tübingen  
Seminar für Sprachwissenschaft

Winter Semester 2022/23

version: 09/07/2022 00:01


## Recap

- Finite state automata come in two flavors
  - Deterministic (DFA): linear recognition time
  - Deterministic (NFA): sometimes more intuitive, easy to define, but exponential time (worst case) recognition
- The DFA and NFA are equivalent: for any language recognized by an NFA there is also a DFA recognizing the same language
- Then, the question is: how can we *determinize* an NFA to obtain an equivalent DFA

C. Çöltekin, INF | University of Tübingen

Winter Semester 2022/23 1/3

## NFA recognition (again)




- Start at  $q_0$
- Take the next input, mark all possible next states
- If an accepting state is marked at the end of the input, accept

C. Çöltekin, INF | University of Tübingen

Winter Semester 2022/23 2/3

## NFA recognition (again)




- Start at  $q_0$
- Take the next input, mark all possible next states
- If an accepting state is marked at the end of the input, accept

C. Çöltekin, INF | University of Tübingen

Winter Semester 2022/23 2/3

## NFA recognition (again)




- Start at  $q_0$
- Take the next input, mark all possible next states
- If an accepting state is marked at the end of the input, accept

C. Çöltekin, INF | University of Tübingen

Winter Semester 2022/23 2/3

## NFA recognition (again)




- Start at  $q_0$
- Take the next input, mark all possible next states
- If an accepting state is marked at the end of the input, accept

C. Çöltekin, INF | University of Tübingen

Winter Semester 2022/23 2/3

## NFA recognition (again)




- Start at  $q_0$
- Take the next input, mark all possible next states
- If an accepting state is marked at the end of the input, accept

C. Çöltekin, INF | University of Tübingen

Winter Semester 2022/23 2/3

## NFA recognition (again)



- Start at  $q_0$
- Take the next input, mark all possible next states
- If an accepting state is marked at the end of the input, accept

The process is *deterministic*, and *finite-state*.

C. Çöltekin, INF | University of Tübingen

Winter Semester 2022/23 2/3

## Determinization

the subset construction

Intuition: remember the parallel NFA recognition. We can consider an NFA being a deterministic machine which is at a *set of states* at any given time.


- Subset construction (sometimes called power set construction) uses this intuition to convert an NFA to a DFA
- The algorithm can be modified to handle  $\epsilon$ -transitions (or we can eliminate  $\epsilon$ 's as a preprocessing step)

C. Çöltekin, INF | University of Tübingen

Winter Semester 2022/23 2/3

## The subset construction

by example



transition table with subsets

	symbol		
	a	b	
$\rightarrow \{0\}$	$\{0, 1\}$	$\{0, 1\}$	
$\{1\}$	$\{1, 2\}$	$\{1\}$	
$* \{2\}$	$\{0, 2\}$	$\{0\}$	
$\{0, 1\}$	$\{0, 1, 2\}$	$\{0, 1\}$	
$* \{0, 2\}$	$\{0, 1, 2\}$	$\{0, 1\}$	
$* \{1, 2\}$	$\{0, 1, 2\}$	$\{0, 1\}$	
$* \{0, 1, 2\}$	$\{0, 1, 2\}$	$\{0, 1\}$	

C. Çöltekin, INF | University of Tübingen


Winter Semester 2022/23 2/3

## The subset construction

by example: the resulting DFA

transition table without useless/inaccessible states

	symbol	
	a	b
$\rightarrow \{0\}$	$\{0, 1\}$	$\{0, 1\}$
$\{0, 1\}$	$\{0, 1, 2\}$	$\{0, 1\}$
$* \{0, 1, 2\}$	$\{0, 1, 2\}$	$\{0, 1\}$





Do you remember the set of states marked during parallel NFA recognition?

C. Çöltekin, INF | University of Tübingen

Winter Semester 2022/23 2/3

## The subset construction

by example: side by side



- What language do they recognize?


C. Çöltekin, INF | University of Tübingen

Winter Semester 2022/23 2/3

The subset construction

wrapping up


- In worst case, resulting DFA has  $2^n$  nodes
- Worst case is rather rare, number of nodes in an NFA and the converted DFA are often similar
- In practice, we do not need to enumerate all  $2^n$  subsets
- We've already seen a typical problematic case:



- We can also skip the unreachable states during subset construction

Yet another exercise

Determine the following automaton



Summary

- FSA are efficient tools with many applications
- FSA have two flavors: DFA, NFA (or maybe three:  $\epsilon$ -NFA)
- DFA recognition is linear, recognition with NFA may require exponential time
- Reading suggestion: [hopcroft1979](#), [jurafsky2009](#)

Next:

- Minimization

Acknowledgments, credits, references