

## Finite state automata

Data Structures and Algorithms for Computational Linguistics III  
(ISCL-BA-07)

Çağrı Çöltekin  
ccoltekin@ifa.uni-tuebingen.de

University of Tübingen  
Seminar für Sprachwissenschaft

Winter Semester 2023/24

© Ç. Çöltekin, 2023. All rights reserved.

## Why study finite-state automata?

- Finite-state automata are efficient models of computation
- There are many applications
  - Electronic circuit design
  - Workflow management
  - Games
  - Pattern matching
  - ...
- But more importantly > >
  - Tokenization, stemming
  - Morphological analysis
  - Spell checking
  - Shallow parsing/chunking
  - ...

© Ç. Çöltekin, 2023. All rights reserved.

Winter Semester 2023/24 1 / 24

## Finite-state automata (FSA)


- A finite-state machine is in one of a finite-number of states in a given time
  - The machine changes its state based on its input
  - Every regular language is generated/recognized by an FSA
  - Every FSA generates/recognizes a regular language
  - Two flavors:
    - Deterministic finite automata (DFA)
    - Non-deterministic finite automata (NFA)
- Note: the NFA is a superset of DFA.

© Ç. Çöltekin, 2023. All rights reserved.

Winter Semester 2023/24 2 / 24

## FSA as a graph

- An FSA is a directed graph
- States are represented as nodes
- Transitions are labeled edges
- One of the states is the *initial state*
- Some states are accepting states



© Ç. Çöltekin, 2023. All rights reserved.

Winter Semester 2023/24 3 / 24

## DFA: formal definition

Formally, a finite state automaton,  $M$ , is a tuple  $(\Sigma, Q, q_0, F, \Delta)$  with

- $\Sigma$  is the alphabet, a finite set of symbols
- $Q$  a finite set of states
- $q_0$  is the start state,  $q_0 \in Q$
- $F$  is the set of final states,  $F \subseteq Q$
- $\Delta$  is a function that takes a state and a symbol in the alphabet, and returns another state ( $\Delta: Q \times \Sigma \rightarrow Q$ )


At any state and for any input,  
a DFA has a single well-defined action to take.

© Ç. Çöltekin, 2023. All rights reserved.

Winter Semester 2023/24 4 / 24

## DFA: formal definition an example

$\Sigma = \{a, b\}$   
 $Q = \{q_0, q_1, q_2\}$   
 $q_0 = q_0$   
 $F = \{q_2\}$   
 $\Delta = \{(q_0, a) \rightarrow q_2, (q_0, b) \rightarrow q_1, (q_1, a) \rightarrow q_2, (q_1, b) \rightarrow q_1\}$




© Ç. Çöltekin, 2023. All rights reserved.

Winter Semester 2023/24 5 / 24

## Another note on DFA

error or sink state

- Is this FSA deterministic?
- To make all transitions well-defined, we can add a sink (or error) state
- For brevity, we skip the explicit error state
  - In that case, when we reach a dead end, recognition fails




© Ç. Çöltekin, 2023. All rights reserved.

Winter Semester 2023/24 6 / 24

## DFA: the transition table

	symbol	
	a	b
	→0	2 1
state	1	2 1
	*2	∅ ∅

→ marks the start state  
\* marks the accepting state(s)




© Ç. Çöltekin, 2023. All rights reserved.

Winter Semester 2023/24 7 / 24

## DFA: the transition table

	symbol	
	a	b
	→0	2 1
state	1	2 1
	*2	3 3
	3	3 3

→ marks the start state  
\* marks the accepting state(s)




© Ç. Çöltekin, 2023. All rights reserved.

Winter Semester 2023/24 8 / 24

## DFA recognition

- Start at  $q_0$
- Process an input symbol, move accordingly
- Accept if in a final state at the end of the input




© Ç. Çöltekin, 2023. All rights reserved.

Winter Semester 2023/24 9 / 24

## DFA recognition

- Start at  $q_0$
- Process an input symbol, move accordingly
- Accept if in a final state at the end of the input




© Ç. Çöltekin, 2023. All rights reserved.

Winter Semester 2023/24 10 / 24

## DFA recognition

- Start at  $q_0$
- Process an input symbol, move accordingly
- Accept if in a final state at the end of the input




© Ç. Çöltekin, 2023. All rights reserved.

Winter Semester 2023/24 11 / 24


## DFA recognition

1. Start at  $q_0$
2. Process an input symbol, move accordingly
3. Accept if in a final state at the end of the input



## DFA recognition


1. Start at  $q_0$
2. Process an input symbol, move accordingly
3. Accept if in a final state at the end of the input



## DFA recognition


1. Start at  $q_0$
2. Process an input symbol, move accordingly
3. Accept if in a final state at the end of the input

- What is the complexity of the algorithm?
- How about inputs:
  - bbbb
  - aa



## A few questions

- What is the language recognized by this DFA?
- Can you draw a simpler DFA for the same language?
- Draw a DFA recognizing strings with even number of 'a's over  $\Sigma = \{a, b\}$




## Non-deterministic finite automata

Formal definition

A non-deterministic finite state automaton,  $M$ , is a tuple  $(\Sigma, Q, q_0, F, \Delta)$  with

- $\Sigma$  is the alphabet, a finite set of symbols
- $Q$  a finite set of states
- $q_0$  is the start state,  $q_0 \in Q$
- $F$  is the set of final states,  $F \subseteq Q$
- $\Delta$  is a function from  $(Q, \Sigma)$  to  $P(Q)$ , power set of  $Q$  ( $\Delta: Q \times \Sigma \rightarrow P(Q)$ )

## An example NFA



transition table

	symbol	
	a	b
state	→0	0,1
1	1,2	1
*2	0,2	0


- We have nondeterminism, e.g., if the first input is a, we need to choose between states 0 or 1
- Transition table cells have sets of states

## Dealing with non-determinism

- Follow one of the links, store alternatives, and backtrack on failure
- Follow all options in parallel

## NFA recognition


as search (with backtracking)



1. Start at  $q_0$
2. Take the next input, place all possible actions to an agenda
3. Get the next action from the agenda, act
4. At the end of input
  - Accept if in an accepting state
  - Reject not in accepting state & agenda empty
  - Backtrack otherwise

## NFA recognition


as search (with backtracking)



1. Start at  $q_0$
2. Take the next input, place all possible actions to an agenda
3. Get the next action from the agenda, act
4. At the end of input
  - Accept if in an accepting state
  - Reject not in accepting state & agenda empty
  - Backtrack otherwise

## NFA recognition


as search (with backtracking)



1. Start at  $q_0$
2. Take the next input, place all possible actions to an agenda
3. Get the next action from the agenda, act
4. At the end of input
  - Accept if in an accepting state
  - Reject not in accepting state & agenda empty
  - Backtrack otherwise

## NFA recognition


as search (with backtracking)



1. Start at  $q_0$
2. Take the next input, place all possible actions to an agenda
3. Get the next action from the agenda, act
4. At the end of input
  - Accept if in an accepting state
  - Reject not in accepting state & agenda empty
  - Backtrack otherwise

## NFA recognition


as search (with backtracking)



1. Start at  $q_0$
2. Take the next input, place all possible actions to an agenda
3. Get the next action from the agenda, act
4. At the end of input
  - Accept if in an accepting state
  - Reject not in accepting state & agenda empty
  - Backtrack otherwise

## NFA recognition


as search (with backtracking)



1. Start at  $q_0$
2. Take the next input, place all possible actions to an agenda
3. Get the next action from the agenda, act
4. At the end of input  
Accept if in an accepting state  
Reject not in accepting state & agenda empty  
Backtrack otherwise

## NFA recognition


as search (with backtracking)



1. Start at  $q_0$
2. Take the next input, place all possible actions to an agenda
3. Get the next action from the agenda, act
4. At the end of input  
Accept if in an accepting state  
Reject not in accepting state & agenda empty  
Backtrack otherwise

## NFA recognition


as search (with backtracking)



1. Start at  $q_0$
2. Take the next input, place all possible actions to an agenda
3. Get the next action from the agenda, act
4. At the end of input  
Accept if in an accepting state  
Reject not in accepting state & agenda empty  
Backtrack otherwise

## NFA recognition


as search (with backtracking)



1. Start at  $q_0$
2. Take the next input, place all possible actions to an agenda
3. Get the next action from the agenda, act
4. At the end of input  
Accept if in an accepting state  
Reject not in accepting state & agenda empty  
Backtrack otherwise

## NFA recognition


as search (with backtracking)



1. Start at  $q_0$
2. Take the next input, place all possible actions to an agenda
3. Get the next action from the agenda, act
4. At the end of input  
Accept if in an accepting state  
Reject not in accepting state & agenda empty  
Backtrack otherwise

## NFA recognition


as search (with backtracking)



1. Start at  $q_0$
2. Take the next input, place all possible actions to an agenda
3. Get the next action from the agenda, act
4. At the end of input  
Accept if in an accepting state  
Reject not in accepting state & agenda empty  
Backtrack otherwise

## NFA recognition


as search (with backtracking)



1. Start at  $q_0$
2. Take the next input, place all possible actions to an agenda
3. Get the next action from the agenda, act
4. At the end of input  
Accept if in an accepting state  
Reject not in accepting state & agenda empty  
Backtrack otherwise

## NFA recognition


as search (with backtracking)



1. Start at  $q_0$
2. Take the next input, place all possible actions to an agenda
3. Get the next action from the agenda, act
4. At the end of input  
Accept if in an accepting state  
Reject not in accepting state & agenda empty  
Backtrack otherwise

## NFA recognition

as search (with backtracking)



1. Start at  $q_0$
2. Take the next input, place all possible actions to an agenda
3. Get the next action from the agenda, act
4. At the end of input  
Accept if in an accepting state  
Reject not in accepting state & agenda empty  
Backtrack otherwise


## NFA recognition as search

summary

- Worst time complexity is exponential
  - Complexity is worse if we want to enumerate all derivations
- We used a stack as *agenda*, performing a depth-first search
- A queue would result in breadth-first search
- If we have a reasonable heuristic  $A^*$  search may be an option
- Machine learning methods may also guide finding a fast or the best solution

## NFA recognition


parallel version



1. Start at  $q_0$
2. Take the next input, mark all possible next states
3. If an accepting state is marked at the end of the input, accept

## NFA recognition


parallel version



1. Start at  $q_0$
2. Take the next input, mark all possible next states
3. If an accepting state is marked at the end of the input, accept

## NFA recognition


parallel version



1. Start at  $q_0$
2. Take the next input, mark all possible next states
3. If an accepting state is marked at the end of the input, accept

## NFA recognition


parallel version



1. Start at  $q_0$
2. Take the next input, mark all possible next states
3. If an accepting state is marked at the end of the input, accept

## NFA recognition


parallel version



1. Start at  $q_0$
2. Take the next input, mark all possible next states
3. If an accepting state is marked at the end of the input, accept

## NFA recognition

parallel version




1. Start at  $q_0$
2. Take the next input, mark all possible next states
3. If an accepting state is marked at the end of the input, accept



Note: the process is *deterministic*, and *finite-state*.

## An exercise

Construct an NFA and a DFA for the language over  $\Sigma = \{a, b\}$  where all sentences end with  $ab$ .

One more complication:  $\epsilon$  transitions


- An extension of NFA,  $\epsilon$ -NFA, allows moving without consuming an input symbol, indicated by an  $\epsilon$ -transition (sometimes called a  $\lambda$ -transition)
- Any  $\epsilon$ -NFA can be converted to an NFA

 $\epsilon$ -transitions need attention


- How does the (depth-first) NFA recognition algorithm we described earlier work on this automaton?
- Can we do without  $\epsilon$  transitions?

 $\epsilon$  removal

- Intuition: if  $q_0 \xrightarrow{a} q_1 \xrightarrow{\epsilon} q_2$ , then  $q_0 \xrightarrow{a} q_2$
- We start with finding the  $\epsilon$ -closure of all states
  - $\epsilon$ -closure( $q_0$ ) =  $\{q_0\}$
  - $\epsilon$ -closure( $q_1$ ) =  $\{q_1, q_2\}$
  - $\epsilon$ -closure( $q_2$ ) =  $\{q_2\}$
- For each incoming arc  $(q_i, q_1)$  to a node  $q_1$  with label  $\ell$ 
  - add a new arc  $(q_i, q_1)$  with label  $\ell$ , for all  $q_i \in \epsilon$ -closure( $q_1$ )
  - remove all  $\epsilon$  transitions  $(q_i, q_1)$  for all  $q_i \in \epsilon$ -closure( $q_1$ )
- $\epsilon$ -transitions from the initial state, and to/from the accepting states need further attention (next slide)
- Remove useless states, if any


 $\epsilon$  removal

a(nother) example

 $\epsilon$  removal

another (less trivial) example

- Compute the  $\epsilon$ -closure:
  - $\epsilon$ -closure( $q_0$ ) =  $\{q_0, q_1\}$
  - $\epsilon$ -closure( $q_1$ ) =  $\{q_1\}$
  - $\epsilon$ -closure( $q_2$ ) =  $\{q_2, q_3\}$
  - $\epsilon$ -closure( $q_3$ ) =  $\{q_3, q_1\}$
- For each incoming arc  $\ell(q_i, q_1)$  to each node  $q_1$ 
  - add  $\ell(q_i, q_1)$  for all  $q_i \in \epsilon$ -closure( $q_1$ )
  - if  $q_1$  is initial, mark  $q_i$  initial
  - if  $q_1$  is accepting, mark  $q_i$  accepting
  - remove all  $\epsilon(q_i, q_1)$  for all  $q_i \in \epsilon$ -closure( $q_1$ )



## NFA-DFA equivalence


- The language recognized by every NFA is recognized by some DFA
- The set of DFA is a subset of the set of NFA (a DFA is also an NFA)
- The same is true for  $\epsilon$ -NFA
- All recognize/generate regular languages
- NFA can automatically be converted to the equivalent DFA

## Why do we use an NFA then?

- NFA (or  $\epsilon$ -NFA) are often easier to construct
  - Intuitive for humans (cf. earlier exercise)
  - Some representations are easy to convert to NFA rather than DFA, e.g., regular expressions
- NFA may require less memory (fewer states)

A quick exercise – and a not-so-quick one

- Construct (draw) an NFA for the language over  $\Sigma = \{a, b\}$ , such that 4th symbol from the end is an  $a$



- Construct a DFA for the same language

## Summary

- FSA are efficient tools with many applications
- FSA have two flavors: DFA, NFA (or maybe three:  $\epsilon$ -NFA)
- DFA recognition is linear, recognition with NFA may require exponential time
- Reading suggestion: Hopcroft and Ullman (1979, Ch. 2&3) (and its successive editions), Jurafsky and Martin (2009, Ch. 2)

Next:

- FSA determinization, minimization
- Reading suggestion: Hopcroft and Ullman (1979, Ch. 2&3) (and its successive editions), Jurafsky and Martin (2009, Ch. 2)

## Acknowledgments, credits, references

- 1 Hopcroft, John E. and Jeffrey D. Ullman (1979). *Introduction to Automata Theory, Languages, and Computation*. Addison-Wesley Series in Computer Science and Information Processing. Addison-Wesley. [isarc: 9780201029888](#).
- 2 Jurafsky, Daniel and James H. Martin (2009). *Speech and Language Processing: An Introduction to Natural Language Processing, Computational Linguistics, and Speech Recognition*. second edition. Pearson Prentice Hall. [isarc: 978-0-13-504196-3](#).

