

NOPT042 Constraint programming: Tutorial 1 – Introduction to Picat

See the [tutorial website](#) for program of classes, links to homework assignments, credit requirements, and a list of useful resources.

Picat is a logic-based multiparadigm general-purpose programming language.

- **Pattern-matching**: predicates defined with pattern-matching rules
- **Intuitive**: incorporates declarative language syntax, e.g. for scripting, mimics for-loops, ...
- **Constraints**: designed with constraint programming in mind, provides 4 solvers, `cp`, `sat`, `smt`, `mip`
- **Actors**: action rules for event-driven behaviour; constraint propagators are implemented as actors
- **Tabling**: store subresults, dynamic programming, module `planner`

Installation

You can install [Picat](#) like this (check if there's a newer version of Picat):

```
cd ~
wget http://picat-lang.org/download/picat328_linux64.tar.gz
tar -xf picat328_linux64.tar.gz
```

Then add the executable to `$PATH` (assuming we use bash):

```
echo 'export PATH="$HOME/Picat:$PATH"' >> ~/.bashrc
source ~/.bashrc
```

Then the command `picat` runs the Picat interpreter.

If you want to execute the notebooks, install [Jupyter Notebook](#) with [ipicat extension](#) (if you want to install them locally, add `--user`):

```
pip install jupyter
pip install ipicat
```

Then run `jupyter notebook`. Once the extension is loaded you can use `%%picat` cell magic or execute picat files: `%picat -e hello-world.pi`.

```
In [1]: %load_ext ipicat
```

```
Picat version 3.2#8
```

Introductory examples

Hello world

```
In [2]: %%picat
main =>
    println("Hello, World!").
```

Hello, World!

```
In [3]: %picat -e hello-world.pi
# alternatively:
!picat hello-world.pi
```

Hello, World!

Hello, World!

Command-line arguments

```
In [4]: # This doesn't work at the moment
# %picat -e hello-world.pi Alice
!picat hello-world.pi Alice
!picat hello-world.pi Alice Bob Carol Dave
```

Hello, Alice! You are my favourite student.

Hello, Alice and Bob and Carol and Dave! You are my favourite students.

```
In [5]: %%bash
cat hello-world.pi
```

```
import util.
```

```
main =>
    println("Hello, World!").
```

```
main([Name]) =>
    printf("Hello, %s! You are my favourite student.\n", Name).
```

```
main(ARGS) =>
    Names = ARGS.join(" and "),
    printf("Hello, %s! You are my favourite students.\n", Names).
```

Example: Fibonacci sequence

```
In [6]: %%picat -n fib
fib(N, F) =>
    if (N = 0) then
        F = 0
    elseif (N = 1) then
        F = 1
    else
        fib(N - 1, F1),
        fib(N - 2, F2),
        F = F1 + F2
    end.
```

```
In [7]: %%picat -n fib
fib(0, F) => F = 0.
fib(1, F) => F = 1.
fib(N, F), N > 1 => fib(N - 1, F1), fib(N - 2, F2), F = F1 + F2.
```

```
In [8]: %%picat -n fib_tabled
table
fib_tabled(0, F) => F = 0.
fib_tabled(1, F) => F = 1.
fib_tabled(N, F), N > 1 => fib_tabled(N - 1, F1), fib_tabled(N - 2, F2), F = F1 + F2.
```

Compare the performance:

```
In [9]: %%picat
main =>
    time(fib(42, F)),
    println(F),
    time(fib_tabled(42, F)),
    println(F).
```

CPU time 21.794 seconds.

267914296

CPU time 0.0 seconds.

267914296

Example: Quicksort

In Jupyter, use `%%picat -e predicate_name` to define a predicate from a cell.

```
In [10]: %%picat -n qsort
qsort([]) = [].
qsort([H | T]) = qsort([E : E in T, E <= H]) ++ [H] ++ qsort([E : E in T, E > H]).
```

Alternative version:

```
In [11]: %%picat -n qsort
qsort(L) = Lsorted =>
    if L = [] then
        Lsorted = []
    else
        L = [H | T],
        Lsorted = qsort([E : E in T, E <= H]) ++ [H] ++ qsort([E : E in T, E > H]).
```

```
In [12]: %%picat
main => L = qsort([5, 2, 6, 4, 1, 3]), println(L).

[1,2,3,4,5,6]
```

```
In [13]: !picat qsort/qsort.pi

List [5,2,6,4,1,3] after sorting is [1,2,3,4,5,6].
```

```
In [14]: !picat qsort/qsort.pi [5,2,6,4,1,3]

[1,2,3,4,5,6]
```

Reading and writing files

```
In [15]: !cat qsort/assorted.lists

[2, 1]
[5, 2, 6, 4, 1, 3]
[44, 11, 29, 53, 59, 70, 63, 68, 16, 30, 95, 9, 55, 71, 84, 81, 64, 46, 26, 89, 15, 40,
22, 97, 39]
```

```
In [16]: !picat qsort/qsort.pi qsort/assorted.lists qsort/sorted.lists
```

```
!cat qsort/sorted.lists
```

```
[1,2]  
[1,2,3,4,5,6]  
[9,11,15,16,22,26,29,30,39,40,44,46,53,55,59,63,64,68,70,71,81,84,89,95,97]
```

```
In [17]: !cat qsort/qsort.pi
```

```
qsort([])    = [].  
qsort([H|T]) = qsort([E : E in T, E <= H]) ++ [H] ++ qsort([E : E in T, E > H]).  
  
main =>  
    L = [5, 2, 6, 4, 1, 3],  
    printf("List %w after sorting is %w.\n", L, qsort(L)).  
  
main([Lstring]) =>  
    L = parse_term(Lstring),  
    println(qsort(L)).  
  
main([InputPath, OutputPath]) =>  
    Lines = read_file_lines(InputPath),  
    OutputFile = open(OutputPath, write),  
    foreach(I in 1..Lines.length)  
        L = parse_term(Lines[I]),  
        writeln(OutputFile, qsort(L))  
    end.
```

TPK algorithm

The TPK algorithm is an artificial problem designed by Trabb Pardo & Knuth to showcase the syntax of a given programming language (see [Wikipedia](#)):

```
ask for N numbers to be read into a sequence S  
reverse sequence S  
for each item in sequence S  
    call a function to do an operation  
    if result overflows  
        alert user  
    else  
        print result
```

The following Picat implementation is from [here](#).

```
In [18]: !cat tpk/tpk.pi
```

```
% TPK Algorithm in Picat  
% from https://www.linuxjournal.com/content/introduction-tabled-logic-programming-picat  
  
f(T) = sqrt(abs(T)) + 5 * T**3.  
main =>  
    N = 4,  
    As = to_array([read_real() : I in 1..N]),  
    foreach (I in N..-1..1)  
        Y = f(As[I]),  
        if Y > 400 then  
            printf("%w TOO LARGE\n", I)  
        else  
            printf("%w %w\n", I, Y)  
        end  
    end.
```

```
In [19]: !cat tpk/some_reals.txt
```

```
!printf "\n"  
!picat tpk/tpk.pi < tpk/some_reals.txt
```

```
1.0e-2  
-2.345  
42.0001  
-0.002  
  
4 0.044721319549996  
3 T00 LARGE  
2 -62.944728841888654  
1 0.100005
```

An overview of Picat

Examples in this section are mostly adapted from or inspired by the [Picat Book](#), [Picat Guide](#), [AAA2017 tutorial](#), and [examples](#). More resources are available [here](#).

TODO, see the [slides](#) (pages 4-18).

A constraint programming example

For the rest of today, we will practice writing programs in "pure" Picat. We will introduce constraint modelling in Picat next tutorial. But here is one example, the N-queens problem: place N queens on an NxN chess board so that no two queens attack each other.

```
In [20]: !picat queens/queens.pi 4  
*** error(instantiation_error,(-)/2)
```

```
In [21]: !cat queens/queens.pi  
  
% adapted from picat-lang.org  
import cp.  
  
queens(N, Q) =>  
    Q = new_list(N),  
    Q :: 1..N,  
    all_different(Q),  
    all_different([Q[I] - I : I in 1..N]),  
    all_different([Q[I] + I : I in 1..N]),  
    solve([ff], Q).  
  
main([N]) =>  
    queens(N.to_int, Q),  
    print(Q).
```

Exercises

Exercise: count occurrences

Write a program that counts the number of occurrences of an integer in a list of integers, e.g.:

```
picat count-occurrences.pi [1,2,4,2,3,2] 2  
picat count-occurrences.pi [1,2,2,1] 3
```

outputs `3` and `0`, respectively.

Exercise: transpose

Write a program that transposes a given matrix (a 2D array), e.g.:

```
picat transpose.pi "{{1,2,3},{4,5,6}}"
```

outputs `{{1,4},{2,5},{3,6}}`. (Note that we need to put the input in quotation marks.) Inside your code define a function `transpose(Matrix) = Transposed_Matrix`.

Exercise: binary trees

Write a function that receives a binary tree encoded using the structure

`$node(Value,LeftChild,RightChild)` and outputs the depth of the tree. For example:

```
picat depth.pi "node(42,nil,nil)"
picat depth.pi "node(1,node(2,nil,nil),node(3,nil,nil))"
picat depth.pi
"node(1,node(2,node(3,node(4,nil,nil),node(5,nil,nil)),nil),node(6,node(7,nil,r
```

should output:

```
0
1
3
```

Homework: leaves

Write a program that receives a binary tree encoded using the structure

`$node(Value,LeftChild,RightChild)` and outputs the list of its leaves (childless nodes) in prefix order (e.g., as in DFS). See the assignment on GitHub Classroom. For example:

```
picat leaves.pi "node(42,nil,nil)"
picat leaves.pi "node(1,node(2,nil,nil),node(3,nil,nil))"
picat leaves.pi
"node(1,node(2,node(3,node(4,nil,nil),node(5,nil,nil)),nil),node(6,node(7,nil,r
```

should output:

```
[42]
[2,3]
[4,5,7,8]
```

See the assignment on GitHub Classroom.