

CS29206: Systems Programming Lab

Autumn 2025

Creating and using Libraries

Acknowledgement

Several slides, and contents of some others, have been taken from the slides made by Prof. Abhijit Das for an earlier offering of the course

Resources

- “An Introduction to gcc” by Brian Gough (Chapters 2-3)
- Manpage of ar command
- “Your Unix/Linux: The Ultimate Guide”, by Sumitabha Das (Chapter 16)

Introduction

- A **library** is a pre-compiled archive of object files
 - These can be linked to user codes during compilation or during runtime
- Example: The **math library** consists of the following.
 - Definition of data types: **float**, **double**, . . .
 - Prototypes of Functions: **pow**, **sqrt**, **atan**, **cosh**, **abs**, . . .
 - Definition of Constants: **M_PI**, **M_E**, **M_LOG2E**, **M_SQRT2**, . . .
 - A precompiled archive of implementations of the math functions defined
- The first three are in the header file **math.h**. You include it in your program **#include <math.h>**
- The fourth one, precompiled math library, is needed for linking to your final executable.
 - You specify the option **-lm** for this linking when you compile your C program

Types of Libraries

- Static libraries

- Prefix: *lib*

- Extension: *.a*

- Example: the static math library has the name *libm.a*

- Functions from static libraries are actually inserted in the final executable during linking

- Pro: the executable can run without needing anything else when it is run

- Con: Since all the library code is added to your code, size of executable can be large

- Example: Even if you call only one function from your program from library with code for 100 functions, the entire code of all functions in the library will be added to the executable if you

Types of Libraries

- Shared (or dynamic) libraries
 - Prefix: *lib*
 - Extension: *.so* (may be followed by another *.* And a version number)
 - Example: the dynamic math library has the name *libm.so*
 - Functions from dynamic libraries are not inserted in the final executable during linking, only pointers are inserted to where the code is
 - The actual functions are read from the library at runtime when the executable is run
 - Pro: the executable file size is small
 - Con: The executable file cannot be run as it is, the dynamic library must also be “loaded” at runtime

Creating Static Libraries

Building a static library

- Write your programs in .h and .c files as before
 - IMPORTANT: No `main()` function should be there in any of the C files
 - The `main()` function will be there in the C program that uses this library
- Generate .o files each of the C files
 - Compile using the -c option of `gcc`
- Combine all the .o files into a static library using the `ar` command
 - Must name the library as per the naming convention mentioned in the last slide

Example

- Suppose you want to create a static library named `libstaqueue.a` that will contain functions to implement `stack` and `queue` data structures
- Put all `typedefs` and function prototypes for `stack` and `queue` datatype are in `defs.h`, `stack.h` and `queue.h` respectively
 - See the files given
 - `stack.h` and `queue.h` includes `defs.h`, but we protect it with a `#ifndef` to make sure that any file (.h or .c) that includes both `stack.h` and `queue.h` includes `def.h` only once
- Put all functions bodies for `stack` and `queue` in `stack.c` and `queue.c` respectively
 - Do not put `main()` function in any file

Example

- Create the .o files for **stack.c** and **queue.c**
- Use the **ar** (archive) command to create the library

```
$ gcc -c stack.c  
$ gcc -c queue.c  
$ ar rcs libstaqueue.a stack.o queue.o
```

```
$ ls -l  
-rw-r--r-- 1 agupta faculty 138 Jul 31 16:35 defs.h  
-rw-r--r-- 1 agupta faculty 5950 Jul 31 17:05 libstaqueue.a  
-rw-r--r-- 1 agupta faculty 698 Jul 31 16:59 queue.c  
-rw-r--r-- 1 agupta faculty 748 Jul 31 16:40 queue.h  
-rw-r--r-- 1 agupta faculty 2680 Jul 31 17:04 queue.o  
-rw-r--r-- 1 agupta faculty 894 Jul 31 17:03 stack.c  
-rw-r--r-- 1 agupta faculty 617 Jul 31 16:37 stack.h  
-rw-r--r-- 1 agupta faculty 2896 Jul 31 17:03 stack.o  
-rw-r--r-- 1 agupta faculty 368 Jul 31 17:01 staqueuecheck.c  
-rw-r--r-- 1 agupta faculty 38 Jul 31 16:40 staqueue.h
```

Options for **ar** command used:

r: insert with replacement

c: create the archive if not there

s: creates an index of the symbols defined

The order (options, then output file name, and the list of files to go in the library) is important.

A peek inside the .o and .a files

A few lines not shown due to space

```
$ nm stack.o
```

```
000000000000000036 T destroystack
000000000000000076 T emptystack
                     U free
000000000000000000 T initstack
                     U malloc
0000000000000000e7 T pop
                     U printf
0000000000000000115 T printstack
0000000000000000ab T push
                     U puts
000000000000000097 T top
```

```
$ nm queue.o
```

```
0000000000000000105 T dequeue
00000000000000004a T destroyqueue
0000000000000000ac T emptyqueue
0000000000000000e4 T enqueue
                     U free
0000000000000000c8 T front
000000000000000000 T initqueue
                     U malloc
0000000000000000121 T printqueue
                     U puts
```

The “U” are undefined still!

Run `nm libstaqueue.a` and see what is printed

Using the library created

- To use the library, a user program has to know the library name, and what header files to include for using the library
 - Example: To use the math library, you need to know the math library name and the header file to include (`math.h`)
- Create a header file `libstaqueue.h` that will include both `stack.h` and `queue.h`
 - This is the single header file that will be `#included` by any user program using the `libstaqueue.a` library
 - Similar to the `math.h` that you include when you want to use the math library
 - Not mandatory to have a single header file, just a convenience so that user does not have to remember the individual file names and which to include for which functions
 - Not always possible if there are large number of diverse types of functions in the library requiring many different header files
 - Example: C standard library. You include `stdio.h` for `printf/scanf` etc., `stdlib.h` for `malloc`, `string.h` for `strcpy/strcmp` etc.
 - Manpage of the function tells you which header file you need to include

Example

- Suppose you write a C program in a file `staqueuecheck.c` that declares variables of type `stack` and `queue` and calls the `stack` and `queue` functions in the library
 - `staqueuecheck.c` will have a `main()` function
 - It will include the header file `staqueue.h` using `#include`
 - Compile it with `-l` option to create the final executable file `a.out`
 - `gcc staqueuecheck.c -lstaqueue`
 - Note that you didn't have to type the full name `libstaqueue.a`. The prefix `lib` and the suffix `.a` is automatically added by `gcc`
 - How will the compiler know in which directory `libstaqueue.a` is?
 - You can tell the compiler with the `-L` option of `gcc` (same format as for `-I` for `.h` files)
 - You can set the `LIBRARY_PATH` shell variable (same way as for `C_INCLUDE_PATH` for header files)

- So why no -L was needed when you used -lm in your programs?
 - There are default directories that the linker automatically looks at by default
 - Similar to what happens for `#include <..>`
 - math library `libm.a` is placed in one of these default directories, `LIBRARY_PATH` already set to them
- For using `printf/scanf` etc., which are in C library, you did not need to specify even -l option. Why?
 - C standard library is linked by default by gcc for C programs
- Actually, by default, dynamic libraries are used for both C standard library and math libraries. However, for them also, the above stands.

```
$ ls -l
```

```
-rwxr-xr-x 1 agupta faculty 17440 Jul 31 17:09 a.out  
-rw-r--r-- 1 agupta faculty  138 Jul 31 16:35 defs.h  
-rw-r--r-- 1 agupta faculty 5950 Jul 31 17:05 libstaque.a  
-rw-r--r-- 1 agupta faculty  698 Jul 31 16:59 queue.c  
-rw-r--r-- 1 agupta faculty  748 Jul 31 16:40 queue.h  
-rw-r--r-- 1 agupta faculty 2680 Jul 31 17:04 queue.o  
-rw-r--r-- 1 agupta faculty  894 Jul 31 17:03 stack.c  
-rw-r--r-- 1 agupta faculty  617 Jul 31 16:37 stack.h  
-rw-r--r-- 1 agupta faculty 2896 Jul 31 17:03 stack.o  
-rw-r--r-- 1 agupta faculty  368 Jul 31 17:01 staquecheck.c  
-rw-r--r-- 1 agupta faculty   38 Jul 31 16:40 staque.h
```

Note that every executable file that is linked with the library will have the full library code added to it.

Creating Dynamic Libraries

Creating dynamic library

- Consider that you want to build the same library, but this time a dynamic library `libstaque.so`
- Generate the .o files (`stack.o` and `queue.o`) for the .c files (`stack.c` and `queue.c`) same as before, but with an extra option
 - `gcc -fPIC -c stack.c`
 - `gcc -fPIC -c queue.c`
 - -fPIC option forces generation of position-independent code (so the library can be loaded anywhere in memory, it is not dependent on being loaded at some specific memory area only)
- Use the command below to generate the library
 - `gcc -shared -o libstaque.so stack.o queue.o`

```
$ gcc -fPIC -c stack.c
```

```
$ gcc -fPIC -c queue.c
```

```
$ gcc -shared -o libstaqueue.so stack.o queue.o
```

```
$ ls -l
```

```
-rw-r--r-- 1 agupta faculty 138 Jul 31 18:04 defs.h
```

```
-rwxr-xr-x 1 agupta faculty 16816 Jul 31 18:10 libstaqueue.so
```

```
-rw-r--r-- 1 agupta faculty 698 Jul 31 18:04 queue.c
```

```
-rw-r--r-- 1 agupta faculty 748 Jul 31 18:04 queue.h
```

```
-rw-r--r-- 1 agupta faculty 2680 Jul 31 18:09 queue.o
```

```
-rw-r--r-- 1 agupta faculty 894 Jul 31 18:04 stack.c
```

```
-rw-r--r-- 1 agupta faculty 617 Jul 31 18:04 stack.h
```

```
-rw-r--r-- 1 agupta faculty 2896 Jul 31 18:09 stack.o
```

```
-rw-r--r-- 1 agupta faculty 368 Jul 31 18:04 staqueuecheck.c
```

```
-rw-r--r-- 1 agupta faculty 38 Jul 31 18:04 staqueue.h
```

Using a shared library

- Use the same command as before
 - `gcc staquecheck.c -lstaque`
 - Use `-L` and `-I` as before as needed

```
$ ls -l
```

```
-rwxr-xr-x 1 agupta faculty 17016 Jul 31 18:17 a.out  
-rw-r--r-- 1 agupta faculty  138 Jul 31 18:04 defs.h  
-rwxr-xr-x 1 agupta faculty 16816 Jul 31 18:10 libstaque.so  
-rw-r--r-- 1 agupta faculty  698 Jul 31 18:04 queue.c  
-rw-r--r-- 1 agupta faculty  748 Jul 31 18:04 queue.h  
-rw-r--r-- 1 agupta faculty 2680 Jul 31 18:09 queue.o  
-rw-r--r-- 1 agupta faculty  894 Jul 31 18:04 stack.c  
-rw-r--r-- 1 agupta faculty  617 Jul 31 18:04 stack.h  
-rw-r--r-- 1 agupta faculty 2896 Jul 31 18:09 stack.o  
-rw-r--r-- 1 agupta faculty  368 Jul 31 18:04 staquecheck.c  
-rw-r--r-- 1 agupta faculty   38 Jul 31 18:04 staque.h
```

- Unlike the static library, the linker does not actually include the code of the library functions to the executable file created
- It only stores “pointer” to which library and where in that library a called function is
- The function code will be read from the .so library at runtime
- The stack and queue function show as undefined in your **a.out** created
- The .so library must be available from where you run your **a.out** at runtime for it to work
- If more than one program links with the same dynamic library, only one copy of the dynamic library will be loaded, all will access that one copy as needed.

```
$nm a.out | grep " U "
```

```
U destroyqueue
```

```
U destroystack
```

```
U enqueue
```

```
U exit@@GLIBC_2.2.5
```

```
U initqueue
```

```
U initstack
```

```
U __libc_start_main@@GLIBC_2.2.5
```

```
U printqueue
```

```
U printstack
```

```
U push
```

```
U rand@@GLIBC_2.2.5
```

Trying to run the a.out

```
$ ./a.out
```

```
./a.out: error while loading shared libraries: libstaque.so: cannot open shared object file: No such file or directory
```

- What is the error? First run this command (**ldd** stands for “load dynamic”)

- **\$ ldd a.out**

```
linux-vdso.so.1 (0x00007ffeda9d4000)
```

```
libstaque.so => not found
```

```
libc.so.6 => /lib/x86_64-linux-gnu/libc.so.6 (0x00007fe9e9609000)
```

```
/lib64/ld-linux-x86-64.so.2 (0x00007fe9e981d000)
```

- It shows **a.out** needs 4 shared libraries, found 3, but could not find **libstaque.so**

- Why? Because you haven't yet told the system where to look for libstaque.so!
 - Same problems we solved at compilation time using -I and -L options, or C_INCLUDE_PATH and LIBRARY_PATH variables
 - But they address the problem at compilation time, not at runtime
- You need to set the environment variable LD_LIBRARY_PATH (LD is short form for "Load") to the directory to look for (in this example the current directory)

```
$ echo $LD_LIBRARY_PATH
```

```
$ export LD_LIBRARY_PATH=$LD_LIBRARY_PATH:..
```

```
$ echo $LD_LIBRARY_PATH
```

```
..
```

```
$ ./a.out
```

```
The contents of the stack (from top) is: 83 0
```

```
...
```

```
...
```

What if the library changes?

- Ideally, all programs that have linked with the library should be recompiled and linked with the new library
- If you don't
 - For static libraries, the executable already has the old library code in it, so it will continue to work without error, just will not see the new changes
 - For dynamic library,
 - The executable has the dynamic library identifier still in it, so if the old library is still available without any change, it will continue to work without error, just will not see the new changes
 - If the old library is updated (name changed or contents of the library changed), you can get errors at runtime

Forcing to use static libraries only

- You may have both static and dynamic versions of a library
 - Example: `libm.a` and `libm.so` for the math library
- What if you want to force the compiler to use only static libraries?
 - Use the `—static` flag in `gcc`
 - Will force the compiler to use only static libraries for all libraries being linked

```
$ gcc -static staqueuecheck.c -lstaqueue
```

```
$ ./a.out
```

```
The contents of the stack (from top) is: 83 0
```

```
...
```

```
...
```

```
$ ldd a.out
```

```
not a dynamic executable
```

There is no dynamic libraries to load for `a.out`

```
$ nm a.out | grep " U "
```

```
$
```

Nothing is undefined in `a.out`

Size difference between using static and dynamic libraries

Using dynamic libraries only

```
$ gcc staqueuecheck.c -lstaqueue
```

```
$ ls -l a.out
```

```
-rwxr-xr-x 1 agupta faculty 17016 Aug  4 12:20 a.out
```

Using static libraries only

```
$ gcc -static staqueuecheck.c -lstaqueue
```

```
$ ls -l a.out
```

```
-rwxr-xr-x 1 agupta faculty 877504 Aug  4 12:24 a.out
```

```
$ ldd a.out
```

not a dynamic executable

- The huge increase in size is coming from the fact that the `-static` option forced the compiler to use the static versions of the standard C library also, putting all code of it in `a.out` even though only `printf` is called from it

An extreme example of size bloat

- Write a C file dummy.c with only these lines

```
int main()  
{  
  
}
```

- Now compile it linking with libstaque.h

```
$ gcc -static dummy.c -lstaque
```

```
$ ls -l a.out
```

```
-rwxr-xr-x 1 agupta faculty 871768 Aug  4 12:30 a.out
```

See the a.out size, even though the .c file basically does nothing and did not use any function from any library!!!

Compile without the -static flag to see the difference

Practice in Lab

- Create a subdirectory under home directory named `stq_library`. Change to the subdirectory.
- Type the files `defs.h` `stack.h` `queue.h` `staque.h` `stack.c` `queue.c` and `staquecheck.c` from the code given, all in the `stq_library` subdirectory
- Create the `.o` files for `stack.c` and `queue.c` only
- Combine the `.o` files into a static library named `libstaque.a`
- Compile `staquecheck.c` linking with `libstaque.a` to create an executable `staquecheck.exe`. Test to see it runs properly. Then delete it.
- Create a subdirectory called `mylib` under your home directory.
- Move (not copy) `libstaque.a` to `~/mylib`
- Compile `staquecheck.c` again linking with `libstaque.c` to create an executable `staquecheck.exe`. Do you see any error?
- Use the `-L` option specifying the directory where `libstaque.a` is to compile without error
- Print the value of the shell variable `LIBRARY_PATH`
- Add the `mylib` directory created to it
- Now compile again without the `-L` option and test everything.

- Create another subdirectory named `stq_shared` under your home directory
- Copy all the `.h` and `.c` files from the `stq_library` subdirectory to it
- Create a dynamic library `libstaque.so`
- Compile `staquecheck.c` linking with `libstack.so` to create `a.out`
- Run `ldd` command on `a.out` to see that it depends on `libstack.so`
- Test out everything same as for the static library in the last slides
- Copy `libstaque.so` to the `stq_library` directory
- Compile `staquecheck.c` with and without the `-static` flag and observe the difference in size of `a.out` created