

The screenshot shows the Postman interface with a collection named "laboratorio-7". A new request is being made to `http://localhost:5000/signin` using the POST method. The request body contains:

```
1 {  
2   "email": "cualquier@correo.com",  
3   "password": "loquequieras"  
4 }
```

The response status is 200 OK, with a response time of 768 ms and a response size of 459 B. The response body is a JSON object containing a token:

```
1 {  
2   "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.  
3   eyJpZCI6MSwiZW1haWwiOiJjdWFscXVpZXJAY29ycmVlbnVsISImIhdCI6MTc2MjA1MzA2OSwIZXhwIjoxNzYyMDU2NjY5fQ.  
4   jI77a0jCUCtsisX97vIqaF7CGomishLfbDm-2b33cEE"  
5 }
```

The screenshot shows the Postman interface with the same collection "laboratorio-7". A new request is being made to `http://localhost:5000/protected` using the GET method. The request includes an Authorization header set to "Bearer Token" with a value of a redacted token.

The response status is 200 OK, with a response time of 14 ms and a response size of 398 B. The response body is a JSON object containing user information:

```
1 {  
2   "message": "Has accedido a la ruta protegida!",  
3   "user": {  
4     "id": 1,  
5     "email": "cualquier@correo.com",  
6     "iat": 1762053069,  
7     "exp": 1762056669  
8   }  
9 }
```