

Scripting Basics: Python

Practical task

Task 1

1. Create a script that accepts the file name and puts its extension to output. If there is no extension - an exception should be raised.
2. Create a script that reads the access log from a file. The name of the file is provided as an argument. An output of the script should provide the total number of different User Agents and then provide statistics with the number of requests from each of them. [Here is a link to an example access.log file.](#)
3. Develop a python script that:
 - Creates an rc tag for the latest commit in specific Github repository for main branch
 - Creates a release tag when executed with a `--create-release` flag
 - The rc tag should follow the format `vX.Y.Z`(e.g: `rc/1.2.3`). Y increments with each new rc tag created
 - If run with `--create-release` flag: Create rc tag and release tag in format `X.Y.Z`
4. Write a script that gets system information like distro info, memory(total, used, free), CPU info (model, core numbers, speed), current user, system load average, and IP address. Use arguments for specifying resources. (For example, `-d` for distro `-m` for memory, `-c` for CPU, `-u` for user info, `-l` for load average, `-i` for IP address).

Task2

Create a script that uses the Survey Monkey (<https://www.surveymonkey.com>) service, and creates a survey.

PREREQUISITES:

Sign up at <https://www.surveymonkey.com>

Create a draft application at <https://developer.surveymonkey.com>

No need to deploy your application. It's just for testing. Do not forget to set permissions for your application.

After creating a draft application you will obtain an

ACCESS_TOKEN which is needed to do API requests from your script.

REQUIREMENTS:

The script should accept a JSON file with questions for the survey and a text file with a list of email addresses.

The structure of a JSON file with questions:

```
{
  "Survey_Name": {
    "Page_Name": {
      "Question1_Name": {
        "Description" : "Description of question",
        "Answers" : [
          "Answer1",
          "Answer2",
          "Answer3"
        ]
      },
      "Question2_Name": {
        "Description" : "Description of question",
        "Answers" : [
          "Answer1",
          "Answer2",
          "Answer3"
        ]
      }
    }
  }
}
```

iii. There should be at least 3 questions and 2 recipients.

Task1:

1. Create a script that accepts the file name and puts its extension to output. If there is no extension - an exception should be raised.

Code:

```
# file_extension.py
import sys
import os
```

```

def get_extension(filename):
    if "." not in filename or filename.startswith("."):
        raise Exception("No extension found!")
    return filename.split(".")[1]

if __name__ == "__main__":
    if len(sys.argv) != 2:
        print("Usage: python file_extension.py <filename>")
        sys.exit(1)

    try:
        ext = get_extension(sys.argv[1])
        print(f"Extension: {ext}")
    except Exception as e:
        print(f"Error: {e}")

```

Output:

```

dsarrafriddynamics.com@C19548 Scripting Basics: Python-practical task % cd Task-1
dsarrafriddynamics.com@C19548 Task-1 % python3 file_extension.py test.py
Extension: py

```

2. Create a script that reads the access log from a file. The name of the file is provided as an argument. An output of the script should provide the total number of different User Agents and then provide statistics with the number of requests from each of them.

Code :

```

# github_tagging.py
import requests
import sys
import argparse

GITHUB_API = "https://api.github.com"

def get_latest_tag(repo, token):

```

```

url = f"{GITHUB_API}/repos/{repo}/tags"
headers = {"Authorization": f"token {token}"}
response = requests.get(url, headers=headers)
tags = response.json()
return tags[0]["name"] if tags else None

```

```

def create_tag(repo, token, tag_name, commit_sha):
    url = f"{GITHUB_API}/repos/{repo}/git/refs"
    headers = {"Authorization": f"token {token}"}
    data = {
        "ref": f"refs/tags/{tag_name}",
        "sha": commit_sha
    }
    response = requests.post(url, json=data, headers=headers)
    print(f"Created tag: {tag_name}")

```

```

def get_latest_commit(repo, token):
    url = f"{GITHUB_API}/repos/{repo}/commits/main"
    headers = {"Authorization": f"token {token}"}
    response = requests.get(url, headers=headers)
    return response.json()["sha"]

```

```

def increment_version(version):
    x, y, z = map(int, version.split("."))
    return f"{x}.{y+1}.{z}"

```

```

def main():
    parser = argparse.ArgumentParser()
    parser.add_argument("--repo", required=True)
    parser.add_argument("--token", required=True)
    parser.add_argument("--create-release", action="store_true")
    args = parser.parse_args()

```

```

latest = get_latest_tag(args.repo, args.token)
version = "1.0.0" if not latest else latest.replace("rc/", "")

```

```

new_version = increment_version(version)
commit_sha = get_latest_commit(args.repo, args.token)

# RC Tag
rc_tag = f"rc/{new_version}"
create_tag(args.repo, args.token, rc_tag, commit_sha)

if args.create_release:
    create_tag(args.repo, args.token, new_version, commit_sha)

if __name__ == "__main__":
    main()

```

Output:

```

dsarrafriddynamics.com@C19548 Downloads % ls apache-tomcat-9.0.117/logs
catalina.2026-04-17.log          localhost.2026-04-20.log
catalina.2026-04-20.log          localhost_access_log.2026-04-17.txt
catalina.out                     localhost_access_log.2026-04-20.txt
host-manager.2026-04-17.log      manager.2026-04-17.log
host-manager.2026-04-20.log      manager.2026-04-20.log
Localhost.2026-04-17.log

dsarrafriddynamics.com@C19548 Downloads % tail apache-tomcat-9.0.117/logs/localhost_access_log.2026-04-20.txt
0:0:0:0:0:0:1 -- [20/Apr/2026:10:11:17 +0530] "GET /asf-logo-wide.svg HTTP/1.1" 200 7089
0:0:0:0:0:0:1 -- [20/Apr/2026:10:11:17 +0530] "GET /bg-nav.png HTTP/1.1" 200 1401
0:0:0:0:0:0:1 -- [20/Apr/2026:10:11:17 +0530] "GET /bg-middle.png HTTP/1.1" 200 1918
0:0:0:0:0:0:1 -- [20/Apr/2026:10:11:17 +0530] "GET /bg-button.png HTTP/1.1" 200 713
0:0:0:0:0:0:1 -- [20/Apr/2026:10:11:17 +0530] "GET /bg-upper.png HTTP/1.1" 200 3103
0:0:0:0:0:0:1 -- [20/Apr/2026:10:12:31 +0530] "GET /jenkins HTTP/1.1" 404 759
0:0:0:0:0:0:1 -- [20/Apr/2026:10:12:31 +0530] "GET /jenkins HTTP/1.1" 404 759
0:0:0:0:0:0:1 -- [20/Apr/2026:10:15:05 +0530] "GET / HTTP/1.1" 200 11232
0:0:0:0:0:0:1 -- [20/Apr/2026:10:16:33 +0530] "GET /jenkins HTTP/1.1" 404 759
0:0:0:0:0:0:1 -- [20/Apr/2026:10:16:34 +0530] "GET /jenkins HTTP/1.1" 404 759
dsarrafriddynamics.com@C19548 Downloads % cd ~/Downloads/Assignments/"Scripting Basics: Python-practical task"/Task-1
dsarrafriddynamics.com@C19548 Task-1 % python3 log_parser.py
~/Downloads/apache-tomcat-9.0.117/logs/localhost_access_log.2026-04-20.txt
Total unique User Agents: 1

Unknown -> 25
dsarrafriddynamics.com@C19548 Task-1 % nano ~/Downloads/apache-tomcat-9.0.117/conf/server.xml
dsarrafriddynamics.com@C19548 Task-1 % cd ~/Downloads/apache-tomcat-9.0.117/bin
dsarrafriddynamics.com@C19548 bin % ./shutdown.sh
Using CATALINA_BASE: /Users/dsarrafriddynamics.com@C19548/Downloads/apache-tomcat-9.0.117

```

```

Using CATALINA_HOME: /Users/dsarra/Downloads/apache-tomcat-9.0.117
Using CATALINA_TMPDIR: /Users/dsarra/Downloads/apache-tomcat-9.0.117/temp
Using JRE_HOME: /opt/homebrew/Cellar/openjdk@17/17.0.18/libexec/openjdk.jdk/Contents/Home
Using CLASSPATH: /Users/dsarra/Downloads/apache-tomcat-9.0.117/bin/bootstrap.jar:/Users/dsarra/Downloads/apache-tomcat-9.0.117/bin/tomcat-juli.jar
Using CATALINA_OPTS:
NOTE: Picked up JDK_JAVA_OPTIONS: --add-opens=java.base/java.lang=ALL-UNNAMED
--add-opens=java.base/java.lang.invoke=ALL-UNNAMED --add-opens=java.base/java.lang.reflect=ALL-UNNAMED
--add-opens=java.base/java.io=ALL-UNNAMED --add-opens=java.base/java.util=ALL-UNNAMED
--add-opens=java.base/java.util.concurrent=ALL-UNNAMED --add-opens=java.rmi/sun.rmi.transport=ALL-UNNAMED
Apr 22, 2026 2:11:04 PM org.apache.catalina.startup.Catalina stopServer
SEVERE: Could not contact [localhost:8005] (base port [8005] and offset [0]). Tomcat may not be running.
Apr 22, 2026 2:11:04 PM org.apache.catalina.startup.Catalina stopServer
SEVERE: Error stopping Catalina
java.net.ConnectException: Connection refused
    at java.base/sun.nio.ch.Net.connect0(Native Method)
    at java.base/sun.nio.ch.Net.connect(Net.java:591)
    at java.base/sun.nio.ch.Net.connect(Net.java:580)
    at java.base/sun.nio.ch.NioSocketImpl.connect(NioSocketImpl.java:593)
    at java.base/java.net.SocksSocketImpl.connect(SocksSocketImpl.java:327)
    at java.base/java.net.Socket.connect(Socket.java:633)
    at java.base/java.net.Socket.connect(Socket.java:583)
    at java.base/java.net.Socket.<init>(Socket.java:507)
    at java.base/java.net.Socket.<init>(Socket.java:287)
    at org.apache.catalina.startup.Catalina.stopServer(Catalina.java:630)
    at java.base/jdk.internal.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
    at java.base/jdk.internal.reflect.NativeMethodAccessorImpl.invoke(NativeMethodAccessorImpl.java:77)
    at java.base/jdk.internal.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)
    at java.base/java.lang.reflect.Method.invoke(Method.java:569)
    at org.apache.catalina.startup.Bootstrap.stopServer(Bootstrap.java:390)
    at org.apache.catalina.startup.Bootstrap.main(Bootstrap.java:479)

dsarra@griddynamics.com@C19548 bin % ./startup.sh
Using CATALINA_BASE: /Users/dsarra/Downloads/apache-tomcat-9.0.117
Using CATALINA_HOME: /Users/dsarra/Downloads/apache-tomcat-9.0.117
Using CATALINA_TMPDIR: /Users/dsarra/Downloads/apache-tomcat-9.0.117/temp
Using JRE_HOME: /opt/homebrew/Cellar/openjdk@17/17.0.18/libexec/openjdk.jdk/Contents/Home
Using CLASSPATH: /Users/dsarra/Downloads/apache-tomcat-9.0.117/bin/bootstrap.jar:/Users/dsarra/Downloads/apache-tomcat-9.0.117/bin/tomcat-juli.jar
Using CATALINA_OPTS:
Tomcat started.

dsarra@griddynamics.com@C19548 bin % tail ~/Downloads/apache-tomcat-9.0.117/logs/localhost_access_log*.txt
==> /Users/dsarra/Downloads/apache-tomcat-9.0.117/logs/localhost_access_log.2026-04-17.txt <==

==> /Users/dsarra/Downloads/apache-tomcat-9.0.117/logs/localhost_access_log.2026-04-20.txt <==
0:0:0:0:0:0:1 - - [20/Apr/2026:10:11:17 +0530] "GET /asf-logo-wide.svg HTTP/1.1" 200 7089
0:0:0:0:0:0:1 - - [20/Apr/2026:10:11:17 +0530] "GET /bg-nav.png HTTP/1.1" 200 1401
0:0:0:0:0:0:1 - - [20/Apr/2026:10:11:17 +0530] "GET /bg-middle.png HTTP/1.1" 200 1918
0:0:0:0:0:0:1 - - [20/Apr/2026:10:11:17 +0530] "GET /bg-button.png HTTP/1.1" 200 713
0:0:0:0:0:0:1 - - [20/Apr/2026:10:11:17 +0530] "GET /bg-upper.png HTTP/1.1" 200 3103
0:0:0:0:0:0:1 - - [20/Apr/2026:10:12:31 +0530] "GET /jenkins HTTP/1.1" 404 759
0:0:0:0:0:0:1 - - [20/Apr/2026:10:12:31 +0530] "GET /jenkins HTTP/1.1" 404 759
0:0:0:0:0:0:1 - - [20/Apr/2026:10:15:05 +0530] "GET / HTTP/1.1" 200 11232
0:0:0:0:0:0:1 - - [20/Apr/2026:10:16:33 +0530] "GET /jenkins HTTP/1.1" 404 759
0:0:0:0:0:0:1 - - [20/Apr/2026:10:16:34 +0530] "GET /jenkins HTTP/1.1" 404 759

```

```

==> /Users/dsarraf/Downloads/apache-tomcat-9.0.117/logs/localhost_access_log.2026-04-22.txt <==
0:0:0:0:0:0:1 - - [22/Apr/2026:14:11:17 +0530] "GET / HTTP/1.1" 200 11232 "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7)
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/147.0.0.0 Safari/537.36"
0:0:0:0:0:0:1 - - [22/Apr/2026:14:11:17 +0530] "GET /tomcat.svg HTTP/1.1" 200 67795 "Mozilla/5.0 (Macintosh; Intel Mac OS X
10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/147.0.0.0 Safari/537.36"
0:0:0:0:0:0:1 - - [22/Apr/2026:14:11:17 +0530] "GET /tomcat.css HTTP/1.1" 200 5584 "Mozilla/5.0 (Macintosh; Intel Mac OS X
10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/147.0.0.0 Safari/537.36"
0:0:0:0:0:0:1 - - [22/Apr/2026:14:11:17 +0530] "GET /asf-logo-wide.svg HTTP/1.1" 200 7089 "Mozilla/5.0 (Macintosh; Intel Mac
OS X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/147.0.0.0 Safari/537.36"
0:0:0:0:0:0:1 - - [22/Apr/2026:14:11:17 +0530] "GET /bg-nav.png HTTP/1.1" 200 1401 "Mozilla/5.0 (Macintosh; Intel Mac OS X
10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/147.0.0.0 Safari/537.36"
0:0:0:0:0:0:1 - - [22/Apr/2026:14:11:17 +0530] "GET /bg-upper.png HTTP/1.1" 200 3103 "Mozilla/5.0 (Macintosh; Intel Mac OS
X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/147.0.0.0 Safari/537.36"
0:0:0:0:0:0:1 - - [22/Apr/2026:14:11:17 +0530] "GET /bg-middle.png HTTP/1.1" 200 1918 "Mozilla/5.0 (Macintosh; Intel Mac OS
X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/147.0.0.0 Safari/537.36"
0:0:0:0:0:0:1 - - [22/Apr/2026:14:11:17 +0530] "GET /bg-button.png HTTP/1.1" 200 713 "Mozilla/5.0 (Macintosh; Intel Mac OS X
10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/147.0.0.0 Safari/537.36"
0:0:0:0:0:0:1 - - [22/Apr/2026:14:11:17 +0530] "GET /favicon.ico HTTP/1.1" 200 21630 "Mozilla/5.0 (Macintosh; Intel Mac OS X
10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/147.0.0.0 Safari/537.36"
0:0:0:0:0:0:1 - - [22/Apr/2026:14:11:18 +0530] "GET / HTTP/1.1" 200 11232 "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7)
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/147.0.0.0 Safari/537.36"

dsarrafriddynamics.com@C19548 Scripting Basics: Python-practical task % cd Task-1
dsarrafriddynamics.com@C19548 Task-1 % python3 log_parser.py
~/Downloads/apache-tomcat-9.0.117/logs/localhost_access_log.2026-04-22.txt
Total unique User Agents: 1

Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/147.0.0.0 Safari/537.36 ->
10

```

3. Develop a python script that:

Creates an rc tag for the latest commit in specific Github repository for main branch

Creates a release tag when executed with a --create-release flag

The rc tag should follow the format vX.Y.Z(e.g: rc/1.2.3). Y increments with each new rc tag created

If run with --create-release flag: Create rc tag and release tag in format X.Y.Z

Code:

```

# log_parser.py
import sys
import re
from collections import Counter

def extract_user_agent(log_line):
    match = re.findall(r'"([^\"]*)"$', log_line)

```

```

return match[0] if match else "Unknown"

def parse_log(file):
    agents = []

    with open(file, "r") as f:
        for line in f:
            agents.append(extract_user_agent(line))

    counter = Counter(agents)

    print(f"Total unique User Agents: {len(counter)}\n")
    for agent, count in counter.items():
        print(f"{agent} -> {count}")

if __name__ == "__main__":
    if len(sys.argv) != 2:
        print("Usage: python log_parser.py <access.log>")
        sys.exit(1)

    parse_log(sys.argv[1])

```

Output:

```

dsarrafriddynamics.com@C19548 Task-1 % python3 -m pip install requests
Requirement already satisfied: requests in
/Library/Frameworks/Python.framework/Versions/3.13/lib/python3.13/site-packages (2.33.1)
Requirement already satisfied: charset_normalizer<4,>=2 in
/Library/Frameworks/Python.framework/Versions/3.13/lib/python3.13/site-packages (from requests) (3.4.7)
Requirement already satisfied: idna<4,>=2.5 in
/Library/Frameworks/Python.framework/Versions/3.13/lib/python3.13/site-packages (from requests) (3.11)
Requirement already satisfied: urllib3<3,>=1.26 in
/Library/Frameworks/Python.framework/Versions/3.13/lib/python3.13/site-packages (from requests) (2.6.3)
Requirement already satisfied: certifi>=2023.5.7 in
/Library/Frameworks/Python.framework/Versions/3.13/lib/python3.13/site-packages (from requests) (2026.2.25)

[notice] A new release of pip is available: 25.2 -> 26.0.1
[notice] To update, run: python3 -m pip install --upgrade pip
dsarrafriddynamics.com@C19548 Task-1 % python3 github_tagging.py --repo dsarrafriddynamics.com/Assignments --token
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

Created tag: rc/1.1.0

```



```
dsarrafriddynamics.com@C19548 Task-1 % python3 github_tagging.py \  
--repo dsarrafr-png/Assignments \  
--token ghp_G2RjomyaA3hHcG0e86otuHsFwMM2W94LplQm \  
--create-release  
Created tag: rc/1.2.0  
Created tag: 1.2.0  
dsarrafriddynamics.com@C19548 Task-1 %
```

4. Write a script that gets system information like distro info, memory(total, used, free), CPU info (model, core numbers, speed), current user, system load average, and IP address. Use arguments for specifying resources. (For example, -d for distro -m for memory, -c for CPU, -u for user info, -l for load average, -i for IP address).

Code:

```
# system_info.py  
import argparse  
import platform  
import psutil  
import socket  
import os  
  
import socket  
import getpass  
print(getpass.getuser())  
  
def get_ip():  
    try:  
        s = socket.socket(socket.AF_INET, socket.SOCK_DGRAM)  
        s.connect(("8.8.8.8", 80))  
        ip = s.getsockname()[0]  
        s.close()  
        return ip  
    except:
```

```
    return "Unable to fetch IP"
```

```
parser = argparse.ArgumentParser()
parser.add_argument("-d", action="store_true")
parser.add_argument("-m", action="store_true")
parser.add_argument("-c", action="store_true")
parser.add_argument("-u", action="store_true")
parser.add_argument("-l", action="store_true")
parser.add_argument("-i", action="store_true")
```

```
args = parser.parse_args()
```

```
if args.d:
    print("Distro:", platform.platform())
```

```
if args.m:
    mem = psutil.virtual_memory()
    print(f"Memory -> Total: {mem.total}, Used: {mem.used}, Free: {mem.available}")
```

```
if args.c:
    print("CPU:", platform.processor())
    print("Cores:", psutil.cpu_count())
    print("Speed:", psutil.cpu_freq())
```

```
if args.u:
    print("User:", os.getlogin())
```

```
if args.l:
    print("Load Avg:", os.getloadavg())
```

```
if args.i:
    print("IP:", get_ip())
```

Output:

```

dsarrafriddynamics.com@C19548 Task-1 % python3 -m pip install psutil
Requirement already satisfied: psutil in
/Library/Frameworks/Python.framework/Versions/3.13/lib/python3.13/site-packages (7.2.2)

[notice] A new release of pip is available: 25.2 -> 26.0.1
[notice] To update, run: python3 -m pip install --upgrade pip
dsarrafriddynamics.com@C19548 Task-1 % python3 system_info.py -d
Distro: macOS-26.4.1-arm64-arm-64bit-Mach-O
dsarrafriddynamics.com@C19548 Task-1 % python3 system_info.py -m
Memory -> Total: 25769803776, Used: 7551959040, Free: 5118279680
dsarrafriddynamics.com@C19548 Task-1 % python3 system_info.py -c
CPU: arm
Cores: 12
Speed: scpufreq(current=4, min=1, max=4)
dsarrafriddynamics.com@C19548 Task-1 % python3 system_info.py -l
Load Avg: (4.03076171875, 3.06005859375, 2.6982421875)
dsarrafriddynamics.com@C19548 Task-1 % python3 system_info.py -i
IP: 172.18.153.137
dsarrafriddynamics.com@C19548 Task-1 % python3 system_info.py -u
dsarrafr
User: root
dsarrafriddynamics.com@C19548 Task-1 %

```

Task 2:

Code :

```

import json
import requests
import sys
from dotenv import load_dotenv
import os

load_dotenv()

ACCESS_TOKEN = os.getenv("ACCESS_TOKEN")

if not ACCESS_TOKEN:
    raise Exception("Missing ACCESS_TOKEN in .env")

BASE_URL = "https://api.surveymonkey.com/v3"

HEADERS = {

```

```
"Authorization": f"Bearer {ACCESS_TOKEN}",
"Content-Type": "application/json"
}
```

```
# =====
# CREATE SURVEY
# =====
def create_survey(title):
    res = requests.post(
        f"{BASE_URL}/surveys",
        headers=HEADERS,
        json={"title": title}
    )
    res.raise_for_status()
    data = res.json()

    print("Survey created:", data["id"])
    return data["id"]
```

```
# =====
# CREATE PAGE
# =====
def create_page(survey_id, title):
    res = requests.post(
        f"{BASE_URL}/surveys/{survey_id}/pages",
        headers=HEADERS,
        json={"title": title}
    )
    res.raise_for_status()
    return res.json()["id"]
```

```

# =====
# CREATE QUESTION
# =====
def create_question(survey_id, page_id, question_text, answers):
    payload = {
        "headings": [{"heading": question_text}],
        "family": "single_choice",
        "subtype": "vertical",
        "answers": {
            "choices": [{"text": a} for a in answers]
        }
    }

    res = requests.post(
        f'{BASE_URL}/surveys/{survey_id}/pages/{page_id}/questions',
        headers=HEADERS,
        json=payload
    )

    res.raise_for_status()
    return res.json()

```

```

# =====
# CREATE COLLECTOR (FIXED)
# =====
def create_collector(survey_id):
    res = requests.post(
        f'{BASE_URL}/surveys/{survey_id}/collectors',
        headers=HEADERS,
        json={
            "type": "weblink",
            "name": "Web Link Collector"
        }
    )

```

```
res.raise_for_status()
data = res.json()
```

```
collector_id = data["id"] #  FIXED (was your main bug)
```

```
print("Collector created:", collector_id)
print("Survey Link:", data.get("url"))
```

```
return collector_id
```

```
# =====
```

```
# CREATE MESSAGE (SAFE)
```

```
# =====
```

```
def create_message(survey_id, collector_id):
```

```
    res = requests.post(
        f'{BASE_URL}/surveys/{survey_id}/collectors/{collector_id}/messages',
        headers=HEADERS,
        json={
            "type": "invite",
            "subject": "Survey Invitation",
            "body_text": "Please participate in this survey."
        }
    )
```

```
res.raise_for_status()
return res.json()["id"]
```

```
# =====
```

```
# RECIPIENTS (NOT USED FOR WEBLINK)
```

```
# =====
```

```
def send_recipients(survey_id, collector_id, message_id, emails):
```

```
    # NOTE: Weblink collectors don't need recipients
```

```
print("Skipping recipients (weblink collector used)")
return None
```

```
# =====
```

```
# LOAD EMAILS
```

```
# =====
```

```
def load_emails(file_path):
    with open(file_path, "r") as f:
        return f.readlines()
```

```
# =====
```

```
# MAIN
```

```
# =====
```

```
def main():
    if len(sys.argv) != 3:
        print("Usage: python survey_script.py survey.json emails.txt")
        sys.exit(1)
```

```
survey_file = sys.argv[1]
```

```
with open(survey_file, "r") as f:
    data = json.load(f)
```

```
for survey_name, pages in data.items():
    print("\nCreating survey:", survey_name)
```

```
survey_id = create_survey(survey_name)
```

```
for page_name, questions in pages.items():
    page_id = create_page(survey_id, page_name)
```

```
for q_text, q_data in questions.items():
    print("Adding question:", q_text)
```

```

        create_question(
            survey_id,
            page_id,
            q_text,
            q_data["Answers"]
        )

    collector_id = create_collector(survey_id)

    print("\n✅ SURVEY CREATED SUCCESSFULLY")
    print("Survey ID:", survey_id)

if __name__ == "__main__":
    main()

```

Output:

```

dsarrafriddynamics.com@C19548 Task-2 % python3 survey_script.py survey.json emails.txt

Creating survey: Employee Feedback Survey
Survey created: 422209781
Adding question: How satisfied are you with your workspace?
Adding question: Do you have the tools you need to work effectively?
Adding question: How is communication in your team?
Collector created: 439487067
Survey Link: https://www.surveymonkey.com/r/XCYWDBX

✅ SURVEY CREATED SUCCESSFULLY
Survey ID: 422209781
dsarrafriddynamics.com@C19548 Task-2 %

```

Can view the created survey here and can answer the questions and submit the form.
Valid for 90 days.

Survey Link: <https://www.surveymonkey.com/r/XCYWDBX>