Program1: PERSONALPROFILE

```
<!DOCTYPEhtml>
<html>
<head>
<title>Personal Profile</title>
<style>
body {
font-family: Arial;
background-color: lightblue;
text-align: center;
}
.profile {
background-color: white;
width: 300px;
margin: 50px auto;
padding: 20px;
border: 2px solid blue;
border-radius: 10px;
}
img {
width: 120px;
height: 120px;
border-radius: 50%;
}
h1 {
color: darkblue;
```

```
}
</style>
</head>
<body>
<div class="profile">
<img src="profile.jpg" alt="Profile Photo">
<h1>KAVITHA</h1>
<p><b>Course:</b> M.Sc IT</p>
<p><b>College:</b> THIRUVALLUVAR UNIVERSITY</p>
<p><b>Skills:</b> HTML, CSS, Java</p>
<p><b>Hobbies:</b> Reading, Coding, Music</p>
<p><b>Email:</b> yourname@email.com</p>
</div>
</body>
</html>
```

Program:2 Create Student Registration Form with Validation

```
<!DOCTYPEhtml>
<html>
<head>
<title>Student Registration Form</title>
<style>
body{font-family:Arial;background:#e8f5e9;display:flex;justify-content:center;align
items:center;height:100vh;margin:0}
.container{width:400px;background:white;padding:20px;border-radius:10px;box-shadow:0
0 10px
gray}
h2{text-align:center;color:darkblue}
label{font-weight:bold}
input,select{width:100%;padding:8px;margin:5px 0 10px;box-sizing:border-box}
input[type=radio]{width:auto}
.buttons{text-align:center}
input[type=submit],input[type=reset]{width:auto;padding:10px 20px;border:0;border
radius:5px;color:white;cursor:pointer;margin:5px}
input[type=submit]{background:green} input[type=reset]{background:red}
#successMessage{text-align:center;color:green;font-weight:bold;font-size:18px}
small{color:gray}
</style>
</head>
<body>
<div class="container">
<h2>Student Registration Form</h2>
```

```
<form id="registrationForm">
<label>Full Name:</label><input type="text" required>
<label>Email:</label><input type="email" required>
<label>Phone:</label><input type="tel" pattern="[0-9]{10}" required>
<small>Enter 10-digit number</small><br>
<label>Age:</label>
<input type="number" min="18" max="30" required>
<label>Gender:</label><br>
<input type="radio" name="gender" required> Male
<input type="radio" name="gender"> Female<br><br>
<label>Course:</label>
<select required><option value="">Select
Course</option><option>BCA</option><option>BSc</option><option>BCom</option><o
ption>B
A</option></select>
<label>Department:</label>
<select required><option value="">Select Department</option><option>Computer
Science</option><option>Data
Science</option><option>Zoology</option><option>Mathematics</option><option>Histo
ry</option
><option>Tamil</option><option>English</option></select>
<label>Password:</label><input type="password" minlength="6" required>
<div class="buttons"><input type="submit" value="Register"><input type="reset"
value="Clear"></div>
</form>
<p id="successMessage"></p>
</div>
```

```
<script>
document.getElementById("registrationForm").onsubmit=function(e){
e.preventDefault();
document.getElementById("successMessage").innerHTML="✅ Registration Successfully
Completed!";
this.reset();
};</script>
</body>
</html>
```

Program:6 To-Do List using JavaScript

```
<!DOCTYPEhtml>
<html>
<head>
<title>To-Do List</title>
<style>
body{font-family:Arial;background:lightgray}
.container{width:350px;margin:80pxauto;background:white;padding:20px;
border-radius:10px;text-align:center;box-shadow:0 0 10px gray}
input{width:65%;padding:10px}
button{padding:10px;background:blue;color:white;border:0;cursor:pointer}
ul{list-style:none;padding:0}
li{background:#f2f2f2;margin:10px
0;padding:10px; display:flex;justify-content:space
between}
.delete{background:red;padding:5px 10px}
</style>
</head>
<body>
<div class="container">
<h2>To-Do List</h2>
<input id="task" placeholder="Enter a task">
<button onclick="addTask()">Add</button>
<ul id="list"></ul>
</div>
<script>
```

```
function addTask(){
let t=document.getElementById("task").value;
if(t=="") return alert("Enter a task");
document.getElementById("list").innerHTML+=
`<li>${t}<button class="delete"
onclick="this.parentElement.remove()">Delete</button></li>`;
document.getElementById("task").value="";
}
</script>
</body>
</html>
```

Program 10: Dynamic Image Movement using JavaScript

```
<html>
<head>
<style>
.moveable {
position: absolute;
}
</style>
<script type="text/javascript">
var x = 5;
var y = 5;
var dest_x = 300;
var dest_y = 300;
var interval = 10;
function moveImage()
{
if (x < dest_x)
x =x+interval;
if (y < dest_y)
y =y+interval;
document.getElementById("ufo").style.top = y + "px";
document.getElementById("ufo").style.left = x + "px";
if ((x + interval < dest_x) && (y + interval < dest_y))
{
window.setTimeout("moveImage()", 100);
}
```

```
}
</script>
</head>
<body onload="moveImage()">
<div id="ufo" class="moveable">
<img src="C:\Users\acer\Desktop\image2.jpeg"
alt="please link to a valid image" />
</div>
</body>
</html>
```