



Multi-Armed Bandits

Daniel Brown



Evaluative feedback




| REPORT CARD | |
|-------------|----|
| Reading | B |
| Writing | C- |
| Mathematics | D |
| Science | C- |
| History | B+ |
| Art | B- |
| P.E. | B |



Applications

- Online Advertising and Recommendation
- Clinical Trials
- Robotics
- Dynamic Pricing
- Search Engine Optimization
- Education and Learning Platforms



Problem formalism


- Arms $\mathcal{A} = \{a_1, \dots, a_k\}$
 - Each arm is associated with an unknown reward distribution
- Rewards $r_t(a_i)$
- Possible Goals
 - Maximize cumulative reward (Minimize regret)
 - Best arm identification
- Assumptions
 - Independence: Rewards from each arm are independent
 - Stationarity: Reward distributions don't change over time

How should we solve this problem?

Random

Greedy



Exploration



ϵ -Greedy

Sutton/Barto figure

- 10 arms
- Each arm has stochastic reward
$$r \sim N(Q^*(a), 1)$$
- Averaged over 2000 bandit problems where each problem starts with $Q^*(a) \sim N(0,1)$ for all a



Problems?

Boltzmann (Softmax) Exploration

Chernoff-Hoeffding Inequality

- Let X_1, X_2, \dots, X_n be independent random variables in the range $[0, 1]$
- Let $\bar{X} = \frac{1}{n} \sum_i X_i$ (the empirical average)
- Then we have $P(\bar{X} \geq \mathbb{E}[X] + c) \leq e^{-2nc^2}$

Some fun math

- $P(\bar{X} \geq \mathbb{E}[X] + c) \leq e^{-2nc^2}$
- Typically, we want to pick some kind of high confidence $1 - \delta$ such that we are very confident about our sample mean being close to the true expectation.
- If we want

$$P(\bar{X} \geq \mathbb{E}[X] + c) \leq \delta$$

What is c ?

More math

- We can pick δ to be whatever we want, so let's pick
- If we select $\delta = \frac{1}{t^2}$

What is c ?

UCB1 (UCB = Upper Confidence Bound)


Key Idea: Optimism in the face of uncertainty

- Play each action once to get initial averages of arm values
- Keep track of counts for each arm n_i
- At each step t select $\arg \max \bar{X}_i + c(i, t)$
 - Where $c(i, t) = \sqrt{\frac{\log(t)}{n_i}}$

Regret


- Define μ^* as the maximum expected payoff over all k arms
- $\text{Regret}(T) = T\mu^* - \sum_{t=1}^T r_t$
- Epsilon-Greedy Regret
 - $O(T)$
- UCB1 Regret
 - $O(\sqrt{kT \log(T)})$
- A **No-Regret** algorithm is such that $\text{Regret}(T)/T \rightarrow 0$ as $T \rightarrow \infty$
 - Average regret goes to zero

Regret Bound vs. Turn



k (number of arms): T (number of steps):

Regret Bound vs. Turn



k (number of arms): T (number of steps):

Other Bandit Topics

- Thompson Sampling
- Best Arm Identification
- Adversarial Bandits
- Contextual Bandits
 - State information, s_t
 - Reward depends on state, and action
- Linear Bandits
 - Type of contextual bandit
 - Reward is a linear combination of state features.