

## Lecture 26 – Review, Conclusion



**DSC 40A, Fall 2022 @ UC San Diego**

Mahdi Soleymani, with help from **many others**

# Announcements

- ▶ Homework 8 is due **Tuesday Dec. 6.** (optional)
- ▶ A recording of Discussion 8 (probability review) is posted on the course website and on Campuswire.
- ▶ Fill out CAPEs survey.
  - ▶ Deadline: Saturday at 8am.
- ▶ The Final Exam is on **Saturday 12/4 from 7:00PM-10:00PM.**
  - ▶ Bring a cheat sheet.
  - ▶ Bring a calculator. No other electronic devices are allowed.
  - ▶ UCSD ID is required!

# Final preparation

- ▶ Review the solutions to previous homeworks and groupworks.
  - ▶ All except Homework 8 are up.
- ▶ Identify which concepts are still iffy. Re-watch lecture, post on Campuswire, come to office hours.
  - ▶ **We have many office hours between now and the exam.**
- ▶ Look at the past exams at <https://dsc40a.com/resources>.
  - ▶ Watch the probability review discussion.
- ▶ Study in groups.
- ▶ Make a “cheat sheet”.

# Agenda

- ▶ High-level summary of the course.
- ▶ Review problems.
- ▶ Conclusion.

**What was this course about?**

# Part 1: Supervised learning

The “learning from data” recipe to make predictions:

1. Choose a **prediction rule**. We've seen a few:
  - ▶ Constant:  $H(x) = h$ .
  - ▶ Simple linear:  $H(x) = w_0 + w_1 x$ .
  - ▶ Multiple linear:  $H(x) = w_0 + w_1 x^{(1)} + w_2 x^{(2)} + \dots + w_d x^{(d)}$ .
2. Choose a **loss function**.
  - ▶ Absolute loss:  $L(h, y) = |y - h|$ .
  - ▶ Squared loss:  $L(h, y) = (y - h)^2$ .
  - ▶ 0-1 loss, UCSD loss, etc.
3. Minimize **empirical risk** to find optimal parameters.
  - ▶ Algebraic arguments.
  - ▶ Calculus (including vector calculus).
  - ▶ Gradient descent.



## Part 1: Unsupervised learning

- ▶ When learning how to fit prediction rules, we were performing **supervised machine learning**.
- ▶ We discussed **k-Means Clustering**, an **unsupervised machine learning** method.
  - ▶ Supervised learning: there is a “right answer” that we are trying to predict.
  - ▶ Unsupervised learning: there is no right answer, instead we’re trying to find patterns in the structure of the data.



## Part 2: Probability fundamentals

- ▶ If all outcomes in the **sample space**  $S$  are equally likely, then  $P(A) = \frac{|A|}{|S|}$ .
- ▶  $\bar{A}$  is the **complement** of event  $A$ .  $P(\bar{A}) = 1 - P(A)$ .
- ▶ Two events  $A, B$  are **mutually exclusive** if they share no outcomes, i.e. they don't overlap. In this case, the probability that  $A$  happens or  $B$  happens is  $P(A \cup B) = P(A) + P(B)$ .
- ▶ More generally, for any two events,  $P(A \cup B) = P(A) + P(B) - P(A \cap B)$ .
- ▶ The probability that events  $A$  and  $B$  both happen is  $P(A \cap B) = P(A)P(B|A)$ .
  - ▶  $P(B|A)$  is the probability that  $B$  happens given that you know  $A$  happened.
  - ▶ Through re-arranging, we see that  $P(B|A) = \frac{P(A \cap B)}{P(A)}$ .

## Part 2: Combinatorics

- ▶ A **sequence** is obtained by selecting  $k$  elements from a group of  $n$  possible elements with replacement, such that order matters.
  - ▶ Number of sequences:  $n^k$ .
- ▶ A **permutation** is obtained by selecting  $k$  elements from a group of  $n$  possible elements without replacement, such that order matters.
  - ▶ Number of permutations:  $P(n, k) = \frac{n!}{(n-k)!}$ .
- ▶ A **combination** is obtained by selecting  $k$  elements from a group of  $n$  possible elements without replacement, such that order does not matter.
  - ▶ Number of combinations:  $\binom{n}{k} = \frac{n!}{(n-k)!k!}$ .

## Part 2: The law of total probability and Bayes' theorem

- ▶ A set of events  $E_1, E_2, \dots, E_k$  is a **partition** of  $S$  if each outcome in  $S$  is in exactly one  $E_i$ .
- ▶ The **law of total probability** states that if  $A$  is an event and  $E_1, E_2, \dots, E_k$  is a partition of  $S$ , then

$$\begin{aligned} P(A) &= P(E_1) \cdot P(A|E_1) + P(E_2) \cdot P(A|E_2) + \dots + P(E_k) \cdot P(A|E_k) \\ &= \sum_{i=1}^k P(E_i) \cdot P(A|E_i) \end{aligned}$$

- ▶ **Bayes' theorem** states that

$$P(B|A) = \frac{P(B) \cdot P(A|B)}{P(A)}$$

- ▶ We often re-write the denominator  $P(A)$  in Bayes' theorem using the law of total probability.

## Part 2: Independence and conditional independence

- ▶ Two events  $A$  and  $B$  are **independent** when knowledge of one event does not change the probability of the other event.
  - ▶ Equivalent conditions:  $P(B|A) = P(B)$ ,  $P(A|B) = P(A)$ ,  $P(A \cap B) = P(A) \cdot P(B)$ .
- ▶ Two events  $A$  and  $B$  are **conditionally independent** if they are independent given knowledge of a third event,  $C$ .
  - ▶ Condition:  $P((A \cap B)|C) = P(A|C) \cdot P(B|C)$ .
- ▶ In general, there is no relationship between independence and conditional independence.
- ▶ See pinned post on Campuswire for clarification.



## Part 2: Naïve Bayes

- ▶ In classification, our goal is to predict a discrete category, called a **class**, given some features.
- ▶ The **Naïve Bayes** classifier works by estimating the numerator of  $P(\text{class}|\text{features})$  for all possible classes.
- ▶ It uses Bayes' theorem:

$$P(\text{class}|\text{features}) = \frac{P(\text{class}) \cdot P(\text{features}|\text{class})}{P(\text{features})}$$

- ▶ It also uses a “naive” simplifying assumption, that **features are conditionally independent given a class**:

$$P(\text{features}|\text{class}) = P(\text{feature}_1|\text{class}) \cdot P(\text{feature}_2|\text{class}) \cdot \dots$$



**Skipped problems**







## Example: Venn diagrams

For three events  $A$ ,  $B$ , and  $C$ , we know that

- ▶  $A$  and  $C$  are independent,
- ▶  $B$  and  $C$  are independent,
- ▶  $A$  and  $B$  are mutually exclusive,
- ▶  $P(A \cup C) = \frac{2}{3}$ ,  $P(B \cup C) = \frac{3}{4}$ ,  $P(A \cup B \cup C) = \frac{11}{12}$ .

Find  $P(A)$ ,  $P(B)$ , and  $P(C)$ .

$$\textcircled{1} + \textcircled{2} : a + b + 2c - ac - bc = \frac{2}{3} + \frac{3}{4}$$

$$\textcircled{1} + \textcircled{2} - \textcircled{3} : c = \frac{2}{3} + \frac{3}{4} - \frac{11}{12} = \frac{8}{12} + \frac{9}{12} - \frac{11}{12} = \frac{1}{2}$$

$$c \text{ into } \textcircled{1} : a + \frac{1}{2} - \frac{1}{2}a = \frac{2}{3} \Rightarrow a = \frac{1}{3}$$

$$c \text{ into } \textcircled{2} : b + \frac{1}{2} - \frac{1}{2}b = \frac{3}{4} \Rightarrow b = \frac{1}{2}$$



## Review problems

## Example: Clustering and combinatorics

- ▶ Suppose we have a dataset of 15 points, each with two features ( $x_1, x_2$ ). In the dataset, there exist 3 “natural” clusters, each of which contain 5 data points.
- ▶ Recall that in the k-Means Clustering algorithm, we initialize  $k$  centroids by choosing  $k$  points at random from our dataset. Suppose  $k = 3$ .

1. What's the probability that all three initial centroids are initialized in the same natural cluster?
2. What's the probability that all three initial centroids are initialized in different natural clusters?



## **Example: basketball**

Suppose we have 6 basketball players who want to organize themselves into 3 basketball teams of 2 players each. Suppose we have three teams, “Team USA”, “Team China”, and “Team Lithuania”. How many ways can these teams be formed?

## **Example: basketball, again**

Suppose we have 6 basketball players who want to organize themselves into 3 basketball teams of 2 players each. Now, suppose the teams are irrelevant, and all we care about is the unique pairings themselves. How many ways can these 6 players be split into 3 teams?

## **Example: high school**

A certain high school has 80 students: 20 freshmen, 20 sophomores, 20 juniors, and 20 seniors. If a random sample of 20 students is drawn without replacement, what is the probability that the sample contains 5 students in each grade level?

## **Example: high school, again**

A certain high school has 80 students: 20 freshmen, 20 sophomores, 20 juniors, and 20 seniors. If a random sample of 20 students is drawn with replacement, what is the probability that all students in the sample are from the same grade level?

## Example: bitstrings

What is the probability of a randomly generated bitstring of length 5 having the same first two bits? Assume that each bit is equally likely to be a 0 or a 1.

## **Example: bitstrings, again**

What is the probability of a randomly generated bitstring of length 5 having the same first two bits, if we know that the bitstring has exactly four 0s? Assume that each bit is equally likely to be a 0 or a 1.

## Conclusion

# Learning objectives

At the start of the quarter, we told you that by the end of DSC 40A, you'll...

- ▶ understand the basic principles underlying almost every machine learning and data science method.
- ▶ be better prepared for the math in upper division: vector calculus, linear algebra, and probability.
- ▶ be able to tackle problems such as:
  - ▶ How do we know if an avocado is going to be ripe before we eat it?
  - ▶ How do we teach a computer to read handwritten text?
  - ▶ How do we predict a future data scientist's salary?



## What's next?

In DSC 40A, we just scratched the surface of the theory behind data science. In future courses, you'll build upon your knowledge from DSC 40A, and will learn:

- ▶ More supervised learning.
  - ▶ Logistic regression, decision trees, neural networks, etc.
- ▶ More unsupervised learning.
  - ▶ Other clustering techniques, PCA, etc.
- ▶ More probability.
  - ▶ Random variables, distributions, etc.
- ▶ More connections between all of these areas.
  - ▶ For instance, you'll learn how probability is related to linear regression.
- ▶ More practical tools.

# Note on grades

## Fall 2016

| Class       | Title   | Un. | Gr. |
|-------------|---|-----|-----|
| CHEM 1A     | General Chemistry                                     | 3   | B-  |
| CHEM 1AL    | General Chemistry Laboratory                          | 1   | C+  |
| COMPSCI 61A | The Structure and Interpretation of Computer Programs | 4   | B+  |
| COMPSCI 70  | Discrete Mathematics and Probability Theory           | 4   | A   |
| COMPSCI 195 | Social Implications of Computer Technology            | 1   | P   |
| MATH 1A     | Calculus  | 4   | A+  |

## Spring 2017

| Class       | Title                                       | Un. | Gr. |
|-------------|---|-----|-----|
| COMPSCI 61B | Data Structures                             | 4   | B+  |
| COMPSCI 97  | Field Study                                 | 1   | P   |
| COMPSCI 197 | Field Study                                 | 1   | P   |
| ELENG 16A   | Designing Information Devices and Systems I | 4   | B-  |
| MATH 110    | Linear Algebra                              | 4   | C   |
| MATH 128A   | Numerical Analysis                          | 4   | B+  |

Moral of the story: good grades aren't everything.

# Thank you!

- ▶ This course would not have been possible without our TA: Pushkar Bhuse.
- ▶ It also would not have been possible without our 8 tutors: Yuxin Guo, Weiyue(Larry) Li, Vivian Lin, Karthikeya Manchala, Shiv Sakthivel, Aryaman Sinha, Jessica Song and Yujia(Joy) Wang.
- ▶ You can contact them with any questions at [dsc40a.com/staff](https://dsc40a.com/staff).

## **Theoretical Foundations of Data Science (Part 1)**