
# DSC 40B

## Theoretical Foundations II

Lecture 11 | Part 1

## Graph Representations

# Last Time: Adjacency Matrices




| | *a* | *b* | *c* | *d* |
|---|---|---|---|---|
| *a* | 0 | 1 | 0 | 0 |
| *b* | 0 | 0 | 1 | 0 |
| *c* | 0 | 1 | 0 | 1 |
| *d* | 0 | 0 | 0 | 1 |

`arr[i,j] = 1` if $(i, j) \in E$, else `0`.

# Observations

- If $G$ is undirected, matrix is symmetric.
- If $G$ is directed, matrix may not be symmetric.

# Time Complexity

| operation[1] | code | time |
|---|---|---|
| edge query | `adj[i,j] == 1` | $\Theta(1)$ |
| degree($i$) | `np.sum(adj[i,:])` | $\Theta(\|V\|)$ |

[1] For undirected graphs

# Space Requirements

- Uses $|V|^2$ bits, even if there are very few edges.
- But most real-world graphs are **sparse**.
  - They contain many fewer edges than possible.

# Example: Facebook

- Facebook has 2 billion users.

$$
\begin{aligned}
(2 \times 10^9)^2 &= 4 \times 10^{18} \text{ bits} \\
&= 500 \text{ petabytes} \\
&\approx 6500 \text{ years of video at 1080p} \\
&\approx 5 \text{ copies of the internet as it was in 2004}
\end{aligned}
$$

# Adjacency Matrices and Math

- Adjacency matrices are useful mathematically.
- Example: $(i, j)$ entry of $A^2$ gives the number of paths of length 2 between $i$ and $j$.

# DSC 40B

## Theoretical Foundations II

Lecture 11 | Part 2

## Adjacency Lists


# What's Wrong with Adjacency Matrices?

- Requires $\Theta(|V|^2)$ storage.
- Even if the graph has no edges.
- **Idea**: only store the edges that exist.


# Adjacency Lists

- Create a list `adj` containing $|V|$ lists.
- The $i$th list (that is, `adj[i]`) contains the neighbors of node $i$.

# Example



# Example



# Observations

- If $G$ is undirected, each edge appears twice.
- If $G$ is directed, each edge appears once.


# Time Complexity

| operation[2] | code | time |
|---|---|---|
| edge query | `j in adj[i]` | $\Theta(\text{degree}(i))$ |
| degree($i$) | `len(adj[i])` | $\Theta(1)$ |

[2] For undirected graphs

## Exercise

What does the following code do?





```
adj = [
    [1],
    [0, 2],
    [1, 3],
    [2]
]
```

```
for u in range(len(adj)):
    for v in adj[u]:
        print(f"({u}, {v})")
```

## Exercise

How many times is the `print` statement executed in terms of $|V|$ and $|E|$?

A) $|E|$ B) $2|E|$ C) $|V| + |E|$ D) $|V| \cdot |E|$





```
adj = [
    [1],
    [0, 2],
    [1, 3],
    [2]
]
```

```
for u in range(len(adj)):
    for v in adj[u]:
        print(f"({u}, {v})")
```

## Exercise

What is the time complexity in terms of $|V|$ and $|E|$?

A) $\Theta(|E|)$ B) $\Theta(|V| + |E|)$ C) $\Theta(|V| \cdot |E|)$ D) $\Theta(|V|^2)$




```
adj = [
    [1],
    [0, 2],
    [1, 3],
    [2]
]
```

```
for u in range(len(adj)):
    for v in adj[u]:
        print(f"({u}, {v})")
```

## Exercise

What is the time complexity of the following code?

A) $\Theta(1)$ B) $\Theta(|V|)$ C) $\Theta(|E|)$ D) $\Theta(|V|^2)$

```
adj = [
    [],
    [],
    [],
    []
]
```

```
for u in range(len(adj)):
    for v in adj[u]:
        print(f"({u}, {v})")
```

# Looping Over Edges

- Looping over all edges in this way takes $\Theta(V + E)$ time.
- In aggregate, the `print` statement is executed:
  - $2|E|$ times if graph is undirected.
  - $|E|$ times if graph is directed.
- This is called an **aggregate analysis**.

# Space Requirements

- Need $\Theta(|V|)$ space for outer list.
- Plus $\Theta(|E|)$ space for inner lists.
- In total: $\Theta(|V| + |E|)$ space.

# Example: Facebook

- Facebook has 2 billion users, 400 billion friendships.

- If each edge requires 32 bits:

$$
\begin{aligned}
&2 \times 32 \text{ bits} \times (400 \times 10^9 \text{ friendships}) \\
&= 64 \times 400 \times 10^9 \text{ bits} \\
&= 3.2 \text{ terabytes} \\
&= 0.04 \text{ years of HD video}
\end{aligned}
$$

# DSC 40B

## Theoretical Foundations II

Lecture 11 | Part 3

## Dictionary of Sets


# Tradeoffs

- Adjacency matrix: fast edge query, lots of space.
- Adjacency list: slower edge query, space efficient.
- Can we have the best of both?

# Idea

- Use **hash tables**.
- Replace inner edge lists by `set`s.
- Replace outer list with `dict`.
  - Doesn't speed things up, but allows nodes to have arbitrary labels.

# Example



# Time Complexity

| operation[3] | code | time |
|---|---|---|
| edge query | `j in adj[i]` | $\Theta(1)$ average |
| degree($i$) | `len(adj[i])` | $\Theta(1)$ |

[3] For undirected graphs

# Space Requirements

- Requires only $\Theta(|V| + |E|)$.
- But there is overhead to using hash tables.

# Dict-of-sets implementation

- Install with `pip install dsc40graph`
- Import with `import dsc40graph`
- Docs: `https://eldridgejm.github.io/dsc40graph/`
- Source code: `https://github.com/eldridgejm/dsc40graph`
- Will be used in HW coding problems.

# DSC 40B

## Theoretical Foundations II

Lecture 11 | Part 4

## Graph Search Strategies

# How do we:

- determine if there is a path between two nodes?
- check if graph is connected?
- count connected components?

# Search Strategies

- A **search strategy** is a procedure for exploring a graph.
- Different strategies are useful in different situations.

# Node Statuses

At any point during a search, a node is in exactly one of three states:

- **visited**
- **pending** (discovered, but not yet visited)
- **undiscovered**

# Rules

- At every step, next visited node chosen from among **pending** nodes.
- When a node is marked as **visited**, all of its neighbors have been discovered (they are **pending** or **visited**).

# Choosing the next Node

How to choose among pending nodes?

- Idea 1: Visit **newest** pending (**depth-first search**).
- Idea 2: Visit **oldest** pending (**breadth-first search**).

## Main Idea

Depth-first search (DFS) and breadth-first search (BFS) each discover different properties of the graph.

For example, we'll see that BFS is useful for finding shortest paths (DFS in general is not).

# DSC 40B

## Theoretical Foundations II

Lecture 11 | Part 5

## Breadth-First Search

# Breadth-First Search

- At every step:
  1. Visit **oldest** pending node.
  2. Mark its undiscovered neighbors as pending.

- Convention: in this class, neighbors produced in sorted order.[4]

[4] In general, the order in which a node's neighbors are produced is arbitrary.

# Example

Step through this example in the interactive demo:

`dsc40b.com/demos/bfs`

# Implementation

- To store pending nodes, use a FIFO **queue**.
  - FIFO = “First in, first out”.
- While queue is not empty:
  - Pop a node, u.
  - Add **undiscovered** neighbors to queue.

# Queues in Python

- Want $\Theta(1)$ time pops/appends on either side.
- `from collections import deque` ("deck").
  - `.popleft()` and `.pop()`
  - `list` doesn't have right time complexity!
  - `import queue` isn't what you want!
- Keep track of node status attribute using dictionary.

# Exercise

```
from collections import deque

def bfs(graph, source):
    """Start a BFS at `source`."""
    status = {node: 'undiscovered' for node in graph.nodes}

    status[source] = 'pending'
    pending = deque([source])

    # while there are still pending nodes
    while pending:
        # EXERCISE: fill this in...
```

# BFS

```
from collections import deque

def bfs(graph, source):
    """Start a BFS at `source`."""
    status = {node: 'undiscovered' for node in graph.nodes}

    status[source] = 'pending'
    pending = deque([source])

    # while there are still pending nodes
    while pending:
        u = pending.popleft()
        for v in graph.neighbors(u):
            # explore edge (u,v)
            if status[v] == 'undiscovered':
                status[v] = 'pending'
                # append to right
                pending.append(v)
        status[u] = 'visited'
```

# Note

- What does this code actually *return*?

# Note

- What does this code actually *return*?
- Nothing, yet. It is a *foundation*.

# Note

- BFS works just as well for directed graphs.

# DSC 40B

## Theoretical Foundations II


Lecture 11 | Part 6

## Analysis of BFS

## Exercise

What will `bfs` do when run on a graph with multiple connected components?

A) visit every node
B) raise an error
C) visit only the nodes reachable from the source
D) loop forever



# Claim

- `bfs` with source *u* will visit all nodes reachable from *u* (and only those nodes).

- Useful!
  - Is there a path between *u* and *v*?
  - Is graph connected?

# Exploring with BFS

- BFS will visit all nodes reachable from source.
- If **disconnected**, BFS will not visit all nodes.
- We can do so with a **full BFS**.
  - Idea: “re-start” BFS on undiscovered node.
  - Must pass statuses between calls.

# Making Full BFS

Modify `bfs` to accept statuses:


```
def bfs(graph, source, status=None):
    """Start a BFS at `source`."""
    if status is None:
        status = {node: 'undiscovered' for node in graph.nodes}
    # ...
```


# Making Full BFS


Call `bfs` multiple times:

```
def full_bfs(graph):
    status = {node: 'undiscovered' for node in graph.nodes}
    for node in graph.nodes:
        if status[node] == 'undiscovered':
            bfs(graph, node, status)
```

# Example







# Observation

- If there are *k* connected components, `bfs` in line 5 is called exactly *k* times.

```
1  def full_bfs(graph):
2      status = {node: 'undiscovered' for node in graph.nodes}
3      for node in graph.nodes:
4          if status[node] == 'undiscovered':
5              bfs(graph, node, status)
```

# Time Complexity of `full_bfs`

- Analyzing `full_bfs` is easier than analyzing `bfs`.
  - `full_bfs` visits all nodes, no matter the graph.

- Result will be **upper bound** on time complexity of `bfs`.

# Time Complexity of `full_bfs`


- To determine the time complexity of `full_bfs`, we will use an **aggregate analysis**.

- We'll need to know:
  1. How many times is each node added to the queue?
  2. How many times is each edge "explored"?

## Exercise

Consider an arbitrary node $u$. How many times is $u$ added to the queue in a full BFS of the graph below?


A) once B) twice C) degree($u$)



## Exercise

Consider an arbitrary edge $(u, v)$. How many times is $(u, v)$ "explored" in a full BFS of the graph below?


A) once B) twice C) can't say



## Exercise

Consider an arbitrary edge $(u, v)$. How many times is edge $(u, v)$ "explored" in a BFS of the *directed* graph below?

A) once B) twice C) can't say



# Key Properties of `full_bfs`


- Each node added to queue **exactly once**.
- Each edge is explored **exactly**:
  - **once** if graph is **directed**.
  - **twice** if graph is **undirected**.


# BFS

```
def bfs(graph, source, status=None):
    """Start a BFS at `source`."""
    if status is None:
        status = {node: 'undiscovered' for node in graph.nodes}

    status[source] = 'pending'
    pending = deque([source])

    # while there are still pending nodes
    while pending:
        u = pending.popleft()
        for v in graph.neighbors(u):
            # explore edge (u,v)
            if status[v] == 'undiscovered':
                status[v] = 'pending'
                # append to right
                pending.append(v)
        status[u] = 'visited'
```



# Time Complexity

```
def full_bfs(graph):
    status = {node: 'undiscovered' for node in graph.nodes}
    for node in graph.nodes:
        if status[node] == 'undiscovered':
            bfs(graph, node, status)


def bfs(graph, source, status=None):
    """Start a BFS at `source`."""
    if status is None:
        status = {node: 'undiscovered' for node in graph.nodes}

    status[source] = 'pending'
    pending = deque([source])

    # while there are still pending nodes
    while pending:
        u = pending.popleft()
        for v in graph.neighbors(u):
            # explore edge (u,v)
            if status[v] == 'undiscovered':
                status[v] = 'pending'
                # append to right
                pending.append(v)
        status[u] = 'visited'
```

# Time Complexity of Full BFS

- $\Theta(V + E)$
- If $|V| > |E|$: $\Theta(V)$
- If $|V| < |E|$: $\Theta(E)$
- Namely, if graph is **complete**: $\Theta(V^2)$.
- Namely, if graph is **very sparse**: $\Theta(V)$.

# Notational Note

- We'll often write $\Theta(V + E)$ instead of $\Theta(|V| + |E|)$.
- You can use whichever.

# Next Time

- Finding **shortest paths** using BFS.